FCC PART 15.407
LP0002-2018
TEST REPORT

For

台灣思科系統股份有限公司

臺北市信義區信義路 4 段 460 號 12 樓

FCC ID: LDKHDGWI1903

Report Type:	**Product type:**
Original Report	Cisco Catalyst C9117AX Series

Prepared By:	Sehni Hu Test Engineer
Report Number:	R1811136-UNII1B Rev C
Report Date:	2019-05-12
Reviewed By:	Simon Ma RF Supervisor

Bay Area Compliance Laboratories Corp. (Taiwan)
70, Lane 169, Sec. 2, Datong Road, Xizhi Dist.,
New Taipei City 22183, Taiwan, R.O.C.
Tel: +886 (2) 2467-6898
Fax: +886 (2) 2647-6895

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA*, NIST, or any agency of the Federal Government.
* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*"

TABLE OF CONTENTS

1 GENERAL DESCRIPTION 5

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 5
1.2 OBJECTIVE 5
1.3 RELATED SUBMITTAL(S)/GRANT(S) 5
1.4 TEST METHODOLOGY 5
1.5 MEASUREMENT UNCERTAINTY 6
1.6 TEST FACILITY REGISTRATIONS 6

2 EUT TEST CONFIGURATION 7

2.1 JUSTIFICATION 7
2.2 EUT EXERCISE SOFTWARE 7
2.3 DUTY CYCLE CORRECTION FACTOR 7
2.4 EQUIPMENT MODIFICATIONS 8
2.5 LOCAL SUPPORT EQUIPMENT 8
2.6 SUPPORT EQUIPMENT 8
2.7 INTERFACE PORTS AND CABLING 8

3 SUMMARY OF TEST RESULTS 9

ONLY THE WORST CASE MEASUREMENT PLOTS ARE PROVIDED IN THE TEST REPORT. 9

4 FCC §2.1091, §15.407(F), LP0002-2018 §5.20.2 - RF EXPOSURE 10

4.1 APPLICABLE STANDARDS 10
4.2 MPE PREDICTION 10
4.3 MPE RESULTS 11

5 FCC §15.203, LP0002-2018 §2.2 - ANTENNA REQUIREMENTS 12

5.1 APPLICABLE STANDARDS 12
5.2 ANTENNA LIST 12

6 FCC §15.407(E), LP0002-2018 §4.7 - 6 DB, 26 DB, AND 99% OCCUPIED BANDWIDTH 13

6.1 APPLICABLE STANDARDS 13
6.2 MEASUREMENT PROCEDURE 13
6.3 TEST EQUIPMENT LIST AND DETAILS 13
6.4 TEST ENVIRONMENTAL CONDITIONS 13
6.5 TEST RESULTS 13

7 FCC §407(A), LP0002-2018 §4.7 - OUTPUT POWER 14

7.1 APPLICABLE STANDARDS 14
7.2 MEASUREMENT PROCEDURE 15
7.3 TEST EQUIPMENT LIST AND DETAILS 15
7.4 TEST ENVIRONMENTAL CONDITIONS 16
7.5 TEST RESULTS 16

8 FCC §15.407(A), LP0002-2018 §4.7 - POWER SPECTRAL DENSITY 17

8.1 APPLICABLE STANDARDS 17
8.2 MEASUREMENT PROCEDURE 18
8.3 TEST EQUIPMENT LIST AND DETAILS 18
8.4 TEST ENVIRONMENTAL CONDITIONS 18
8.5 TEST RESULTS 19

9 FCC §15.407(B), LP0002-2018 §4.7 - OUT OF BAND EMISSIONS 20

9.1 APPLICABLE STANDARDS 20
9.2 MEASUREMENT PROCEDURE 20

9.3 TEST EQUIPMENT LIST AND DETAILS 21
9.4 TEST ENVIRONMENTAL CONDITIONS 21
9.5 TEST RESULTS 21
10 APPENDIX (NORMATIVE) - EUT PHOTOGRAPHS 22
11 APPENDIX D (INFORMATIVE) – DECLARATION OF SIMILARITY 23
12 ANNEX – TEST RESULTS AND MEASUREMENT PLOTS 25

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R1811136-UNII1B	Original Report	2019-02-14
1	R1811136-UNII1B Rev A	Added LP0002-2018 standard for Taiwan NCC approval Provided antenna information details	2019-04-03
2	R1811136-UNII1B Rev B	Added multiple Cisco PIDs based on customer's request, and Declaration of Similarity Letter in Appendix D	2019-04-10
3	R1811136-UNII1B Rev C	Revised DoS in Appendix D, and added more Cisco PIDs based on customer's request	2019-05-12

1 General Description

1.1 Product Description for Equipment under Test (EUT)

This test and measurement report was prepared on behalf of *Cisco Systems, Inc.* and their product brand name: Cisco, model: *C9117AXI-B (US) and C9117AXI-T (Taiwan),* FCC ID: LDKHDGWI1903, or the "EUT" as referred to in this report. The product is an 802.11ax Access Point.

Product model: C9117AXI-Z (Australia/New Zealand), C9117AXI-S (Singapore/Hong Kong), and C9117AXI-D (India) are similar to the model tested. Please refer to the Declaration of Similarity Letter in Appendix D for details.

1.2 Objective

This report is prepared on behalf of Cisco Systems, Inc. in accordance with FCC CFR47 §15.407 and LP0002-2018.

The objective is to determine compliance with FCC Part 15.407 and LP0002-2018 rules for Output Power, Antenna Requirements, AC Line Conducted Emissions, Emission Bandwidth, Power spectral density, Conducted and Radiated Spurious Emissions.

1.3 Related Submittal(s)/Grant(s)

DTS EDCS-15634526, EDCS-15797453, and R1811136-247

1.4 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz, and FCC KDB 789033 D02 General UNII Test Procedure New Rules v02r01.

1.5 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatabil

Parameter	Measurement uncertainty
Occupied Channel Bandwidth	34kHz
RF output power, conducted	4.84 dB
Power Spectral Density, conducted	1.69 dB
Unwanted Emissions, conducted	4.84dB
All emissions, radiated	5.18 dB
AC power line Conducted Emission	4.22 dB
Temperature	±2 º C
Humidity	±5 %
DC and low frequency voltages	±1.0 %
Time	±2 %
Duty Cycle	±3 %

1.6 Test Facility Registrations

The Test site used by Bay Area Compliance Laboratories Corp. (Taiwan) to collect test data is located on
☒70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.
☐68-3, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

Bay Area Compliance Laboratories Corp. (Taiwan) Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3180) and the FCC designation No.TW3180 under the Mutual Recognition Agreement (MRA) in FCC Test. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 974454. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

2 EUT Test Configuration

2.1 Justification

The EUT was configured for testing according to ANSI C63.10-2013 and FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

The EUT was tested in a testing mode to represent worst-case results during the final qualification test.

The worst-case data rates are determined by measuring the average power, peak power and PPSD across all data rates bandwidths, and modulations.

2.2 EUT Exercise Software

The test software used was Tera Term. The software is compliant with the standard requirements being tested against.

2.3 Duty Cycle Correction Factor

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01 section B:

All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum-power transmission duration, T, are required for each tested mode of operation.

Radio Mode	On Time (ms)	Period (ms)	Duty Cycle (%)	DCCF* (dB)	DCCF* (dB)
Non HT20	2.099	2.207	95.11	0.22	0.44
HT/VHT/HE20	5.438	5.720	95.07	0.22	0.44
HT/VHT/HE40	5.426	5.651	96.02	0.18	0.36
VHT/HE80	5.438	5.709	95.25	0.21	0.42

Note*: DCCF = Duty Cycle Correction Factor = 10*log(1/duty cycle), when power averaging was applied in average measurement; DCCF = 20*log(1/duty cycle), when voltage averaging was applied in average measurement.

2.4 Equipment Modifications

There are two RF cables, one for each antenna port, coming out of the EUT to connect the antenna ports to the measurement instrument.

2.5 Local Support Equipment

Manufacturer	Description	Model
Dell	NB	E6410

2.6 Support Equipment

None

2.7 Interface Ports and Cabling

Cable Description	Length (m)	To	From
Cat5e	~1	EUT	POE Injector
Cat5e	~1	POE Injector	NB

3 Summary of Test Results

FCC Rules	Description of Test	Result
FCC §2.1091, §15.407(f) LP0002-2018 §5.20.2	RF Exposure	Compliant
FCC §15.203 LP0002-2018 §2.2	Antenna Requirement	Compliant
FCC §15.207 LP0002-2018 §2.3	AC Power Line Conducted Emissions	Note[1]
FCC §2.1053, §15.205, §15.209, 15.407(b) LP0002-2018 §2.7, §2.8, §4.7	Spurious Radiated Emissions	Note[1]
FCC §15.407(e) LP0002-2018 §4.7	Emission Bandwidth	Compliant
FCC §407(a) LP0002-2018 §4.7	Output Power	Compliant
FCC §2.1051, §15.407(b) LP0002-2018 §4.7	Band Edges	Compliant
FCC §15.407(a) LP0002-2018 §4.7	Power Spectral Density	Compliant
FCC §2.1051, §15.407(b) LP0002-2018 §4.7	Spurious Emissions at Antenna Terminals	Compliant
FCC §15.407(h) LP0002-2018 §4.7	Dynamic Frequency Selection (DFS)	N/A

Note[1]: compliance test data was recorded in a seprate report, please refer to Test Report: R1811136-407

Only the worst case measurement plots are provided in the test report.

4 FCC §2.1091, §15.407(f), LP0002-2018 §5.20.2 - RF Exposure

4.1 Applicable Standards

According to FCC §15.247(i), §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* ($180/f^2$)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz
* = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of ISED RSS-102 must be followed concerning the exposure of humans to RF field

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density
P = power input to antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

4.3 MPE Results

BLE:

Maximum average output power at antenna input terminal (dBm):	4.21
Maximum average output power at antenna input terminal (mW):	2.64
Prediction distance (cm):	30
Prediction frequency (MHz):	2402
Maximum Antenna Gain, typical (dBi):	2
Maximum Antenna Gain (numeric):	1.58
Power density of prediction frequency at 30.0 cm (mW/cm^2):	0.0004
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

2.4 GHz Wi-Fi:

Maximum average output power at antenna input terminal (dBm):	24.3
Maximum average output power at antenna input terminal (mW):	269.15
Prediction distance (cm):	30
Prediction frequency (MHz):	2437
Maximum Antenna Gain, typical (dBi):	10
Maximum Antenna Gain (numeric):	10
Power density of prediction frequency at 30.0 cm (mW/cm^2):	0.238
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

5.2 GHz band:

Maximum average output power at antenna input terminal (dBm):	24.23
Maximum average output power at antenna input terminal (mW):	264.85
Prediction distance (cm):	30
Prediction frequency (MHz):	5200
Maximum Antenna Gain, typical (dBi):	10.26
Maximum Antenna Gain (numeric):	10.62
Power density of prediction frequency at 30.0 cm (mW/cm^2):	0.249
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

5.3 GHz band:

Maximum average output power at antenna input terminal (dBm):	13.68
Maximum average output power at antenna input terminal (mW):	23.335
Prediction distance (cm):	30
Prediction frequency (MHz):	5270
Maximum Antenna Gain, typical (dBi):	13.78
Maximum Antenna Gain (numeric):	23.878
Power density of prediction frequency at 30.0 cm (mW/cm^2):	0.049
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

5.6 GHz band:

Maximum average output power at antenna input terminal (dBm):	20.75
Maximum average output power at antenna input terminal (mW):	118.85
Prediction distance (cm):	30
Prediction frequency (MHz):	5700
Maximum Antenna Gain, typical (dBi):	6.88
Maximum Antenna Gain (numeric):	4.88
Power density of prediction frequency at 30.0 cm (mW/cm^2):	0.051
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

5.8 GHz band:

Maximum average output power at antenna input terminal (dBm):	23.87
Maximum average output power at antenna input terminal (mW):	243.78
Prediction distance (cm):	30
Prediction frequency (MHz):	5755
Maximum Antenna Gain, typical (dBi):	12.02
Maximum Antenna Gain (numeric):	15.92
Power density of prediction frequency at 30.0 cm (mW/cm^2):	0.343
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0

Radio Co-location

BLE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi:

$0.0004/1 + 0.238/1 + 0.343/1 = 0.581 < 1$

Conclusion

The device is compliant with the requirement MPE limit for uncontrolled exposure. All transceiver modules must be installed with a separation distance of no less than **30** cm from all persons.

5 FCC §15.203, LP0002-2018 §2.2 - Antenna Requirements

5.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2 Antenna List

Below detailed antenna information are provided by the applicant.

Frequency	HOST PID | Part Number - Please align Host(s) with antenna(s)	ANTENNA PID | Part Number	Antenna Type	Antenna Gain (includes antenna cable loss)
2.4 GHz & 5 GHz	TX/RX: Internal	(ANT A: Wi-Fi 2.4 GHz & 5 GHz)	Single port, dual band omni	2.4 GHz: 3.5 dBi 5 GHz: 4.5 dBi
2.4 GHz & 5 GHz	TX/RX: Internal	(ANT B: Wi-Fi 2.4 GHz & 5 GHz)	Single port, dual band omni	2.4 GHz: 3.5 dBi 5 GHz: 6 dBi
2.4 GHz & 5 GHz	TX/RX: Internal	(ANT C: Wi-Fi 2.4 GHz & 5 GHz)	Single port, dual band omni	2.4 GHz: 4 dBi 5 GHz: 6 dBi
2.4 GHz & 5 GHz	TX/RX: Internal	(ANT D: Wi-Fi 2.4 GHz/BLE 2.4 GHz & 5 GHz)	Single port, dual band omni	2.4 GHz: 3.5 dBi 5 GHz: 5 dBi
2.4 GHz & 5 GHz	TX/RX: Internal	(ANT D: Wi-Fi 2.4 GHz/BLE 2.4 GHz & 5 GHz)	Single port, dual band omni	2.4 GHz: 3.5 dBi 5 GHz: 5 dBi
5 GHz	TX/RX: Internal	(ANT E: Wi-Fi 5 GHz)	Single port, single band omni	5 GHz: 6 dBi
5 GHz	TX/RX: Internal	(ANT E: Wi-Fi 5 GHz)	Single port, single band omni	5 GHz: 6 dBi
5 GHz	TX/RX: Internal	(ANT E: Wi-Fi 5 GHz)	Single port, single band omni	5 GHz: 6 dBi
5 GHz	TX/RX: Internal	(ANT E: Wi-Fi 5 GHz)	Single port, single band omni	5 GHz: 5.5 dBi

6 FCC §15.407(e), LP0002-2018 §4.7 - 6 dB, 26 dB, and 99% Occupied Bandwidth

6.1 Applicable Standards

As per FCC §15.407(e): for equipment operating in the band 5725 – 5850 MHz, the minimum 6 dB bandwidth of U-NII devices shall be 500 kHz.

6.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 or 26 dB from the reference level. Record the frequency difference as the minimum emission or emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

6.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due
Rohde & Schwarz	Spectrum Analyzer	FSV40	101140	2018/11/14	2019/11/13
MINI-CIRCUITS	Attenuator	BW-S6W5+	N/A	2018/03/08	2019/03/07
WOKEN	Cable	SFL402	S02-160323-07	2018/02/12	2019/02/11
WOKEN	Cable	SFL402	S02-160323-07	2019/02/11	2020/02/10

Statement of Traceability: BACL Corp. *attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 09 June 2016) "A2LA Policy on Metrological Traceability".*

6.4 Test Environmental Conditions

Temperature:	25 ºC
Relative Humidity:	58 %
ATM Pressure:	1010 hPa

The testing was performed by Boris Kao on 2018-11-28~2019-02-14.

6.5 Test Results

Please refer to Annex for test results and plots

7 FCC §407(a), LP0002-2018 §4.7 - Output Power

7.1 Applicable Standards

According to FCC §15.407(a):

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Note to paragraph (a)(3): The Commission strongly recommends that parties employing U-NII devices to provide critical communications services should determine if there are any nearby Government radar systems that could affect their operation.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

(5) The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

7.2 Measurement Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a spectrum analyzer.

7.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due
KEYSIGHT	Power Sensor	U2021XA	MY54080018	2018/03/07	2019/03/06
MINI-CIRCUITS	Attenuator	BW-S6W5+	N/A	2018/03/08	2019/03/07
WOKEN	Cable	SFL402	S02-160323-07	2018/02/12	2019/02/11

Statement of Traceability: BACL Corp. *attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 09 June 2016) "A2LA Policy on Metrological Traceability".*

7.4 Test Environmental Conditions

Temperature:	25 ºC
Relative Humidity:	58 %
ATM Pressure:	1010 hPa

The testing was performed by Boris Kao on 2018-11-28~2019-02-14.

7.5 Test Results

Please refer to Annex for test results and plots

8 FCC §15.407(a), LP0002-2018 §4.7 - Power Spectral Density

8.1 Applicable Standards

According to FCC §15.407(a):

For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may

employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

8.2 Measurement Procedure

(i) Set span to encompass the entire emission bandwidth (EBW) of the signal.
(ii) Set RBW = 1 MHz.
(iii) Set VBW ≥ 3 MHz.
(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)
(v) Sweep time = auto.
(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".
(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
(ix) Use the peak search function on the instrument to find the peak of the spectrum and record its value.

8.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due
Rohde & Schwarz	Spectrum Analyzer	FSV40	101140	2018/11/14	2019/11/13
MINI-CIRCUITS	Attenuator	BW-S6W5+	N/A	2018/03/08	2019/03/07
WOKEN	Cable	SFL402	S02-160323-07	2018/02/12	2019/02/11

Statement of Traceability: BACL Corp. *attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 09 June 2016) "A2LA Policy on Metrological Traceability".*

8.4 Test Environmental Conditions

Temperature:	25 ºC
Relative Humidity:	58 %
ATM Pressure:	1010 hPa

The testing was performed by Boris Kao on 2018-11-28~2019-02-14.

8.5 Test Results

Please refer to Annex for test results and plots

9 FCC §15.407(b), LP0002-2018 §4.7 - Out of Band Emissions

9.1 Applicable Standards

According to FCC §15.407(b):

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

The provisions of §15.205 apply to intentional radiators operating under this section.

9.2 Measurement Procedure

Add a correction factor (antenna gain+ Attenuator loss+cable loss) to the offset of the spectrum analyzer.
Integration Method

1. For peak emissions measurements, follow the procedures described in section H)5), “Procedures for Peak Unwanted Emissions Measurements above 1000 MHz”, except for the following changes:

- Set RBW = 100 kHz
- Set VBW = 3RBW
- Perform a band-power integration across the 1 MHz bandwidth in which the band-edge emission level is to be measured. CAUTION: You must ensure that the spectrum analyzer or EMI receiver is set for peak-detection and max-hold for this measurement.

2. For average emissions measurements, follow the procedures described in section H)6), “Procedures for Average Unwanted Emissions Measurements above 1000 MHz”, except for the following changes:

- Set RBW = 100 kHz
- Set VBW = 3RBW
- Perform a band-power integration across the 1 MHz bandwidth in which the band-edge emission level is to be measured.

9.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due
Rohde & Schwarz	Spectrum Analyzer	FSV40	101140	2018/11/14	2019/11/13
MINI-CIRCUITS	Attenuator	BW-S6W5+	N/A	2018/03/08	2019/03/07
WOKEN	Cable	SFL402	S02-160323-07	2018/02/12	2019/02/11

Statement of Traceability: BACL Corp. *attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 09 June 2016) "A2LA Policy on Metrological Traceability".*

9.4 Test Environmental Conditions

Temperature:	25 ºC
Relative Humidity:	58 %
ATM Pressure:	1010 hPa

The testing was performed by Boris Kao on 2018-11-28~2019-02-14.

9.5 Test Results

Please refer to Annex for test results and plots

10 Appendix (Normative) - EUT Photographs

Please see attachments:

Appendix A – EUT Test Setup Photographs
Appendix B – EUT External Photographs
Appendix C – EUT Internal Photographs

11 Appendix D (Informative) – Declaration of Similarity

DECLARATION OF SIMILARITY

February 15, 2019

To:
Bay Area Compliance Laboratories Corp.
1274 Anvilwood Ave.
Sunnyvale, CA 94089
Phone: 408-732-9162, Fax: 408-732-9164
http://www.baclcorp.com

Dear Sir or Madam:

We *Cisco Systems, Inc.* hereby declare that product: *Cisco Catalyst 9117AX*, model(s): *C9117AXI-T* is electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics as model: *C9117AXI-B* tested by BACL, the results of which are featured in BACL project: *R1811136*. Both model numbers have the same hardware and software/firmware build with the same radio capabilities and characteristics.

A description of the differences between the tested model and those that are declared similar are as follows:

Different model numbers to represent different regulatory domain.

Please contact me should there be need for any additional clarification or information.

Best Regards,

Responsible Party Signature

L. W. Custroe

Compliance Manager
125 W. Tasman Dr. San Jose, CA 95134

DECLARATION OF SIMILARITY

May 9, 2019

To:
Bay Area Compliance Laboratories Corp.
1274 Anvilwood Ave.
Sunnyvale, CA 94089
Phone: 408-732-9162, Fax: 408-732-9164
http://www.baclcorp.com

Dear Sir or Madam:

We *Cisco Systems, Inc.* hereby declare that product: *Cisco Catalyst 9117AX*, model(s): *C9117AXI-S, C9117AXI-Z, and C9117AXI-D* are electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics as model: *C9117AXI-B* tested by BACL, the results of which are featured in BACL project: *R1811136*. Both model numbers have the same hardware build with the same radio characteristics. Both model numbers have the same software/firmware except channels listed below are disabled to satisfy the frequency allocation in specific countries.

A description of the differences between the tested model and those that are declared similar are as follows:

- *Different model numbers to represent different regulatory domain.*
- *Channel 142, and 138 are disabled in C9117AXI-S image. This configuration cannot be modified by end uses.*
- *Channel 120, 124, 128, 118, 126, 142, 122, 138, & 114 are disabled in C9117AXI-Z image. This configuration cannot be modified by end users.*
- *The test report does not contain any measurement results for channel frequency: 5845 MHz, 5865 MHz, and 5855 MHz because these channels are not supported by C9117AXI-B and are disabled in C9117AXI-D system firmware. The end users do not have access to alter this setting.*

Please contact me should there be need for any additional clarification or information.

Best Regards,

Responsible Party Signature

L. W. Custroe

Compliance Manager
125 W. Tasman Dr. San Jose, CA
95134

12 Annex – Test Results and Measurement Plots

Test Data for Occupied Bandwidth

Freqency (MHz)	Mode	Data Rate (Mbps)	26dB BW (MHz)	99% BW (MHz)
5180	non HT20, 6 to 54 Mbps	6	26.2	16.56
	HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	m0	21.17	17.54
5190	HT/VHT/HE40, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	m0	40.17	36.24
5200	non HT20, 6 to 54 Mbps	6	25.46	16.56
	HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	m0	20.83	17.6
5210	VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	m0.1	79.51	75.48
5230	HT/VHT/HE40, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	m0	40	36.24
5240	non HT20, 6 to 54 Mbps	6	25.76	16.61
	HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	m0	20.96	17.6

Please refer to the following plots

26 dB Bandwidth

non HT20, 6 to 54 Mbps @ 5180 MHz



Date: 2.NOV.2018 10:17:46

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5180 MHz



Date: 2.NOV.2018 10:20:15

HT/VHT/HE40, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5190 MHz



Date: 12.DEC.2018 14:23:07

non HT20, 6 to 54 Mbps @ 5200 MHz



Date: 2.NOV.2018 10:24:49

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5200 MHz



Date: 2.NOV.2018 10:26:25

VHT/HE80, M0.1 to M9.1, M0.1 to M11.1 @ 5210 MHz



Date: 12.DEC.2018 15:01:32

HT/VHT/HE40, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5230 MHz



Date: 12.DEC.2018 14:27:45

non HT20, 6 to 54 Mbps @ 5240 MHz



Date: 2.NOV.2018 10:30:45

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5240 MHz



Date: 2.NOV.2018 10:35:15

99% Occupied Bandwidth

non HT20, 6 to 54 Mbps @ 5180 MHz



Date: 1.NOV.2018 18:25:48

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5180 MHz



Date: 1.NOV.2018 18:55:50

HT/VHT/HE40, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5190 MHz



Date: 1.NOV.2018 19:00:04

non HT20, 6 to 54 Mbps @ 5200 MHz



Date: 1.NOV.2018 19:02:08

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5200 MHz



Date: 1.NOV.2018 19:03:50

VHT/HE80, M0.1 to M9.1, M0.1 to M11.1 @ 5210 MHz



Date: 2.NOV.2018 09:37:24

HT/VHT/HE40, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5230 MHz



Date: 1.NOV.2018 20:11:35

non HT20, 6 to 54 Mbps @ 5240 MHz



Date: 1.NOV.2018 19:05:11

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1 @ 5240 MHz



Test results for Output power

5180 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Max Power (dBm)	Tx 2 Max Power (dBm)	Tx 3 Max Power (dBm)	Tx 4 Max Power (dBm)	Tx 5 Max Power (dBm)	Tx 6 Max Power (dBm)	Tx 7 Max Power (dBm)	Tx 8 Max Power (dBm)	DCCF (dB)	Total Max Power (dBm)	FCC Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	16.54								0.22	16.76	30.00	13.24
non HT20, 6 to 54 Mbps	2	6.00	15.51	13.76							0.22	17.95	30.00	12.05
non HT20, 6 to 54 Mbps	3	6.00	15.51	13.94	14.25						0.22	19.61	30.00	10.39
non HT20, 6 to 54 Mbps	4	6.00	14.53	13.19	13.67	14.46					0.22	20.24	30.00	9.76
non HT20, 6 to 54 Mbps	6	9.00	13.30	10.93	11.34	12.25	12.42	11.98			0.22	20.10	27.00	6.90
non HT20, 6 to 54 Mbps	8	9.00	10.67	8.35	8.57	10.15	10.47	10.02	9.37	9.50	0.22	18.96	27.00	8.04
non HT20, 6 to 54 Mbps-BF	2	9.01	14.45	13.03							0.22	17.03	26.99	9.96
non HT20, 6 to 54 Mbps-BF	3	10.77	13.86	11.90	13.22						0.22	18.06	25.23	7.17
non HT20, 6 to 54 Mbps-BF	4	12.02	14.08	11.63	12.75	13.29					0.22	19.27	23.98	4.71
non HT20, 6 to 54 Mbps-BF	6	13.78	9.97	7.62	9.20	8.66	9.26	8.46			0.22	16.92	22.22	5.30
non HT20, 6 to 54 Mbps-BF	8	15.03	5.96	5.43	5.51	5.12	6.34	5.32	5.40	5.17	0.22	14.80	20.97	6.17
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	16.46								0.22	16.68	30.00	13.32
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	16.47	14.41							0.22	18.79	30.00	11.21
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	16.46	14.47							0.22	18.81	30.00	11.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	16.52	14.23	15.32						0.22	20.45	30.00	9.55
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	16.75	14.50	15.50						0.22	20.67	30.00	9.33
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	15.64	13.97	14.33						0.22	19.70	30.00	10.30
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	15.42	13.70	14.13	14.89					0.22	20.83	30.00	9.17
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	15.60	13.93	14.43	15.06					0.22	21.04	30.00	8.96
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	14.79	13.51	13.93	14.85					0.22	20.55	30.00	9.45

HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	14.55	13.35	13.66	14.60					0.22	20.31	30.00	9.69
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	13.11	10.68	10.54	12.15	12.22	12.50			0.22	19.97	27.00	7.03
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	16.12	14.07	13.57	15.30	15.45	15.58			0.22	23.10	27.61	4.51
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	15.34	13.61	13.02	15.00	14.75	15.08			0.22	22.55	28.49	5.94
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	15.33	13.62	12.99	15.00	14.74	15.08			0.22	22.54	29.12	6.58
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	15.91	13.88	13.33	15.05	15.23	15.35			0.22	22.88	29.60	6.72
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	16.12	14.09	13.56	15.25	15.45	15.55			0.22	23.09	30.00	6.91
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	10.52	7.87	8.89	9.73	10.18	9.84	10.01	9.30	0.22	18.86	27.00	8.14
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	14.11	11.52	12.43	13.35	13.71	13.47	13.52	12.85	0.22	22.44	27.00	4.56
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	13.36	10.72	11.71	12.57	12.84	12.48	14.30	12.12	0.22	21.88	27.87	5.99
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	13.36	10.71	11.75	12.63	12.81	12.50	12.58	12.14	0.22	21.62	28.49	6.87
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	14.43	12.65	13.05	14.30	14.35	14.12	12.54	13.88	0.22	22.98	28.98	6.00
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	14.66	12.85	13.31	14.51	14.54	14.26	13.79	14.00	0.22	23.28	29.38	6.10
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	14.46	11.90	12.86	13.73	14.03	13.75	13.65	13.25	0.22	22.76	29.71	6.95
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	14.51	11.86	12.87	13.75	14.04	13.77	13.67	13.30	0.22	22.79	30.00	7.21
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	16.53	14.43							0.22	18.83	26.99	8.16
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	16.51	14.52							0.22	18.86	30.00	11.14
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	15.37	13.99	14.10						0.22	19.52	25.23	5.71
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	15.62	14.14	14.31						0.22	19.73	28.24	8.51
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	14.51	13.58	13.51						0.22	18.88	30.00	11.12
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	14.33	12.80	13.16	14.31					0.22	19.94	23.98	4.04
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	15.74	13.72	14.16	15.06					0.22	20.98	26.99	6.01
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	14.39	12.02	12.85	13.71					0.22	19.57	28.75	9.18
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	14.63	13.11	13.58	14.59					0.22	20.27	30.00	9.73
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	12.86	9.51	10.55	12.04	12.28	12.52			0.22	19.78	22.22	2.44
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	14.78	12.22	12.68	14.54	14.49	14.80			0.22	22.04	25.23	3.19
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	13.45	10.06	11.11	12.59	12.80	13.05			0.22	20.33	26.99	6.66
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	14.53	11.17	12.19	13.71	13.96	14.29			0.22	21.47	28.24	6.77

VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	15.68	12.67	13.36	14.92	15.28	15.37			0.22	22.68	29.21	6.53
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	15.89	12.88	13.56	15.13	15.50	15.55			0.22	22.89	30.00	7.11
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	9.41	6.83	7.20	8.44	8.98	8.96	8.91	8.23	0.22	17.70	20.97	3.27
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	13.00	10.43	10.68	12.23	12.38	12.60	12.39	11.76	0.22	21.27	23.98	2.71
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	12.29	9.58	9.96	11.44	11.60	11.80	11.68	11.06	0.22	20.51	25.74	5.23
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	13.34	10.77	11.06	12.65	12.74	12.98	12.72	12.13	0.22	21.63	26.99	5.36
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	13.86	11.36	11.64	13.19	13.38	13.68	12.57	12.73	0.22	22.13	27.96	5.83
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	14.67	12.90	12.68	14.54	14.40	14.67	13.26	14.05	0.22	23.21	28.75	5.54
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	14.42	11.91	12.17	13.73	13.93	14.20	13.90	13.25	0.22	22.77	29.42	6.65
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	14.45	11.92	12.22	13.79	13.95	14.21	13.67	13.29	0.22	22.77	30.00	7.23
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	16.52	14.28							0.22	18.78	30.00	11.22
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	16.47	14.49	15.42						0.22	20.53	30.00	9.47
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	15.64	13.54	14.38	14.91					0.22	20.93	30.00	9.07
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	15.70	13.42	13.34	14.91	15.29	15.37			0.22	22.77	30.00	7.23
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	13.89	11.97	13.33	13.18	13.55	13.32	13.26	12.73	0.22	22.44	30.00	7.56

5200 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Max Power (dBm)	Tx 2 Max Power (dBm)	Tx 3 Max Power (dBm)	Tx 4 Max Power (dBm)	Tx 5 Max Power (dBm)	Tx 6 Max Power (dBm)	Tx 7 Max Power (dBm)	Tx 8 Max Power (dBm)	DCCF (dB)	Total Max Power (dBm)	FCC Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	16.52								0.22	16.74	30.00	13.26
non HT20, 6 to 54 Mbps	2	6.00	16.53	14.88							0.22	19.01	30.00	10.99
non HT20, 6 to 54 Mbps	3	6.00	16.53	14.99	15.48						0.22	20.71	30.00	9.29
non HT20, 6 to 54 Mbps	4	6.00	16.70	14.96	15.63	16.06					0.22	22.12	30.00	7.88
non HT20, 6 to 54 Mbps	6	9.00	13.37	9.98	13.61	12.51	12.40	11.87			0.22	20.44	27.00	6.56
non HT20, 6 to 54 Mbps	8	9.00	10.69	8.70	10.29	10.14	10.23	10.27	9.81	9.19	0.22	19.21	27.00	7.79
non HT20, 6 to 54 Mbps-BF	2	9.01	16.56	14.86							0.22	19.02	26.99	7.97
non HT20, 6 to 54 Mbps-BF	3	10.77	16.63	14.99	16.16						0.22	20.97	25.23	4.26
non HT20, 6 to 54 Mbps-BF	4	12.02	16.65	14.99	15.89	16.07					0.22	22.18	23.98	1.80
non HT20, 6 to 54 Mbps-BF	6	13.78	13.41	11.41	13.59	12.06	12.51	11.82			0.22	20.54	22.22	1.68
non HT20, 6 to 54 Mbps-BF	8	15.03	10.74	8.50	8.95	10.08	10.47	9.79	9.94	9.14	0.22	19.01	20.97	1.96
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	16.46								0.22	16.68	30.00	13.32
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	16.45	14.60							0.22	18.85	30.00	11.15
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	16.41	14.64							0.22	18.84	30.00	11.16
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	16.42	14.94	15.39						0.22	20.62	30.00	9.38
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	16.38	14.96	15.35						0.22	20.60	30.00	9.40
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	16.62	15.21	15.48						0.22	20.81	30.00	9.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	16.71	14.91	15.22	15.85					0.22	21.97	30.00	8.03
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	16.70	14.93	15.26	15.86					0.22	21.98	30.00	8.02
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	16.92	15.22	15.55	16.06					0.22	22.23	30.00	7.77
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	16.94	15.18	15.58	16.11					0.22	22.24	30.00	7.76

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	13.19	11.22	11.10	12.27	12.28	11.53			0.22	20.00	27.00	7.00
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	16.00	14.35	13.89	15.15	15.29	14.39			0.22	22.90	27.61	4.71
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	17.19	15.41	15.46	16.48	16.40	15.69			0.22	24.15	28.49	4.34
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	17.21	15.35	15.39	16.43	16.45	15.69			0.22	24.14	29.12	4.98
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	17.04	15.15	15.22	16.14	16.17	15.45			0.22	23.92	29.60	5.68
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	17.11	15.17	15.13	16.18	16.21	15.39			0.22	23.93	30.00	6.07
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	10.51	8.57	9.96	9.97	11.17	9.96	9.23	8.84	0.22	19.10	27.00	7.90
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	13.83	12.14	13.30	13.35	13.59	13.39	12.72	12.39	0.22	22.38	27.00	4.62
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	15.75	14.36	15.28	15.39	15.57	15.20	14.54	14.49	0.22	24.35	27.87	3.52
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	16.78	15.21	16.37	16.46	16.52	16.15	15.65	15.34	0.22	25.34	28.49	3.15
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	16.63	14.84	16.26	16.22	16.32	15.97	15.54	15.13	0.22	25.15	28.98	3.83
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	16.65	14.83	16.21	16.18	16.27	15.94	15.48	15.18	0.22	25.13	29.38	4.25
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	16.74	15.18	16.42	16.40	16.50	16.18	15.63	15.33	0.22	25.33	29.71	4.38
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	16.76	15.15	16.39	16.42	16.47	16.14	15.68	15.35	0.22	25.33	30.00	4.67
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	16.47	14.67							0.22	18.89	26.99	8.10
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	16.47	14.57							0.22	18.85	30.00	11.15
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	16.51	14.54	15.94						0.22	20.73	25.23	4.50
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	16.47	14.62	15.96						0.22	20.74	28.24	7.50
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	16.69	14.89	16.17						0.22	20.97	30.00	9.03
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	16.52	14.32	15.70	15.93					0.22	21.93	23.98	2.05
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	16.56	14.41	15.77	15.94					0.22	21.98	26.99	5.01
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	16.77	14.54	15.89	16.11					0.22	22.14	28.75	6.61
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	16.74	14.56	15.92	16.09					0.22	22.14	30.00	7.86
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	12.30	11.24	13.42	11.40	12.28	11.48			0.22	20.09	22.22	2.13
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	15.09	14.29	16.18	14.35	15.26	14.32			0.22	22.97	25.23	2.26
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	16.41	15.38	17.44	15.74	16.41	15.64			0.22	24.23	26.99	2.76
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	16.41	15.38	17.44	15.72	16.41	15.69			0.22	24.23	28.24	4.01
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	16.25	15.11	17.26	15.38	16.24	15.42			0.22	24.01	29.21	5.20

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	16.23	15.08	17.25	15.41	16.21	15.41			0.22	24.00	30.00	6.00
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	10.56	8.16	8.54	9.89	10.05	10.18	9.68	8.97	0.22	18.83	20.97	2.14
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	13.86	11.79	11.75	13.31	13.43	13.66	13.02	12.36	0.22	22.22	23.98	1.76
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	15.76	14.02	13.88	15.36	15.48	15.36	15.05	14.56	0.22	24.23	25.74	1.51
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	16.80	14.70	15.05	16.37	16.30	16.44	16.17	15.32	0.22	25.20	26.99	1.79
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	16.62	14.45	14.78	16.14	16.07	16.21	15.94	15.12	0.22	24.98	27.96	2.98
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	16.63	14.48	14.75	16.06	16.12	16.21	15.98	15.18	0.22	24.99	28.75	3.76
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	16.77	14.74	15.03	16.34	16.33	16.34	16.10	15.34	0.22	25.18	29.42	4.24
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	16.78	14.77	15.11	16.39	16.31	16.40	16.04	15.38	0.22	25.20	30.00	4.80
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	16.45	14.64							0.22	18.87	30.00	11.13
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	16.39	14.79	15.92						0.22	20.74	30.00	9.26
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	16.52	14.73	15.28	15.85					0.22	21.89	30.00	8.11
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	15.69	14.45	15.66	14.33	15.29	14.37			0.22	23.01	30.00	6.99
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	13.76	12.14	12.03	13.37	13.41	13.53	12.97	12.35	0.22	22.24	30.00	7.76

5240 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Max Power (dBm)	Tx 2 Max Power (dBm)	Tx 3 Max Power (dBm)	Tx 4 Max Power (dBm)	Tx 5 Max Power (dBm)	Tx 6 Max Power (dBm)	Tx 7 Max Power (dBm)	Tx 8 Max Power (dBm)	DCCF (dB)	Total Max Power (dBm)	FCC Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	16.34								0.22	16.56	30.00	13.44
non HT20, 6 to 54 Mbps	2	6.00	16.29	14.53							0.22	18.73	30.00	11.27
non HT20, 6 to 54 Mbps	3	6.00	16.34	14.38	15.47						0.22	20.46	30.00	9.54
non HT20, 6 to 54 Mbps	4	6.00	16.46	14.45	15.63	15.73					0.22	21.87	30.00	8.13
non HT20, 6 to 54 Mbps	6	9.00	12.91	10.72	13.40	12.32	12.30	10.43			0.22	20.15	27.00	6.85
non HT20, 6 to 54 Mbps	8	9.00	10.64	8.39	9.06	8.95	9.89	9.28	9.49	8.71	0.22	18.60	27.00	8.40
non HT20, 6 to 54 Mbps-BF	2	9.01	16.30	14.68							0.22	18.80	26.99	8.19
non HT20, 6 to 54 Mbps-BF	3	10.77	16.25	14.42	16.07						0.22	20.65	25.23	4.58
non HT20, 6 to 54 Mbps-BF	4	12.02	16.44	14.71	15.58	15.76					0.22	21.91	23.98	2.07
non HT20, 6 to 54 Mbps-BF	6	13.78	12.33	10.77	11.26	12.36	12.35	12.34			0.22	19.95	22.22	2.27
non HT20, 6 to 54 Mbps-BF	8	15.03	10.60	8.30	9.10	9.08	10.37	8.80	9.41	8.80	0.22	18.62	20.97	2.35
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	16.11								0.22	16.33	30.00	13.67
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	16.12	14.42							0.22	18.58	30.00	11.42
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	16.14	14.44							0.22	18.60	30.00	11.40
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	16.05	14.38	15.40						0.22	20.32	30.00	9.68
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	16.06	14.38	15.31						0.22	20.30	30.00	9.70
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	16.20	14.61	15.55						0.22	20.49	30.00	9.51
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	16.36	14.53	15.43	15.53					0.22	21.75	30.00	8.25
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	16.37	14.57	15.35	15.54					0.22	21.75	30.00	8.25
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	16.54	14.76	15.57	15.86					0.22	21.97	30.00	8.03
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	16.52	14.84	15.65	15.87					0.22	22.00	30.00	8.00

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	12.89	9.45	12.58	11.17	12.05	10.17			0.22	19.56	27.00	7.44
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	15.95	12.25	15.58	14.05	14.97	13.31			0.22	22.54	27.61	5.07
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	16.97	13.35	16.68	15.40	16.22	14.49			0.22	23.70	28.49	4.79
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	16.95	13.25	16.68	15.45	16.17	14.46			0.22	23.68	29.12	5.44
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	16.79	12.96	16.47	15.33	16.01	14.26			0.22	23.50	29.60	6.10
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	16.77	12.97	16.61	15.25	16.05	14.23			0.22	23.51	30.00	6.49
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	10.37	8.33	10.28	9.77	9.82	9.05	9.65	8.57	0.22	18.79	27.00	8.21
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	13.38	11.78	13.50	13.31	13.13	12.42	12.68	12.23	0.22	22.09	27.00	4.91
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	15.68	13.81	15.59	15.21	15.06	14.27	15.00	14.20	0.22	24.15	27.87	3.72
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	16.54	14.68	16.40	16.39	16.17	15.29	16.03	15.12	0.22	25.13	28.49	3.36
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	16.39	14.48	16.31	16.12	15.92	15.15	15.87	14.80	0.22	24.93	28.98	4.05
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	16.32	14.35	16.31	16.11	15.87	15.02	15.80	14.87	0.22	24.89	29.38	4.49
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	16.51	14.63	16.52	16.36	16.16	15.29	16.07	15.18	0.22	25.14	29.71	4.57
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	16.49	14.67	16.45	16.38	16.19	15.30	15.97	15.13	0.22	25.12	30.00	4.88
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	16.14	14.53							0.22	18.64	26.99	8.35
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	16.21	14.47							0.22	18.66	30.00	11.34
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	16.08	14.45	15.35						0.22	20.34	25.23	4.89
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	16.03	14.51	15.35						0.22	20.33	28.24	7.91
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	16.27	14.83	15.54						0.22	20.58	30.00	9.42
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	16.48	14.21	16.02	15.46					0.22	21.86	23.98	2.12
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	16.38	14.27	15.96	15.41					0.22	21.82	26.99	5.17
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	16.58	14.46	16.09	15.71					0.22	22.02	28.75	6.73
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	16.56	14.51	16.13	15.81					0.22	22.06	30.00	7.94
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	12.01	10.53	12.06	12.38	12.05	10.15			0.22	19.61	22.22	2.61
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	15.00	13.28	15.10	15.15	14.94	13.24			0.22	22.53	25.23	2.70
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	16.09	14.35	16.30	16.53	16.21	14.54			0.22	23.76	26.99	3.23
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	16.10	14.41	16.34	16.51	16.18	14.55			0.22	23.76	28.24	4.48
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	15.84	14.06	16.04	16.31	16.00	14.20			0.22	23.50	29.21	5.71

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	15.84	14.07	16.10	16.34	16.00	14.19			0.22	23.52	30.00	6.48
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	10.30	8.51	8.56	8.82	10.12	9.50	9.47	8.55	0.22	18.53	20.97	2.44
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	13.33	11.93	11.91	12.12	13.37	12.90	12.64	12.22	0.22	21.84	23.98	2.14
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	15.62	13.96	14.20	14.03	15.37	14.89	15.01	14.25	0.22	23.96	25.74	1.78
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	16.43	14.81	15.17	15.32	16.38	15.86	16.05	15.13	0.22	24.93	26.99	2.06
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	16.28	14.44	14.78	15.11	16.22	15.55	15.79	14.80	0.22	24.67	27.96	3.29
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	16.28	14.46	14.90	15.15	16.18	15.63	15.70	14.88	0.22	24.69	28.75	4.06
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	16.43	14.86	15.16	15.40	16.40	15.84	16.05	15.18	0.22	24.95	29.42	4.47
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	16.46	14.80	15.21	15.34	16.40	15.86	16.04	15.14	0.22	24.95	30.00	5.05
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	16.10	14.44							0.22	18.58	30.00	11.42
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	16.05	14.44	15.85						0.22	20.49	30.00	9.51
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	16.21	14.02	15.35	15.85					0.22	21.67	30.00	8.33
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	15.01	13.43	15.67	15.17	15.00	15.10			0.22	22.95	30.00	7.05
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	13.41	11.92	13.85	13.17	13.48	12.92	12.33	12.11	0.22	22.20	30.00	7.80

5190 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Max Power (dBm)	Tx 2 Max Power (dBm)	Tx 3 Max Power (dBm)	Tx 4 Max Power (dBm)	Tx 5 Max Power (dBm)	Tx 6 Max Power (dBm)	Tx 7 Max Power (dBm)	Tx 8 Max Power (dBm)	DCCF (dB)	Total Max Power (dBm)	FCC Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	15.73								0.18	15.91	30.00	14.09
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	14.76	13.23							0.18	17.25	30.00	12.75
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	14.77	13.30							0.18	17.29	30.00	12.71
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	13.95	12.50	12.76						0.18	18.07	30.00	11.93
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	14.11	12.69	12.99						0.18	18.26	30.00	11.74
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	12.90	11.66	11.87						0.18	17.13	30.00	12.87
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	12.94	11.56	12.14	10.64					0.18	18.10	30.00	11.90
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	13.13	11.79	12.27	10.85					0.18	18.29	30.00	11.71
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	12.12	11.06	11.34	9.80					0.18	17.36	30.00	12.64
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	11.86	10.88	11.12	9.56					0.18	17.13	30.00	12.87
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	6.00	13.10	11.95	13.76	10.54	12.78	13.77			0.18	20.75	30.00	9.25
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	6.00	13.30	12.15	13.95	10.77	12.99	13.99			0.18	20.95	30.00	9.05
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	6.00	11.25	10.19	11.89	8.32	10.80	11.93			0.18	18.85	30.00	11.15
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.00	12.29	11.31	13.01	9.66	12.02	13.03			0.18	19.99	30.00	10.01
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.00	11.96	10.98	12.65	9.31	11.67	12.71			0.18	19.65	30.00	10.35
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	12.21	11.24	12.93	9.58	11.97	12.98			0.18	19.92	30.00	10.08
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	6.00	11.81	10.57	10.91	9.30	11.61	11.46	11.09	10.57	0.18	20.19	30.00	9.81
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	6.00	11.98	10.68	11.10	9.52	11.79	11.59	11.31	10.78	0.18	20.36	30.00	9.64
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	6.00	11.08	9.70	10.17	8.36	10.78	10.61	10.37	9.66	0.18	19.37	30.00	10.63
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	6.00	11.09	9.71	10.23	8.35	10.86	10.59	10.42	9.75	0.18	19.41	30.00	10.59
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	6.00	10.80	9.43	9.83	7.99	10.41	10.39	10.00	9.36	0.18	19.06	30.00	10.94
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.00	11.05	9.68	10.10	8.26	10.66	10.55	10.19	9.63	0.18	19.29	30.00	10.71

VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.00	11.08	9.71	10.24	8.44	10.84	10.64	10.36	9.69	0.18	19.40	30.00	10.60
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	10.91	9.63	10.33	8.45	10.81	10.63	10.49	9.68	0.18	19.39	30.00	10.61
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	12.86	11.39							0.18	15.38	26.99	11.61
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	13.98	12.44							0.18	16.47	30.00	13.53
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	11.71	10.87	11.12						0.18	16.20	25.23	9.03
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	13.09	12.08	12.41						0.18	17.49	28.24	10.75
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	12.97	12.09	12.32						0.18	17.43	30.00	12.57
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	10.80	9.53	10.11	8.04					0.18	15.93	23.98	8.05
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	12.04	10.85	11.40	9.55					0.18	17.25	26.99	9.74
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	12.14	11.07	11.53	9.69					0.18	17.40	28.75	11.35
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	13.03	11.79	12.39	10.70					0.18	18.26	30.00	11.74
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	8.49	7.34	6.21	5.95	7.95	9.26			0.18	15.65	22.22	6.57
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	9.84	8.43	7.43	7.24	9.46	10.66			0.18	16.98	25.23	8.25
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	10.96	9.42	8.87	8.58	10.80	11.95			0.18	18.23	26.99	8.76
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	11.97	10.60	9.97	9.88	11.97	13.07			0.18	19.37	28.24	8.87
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	12.81	11.20	10.81	10.76	12.72	13.82			0.18	20.14	29.21	9.07
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	13.08	11.48	11.06	11.06	13.00	14.09			0.18	20.41	30.00	9.59
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	6.63	5.83	5.22	3.28	5.73	5.81	5.77	5.37	0.18	14.75	20.97	6.22
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	8.85	7.84	7.59	5.91	8.10	8.15	8.09	7.52	0.18	17.03	23.98	6.95
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	10.07	8.82	8.80	7.21	9.63	9.45	9.22	8.73	0.18	18.27	25.74	7.47
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	10.09	8.88	8.83	7.24	9.69	9.42	9.18	8.85	0.18	18.30	26.99	8.69
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	10.84	9.49	9.75	8.12	10.42	10.35	9.98	9.34	0.18	19.07	27.96	8.89
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	11.09	9.64	9.94	8.39	10.68	10.54	10.20	9.60	0.18	19.29	28.75	9.46
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	11.12	9.78	10.06	8.49	10.84	10.65	10.31	9.73	0.18	19.40	29.42	10.02
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	11.95	10.86	11.23	9.84	12.00	11.75	11.45	10.91	0.18	20.51	30.00	9.49
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	14.84	13.56							0.18	17.44	30.00	12.56
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	14.83	13.78	14.40						0.18	19.31	30.00	10.69
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	14.21	12.78	13.22	11.85					0.18	19.30	30.00	10.70

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	13.14	12.20	11.15	10.47	12.84	13.82			0.18	20.38	30.00	9.62
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	11.84	10.66	10.92	9.32	11.67	11.45	10.95	10.56	0.18	20.19	30.00	9.81

5230 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Max Power (dBm)	Tx 2 Max Power (dBm)	Tx 3 Max Power (dBm)	Tx 4 Max Power (dBm)	Tx 5 Max Power (dBm)	Tx 6 Max Power (dBm)	Tx 7 Max Power (dBm)	Tx 8 Max Power (dBm)	DCCF (dB)	Total Max Power (dBm)	FCC Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	15.86								0.18	16.04	30.00	13.96
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	15.86	13.94							0.18	18.19	30.00	11.81
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	15.90	14.03							0.18	18.26	30.00	11.74
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	15.92	13.87	15.01						0.18	19.96	30.00	10.04
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	16.16	14.06	15.28						0.18	20.20	30.00	9.80
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	15.98	14.02	15.10						0.18	20.06	30.00	9.94
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	15.99	14.14	15.24	15.24					0.18	21.40	30.00	8.60
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	16.17	14.38	15.53	15.47					0.18	21.64	30.00	8.36
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	16.22	14.51	15.70	15.59					0.18	21.75	30.00	8.25
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	16.00	14.35	15.41	15.35					0.18	21.52	30.00	8.48
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	6.00	14.61	13.63	13.06	13.94	14.68	13.90			0.18	21.97	30.00	8.03
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	6.00	15.93	14.78	14.56	15.32	15.95	14.95			0.18	23.24	30.00	6.76
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	6.00	16.00	14.89	14.69	15.45	16.04	15.04			0.18	23.34	30.00	6.66
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.00	16.00	14.89	14.65	15.43	16.02	15.04			0.18	23.33	30.00	6.67
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.00	15.69	14.56	14.32	15.15	15.77	14.72			0.18	23.03	30.00	6.97
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	15.91	14.82	14.57	15.35	15.98	14.96			0.18	23.26	30.00	6.74
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	6.00	13.23	11.26	12.38	12.43	12.98	12.49	12.32	11.86	0.18	21.62	30.00	8.38
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	6.00	16.22	14.27	15.49	15.55	16.03	15.57	15.39	14.56	0.18	24.64	30.00	5.36
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	6.00	16.34	14.38	15.64	15.69	16.10	15.70	15.55	14.69	0.18	24.76	30.00	5.24
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	6.00	16.32	14.42	15.69	15.67	16.18	15.72	15.61	14.76	0.18	24.80	30.00	5.20
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	6.00	15.96	14.04	15.24	15.35	15.84	15.34	15.18	14.38	0.18	24.42	30.00	5.58
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.00	16.20	14.27	15.43	15.56	16.05	15.62	15.44	14.66	0.18	24.66	30.00	5.34

VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.00	16.27	14.40	15.63	15.70	16.15	15.74	15.56	14.63	0.18	24.76	30.00	5.24
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	16.15	14.36	15.73	15.71	16.14	15.73	15.65	14.58	0.18	24.76	30.00	5.24
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	15.86	13.99							0.18	18.22	26.99	8.77
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	15.88	14.04							0.18	18.25	30.00	11.75
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	15.85	14.04	15.57						0.18	20.18	25.23	5.05
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	16.04	14.25	15.80						0.18	20.38	28.24	7.86
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	15.85	14.18	15.65						0.18	20.24	30.00	9.76
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	16.08	13.91	15.52	15.42					0.18	21.50	23.98	2.48
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	16.35	14.09	15.69	15.60					0.18	21.71	26.99	5.28
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	16.44	14.21	15.78	15.73					0.18	21.81	28.75	6.94
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	16.16	13.97	15.54	15.46					0.18	21.55	30.00	8.45
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	13.88	10.94	11.31	12.90	12.83	11.66			0.18	20.34	22.22	1.88
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	16.88	13.86	14.43	16.04	15.93	14.85			0.18	23.42	25.23	1.81
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	16.91	13.98	14.58	16.10	15.98	14.91			0.18	23.49	26.99	3.50
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	16.92	13.99	14.57	16.14	16.00	14.95			0.18	23.51	28.24	4.73
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	16.65	13.64	14.22	15.84	15.71	14.63			0.18	23.20	29.21	6.01
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	16.86	13.93	14.50	16.06	15.92	14.86			0.18	23.43	30.00	6.57
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	9.89	8.34	9.18	9.12	9.52	9.31	9.07	8.38	0.18	18.34	20.97	2.63
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	13.55	11.35	12.67	12.67	13.02	12.74	12.56	12.03	0.18	21.83	23.98	2.15
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	15.27	13.34	14.53	14.53	14.93	14.98	14.55	13.81	0.18	23.74	25.74	2.00
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	16.38	14.28	15.68	15.69	16.11	15.82	15.47	14.72	0.18	24.78	26.99	2.21
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	16.07	13.93	15.37	15.37	15.78	15.42	15.18	14.34	0.18	24.44	27.96	3.52
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	16.33	14.19	15.71	15.56	15.93	15.63	15.35	14.58	0.18	24.67	28.75	4.08
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	16.37	14.27	15.75	15.74	16.13	15.82	15.46	14.59	0.18	24.78	29.42	4.64
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	16.24	14.22	15.77	15.78	16.10	15.91	15.53	14.61	0.18	24.78	30.00	5.22
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	15.90	14.09							0.18	18.28	30.00	11.72
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	15.90	14.09	15.04						0.18	20.02	30.00	9.98
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	16.13	14.04	15.24	15.20					0.18	21.41	30.00	8.59

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	16.65	14.67	16.44	15.05	15.75	16.14			0.18	23.80	30.00	6.20
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	16.11	13.94	15.29	15.32	15.87	15.44	15.13	14.31	0.18	24.44	30.00	5.56

5210 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Max Power (dBm)	Tx 2 Max Power (dBm)	Tx 3 Max Power (dBm)	Tx 4 Max Power (dBm)	Tx 5 Max Power (dBm)	Tx 6 Max Power (dBm)	Tx 7 Max Power (dBm)	Tx 8 Max Power (dBm)	DCCF (dB)	Total Max Power (dBm)	FCC Limit (dBm)	Margin (dB)
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	1	6.00	12.98								0.22	13.20	30.00	16.81
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	2	6.00	11.79	10.02							0.22	14.22	30.00	15.78
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	2	6.00	11.80	10.01							0.22	14.22	30.00	15.78
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	3	6.00	10.67	8.74	10.24						0.22	14.95	30.00	15.05
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	3	6.00	10.80	8.84	10.40						0.22	15.08	30.00	14.92
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	3	6.00	10.86	9.01	10.50						0.22	15.19	30.00	14.81
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	4	6.00	9.57	8.13	8.50	8.65					0.22	14.99	30.00	15.01
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	4	6.00	9.68	8.30	8.60	8.81					0.22	15.12	30.00	14.88
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	4	6.00	9.88	8.53	8.93	9.14					0.22	15.39	30.00	14.61
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	4	6.00	9.77	8.37	8.71	8.90					0.22	15.21	30.00	14.79
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	6	6.00	7.50	6.53	7.83	5.88	7.11	7.43			0.22	15.10	30.00	14.90
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	6	6.00	7.60	6.67	7.90	5.87	7.14	7.56			0.22	15.18	30.00	14.82
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	6	6.00	7.78	6.80	8.13	6.15	7.37	7.70			0.22	15.37	30.00	14.63
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	6	6.00	7.72	6.71	8.07	6.10	7.29	7.69			0.22	15.31	30.00	14.69
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	6	6.00	7.75	6.80	8.12	6.20	7.43	7.75			0.22	15.39	30.00	14.61
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	6	6.00	7.68	6.78	7.98	6.03	7.27	7.61			0.22	15.27	30.00	14.73
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	8	6.00	7.24	6.45	6.47	6.46	7.14	6.81	6.66	5.85	0.22	15.90	30.00	14.10
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	8	6.00	7.31	6.54	6.57	6.60	7.30	6.94	6.76	5.94	0.22	16.02	30.00	13.98
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	8	6.00	6.47	5.78	5.82	5.85	6.59	6.13	5.94	5.05	0.22	15.23	30.00	14.77
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	8	6.00	6.43	5.77	5.86	5.74	6.48	6.12	6.01	5.16	0.22	15.22	30.00	14.78
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	8	6.00	6.60	5.81	5.88	5.81	6.46	6.09	6.09	5.09	0.22	15.25	30.00	14.75
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	8	6.00	6.54	5.86	5.93	5.69	6.54	5.95	6.10	5.16	0.22	15.24	30.00	14.76

VHT/HE80, M0.7 to M9.7, M0.7 to M11.7	8	6.00	6.60	5.83	5.82	5.73	6.46	6.15	6.05	5.23	0.22	15.25	30.00	14.75
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8	8	6.00	6.40	5.71	5.55	5.50	6.46	5.98	5.84	4.98	0.22	15.08	30.00	14.92
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	8.36	7.39							0.22	11.13	26.99	15.86
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	11.81	9.92							0.22	14.20	30.00	15.80
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	7.06	6.30	6.11						0.22	11.50	25.23	13.73
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	8.48	7.34	7.22						0.22	12.71	28.24	15.53
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	10.83	9.05	9.84						0.22	14.96	30.00	15.04
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	5.01	4.78	4.34	4.23					0.22	10.84	23.98	13.14
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	7.30	6.82	6.68	6.74					0.22	13.13	26.99	13.86
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	7.43	7.12	6.92	6.96					0.22	13.35	28.75	15.40
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	9.80	8.65	9.07	9.09					0.22	15.41	30.00	14.59
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	3.79	6.43	6.23	5.71	4.02	2.53			0.22	13.01	22.22	9.21
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	4.78	5.10	3.54	3.99	5.22	4.17			0.22	12.51	25.23	12.72
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	5.05	5.25	3.87	4.31	5.33	4.26			0.22	12.71	26.99	14.28
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	6.21	6.25	4.94	5.49	6.30	5.32			0.22	13.79	28.24	14.45
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	7.24	7.28	6.13	6.70	7.36	6.44			0.22	14.88	29.21	14.33
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	7.03	7.13	6.01	6.67	7.34	6.38			0.22	14.78	30.00	15.22
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	2.02	2.86	2.06	2.01	2.13	1.65	2.05	2.13	0.22	11.38	20.97	9.59
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	3.85	4.73	4.25	4.12	4.35	3.40	3.35	4.21	0.22	13.31	23.98	10.67
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	3.99	5.15	4.67	4.76	4.60	3.83	3.81	4.94	0.22	13.75	25.74	11.99
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	4.08	5.42	4.97	4.80	4.48	3.76	3.93	5.01	0.22	13.84	26.99	13.15
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	6.41	6.01	5.89	5.87	6.50	6.31	6.02	5.15	0.22	15.29	27.96	12.67
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	6.49	5.92	5.90	5.67	6.60	6.17	6.01	5.12	0.22	15.26	28.75	13.49
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	6.54	5.93	5.88	5.81	6.46	6.22	5.93	5.20	0.22	15.26	29.42	14.16
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	6.33	5.96	5.68	5.66	6.48	6.14	5.74	4.94	0.22	15.14	30.00	14.86
VHT/HE80, M0 to M9, M0 to M11-STBC	2	6.00	11.71	10.04							0.22	14.19	30.00	15.81
VHT/HE80, M0 to M9, M0 to M11-STBC	3	6.00	10.66	8.96	9.61						0.22	14.79	30.00	15.21
VHT/HE80, M0 to M9, M0 to M11-STBC	4	6.00	9.58	8.39	8.67	8.82					0.22	15.13	30.00	14.87

VHT/HE80, M0 to M9, M0 to M11-STBC	6	6.00	8.11	7.92	8.79	8.20	8.16	7.20			0.22	16.09	30.00	13.91
VHT/HE80, M0 to M9, M0 to M11-STBC	8	6.00	6.46	6.50	6.56	6.48	7.14	6.87	6.54	5.91	0.22	15.82	30.00	14.18

Test results for Power Spectrum Density

5180 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 PSD (dBm/MHz)	Tx 2 PSD (dBm/MHZ)	Tx 3 PSD (dBm/MHz)	Tx 4 PSD (dBm/MHz)	Tx 5 PSD (dBm/MHz)	Tx 6 PSD (dBm/MHz)	Tx 7 PSD (dBm/MHz)	Tx 8 PSD (dBm/MHz)	DCCF (dB)	Total PSD (dBm/MHz)	FCC Limit (dBm/MHz)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	4.35								0.44	4.79	17.00	12.21
non HT20, 6 to 54 Mbps	2	9.01	3.54	4.06							0.44	7.26	13.99	6.73
non HT20, 6 to 54 Mbps	3	10.77	3.30	4.04	4.33						0.44	9.12	12.23	3.11
non HT20, 6 to 54 Mbps	4	12.02	2.49	3.18	3.44	2.40					0.44	9.36	10.98	1.62
non HT20, 6 to 54 Mbps	6	13.78	1.14	0.37	-0.78	0.23	0.22	-0.17			0.44	8.62	9.22	0.79
non HT20, 6 to 54 Mbps	**8**	**15.03**	**-1.99**	**-2.27**	**-2.24**	**-2.12**	**-2.40**	**-2.18**	**-1.95**	**-2.39**	**0.44**	**7.28**	**7.97**	**0.69**
non HT20, 6 to 54 Mbps-BF	2	9.01	2.66	0.99							0.44	5.36	13.99	8.63
non HT20, 6 to 54 Mbps-BF	3	10.77	2.05	-0.01	1.19						0.44	6.37	12.23	5.86
non HT20, 6 to 54 Mbps-BF	4	12.02	2.36	-0.30	1.25	1.23					0.44	7.70	10.98	3.28
non HT20, 6 to 54 Mbps-BF	6	13.78	-2.33	-4.75	-3.01	-3.77	-2.95	-3.80			0.44	4.85	9.22	4.37
non HT20, 6 to 54 Mbps-BF	8	15.03	-6.14	-6.96	-6.04	-7.17	-5.81	-6.29	-6.64	-6.83	0.44	3.01	7.97	4.96
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	4.15								0.44	4.59	17.00	12.41
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	9.01	4.63	2.13							0.44	7.01	13.99	6.98
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	4.15	2.26							0.44	6.76	17.00	10.24
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	10.77	4.54	1.91	2.97						0.44	8.49	12.23	3.74
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	7.76	4.27	2.01	2.97						0.44	8.39	15.24	6.85
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	3.26	1.53	1.90						0.44	7.51	17.00	9.49
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	12.02	2.98	1.17	2.30	2.78					0.44	8.82	10.98	2.16
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	9.01	3.35	1.65	2.03	2.59					0.44	8.91	13.99	5.08
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	7.25	2.01	0.82	1.26	2.19					0.44	8.07	15.75	7.68

HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	2.06	0.91	1.21	2.12					0.44	8.07	17.00	8.93
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	13.78	0.76	-1.56	-1.79	-0.06	0.02	0.15			0.44	7.90	9.22	1.32
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	10.77	3.62	1.43	1.09	2.82	3.07	3.14			0.44	10.85	12.23	1.38
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	9.01	2.45	0.96	0.17	2.13	2.13	2.23			0.44	9.97	13.99	4.02
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	7.76	2.69	0.98	0.38	2.10	1.94	2.34			0.44	10.03	15.24	5.21
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.79	3.71	1.61	1.01	2.86	3.06	3.07			0.44	10.87	16.21	5.34
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	3.81	1.48	0.97	2.77	2.85	3.08			0.44	10.82	17.00	6.18
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	15.03	-1.82	-4.13	-2.94	-2.49	-1.86	-1.70	-1.67	-2.84	0.44	7.11	7.97	0.86
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	12.02	0.12	-0.39	0.12	0.77	1.38	1.64	1.50	0.52	0.44	10.23	10.98	0.75
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	10.26	0.83	-1.73	-0.50	-0.38	0.34	0.33	2.72	-0.77	0.44	9.76	12.74	2.98
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	9.01	0.87	-1.92	-0.70	-0.16	0.30	0.03	0.35	-0.71	0.44	9.30	13.99	4.69
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	8.04	2.60	0.66	1.16	2.07	2.16	2.63	0.76	1.78	0.44	11.26	14.96	3.70
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	7.25	2.58	0.92	1.28	2.11	2.22	2.32	2.17	1.54	0.44	11.40	15.75	4.35
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.58	2.13	-0.68	0.57	1.13	1.41	1.39	1.84	0.42	0.44	10.57	16.42	5.85
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	2.01	-0.59	0.45	0.88	1.54	1.13	1.29	0.68	0.44	10.45	17.00	6.55
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	4.61	2.19							0.44	7.02	13.99	6.97
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	4.32	2.12							0.44	6.81	17.00	10.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	3.34	2.16	1.95						0.44	7.74	12.23	4.49
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	3.12	1.88	1.96						0.44	7.57	15.24	7.67
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	2.10	1.07	1.03						0.44	6.64	17.00	10.36
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	2.38	0.92	1.42	2.09					0.44	8.20	10.98	2.78
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	3.33	1.70	2.07	2.66					0.44	8.94	13.99	5.05
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	1.69	-0.50	0.18	0.97					0.44	7.12	15.75	8.63
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	1.98	0.67	0.95	2.09					0.44	7.93	17.00	9.07
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-0.91	-2.83	-1.63	-0.38	-0.08	0.30			0.44	7.42	9.22	1.80
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	2.27	-0.30	0.21	2.01	1.88	2.27			0.44	9.73	12.23	2.50
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	0.85	-2.69	-1.47	-0.28	0.13	0.35			0.44	7.86	13.99	6.13
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	1.69	-1.61	-0.79	0.86	1.22	1.56			0.44	8.88	15.24	6.36

VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	3.37	0.27	0.89	2.55	2.94	3.11			0.44	10.56	16.21	5.65
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	3.29	0.37	0.89	2.66	3.14	2.87			0.44	10.56	17.00	6.44
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-2.45	-4.92	-4.63	-3.65	-2.63	-2.88	-2.82	-3.95	0.44	6.07	7.97	1.90
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	0.91	-1.49	-1.32	-0.26	0.50	0.54	0.58	-0.63	0.44	9.41	10.98	1.57
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-0.23	-2.45	-2.29	-1.27	-1.24	-0.56	-0.62	-1.78	0.44	8.23	12.74	4.51
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	0.66	-1.77	-1.47	-0.11	-0.13	0.33	0.29	-0.59	0.44	9.20	13.99	4.79
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	2.18	-0.80	-0.02	0.82	1.24	2.18	0.19	0.71	0.44	10.39	14.96	4.57
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	2.51	0.70	0.52	2.10	2.41	2.58	1.45	1.36	0.44	11.24	15.75	4.51
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	1.96	-0.53	-0.20	1.08	1.12	1.67	1.72	0.68	0.44	10.49	16.42	5.93
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	1.98	-0.56	-0.27	1.17	1.31	1.53	1.17	0.42	0.44	10.39	17.00	6.61
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	4.50	2.00							0.44	6.88	17.00	10.12
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	4.60	2.51	3.29						0.44	8.76	17.00	8.24
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	3.59	1.53	2.51	2.62					0.44	9.08	17.00	7.92
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	3.47	1.11	1.06	2.72	3.01	3.15			0.44	10.74	17.00	6.26
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	1.82	-0.08	1.65	1.03	1.70	1.82	1.66	0.71	0.44	10.80	17.00	6.20

5200 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 PSD (dBm/MHz)	Tx 2 PSD (dBm/MHZ)	Tx 3 PSD (dBm/MHz)	Tx 4 PSD (dBm/MHz)	Tx 5 PSD (dBm/MHz)	Tx 6 PSD (dBm/MHz)	Tx 7 PSD (dBm/MHz)	Tx 8 PSD (dBm/MHz)	DCCF (dB)	Total PSD (dBm/MHz)	FCC Limit (dBm/MHz)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	4.30								0.44	4.74	17.00	12.26
non HT20, 6 to 54 Mbps	2	9.01	4.70	2.77							0.44	7.29	13.99	6.70
non HT20, 6 to 54 Mbps	3	10.77	4.63	2.97	3.68						0.44	9.02	12.23	3.21
non HT20, 6 to 54 Mbps	4	12.02	4.21	2.34	3.36	4.15					0.44	10.04	10.98	0.94
non HT20, 6 to 54 Mbps	6	13.78	0.62	-0.42	0.34	0.52	0.62	0.06			0.44	8.53	9.22	0.69
non HT20, 6 to 54 Mbps	8	15.03	-1.85	-3.73	-3.45	-1.96	-1.58	-1.43	-2.56	-2.53	0.44	7.15	7.97	0.82
non HT20, 6 to 54 Mbps-BF	2	9.01	4.56	2.56							0.44	7.12	13.99	6.87
non HT20, 6 to 54 Mbps-BF	3	10.77	4.94	2.93	3.09						0.44	8.96	12.23	3.27
non HT20, 6 to 54 Mbps-BF	4	12.02	4.31	2.81	3.80	3.91					0.44	10.20	10.98	0.78
non HT20, 6 to 54 Mbps-BF	6	13.78	0.03	-1.58	0.01	0.22	0.32	0.59			0.44	8.21	9.22	1.01
non HT20, 6 to 54 Mbps-BF	8	15.03	-1.82	-3.80	-2.97	-1.91	-1.29	-1.85	-1.91	-2.60	0.44	7.26	7.97	0.71
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	4.05								0.44	4.49	17.00	12.51
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	9.01	4.45	2.23							0.44	6.93	13.99	7.06
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	3.92	2.17							0.44	6.58	17.00	10.42
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	10.77	4.65	1.85	3.15						0.44	8.58	12.23	3.65
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	7.76	4.16	1.74	3.14						0.44	8.34	15.24	6.90
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	4.22	1.92	3.42						0.44	8.50	17.00	8.50
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	12.02	4.04	2.37	3.72	3.75					0.44	9.97	10.98	1.01
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	9.01	4.50	2.15	3.55	3.64					0.44	10.00	13.99	3.99
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	7.25	4.50	2.07	3.11	3.56					0.44	9.86	15.75	5.89
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	4.36	1.98	3.23	3.60					0.44	9.84	17.00	7.16

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	13.78	-0.13	-1.93	-2.23	-0.38	-0.22	-0.88			0.44	7.34	9.22	1.88
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	10.77	2.97	1.18	0.74	2.24	2.83	1.77			0.44	10.25	12.23	1.98
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	9.01	4.64	2.01	2.17	3.69	3.87	3.05			0.44	11.56	13.99	2.43
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	7.76	4.83	1.87	1.94	3.27	3.80	3.20			0.44	11.50	15.24	3.74
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.79	4.85	2.12	2.09	3.30	3.74	3.02			0.44	11.52	16.21	4.69
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	4.64	2.06	2.10	3.59	3.51	3.01			0.44	11.47	17.00	5.53
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	15.03	-2.36	-3.82	-3.44	-3.05	-1.64	-1.66	-2.84	-2.99	0.44	6.81	7.97	1.16
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	12.02	0.78	-0.64	-0.47	0.27	1.41	1.60	1.00	0.22	0.44	10.06	10.98	0.92
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	10.26	3.03	1.17	1.52	2.20	2.87	3.59	2.30	2.26	0.44	11.90	12.74	0.84
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	9.01	4.28	1.85	2.47	3.33	3.57	4.21	3.52	3.04	0.44	12.82	13.99	1.17
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	8.04	3.98	2.19	2.99	3.32	4.17	4.30	3.69	3.22	0.44	13.00	14.96	1.96
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	7.25	4.44	1.98	2.67	3.25	4.05	4.28	4.00	2.88	0.44	12.99	15.75	2.76
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.58	4.39	1.81	2.46	3.11	3.79	4.28	3.45	2.90	0.44	12.82	16.42	3.60
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	4.09	1.86	2.44	3.21	3.82	4.14	3.56	2.99	0.44	12.80	17.00	4.20
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	4.26	2.27							0.44	6.83	13.99	7.16
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	3.85	2.17							0.44	6.54	17.00	10.46
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	4.55	2.90	3.22						0.44	8.83	12.23	3.40
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	4.36	2.60	3.05						0.44	8.61	15.24	6.63
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	4.13	2.40	2.97						0.44	8.44	17.00	8.56
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	4.14	2.11	3.06	3.50					0.44	9.73	10.98	1.25
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	4.38	2.21	3.23	3.38					0.44	9.83	13.99	4.16
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	4.41	2.13	2.78	3.63					0.44	9.78	15.75	5.97
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	4.25	2.15	3.02	3.48					0.44	9.75	17.00	7.25
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-0.20	-2.25	-1.27	-1.08	-0.32	-0.78			0.44	7.29	9.22	1.93
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	2.56	0.94	1.30	1.91	2.96	1.92			0.44	10.21	12.23	2.02
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	3.97	1.73	2.84	2.90	3.71	2.98			0.44	11.30	13.99	2.69
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	3.79	1.65	2.55	2.92	3.61	3.08			0.44	11.21	15.24	4.03
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	3.89	1.72	2.60	2.96	3.68	3.16			0.44	11.28	16.21	4.93

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	3.93	1.64	2.88	3.05	3.76	3.02			0.44	11.33	17.00	5.67
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-1.92	-3.97	-1.84	-2.91	-1.95	-1.73	-2.55	-2.91	0.44	7.06	7.97	0.91
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	1.18	-0.69	1.49	0.37	1.49	0.81	0.91	0.24	0.44	10.25	10.98	0.73
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	3.13	0.96	2.90	2.25	3.15	2.23	2.54	2.36	0.44	11.96	12.74	0.78
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	4.31	1.75	3.81	3.38	4.00	4.09	3.69	2.92	0.44	13.03	13.99	0.96
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	3.73	2.21	4.25	3.27	4.19	4.38	3.64	3.50	0.44	13.16	14.96	1.80
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	4.55	2.09	4.27	3.21	3.98	4.34	3.30	3.29	0.44	13.16	15.75	2.59
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	4.59	1.85	4.03	3.28	4.13	3.44	3.13	3.24	0.44	13.00	16.42	3.42
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	4.51	2.10	3.86	3.24	3.99	3.52	3.28	2.92	0.44	12.95	17.00	4.05
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	4.48	2.25							0.44	6.96	17.00	10.04
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	4.35	2.77	3.38						0.44	8.76	17.00	8.24
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	4.42	2.13	2.94	3.66					0.44	9.83	17.00	7.17
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	3.42	1.22	3.80	2.82	3.02	2.29			0.44	11.06	17.00	5.94
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	1.83	0.04	1.07	1.52	1.53	0.67	0.26	0.42	0.44	10.43	17.00	6.57

5240 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 PSD (dBm/MHz)	Tx 2 PSD (dBm/MHZ)	Tx 3 PSD (dBm/MHz)	Tx 4 PSD (dBm/MHz)	Tx 5 PSD (dBm/MHz)	Tx 6 PSD (dBm/MHz)	Tx 7 PSD (dBm/MHz)	Tx 8 PSD (dBm/MHz)	DCCF (dB)	Total PSD (dBm/MHz)	FCC Limit (dBm/MHz)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	4.19								0.44	4.63	17.00	12.37
non HT20, 6 to 54 Mbps	2	9.01	4.43	2.50							0.44	7.02	13.99	6.97
non HT20, 6 to 54 Mbps	3	10.77	4.42	2.79	3.35						0.44	8.78	12.23	3.45
non HT20, 6 to 54 Mbps	4	12.02	3.99	2.96	4.03	3.75					0.44	10.16	10.98	0.82
non HT20, 6 to 54 Mbps	6	13.78	0.25	-1.23	1.24	0.10	0.34	-1.79			0.44	8.16	9.22	1.06
non HT20, 6 to 54 Mbps	8	15.03	-1.91	-3.53	-2.65	-2.90	-1.86	-1.88	-1.91	-3.31	0.44	7.02	7.97	0.95
non HT20, 6 to 54 Mbps-BF	2	9.01	4.41	2.59							0.44	7.04	13.99	6.95
non HT20, 6 to 54 Mbps-BF	3	10.77	4.67	3.06	3.94						0.44	9.15	12.23	3.08
non HT20, 6 to 54 Mbps-BF	4	12.02	4.00	2.88	3.93	3.66					0.44	10.10	10.98	0.88
non HT20, 6 to 54 Mbps-BF	6	13.78	0.35	-1.39	-0.56	0.18	0.17	0.32			0.44	8.11	9.22	1.11
non HT20, 6 to 54 Mbps-BF	8	15.03	-1.81	-3.26	-2.80	-3.10	-1.47	-2.54	-1.94	-3.17	0.44	7.01	7.97	0.96
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	3.89								0.44	4.33	17.00	12.67
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	9.01	4.13	2.06							0.44	6.67	13.99	7.32
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	3.88	2.09							0.44	6.53	17.00	10.47
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	10.77	3.85	2.82	3.50						0.44	8.62	12.23	3.61
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	7.76	3.94	2.33	3.26						0.44	8.44	15.24	6.80
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	3.86	2.13	3.10						0.44	8.30	17.00	8.70
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	12.02	3.95	2.64	3.56	3.41					0.44	9.88	10.98	1.10
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	9.01	4.42	2.20	3.54	3.39					0.44	9.92	13.99	4.07
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	7.25	3.93	2.51	3.14	3.50					0.44	9.76	15.75	5.99
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	4.33	2.35	3.22	3.54					0.44	9.88	17.00	7.12

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	13.78	0.31	-2.64	0.50	-1.07	-0.12	-2.09			0.44	7.53	9.22	1.69
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	10.77	2.81	-0.07	3.36	1.72	2.84	0.99			0.44	10.32	12.23	1.91
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	9.01	4.36	0.98	4.41	3.19	3.87	1.99			0.44	11.53	13.99	2.46
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	7.76	4.45	0.86	4.42	3.21	3.83	2.16			0.44	11.55	15.24	3.69
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.79	4.81	0.78	4.23	3.18	3.72	2.07			0.44	11.55	16.21	4.66
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	4.49	0.90	4.36	3.15	3.87	1.93			0.44	11.52	17.00	5.48
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	15.03	-2.26	-3.71	-1.51	-2.32	-1.91	-2.27	-2.31	-3.84	0.44	7.02	7.97	0.95
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	12.02	-0.28	-0.75	1.81	1.03	1.53	1.10	0.71	0.09	0.44	10.20	10.98	0.78
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	10.26	2.89	1.72	3.45	2.64	3.15	2.24	2.12	1.71	0.44	12.13	12.74	0.74
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	9.01	3.91	2.67	4.15	3.92	3.82	3.08	4.11	2.74	0.44	13.06	13.99	0.93
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	8.04	3.58	2.35	4.61	3.95	4.20	3.72	4.11	2.43	0.44	13.15	14.96	1.81
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	7.25	3.93	1.86	4.65	3.91	4.25	3.68	3.83	2.67	0.44	13.15	15.75	2.60
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.58	4.40	2.57	4.46	4.07	3.88	3.23	4.18	2.76	0.44	13.22	16.42	3.20
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	4.34	2.56	4.36	3.93	3.79	3.13	3.97	2.91	0.44	13.14	17.00	3.86
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	4.17	2.15							0.44	6.73	13.99	7.26
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	3.86	2.17							0.44	6.55	17.00	10.45
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	4.10	2.84	3.19						0.44	8.62	12.23	3.61
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	3.92	2.53	2.99						0.44	8.40	15.24	6.84
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	3.83	2.44	3.17						0.44	8.39	17.00	8.61
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	3.73	2.20	4.19	3.44					0.44	9.91	10.98	1.07
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	4.36	2.06	3.79	3.16					0.44	9.88	13.99	4.11
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	3.93	2.14	3.72	3.32					0.44	9.79	15.75	5.96
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	4.25	1.92	3.53	3.28					0.44	9.78	17.00	7.22
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-0.39	-1.76	0.03	0.03	-0.23	-2.15			0.44	7.56	9.22	1.66
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	2.78	0.98	2.78	2.76	2.54	1.12			0.44	10.45	12.23	1.78
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	3.59	1.87	3.91	4.00	3.62	2.04			0.44	11.48	13.99	2.51
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	3.78	1.94	3.82	4.00	3.75	2.00			0.44	11.52	15.24	3.72
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	3.64	1.91	3.77	4.16	3.90	1.97			0.44	11.54	16.21	4.67

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	3.47	1.93	3.68	4.30	3.91	1.95			0.44	11.52	17.00	5.48
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-2.35	-3.32	-3.15	-3.30	-1.79	-2.19	-2.47	-3.52	0.44	6.75	7.97	1.22
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-0.35	-0.03	0.11	-0.25	1.67	1.01	0.56	0.32	0.44	9.90	10.98	1.08
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	2.99	2.08	1.96	1.55	3.09	3.21	3.28	1.61	0.44	12.00	12.74	0.74
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	3.91	2.64	3.28	2.77	4.12	3.54	3.93	2.80	0.44	12.88	13.99	1.11
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	3.59	2.62	2.78	3.09	4.48	3.73	3.73	2.69	0.44	12.85	14.96	2.11
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	4.44	2.49	2.98	2.76	4.19	3.80	3.79	2.52	0.44	12.90	15.75	2.85
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	4.10	2.59	3.13	2.98	3.97	3.81	4.18	2.61	0.44	12.94	16.42	3.48
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	4.28	2.62	3.22	2.96	3.90	3.74	3.94	2.69	0.44	12.93	17.00	4.07
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	4.17	2.22							0.44	6.75	17.00	10.25
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	3.89	2.80	3.64						0.44	8.68	17.00	8.32
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	4.36	2.41	3.72	3.55					0.44	10.03	17.00	6.97
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	2.65	1.18	3.42	2.93	2.66	2.83			0.44	10.88	17.00	6.12
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	1.39	0.07	1.80	1.19	1.67	1.17	0.56	-0.14	0.44	10.49	17.00	6.51

5190 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 PSD (dBm/MHz)	Tx 2 PSD (dBm/MHZ)	Tx 3 PSD (dBm/MHz)	Tx 4 PSD (dBm/MHz)	Tx 5 PSD (dBm/MHz)	Tx 6 PSD (dBm/MHz)	Tx 7 PSD (dBm/MHz)	Tx 8 PSD (dBm/MHz)	DCCF (dB)	Total PSD (dBm/MHz)	FCC Limit (dBm/MHz)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	0.14								0.36	0.50	17.00	16.50
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	9.01	-0.28	-3.37							0.36	1.81	13.99	12.18
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-0.75	-3.55							0.36	1.44	17.00	15.56
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	10.77	-1.02	-4.01	-2.23						0.36	2.88	12.23	9.35
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	7.76	-1.49	-4.45	-2.17						0.36	2.60	15.24	12.64
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-2.77	-5.59	-3.49						0.36	1.34	17.00	15.66
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	12.02	-2.30	-4.40	-2.64	-2.67					0.36	3.45	10.98	7.53
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	9.01	-2.12	-4.68	-2.59	-2.84					0.36	3.42	13.99	10.57
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	7.25	-3.53	-6.23	-4.13	-4.21					0.36	1.97	15.75	13.78
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-3.91	-6.17	-4.52	-4.25					0.36	1.75	17.00	15.25
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	13.78	-2.48	-5.03	-3.47	-2.82	-2.56	-4.19			0.36	4.81	9.22	4.41
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	10.77	-2.42	-5.03	-3.53	-2.76	-2.58	-4.00			0.36	4.85	12.23	7.38
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	9.01	-5.04	-7.35	-5.85	-5.40	-4.92	-6.54			0.36	2.37	13.99	11.62
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	7.76	-3.99	-6.22	-4.83	-4.24	-3.68	-5.55			0.36	3.48	15.24	11.76
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.79	-3.75	-6.12	-4.67	-4.10	-3.64	-5.16			0.36	3.65	16.21	12.56
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-3.90	-6.13	-4.75	-4.19	-3.69	-5.60			0.36	3.52	17.00	13.48
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	15.03	-3.17	-5.83	-3.66	-3.93	-3.08	-3.60	-3.54	-4.68	0.36	5.53	7.97	2.44
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	12.02	-3.09	-6.13	-3.83	-4.02	-3.19	-3.55	-3.77	-4.81	0.36	5.43	10.98	5.55
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	10.26	-4.72	-6.98	-4.99	-5.42	-4.60	-4.51	-5.08	-5.88	0.36	4.18	12.74	8.56
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	9.01	-4.79	-7.38	-5.16	-5.46	-4.66	-4.66	-5.13	-6.30	0.36	4.03	13.99	9.96
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	8.04	-4.18	-6.65	-5.06	-5.12	-4.00	-4.36	-4.80	-5.81	0.36	4.47	14.96	10.49
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	7.25	-4.51	-6.69	-5.04	-5.46	-4.08	-4.67	-5.05	-5.93	0.36	4.28	15.75	11.47

VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.58	-4.34	-7.29	-4.39	-4.92	-4.00	-3.79	-4.31	-5.69	0.36	4.67	16.42	11.75
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-4.67	-7.21	-4.00	-4.09	-4.36	-3.00	-3.99	-6.18	0.36	4.87	17.00	12.13
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-2.38	-5.62							0.36	-0.33	13.99	14.32
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-1.24	-4.59							0.36	0.77	17.00	16.23
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-3.18	-5.85	-4.20						0.36	0.86	12.23	11.37
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-2.56	-5.28	-2.78						0.36	1.75	15.24	13.49
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-2.88	-5.48	-3.20						0.36	1.42	17.00	15.58
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-4.04	-6.77	-4.52	-5.11					0.36	1.39	10.98	9.59
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-3.36	-5.60	-3.39	-4.00					0.36	2.38	13.99	11.61
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-3.71	-6.20	-4.02	-4.24					0.36	1.94	15.75	13.81
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-2.68	-5.34	-2.94	-3.01					0.36	3.01	17.00	13.99
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-6.91	-9.00	-6.66	-7.95	-7.16	-8.67			0.36	0.50	9.22	8.72
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-5.74	-8.13	-5.48	-6.70	-5.96	-7.54			0.36	1.65	12.23	10.58
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-5.07	-7.32	-4.69	-5.64	-4.97	-6.51			0.36	2.54	13.99	11.45
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-4.12	-6.29	-3.51	-4.43	-3.62	-5.59			0.36	3.66	15.24	11.58
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-2.74	-4.90	-2.18	-2.84	-2.55	-4.04			0.36	5.03	16.21	11.18
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-2.90	-5.13	-2.49	-2.98	-2.74	-4.39			0.36	4.81	17.00	12.19
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-8.15	-10.7	-9.68	-10.3	-8.87	-8.90	-9.36	-9.92	0.36	-0.02	7.97	7.99
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-6.57	-9.10	-7.53	-7.84	-6.81	-6.78	-7.36	-7.49	0.36	2.02	10.98	8.96
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-5.56	-8.48	-6.25	-6.85	-5.62	-6.12	-6.38	-7.16	0.36	2.92	12.74	9.82
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-5.69	-8.44	-6.05	-6.77	-5.81	-6.47	-6.59	-6.99	0.36	2.86	13.99	11.13
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-4.37	-7.03	-4.88	-4.99	-4.14	-4.25	-5.18	-5.76	0.36	4.40	14.96	10.56
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-4.57	-6.86	-4.91	-5.44	-4.34	-4.66	-5.02	-5.75	0.36	4.26	15.75	11.49
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-3.95	-6.76	-4.48	-5.00	-3.85	-4.79	-5.08	-5.52	0.36	4.55	16.42	11.87
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-3.59	-6.26	-2.71	-2.92	-3.23	-3.10	-3.28	-4.91	0.36	5.77	17.00	11.23
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	-0.24	-3.40							0.36	1.83	17.00	15.17
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	-0.32	-3.50	-0.89						0.36	3.77	17.00	13.23
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	-0.85	-3.61	-1.48	-1.40					0.36	4.66	17.00	12.34

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	-2.49	-4.71	-2.22	-2.97	-2.42	-4.14			0.36	5.08	17.00	11.92
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	-3.09	-5.91	-3.38	-4.09	-3.01	-3.23	-3.94	-4.66	0.36	5.57	17.00	11.43

5230 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 PSD (dBm/MHz)	Tx 2 PSD (dBm/MHZ)	Tx 3 PSD (dBm/MHz)	Tx 4 PSD (dBm/MHz)	Tx 5 PSD (dBm/MHz)	Tx 6 PSD (dBm/MHz)	Tx 7 PSD (dBm/MHz)	Tx 8 PSD (dBm/MHz)	DCCF (dB)	Total PSD (dBm/MHz)	FCC Limit (dBm/MHz)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	0.74								0.36	1.10	17.00	15.90
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	9.01	0.92	-1.32							0.36	3.31	13.99	10.68
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	0.71	-1.50							0.36	3.11	17.00	13.89
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	10.77	0.90	-0.78	-0.31						0.36	5.13	12.23	7.10
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	7.76	0.80	-1.38	-0.47						0.36	4.87	15.24	10.37
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	0.32	-1.64	-0.44						0.36	4.62	17.00	12.38
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	12.02	1.21	-0.48	0.85	0.00					0.36	6.83	10.98	4.15
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	9.01	0.89	-0.71	0.51	0.11					0.36	6.62	13.99	7.37
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	7.25	0.50	-1.36	-0.15	-0.12					0.36	6.15	15.75	9.60
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	0.39	-1.49	-0.28	-0.31					0.36	6.01	17.00	10.99
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	13.78	-0.68	-1.70	-2.14	-1.40	-0.66	-1.33			0.36	6.86	9.22	2.36
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	10.77	0.30	-0.94	-1.21	-0.23	0.42	-0.74			0.36	7.78	12.23	4.45
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	9.01	0.01	-1.03	-0.94	-0.54	0.07	-0.89			0.36	7.61	13.99	6.38
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	7.76	-0.06	-1.02	-1.19	-0.55	0.17	-0.83			0.36	7.59	15.24	7.65
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.79	0.51	-0.93	-1.18	-0.09	0.38	-0.80			0.36	7.84	16.21	8.37
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	0.06	-1.12	-1.14	-0.37	0.01	-0.80			0.36	7.61	17.00	9.39
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	15.03	-1.82	-3.55	-1.91	-2.72	-2.14	-2.24	-2.67	-3.13	0.36	6.90	7.97	1.07
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	12.02	0.86	-1.13	0.45	0.02	0.86	0.61	0.08	-0.99	0.36	9.54	10.98	1.44
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	10.26	0.56	-1.23	0.25	0.07	0.42	0.15	0.21	-1.20	0.36	9.34	12.74	3.40
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	9.01	0.60	-1.15	0.07	-0.06	0.52	0.18	0.08	-1.31	0.36	9.31	13.99	4.68
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	8.04	0.97	-0.90	0.74	0.02	1.01	0.64	0.21	-0.96	0.36	9.67	14.96	5.29
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	7.25	0.56	-1.10	0.01	-0.27	0.54	0.17	0.15	-1.00	0.36	9.31	15.75	6.44

VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.58	1.25	-0.79	0.58	0.33	0.76	0.51	0.36	-0.71	0.36	9.73	16.42	6.69
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	0.75	-1.14	1.13	0.92	0.66	0.59	0.84	-1.10	0.36	9.80	17.00	7.20
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	1.04	-1.22							0.36	3.43	13.99	10.56
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	0.56	-1.47							0.36	3.03	17.00	13.97
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	0.88	-0.98	0.29						0.36	5.26	12.23	6.97
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	0.51	-1.14	0.21						0.36	5.05	15.24	10.19
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	0.30	-1.56	-0.01						0.36	4.78	17.00	12.22
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	1.11	-1.20	0.43	0.08					0.36	6.56	10.98	4.42
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	0.94	-1.35	0.43	0.08					0.36	6.48	13.99	7.51
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	0.76	-1.66	-0.03	0.03					0.36	6.24	15.75	9.51
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	0.60	-1.75	0.04	-0.25					0.36	6.12	17.00	10.88
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-1.44	-4.37	-4.07	-2.50	-2.30	-3.65			0.36	5.21	9.22	4.01
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	1.37	-1.84	-1.26	0.52	0.14	-0.66			0.36	7.99	12.23	4.24
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	1.08	-1.90	-1.41	0.28	0.08	-1.04			0.36	7.78	13.99	6.21
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	1.00	-1.71	-1.30	0.29	0.04	-0.99			0.36	7.80	15.24	7.44
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	1.40	-1.62	-1.11	0.41	0.39	-0.77			0.36	8.05	16.21	8.16
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	1.03	-1.65	-1.41	0.29	0.04	-0.84			0.36	7.82	17.00	9.18
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-4.93	-6.67	-5.79	-6.10	-5.47	-5.05	-5.81	-6.96	0.36	3.59	7.97	4.38
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-1.85	-3.82	-2.69	-2.76	-2.19	-1.95	-2.36	-3.33	0.36	6.82	10.98	4.16
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-0.53	-2.05	-0.92	-1.35	-0.56	-0.61	-0.83	-2.04	0.36	8.32	12.74	4.42
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	0.58	-1.51	-0.03	-0.22	0.31	0.22	0.06	-1.23	0.36	9.22	13.99	4.77
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	1.19	-0.83	0.38	0.08	0.88	1.07	0.24	-0.76	0.36	9.73	14.96	5.23
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	0.90	-1.17	0.34	-0.05	0.45	0.56	-0.13	-1.15	0.36	9.42	15.75	6.33
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	1.22	-0.64	0.82	0.63	0.59	1.46	0.47	-0.84	0.36	9.92	16.42	6.50
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	0.72	-1.23	1.45	0.96	0.48	1.70	1.16	-1.32	0.36	10.01	17.00	6.99
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	0.75	-1.27							0.36	3.23	17.00	13.77
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	0.95	-0.76	-0.12						0.36	5.21	17.00	11.79
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	1.04	-0.81	0.62	-0.14					0.36	6.62	17.00	10.38

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	1.43	-0.74	1.05	-0.34	0.65	0.81			0.36	8.68	17.00	8.32
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	1.04	-0.81	0.27	-0.04	1.00	0.74	0.27	-0.80	0.36	9.65	17.00	7.35

5210 MHz:

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 PSD (dBm/MHz)	Tx 2 PSD (dBm/MHZ)	Tx 3 PSD (dBm/MHz)	Tx 4 PSD (dBm/MHz)	Tx 5 PSD (dBm/MHz)	Tx 6 PSD (dBm/MHz)	Tx 7 PSD (dBm/MHz)	Tx 8 PSD (dBm/MHz)	DCCF (dB)	Total PSD (dBm/MHz)	FCC Limit (dBm/MHz)	Margin (dB)
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-5.19								0.44	-4.75	17.00	21.75
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	2	9.01	-6.16	-8.28							0.44	-3.64	13.99	17.63
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-6.33	-8.07							0.44	-3.66	17.00	20.66
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	3	10.77	-7.27	-9.04	-7.86						0.44	-2.78	12.23	15.01
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	3	7.76	-7.18	-8.70	-7.40						0.44	-2.50	15.24	17.74
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-7.95	-9.76	-8.19						0.44	-3.35	17.00	20.35
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	4	12.02	-8.16	-9.65	-9.30	-9.50					0.44	-2.65	10.98	13.63
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	4	9.01	-8.41	-9.76	-8.94	-8.95					0.44	-2.53	13.99	16.52
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	4	7.25	-8.70	-9.63	-9.61	-8.91					0.44	-2.73	15.75	18.48
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-8.83	-10.40	-9.96	-9.93					0.44	-3.28	17.00	20.28
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	6	13.78	-10.97	-11.75	-10.28	-12.63	-11.02	-10.81			0.44	-2.96	9.22	12.18
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	6	10.77	-10.34	-11.64	-9.83	-12.21	-11.02	-10.56			0.44	-2.64	12.23	14.87
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	6	9.01	-11.06	-11.77	-10.10	-12.25	-10.97	-11.12			0.44	-2.94	13.99	16.93
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	6	7.76	-11.03	-12.23	-10.79	-13.01	-11.57	-11.21			0.44	-3.35	15.24	18.59
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	6	6.79	-10.93	-12.21	-10.74	-13.03	-11.49	-11.34			0.44	-3.33	16.21	19.54
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-10.97	-11.90	-10.61	-12.75	-11.20	-10.91			0.44	-3.11	17.00	20.11
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	8	15.03	-10.49	-11.79	-11.39	-11.68	-10.50	-10.92	-10.89	-12.31	0.44	-1.73	7.97	9.70
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	8	12.02	-10.45	-11.25	-10.93	-11.33	-10.58	-10.96	-10.81	-12.27	0.44	-1.57	10.98	12.55
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	8	10.26	-11.82	-12.87	-11.88	-12.00	-11.88	-12.21	-11.81	-13.67	0.44	-2.75	12.74	15.49
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	8	9.01	-12.33	-12.98	-11.81	-11.43	-12.11	-11.23	-11.69	-13.69	0.44	-2.62	13.99	16.61
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	8	8.04	-12.36	-12.96	-11.29	-11.77	-12.31	-11.35	-11.48	-13.44	0.44	-2.59	14.96	17.55
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	8	7.25	-12.40	-13.19	-11.23	-12.84	-12.40	-12.81	-11.02	-13.80	0.44	-2.90	15.75	18.65

VHT/HE80, M0.7 to M9.7, M0.7 to M11.7	8	6.58	-12.17	-12.89	-11.81	-12.35	-12.66	-12.83	-12.05	-13.51	0.44	-3.03	16.42	19.45
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-12.40	-13.35	-13.26	-13.22	-12.28	-12.84	-12.92	-13.96	0.44	-3.53	17.00	20.53
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-9.59	-10.93							0.44	-6.76	13.99	20.75
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-6.50	-8.25							0.44	-3.84	17.00	20.84
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-10.74	-11.67	-12.19						0.44	-6.28	12.23	18.51
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-9.35	-10.25	-10.28						0.44	-4.73	15.24	19.97
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-7.85	-9.59	-8.91						0.44	-3.51	17.00	20.51
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-12.99	-12.91	-13.62	-14.23					0.44	-6.94	10.98	17.92
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-10.82	-11.12	-11.04	-11.56					0.44	-4.67	13.99	18.66
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-11.13	-11.03	-11.68	-10.84					0.44	-4.70	15.75	20.45
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-8.91	-10.26	-9.74	-9.62					0.44	-3.14	17.00	20.14
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-14.83	-12.42	-12.39	-12.39	-14.55	-15.81			0.44	-5.30	9.22	14.52
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-13.24	-13.11	-14.43	-14.26	-12.80	-13.79			0.44	-5.34	12.23	17.57
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-13.26	-13.06	-14.49	-14.40	-13.23	-14.42			0.44	-5.54	13.99	19.53
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-12.82	-12.91	-13.58	-13.51	-12.53	-13.73			0.44	-4.94	15.24	20.18
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-11.79	-11.85	-12.54	-12.40	-11.64	-12.34			0.44	-3.86	16.21	20.07
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-11.64	-11.84	-12.46	-12.36	-11.45	-12.34			0.44	-3.78	17.00	20.78
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-13.39	-13.79	-13.50	-14.84	-12.91	-12.99	-12.63	-13.81	0.44	-3.96	7.97	11.93
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-14.22	-11.15	-11.24	-12.54	-13.59	-13.60	-14.16	-11.65	0.44	-3.13	10.98	14.11
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-15.00	-11.29	-11.47	-12.60	-13.82	-13.44	-14.34	-12.57	0.44	-3.42	12.74	16.16
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-14.90	-11.56	-11.95	-12.45	-14.43	-12.77	-13.50	-12.23	0.44	-3.36	13.99	17.35
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-12.45	-12.06	-11.37	-11.60	-12.29	-11.26	-11.32	-13.35	0.44	-2.44	14.96	17.40
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-12.23	-12.11	-11.09	-13.06	-12.12	-12.59	-11.13	-13.72	0.44	-2.71	15.75	18.46
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-12.32	-11.86	-11.75	-12.57	-12.53	-11.80	-12.03	-13.44	0.44	-2.79	16.42	19.21
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-12.54	-13.03	-13.20	-13.24	-12.41	-12.59	-13.08	-13.97	0.44	-3.51	17.00	20.51
VHT/HE80, M0 to M9, M0 to M11-STBC	2	6.00	-6.12	-8.23							0.44	-3.60	17.00	20.60
VHT/HE80, M0 to M9, M0 to M11-STBC	3	6.00	-6.91	-8.54	-8.40						0.44	-2.67	17.00	19.67
VHT/HE80, M0 to M9, M0 to M11-STBC	4	6.00	-8.33	-9.05	-8.91	-9.54					0.44	-2.48	17.00	19.48

VHT/HE80, M0 to M9, M0 to M11-STBC	6	6.00	-10.10	-10.44	-9.61	-9.99	-10.21	-11.16			0.44	-2.00	17.00	19.00
VHT/HE80, M0 to M9, M0 to M11-STBC	8	6.00	-11.51	-11.29	-11.77	-11.11	-10.33	-10.83	-11.30	-12.21	0.44	-1.79	17.00	18.79

Please refer to the following plots for the worst case configuration

Ant-a



Ant-b



Ant-c


Spectrum
Ref Level 12.60 dBm Offset 12.60 dB RBW (CISPR) 1 MHz
Att 10 dB SWT 1 ms VBW 3 MHz Mode Sweep
Count 100/100
1Rm AvgLin
M1[1] -2.24 dBm
5.1824310 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 5.18 GHz
691 pts
Span 30.0 MHz
Measuring...
02/15/2019
05:38:05 AM

Ant-d


Spectrum
Ref Level 12.60 dBm Offset 12.60 dB RBW (CISPR) 1 MHz
Att 10 dB SWT 1 ms VBW 3 MHz Mode Sweep
Count 100/100
1Rm AvgLin
M1[1] -2.12 dBm
5.1725760 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 5.18 GHz
691 pts
Span 30.0 MHz
Measuring...
02/15/2019
05:38:30 AM

Ant-e


Spectrum
Ref Level 12.60 dBm Offset 12.60 dB RBW (CISPR) 1 MHz
Att 10 dB SWT 1 ms VBW 3 MHz Mode Sweep
Count 100/100
1Rm AvgLin
M1[1] -2.40 dBm
5.1873810 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 5.18 GHz
691 pts
Span 30.0 MHz
Measuring...
02/15/2019
05:38:49 AM

Ant-f


Spectrum
Ref Level 12.60 dBm Offset 12.60 dB RBW (CISPR) 1 MHz
Att 10 dB SWT 1 ms VBW 3 MHz Mode Sweep
Count 100/100
1Rm AvgLin
M1[1] -2.18 dBm
5.1734440 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 5.18 GHz
691 pts
Span 30.0 MHz
Measuring...
02/15/2019
05:39:03 AM

Ant-g


Spectrum
Ref Level 12.60 dBm Offset 12.60 dB RBW (CISPR) 1 MHz
Att 10 dB SWT 1 ms VBW 3 MHz Mode Sweep
Count 100/100
1Rm AvgLin
M1[1] -1.95 dBm
5.1859910 GHz
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 5.18 GHz
691 pts
Span 30.0 MHz
Measuring...
02/15/2019
05:39:18 AM

Ant-h


Spectrum
Ref Level 12.60 dBm Offset 12.60 dB RBW (CISPR) 1 MHz
Att 10 dB SWT 1 ms VBW 3 MHz Mode Sweep
Count 100/100
1Rm AvgLin
M1[1] -2.39 dBm
5.1857310 GHz
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 5.18 GHz
691 pts
Span 30.0 MHz
Measuring...
02/15/2019
05:39:29 AM

Test results for Out of Band Emissions

5180 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-69.17								-63.17	-21.25	41.92
non HT20, 6 to 54 Mbps	2	6.00	-69.18	-68.45							-59.79	-21.25	38.54
non HT20, 6 to 54 Mbps	3	6.00	-69.05	-69.53	-68.98						-58.40	-21.25	37.15
non HT20, 6 to 54 Mbps	4	6.00	-68.21	-69.27	-69.36	-69.14					-56.95	-21.25	35.70
non HT20, 6 to 54 Mbps	6	9.00	-68.89	-70.08	-69.98	-69.44	-69.06	-69.64			-52.71	-21.25	31.46
non HT20, 6 to 54 Mbps	8	9.00	-68.47	-69.70	-68.68	-68.78	-68.91	-69.66	-69.52	-69.10	-51.05	-21.25	29.80
non HT20, 6 to 54 Mbps-BF	2	9.01	-68.45	-69.12							-56.75	-21.25	35.50
non HT20, 6 to 54 Mbps-BF	3	10.77	-69.59	-69.22	-69.40						-53.86	-21.25	32.61
non HT20, 6 to 54 Mbps-BF	4	12.02	-69.45	-69.99	-69.07	-69.18					-51.36	-21.25	30.11
non HT20, 6 to 54 Mbps-BF	6	13.78	-69.63	-69.53	-68.91	-68.63	-69.40	-70.36			-47.81	-21.25	26.56
non HT20, 6 to 54 Mbps-BF	8	15.03	-69.57	-69.38	-68.85	-69.18	-69.33	-69.64	-69.31	-68.72	-45.18	-21.25	23.93
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-69.16								-63.16	-21.25	41.91
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-68.94	-68.96							-59.94	-21.25	38.69
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-69.67	-69.46							-60.55	-21.25	39.30
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-68.62	-69.63	-68.64						-58.17	-21.25	36.92
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-68.83	-69.32	-69.16						-58.33	-21.25	37.08
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-68.96	-69.31	-68.26						-58.05	-21.25	36.80
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-69.60	-69.43	-69.00	-69.20					-57.28	-21.25	36.03
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-68.83	-70.15	-68.89	-69.22					-57.22	-21.25	35.97
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-69.44	-68.92	-68.54	-68.99					-56.94	-21.25	35.69

HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-69.05	-69.59	-69.14	-68.71					-57.09	-21.25	35.84
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-68.97	-69.49	-69.40	-69.05	-69.31	-68.74			-52.37	-21.25	31.12
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-69.00	-69.50	-69.02	-69.29	-68.41	-69.41			-52.92	-21.25	31.67
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	-68.89	-68.53	-68.69	-69.70	-69.49	-69.06			-53.75	-21.25	32.50
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-69.30	-69.01	-69.51	-69.51	-68.39	-68.99			-54.44	-21.25	33.19
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-68.29	-68.39	-68.43	-68.79	-69.17	-69.21			-54.52	-21.25	33.27
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-69.16	-68.30	-68.81	-69.52	-68.87	-68.14			-54.99	-21.25	33.74
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-69.37	-69.15	-69.18	-69.41	-69.43	-69.07	-68.66	-67.76	-50.94	-21.25	29.69
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-68.98	-69.12	-69.59	-68.52	-68.99	-69.71	-69.57	-69.12	-51.15	-21.25	29.90
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-69.27	-69.68	-68.93	-69.90	-68.58	-68.42	-69.60	-69.49	-52.04	-21.25	30.79
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-68.66	-68.80	-69.51	-69.08	-69.57	-67.86	-69.26	-69.26	-52.43	-21.25	31.18
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-69.23	-68.92	-69.28	-69.28	-69.17	-68.45	-69.38	-68.25	-52.93	-21.25	31.68
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-69.45	-69.17	-69.35	-69.32	-68.36	-68.91	-69.06	-68.70	-53.38	-21.25	32.13
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-68.77	-68.72	-68.95	-69.49	-69.26	-69.13	-68.93	-69.37	-53.75	-21.25	32.50
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-68.97	-69.47	-69.74	-69.44	-68.77	-68.29	-69.22	-69.45	-54.12	-21.25	32.87
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	-69.06	-69.80							-57.40	-21.25	36.15
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-68.49	-69.12							-59.78	-21.25	38.53
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-69.33	-69.57	-69.04						-53.77	-21.25	32.52
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-69.08	-69.28	-69.48						-56.75	-21.25	35.50
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-69.32	-69.82	-69.26						-58.69	-21.25	37.44
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-68.90	-69.33	-68.43	-68.75					-50.80	-21.25	29.55
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-69.52	-69.06	-68.77	-69.11					-54.08	-21.25	32.83
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-69.24	-69.35	-69.13	-68.64					-55.81	-21.25	34.56
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-68.91	-68.64	-68.83	-69.41					-56.92	-21.25	35.67
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-69.19	-69.25	-69.57	-69.63	-69.02	-69.14			-47.73	-21.25	26.48
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-68.32	-68.81	-69.16	-69.48	-69.51	-69.41			-50.54	-21.25	29.29
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-69.71	-68.75	-69.17	-68.61	-68.18	-67.87			-51.88	-21.25	30.63
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-69.45	-69.06	-69.27	-68.47	-67.38	-69.60			-53.26	-21.25	32.01

VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-69.72	-69.28	-69.07	-69.42	-69.62	-68.57			-54.69	-21.25	33.44
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-68.85	-68.14	-69.82	-67.71	-68.80	-69.51			-54.96	-21.25	33.71
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-69.43	-68.84	-68.93	-69.15	-69.65	-69.46	-68.25	-69.09	-45.02	-21.25	23.77
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-68.83	-69.22	-69.16	-68.22	-69.72	-68.42	-68.74	-69.14	-47.86	-21.25	26.61
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-69.44	-68.75	-68.70	-69.38	-69.62	-69.14	-69.38	-69.06	-49.88	-21.25	28.63
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-68.28	-69.59	-68.81	-69.40	-68.85	-68.56	-69.46	-69.26	-50.96	-21.25	29.71
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-69.08	-68.67	-68.85	-68.09	-69.26	-69.12	-68.89	-69.60	-51.86	-21.25	30.61
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-69.00	-69.47	-68.46	-69.11	-68.53	-69.28	-68.81	-69.56	-52.73	-21.25	31.48
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-69.19	-68.67	-69.45	-69.20	-68.61	-69.04	-69.11	-68.76	-53.38	-21.25	32.13
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-69.45	-67.66	-68.60	-68.37	-69.74	-68.99	-69.56	-69.07	-53.85	-21.25	32.60
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-68.90	-68.52							-59.70	-21.25	38.45
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-69.14	-69.13	-68.98						-58.31	-21.25	37.06
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-69.17	-69.68	-69.12	-68.79					-57.16	-21.25	35.91
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-69.30	-68.97	-69.74	-69.46	-69.35	-69.70			-55.63	-21.25	34.38
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-68.96	-68.76	-69.07	-69.45	-68.77	-68.87	-69.41	-67.84	-53.83	-21.25	32.58

5180 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-77.51								-71.51	-41.25	30.26
non HT20, 6 to 54 Mbps	2	6.00	-77.54	-77.70							-68.61	-41.25	27.36
non HT20, 6 to 54 Mbps	3	6.00	-77.66	-77.77	-77.49						-66.87	-41.25	25.62
non HT20, 6 to 54 Mbps	4	6.00	-77.96	-77.34	-76.93	-77.25					-65.34	-41.25	24.09
non HT20, 6 to 54 Mbps	6	9.00	-77.71	-77.28	-77.07	-77.01	-76.65	-76.91			-60.31	-41.25	19.06
non HT20, 6 to 54 Mbps	8	9.00	-77.05	-77.67	-77.09	-77.40	-77.08	-77.10	-77.39	-77.42	-59.24	-41.25	17.99
non HT20, 6 to 54 Mbps-BF	2	9.01	-77.46	-77.20							-65.31	-41.25	24.06
non HT20, 6 to 54 Mbps-BF	3	10.77	-77.56	-77.56	-77.30						-61.93	-41.25	20.68
non HT20, 6 to 54 Mbps-BF	4	12.02	-77.60	-77.03	-77.15	-76.94					-59.13	-41.25	17.88
non HT20, 6 to 54 Mbps-BF	6	13.78	-77.80	-77.33	-77.48	-77.67	-77.52	-77.02			-55.90	-41.25	14.65
non HT20, 6 to 54 Mbps-BF	8	15.03	-77.96	-77.44	-77.64	-77.23	-76.76	-77.29	-77.73	-76.70	-53.26	-41.25	12.01
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-77.89								-71.89	-41.25	30.64
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-77.27	-76.67							-67.95	-41.25	26.70
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-76.89	-77.61							-68.23	-41.25	26.98
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-77.80	-77.68	-76.70						-66.59	-41.25	25.34
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-77.39	-77.70	-77.79						-66.85	-41.25	25.60
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-77.51	-77.64	-77.76						-66.87	-41.25	25.62
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-77.75	-77.27	-77.35	-77.38					-65.41	-41.25	24.16
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-77.52	-77.53	-77.25	-77.83					-65.51	-41.25	24.26
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-77.09	-76.91	-77.42	-77.26					-65.15	-41.25	23.90
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-77.47	-77.59	-77.17	-77.57					-65.42	-41.25	24.17

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-78.01	-78.29	-77.58	-77.27	-77.51	-77.42			-60.88	-41.25	19.63
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-77.50	-77.78	-77.27	-77.67	-76.98	-77.16			-61.21	-41.25	19.96
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	-77.61	-77.35	-77.27	-77.31	-76.82	-76.60			-61.85	-41.25	20.60
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-77.73	-77.24	-77.50	-77.33	-77.36	-77.66			-62.80	-41.25	21.55
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-77.37	-76.91	-77.43	-77.58	-77.45	-77.62			-63.21	-41.25	21.96
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-77.31	-77.30	-76.97	-77.28	-77.19	-77.40			-63.46	-41.25	22.21
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-78.88	-77.61	-77.26	-77.40	-77.34	-77.39	-77.56	-77.27	-59.53	-41.25	18.28
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-77.79	-77.20	-76.56	-77.68	-77.20	-77.69	-77.12	-77.50	-59.29	-41.25	18.04
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-77.89	-77.10	-77.35	-77.36	-77.09	-77.30	-77.36	-77.10	-60.15	-41.25	18.90
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-77.79	-77.66	-77.59	-77.29	-77.25	-77.54	-77.48	-77.31	-60.94	-41.25	19.69
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-77.51	-77.42	-77.65	-76.88	-77.30	-76.90	-77.25	-77.70	-61.27	-41.25	20.02
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-77.95	-77.06	-77.43	-77.08	-77.44	-76.88	-77.17	-77.69	-61.67	-41.25	20.42
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-77.21	-77.44	-77.80	-77.61	-77.50	-76.71	-76.97	-77.57	-62.02	-41.25	20.77
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-77.97	-76.92	-77.33	-77.32	-77.23	-77.50	-77.82	-77.47	-62.40	-41.25	21.15
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	-77.56	-76.88							-65.19	-41.25	23.94
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-77.11	-77.56							-68.32	-41.25	27.07
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-78.20	-77.31	-77.74						-62.19	-41.25	20.94
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-78.22	-77.04	-77.06						-64.88	-41.25	23.63
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-77.24	-77.69	-77.53						-66.71	-41.25	25.46
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-77.72	-77.40	-77.71	-77.27					-59.48	-41.25	18.23
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-77.70	-77.45	-77.42	-77.34					-62.44	-41.25	21.19
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-77.58	-77.23	-77.27	-77.19					-64.04	-41.25	22.79
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-77.89	-77.46	-77.78	-77.63					-65.67	-41.25	24.42
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-77.39	-77.49	-77.38	-77.43	-77.28	-76.77			-55.72	-41.25	14.47
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-77.86	-77.56	-77.62	-77.73	-77.23	-77.07			-58.95	-41.25	17.70
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-77.97	-77.58	-77.07	-77.26	-77.02	-77.35			-60.57	-41.25	19.32
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-77.89	-76.89	-77.45	-76.76	-77.41	-77.58			-61.77	-41.25	20.52
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-77.25	-76.57	-77.63	-77.57	-77.22	-77.43			-62.69	-41.25	21.44

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-77.25	-77.57	-77.34	-77.75	-77.63	-77.18			-63.67	-41.25	22.42
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	**8**	**15.03**	**-76.33**	**-77.00**	**-77.19**	**-77.71**	**-76.83**	**-77.57**	**-77.17**	**-77.63**	**-53.10**	**-41.25**	**11.85**
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-77.43	-77.34	-77.23	-77.40	-77.89	-77.29	-77.62	-77.21	-56.37	-41.25	15.12
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-77.25	-77.41	-76.96	-77.36	-77.03	-77.53	-77.15	-77.57	-57.99	-41.25	16.74
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-77.72	-77.42	-77.37	-77.10	-77.47	-77.04	-77.65	-77.45	-59.35	-41.25	18.10
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-76.92	-77.46	-77.32	-78.07	-77.79	-77.66	-77.23	-77.41	-60.40	-41.25	19.15
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-77.41	-77.23	-77.49	-77.33	-77.78	-77.41	-77.21	-77.00	-61.07	-41.25	19.82
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-77.39	-77.30	-77.45	-77.58	-77.49	-77.39	-77.49	-77.37	-61.82	-41.25	20.57
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-77.21	-77.47	-76.55	-77.27	-77.67	-77.01	-77.36	-77.61	-62.23	-41.25	20.98
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-77.54	-77.42							-68.47	-41.25	27.22
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-76.30	-77.42	-77.72						-66.33	-41.25	25.08
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-77.40	-77.33	-77.56	-76.36					-65.11	-41.25	23.86
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-76.46	-77.32	-77.37	-77.58	-77.64	-77.43			-63.50	-41.25	22.25
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-76.53	-77.76	-77.51	-77.44	-77.32	-77.08	-76.94	-77.41	-62.20	-41.25	20.95

Please refer to the following plots for the worst case configuration

Ant-a


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -76.33 dBm
39.3628 GHz
D1 -41.250 dBm
M1
Start 30.0 MHz 691 pts Stop 40.0 GHz
Date: 30.NOV.2018 23:01:05

Ant-b


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -77.00 dBm
39.8841 GHz
D1 -41.250 dBm
Start 30.0 MHz 691 pts Stop 40.0 GHz
Date: 30.NOV.2018 23:39:09

Ant-c


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -77.19 dBm
39.8841 GHz
D1 -41.250 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
-90 dBm
-100 dBm
Start 30.0 MHz
691 pts
Stop 40.0 GHz
Date: 1.DEC.2018 00:14:43

Ant-d


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -77.71 dBm
39.4207 GHz
D1 -41.250 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
-90 dBm
-100 dBm
Start 30.0 MHz
691 pts
Stop 40.0 GHz
Date: 1.DEC.2018 00:46:31

Ant-e


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -76.83 dBm
39.7683 GHz
D1 -41.250 dBm
Start 30.0 MHz 691 pts Stop 40.0 GHz
Date: 1.DEC.2018 01:13:43

Ant-f


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -77.57 dBm
39.3628 GHz
D1 -41.250 dBm
Start 30.0 MHz 691 pts Stop 40.0 GHz
Date: 1.DEC.2018 01:35:28

Ant-g


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -77.17 dBm
39.3628 GHz
D1 -41.250 dBm
M1
Start 30.0 MHz 691 pts Stop 40.0 GHz
Date: 1.DEC.2018 01:50:57

Ant-h


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 1 s VBW 30 kHz Mode Auto Sweep
1Pk Max
M1[1] -77.63 dBm
40.0000 GHz
D1 -41.250 dBm
Start 30.0 MHz 691 pts Stop 40.0 GHz
Date: 1.DEC.2018 01:59:19

5200 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-68.87								-62.87	-21.25	41.62
non HT20, 6 to 54 Mbps	2	6.00	-69.27	-69.59							-60.42	-21.25	39.17
non HT20, 6 to 54 Mbps	3	6.00	-69.17	-69.76	-68.78						-58.45	-21.25	37.20
non HT20, 6 to 54 Mbps	4	6.00	-69.26	-69.08	-69.04	-69.86					-57.28	-21.25	36.03
non HT20, 6 to 54 Mbps	6	9.00	-68.67	-69.34	-68.79	-69.31	-69.08	-68.78			-52.21	-21.25	30.96
non HT20, 6 to 54 Mbps	8	9.00	-69.07	-69.25	-69.04	-69.92	-69.10	-69.26	-69.19	-69.93	-51.30	-21.25	30.05
non HT20, 6 to 54 Mbps-BF	2	9.01	-69.33	-69.27							-57.28	-21.25	36.03
non HT20, 6 to 54 Mbps-BF	3	10.77	-69.28	-69.40	-68.97						-53.67	-21.25	32.42
non HT20, 6 to 54 Mbps-BF	4	12.02	-68.65	-69.11	-69.37	-68.27					-50.79	-21.25	29.54
non HT20, 6 to 54 Mbps-BF	6	13.78	-68.98	-69.12	-69.04	-69.52	-69.61	-68.81			-47.61	-21.25	26.36
non HT20, 6 to 54 Mbps-BF	8	15.03	-68.86	-68.81	-69.13	-69.09	-69.39	-68.66	-69.00	-69.44	-44.98	-21.25	23.73
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-68.88								-62.88	-21.25	41.63
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-68.65	-70.02							-60.27	-21.25	39.02
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-68.89	-68.69							-59.78	-21.25	38.53
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-69.29	-68.87	-69.02						-58.28	-21.25	37.03
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-68.94	-68.60	-69.05						-58.09	-21.25	36.84
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-68.36	-69.54	-69.22						-58.24	-21.25	36.99
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-68.40	-69.63	-69.02	-69.40					-57.07	-21.25	35.82
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-69.19	-69.97	-68.94	-69.36					-57.33	-21.25	36.08
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-69.67	-69.41	-68.25	-69.55					-57.16	-21.25	35.91
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-69.08	-69.32	-68.95	-68.65					-56.97	-21.25	35.72

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-68.88	-68.91	-69.59	-69.06	-69.32	-68.93			-52.32	-21.25	31.07
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-69.30	-68.68	-69.19	-69.60	-67.90	-69.56			-52.82	-21.25	31.57
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	-69.49	-69.22	-69.32	-69.30	-69.05	-69.46			-54.01	-21.25	32.76
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-68.49	-69.27	-69.32	-68.43	-68.57	-69.19			-54.20	-21.25	32.95
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-69.33	-69.18	-69.51	-69.48	-69.73	-68.55			-55.10	-21.25	33.85
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-69.64	-69.12	-68.92	-69.56	-69.10	-68.85			-55.41	-21.25	34.16
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-69.63	-68.06	-69.12	-69.36	-67.67	-69.13	-68.43	-68.13	-50.61	-21.25	29.36
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-69.26	-68.45	-68.98	-69.64	-69.19	-69.60	-68.97	-69.28	-51.13	-21.25	29.88
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-68.97	-69.28	-69.70	-68.91	-69.21	-69.50	-69.35	-69.16	-52.09	-21.25	30.84
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-69.63	-69.47	-69.38	-69.34	-69.18	-68.85	-69.64	-69.24	-52.79	-21.25	31.54
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-69.20	-69.59	-69.23	-69.17	-68.70	-69.00	-69.66	-69.62	-53.21	-21.25	31.96
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-68.75	-68.84	-69.29	-69.43	-69.13	-68.88	-69.29	-68.89	-53.41	-21.25	32.16
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-68.68	-69.33	-69.27	-69.54	-68.96	-68.67	-69.73	-67.55	-53.60	-21.25	32.35
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-69.25	-69.03	-69.49	-68.94	-69.36	-69.06	-69.12	-68.94	-54.11	-21.25	32.86
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	-69.79	-69.49							-57.61	-21.25	36.36
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-68.45	-69.03							-59.72	-21.25	38.47
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-68.24	-69.26	-67.89						-52.88	-21.25	31.63
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-69.54	-68.75	-69.94						-56.85	-21.25	35.60
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-69.31	-69.46	-68.89						-58.44	-21.25	37.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-69.27	-68.52	-68.63	-68.76					-50.75	-21.25	29.50
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-69.08	-69.49	-69.56	-69.51					-54.37	-21.25	33.12
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-69.57	-68.61	-69.09	-68.76					-55.72	-21.25	34.47
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-69.69	-69.65	-68.82	-68.92					-57.23	-21.25	35.98
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-69.25	-68.81	-69.11	-68.52	-69.14	-68.90			-47.38	-21.25	26.13
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-69.25	-69.47	-69.01	-69.17	-69.11	-68.82			-50.58	-21.25	29.33
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-69.47	-68.78	-69.21	-69.33	-69.38	-68.84			-52.37	-21.25	31.12
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-69.08	-68.77	-69.16	-68.41	-68.89	-68.92			-53.32	-21.25	32.07
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-68.62	-68.70	-69.36	-69.25	-68.35	-69.57			-54.38	-21.25	33.13

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-68.70	-69.17	-69.21	-68.72	-68.13	-69.11			-55.04	-21.25	33.79
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-69.68	-68.86	-69.25	-69.46	-68.90	-69.24	-68.59	-68.72	-45.01	-21.25	23.76
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-69.63	-68.76	-69.63	-69.25	-69.25	-69.30	-69.62	-68.96	-48.24	-21.25	26.99
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-69.60	-68.83	-69.48	-68.61	-69.44	-68.76	-69.68	-69.41	-49.92	-21.25	28.67
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-69.49	-68.97	-69.00	-68.96	-69.65	-68.69	-68.07	-69.15	-50.93	-21.25	29.68
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-69.13	-68.32	-68.84	-68.94	-69.19	-69.82	-68.89	-68.31	-51.84	-21.25	30.59
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-69.01	-69.07	-69.05	-69.45	-68.24	-69.20	-68.75	-69.30	-52.71	-21.25	31.46
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-69.25	-68.70	-68.45	-68.28	-69.03	-69.16	-68.73	-69.04	-53.21	-21.25	31.96
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-68.99	-68.92	-69.65	-69.04	-69.48	-69.51	-69.53	-69.02	-54.23	-21.25	32.98
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-69.77	-69.67							-60.71	-21.25	39.46
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-68.56	-67.95	-68.56						-57.58	-21.25	36.33
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-69.60	-69.36	-69.54	-69.19					-57.40	-21.25	36.15
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-69.08	-69.25	-69.60	-69.35	-69.18	-68.91			-55.44	-21.25	34.19
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-68.62	-68.40	-69.00	-68.94	-69.01	-69.19	-69.01	-69.61	-53.93	-21.25	32.68

5200 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-77.45								-71.45	-41.25	30.20
non HT20, 6 to 54 Mbps	2	6.00	-77.31	-77.35							-68.32	-41.25	27.07
non HT20, 6 to 54 Mbps	3	6.00	-77.44	-77.22	-77.43						-66.59	-41.25	25.34
non HT20, 6 to 54 Mbps	4	6.00	-77.00	-77.61	-77.53	-77.25					-65.32	-41.25	24.07
non HT20, 6 to 54 Mbps	6	9.00	-77.01	-77.70	-77.61	-77.70	-77.49	-77.40			-60.70	-41.25	19.45
non HT20, 6 to 54 Mbps	8	9.00	-76.75	-77.51	-77.22	-77.36	-77.20	-77.42	-77.48	-77.59	-59.28	-41.25	18.03
non HT20, 6 to 54 Mbps-BF	2	9.01	-77.82	-77.42							-65.60	-41.25	24.35
non HT20, 6 to 54 Mbps-BF	3	10.77	-76.88	-77.48	-77.58						-61.76	-41.25	20.51
non HT20, 6 to 54 Mbps-BF	4	12.02	-77.04	-77.52	-77.66	-77.80					-59.46	-41.25	18.21
non HT20, 6 to 54 Mbps-BF	6	13.78	-77.73	-77.46	-77.13	-77.43	-76.97	-77.31			-55.77	-41.25	14.52
non HT20, 6 to 54 Mbps-BF	8	15.03	-77.13	-77.35	-77.55	-78.05	-77.14	-77.33	-77.18	-77.19	-53.29	-41.25	12.04
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-77.25								-71.25	-41.25	30.00
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-77.49	-77.17							-68.31	-41.25	27.06
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-76.93	-77.73							-68.30	-41.25	27.05
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-77.42	-76.99	-77.17						-66.42	-41.25	25.17
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-77.93	-77.48	-77.87						-66.98	-41.25	25.73
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-77.31	-77.82	-77.04						-66.60	-41.25	25.35
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-77.56	-77.43	-77.44	-77.79					-65.53	-41.25	24.28
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-77.64	-77.50	-77.13	-77.20					-65.34	-41.25	24.09
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-77.06	-77.40	-77.93	-77.43					-65.42	-41.25	24.17
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-77.46	-77.55	-77.53	-77.84					-65.57	-41.25	24.32

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-77.32	-77.21	-76.91	-77.67	-77.57	-77.37			-60.55	-41.25	19.30
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-77.26	-77.46	-77.05	-77.64	-77.27	-77.58			-61.20	-41.25	19.95
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	-77.61	-77.46	-77.83	-77.67	-77.41	-77.52			-62.29	-41.25	21.04
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-77.64	-77.50	-76.78	-77.48	-77.00	-77.03			-62.57	-41.25	21.32
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-77.37	-77.29	-77.73	-77.66	-77.74	-77.15			-63.30	-41.25	22.05
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-77.28	-77.01	-77.43	-77.85	-76.65	-77.32			-63.46	-41.25	22.21
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-77.52	-77.12	-76.86	-77.45	-77.29	-77.43	-77.30	-77.63	-59.29	-41.25	18.04
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-77.18	-77.92	-77.70	-77.38	-77.80	-77.48	-77.41	-77.66	-59.53	-41.25	18.28
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-76.88	-77.14	-77.81	-77.52	-77.73	-77.54	-77.36	-77.53	-60.27	-41.25	19.02
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-77.54	-77.07	-77.78	-77.66	-77.01	-77.54	-77.52	-77.76	-60.93	-41.25	19.68
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-77.26	-77.34	-77.27	-77.72	-77.74	-77.74	-77.83	-77.65	-61.51	-41.25	20.26
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-77.74	-77.30	-76.98	-77.25	-77.18	-77.38	-77.61	-77.84	-61.75	-41.25	20.50
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-76.84	-77.38	-77.09	-77.58	-77.47	-77.83	-77.61	-77.40	-62.07	-41.25	20.82
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-77.36	-77.42	-77.11	-77.62	-77.60	-76.88	-77.29	-77.67	-62.33	-41.25	21.08
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	-77.39	-77.72							-65.53	-41.25	24.28
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-77.47	-77.46							-68.45	-41.25	27.20
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-76.62	-77.14	-77.15						-61.42	-41.25	20.17
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-76.93	-77.57	-76.89						-64.59	-41.25	23.34
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-77.74	-77.47	-77.01						-66.63	-41.25	25.38
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-77.24	-77.39	-76.99	-77.45					-59.22	-41.25	17.97
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-77.51	-77.15	-77.64	-77.76					-62.48	-41.25	21.23
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-77.33	-77.60	-77.89	-77.81					-64.38	-41.25	23.13
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-77.34	-77.65	-77.37	-77.47					-65.44	-41.25	24.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-77.48	-77.59	-77.91	-77.62	-77.74	-77.73			-56.11	-41.25	14.86
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-77.36	-76.38	-77.11	-77.81	-77.17	-77.57			-58.66	-41.25	17.41
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-76.82	-77.59	-77.06	-77.04	-77.55	-77.24			-60.41	-41.25	19.16
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-77.57	-77.40	-77.20	-77.13	-77.41	-76.61			-61.67	-41.25	20.42
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-77.34	-77.62	-77.58	-77.54	-77.40	-77.57			-62.94	-41.25	21.69

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-77.51	-77.22	-77.50	-77.21	-77.52	-77.32			-63.60	-41.25	22.35
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-77.51	-77.15	-77.18	-77.07	-77.69	-77.54	-77.51	-76.92	-53.25	-41.25	12.00
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-77.53	-77.29	-77.67	-77.04	-77.70	-77.46	-77.85	-77.35	-56.43	-41.25	15.18
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-77.10	-77.71	-77.32	-77.09	-77.33	-77.67	-77.75	-77.24	-58.10	-41.25	16.85
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-76.71	-77.47	-77.23	-77.64	-77.13	-77.29	-77.82	-77.78	-59.33	-41.25	18.08
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-77.52	-77.28	-77.29	-77.41	-77.48	-77.03	-77.61	-77.58	-60.32	-41.25	19.07
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-77.56	-77.63	-76.92	-77.34	-77.25	-77.67	-77.63	-77.42	-61.14	-41.25	19.89
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-77.16	-77.51	-76.51	-77.30	-77.31	-77.56	-77.30	-76.99	-61.58	-41.25	20.33
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-77.25	-77.05	-77.13	-77.11	-77.32	-77.32	-77.23	-77.51	-62.21	-41.25	20.96
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-77.39	-77.31							-68.34	-41.25	27.09
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-77.39	-76.62	-77.55						-66.39	-41.25	25.14
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-77.39	-77.55	-77.58	-77.89					-65.58	-41.25	24.33
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-77.64	-77.56	-77.51	-77.45	-77.04	-77.10			-63.59	-41.25	22.34
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-77.40	-77.75	-77.25	-77.52	-77.29	-77.37	-77.74	-77.44	-62.43	-41.25	21.18

5240 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-69.71								-63.71	-21.25	42.46
non HT20, 6 to 54 Mbps	2	6.00	-68.62	-69.69							-60.11	-21.25	38.86
non HT20, 6 to 54 Mbps	3	6.00	-69.12	-69.44	-68.77						-58.33	-21.25	37.08
non HT20, 6 to 54 Mbps	4	6.00	-69.24	-68.83	-69.37	-68.85					-57.05	-21.25	35.80
non HT20, 6 to 54 Mbps	6	9.00	-69.59	-69.37	-68.88	-69.62	-69.02	-69.74			-52.58	-21.25	31.33
non HT20, 6 to 54 Mbps	8	9.00	-69.45	-68.77	-69.65	-67.74	-69.55	-68.74	-69.04	-69.64	-51.00	-21.25	29.75
non HT20, 6 to 54 Mbps-BF	2	9.01	-68.99	-68.14							-56.52	-21.25	35.27
non HT20, 6 to 54 Mbps-BF	3	10.77	-69.41	-69.76	-68.91						-53.81	-21.25	32.56
non HT20, 6 to 54 Mbps-BF	4	12.02	-68.57	-69.33	-69.28	-69.26					-51.06	-21.25	29.81
non HT20, 6 to 54 Mbps-BF	6	13.78	-67.96	-69.57	-69.30	-69.43	-69.33	-68.60			-47.43	-21.25	26.18
non HT20, 6 to 54 Mbps-BF	8	15.03	-69.48	-68.75	-69.16	-69.26	-69.07	-69.39	-69.63	-69.30	-45.19	-21.25	23.94
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-69.20								-63.20	-21.25	41.95
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-69.10	-69.86							-60.45	-21.25	39.20
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-69.56	-69.54							-60.54	-21.25	39.29
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-69.34	-68.83	-69.70						-58.51	-21.25	37.26
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-68.68	-69.44	-68.78						-58.18	-21.25	36.93
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-69.56	-69.38	-68.94						-58.52	-21.25	37.27
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-68.97	-69.05	-68.29	-69.56					-56.93	-21.25	35.68
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-69.06	-69.29	-69.05	-67.96					-56.79	-21.25	35.54
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-69.44	-69.57	-67.57	-69.30					-56.87	-21.25	35.62
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-69.22	-69.37	-69.14	-69.30					-57.23	-21.25	35.98

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-69.29	-69.53	-69.49	-69.64	-69.27	-68.75			-52.54	-21.25	31.29
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-69.31	-69.15	-68.90	-68.48	-68.80	-68.90			-52.74	-21.25	31.49
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	-69.27	-68.29	-69.38	-69.42	-69.22	-69.40			-53.85	-21.25	32.60
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-69.62	-68.05	-69.57	-68.85	-69.25	-69.56			-54.45	-21.25	33.20
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-69.32	-68.94	-69.69	-68.35	-68.35	-69.84			-54.86	-21.25	33.61
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-69.37	-69.47	-68.79	-69.35	-69.05	-69.37			-55.44	-21.25	34.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-68.52	-69.51	-69.24	-69.42	-69.27	-69.23	-69.00	-69.54	-51.17	-21.25	29.92
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-68.32	-68.48	-68.54	-68.28	-68.46	-69.60	-68.75	-68.46	-50.56	-21.25	29.31
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-69.90	-69.52	-68.68	-69.57	-69.66	-69.09	-69.03	-69.41	-52.18	-21.25	30.93
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-69.20	-69.49	-69.21	-69.60	-69.61	-67.77	-69.30	-69.43	-52.62	-21.25	31.37
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-69.10	-68.94	-69.22	-69.65	-69.06	-69.53	-68.52	-68.46	-52.99	-21.25	31.74
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-69.64	-69.09	-68.97	-69.14	-68.77	-69.24	-69.93	-69.52	-53.62	-21.25	32.37
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-69.47	-69.41	-67.41	-68.57	-68.94	-69.28	-69.50	-69.02	-53.57	-21.25	32.32
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-69.11	-69.40	-69.55	-69.25	-69.46	-69.60	-68.62	-69.38	-54.26	-21.25	33.01
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	-69.54	-69.32							-57.40	-21.25	36.15
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-68.88	-68.95							-59.90	-21.25	38.65
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-68.36	-69.90	-68.83						-53.44	-21.25	32.19
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-68.39	-68.41	-69.28						-56.14	-21.25	34.89
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-68.99	-69.17	-68.91						-58.25	-21.25	37.00
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-68.72	-69.74	-69.13	-69.06					-51.10	-21.25	29.85
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-68.91	-68.88	-69.15	-69.28					-54.02	-21.25	32.77
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-68.38	-68.83	-69.37	-69.54					-55.74	-21.25	34.49
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-69.67	-69.45	-68.77	-68.72					-57.11	-21.25	35.86
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-69.62	-69.22	-69.26	-68.69	-68.98	-69.49			-47.64	-21.25	26.39
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-69.52	-69.40	-68.50	-69.28	-69.41	-67.95			-50.42	-21.25	29.17
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-68.69	-69.16	-68.83	-69.31	-68.86	-69.27			-52.22	-21.25	30.97
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-69.44	-68.63	-69.14	-68.39	-68.62	-69.07			-53.32	-21.25	32.07
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-68.57	-68.96	-68.21	-69.06	-68.28	-69.36			-54.15	-21.25	32.90

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-68.90	-69.19	-69.58	-68.96	-67.89	-69.45			-55.18	-21.25	33.93
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	**8**	**15.03**	**-69.30**	**-69.03**	**-68.65**	**-69.03**	**-68.83**	**-69.24**	**-69.02**	**-68.75**	**-44.91**	**-21.25**	**23.66**
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-68.66	-69.64	-68.95	-68.82	-69.35	-68.78	-68.57	-69.75	-47.99	-21.25	26.74
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-69.71	-68.50	-69.06	-69.58	-68.34	-68.92	-68.95	-69.24	-49.72	-21.25	28.47
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-68.81	-69.40	-69.59	-69.14	-69.02	-68.87	-69.14	-69.29	-51.11	-21.25	29.86
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-69.38	-69.37	-68.49	-69.44	-68.80	-69.56	-68.83	-69.58	-52.09	-21.25	30.84
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-69.61	-69.00	-68.74	-68.76	-69.51	-69.60	-69.14	-68.99	-52.87	-21.25	31.62
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-68.93	-69.10	-68.99	-68.90	-69.28	-68.87	-69.07	-69.55	-53.47	-21.25	32.22
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-69.42	-69.36	-68.66	-69.31	-69.35	-68.56	-69.09	-69.32	-54.09	-21.25	32.84
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-68.41	-69.70							-60.00	-21.25	38.75
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-68.68	-68.93	-68.70						-58.00	-21.25	36.75
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-69.62	-68.68	-68.90	-68.18					-56.79	-21.25	35.54
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-69.58	-69.42	-68.52	-69.46	-68.95	-69.19			-55.39	-21.25	34.14
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-68.98	-69.60	-69.35	-67.88	-68.94	-69.58	-69.38	-69.21	-54.05	-21.25	32.80

Please refer to the following plots for the worst case configuration

Ant-a



Date: 1.DEC.2018 12:22:52

Ant-b



Date: 1.DEC.2018 13:06:21

Ant-c


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 160 ms VBW 3 MHz Mode Auto Sweep
1Pk Max
M1[1] -68.65 dBm
39.3628 GHz
D1 -21.250 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
-90 dBm
-100 dBm
M1
Start 30.0 MHz
691 pts
Stop 40.0 GHz
Date: 1.DEC.2018 13:47:01

Ant-d


Spectrum
Ref Level -5.00 dBm Offset 0.10 dB RBW 1 MHz
Att 5 dB SWT 160 ms VBW 3 MHz Mode Auto Sweep
1Pk Max
M1[1] -69.03 dBm
39.7683 GHz
D1 -21.250 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
-90 dBm
-100 dBm
M
Start 30.0 MHz
691 pts
Stop 40.0 GHz
Date: 1.DEC.2018 14:23:22

Ant-e



Date: 1.DEC.2018 14:54:28

Ant-f



Date: 1.DEC.2018 15:19:21

Ant-g



Date: 1.DEC.2018 15:37:03

Ant-h



Date: 1.DEC.2018 15:46:37

5240 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-77.02								-71.02	-41.25	29.77
non HT20, 6 to 54 Mbps	2	6.00	-77.59	-77.50							-68.53	-41.25	27.28
non HT20, 6 to 54 Mbps	3	6.00	-77.47	-76.74	-77.47						-66.44	-41.25	25.19
non HT20, 6 to 54 Mbps	4	6.00	-77.64	-77.37	-77.31	-77.56					-65.45	-41.25	24.20
non HT20, 6 to 54 Mbps	6	9.00	-77.46	-76.90	-77.35	-77.75	-77.44	-77.20			-60.56	-41.25	19.31
non HT20, 6 to 54 Mbps	8	9.00	-77.62	-77.17	-77.59	-76.61	-77.23	-77.31	-76.88	-77.56	-59.20	-41.25	17.95
non HT20, 6 to 54 Mbps-BF	2	9.01	-77.66	-77.39							-65.50	-41.25	24.25
non HT20, 6 to 54 Mbps-BF	3	10.77	-77.63	-77.53	-77.51						-62.02	-41.25	20.77
non HT20, 6 to 54 Mbps-BF	4	12.02	-76.99	-77.34	-77.45	-77.49					-59.27	-41.25	18.02
non HT20, 6 to 54 Mbps-BF	6	13.78	-77.47	-76.99	-77.35	-77.34	-77.04	-77.42			-55.70	-41.25	14.45
non HT20, 6 to 54 Mbps-BF	8	15.03	-77.42	-77.66	-77.56	-77.74	-77.32	-77.19	-77.75	-77.54	-53.46	-41.25	12.21
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-77.31								-71.31	-41.25	30.06
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-77.14	-77.27							-68.19	-41.25	26.94
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-77.50	-77.44							-68.46	-41.25	27.21
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-77.46	-77.11	-77.05						-66.43	-41.25	25.18
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-77.35	-77.35	-77.25						-66.54	-41.25	25.29
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-77.24	-77.08	-77.05						-66.35	-41.25	25.10
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-77.58	-77.03	-77.45	-77.38					-65.33	-41.25	24.08
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-77.61	-77.30	-77.06	-77.44					-65.33	-41.25	24.08
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-77.19	-77.35	-77.66	-77.17					-65.32	-41.25	24.07
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-77.16	-77.67	-77.46	-77.89					-65.52	-41.25	24.27

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-77.52	-76.99	-77.32	-77.38	-77.39	-76.52			-60.39	-41.25	19.14
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-77.29	-77.37	-77.16	-77.07	-77.16	-77.00			-61.00	-41.25	19.75
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	-77.70	-77.42	-76.85	-77.23	-77.56	-77.13			-62.01	-41.25	20.76
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-77.41	-77.55	-77.57	-77.31	-78.04	-77.24			-62.85	-41.25	21.60
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-77.18	-77.43	-77.67	-77.28	-77.64	-77.86			-63.32	-41.25	22.07
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-77.44	-77.89	-77.01	-76.78	-77.76	-77.72			-63.63	-41.25	22.38
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-76.96	-77.61	-77.53	-77.15	-77.26	-77.07	-77.09	-77.60	-59.25	-41.25	18.00
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-77.59	-77.15	-77.38	-78.05	-77.10	-77.69	-77.37	-77.35	-59.42	-41.25	18.17
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-77.47	-77.69	-77.41	-77.81	-77.45	-77.43	-77.00	-77.50	-60.30	-41.25	19.05
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-77.68	-77.71	-77.71	-77.48	-78.01	-77.48	-77.63	-77.36	-61.09	-41.25	19.84
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-77.11	-77.23	-77.16	-77.44	-77.52	-77.62	-77.22	-77.29	-61.27	-41.25	20.02
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-77.44	-77.39	-77.44	-77.40	-76.95	-77.14	-76.98	-76.95	-61.55	-41.25	20.30
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-77.25	-77.20	-77.75	-77.33	-76.97	-77.55	-77.16	-77.24	-61.98	-41.25	20.73
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-76.45	-77.09	-77.45	-76.88	-77.55	-77.42	-76.95	-77.84	-62.15	-41.25	20.90
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	-76.84	-77.82							-65.28	-41.25	24.03
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-77.52	-77.85							-68.67	-41.25	27.42
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-77.14	-76.91	-76.92						-61.45	-41.25	20.20
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-77.44	-77.42	-77.33						-64.86	-41.25	23.61
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-77.95	-77.39	-77.05						-66.67	-41.25	25.42
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-77.48	-77.14	-77.95	-77.47					-59.46	-41.25	18.21
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-77.01	-77.03	-77.48	-76.94					-62.08	-41.25	20.83
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-77.58	-77.71	-77.04	-77.59					-64.20	-41.25	22.95
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-76.77	-77.07	-77.42	-77.13					-65.07	-41.25	23.82
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-77.30	-77.81	-77.83	-77.17	-77.38	-77.67			-55.96	-41.25	14.71
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-77.05	-77.08	-77.33	-77.58	-77.22	-77.87			-58.79	-41.25	17.54
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-77.52	-76.95	-77.49	-77.29	-77.23	-77.32			-60.50	-41.25	19.25
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-77.67	-77.72	-77.55	-77.34	-77.34	-77.52			-61.98	-41.25	20.73
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-77.45	-77.75	-76.82	-77.43	-77.58	-77.11			-62.77	-41.25	21.52

VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-77.56	-77.64	-76.85	-77.58	-76.96	-78.11			-63.65	-41.25	22.40
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-77.30	-76.74	-77.14	-77.23	-77.04	-77.19	-77.31	-77.59	-53.12	-41.25	11.87
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-77.29	-76.89	-77.74	-77.43	-77.21	-77.35	-77.01	-77.08	-56.19	-41.25	14.94
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-77.61	-77.02	-77.59	-77.30	-77.47	-77.37	-77.33	-77.52	-58.10	-41.25	16.85
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-77.53	-76.97	-77.25	-77.61	-77.73	-77.95	-77.54	-77.03	-59.40	-41.25	18.15
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-77.05	-77.69	-77.28	-77.05	-77.26	-77.71	-77.57	-77.38	-60.30	-41.25	19.05
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-77.09	-77.53	-77.21	-77.54	-77.55	-76.81	-77.55	-77.39	-61.05	-41.25	19.80
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-77.32	-77.27	-76.97	-77.60	-77.37	-77.51	-77.57	-77.39	-61.76	-41.25	20.51
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-77.63	-77.61	-77.47	-77.53	-77.44	-77.46	-77.32	-77.50	-62.46	-41.25	21.21
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-77.07	-77.51							-68.27	-41.25	27.02
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-77.09	-77.40	-76.80						-66.32	-41.25	25.07
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-76.55	-77.73	-77.20	-77.47					-65.19	-41.25	23.94
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-77.41	-77.76	-76.50	-76.87	-77.23	-77.41			-63.39	-41.25	22.14
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-76.84	-77.58	-76.98	-77.49	-77.97	-77.67	-77.69	-77.51	-62.42	-41.25	21.17

5190 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-69.40								-63.40	-21.25	42.15
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-69.10	-68.05							-59.53	-21.25	38.28
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-69.00	-68.70							-59.84	-21.25	38.59
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-68.92	-69.44	-69.15						-58.39	-21.25	37.14
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-69.09	-68.53	-69.13						-58.14	-21.25	36.89
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-68.42	-68.41	-68.95						-57.81	-21.25	36.56
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-68.70	-69.29	-68.51	-68.90					-56.82	-21.25	35.57
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-68.83	-68.93	-68.88	-69.20					-56.94	-21.25	35.69
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-68.99	-68.80	-68.38	-69.21					-56.81	-21.25	35.56
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-68.67	-68.97	-69.07	-69.63					-57.05	-21.25	35.80
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-68.86	-69.17	-69.27	-68.95	-68.87	-69.36			-55.29	-21.25	34.04
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-69.36	-69.10	-69.12	-68.06	-68.28	-69.16			-55.04	-21.25	33.79
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-68.71	-69.26	-68.94	-69.61	-68.39	-69.40			-55.25	-21.25	34.00
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-69.42	-69.00	-69.04	-68.67	-68.79	-69.28			-55.24	-21.25	33.99
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-69.16	-68.73	-68.97	-68.34	-68.67	-68.79			-54.99	-21.25	33.74
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-68.17	-68.37	-67.97	-68.50	-68.51	-69.27			-54.66	-21.25	33.41
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-67.99	-69.21	-68.49	-68.90	-69.29	-68.47	-68.57	-68.76	-53.66	-21.25	32.41
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-68.51	-69.02	-69.14	-69.22	-69.23	-69.67	-69.08	-69.17	-54.09	-21.25	32.84
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-68.57	-68.00	-69.42	-68.71	-69.52	-68.80	-68.96	-69.57	-53.88	-21.25	32.63
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-69.08	-69.19	-68.89	-68.41	-68.59	-69.78	-68.76	-68.61	-53.86	-21.25	32.61
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-69.23	-69.07	-68.67	-69.60	-68.87	-68.84	-68.96	-68.78	-53.96	-21.25	32.71
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-68.98	-68.58	-68.86	-68.68	-68.06	-69.27	-69.56	-69.14	-53.84	-21.25	32.59

VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-68.57	-68.67	-69.10	-69.34	-68.96	-68.83	-69.52	-69.36	-54.00	-21.25	32.75
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-69.13	-68.49	-68.51	-68.37	-68.83	-68.20	-68.65	-69.10	-53.62	-21.25	32.37
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-68.78	-69.90							-57.28	-21.25	36.03
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-68.57	-69.04							-59.79	-21.25	38.54
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-69.08	-69.12	-69.40						-53.66	-21.25	32.41
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-69.69	-69.50	-69.15						-56.91	-21.25	35.66
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-68.89	-69.45	-68.63						-58.21	-21.25	36.96
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-69.28	-69.44	-68.84	-68.08					-50.84	-21.25	29.59
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-68.62	-69.15	-69.38	-69.01					-54.00	-21.25	32.75
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-68.41	-69.89	-68.50	-69.25					-55.70	-21.25	34.45
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-69.00	-68.53	-69.30	-68.15					-56.70	-21.25	35.45
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-68.57	-68.57	-68.93	-68.71	-69.08	-69.28			-47.29	-21.25	26.04
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-68.70	-69.19	-69.10	-68.65	-69.16	-69.00			-50.41	-21.25	29.16
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-69.19	-68.57	-68.98	-67.67	-69.48	-68.84			-51.96	-21.25	30.71
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-68.46	-69.65	-68.52	-69.05	-69.29	-69.15			-53.46	-21.25	32.21
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-68.51	-69.46	-68.94	-68.95	-68.03	-69.28			-54.26	-21.25	33.01
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-69.02	-68.64	-68.63	-68.78	-69.29	-68.43			-55.01	-21.25	33.76
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-69.30	-68.72	-68.97	-68.83	-69.76	-69.39	-68.17	-69.40	-44.98	-21.25	23.73
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-69.47	-68.62	-68.33	-69.30	-68.46	-69.68	-69.62	-68.58	-47.92	-21.25	26.67
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-68.80	-68.56	-69.02	-69.23	-69.32	-68.53	-69.04	-69.42	-49.69	-21.25	28.44
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-68.65	-69.63	-69.19	-68.82	-69.07	-69.57	-68.13	-68.72	-50.91	-21.25	29.66
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-68.37	-67.96	-69.02	-68.75	-69.25	-68.70	-69.08	-69.03	-51.68	-21.25	30.43
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-68.72	-68.38	-69.49	-68.12	-68.83	-68.68	-69.22	-68.44	-52.43	-21.25	31.18
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-69.11	-68.13	-69.18	-69.23	-69.32	-68.97	-69.01	-69.43	-53.42	-21.25	32.17
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-68.81	-68.97	-69.19	-69.16	-68.93	-67.40	-68.71	-68.98	-53.70	-21.25	32.45
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	-69.12	-68.70							-59.89	-21.25	38.64
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	-69.15	-69.11	-68.83						-58.26	-21.25	37.01
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	-69.29	-69.13	-68.90	-68.98					-57.05	-21.25	35.80

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	-69.36	-68.84	-69.48	-69.62	-69.37	-68.84			-55.46	-21.25	34.21
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	-68.42	-68.98	-68.77	-68.36	-69.18	-69.11	-69.01	-69.37	-53.86	-21.25	32.61

5190 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-77.34								-71.34	-41.25	30.09
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-78.49	-78.45							-69.46	-41.25	28.21
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-77.78	-77.41							-68.58	-41.25	27.33
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-78.66	-77.37	-77.25						-66.94	-41.25	25.69
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-76.90	-77.81	-77.02						-66.45	-41.25	25.20
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-77.19	-77.62	-78.40						-66.94	-41.25	25.69
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-77.53	-78.59	-77.48	-77.80					-65.81	-41.25	24.56
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-76.91	-77.38	-78.65	-78.19					-65.71	-41.25	24.46
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-77.86	-78.23	-78.63	-76.97					-65.86	-41.25	24.61
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-77.27	-77.42	-78.35	-78.53					-65.84	-41.25	24.59
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-76.93	-78.64	-77.22	-78.66	-77.68	-77.39			-63.92	-41.25	22.67
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-77.56	-77.65	-77.34	-77.27	-77.18	-77.07			-63.56	-41.25	22.31
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-77.24	-77.41	-77.12	-77.49	-77.63	-78.48			-63.76	-41.25	22.51
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-78.29	-78.62	-77.46	-77.13	-77.10	-77.38			-63.84	-41.25	22.59
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-76.98	-77.43	-77.51	-77.52	-79.37	-77.66			-63.90	-41.25	22.65
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-77.20	-77.16	-77.31	-77.10	-79.65	-77.39			-63.77	-41.25	22.52
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-78.50	-77.34	-77.01	-78.41	-78.57	-77.54	-77.32	-77.71	-62.73	-41.25	21.48
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-77.55	-77.21	-76.08	-79.23	-77.39	-77.12	-77.63	-78.58	-62.48	-41.25	21.23
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-78.30	-77.24	-77.38	-76.97	-77.40	-77.17	-77.87	-77.48	-62.43	-41.25	21.18
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-77.26	-77.32	-77.53	-77.60	-78.13	-77.04	-78.99	-77.57	-62.61	-41.25	21.36
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-77.71	-76.60	-77.04	-77.26	-77.63	-77.55	-77.60	-77.39	-62.30	-41.25	21.05
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-77.38	-78.34	-77.63	-77.25	-78.32	-77.52	-77.32	-77.26	-62.58	-41.25	21.33

VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-77.10	-78.45	-78.38	-76.76	-77.25	-76.90	-77.02	-77.46	-62.34	-41.25	21.09
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-77.45	-77.49	-77.31	-77.02	-77.15	-78.89	-77.11	-77.33	-62.40	-41.25	21.15
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-76.93	-77.44							-65.16	-41.25	23.91
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-77.68	-77.13							-68.39	-41.25	27.14
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-77.05	-76.69	-77.28						-61.46	-41.25	20.21
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-77.76	-79.22	-77.67						-65.63	-41.25	24.38
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-78.05	-78.26	-77.32						-67.09	-41.25	25.84
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-77.35	-78.26	-77.27	-79.83					-60.02	-41.25	18.77
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-77.17	-78.57	-77.09	-78.14					-62.67	-41.25	21.42
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-77.57	-78.51	-77.51	-77.17					-64.39	-41.25	23.14
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-77.71	-77.18	-77.33	-77.22					-65.33	-41.25	24.08
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-76.99	-76.88	-77.46	-78.13	-76.98	-76.38			-55.54	-41.25	14.29
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-77.51	-77.37	-77.75	-77.12	-77.72	-77.70			-58.97	-41.25	17.72
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-77.02	-78.38	-77.02	-77.51	-77.50	-77.10			-60.61	-41.25	19.36
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-78.62	-77.14	-78.66	-77.21	-77.43	-77.53			-62.18	-41.25	20.93
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-77.29	-77.37	-77.33	-78.51	-78.62	-77.23			-63.11	-41.25	21.86
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-77.57	-77.32	-77.51	-77.67	-77.81	-77.53			-63.78	-41.25	22.53
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-76.89	-76.77	-77.32	-77.44	-77.58	-78.59	-77.53	-77.41	-53.35	-41.25	12.10
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-77.26	-77.62	-76.62	-79.49	-77.61	-77.29	-77.59	-78.59	-56.63	-41.25	15.38
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-77.12	-76.75	-77.31	-77.32	-77.53	-77.22	-77.48	-78.49	-58.09	-41.25	16.84
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-79.50	-78.27	-78.79	-76.72	-77.28	-77.59	-77.05	-77.77	-59.75	-41.25	18.50
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-77.72	-77.14	-77.28	-77.15	-77.65	-77.08	-77.27	-77.41	-60.26	-41.25	19.01
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-77.45	-76.72	-78.40	-77.67	-77.15	-78.16	-78.36	-77.18	-61.32	-41.25	20.07
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-77.42	-76.89	-78.85	-78.34	-78.19	-77.00	-77.74	-78.00	-62.15	-41.25	20.90
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-76.74	-77.33	-77.29	-77.72	-77.63	-76.97	-77.11	-77.35	-62.23	-41.25	20.98
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	-77.75	-76.60							-68.13	-41.25	26.88
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	-78.41	-77.40	-79.20						-67.50	-41.25	26.25
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	-78.83	-76.86	-77.24	-78.34					-65.72	-41.25	24.47

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	-78.49	-78.12	-77.51	-78.37	-77.56	-77.62			-64.15	-41.25	22.90
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	-78.94	-78.33	-77.24	-77.56	-78.43	-78.46	-77.17	-77.51	-62.88	-41.25	21.63

5230 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-68.94								-62.94	-21.25	41.69
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-69.33	-69.57							-60.44	-21.25	39.19
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-69.22	-68.92							-60.06	-21.25	38.81
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-68.07	-68.59	-69.15						-57.81	-21.25	36.56
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-69.09	-68.23	-68.93						-57.96	-21.25	36.71
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-68.17	-68.95	-69.08						-57.94	-21.25	36.69
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-69.38	-68.32	-68.98	-68.50					-56.75	-21.25	35.50
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-68.54	-69.27	-68.57	-69.32					-56.89	-21.25	35.64
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-68.66	-69.87	-69.78	-69.17					-57.32	-21.25	36.07
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-68.90	-68.99	-69.10	-68.80					-56.93	-21.25	35.68
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-69.28	-69.15	-69.00	-69.14	-68.91	-68.93			-55.28	-21.25	34.03
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-69.20	-69.00	-69.39	-69.31	-68.30	-69.33			-55.29	-21.25	34.04
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-69.49	-68.93	-68.97	-68.28	-68.56	-68.44			-54.98	-21.25	33.73
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-69.02	-68.84	-68.92	-69.34	-68.70	-69.60			-55.28	-21.25	34.03
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-69.06	-69.78	-68.60	-69.05	-68.22	-68.72			-55.10	-21.25	33.85
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-68.83	-69.53	-68.00	-67.94	-69.06	-69.25			-54.94	-21.25	33.69
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-69.28	-69.18	-68.31	-69.27	-69.27	-69.42	-68.70	-68.98	-54.01	-21.25	32.76
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-68.67	-68.55	-69.30	-68.86	-69.07	-68.45	-68.83	-69.38	-53.85	-21.25	32.60
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-69.00	-69.19	-69.15	-69.12	-69.14	-69.14	-68.78	-69.24	-54.06	-21.25	32.81
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-69.13	-69.09	-69.66	-68.32	-69.11	-69.30	-69.10	-68.85	-54.02	-21.25	32.77
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-69.38	-68.80	-69.32	-68.92	-69.46	-68.95	-69.16	-68.86	-54.07	-21.25	32.82

VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-68.67	-69.38	-69.09	-68.53	-68.62	-68.78	-68.49	-68.72	-53.75	-21.25	32.50
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-69.19	-69.10	-69.89	-68.83	-68.60	-69.49	-68.67	-69.32	-54.09	-21.25	32.84
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-68.20	-69.08	-68.84	-67.72	-69.07	-67.99	-68.86	-68.93	-53.53	-21.25	32.28
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-68.62	-68.92							-56.75	-21.25	35.50
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-68.82	-69.39							-60.09	-21.25	38.84
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-68.94	-68.98	-68.63						-53.31	-21.25	32.06
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-69.02	-69.15	-68.89						-56.49	-21.25	35.24
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-68.29	-69.95	-68.08						-57.93	-21.25	36.68
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-68.45	-68.85	-68.25	-69.07					-50.60	-21.25	29.35
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-68.53	-69.45	-68.75	-69.09					-53.91	-21.25	32.66
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-69.10	-69.12	-68.54	-69.22					-55.72	-21.25	34.47
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-68.82	-69.02	-68.65	-69.19					-56.89	-21.25	35.64
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-69.57	-68.42	-69.60	-69.15	-68.64	-69.18			-47.51	-21.25	26.26
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-68.90	-69.13	-68.68	-68.30	-69.17	-69.58			-50.39	-21.25	29.14
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-69.32	-68.42	-68.43	-68.93	-69.16	-68.45			-51.98	-21.25	30.73
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-69.07	-69.37	-68.90	-68.38	-69.01	-69.20			-53.44	-21.25	32.19
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-68.48	-69.18	-69.35	-69.29	-68.59	-68.60			-54.33	-21.25	33.08
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-68.89	-69.07	-68.87	-68.50	-68.49	-68.97			-55.01	-21.25	33.76
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-69.31	-69.01	-69.20	-69.00	-69.39	-69.20	-69.08	-68.29	-44.99	-21.25	23.74
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-68.73	-68.40	-68.55	-69.17	-68.39	-69.22	-69.66	-69.08	-47.83	-21.25	26.58
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-68.60	-69.26	-69.59	-69.13	-69.25	-69.41	-68.83	-69.35	-49.88	-21.25	28.63
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-69.19	-68.92	-68.50	-68.54	-68.76	-68.33	-69.17	-69.23	-50.78	-21.25	29.53
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-69.71	-69.67	-68.67	-68.86	-69.99	-69.12	-69.03	-68.78	-52.13	-21.25	30.88
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-68.46	-68.92	-68.68	-68.38	-68.86	-68.91	-69.16	-69.02	-52.51	-21.25	31.26
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-69.47	-69.29	-69.27	-68.51	-69.28	-68.44	-69.08	-69.18	-53.44	-21.25	32.19
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-68.72	-69.63	-69.01	-68.93	-69.19	-69.47	-69.17	-69.41	-54.15	-21.25	32.90
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	-68.03	-68.93							-59.45	-21.25	38.20
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	-68.70	-69.26	-68.93						-58.19	-21.25	36.94

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	-69.31	-69.61	-68.31	-69.54					-57.14	-21.25	35.89
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	-68.46	-68.55	-69.64	-69.24	-69.35	-68.44			-55.14	-21.25	33.89
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	-69.02	-67.58	-69.19	-68.75	-69.46	-68.11	-68.74	-68.88	-53.65	-21.25	32.40

5230 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-77.79								-71.79	-41.25	30.54
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-77.04	-77.35							-68.18	-41.25	26.93
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-78.44	-77.13							-68.73	-41.25	27.48
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-76.55	-77.12	-77.35						-66.22	-41.25	24.97
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-77.68	-77.44	-78.60						-67.11	-41.25	25.86
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-78.12	-77.04	-76.97						-66.57	-41.25	25.32
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-77.03	-77.39	-77.49	-77.31					-65.28	-41.25	24.03
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-76.74	-78.51	-77.39	-77.02					-65.34	-41.25	24.09
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-77.30	-79.88	-78.19	-78.37					-66.32	-41.25	25.07
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-77.52	-78.59	-77.25	-78.22					-65.84	-41.25	24.59
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-78.79	-77.70	-77.98	-77.03	-77.11	-78.28			-63.99	-41.25	22.74
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-76.88	-78.08	-77.64	-76.80	-79.50	-77.54			-63.87	-41.25	22.62
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-77.10	-77.13	-77.57	-77.34	-77.65	-77.06			-63.52	-41.25	22.27
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-77.62	-78.39	-78.23	-78.08	-77.20	-77.41			-64.02	-41.25	22.77
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-77.20	-77.37	-78.42	-77.06	-77.41	-77.22			-63.64	-41.25	22.39
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-79.40	-77.36	-77.43	-77.41	-77.56	-77.46			-63.93	-41.25	22.68
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-77.39	-77.14	-77.05	-77.29	-78.62	-77.09	-77.37	-76.99	-62.31	-41.25	21.06
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-77.36	-77.09	-77.04	-77.28	-77.40	-77.60	-79.50	-76.38	-62.35	-41.25	21.10
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-76.86	-78.61	-77.15	-77.59	-77.54	-77.23	-77.25	-77.43	-62.40	-41.25	21.15
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-78.86	-77.63	-79.10	-79.36	-77.58	-77.04	-77.37	-77.41	-62.93	-41.25	21.68
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-77.29	-77.08	-77.51	-77.54	-77.18	-76.90	-77.09	-76.70	-62.12	-41.25	20.87

VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-77.67	-77.24	-77.64	-77.21	-78.73	-77.24	-77.68	-78.20	-62.64	-41.25	21.39
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-79.77	-78.57	-77.32	-77.49	-77.50	-77.56	-76.88	-78.00	-62.78	-41.25	21.53
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-77.16	-77.23	-77.60	-78.91	-77.52	-77.44	-76.97	-77.60	-62.49	-41.25	21.24
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-77.11	-78.34							-65.66	-41.25	24.41
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-79.30	-77.42							-69.25	-41.25	28.00
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-76.97	-79.40	-77.31						-62.23	-41.25	20.98
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-77.66	-76.53	-77.57						-64.69	-41.25	23.44
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-77.54	-78.88	-77.69						-67.23	-41.25	25.98
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-77.11	-78.41	-78.16	-78.17					-59.89	-41.25	18.64
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-78.69	-79.33	-76.91	-77.35					-62.93	-41.25	21.68
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-77.25	-78.71	-77.33	-78.12					-64.54	-41.25	23.29
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-79.97	-77.56	-77.57	-78.44					-66.26	-41.25	25.01
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-76.53	-77.54	-77.22	-77.58	-77.01	-77.49			-55.65	-41.25	14.40
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-78.97	-77.39	-77.62	-77.58	-79.37	-76.90			-59.33	-41.25	18.08
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-77.67	-77.21	-77.07	-77.91	-76.32	-77.33			-60.43	-41.25	19.18
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-77.17	-77.42	-77.44	-77.22	-77.26	-77.71			-61.82	-41.25	20.57
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-78.23	-77.33	-76.76	-77.08	-77.24	-77.55			-62.77	-41.25	21.52
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-77.01	-77.51	-78.28	-76.77	-77.10	-78.55			-63.71	-41.25	22.46
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-77.65	-77.42	-77.44	-77.39	-77.39	-77.55	-77.35	-77.39	-53.39	-41.25	12.14
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-77.36	-78.31	-77.59	-76.46	-79.28	-78.74	-77.31	-77.51	-56.69	-41.25	15.44
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-76.85	-77.39	-76.99	-79.10	-78.13	-76.42	-77.19	-76.98	-58.02	-41.25	16.77
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-79.67	-78.32	-77.37	-78.06	-77.23	-78.20	-77.10	-77.72	-59.85	-41.25	18.60
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-77.40	-77.01	-78.32	-76.84	-77.56	-77.28	-78.51	-78.51	-60.56	-41.25	19.31
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-77.24	-77.01	-77.51	-77.45	-76.95	-79.51	-77.38	-78.35	-61.33	-41.25	20.08
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-76.86	-77.53	-77.13	-77.06	-77.29	-77.39	-77.31	-77.36	-61.63	-41.25	20.38
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-78.45	-77.42	-77.17	-78.82	-78.70	-77.49	-78.51	-77.50	-62.93	-41.25	21.68
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	-78.33	-77.99							-69.15	-41.25	27.90
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	-77.49	-77.44	-78.43						-66.99	-41.25	25.74

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	-77.33	-77.63	-76.48	-76.69					-64.99	-41.25	23.74
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	-77.33	-77.01	-77.15	-77.24	-76.80	-77.99			-63.46	-41.25	22.21
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	-77.20	-77.58	-77.41	-77.89	-78.08	-77.27	-77.04	-79.42	-62.65	-41.25	21.40

5210 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-69.31								-63.31	-21.25	42.06
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-69.44	-69.32							-60.37	-21.25	39.12
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-68.85	-68.84							-59.83	-21.25	38.58
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-69.43	-69.18	-68.74						-58.34	-21.25	37.09
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-68.64	-69.18	-68.46						-57.98	-21.25	36.73
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-69.19	-68.61	-69.08						-58.18	-21.25	36.93
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-69.00	-69.46	-69.29	-68.48					-57.02	-21.25	35.77
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-69.27	-68.93	-68.53	-68.92					-56.88	-21.25	35.63
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-69.12	-68.70	-68.64	-69.23					-56.90	-21.25	35.65
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-69.02	-69.09	-69.04	-68.67					-56.93	-21.25	35.68
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-69.38	-69.22	-69.19	-69.08	-69.53	-68.82			-55.41	-21.25	34.16
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-68.74	-68.62	-68.70	-69.01	-69.39	-68.63			-55.06	-21.25	33.81
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-68.62	-69.36	-68.87	-69.05	-69.42	-68.69			-55.21	-21.25	33.96
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-69.07	-68.55	-68.53	-69.39	-68.84	-68.34			-54.99	-21.25	33.74
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-69.64	-68.36	-69.02	-69.03	-68.49	-68.90			-55.11	-21.25	33.86
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-68.62	-69.15	-68.56	-67.74	-68.85	-68.07			-54.69	-21.25	33.44
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-68.80	-68.63	-69.33	-68.81	-68.62	-68.57	-69.17	-69.33	-53.87	-21.25	32.62
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-68.28	-69.18	-69.03	-69.27	-67.87	-68.96	-69.31	-69.06	-53.81	-21.25	32.56
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-68.99	-69.33	-69.07	-69.23	-69.31	-69.53	-69.20	-69.15	-54.19	-21.25	32.94
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-68.97	-69.39	-69.65	-68.83	-69.67	-69.20	-69.20	-69.00	-54.20	-21.25	32.95
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-69.16	-68.87	-68.64	-69.24	-69.01	-69.38	-68.02	-68.80	-53.84	-21.25	32.59

VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-68.88	-69.04	-68.67	-69.09	-69.47	-68.90	-69.61	-68.97	-54.04	-21.25	32.79
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-68.88	-69.59	-68.41	-69.23	-69.26	-69.32	-68.93	-69.52	-54.10	-21.25	32.85
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-69.22	-68.53	-69.30	-68.80	-69.04	-68.45	-69.26	-69.01	-53.91	-21.25	32.66
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-68.88	-69.31							-57.07	-21.25	35.82
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-69.21	-68.69							-59.93	-21.25	38.68
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-69.09	-68.42	-68.20						-53.01	-21.25	31.76
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-69.30	-68.73	-69.33						-56.58	-21.25	35.33
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-69.34	-68.24	-69.33						-58.17	-21.25	36.92
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-68.87	-68.70	-68.91	-69.27					-50.89	-21.25	29.64
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-68.86	-68.46	-69.05	-69.10					-53.83	-21.25	32.58
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-68.26	-68.52	-68.73	-69.00					-55.35	-21.25	34.10
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-68.47	-68.69	-69.16	-68.85					-56.77	-21.25	35.52
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-68.34	-69.32	-69.15	-68.47	-68.62	-69.38			-47.30	-21.25	26.05
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-68.55	-69.74	-69.51	-69.40	-69.56	-69.72			-50.84	-21.25	29.59
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-69.16	-69.09	-68.92	-69.30	-68.99	-69.28			-52.33	-21.25	31.08
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-69.59	-69.31	-68.88	-68.35	-68.78	-69.10			-53.44	-21.25	32.19
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-69.03	-69.08	-69.18	-69.26	-69.22	-68.96			-54.55	-21.25	33.30
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-68.68	-69.76	-69.66	-68.29	-68.63	-69.13			-55.21	-21.25	33.96
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-69.81	-69.29	-69.30	-68.99	-69.38	-69.64	-69.26	-68.50	-45.19	-21.25	23.94
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-68.70	-68.52	-67.54	-67.99	-68.57	-68.76	-69.19	-69.00	-47.45	-21.25	26.20
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-69.27	-68.72	-68.66	-69.02	-69.24	-68.99	-68.12	-68.83	-49.55	-21.25	28.30
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-69.29	-69.34	-68.74	-69.43	-68.93	-69.15	-69.07	-68.90	-51.06	-21.25	29.81
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-68.54	-68.68	-68.81	-69.23	-68.62	-68.82	-68.11	-69.04	-51.65	-21.25	30.40
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-69.37	-68.48	-69.37	-69.03	-68.96	-68.28	-69.05	-68.99	-52.65	-21.25	31.40
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-68.98	-69.22	-69.32	-68.94	-68.08	-68.82	-68.05	-69.39	-53.21	-21.25	31.96
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-69.55	-68.45	-69.06	-68.90	-68.88	-68.98	-68.91	-69.03	-53.93	-21.25	32.68
VHT/HE80, M0 to M9, M0 to M11-STBC	2	6.00	-69.41	-68.30							-59.81	-21.25	38.56
VHT/HE80, M0 to M9, M0 to M11-STBC	3	6.00	-68.62	-69.42	-68.50						-58.05	-21.25	36.80

VHT/HE80, M0 to M9, M0 to M11-STBC	4	6.00	-68.94	-69.46	-68.02	-68.40					-56.65	-21.25	35.40
VHT/HE80, M0 to M9, M0 to M11-STBC	6	6.00	-69.15	-68.13	-69.51	-68.52	-68.71	-69.16			-55.05	-21.25	33.80
VHT/HE80, M0 to M9, M0 to M11-STBC	8	6.00	-69.29	-68.99	-69.03	-68.82	-68.58	-69.43	-69.16	-68.36	-53.91	-21.25	32.66

5210 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Spurious (dBm)	Tx 2 Spurious (dBm)	Tx 3 Spurious (dBm)	Tx 4 Spurious (dBm)	Tx 5 Spurious (dBm)	Tx 6 Spurious (dBm)	Tx 7 Spurious (dBm)	Tx 8 Spurious (dBm)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-77.28								-71.28	-41.25	30.03
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-77.42	-77.26							-68.33	-41.25	27.08
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-77.82	-77.39							-68.59	-41.25	27.34
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-77.57	-77.50	-77.64						-66.80	-41.25	25.55
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-77.84	-76.89	-77.50						-66.62	-41.25	25.37
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-76.88	-76.84	-77.47						-66.28	-41.25	25.03
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-77.32	-77.46	-77.41	-77.54					-65.41	-41.25	24.16
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-76.98	-77.42	-77.53	-77.14					-65.24	-41.25	23.99
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-77.67	-77.10	-77.42	-77.56					-65.41	-41.25	24.16
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-77.06	-77.20	-77.02	-77.34					-65.13	-41.25	23.88
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-76.83	-77.66	-77.41	-77.57	-77.13	-77.65			-63.58	-41.25	22.33
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-77.52	-76.86	-77.40	-77.38	-77.50	-77.38			-63.55	-41.25	22.30
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-77.40	-76.92	-76.85	-77.32	-77.09	-77.22			-63.35	-41.25	22.10
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-77.45	-77.52	-77.35	-77.40	-77.58	-77.32			-63.66	-41.25	22.41
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-77.21	-77.15	-77.70	-77.60	-77.09	-76.58			-63.42	-41.25	22.17
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-76.96	-77.52	-77.29	-77.52	-76.85	-77.87			-63.54	-41.25	22.29
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-77.26	-77.71	-76.79	-77.39	-77.16	-77.45	-77.68	-77.36	-62.31	-41.25	21.06
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-77.62	-77.73	-77.59	-77.18	-77.94	-77.66	-77.07	-77.68	-62.52	-41.25	21.27
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-77.52	-77.31	-77.51	-77.40	-77.49	-77.35	-77.33	-76.02	-62.18	-41.25	20.93
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-77.30	-77.63	-77.65	-77.50	-77.66	-77.33	-77.63	-77.61	-62.50	-41.25	21.25
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-77.31	-77.69	-77.48	-77.18	-76.99	-76.80	-77.58	-77.48	-62.27	-41.25	21.02

VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-77.31	-77.56	-77.39	-77.66	-77.30	-76.28	-77.75	-77.58	-62.30	-41.25	21.05
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-77.19	-77.79	-77.31	-77.83	-77.57	-76.90	-77.70	-77.30	-62.41	-41.25	21.16
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-77.08	-77.44	-77.71	-77.06	-77.54	-76.71	-77.39	-77.27	-62.23	-41.25	20.98
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-77.82	-76.97							-65.35	-41.25	24.10
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-77.56	-77.42							-68.48	-41.25	27.23
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-77.40	-77.31	-76.63						-61.56	-41.25	20.31
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-77.71	-77.50	-77.27						-64.96	-41.25	23.71
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-76.88	-77.06	-77.53						-66.38	-41.25	25.13
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-77.66	-77.14	-77.27	-77.37					-59.31	-41.25	18.06
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-77.46	-77.01	-77.53	-77.82					-62.41	-41.25	21.16
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-77.73	-77.82	-77.64	-77.43					-64.38	-41.25	23.13
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-77.53	-78.00	-77.50	-77.33					-65.56	-41.25	24.31
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-77.67	-77.43	-77.38	-77.83	-77.54	-77.41			-55.98	-41.25	14.73
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-77.59	-77.65	-77.55	-77.15	-76.93	-77.14			-58.77	-41.25	17.52
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-77.58	-77.09	-77.22	-77.43	-76.89	-76.70			-60.35	-41.25	19.10
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-77.76	-77.53	-76.90	-77.20	-77.55	-77.87			-61.91	-41.25	20.66
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-77.26	-77.44	-77.66	-77.26	-77.15	-77.91			-62.87	-41.25	21.62
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-77.38	-76.67	-77.44	-77.56	-76.94	-77.21			-63.41	-41.25	22.16
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-77.21	-77.79	-77.40	-77.21	-77.49	-77.25	-77.68	-77.43	-53.37	-41.25	12.12
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-77.46	-77.42	-77.46	-77.35	-77.64	-76.94	-77.41	-77.30	-56.32	-41.25	15.07
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-77.72	-77.74	-76.96	-77.21	-77.48	-77.89	-77.15	-77.16	-58.11	-41.25	16.86
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-77.57	-77.65	-77.40	-77.31	-76.96	-76.91	-77.51	-77.31	-59.28	-41.25	18.03
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-76.98	-77.41	-77.31	-77.09	-77.07	-77.50	-77.38	-77.21	-60.17	-41.25	18.92
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-77.38	-77.43	-76.44	-77.65	-77.42	-77.49	-77.36	-77.43	-61.03	-41.25	19.78
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-77.13	-77.26	-77.51	-77.44	-76.92	-77.74	-77.36	-77.66	-61.76	-41.25	20.51
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-77.67	-77.31	-77.18	-77.17	-77.48	-77.35	-76.99	-77.06	-62.24	-41.25	20.99
VHT/HE80, M0 to M9, M0 to M11-STBC	2	6.00	-77.72	-77.39							-68.54	-41.25	27.29
VHT/HE80, M0 to M9, M0 to M11-STBC	3	6.00	-77.24	-77.54	-76.94						-66.46	-41.25	25.21

VHT/HE80, M0 to M9, M0 to M11-STBC	4	6.00	-77.37	-77.30	-77.51	-77.63					-65.43	-41.25	24.18
VHT/HE80, M0 to M9, M0 to M11-STBC	6	6.00	-77.11	-77.30	-77.65	-76.81	-77.51	-77.46			-63.52	-41.25	22.27
VHT/HE80, M0 to M9, M0 to M11-STBC	8	6.00	-77.81	-77.45	-77.49	-77.50	-77.49	-77.38	-77.18	-77.39	-62.43	-41.25	21.18

Test results for Band-edge

5180 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Band-edge (dBm)	Tx 2 Band-edge (dBm)	Tx 3 Band-edge (dBm)	Tx 4 Band-edge (dBm)	Tx 5 Band-edge (dBm)	Tx 6 Band-edge (dBm)	Tx 7 Band-edge (dBm)	Tx 8 Band-edge (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-31.53								-25.53	-21.25	4.28
non HT20, 6 to 54 Mbps	2	6.00	-33.44	-43.60							-27.04	-21.25	5.79
non HT20, 6 to 54 Mbps	3	6.00	-32.54	-40.95	-42.59						-25.59	-21.25	4.34
non HT20, 6 to 54 Mbps	4	6.00	-38.23	-45.16	-41.48	-41.29					-28.87	-21.25	7.62
non HT20, 6 to 54 Mbps	6	9.00	-44.04	-51.39	-51.91	-49.91	-50.67	-49.70			-31.83	-21.25	10.58
non HT20, 6 to 54 Mbps	8	9.00	-49.05	-55.25	-54.93	-54.64	-54.81	-53.80	-53.13	-54.38	-35.19	-21.25	13.94
non HT20, 6 to 54 Mbps-BF	2	9.01	-40.17	-47.76							-30.46	-21.25	9.21
non HT20, 6 to 54 Mbps-BF	3	10.77	-44.58	-51.64	-48.36						-31.73	-21.25	10.48
non HT20, 6 to 54 Mbps-BF	4	12.02	-41.91	-51.65	-50.24	-46.27					-27.80	-21.25	6.55
non HT20, 6 to 54 Mbps-BF	6	13.78	-53.62	-54.98	-54.95	-54.15	-53.98	-53.47			-32.59	-21.25	11.34
non HT20, 6 to 54 Mbps-BF	8	15.03	-55.96	-57.26	-57.27	-56.69	-56.55	-56.54	-56.82	-55.87	-32.53	-21.25	11.28
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-39.68								-33.68	-21.25	12.43
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-40.96	-50.89							-34.54	-21.25	13.29
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-39.01	-50.12							-32.69	-21.25	11.44
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-39.84	-49.48	-48.73						-32.91	-21.25	11.66
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-38.53	-49.03	-49.07						-31.82	-21.25	10.57
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-31.04	-43.30	-41.40						-24.43	-21.25	3.18
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-42.46	-49.17	-51.10	-48.76					-34.46	-21.25	13.21
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-47.13	-50.98	-51.50	-48.35					-37.09	-21.25	15.84
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-37.32	-42.55	-32.90	-39.29					-24.60	-21.25	3.35

HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-38.48	-38.51	-36.28	-32.05					-23.42	-21.25	2.17
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-53.18	-54.47	-54.55	-53.82	-54.19	-53.27			-37.10	-21.25	15.85
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-43.78	-51.68	-53.19	-46.95	-45.75	-45.13			-30.44	-21.25	9.19
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	**6**	**7.51**	**-35.19**	**-38.46**	**-36.63**	**-37.86**	**-36.27**	**-36.66**			**-21.42**	**-21.25**	**0.17**
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-34.15	-39.50	-37.50	-34.45	-36.28	-38.53			-21.63	-21.25	0.38
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-44.00	-51.91	-52.70	-47.50	-46.53	-44.88			-32.66	-21.25	11.41
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-41.69	-50.80	-53.43	-47.43	-47.30	-46.32			-32.52	-21.25	11.27
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-53.41	-56.35	-56.12	-54.17	-55.22	-55.21	-55.10	-55.90	-37.05	-21.25	15.80
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-50.96	-53.44	-54.64	-53.47	-52.93	-52.66	-54.22	-52.88	-34.99	-21.25	13.74
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-36.36	-54.90	-52.15	-42.07	-45.51	-48.62	-50.85	-39.82	-25.27	-21.25	4.02
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-36.43	-54.55	-52.09	-37.70	-44.05	-50.10	-41.99	-50.07	-25.25	-21.25	4.00
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-50.13	-53.58	-52.49	-49.48	-51.15	-52.42	-54.53	-50.55	-35.44	-21.25	14.19
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-48.57	-53.79	-53.15	-50.25	-49.58	-51.81	-52.25	-48.80	-34.99	-21.25	13.74
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-38.91	-39.57	-38.64	-37.47	-39.08	-31.56	-59.69	-40.03	-22.01	-21.25	0.76
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-39.54	-40.03	-38.04	-33.58	-35.92	-38.86	-59.89	-41.23	-22.97	-21.25	1.72
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	2	9.01	-40.13	-50.43							-30.73	-21.25	9.48
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-39.60	-50.67							-33.28	-21.25	12.03
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-47.55	-51.40	-50.76						-34.01	-21.25	12.76
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-44.79	-51.06	-51.69						-35.45	-21.25	14.20
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-40.36	-44.09	-37.13						-28.89	-21.25	7.64
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-49.36	-53.96	-52.72	-50.76					-33.31	-21.25	12.06
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-45.51	-50.85	-51.01	-50.07					-33.66	-21.25	12.41
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-35.42	-39.95	-40.28	-34.61					-23.57	-21.25	2.32
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-37.24	-34.35	-39.94	-36.10					-24.44	-21.25	3.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-53.05	-54.38	-54.08	-52.08	-53.48	-52.93			-31.70	-21.25	10.45
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-49.09	-53.98	-54.49	-50.53	-50.27	-48.53			-32.05	-21.25	10.80
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-37.31	-54.65	-53.80	-38.14	-41.90	-41.72			-24.19	-21.25	2.94
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-36.76	-44.28	-45.44	-34.68	-40.76	-39.37			-23.12	-21.25	1.87

VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-44.01	-51.15	-53.39	-46.69	-47.21	-43.66			-31.89	-21.25	10.64
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-43.71	-51.26	-52.94	-47.46	-43.29	-45.94			-32.37	-21.25	11.12
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-53.72	-56.39	-56.98	-56.45	-55.19	-55.66	-56.40	-55.12	-31.56	-21.25	10.31
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-53.14	-54.70	-54.39	-53.80	-54.10	-53.19	-54.58	-52.64	-32.71	-21.25	11.46
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-45.09	-54.59	-55.12	-49.57	-51.33	-49.03	-42.77	-51.26	-28.64	-21.25	7.39
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-39.08	-54.58	-52.64	-41.03	-44.66	-47.48	-46.84	-50.52	-26.32	-21.25	5.07
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-49.74	-54.23	-54.81	-53.73	-53.19	-50.20	-39.01	-54.34	-29.77	-21.25	8.52
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-49.64	-54.01	-53.66	-49.98	-49.74	-49.74	-53.25	-50.47	-34.68	-21.25	13.43
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-39.64	-46.56	-46.73	-36.41	-37.80	-38.57	-52.14	-36.78	-23.87	-21.25	2.62
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-40.67	-46.78	-38.07	-35.31	-36.71	-38.59	-38.60	-34.89	-22.63	-21.25	1.38
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-40.02	-49.47							-33.55	-21.25	12.30
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-39.27	-51.06	-49.65						-32.63	-21.25	11.38
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-44.42	-50.75	-50.68	-46.61					-35.25	-21.25	14.00
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-44.40	-51.22	-52.46	-48.37	-43.99	-45.62			-32.82	-21.25	11.57
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-51.01	-54.44	-54.33	-53.71	-52.51	-52.51	-52.69	-54.29	-38.00	-21.25	16.75

Please refer to the following plots for the worst case configuration

Ant-a



Date: 18.NOV.2018 18:53:24

Ant-b



Date: 18.NOV.2018 19:40:02

Ant-c



Date: 18.NOV.2018 20:23:44

Ant-d



Date: 18.NOV.2018 21:02:37

Ant-e



Date: 18.NOV.2018 21:34:17

Ant-f



Date: 18.NOV.2018 22:03:38

5180 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Band-edge (dBm)	Tx 2 Band-edge (dBm)	Tx 3 Band-edge (dBm)	Tx 4 Band-edge (dBm)	Tx 5 Band-edge (dBm)	Tx 6 Band-edge (dBm)	Tx 7 Band-edge (dBm)	Tx 8 Band-edge (dBm)	DCCF (dB)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
non HT20, 6 to 54 Mbps	1	6.00	-50.1								0.44	-43.66	-41.25	2.41
non HT20, 6 to 54 Mbps	2	6.00	-51.36	-59.28							0.44	-44.27	-41.25	3.02
non HT20, 6 to 54 Mbps	3	6.00	-52.06	-56.99	-56.85						0.44	-43.44	-41.25	2.19
non HT20, 6 to 54 Mbps	4	6.00	-54.85	-59.54	-58.77	-56.04					0.44	-44.42	-41.25	3.17
non HT20, 6 to 54 Mbps	6	9.00	-59.32	-61.64	-62.04	-60.65	-60.57	-60.46			0.44	-43.47	-41.25	2.22
non HT20, 6 to 54 Mbps	8	9.00	-62.76	-65.06	-64.84	-64.69	-64.00	-63.51	-63.43	-63.56	0.44	-45.44	-41.25	4.19
non HT20, 6 to 54 Mbps-BF	2	9.01	-55.65	-60.35							0.44	-44.93	-41.25	3.68
non HT20, 6 to 54 Mbps-BF	3	10.77	-58.77	-61.88	-61.02						0.44	-44.37	-41.25	3.12
non HT20, 6 to 54 Mbps-BF	4	12.02	-62.227	-61.52	-61.11	-60.76					0.44	-42.89	-41.25	1.64
non HT20, 6 to 54 Mbps-BF	6	13.78	-65.814	-65.26	-64.86	-64.67	-64.65	-63.89			0.44	-42.82	-41.25	1.57
non HT20, 6 to 54 Mbps-BF	8	15.03	-66.80	-65.89	-65.89	-65.89	-65.89	-65.89	-65.89	-65.89	0.44	-41.49	-41.25	0.24
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	1	6.00	-52.08								0.44	-45.64	-41.25	4.39
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	2	6.00	-52.16	-60.25							0.44	-45.09	-41.25	3.84
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	2	6.00	-51.89	-59.89							0.44	-44.81	-41.25	3.56
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	3	6.00	-52.03	-59.22	-59.21						0.44	-44.18	-41.25	2.93
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	3	6.00	-51.06	-60.03	-59.07						0.44	-43.53	-41.25	2.28
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	3	6.00	-51.59	-58.08	-57.44						0.44	-43.43	-41.25	2.18
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	4	6.00	-56.84	-60.43	-61.27	-58.70					0.44	-46.51	-41.25	5.26
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	4	6.00	-57.06	-60.62	-60.73	-59.10					0.44	-46.65	-41.25	5.40
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	4	6.00	-55.34	-59.67	-57.32	-56.09					0.44	-44.36	-41.25	3.11
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	4	6.00	-55.34	-59.27	-59.60	-55.33					0.44	-44.46	-41.25	3.21

HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	6	9.00	-63.00	-64.89	-64.53	-63.75	-63.48	-63.52			0.44	-46.59	-41.25	5.34
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	6	8.39	-61.407	-60.82	-63.15	-57.72	-57.62	-56.81			0.44	-42.40	-41.25	1.15
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	6	7.51	-60.695	-59.80	-61.02	-57.46	-57.73	-57.53			0.44	-43.05	-41.25	1.80
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	6	6.88	-61.055	-59.76	-61.43	-58.18	-58.05	-57.95			0.44	-44.08	-41.25	2.83
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	6	6.40	-55.55	-60.58	-62.85	-58.19	-57.19	-56.76			0.44	-43.29	-41.25	2.04
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	6	6.00	-55.68	-60.68	-63.13	-57.97	-56.85	-56.24			0.44	-43.52	-41.25	2.27
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1	8	9.00	-62.79	-66.75	-66.61	-64.87	-65.22	-65.61	-64.62	-65.23	0.44	-46.58	-41.25	5.33
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2	8	9.00	-60.21	-64.26	-64.31	-63.23	-62.03	-62.63	-63.66	-62.78	0.44	-44.22	-41.25	2.97
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3	8	8.13	-59.89	-64.45	-63.61	-62.16	-62.37	-62.09	-60.66	-62.84	0.44	-44.44	-41.25	3.19
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4	8	7.51	-60.42	-64.59	-63.93	-62.80	-61.76	-62.84	-70.77	-62.77	0.44	-46.05	-41.25	4.80
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5	8	7.02	-59.38	-63.52	-63.97	-60.15	-61.10	-62.22	-63.79	-60.14	0.44	-44.96	-41.25	3.71
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6	8	6.62	-59.51	-63.89	-64.08	-60.67	-60.17	-62.20	-70.82	-59.76	0.44	-45.55	-41.25	4.30
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7	8	6.29	-55.67	-64.01	-62.70	-58.00	-58.97	-59.04	-70.70	-60.66	0.44	-43.88	-41.25	2.63
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8	8	6.00	-56.74	-64.08	-62.24	-58.13	-58.45	-59.59	-70.79	-60.44	0.44	-44.44	-41.25	3.19
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	**2**	**9.01**	**-51.30**	**-60.33**							**0.44**	**-41.34**	**-41.25**	**0.09**
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	2	6.00	-52.03	-60.06							0.44	-44.96	-41.25	3.71
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	3	10.77	-57.34	-61.42	-61.31						0.44	-43.60	-41.25	2.35
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	3	7.76	-57.38	-60.69	-61.78						0.44	-46.56	-41.25	5.31
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	3	6.00	-55.75	-59.05	-59.43						0.44	-46.53	-41.25	5.28
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	4	12.02	-62.132	-63.67	-63.01	-60.10					0.44	-43.53	-41.25	2.28
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	4	9.01	-56.72	-61.13	-61.03	-59.81					0.44	-43.80	-41.25	2.55
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	4	7.25	-56.43	-62.85	-62.89	-59.35					0.44	-45.81	-41.25	4.56
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	4	6.00	-55.43	-60.56	-59.03	-55.21					0.44	-44.53	-41.25	3.28
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	6	13.78	-65.481	-65.00	-64.63	-63.48	-63.73	-63.62			0.44	-42.26	-41.25	1.01
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	6	10.77	-61.622	-64.11	-63.39	-59.49	-61.55	-59.10			0.44	-42.17	-41.25	0.92
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	6	9.01	-60.08	-65.20	-64.15	-61.62	-62.68	-61.92			0.44	-45.06	-41.25	3.81

HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	6	7.76	-61.583	-64.27	-62.99	-58.76	-58.70	-56.37			0.44	-43.63	-41.25	2.38
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	6	6.79	-57.69	-61.62	-62.74	-58.40	-57.11	-56.46			0.44	-43.44	-41.25	2.19
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	6	6.00	-55.30	-61.39	-62.78	-58.10	-57.41	-56.65			0.44	-43.68	-41.25	2.43
HT/VHT/HE20, M0 to M7, M0.1 to M8.1, M0.1 to M11.1-BF	8	15.03	-66.169	-67.32	-66.92	-67.06	-65.53	-65.64	-66.88	-65.83	0.44	-41.87	-41.25	0.62
HT/VHT/HE20, M8 to M15, M0.2 to M8.2, M0.2 to M11.2-BF	8	12.02	-65.432	-64.78	-64.71	-63.98	-64.08	-62.81	-64.25	-62.92	0.44	-42.55	-41.25	1.30
HT/VHT/HE20, M16 to M23, M0.3 to M8.3, M0.3 to M11.3-BF	8	10.26	-62.79	-65.18	-64.77	-63.80	-63.75	-63.28	-63.94	-63.22	0.44	-44.05	-41.25	2.80
HT/VHT/HE20, M24 to M31, M0.4 to M8.4, M0.4 to M11.4-BF	8	9.01	-60.78	-64.79	-64.54	-62.50	-61.74	-61.60	-63.41	-63.13	0.44	-44.13	-41.25	2.88
VHT/HE20, M0.5 to M8.5, M0.5 to M11.5-BF	8	8.04	-60.07	-64.09	-64.56	-63.64	-62.75	-62.30	-62.00	-62.79	0.44	-45.05	-41.25	3.80
VHT/HE20, M0.6 to M8.6, M0.6 to M11.6-BF	8	7.25	-59.32	-63.92	-64.19	-59.90	-61.78	-59.04	-62.24	-59.88	0.44	-44.17	-41.25	2.92
VHT/HE20, M0.7 to M8.7, M0.7 to M11.7-BF	8	6.58	-56.49	-64.09	-63.62	-58.15	-58.64	-58.53	-61.87	-59.87	0.44	-43.41	-41.25	2.16
VHT/HE20, M0.8 to M8.8, M0.8 to M11.8-BF	8	6.00	-56.26	-63.90	-63.69	-59.25	-58.55	-58.18	-59.12	-60.78	0.44	-43.84	-41.25	2.59
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	2	6.00	-52.08	-60.45							0.44	-45.05	-41.25	3.80
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	3	6.00	-51.96	-60.95	-59.11						0.44	-44.32	-41.25	3.07
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	4	6.00	-56.40	-61.11	-61.10	-59.21					0.44	-46.53	-41.25	5.28
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	6	6.00	-56.56	-61.33	-62.84	-58.58	-56.80	-56.69			0.44	-43.98	-41.25	2.73
HT/VHT/HE20, M0 to M7, M0 to M8, M0 to M11-STBC	8	6.00	-59.85	-64.21	-63.56	-63.53	-62.91	-62.72	-61.92	-62.92	0.44	-47.03	-41.25	5.78

Please refer to the following plots for the worst case configuration

Ant-a



Date: 18.NOV.2018 19:01:24

Ant-b



Date: 18.NOV.2018 19:48:28

5190 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Band-edge (dBm)	Tx 2 Band-edge (dBm)	Tx 3 Band-edge (dBm)	Tx 4 Band-edge (dBm)	Tx 5 Band-edge (dBm)	Tx 6 Band-edge (dBm)	Tx 7 Band-edge (dBm)	Tx 8 Band-edge (dBm)	Total (dBm)	FCC Peak Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-38.38								-32.38	-21.25	11.13
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-40.38	-42.79							-32.41	-21.25	11.16
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-42.29	-43.13							-33.68	-21.25	12.43
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-40.65	-46.05	-45.56						-32.58	-21.25	11.33
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-42.61	-45.45	-46.96						-33.85	-21.25	12.60
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-31.64	-42.25	-42.97						-25.00	-21.25	3.75
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-45.37	-45.66	-48.99	-43.73					-33.54	-21.25	12.29
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-44.46	-45.33	-49.52	-44.08					-33.38	-21.25	12.13
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-40.24	-44.33	-44.35	-36.66					-28.16	-21.25	6.91
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-39.67	-47.07	-46.18	-41.12					-30.40	-21.25	9.15
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	9.00	-44.71	-45.61	-47.23	-44.25	-45.54	-47.71			-28.89	-21.25	7.64
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	8.39	-43.14	-46.59	-48.88	-43.80	-45.77	-49.44			-29.49	-21.25	8.24
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	7.51	-45.63	-48.02	-35.65	-46.57	-44.20	-36.17			-24.59	-21.25	3.34
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.88	-42.70	-43.75	-45.21	-42.77	-44.66	-33.76			-25.10	-21.25	3.85
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.40	-47.84	-48.97	-50.76	-45.90	-45.11	-50.82			-33.50	-21.25	12.25
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-35.39	-45.86	-45.85	-42.81	-42.83	-47.15			-27.33	-21.25	6.08
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	9.00	-44.49	-47.49	-49.99	-45.01	-42.04	-47.92	-46.69	-47.57	-27.73	-21.25	6.48
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	9.00	-41.72	-48.05	-51.48	-46.98	-47.56	-48.10	-47.66	-48.73	-28.60	-21.25	7.35
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	8.13	-46.34	-36.79	-35.89	-44.73	-44.48	-45.43	-46.68	-35.89	-22.49	-21.25	1.24
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	7.51	-45.47	-37.08	-36.64	-46.70	-45.84	-40.69	-47.63	-36.90	-23.48	-21.25	2.23
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	7.02	-49.62	-51.22	-51.44	-47.62	-46.46	-50.40	-50.26	-49.61	-33.20	-21.25	11.95

VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.62	-45.28	-47.64	-50.52	-44.56	-47.78	-47.32	-45.43	-47.02	-30.96	-21.25	9.71
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.29	-46.49	-48.90	-51.33	-44.59	-48.27	-44.66	-47.23	-46.81	-31.50	-21.25	10.25
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-41.25	-38.05	-34.15	-45.15	-41.69	-45.47	-47.27	-32.80	-22.91	-21.25	1.66
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-44.27	-46.63							-33.27	-21.25	12.02
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-43.11	-44.72							-34.83	-21.25	13.58
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-47.18	-47.87	-48.98						-32.40	-21.25	11.15
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-44.92	-47.18	-48.16						-34.01	-21.25	12.76
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-31.77	-42.82	-35.74						-24.07	-21.25	2.82
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-48.25	-50.80	-51.39	-48.91					-31.61	-21.25	10.36
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-47.54	-48.74	-49.48	-47.42					-33.18	-21.25	11.93
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-42.15	-44.44	-44.58	-32.62					-24.43	-21.25	3.18
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-37.06	-39.86	-38.61	-35.69					-25.50	-21.25	4.25
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-52.15	-54.35	-54.87	-53.49	-52.35	-53.65			-31.80	-21.25	10.55
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-50.05	-50.18	-52.51	-51.52	-52.23	-54.61			-33.04	-21.25	11.79
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-42.27	-44.66	-49.10	-45.58	-45.57	-35.26			-24.37	-21.25	3.12
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-42.95	-43.13	-39.32	-38.98	-44.23	-33.30			-22.96	-21.25	1.71
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-45.23	-45.36	-43.73	-44.45	-41.87	-48.25			-29.84	-21.25	8.59
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-38.02	-44.40	-37.67	-38.15	-40.82	-42.69			-25.84	-21.25	4.59
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-54.75	-55.07	-55.89	-56.41	-56.60	-54.35	-55.85	-54.92	-31.35	-21.25	10.10
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-52.45	-54.30	-55.58	-52.94	-52.87	-53.89	-54.65	-54.17	-32.70	-21.25	11.45
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-44.38	-44.15	-44.45	-38.51	-41.16	-40.69	-42.92	-50.09	-22.14	-21.25	1.73
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-39.38	-46.96	-38.22	-51.76	-51.95	-39.14	-41.08	-43.39	-23.63	-21.25	2.38
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-48.73	-51.03	-51.74	-47.34	-48.58	-47.56	-49.55	-49.70	-31.98	-21.25	10.73
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-43.72	-49.65	-50.15	-45.61	-45.12	-47.68	-47.99	-46.74	-30.31	-21.25	9.06
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-46.48	-47.46	-49.71	-45.45	-48.27	-46.36	-48.78	-48.29	-31.78	-21.25	10.53
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-40.29	-46.55	-46.10	-37.42	-38.12	-42.95	-38.86	-44.68	-25.61	-21.25	4.36
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	-35.33	-42.52							-28.57	-21.25	7.32
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	-39.92	-44.55	-43.89						-31.50	-21.25	10.25

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	-42.78	-44.52	-45.50	-40.88					-31.03	-21.25	9.78
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	-44.60	-47.45	-46.01	-42.98	-43.42	-48.48			-31.27	-21.25	10.02
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	-41.27	-50.11	-47.89	-46.55	-47.27	-47.26	-48.96	-48.02	-31.24	-21.25	9.99

5190 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Band-edge (dBm)	Tx 2 Band-edge (dBm)	Tx 3 Band-edge (dBm)	Tx 4 Band-edge (dBm)	Tx 5 Band-edge (dBm)	Tx 6 Band-edge (dBm)	Tx 7 Band-edge (dBm)	Tx 8 Band-edge (dBm)	DCCF (dB)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-48.85								0.36	-42.49	-41.25	1.24
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-51.21	-53.68							0.36	-42.90	-41.25	1.65
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-51.97	-54.71							0.36	-43.76	-41.25	2.51
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-52.65	-56.43	-58.04						0.36	-43.97	-41.25	2.72
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-52.83	-56.07	-57.55						0.36	-43.89	-41.25	2.64
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-53.03	-56.21	-58.02						0.36	-44.12	-41.25	2.87
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-55.13	-56.57	-58.72	-54.19					0.36	-43.46	-41.25	2.21
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-54.93	-56.76	-58.87	-53.98					0.36	-43.38	-41.25	2.13
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-56.01	-57.60	-59.08	-54.74					0.36	-44.18	-41.25	2.93
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-55.69	-57.46	-59.02	-55.07					0.36	-44.17	-41.25	2.92
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-56.47	-57.74	-58.59	-54.14	-57.09	-58.77			0.36	-42.68	-41.25	1.43
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-56.83	-59.34	-58.35	-54.59	-56.81	-58.80			0.36	-43.00	-41.25	1.75
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-57.34	-59.68	-58.47	-57.56	-59.61	-60.36			0.36	-44.55	-41.25	3.30
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-56.48	-57.06	-58.16	-55.06	-56.87	-56.00			0.36	-42.36	-41.25	1.11
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-57.58	-59.60	-61.10	-56.88	-58.10	-62.24			0.36	-44.71	-41.25	3.46
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-57.96	-57.12	-58.94	-54.98	-55.94	-59.07			0.36	-42.93	-41.25	1.68
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-57.98	-59.15	-61.07	-56.53	-58.52	-59.33	-57.68	-58.09	0.36	-42.98	-41.25	1.73
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-58.26	-58.91	-61.05	-58.78	-58.36	-58.80	-57.96	-58.32	0.36	-43.33	-41.25	2.08
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-58.46	-58.21	-56.18	-57.69	-58.74	-58.76	-58.92	-57.32	0.36	-42.55	-41.25	1.30
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-58.64	-58.87	-61.07	-57.92	-58.17	-58.36	-59.29	-56.96	0.36	-43.13	-41.25	1.88
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-58.95	-61.12	-62.64	-58.73	-60.14	-60.92	-59.25	-60.54	0.36	-44.73	-41.25	3.48
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-57.22	-59.24	-61.07	-57.82	-58.89	-59.27	-58.52	-58.80	0.36	-43.34	-41.25	2.09

VHT/HE40, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-57.47	-59.23	-61.31	-57.43	-58.45	-59.24	-58.56	-59.21	0.36	-43.33	-41.25	2.08
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-58.73	-58.77	-56.63	-57.82	-58.47	-58.36	-58.16	-55.85	0.36	-42.34	-41.25	1.09
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-55.28	-57.42							0.36	-43.84	-41.25	2.59
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-53.38	-56.09							0.36	-45.16	-41.25	3.91
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-58.06	-59.93	-60.36						0.36	-43.43	-41.25	2.18
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-56.03	-57.80	-58.65						0.36	-44.46	-41.25	3.21
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-53.12	-56.39	-55.86						0.36	-43.74	-41.25	2.49
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-60.12	-60.59	-60.92	-59.26					0.36	-41.78	-41.25	0.53
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-58.39	-59.24	-60.75	-56.36					0.36	-43.00	-41.25	1.75
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-56.04	-57.34	-58.85	-54.69					0.36	-42.83	-41.25	1.58
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-55.96	-55.33	-56.11	-54.84					0.36	-43.15	-41.25	1.90
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-63.24	-64.08	-64.53	-63.35	-64.36	-64.93			0.36	-42.12	-41.25	0.87
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-61.00	-62.72	-62.72	-61.50	-62.03	-64.17			0.36	-43.33	-41.25	2.08
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-59.93	-59.55	-59.31	-57.82	-59.23	-59.44			0.36	-42.01	-41.25	0.76
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-58.59	-57.37	-61.36	-56.83	-57.14	-56.85			0.36	-41.87	-41.25	0.62
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-56.87	-57.20	-56.58	-55.00	-56.68	-62.51			0.36	-42.05	-41.25	0.80
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-58.32	-58.32	-58.24	-54.86	-54.49	-56.84			0.36	-42.39	-41.25	1.14
HT/VHT/HE40, M0 to M7, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-65.95	-66.60	-66.97	-66.40	-65.84	-66.16	-66.23	-65.88	0.36	-41.82	-41.25	0.57
HT/VHT/HE40, M8 to M15, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-63.41	-64.78	-65.40	-63.48	-63.96	-64.25	-64.51	-63.90	0.36	-42.76	-41.25	1.51
HT/VHT/HE40, M16 to M23, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-62.38	-61.84	-62.21	-61.36	-59.25	-61.82	-61.75	-61.48	0.36	-41.75	-41.25	0.50
HT/VHT/HE40, M24 to M31, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-60.27	-61.66	-61.88	-59.18	-59.09	-59.53	-60.23	-59.49	0.36	-41.65	-41.25	0.40
VHT/HE40, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-60.17	-61.46	-61.72	-59.44	-59.86	-59.22	-60.73	-60.56	0.36	-42.88	-41.25	1.63
VHT/HE40, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-60.35	-60.57	-60.94	-57.88	-59.65	-58.81	-59.25	-58.86	0.36	-42.79	-41.25	1.54
VHT/HE40, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-58.12	-60.69	-61.19	-57.28	-58.88	-58.45	-58.94	-59.10	0.36	-42.95	-41.25	1.70
VHT/HE40, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-55.95	-58.37	-59.08	-56.34	-56.30	-56.30	-57.30	-59.91	0.36	-41.84	-41.25	0.59
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	2	6.00	-51.96	-53.73							0.36	-43.39	-41.25	2.14
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	3	6.00	-53.16	-55.07	-55.22						0.36	-43.25	-41.25	2.00
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	4	6.00	-53.89	-55.63	-55.88	-52.63					0.36	-41.92	-41.25	0.67

HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	6	6.00	-56.35	-57.40	-56.46	-54.26	-55.36	-59.94			0.36	-42.16	-41.25	0.91
HT/VHT/HE40, M0 to M7, M0 to M9, M0 to M11-STBC	8	6.00	-57.89	-59.57	-60.39	-57.06	-57.86	-57.88	-58.70	-60.00	0.36	-43.14	-41.25	1.89

5210 MHz (Peak):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Band-edge (dBm)	Tx 2 Band-edge (dBm)	Tx 3 Band-edge (dBm)	Tx 4 Band-edge (dBm)	Tx 5 Band-edge (dBm)	Tx 6 Band-edge (dBm)	Tx 7 Band-edge (dBm)	Tx 8 Band-edge (dBm)	Total (dBm)	FCC PeaK Limit (dBm)	Margin (dB)
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-37.40								-31.40	-21.25	10.15
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-40.51	-43.26							-32.66	-21.25	11.41
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-40.28	-43.35							-32.54	-21.25	11.29
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-41.58	-45.09	-45.17						-32.83	-21.25	11.58
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-43.22	-45.37	-45.69						-33.84	-21.25	12.59
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-36.62	-33.85	-38.92						-25.20	-21.25	3.95
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-40.46	-47.29	-46.85	-44.88					-31.91	-21.25	10.66
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-43.55	-46.88	-49.79	-47.14					-34.25	-21.25	13.00
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-41.85	-35.69	-39.92	-43.73					-27.19	-21.25	5.94
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-41.19	-37.91	-39.27	-44.73					-28.09	-21.25	6.84
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-48.19	-50.75	-51.69	-52.00	-53.35	-51.32			-37.13	-21.25	15.88
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-48.41	-52.11	-52.52	-53.17	-53.22	-51.45			-37.67	-21.25	16.42
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-41.91	-49.05	-43.90	-48.65	-43.94	-41.78			-30.23	-21.25	8.98
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-43.98	-48.56	-44.57	-46.66	-45.63	-43.47			-31.38	-21.25	10.13
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-45.21	-46.96	-46.61	-48.12	-42.79	-41.05			-30.60	-21.25	9.35
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-42.63	-46.48	-46.16	-45.97	-44.47	-41.00			-30.17	-21.25	8.92
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-45.43	-50.78	-52.29	-50.75	-50.38	-52.49	-52.40	-54.02	-35.20	-21.25	13.95
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-49.54	-50.76	-52.43	-49.41	-52.64	-52.45	-52.66	-55.13	-36.49	-21.25	15.24
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-44.00	-50.27	-39.86	-48.23	-48.44	-47.38	-50.52	-51.72	-30.66	-21.25	9.41
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-47.50	-49.51	-39.93	-44.96	-52.99	-50.41	-50.76	-39.71	-29.34	-21.25	8.09
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-47.28	-50.42	-52.90	-47.83	-50.61	-48.71	-50.50	-39.91	-31.39	-21.25	10.14

VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-48.27	-51.30	-39.32	-47.99	-51.18	-52.17	-45.64	-51.76	-30.93	-21.25	9.68
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-47.83	-50.49	-39.44	-49.89	-52.85	-52.70	-51.39	-53.11	-31.64	-21.25	10.39
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-47.80	-48.39	-35.54	-48.19	-49.91	-48.42	-47.71	-42.85	-27.78	-21.25	6.53
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-46.91	-48.30							-35.53	-21.25	14.28
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-38.20	-43.51							-31.08	-21.25	9.83
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-49.26	-51.19	-53.95						-35.52	-21.25	14.27
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-47.11	-49.04	-53.08						-36.58	-21.25	15.33
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-38.30	-34.55	-42.55						-26.56	-21.25	5.31
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-48.53	-54.15	-56.69	-54.45					-34.25	-21.25	13.00
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-50.41	-50.76	-53.75	-50.67					-36.18	-21.25	14.93
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-41.75	-47.94	-46.47	-36.90					-27.84	-21.25	6.59
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-42.42	-37.71	-34.74	-43.75					-26.19	-21.25	4.94
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-55.79	-57.83	-58.41	-58.40	-48.08	-57.44			-32.32	-21.25	11.07
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-52.72	-51.14	-57.75	-54.77	-56.35	-55.72			-35.60	-21.25	14.35
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-41.83	-40.79	-46.41	-47.00	-55.84	-39.61			-26.16	-21.25	4.91
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-47.88	-47.45	-42.40	-49.62	-52.91	-54.52			-31.77	-21.25	10.52
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-45.90	-47.22	-51.33	-44.78	-43.62	-50.18			-31.80	-21.25	10.55
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-44.48	-45.97	-53.85	-42.79	-46.41	-49.36			-32.18	-21.25	10.93
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-58.69	-58.71	-58.29	-57.80	-58.81	-58.53	-58.48	-57.81	-34.31	-21.25	13.06
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-55.86	-58.72	-57.65	-58.84	-55.69	-55.91	-56.76	-58.63	-36.02	-21.25	14.77
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-43.59	-58.43	-57.99	-58.33	-44.57	-47.97	-44.36	-58.71	-28.37	-21.25	7.12
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-45.14	-57.97	-57.72	-58.12	-44.49	-45.84	-44.79	-58.37	-29.79	-21.25	8.54
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-48.50	-49.36	-38.45	-48.59	-49.67	-47.48	-50.29	-53.42	-28.44	-21.25	7.19
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-47.96	-51.60	-53.72	-49.75	-48.44	-47.11	-50.51	-52.44	-33.40	-21.25	12.15
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-48.52	-49.64	-54.05	-46.92	-50.66	-48.94	-47.27	-51.41	-33.57	-21.25	12.32
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-48.54	-48.32	-53.34	-46.61	-48.79	-50.35	-48.89	-39.47	-30.91	-21.25	9.66
VHT/HE80, M0 to M9, M0 to M11-STBC	2	6.00	-39.66	-44.12							-32.33	-21.25	11.08
VHT/HE80, M0 to M9, M0 to M11-STBC	3	6.00	-42.72	-44.47	-47.71						-33.74	-21.25	12.49

VHT/HE80, M0 to M9, M0 to M11-STBC	4	6.00	-42.01	-45.70	-49.21	-47.23					-33.18	-21.25	11.93
VHT/HE80, M0 to M9, M0 to M11-STBC	6	6.00	-45.32	-46.42	-50.03	-48.35	-50.70	-51.51			-34.35	-21.25	13.10
VHT/HE80, M0 to M9, M0 to M11-STBC	8	6.00	-50.30	-53.09	-50.56	-53.38	-52.54	-51.92	-50.79	-54.71	-36.90	-21.25	15.65

5210 MHz (Average):

Mode	Tx paths	correlated antenna gain (dBi)	Tx 1 Band-edge (dBm)	Tx 2 Band-edge (dBm)	Tx 3 Band-edge (dBm)	Tx 4 Band-edge (dBm)	Tx 5 Band-edge (dBm)	Tx 6 Band-edge (dBm)	Tx 7 Band-edge (dBm)	Tx 8 Band-edge (dBm)	DCCF (dB)	Total (dBm)	FCC Average Limit (dBm)	Margin (dB)
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	1	6.00	-54.88								0.44	-48.44	-41.25	7.19
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	2	6.00	-55.16	-54.47							0.44	-45.35	-41.25	4.10
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	2	6.00	-70.78	-54.03							0.44	-47.50	-41.25	6.25
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	3	6.00	-52.41	-56.11	-57.39						0.44	-43.55	-41.25	2.30
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	3	6.00	-53.11	-56.15	-68.91						0.44	-44.84	-41.25	3.59
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	3	6.00	-58.40	-53.18	-55.07						0.44	-43.84	-41.25	2.59
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	4	6.00	-54.98	-56.81	-59.70	-57.22					0.44	-44.41	-41.25	3.16
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	4	6.00	-55.56	-57.63	-60.36	-57.48					0.44	-44.98	-41.25	3.73
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	4	6.00	-59.45	-55.15	-57.26	-55.97					0.44	-44.22	-41.25	2.97
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	4	6.00	-56.13	-55.23	-56.99	-55.79					0.44	-43.53	-41.25	2.28
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	6	6.00	-60.65	-61.32	-62.83	-62.98	-63.85	-62.01			0.44	-47.92	-41.25	6.67
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	6	6.00	-59.49	-61.23	-62.51	-62.86	-63.80	-62.14			0.44	-47.56	-41.25	6.31
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	6	6.00	-57.53	-60.01	-60.33	-61.14	-62.04	-60.06			0.44	-45.73	-41.25	4.48
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	6	6.00	-57.55	-59.75	-61.01	-61.33	-62.60	-60.24			0.44	-45.89	-41.25	4.64
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	6	6.00	-57.84	-59.60	-60.33	-60.68	-62.21	-59.39			0.44	-45.58	-41.25	4.33
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	6	6.00	-57.03	-59.94	-60.54	-61.00	-61.95	-59.28			0.44	-45.44	-41.25	4.19
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1	8	6.00	-66.24	-61.84	-63.47	-61.59	-63.95	-62.36	-62.62	-64.83	0.44	-47.66	-41.25	6.41
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2	8	6.00	-60.01	-61.26	-63.90	-61.19	-63.75	-62.78	-65.06	-64.49	0.44	-47.00	-41.25	5.75
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3	8	6.00	-60.48	-65.38	-59.07	-62.01	-63.58	-63.13	-62.63	-64.71	0.44	-46.69	-41.25	5.44
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4	8	6.00	-60.59	-61.91	-58.83	-61.76	-64.00	-63.04	-63.19	-60.44	0.44	-45.95	-41.25	4.70
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5	8	6.00	-60.67	-62.14	-64.39	-62.07	-64.44	-69.27	-62.64	-60.65	0.44	-47.19	-41.25	5.94
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6	8	6.00	-60.73	-62.10	-58.79	-61.76	-64.38	-63.41	-62.67	-64.93	0.44	-46.46	-41.25	5.21

VHT/HE80, M0.7 to M9.7, M0.7 to M11.7	8	6.00	-60.65	-66.18	-58.83	-61.69	-63.92	-62.92	-62.89	-64.90	0.44	-46.71	-41.25	5.46
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8	8	6.00	-60.59	-63.72	-59.23	-61.83	-63.80	-62.90	-62.88	-61.15	0.44	-46.27	-41.25	5.02
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	2	9.01	-57.05	-59.83							0.44	-45.76	-41.25	4.51
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	2	6.00	-53.64	-54.74							0.44	-44.70	-41.25	3.45
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	3	10.77	-60.23	-62.09	-64.97						0.44	-46.04	-41.25	4.79
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	3	7.76	-57.42	-59.53	-63.01						0.44	-46.45	-41.25	5.20
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	3	6.00	-58.39	-55.16	-56.99						0.44	-45.43	-41.25	4.18
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	4	12.02	-62.48	-64.21	-66.40	-65.04					0.44	-45.82	-41.25	4.57
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	4	9.01	-60.12	-65.67	-64.01	-61.32					0.44	-46.79	-41.25	5.54
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	4	7.25	-58.45	-59.46	-62.36	-58.34					0.44	-45.68	-41.25	4.43
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	4	6.00	-56.78	-54.19	-55.92	-55.38					0.44	-43.00	-41.25	1.75
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	6	13.78	-65.69	-69.12	-68.84	-68.74	-66.97	-69.69			0.44	-45.94	-41.25	4.69
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	6	10.77	-64.23	-63.25	-67.56	-65.83	-69.92	-65.88			0.44	-46.62	-41.25	5.37
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	6	9.01	-60.29	-59.92	-66.71	-63.64	-68.88	-62.29			0.44	-45.34	-41.25	4.09
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	6	7.76	-61.85	-60.85	-63.26	-62.47	-64.07	-64.61			0.44	-46.68	-41.25	5.43
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	6	6.79	-59.05	-58.77	-64.87	-60.12	-62.31	-62.49			0.44	-45.76	-41.25	4.51
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	6	6.00	-59.17	-58.81	-64.73	-59.32	-62.15	-62.26			0.44	-46.37	-41.25	5.12
VHT/HE80, M0.1 to M9.1, M0.1 to M11.1-BF	8	15.03	-68.03	-69.58	-68.98	-69.13	-67.61	-68.88	-68.69	-68.79	0.44	-44.17	-41.25	2.92
VHT/HE80, M0.2 to M9.2, M0.2 to M11.2-BF	8	12.02	-65.81	-69.84	-68.86	-68.86	-66.62	-70.65	-66.24	-68.95	0.44	-46.42	-41.25	5.17
VHT/HE80, M0.3 to M9.3, M0.3 to M11.3-BF	8	10.26	-63.77	-69.39	-69.03	-68.28	-63.16	-64.70	-62.81	-68.53	0.44	-45.69	-41.25	4.44
VHT/HE80, M0.4 to M9.4, M0.4 to M11.4-BF	8	9.01	-63.95	-69.26	-69.36	-68.74	-63.73	-66.88	-63.22	-68.90	0.44	-47.53	-41.25	6.28
VHT/HE80, M0.5 to M9.5, M0.5 to M11.5-BF	8	8.04	-60.49	-61.75	-58.79	-61.93	-64.09	-63.09	-62.92	-64.86	0.44	-44.32	-41.25	3.07
VHT/HE80, M0.6 to M9.6, M0.6 to M11.6-BF	8	7.25	-60.62	-62.02	-64.20	-62.16	-63.94	-63.02	-62.77	-65.17	0.44	-46.06	-41.25	4.81
VHT/HE80, M0.7 to M9.7, M0.7 to M11.7-BF	8	6.58	-60.83	-61.97	-67.05	-61.95	-63.98	-63.22	-62.79	-65.04	0.44	-46.95	-41.25	5.70
VHT/HE80, M0.8 to M9.8, M0.8 to M11.8-BF	8	6.00	-60.46	-61.99	-64.68	-61.76	-65.82	-63.01	-62.94	-64.66	0.44	-47.38	-41.25	6.13
VHT/HE80, M0 to M9, M0 to M11-STBC	2	6.00	-56.80	-54.49							0.44	-46.04	-41.25	4.79
VHT/HE80, M0 to M9, M0 to M11-STBC	3	6.00	-52.42	-55.20	-58.44						0.44	-43.48	-41.25	2.23
VHT/HE80, M0 to M9, M0 to M11-STBC	4	6.00	-54.90	-56.94	-70.77	-57.18					0.44	-44.95	-41.25	3.70

VHT/HE80, M0 to M9, M0 to M11-STBC	6	6.00	-58.10	-59.41	-60.32	-58.88	-62.05	-61.89			0.44	-45.64	-41.25	4.39
VHT/HE80, M0 to M9, M0 to M11-STBC	8	6.00	-61.14	-63.71	-61.36	-63.66	-63.70	-63.11	-62.59	-64.64	0.44	-47.36	-41.25	6.11

--- END OF REPORT ---