

Test Report No.50177430 001

Appendix D: Radiated and Mains Spurious Emission Data



(File: 50177430 001 AppendixD)

Contents



Spurious Emissions, Band Edges, 2.35-2.5G	3
Spurious Emissions, TX Mode, 1-18G	15
Spurious Emissions, TX Mode, 18-26G	33
Spurious Emissions, TX Mode, 30M-1G	51
Spurious Emissions, TX Mode, 9k-30M	53
Spurious Emissions, RX Mode, 1-18G.....	55
Spurious Emissions, RX Mode, 18-26G.....	57
Spurious Emissions, RX Mode, 30M-1G	59
Spurious Emissions, RX Mode, 9K-30M	61

Radiated Bandedge 11b

Low Channel (Hor)





Low Channel (Ver)




Radiated Bandedge 11b


High Channel (Hor)



High Channel (Ver)





Date: 28.JUN.2018 21:00:07





Date: 28.JUN.2018 20:59:44

Radiated Bandedge 11g

Low Channel (Hor)





Low Channel (Ver)





Radiated Bandedge 11g

High Channel (Hor)





High Channel (Ver)





Radiated Bandedge 11n

Low Channel (Hor)





Low Channel (Ver)





Radiated Bandedge 11n

High Channel (Hor)



High Channel (Ver)




Spurious Emissions, TX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:39:04
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-3.34	48.05	44.71	74.00	-29.29	peak	100	205	
2	7236.000	4.38	45.14	49.52	74.00	-24.48	peak	100	47	
3	9313.000	5.60	44.09	49.69	74.00	-24.31	peak	100	300	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:40:07
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-3.34	52.59	49.25	74.00	-24.75	peak	100	36	
2	7236.000	4.38	45.36	49.74	74.00	-24.26	peak	100	25	
3	8990.000	5.65	44.51	50.16	74.00	-23.84	peak	100	158	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:42:58
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-3.26	50.18	46.92	74.00	-27.08	peak	100	308	
2	7311.000	4.56	44.53	49.09	74.00	-24.91	peak	100	20	
3	9058.000	5.64	44.67	50.31	74.00	-23.69	peak	100	297	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:44:01
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-3.26	54.90	51.64	74.00	-22.36	peak	100	204	
2	7311.000	4.56	43.91	48.47	74.00	-25.53	peak	100	147	
3	9007.000	5.64	44.81	50.45	74.00	-23.55	peak	100	136	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:47:09
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-3.18	52.26	49.08	74.00	-24.92	peak	100	3	
2	7386.000	4.73	43.99	48.72	74.00	-25.28	peak	100	201	
3	9789.000	5.07	46.27	51.34	74.00	-22.66	peak	100	189	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:48:12
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-3.18	59.91	56.73	74.00	-17.27	peak	100	360	
2	4924.000	-3.18	54.17	50.99	54.00	-3.01	AVG	100	360	
3	7386.000	4.73	43.92	48.65	74.00	-25.35	peak	100	208	
4	9483.000	5.56	46.05	51.61	74.00	-22.39	peak	100	166	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:53:23
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-3.34	47.67	44.33	74.00	-29.67	peak	100	208	
2	7236.000	4.38	45.90	50.28	74.00	-23.72	peak	100	312	
3	9007.000	5.64	44.94	50.58	74.00	-23.42	peak	100	2	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:54:25
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-3.34	48.44	45.10	74.00	-28.90	peak	100	117	
2	7236.000	4.38	46.11	50.49	74.00	-23.51	peak	100	36	
3	9126.000	5.63	45.11	50.74	74.00	-23.26	peak	100	230	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:58:45
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-3.26	48.54	45.28	74.00	-28.72	peak	100	269	
2	7311.000	4.56	44.50	49.06	74.00	-24.94	peak	100	306	
3	9194.000	5.62	43.75	49.37	74.00	-24.63	peak	100	130	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:59:48
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-3.26	51.09	47.83	74.00	-26.17	peak	100	141	
2	7311.000	4.56	43.49	48.05	74.00	-25.95	peak	100	345	
3	9007.000	5.64	44.85	50.49	74.00	-23.51	peak	100	217	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:02:33
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-3.18	50.56	47.38	74.00	-26.62	peak	100	101	
2	7386.000	4.73	44.91	49.64	74.00	-24.36	peak	100	336	
3	9211.000	5.60	44.69	50.29	74.00	-23.71	peak	100	146	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:03:35
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-3.18	53.93	50.75	74.00	-23.25	peak	100	24	
2	7386.000	4.73	44.38	49.11	74.00	-24.89	peak	100	118	
3	9534.000	5.51	46.40	51.91	74.00	-22.09	peak	100	324	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:26:52
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-3.34	49.30	45.96	74.00	-28.04	peak	100	207	
2	7236.000	4.38	44.78	49.16	74.00	-24.84	peak	100	117	
3	9874.000	4.93	46.54	51.47	74.00	-22.53	peak	100	35	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:27:55
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-3.34	49.24	45.90	74.00	-28.10	peak	100	201	
2	7236.000	4.38	45.38	49.76	74.00	-24.24	peak	100	339	
3	8990.000	5.65	45.12	50.77	74.00	-23.23	peak	100	66	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:30:54
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-3.26	48.32	45.06	74.00	-28.94	peak	100	201	
2	7311.000	4.56	44.14	48.70	74.00	-25.30	peak	100	34	
3	9211.000	5.60	44.25	49.85	74.00	-24.15	peak	100	84	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:31:56
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-3.26	52.46	49.20	74.00	-24.80	peak	100	357	
2	7311.000	4.56	44.59	49.15	74.00	-24.85	peak	100	266	
3	9109.000	5.63	45.42	51.05	74.00	-22.95	peak	100	210	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 21:34:42
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-3.18	50.05	46.87	74.00	-27.13	peak	100	247	
2	7386.000	4.73	43.49	48.22	74.00	-25.78	peak	100	108	
3	9347.000	5.59	46.20	51.79	74.00	-22.21	peak	100	20	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 21:35:45
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-3.18	54.71	51.53	74.00	-22.47	peak	100	359	
2	7386.000	4.73	45.02	49.75	74.00	-24.25	peak	100	211	
3	9024.000	5.65	45.61	51.26	74.00	-22.74	peak	100	257	


Spurious Emissions, TX Mode, 18-26G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:18:10
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19445.000	3.65	43.40	47.05	74.00	-26.95	peak	100	310	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:19:13
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23474.000	5.57	41.07	46.64	74.00	-27.36	peak	100	53	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:21:20
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22862.000	4.89	41.87	46.76	74.00	-27.24	peak	100	224	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:22:23
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21476.500	4.17	44.73	48.90	74.00	-25.10	peak	100	280	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:24:25
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21068.500	4.54	42.55	47.09	74.00	-26.91	peak	100	36	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:25:28
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23669.500	5.49	41.17	46.66	74.00	-27.34	peak	100	197	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:27:35
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	24145.500	5.21	41.11	46.32	74.00	-27.68	peak	100	215	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:28:37
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22717.500	4.72	41.37	46.09	74.00	-27.91	peak	100	170	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:31:19
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	19071.000	4.15	44.34	48.49	74.00	-25.51	peak	100	52	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:32:21
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22853.500	4.87	43.37	48.24	74.00	-25.76	peak	100	327	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:34:29
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	20397.000	4.01	42.78	46.79	74.00	-27.21	peak	100	9	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:35:32
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	G-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23899.000	5.34	40.93	46.27	74.00	-27.73	peak	100	17	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:37:39
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22853.500	4.87	43.09	47.96	74.00	-26.04	peak	100	83	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:38:42
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2412		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	24222.000	5.18	43.75	48.93	74.00	-25.07	peak	100	0	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:40:35
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23873.500	5.36	41.54	46.90	74.00	-27.10	peak	100	274	




Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:41:38
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22139.500	4.08	42.37	46.45	74.00	-27.55	peak	100	292	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:43:31
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23440.000	5.53	41.39	46.92	74.00	-27.08	peak	100	99	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:44:34
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	N20-TX-2462		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22887.500	4.91	42.89	47.80	74.00	-26.20	peak	100	100	


Spurious Emissions, TX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 19:22:06
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	30.0000	-0.23	25.05	24.82	40.00	-15.18	QP	100	163	
2	151.2500	-7.36	30.31	22.95	43.50	-20.55	QP	100	123	
3	287.0500	-4.81	36.15	31.34	46.00	-14.66	QP	100	48	
4	675.0500	1.05	34.96	36.01	46.00	-9.99	QP	100	133	
5	773.9900	2.74	35.95	38.69	46.00	-7.31	QP	100	184	
6	983.5100	5.89	32.61	38.50	54.00	-15.50	QP	100	203	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 19:23:10
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	30.0000	-0.23	25.04	24.81	40.00	-15.19	QP	100	40	
2	165.8000	-8.54	30.87	22.33	43.50	-21.17	QP	100	155	
3	269.5900	-5.27	32.16	26.89	46.00	-19.11	QP	100	14	
4	600.3600	0.22	38.50	38.72	46.00	-7.28	QP	100	360	
5	647.8900	0.65	38.37	39.02	46.00	-6.98	QP	100	360	
6	675.0500	1.05	36.64	37.69	46.00	-8.31	QP	100	35	


Spurious Emissions, TX Mode, 9k-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC2.8_9k-1G_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/6/28 20:02:25
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0168	18.80	27.27	46.07	123.00	-76.93	QP	100	308	
2	0.0421	19.09	22.27	41.36	115.05	-73.69	QP	100	134	
3	0.0701	18.69	14.66	33.35	110.63	-77.28	QP	100	258	
4	0.1026	18.33	11.79	30.12	107.33	-77.21	QP	100	114	
5	0.1208	18.34	11.84	30.18	105.92	-75.74	QP	100	25	
6	0.1398	18.35	19.43	37.78	104.66	-66.88	QP	100	101	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC2.8_9k-1G_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/6/28 20:03:58
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-TX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.1500	18.35	25.88	44.23	104.05	-59.82	QP	100	89	
2	2.1201	18.59	16.00	34.59	69.50	-34.91	QP	100	1	
3	7.9707	20.03	9.97	30.00	69.50	-39.50	QP	100	228	
4	11.0751	20.55	19.54	40.09	69.50	-29.41	QP	100	36	
5	18.5376	21.42	8.38	29.80	69.50	-39.70	QP	100	149	
6	22.2987	21.67	13.23	34.90	69.50	-34.60	QP	100	223	


Spurious Emissions, RX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:07:17
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	1459.000	-11.34	51.65	40.31	74.00	-33.69	peak	100	285	
2	1986.000	-8.12	51.71	43.59	74.00	-30.41	peak	100	96	
3	7273.000	4.47	45.72	50.19	74.00	-23.81	peak	100	0	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:08:19
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	1272.000	-11.01	49.85	38.84	74.00	-35.16	peak	100	275	
2	6253.000	3.43	44.40	47.83	74.00	-26.17	peak	100	17	
3	7766.000	4.89	44.50	49.39	74.00	-24.61	peak	100	17	


Spurious Emissions, RX Mode, 18-26G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 22:46:34
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23856.500	5.37	41.60	46.97	74.00	-27.03	peak	100	299	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 22:47:36
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23380.500	5.47	41.70	47.17	74.00	-26.83	peak	100	314	


Spurious Emissions, RX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel: +886-2172-7000 fax: +886-2528-0018



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/6/28 19:31:30
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	165.8000	-8.54	32.24	23.70	43.50	-19.80	QP	100	128	
2	302.5700	-4.39	34.93	30.54	46.00	-15.46	QP	100	11	
3	367.5600	-2.91	34.95	32.04	46.00	-13.96	QP	100	359	
4	688.6300	1.25	37.94	39.19	46.00	-6.81	QP	100	359	
5	767.2000	2.68	34.73	37.41	46.00	-8.59	QP	100	126	
6	983.5100	5.89	32.92	38.81	54.00	-15.19	QP	100	348	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/6/28 19:28:51
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	30.0000	-0.23	25.60	25.37	40.00	-14.63	QP	100	190	
2	207.5100	-8.54	30.82	22.28	43.50	-21.22	QP	100	251	
3	400.5400	-2.29	32.25	29.96	46.00	-16.04	QP	100	86	
4	600.3600	0.22	38.73	38.95	46.00	-7.05	QP	100	0	
5	647.8900	0.65	37.85	38.50	46.00	-7.50	QP	100	0	
6	983.5100	5.89	32.39	38.28	54.00	-15.72	QP	100	2	


Spurious Emissions, RX Mode, 9K-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC2.8_9k-1G_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/6/28 19:56:32
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%):	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0100	18.50	32.13	50.63	127.49	-76.86	QP	100	201	
2	0.0421	19.06	22.77	41.83	115.05	-73.22	QP	100	225	
3	0.0670	18.70	14.58	33.28	111.02	-77.74	QP	100	109	
4	0.1004	18.30	11.37	29.67	107.52	-77.85	QP	100	227	
5	0.1177	18.31	11.74	30.05	106.15	-76.10	QP	100	47	
6	0.1418	18.32	19.03	37.35	104.53	-67.18	QP	100	350	



Service No.:	114078137-Wifi	Test Distance:	3m
Test Standard:	NCC2.8_9k-1G_3m	Ant. Polarization:	N/A
Test item:	Radiation Emission	Test Time:	2018/6/28 19:59:15
Applicant:	奧迪福斯汽車股份有限公司	Test Rating:	DC 12V
Product:	Head Unit	Temp.(°C)/Hum.(%)	20(°C)/56%
Model No.:	MIB2 STD	Test Engineer:	Kevin.Kuo
Test Mode:	B-RX-2437		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.1500	18.32	25.89	44.21	104.05	-59.84	QP	100	21	
2	2.1201	18.49	13.93	32.42	69.50	-37.08	QP	100	3	
3	6.0603	19.49	10.39	29.88	69.50	-39.62	QP	100	139	
4	10.3587	20.49	12.78	33.27	69.50	-36.23	QP	100	227	
5	20.2390	21.64	11.13	32.77	69.50	-36.73	QP	100	36	
6	24.5076	21.80	10.51	32.31	69.50	-37.19	QP	100	114	