

EUROFINS ELECTRICAL TESTING SERVICE (SHENZHEN) CO., LTD.

RADIO TEST - REPORT

Japan Compliance Test Report

Test Report Number: EFGX26010361-IE-03-E01

Test Report No.: EFGX26010361-IE-03-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

Room 20 of 2/F., 1/F., Building 2, Spring Block & Room 102, Building 8, Autumn Block, Meishenghuigu Innovation Park, No.83, Dabao Road, Bao'an District, Shenzhen, Guangdong, China. Telephone: +86-755-82911867, Fax : +86-755-82910749

Page 1 of 24

Content

1	General Information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of approval holder	4
1.4	Details of Manufacturer	4
1.5	Application details	5
1.6	Test item	5
1.7	Standards	6
2	Technical test	7
2.1	Summary of test results	7
2.2	Test environment	7
2.3	Measurement uncertainty	7
2.4	Test mode	7
2.5	Test equipment utilized	8
2.6	Auxiliary Equipment Used during Test:	8
2.7	Test software information:	8
2.8	Customized Configurations	8
2.9	Test Environments	8
2.10	Test results	9
3	Technical Requirement	10
3.1	Antenna Power	10
3.2	Tolerances for Antenna Power	12
3.3	Frequency Tolerance	14
3.4	Occupied Frequency Bandwidth	16
3.5	Spread Bandwidth	18
3.6	Transmitter Spurious Emissions (Conducted) (For transmitter)	20
3.7	Secondary Radiated Emissions (Conducted) (For receiver)	22
3.8	Interference prevention function	24

1 General Information

1.1 Notes

The results of this test report relate exclusively to the item tested as specified in chapter "Description of test item" and are not transferable to any other test items.

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. is not responsible for any generalisations and conclusions drawn from this report. Any modification of the test item can lead to invalidity of test results and this test report may therefore be not applicable to the modified test item.

The test report may only be reproduced or published in full. Reproducing or publishing extracts of the report requires the prior written approval of the Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

This document is subject to the General Terms and Conditions and the Testing and Certification System of Eurofins Electrical Testing Service (Shenzhen) Co., Ltd., available on request or accessible at www.eurofins.com.

Operator:

2025-02-26

Bruce Zheng / Project Engineer



Date

Eurofins-Lab.


Name / Title

Signature

Technical responsibility for area of testing:

2025-02-26

Albert Xu / Lab Manager



Date

Eurofins-Lab.

Name / Title

Signature

1.2 Testing laboratory

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

Room 20 of 2/F., 1/F., Building 2, Spring Block & Room 102, Building 8, Autumn Block,

Meishenghuigu Innovation Park, No.83, Dabao Road, Bao'an District, Shenzhen, Guangdong, China

Telephone : +86-755-82911867

Fax : +86-755-82910749

The Laboratory has passed the Accreditation by the American Association for Laboratory Accreditation (A2LA). The Accreditation number is 5376.01.

The Laboratory has been listed by industry Canada to perform electromagnetic emission measurements, The CAB identifier is CN0088.

1.3 Details of approval holder

Name : PEANUTS CLUB CO., LTD

Address : 2-1-33 MIKURIYAMINAMI, HIGASHIOSAKA, OSAKA,
JAPAN

Telephone : N/A

Fax : N/A

1.4 Details of Manufacturer

Name : Z-MART INDUSTRIES CO.,LTD.

Address : 7 FLOOR,#2 BUILDING,SUN LAKE MAOYUE BUSI-NESS
CENTER,NO.33,207 LANE,WEST OF NORTHHUAN-
CHENG ROAD.NINGBO.CHINA

Telephone : N/A

Fax : N/A

1.5 Application details

Date of receipt of application : 2026-01-19
Date of receipt of test item : 2026-01-19
Date of test : 2026-01-19 to 2025-02-26
Date of issue : 2025-02-26

1.6 Test item

Product type : Mini Printer
Model name : ZM-2602
Brand : N/A
Serial number : N/A
Sample ID : 260120-12-003
Ratings : DC 3.7V
Test voltage : DC 3.7V
Additional information : N/A

RadioTechnical data

Frequency range : 2402MHz – 2480MHz
Radio Tech. : 2.4GHz Bluetooth Low Energy
Frequency channel : 40 Channels
Modulation : GFSK
Antenna type : Internal antenna
Antenna gain : -0.58dBi

The above sample(s) and sample information was/were submitted and identified on behalf of the applicant.
Eurofins assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information and technical documents.

1.7 Standards

Standards	
Article 2 paragraph 1 item (19)	Low power data communications system in the 2.4GHz band
ARIB STD-T66 V3.7	SECOND GENERATION LOW POWER DATA COMMUNICATION SYSTEM/ WIRELESS LAN SYSTEM

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	: 20	...	25°C
Relative humidity content	: 30	...	60%
Air pressure	: 100	...	101kPa

2.3 Measurement uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted RF test	RF Power Conducted: 1.16dB Frequency test involved: 1.05×10 ⁻⁷ or 1%

2.4 Test mode

The EUT was set at continuously transmitting and receiving mode (CH0, CH19, CH39) during the test.

EUT test voltage requirement:

The RF unit is supplied by DC power. The fluctuation of input voltage to the circuit of RF unit of test equipment is under ±1%, when input voltage from DC 3.7V to the test equipment is fluctuated by ±10%, So, the DC 3.7V is chosen in the test report.

The measurement result of the voltage fluctuation at RF circuit when DC 5V +/- 10%.

DC Input	DC 3V
3.33V	3V
3.7V	3V
4.07V	3V

2.5 Test equipment utilized

EQUIPMENT ID	EQUIPMENT NAME	MODEL NO.	SN NO.	CAL. DUE DATE
23-2-13-12	Signal Analyzer	N9010B-544	MY57471523	2026-03-26
23-2-10-44	DC power supply	E3642A	MY58386620	2026-03-26
23-2-10-50	Temperature & Humidity Meter	COS-03	582951	2026-03-26

All calibration reports are from CCIC (Shenzhen) Metrology & Testing Service Co.,Ltd.

2.6 Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Laptop	LENOVO	TP00096A	PF-1QH0LV

2.7 Test software information:

Test Software Version	FCC assist		
Modulation	Setting TX Power	TX Pattern	Packet Type
GFSK	DEF	TX Packet	BLE/1M,2M

2.8 Customized Configurations

EUT Conf.	Signal Description	Operating Frequency	Duty Cycle
2402	GFSK	Ch No. 0	67.62%
2440	GFSK	Ch No. 19	67.62%
2480	GFSK	Ch No. 39	67.62%

2.9 Test Environments

Enviroment Parameter	Temperature	Voltage	Relative Humidity
101.7Kpa	26.5℃	3.7Vdc	54.3%

2.10 Test results

☒ 1st test

☐ test after modification

☐ production test

Conformance requirement according to Article 2 paragraph 1 item (19) and ARIB STD-T66 Version 3.7/2014-10		Result	Test site
Essential parameter	Corresponding technical requirements		
Transmitter requirements	3.2 (2) Antenna Power	PASS	Site 1
	3.2 (3) Tolerances for Antenna Power	PASS	Site 1
	3.2 (4) Frequency Tolerance	PASS	Site 1
	3.2 (5) Transmission Rate	N/A*	N/A
	3.2 (7) Occupied Frequency Bandwidth	PASS	Site 1
	3.2 (8) Spread Bandwidth	PASS	Site 1
	3.2 (9) Process Gain	PASS	Site 1
	3.2 (10) Number of Carriers	N/A*	N/A
	3.2 (11) Dwell Time	N/A*	N/A
	3.2 (6) Spurious Emissions	PASS	Site 1
Receiver requirements	3.5 (1) Secondary Radiated Emissions	PASS	Site 1
	3.4 (1) Interference prevention function	PASS	Site 1

NOTE 1: Measurement taken is within the measurement uncertainty of measurement system.

NOTE 2: "*" N/A is an abbreviation for Not Applicable.

NOTE 3: Test method: MIC Notice No.88 Appendix No.43


3 Technical Requirement

3.1 Antenna Power

3.1.1 Test Method

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency and measure the conducted output power separately.
4. RBW=1MHz, VBW $\geq$ RBW, Sweep = auto, Detector function = Positive peak, Trace = max hold
5. Repeat above procedures until all frequencies measured were complete.

3.1.2 Test Setup:



3.1.3 Limit (ARIB STD-T66/ARIB STD-T33, Clause 3.2 (2)-a)

- a. The antenna power of a transmitting equipment (with a frequency band of 2,427 – 2,470.75 MHz, for spread spectrum systems using FH systems, hybrid systems of DS and FH, or hybrid systems of FH and OFDM) shall be such that the mean power within a bandwidth of 1 MHz is 3 mW or less in the case of modulation using a standard coding test signal with the same transmission rate as that of the modulation signal.
- b. The antenna power of a transmitting equipment using a spread spectrum system other than any of those in “a” and the OFDM system shall be such that the mean power within a bandwidth of 1 MHz is 10 mW or less in the case of modulation using a standard coding test signal with the same transmission rate as that of the modulation signal.

3.1.4 Test result

Antenna Power							
TestCondition	Test-Mode	Antenna	Freq(MHz)	Re-sult(dBm)	Result(mW)	Limit(mW)	Verdict
NTNV	BLE_1M	Ant1	2402	2.86	1.932	≤10	PASS
			2440	3.24	2.109	≤10	PASS
			2480	2.80	1.905	≤10	PASS
	BLE_2M	Ant1	2402	2.76	1.888	≤10	PASS
			2440	3.42	2.198	≤10	PASS
			2480	2.98	1.986	≤10	PASS

EIRP							
TestCondition	Test-Mode	Antenna	Freq(MHz)	Result(dBm)	EIRP(dBm)	Limit(dBm)	Verdict
NTNV	BLE_1M	Ant1	2402	2.86	2.28	≤12.14	PASS
			2440	3.24	2.66	≤12.14	PASS
			2480	2.80	2.22	≤12.14	PASS
	BLE_2M	Ant1	2402	2.76	2.18	≤12.14	PASS
			2440	3.42	2.84	≤12.14	PASS
			2480	2.98	2.40	≤12.14	PASS


3.2 Tolerances for Antenna Power

3.2.1 Test Method

6. Connect EUT test port to spectrum analyzer.
7. Set the EUT to transmit maximum output power at 2.4GHz.
8. Then set the EUT to transmit at Highest, Middle, and Lowest frequency and measure the conducted output power separately.
9. RBW=1MHz, VBW $\geq$ RBW, Sweep = auto, Detector function = Average, Meas=channel power
Meas setup=1MHz, Trace = max hold
10. Repeat above procedures until all frequencies measured were complete.

3.2.2 Test Setup:

The WIFI component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.2.3 Limit (ARIB STD-T66/ARIB STD-T33, Clause 3.2 (3))

Upper limits of the tolerance for antenna power shall be 20%, respectively. Note that they represent the tolerance for the maximum rated antenna power and that no upper and lower limits of the tolerance are regulated in the case of antenna power reduction for communications reasons.

3.2.4 Test result

Tolerance								
Test Condition	Test Mode	Antenna	Freq(MHz)	Power (mW)	RatedPower (mW)	Result (%)	Limit (%)	Verdict
NTNV	BLE_1M	Ant1	2402	1.932	10	-80.68	+20	PASS
			2440	2.109	10	-78.91	+20	PASS
			2480	1.905	10	-80.95	+20	PASS
	BLE_2M	Ant1	2402	1.888	10	-81.12	+20	PASS
			2440	2.198	10	-78.02	+20	PASS
			2480	1.986	10	-80.14	+20	PASS

Note: Deviation = (Output power – Declared Output Power) / Declared Output Power * 100%

3.2.5 Result

The equipment met the requirement of this clause.


3.3 Frequency Tolerance

3.3.1 Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency and measure the conducted output power separately.
4. RBW=10kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold
5. Repeat above procedures until all frequencies measured were complete.

3.3.2 Test Setup:

The WIFI component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.3.3 Limit (ARIB STD-T66/ ARIB STD-T33, Clause 3.2 (4))

Tolerance of frequency: $\pm 50 \times 10^{-6}$.

3.3.4 Test Result

TestCondition	Antenna	Freq(MHz)	CenterFreq [MHz]	Result[ppm]	Limit[ppm]	Verdict
NTNV	Ant1	2402	2401.988	-4.99584	±50	PASS
		2440	2439.988	-4.91803	±50	PASS
		2480	2479.988	-4.83871	±50	PASS

Note: Frequency Tolerance (ppm) = [Measurement Frequency - Center Frequency] / Center Frequency*10⁶

Test Result: Pass

Please refer to the appendix A for test plots
The equipment met the requirement of this clause.


3.4 Occupied Frequency Bandwidth

3.4.1 Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
4. Set Occupied bandwidth 99%
5. Set RBW=300KHz , VBW $\geq$ RBW.
6. Set Sweep = auto.
7. Set Detector function = peak.
8. Allow the trace to stabilize.
9. Repeat above procedures until all frequencies measured were complete.

3.4.2 Test Setup:

The WIFI component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.4.3 Limit (ARIB STD-T66/ARIB STD-T33, Clause 3.2 (7))

Permissible value for occupied bandwidth using the FH system, a hybrid system combining DS and FH systems, or a hybrid system combining FH and OFDM systems shall be 83.5 MHz or less, while necessary bandwidth (minimum occupied bandwidth sufficient to ensure information transmission of required quality at a required transmission rate for the system used under specified conditions for a given emission type) using a system other than any of the above shall be 26 MHz or less.

3.4.4 Test Result

TestCondition	Test-Mode	Antenna	Freq(MHz)	Result [MHz]	Limit [MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	1.254	≤26	PASS
			2440	1.253	≤26	PASS
			2480	1.255	≤26	PASS
	BLE_2M	Ant1	2402	2.152	≤26	PASS
			2440	2.151	≤26	PASS
			2480	2.145	≤26	PASS

Test Result: Pass

Please refer to the appendix C for test plots
The equipment met the requirement of this clause.


3.5 Spread Bandwidth and spreading factor

3.5.1 Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
4. Set Occupied bandwidth 90%
5. Set analyzer center frequency to DTS channel center frequency.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Repeat above procedures until all frequencies measured were complete.

3.5.2 Test Setup:

The WIFI component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.5.3 Limit (ARIB STD-T66/ARIB STD-T33, Clause 3.2 (8))

In spread spectrum systems, spread bandwidth (which refers to a frequency bandwidth with an upper limit and lower limit such that each of the mean powers radiated above the upper frequency limit and below the lower frequency limit is equal to 5 % of the total mean power radiated; this also applies hereafter) shall be 500 kHz or more.

Process gain (value obtained by dividing the spread bandwidth by a frequency equal to the transmission rate of the modulation signal; this also applies hereafter) in the spread spectrum system shall be 5 or more.

3.5.4 Test Result

TestCondition	Test-Mode	Antenna	Freq(MHz)	Result [MHz]	Limit [MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	0.832	≥ 0.5	PASS
			2440	0.833	≥ 0.5	PASS
			2480	0.834	≥ 0.5	PASS
	BLE_2M	Ant1	2402	1.367	≥ 0.5	PASS
			2440	1.369	≥ 0.5	PASS
			2480	1.369	≥ 0.5	PASS

Test Result: Pass

Please refer to the appendix D for test plots
The equipment met the requirement of this clause.


3.6 Transmitter Spurious Emissions (Conducted) (For transmitter)

Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
4. Set Frequency range and limit: $2,387\text{MHz} \leq f \leq 2,400\text{MHz}$ and $2,483.5\text{MHz} < f \leq 2,496.5\text{MHz}$ 25 μW or less b. $2,387\text{MHz} > f$ and $2,496.5\text{MHz} < f$ 2.5 μW or less
5. Set RBW = 1MHz, VBW $\geq$ RBW.
6. Set Sweep = auto.
7. Set Detector function = peak.
8. Allow the trace to stabilize.
9. Repeat above procedures until all frequencies measured were complete.

Test Setup:

The WIFI component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.6.1 Limit (ARIB STD-T66/ARIB STD-T33, Clause 3.2 (6))

ARIB STD-T66

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows: a. $2,387\text{MHz} \leq f \leq 2,400\text{MHz}$ and $2,483.5\text{MHz} < f \leq 2,496.5\text{MHz}$ 25 μW or less b. $2,387\text{MHz} > f$ and $2,496.5\text{MHz} < f$ 2.5 μW or less.

ARIB STD-T33

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows: a. $2,458\text{MHz} \leq f \leq 2,471\text{MHz}$ and $2,497\text{MHz} < f \leq 2,510\text{MHz}$ 25 μW or less b. $2,458\text{MHz} > f$ and $2,510\text{MHz} < f$ 2.5 μW or less.

3.6.2 Test Result

TestCondition	Test-Mode	Antenna	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [μW]	Limit [μW]	Verdict
NTNV	BLE_1M	Ant1	2402	30~1000	833.16	-48.22	≤-26	0.01507	≤2.5	PASS
				1000~2387	2271.19	-36.61	≤-26	0.21827	≤2.5	PASS
				2387~2400	2399.99	-24.41	≤-16	3.62243	≤25	PASS
				2483.5~2496.5	2488.19	-36.27	≤-16	0.23605	≤25	PASS
				2496.5~13000	4803.59	-37.77	≤-26	0.16711	≤2.5	PASS
			2440	30~1000	887.97	-48.77	≤-26	0.01327	≤2.5	PASS
				1000~2387	2267.02	-34.73	≤-26	0.33651	≤2.5	PASS
				2387~2400	2392.16	-34.88	≤-16	0.32509	≤25	PASS
				2483.5~2496.5	2488.06	-34.52	≤-16	0.35318	≤25	PASS
				2496.5~13000	4880.27	-37.98	≤-26	0.15922	≤2.5	PASS
			2480	30~1000	863.96	-48.31	≤-26	0.01476	≤2.5	PASS
				1000~2387	2266.68	-42.98	≤-26	0.05035	≤2.5	PASS
				2387~2400	2389.18	-37.28	≤-16	0.18707	≤25	PASS
				2483.5~2496.5	2483.62	-29.28	≤-16	1.18032	≤25	PASS
				2496.5~13000	4960.62	-38.37	≤-26	0.14555	≤2.5	PASS
	BLE_2M	Ant1	2402	30~1000	780.78	-48.43	≤-26	0.01435	≤2.5	PASS
				1000~2387	2268.41	-38.02	≤-26	0.15776	≤2.5	PASS
				2387~2400	2400.00	-19.42	≤-16	11.4287	≤25	PASS
				2483.5~2496.5	2495.23	-36.42	≤-16	0.22803	≤25	PASS
				2496.5~13000	4805.17	-38.78	≤-26	0.13243	≤2.5	PASS
			2440	30~1000	896.94	-48.02	≤-26	0.01578	≤2.5	PASS
				1000~2387	2265.29	-39.05	≤-26	0.12445	≤2.5	PASS
				2387~2400	2391.99	-34.79	≤-16	0.33189	≤25	PASS
				2483.5~2496.5	2487.78	-33.59	≤-16	0.43752	≤25	PASS
				2496.5~13000	4880.79	-38.66	≤-26	0.13614	≤2.5	PASS
			2480	30~1000	906.88	-48.43	≤-26	0.01435	≤2.5	PASS
				1000~2387	2268.76	-40.42	≤-26	0.09078	≤2.5	PASS
				2387~2400	2388.25	-37.21	≤-16	0.19011	≤25	PASS
				2483.5~2496.5	2485.97	-21.93	≤-16	6.41210	≤25	PASS
				2496.5~13000	4959.05	-38.42	≤-26	0.14388	≤2.5	PASS

3.6.3 Result

Please refer to the appendix E for test plots
The equipment met the requirement of this clause.

3.7 Secondary Radiated Emissions (Conducted) (For receiver)


Test Method:

The test method was referred to the subclause 11.13.3.4 of ANSI C63.10-2013.

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 2.4GHz.
3. Then set the EUT to transmit at Highest, Middle, and Lowest frequency separately.
4. Set Frequency range and limit: 30MHz - 1 GHz and 20 nW or 1 GHz – 13GHz
5. Set RBW $\geq$ 1MHz, VBW $\geq$ RBW.
6. Set Sweep = auto.
7. Set Detector function = peak.
8. Allow the trace to stabilize.
9. Repeat above procedures until all frequencies measured were complete.

Test Setup:

The WIFI component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



3.7.1 Limit (ARIB STD-T66/ARIB STD-T33, Clause 3.5 (1))

The limit on secondary emissions radiated from the receiving equipment within which the function of other radio equipment will not be impaired shall be, in terms of the power of a dummy antenna circuit that has the same electrical constant as the receiving antenna, 4 nW or less at a frequency below 1 GHz and 20 nW or less at a frequency of 1 GHz or higher as measured using the circuit.

3.7.2 Test Result

TestCondition	Test-Mode	Antenna	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	BLE_1M	Ant1	2402	30~1000	384.05	-63.81	≤-54	0.41591	≤4	PASS
				1000~12500	2413.35	-53.98	≤-47	3.99945	≤20	PASS
			2440	30~1000	383.57	-65.71	≤-54	0.26853	≤4	PASS
				1000~12500	2413.93	-53.99	≤-47	3.99025	≤20	PASS
			2480	30~1000	384.05	-65.78	≤-54	0.26424	≤4	PASS
				1000~12500	2431.18	-51.08	≤-47	7.79830	≤20	PASS
	BLE_2M	Ant1	2402	30~1000	383.57	-64.43	≤-54	0.36058	≤4	PASS
				1000~12500	2462.23	-60.40	≤-47	0.91201	≤20	PASS
			2440	30~1000	384.05	-64.38	≤-54	0.36475	≤4	PASS
				1000~12500	2413.93	-55.12	≤-47	3.07610	≤20	PASS
			2480	30~1000	384.54	-66.02	≤-54	0.25003	≤4	PASS
				1000~12500	2413.93	-54.52	≤-47	3.53183	≤20	PASS

3.7.3 Result

Please refer to the appendix F for test plots
The equipment met the requirement of this clause.

3.8 Interference prevention function

3.8.1 Limit

Item	Limits
Identification Code	≥48 bits

Measuring ID code Software
MAC IP List: MAC Scan

3.8.2 Test Procedure

1. In the case that the EUT has the function of automatically transmitting the identification code: a. Transmit the predetermined identification codes from EUT. b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code: a. Transmit the predetermined identification codes from the counterpart. b. Check if communication is normal. c. Transmit the signals other than predetermined ID codes from the counterpart. d. Check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

3.8.3 Conditions of Equipment under Test

Required normal mode of the applicable equipment (EUT)

3.8.4 TEST RESULTS

The radio equipment has an identification code. A verification of this code is done before a communication channel is established

MAC address: 90B0EA2948156

The equipment meets the requirement of this clause.

End