Perle IRG7000/5000 5G/LTE Cellular Router Command Line Interface Reference Guide

Updated: June 2023
Version: A.06.06.2023
Document Part#:5500446-10

www.perle.com

Table of Contents

Preface 14

About This Book 14

Intended Audience 14

Typeface Conventions 14

Setting up the Router 14

Chapter 2 User Exec Mode 28

clear ip dhcp binding 28

enable 28

exit 29

line-attach 29

logout 29

password 30

ping 30

release 31

renew 32

show alarm 32

show arp 34

show clock 34

show crypto 35

show dot1x 36

show eap 37

show environment 38

show facility-alarm 39

show flash: 40

show hosts 41

show ip arp 41
show ip ddns 42
show ip dhcp 43
show ip host-group 43
show ip http 44
show ip interface 45
show ip ssh 45
show ipv6 46
show ldap 47
show line 48
show lldp 49
show mab 49
show mac 51
show ntp 52
show nvram: 53
show radius 54
show snmp 54
show ssh 55
show tacacs 56
show terminal 56
show users 57
show version 58
ssh 59
telnet 59
terminal 60

testemail 60
testsms 61
traceroute 61
two-factor 62
2 Privileged EXEC mode 64
archive 64
boot 67
cd 68
cellular 68
clear aaa 69
clear arp-cache 69
clear bridge 70
clear contact 70
clear counters 71
clear ip 71
clear ipv6 72
clear ldap 73
clear line 74
clear lldp 74
clear logging 75
clear radius 75
clear tacacs 76
clock 76
configure 77
container (OCI) 78

copy 80
debug 81
delete 83
dir 84
disable 85
disconnect 85
dot1x 86
exit 87
kill 87
line-attach 87
logout 88
mkdir 88
more 89
password 90
ping 90
pwd 91
release 92
reload 92
rename 93
renew 93
reset 93
rmdir 94
serialt 94
show aaa 95
show alarm 96

show archive 96
show arp 97
show bgp 97
show bridge 99
show cellular 100
show clock 102
show container (OCI) 102
show container-management (OCI) 104
show debugging 104
show crypto 105
show dhcp 105
show dot11 106
show dot1x 107
show eap 107
show eee 107
show email 108
show environment 109
show facility-alarm 109
show flash: 109
show format 109
show gnss 109
show hosts 110
show hotspot 110
show interfaces 111
show ip access-lists 113

show ip alg 113
show ip arp 114
show ip as-path-access-list 114
show ip bgp 115
show ip community-list 117
show ip ddns 117
show ip dhcp 117
show ip dns 118
show ip extcommunity-list 118
show ip firewall 119
show ip health 120
show ip host-group 121
show ip http 122
show ip interface 123
show ip nat 123
show ip ospf 124
show ip prefix-list 126
show ip rip 126
show ip route 127
show ip route-policy 127
show ip ssh 128
show ipv6 129
show ldap 129
show license 129
show line 129

show lldp 131
show logging 131
show mab 132
show mac 132
show management-access 132
show nat66 133
show network-watchdog 134
show ntp 135
show nvram: 135
show policy-map 135
show processes 136
show radius 136
show reload 136
show rest-api 137
show route-map 138
show running-config 139
show sdm 140
show serial 140
show snmp 141
show ssh 142
show startup-config 142
show system 143
show tacacs 144
show task-status 144
show tech-support 145

show terminal 146
show username 146
show users 146
show version 146
show vrrp 147
show wan 147
show zone-policy 149
shutdown 149
ssh 149
standby 149
telnet 150
terminal 150
testemail 150
testsms 150
traceroute 150
undebug 150
vrrp 152
Chapter 1 Global Configuration Mode 154
aaa 154
alarm 158
archive 161
arp 162
banner 163
boot 164
bridge 165

cellular 169
class-map 171
clock 175
container (OCI) 176
container-management (OCI) 180
controller 180
crypto 182
dot11 197
dot1x 199
eap 201
email 202
enable 204
gnss 204
(config-gnss-profile)# 205
(config-gnss-client) 207
(config-gnss-server) 208
(config-gnss-tty) 209
(config-gnss-usb) 210
hostname 211
interface 211
ip access-list 212
ip alg 214
ip as-path 215
ip community-list 216
ip default-gateway 218
ip dhcp 218
ip dns 220

ip domain 221
ip domain-name 222
ip extcommunity-list 222
ip firewall 223
ip ftp 230
ip health 231
ip host 232
ip host-group 232
ip http 233
ip name-server 235
ip nat 235
ip passthrough 237
ip prefix-list 237
ip radius 238
ip route 239
ip route-policy 239
ip scp 243
ip sftp 243
ip ssh 244
ip tacacs 246
ip telnet 247
ipv6 247
key 264
ldap 265
line 268

lldp 269
logging 271
login 273
low-power-mode 274
mac 274
management-access 277
nat66 279
network-watchdog 280
ntp 282
policy-map 285
power 294
(config-smrt-stdby) 296
power-supply 297
radius 298
radius-server 299
remote-management 300
route-map 302
router 305
sdm 326
serial 327
service 329
snmp-server 330
standby 333
tacacs 333
tacacs-server 334

tty 336
usb 336
username 337
wan 343
zone 346
zone-pair 348
Chapter 2 Interface configuration 349
Interface 349
(config-if-ssid)# 390
hotspot)# 402
Chapter 3 Interface line mode 477
line 477
(config-line)#console 477
(config-line)#tty 479
(config-line)#vty 497

Preface

About This Book

This guide provides the information you need to:

- configure the Perle Router using the Command Line Interface (CLI)
- Some CLI commands are not available, on some models

Intended Audience

This guide is for administrators who will be configuring the Perle Router, hereafter known as the router.

Some prerequisite knowledge is needed to understand the concepts and examples in this guide:

- If you are using an external authentication application(s), working knowledge of the authentication application(s).
- Knowledge of the file transfer protocols the router uses.

Typeface Conventions

Most text is presented in the typeface used in this paragraph. Other typefaces are used to help you identify certain types of information.
The other typefaces are:

Typeface Example	Usage
clear {**[ip dhcp binding]**}	Commands are in bold blue text and keywords for those command use bold green text.
<WORD>	Arguments in which you supply the values are in purple italics.
username [nopassword] | [privilege 1] | 15] | [secret 0 *<cleartext-password>*] | [5 *<hidden-user-secret>* | *<cleartext-password>*]	Square brackets means optional elements, but not required to complete the command. Such as command username does not require nopassword, privilege or secret for completion. Vertical bars within this example separate alternative choices and can be viewed as an or between parameters.
snmp-server {**contact *<contact-name>***}	Curly braces surround the entire keyword/ optional commands.
Perle IRG7000/5000 5G/LTE Router Series, User's Guide	This typeface indicates a book or document title.
See ***About This Book*** for more information.	This indicates a cross-reference to another chapter or section that you can click on to jump to that section.

Setting up the Router

For information on how to set up your router for the first time, see the Hardware Installation Guide (HIG) or User's Guide for your product. These are available on the Perle Web site at https://www.perle.com/downloads/.

1 Using the Command-Line Interface

This book provides the command line interface (CLI) options available for the Perle router. This chapter describes how to use the command-line interface (CLI) to configure software features. Commands are grouped by Command modes. Some CLI commands may not be applicable to your model or running software.

Command Modes

Command Mode	Prompt	Exit Mode	Access Next Mode
User EXEC mode	Perle>	**logout** command	**enable** command
Privileged EXEC mode	Perle#	**disable** command	**configure** command
Global configuration mode	Perle(config)#	**end** or **exit** command	**interface** command
Interface configuration mode	Perle(config-if)# Perle(config-if-range)#	**end** command	**interface** command, interface type, interface number
Line configuration mode	Perle(config-line)#	**end** command	**interface** command, interface type, interface number

Each command is broken down into several categories:

- **Description**—Provides a brief explanation of how the command is used.
- **Syntax**—Shows the actual command line options. The options can be typed in any order on the command line. The syntax explanation will use the following command to break down the command syntax:

  ```
  For example: telnet 172.16.4.92
  This command opens a telnet session to the host with the
  IP address of 172.16.4.92. If you use a name rather than
  an IP address, you can use the /ipv4 option to force the
  connection to use an IPv4 format for the network address.

  For example: sdm [default|dual-ipv4-and-ipv6]
  This command sdm has an option of either default or dual
  ipv4 and ipv6. You can choose either option but not both.
  ```

Braces ({}) group required choices and vertical bars (|) separate the alternative choices. Square brackets ([]) show the options that are available for the command. You can type a command with each option individually, or string options together in any order you want. Brace and vertical bars within square brackets {[]} means requires a choice within and optional element. The pipe (|) within a square bracket means a choice between the elements.

For example, valid values for (config)#ip {community-list [expanded | standard]}. Valid values are expanded or standard but you cannot select both at the same time.

- **Options**—Provides an explanation of each of the options for a command and the default value if there is one. Some commands do not have any options, so this category is absent.
- **UP arrow**—show a history of the previous commands entered.

Command Shortcuts

When you type a command, you can specify the shortest unique version of that command or you can press the **TAB** key to complete the command. For example, the following command:

```
Perle(config)#service dhcp
```

can be typed as:

```
Perle(config)#se d
```

or, you can use the **TAB** key to complete the lines as you go along:

se<**TAB**>d<**TAB**>

where the **TAB** key was pressed to complete the option as it was typed.

Command Options

When you are typing commands on the command line (while connected to the router, you can view the options by typing a question mark (**?**), after any part of the command to see what options are available/valid. For example:

Perle#terminal ?

```
help
history
length
monitor
no
width
```

Common Commands

default

Use the default command to set a command back to it's defaults.

disable

Use the disable command to de-elevate from Privilege EXEC mode to User Exec mode.

do-exec

Run exec commands while in config mode.

enable

Use the enable command to elevate to Privilege EXEC mode from User Exec mode.

exit

The exit command in User EXEC mode logs you out of the router. In command mode it takes you to down one level of authority.

help

The help command gives you full help or partial help depending on your needs.

Usage Guidelines

Help may be requested at any point in a command by entering a question mark '?'. If nothing matches, the help list is empty and you must backup until entering a '?' shows available options.

Two styles of help are provided:

1. Full help is available when you are ready to enter a command argument (e.g. show ?.)
2. Partial help is provided when an abbreviated argument and you want to know what arguments match the input (e.g. 'show pr?'.)

login

Log into the router.

logout

Log out of the router.

no

Use the no command to negate a command.

Perle> ?

- The ">" indicates that the current mode is "User EXEC"

User Exec Mode

clear	Reset functions
enable	Switch to privilege mode
exit	Exit from EXEC
help	Description of the interactive help
line-attach	Attach to a configured terminal line
logout	Logout of current user
password	Change your password
ping	Send echo messages
release	Release a resource
renew	Renew a resource
show	Display internal settings
ssh	Open a secure shell client connection
telnet	Open a telnet connection
terminal	Set terminal characteristics
testemail	Send a test email message
traceroute	Trace route to destination
two-factor	Change two factor settings

Example:
>clear ip dhcp binding *

Perle# ?

- The "#" indicates that the current mode is "Priviliged EXEC"

Privilege EXEC Mode

archive	Manage archive files
boot	Modify system boot parameters
cd	Change current directory
cellular	Cellular commands
clear	Reset functions
clock	Manage system clock
configure	Switch to (config)#
container (OCI)	Container operational commands
copy	Copy from one file to another
debug	Debugging functions (see also ’undebug’)
delete	Delete files
dir	List files on a file system
disable	Leave privileged mode
disconnect	Disconnect an existing network connection
dot1x	IEEE 802.1X Exec commands
exit	Exit from the EXEC
help	Description of interactive help
kill	Reset the serial line
line-attach	Attach to a configured terminal line
logout	Logout of current user
mkdir	Create a new directory
more	Display the contents of a file
no	Negate a command or set to defaults
password	Change your password
ping	Send echo messages
pwd	Display present working directory
release	Release a resource

reload	Reboot the router
rename	Rename a file
renew	Renew a DHCP lease
reset	Reset commands
rmdir	Remove a directoy
serialt	Take a serial trace
show	Display internal settings
shutdown	Shut down the router
ssh	Open a secure shell client connection
standby	Power standby mode operations
telnet	Open a telnet connection
terminal	Set terminal characteristics
testemail	Send a test email message
testsms	Send a test SMS message
traceroute	Trace route to destination
two-factor	Change your two factor settings
undebug	Disable debugging function (also see ’debug’)
vrrp	VRRP commands

Example:
Perle(config)#hostname TESTLAB<cr>
TESTLAB(config)#

Global Configuration Mode

aaa	Authentication, Authorization and Accounting
alarm	Environmental facilities
archive	Archive software and configuration commands
arp	Set ARP options or static entry
banner	Define a login banner
boot	Modify system boot parameters
bridge	Bridge group and spanning-tree logging
cellular	Cellular commands
class-map	Configure class map
clock	Configure time-of-day clock
container (OCI)	Configure container (OCI) applications
container management (OCI)	Configure container (OCI) management
controller	Configure a specific controller
crypto	Encryption operations
default	Set a command to its default
do-exec	Run exec command in config mode
dot11	IEEE 802.11 WLAN
dot1x	IEEE 802.1X global configuration commands
eap	EAP global configure commands
email	Email notifications configuration
enable	Set enable password
end	End the config session
exit	Exit config mode
gnss	GNSS configuration
help	Description of interactive help
hostname	Set system's network name
interface	Select an interface
ip	Global configuration commands

ipv6	Global IPv6 configuration commands
key	Key management
ldap	LDAP server configuration command
line	Configure a terminal line
lldp	Global LLDP configuration subcommands
logging	Set logging
login	Login configuration
low-power-mode	Low power mode configuration
mac	Global MAC configuration subcommands
management-access	Management access commands
nat66	NAT66 interface commands
network-watchdog	Configure network watchdog
no	Negate a command or set its default
ntp	Configure NTP
policy-map	Configure policy map
power	Configure power parameters
radius	RADIUS configuration
radius-server	RADIUS server configuration
remote-management	Configure remote management/RESTful API
route-map	Create route map or enter route map mode
router	Enable a routing process
sdm	Configure system network profile (enable IPv6)
serial	Serial commands
service	Network based services configuration
snmp-server	Enable SNMP, modify SNMP engine parameters
standby	Configure power management standby
tacacs	TACACS+ configuration
tacacs-server	TACACS+ server configuration
tty	Configure terminal controller

usb	Configure USB parameters
username	Configure user name authentication
wan	Configure WAN management
zone	Firewall with zoning
zone-pair	Zone pair firewall

```
Perle#configure
Configuring from terminal
Perle(config)#
Perle(config)#interface eth 1
Perle(config-if)#
```

Show Command Filtering and Redirection

The router's CLI command prompt provides you ways of searching through large amounts of show/more output and then filtering the output according to parameters (regular expressions) that you supply on the command line. This allows you to filter on patterns such as a phrase, number, or more complex patterns.

A regular expression can be a single-character pattern or a multiple-character pattern. That is, a regular expression can be a single character that matches the same single character in the command output or multiple characters that match the same multiple characters in the command output. The pattern in the command output is referred to as ***<LINE>***. This section describes creating both single-character patterns and multiple-character patterns.

```
[begin | count | exclude | include} <LINE> |
        section [exclude | include] <LINE> |
        format json |
        redirect flash: <file-name> |
            ftp:///[[username:password@]{hostname | host-ip}/directory]/<filename> |
            http://[[username:password]@]{hostname | host-ip}/ [directory]/<filename> |
            http://[[username:password]@]{hostname | host-ip}/ [directory]/<filename> |
            nvram:<file-name> |
            scp://[[username:password@location]/directory]/<filename> |
            sftp://[[//username:password]@location]/directory]/<filename> |
            tftp://[{hostname | host-ip}/ [directory]/<filename> |
        append flash: <file-name> | nvram:<file-name> |
        tee /append]flash:<file-name> |
            ftp:///[[username:password@]{hostname | host-ip}/directory]/<filename> |
            http://[[username:password]@]{hostname | host-ip}/ [directory]/<filename> |
            http://[[username:password]@]{hostname | host-ip}/ [directory]/<filename> |
            nvram:<file-name> |
            scp://[[username:password@location]/directory]/<filename> |
```

sftp://*[[//username:password]@location]/directory]/<filename>* |
tftp://*[{hostname | host-ip}/ [directory]/<filename>*}

Output Modifiers

append	Appends redirected output to the specified flash: or nvram: filename.
begin	Begin unfiltered output with the first line that contains the regular expression and every line there after.
count	Displays a count of the number of occurrences of the regular expression.
exclude	Display output lines that do not contain the regular expression.
format	Format the output using the specified format.
include	Display output line that contain the regular expression.
redirect	Redirect output to specified URL and file name. The file is created or overwrites it if it already exists.
section	Displays output lines that contain the regular expression as well as any lines associated, (any lines immediately following the line that contains the regular expression).
tee	Display the output on-screen while being redirected or appended to the specified URL and file name.
line	This is a regular expression that is used to filter the output. A regular expression is a pattern (a phrase, number, or more complex pattern) that the router's CLI command uses to match against show or more command output. Regular expressions are case-sensitive and allow for simple matching requirements such as "include" entries like "serial or 138".

Single-Character Patterns

The simplest regular expression is a single character that matches the same single character in the command output.
You can use any letter

- (A-Z, a-z)
- or digits (0-9)
- or characters such as ! or ~

Certain key board characters have special meaning using in regular expressins.The table below lists the keyboard character that have special meaning.

Character	Special Meaning
.	Match any single character, including white space.
*	Matches 0 or more sequences of the pattern.
+	Displays output lines that do not contain the regular expression.

?	Matches 0 or 1 occurrences of the pattern. Use <ctl-v) if you need to enter a "?".
^	Matches the beginning of the string.
$	Redirect output to specified URL and file name. The file is created or overwrites it if it already exists.
_ (underscore)	Matches a comma (,), left brace ({), right brace (}), right parenthesis ()), left parenthesis (()), the beginning of the string, the end of the string, or a space.

To use these special characters as single-character patterns, you must remove the special meaning by preceding each character with a backslash (\).
For example:
\$ = $ (dollar sign)
_ = _ (underscore)
\+ = + (plus symbol

You can also specify a range of single-character matches against the command output by placing the square brackets around the characters to be matched.
For example:
[abcd] or simply [a-d]

You can include a left square bracket ([) as a single-character pattern in your range, by preceding the ([) with a backslash. The following example match son character a-d and ([)
For example:
[a-d\[]

You can reverse the matching of the range by including a caret (^) at the start of the range. The following example matches any letter except the ones listed.
For example:
[^a-dqsk]

Multiple-Character Patterns

When creating regular expressions, you can also specify a pattern containing multiple characters. You create multiple-character regular expressions by joining letters, digits, or keyboard characters that do not have special meaning.
For example:
a4% = a multiple-character regular expression.
Note: Insert a backslash before the keyboard characters that have special meaning when you want to indicate that the character should be interpreted literally.
\$ = $ (dollar sign)
_ = _ (underscore)
\+ = + (plus symbol

Order is important with multiple-character patterns. The regular expression b5! matches the character b followed by a 5 followed by a ! symbol. If the string does not have b5!, in that order, pattern matching fails.

In this example the multiple-character regular expression b.uses the special meaning of the period character to match the letter a followed by any single character. The use of (.) period character within a multiple-character expression has a special meaning in that any character matching after the initial character is deemed a match.
For example:
b. = matches bb, b!, b2

Note: You can remove the special meaning of the period character by inserting a backslash before it. For example, when the expression b\. is used in the command syntax, only the string b. is matched.

You can also create multiple-character regular expressions with combination of letters, digits, and other keyboard characters.
For example:
abc33vu77 is a valid regular expression.

2 User Exec Mode

Once you have accessed the router, you are automatically in User Exec mode. The following commands are valid in User EXEC mode. Some CLI commands may not be applicable to your model or running software.

clear ip dhcp binding

{**clear ip dhcp binding** * | *A.B.C.D*}

Syntax Description	**clear ip dhcp binding**
* | *A.B.C.D*}	Type * to clear all automatic bindings. Type the IPv4 address of the specific DHCP binding to clear.
Command Modes	Perle>clear ip dhcp binding

Usage Guidelines

Use this command to clear DHCP client bindings. The * parameter clears all or enter the IPv4 address to clear.

Examples

This example clears all IP DHCP client bindings.

```
Perle>clear ip dhcp binding *
```

This example clears IP DHCP bindings for a specified IP address.

```
Perle>clear ip dhcp binding 172.16.113.44
```

Related Commands

renew

release

enable

Syntax Description	**enable**
Command Modes	Perle>enable

Usage Guidelines

Use this command to elevate the user from user exec level to privileged level.

Examples

This example sets user level to privileged level.

```
>enable
Password:perle
Perle#
```

Related Commands

disable

exit

exit

Syntax Description	exit
Command Modes	Perle#exit

Usage Guidelines

Use this command to exit from EXEC mode.

Related Commands

logout

disable

line-attach

line-attach

{tty <*1-2*> <*WORD*>}

Syntax Description	line-attach
{tty *<1-2><WORD>*}	Applies only to models with serial ports. Displays available serial ports configured for ssh or telnet protocol. On user log in, line access privileges will be based on this authentication not the original authentication request. *<WORD>* SSH user name is optional. If it is not entered, the username logged into the router's main session is used.
Command Modes	Perle>line-attach

Usage Guidelines

Use this command to connect to serial ports configured as Console Management ports. The available ports for both Telnet and SSH are displayed. This feature only exists on models which have serial port/s.

Examples

This example connects a user to serial port 1.

```
Perle>line-attach tty 1
```

logout

logout

Syntax Description	logout
logout	Logs out of the router.
Command Modes	Perle>logout

Usage Guidelines

Use this command to log out of the router.

Examples

This example logs you out of your router.

Perle>logout

password

password

Syntax Description	password
Command Modes	Perle>password

Usage Guidelines

Allows logged in user to change their password.

Examples

This example changes a logged in user's password.

Perle> password

Password must be less than 128 characters long

May not use 5 previous Passwords

Enter Old password

Enter New password

Re-Enter new password

ping

ping

{*<WORD>* **data** *<HEX DIGITS>* | **repeat** *<1–2147483647>* | **size** *<36–18024>*}

Syntax Description	ping
{*<WORD>* **data** *<HEX DIGITS>* | **repeat** *<1–2147483647>* | **size** *<36–18024>*}	Configure the destination. • IPv4 address or IPv6 address • Host name (pre-configured in your router's host table) or a DNS server needs to be reachable • Data—input in hex data to repeat • Repeat—how many time to run the ping command • Size—Configure the size of the packet to ping with
Command Default	56 (84) bytes of data 10 times
Command Modes	Perle>ping

Usage Guidelines

Use this command to ping a remote host.

This example pings a host with an IP address of 172.16.113.44 and repeats the ping 10 times.

```
Perle>ping 172.16.113.44 repeat 10
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=2.91 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=1.17 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=2.93 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=1.666 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=0.921 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=1.05 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=1.118 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=1.00 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=1.00 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=1.50 ms
64 bytes from 172.16.4.90: icmp_seq=1 ttl=64 time=0.897 ms
```

Related Commands

testemail
testsms
show ip interface

release

release

{**dhcp | dhcpv6 [bvi *<1–9999>*] | [dot11radio <0-4>] | [ethernet*<1-5>* . *<1–4000>*]** }

Syntax Description	**release dhcp | dhcpv6**
{**dhcp | dhcpv6 [bvi *<1–9999>*] | [dot11radio <0-4>] | [ethernet *<1-5>*. *<1–4000>*]** }	Type the Ethernet interface (and sub-interface) or BVI interface to release the DHCP/DHCPv6 IP address. Ethernet values are ***<1-5>*** sub-interfaces 1–4000 bvi values are 1–9999 Dot11radio interface to release the DHCP / DHCPv6 IP address. Values are Dot11radio 0–4
Command Modes	Perle>release dhcp

Usage Guidelines

Use this command to release the DHCP/DHCPv6 IP address given to the router by the DHCP/DHCPv6 server. To obtain a new DHCP/DHCPv6 IP address lease, use the DHCP/DHCPv6 renew command.

Examples

This example releases the DHCP IP address for Ethernet interface 2.

```
Perle>release dhcp ethernet 2
```

Related Commands

renew

renew

renew

{dhcp | dhcpv6 [bvi *<1–9999>*] | [dot11radio <0-4>]| [ethernet *<1-5>* . *<1–4000>*] }

Syntax Description	renew dhcp | dhcpv6
{dhcp | dhcpv6 [bvi *<1–9999>*] | [dot11radio <0-4>]| [ethernet *<1-5>* . *<1–4000>*] }	Type the Ethernet interface (and sub-interface) or BVI interface to renew the DHCP/DHCPv6 IP address. Ethernet values are *<1-5>*, sub-interfaces 1–4000 Bvi values are 1-9999 Type the dot11radio interface to renew the DHCP/DHCPv6 IP address. Values are 0–4.
Command Modes	Perle>renew dhcp

Usage Guidelines

Use this command to renew the DHCP/DHCPv6 IP address lease from the DHCP/DHCPv6 server pool.

Examples

This example renews the DHCP lP address lease on Ethernet 1.

```
Perle>renew dhcp eth 1
```

Related Commands

release

show alarm

show alarm

{description port |
profile [*<WORD>*] |
settings enabled |

[*<filter/redirection options>*]}

Syntax Description	show alarm
{**description port** |	Displays alarm statuses. • 1—Link has failed • 2—Port not-forwarding • 3—Port not operating
profile [*<WORD>*] |	Type the alarm profile name to view.
settings enabled |	Displays settings for enabled alarms.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show alarm

Usage Guidelines

Depending on the model, your show alarms output maybe different.

Use this command to display alarm descriptions, profiles, and enabled alarms.

Link has failed—The router generates a link fault alarm when problems with a port's physical layer causes unreliable data transmission. A typical link fault condition is loss of signal or clock. The link fault alarm clears automatically when the link fault condition clears. The severity for this alarm is error condition, level 3.

Port not forwarding—Only used for Ethernet ports. The router generates a port not-forwarding alarm when a port is not forwarding packets. This alarm clears automatically when the port begins to forward packets. The severity for this alarm is warning, level 4.

Port not operating—The router generates a port not-operating alarm when a port fails during the startup self-test. When triggered, the port not-operating alarm only clears when the router is restarted and the port is operational. The severity for this alarm is error condition, level 3.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

To show alarm descriptions.

```
Perle>show alarms description
1 Link Fault
2 Port not Forwarding
3 Port Not Operating
```

```
Perle>show alarms profile
DefaultPort:
      Interfaces wlm0, eth1, eth2, eth3, eth4

Alarms      link fault, not operating
      Syslog      link fault, not operating
      Notifies     link fault, not operating
      Relay Major link fault, not operating
```

Related Commands

alarm

show arp

show arp

{**<A.B.C.D>** |
[*<filter/redirection options>*]}

Syntax Description	**show arp**
{**<A.B.C.D>** |	Displays the ARP table or entry.
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show arp

Usage Guidelines

Use this command to display the ARP table or entry.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the ARP table.

```
Perle>show arp
Address          Hardware Addr      Interface      Hw Type
172.16.23.124      6c:3b:e5:20:26:db   eth3          ether
172.16.73.200      a4:bb:6d:ac:5c:65   eth3          ether
```

Related Commands

clear arp-cache

arp

show clock

show clock

{[*<filter/redirection options>*]}

Syntax Description	**show clock**

{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show clock

Usage Guidelines

Use this command to display current clock information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows you how to display clock information.

```
Perle>show clock
.Tue Mar 16 17:58:02 EDT 2021
```

Related Commands

clock

show crypto

show crypto

{ipsec [client <*WORD*>] | [esp-group <*WORD*>] | [ike-group <*WORD*>] | [ipsec.conf] | [12tp] | [status] |

openvpn ca [<*NAME*>] | cert [<*NAME*>] | connection [<*WORD*>] | dh [<*WORD*>] | key [<*NAME*>] | secret [<*NAME*>] | [status] | template [<*NAME*>] |

pki client trustpoint | openvpn ca [<*NAME*>] | cert [<*NAME*> | key [<*NAME*>] | server trustpoints [<*WORD*>] | [status] |

ssl |

[<*filter/redirection options*>]}

Syntax Description	show crypto
{ipsec [client <*WORD*>] | [esp-group <*WORD*>] | [ike-group <*WORD*>] | [ipsec.conf] | [12tp] | [status] |	Displays crypto details. Displays L2TP details. Displays status. IPsec client (peer)—typically @leftside or a hostname.
openvpn ca [<*NAME*>] | cert [<*NAME*>] | connection [<*WORD*>] | dh [<*WORD*>] | key [<*NAME*>] | secret [<*NAME*>] | [status] | template [<*NAME*>]} |	Displays OpenVPN details.

pki client trustpoint | openvpn ca [<*NAME*>] | cert [<*NAME*> | key [<*NAME*>] | server trustpoints [<*WORD*>] | [status] |	Displays details for pki client trustpoints, and OpenVPN.
ssl |	Displays SSLdetails.
[<*filter/redirection options*>]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show crypto

Usage Guidelines

Use this command to display session information for encryption based services.

Examples

This example displays the version of SSL installed on the router.

```
Perle>show crypto ssl
SSL cipher suite: TLS v1.2
```

Related Commands

crypto

show dot1x

show dot1x

{**[all | details | statistics] |**
[credential <*WORD*>] |
[interface ethernet <*1-5*> details | statistics] |
[radius statistics interface ethernet <*1-5*>] |
[<*filter/redirection options*>]}

Syntax Description	show dot1x
{**[all | details | statistics] |**	Select all, details, or statistics to view dot1x connection details.
[credential <*WORD*>] |	Displays the credential profile for this user.
interface ethernet <*1-5*> details | statistics] |	Enter the Ethernet interface to show connections authenticated with dot1x.
[radius statistics interface ethernet <*1-5*>] |	Displays RADIUS statistics for authenticator mode.
[<*filter/redirection options*>]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show dot1x

Usage Guidelines

Use this command to display the connection information for Dot1x supplicant and authenticator connections.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays all dot1x devices.

```
PerleRouter>show dot1x all
Sysauthcontrol          Enabled
Dot1x Protocol Version        3

Dot1x Info for Ethernet2
=================================
PAE  = AUTHENTICATOR
QuietPeriod  = 60
SuppTimeout = 30
ReAuthMax   = 2
MaxReq      = 2
TxPeriod    = 30
Dot1x Info for Ethernet2
=================================
PAE  = SUPPLICANT
StartPeriod  = 30 (fixed)
AuthPeriod  = 30 (fixed)
HeldPeriod  = 60 (fixed)
MaxStart    = 3  (fixed)
Credentials profile  = lfelton
EAP profile  = md5chap
```

Related Commands

dot1x

(config-dot1x-creden)

show eap

show eap

{**profile** *<WORD>* |

registration |

[*<filter/redirection options>*]}

Syntax Description	show eap
{**profile** *<WORD>* |	Displays pre-defined EAP profiles.
registrations |	Displays registered EAP methods.

[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show eap

Usage Guidelines

Use this command to display configured methods and pki-trustpoints for EAP configured profiles. EAP profiles are configured using the eap profile <name> command. The registration show command displays the EAP methods supported by your router.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays eap registrations.

```
Perle>show eap registrations

Registered EAP Methods:
=======================
 Method  Type          Name
  4     Auth and Peer  MD5
  6     Auth and Peer  GTC
  13    Auth and Peer  TLS
  21    Auth and Peer  TTLS
  25    Auth and Peer  PEAP
  26    Auth and Peer  MSCHAPV2
```

Related Commands

eap

(config-eap-profile)

show environment

show environment

{**alarm-contact | all | temperature status** |
[*<filter/redirection options>*]}

Syntax Description	**show environment**
{**alarm-contact | all | temperature status** |	Shows alarm contact, all and temperature
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show environment

Usage Guidelines

Use this command to show the router's environment. Output can be different depending on your model.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays environment settings.

```
>show environment alarm-contact
External alarm contact A:
  Description: AUX-IO: Digital Input A
  Digital Input: Value: Closed  Transitions: 0  Pulses: 0
External alarm contact B:
  Description: AUX-IO: Digital Input B
  Digital Input: Value: Closed  Transitions: 0  Pulses: 0
External alarm contact 1:
  Description: DC-POWER: IGN
  Analog Input: Value: 0.17 Volts  Transposed Value: 9.962 Celsius
External alarm contact 2:
  Description: DC-POWER: GPIO
  Digital Input: Value: Closed  Transitions: 0  Pulses: 0
  Analog Input: Value: 1.15 Volts  Transposed Value: 1.148 kelvin
Perle>show environment alarm-contact
External alarm contact 1
   Description: DC-POWER:A1
   Analog Input: Value: 42.32 Volts Transposed Value:42.324 Volts
```

show facility-alarm

show facility-alarm

{**relay major** |
status |
[*<filter/redirection options>*]}

Syntax Description	show facility-alarm
{**relay major** |	Displays alarms on major relay.
status |	Displays facility alarm status.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show facility-alarm

Usage Guidelines

Use this command to display alarm statuses. Output can be different depending on your model.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays facility alarm statuses.

```
Perle>show facility-alarm status
Source                Severity              Description Actions
-----------------------------------------------------------------------------------------------------
PerleServer           Minor Temperature below min secondary LOG,NOT,LTE-D MAJ
```

show flash:

show flash:

{[*<filter/redirection options>*]}

Syntax Description	show flash:
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show flash:

Usage Guidelines

Use this command to display files on the internal flash drive.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

```
Perle>show flash:
Directory of flash:
 14      drwx      4096 Dec 31 2019 19:00 -04:00 doc
 32      -rw-       932 Nov 23 2020 16:52 -04:00 perle-internal.log
2254      dr-x      1024 Jan 3 2020 20:36 -04:00 copyright
 37      -rw-    717385 Mar 14 2021 04:12 -04:00 managed-devices.yaml
 28      -rw-         5 Jan 5 2020 18:27 -04:00 update-sw-control.txt

1372160 KBytes total (1282048 KBytes free)
```

Related Commands

delete

mkdir

copy

dir

cd

rmdir

show hosts

show hosts

{[*<filter/redirection options>*]}

Syntax Description	show hosts
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show hosts

Usage Guidelines

Use this command to display the host table.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays host table information.

```
Perle>show hosts
Default domain name is Perle
DNS lookup is enabled
Name servers are not configured

Host Table:
accounting-host 172.16.77.99
banking-host 172.16.88.99
test-host 172.16.55.44
```

Related Commands

ip host

show ip arp

show ip arp

{[*<filter/redirection options>*]}

Syntax Description	show ip arp
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ip arp

Examples

Perle>show ip arp

```
Address          Hardware Addr      Interface     Hw Type
0.0.0.0          81:01:71:e1:71:51  eth3          ether
172.16.73.200    41:b1:d1:c1:c1:51  eth3          ether
172.16.1.1       41:c1:c1:a1:91:31  eth3          ether
172.16.23.124    c1:b1:51:a1:61:b1  eth3          ether
172.16.113.215   c1:b1:21:a1:21:11  eth3          ether
```

Usage Guidelines

Use this command to display ARP entries.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Related Commands

arp

show ip ddns

show ip ddns

{service [bvi *<1–9999>*] |[cellular *<0–0>*] | [dialer *<0–15>*] | [ethernet *<1-5>*] | [openvpn-tunnel *<0–999>*] | [tunnel *<0–999>*] |
use-web [bvi *<1–9999>*] |[cellular *<0–0>*] | [dialer *<0–15>*] | [ethernet *<1-5>*] |[openvpn-tunnel *<0–999*] | [tunnel *<0–999>*] |
[*<filter/redirection options>*]}

Syntax Description	show ip ddns
**{service [bvi *<1–9999>*] |[cellular *<0–0>*]	[dialer *<0–15>*]	[ethernet *<1-5>*]	[openvpn-tunnel *<0–999>*]	[tunnel *<0–999>*] |**	Displays interfaces with DDNS service enabled.
**use-web [bvi *<1–9999>*] |[cellular *<0–0>*]	[dialer *<0–15>*]	[ethernet *<1-5>*] |[openvpn-tunnel *<0–999*]	[tunnel *<0–999>*] |**	Web check used for obtaining the external IP address.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ip ddns

Usage Guidelines

Use this command to display information for Dynamic DNS (DDNS).

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the DDNS service configured on Ethernet port 2.

```
Perle>show ip ddns service ethernet 1
Service dyndns
  Login       testddns
  Password    ********
```

show ip dhcp

show ip dhcp

{**bindings** |
pool *<WORD>* |
[*<filter/redirection options>*]}

Syntax Description	show ip dhcp
{**bindings** | **pool** *<WORD>* |	Displays current bindings.
pool *<WORD>* |	Displays current DHCP configured pools.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ip dhcp

Usage Guidelines

Use this command to display DHCP bindings and pool information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the configured DHCP pools.

```
Perle>show ip dhcp pool
Pool pooltest:
  Total addresses: 11
  Leased addresses : 2
  Exluded addresses: 0
  IP address Range: 172.16.113.60 - 172.16.113.70
```

Related Commands

renew

release

show ip host-group

show ip host-group

{[*<WORD>*] |
[*<filter/redirection options>*]}

Syntax Description	show ip host-group
{[*<WORD>*] |	Displays IP host group.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ip host-group

Usage Guidelines

Use this command to display IP Host Group information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays all IP host groups.

```
Perle>show ip host-group
Host list: Perle
  172.16.66.99
   radius
   Rad2
```

show ip http

show ip http

{**server status** |
[*<filter/redirection options>*]}

Syntax Description	show ip http
{**server status** |	Displays the configured HTTP server parameters.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ip http

Usage Guidelines

Use this command to display HTTP server information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the parameters for the HTTP server.

```
Perle>show ip http server status
HTTP server status: Enabled
HTTP server port:80
User session idle timeout: 1440 seconds
HTTP secure server status: Enabled
HTTP secure server port: 443
```

Related Commands

ip http

show ip interface

show ip interface

{[*<filter/redirection options>*]}

Syntax Description	show ip interface
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ip interface

Usage Guidelines

Use this command to display all interfaces on the router.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the IP interfaces.

Perle>show ip interface

```
Interface   IP Address          Mask               Admin Status   Link Status  Description
=========   ==================  =================  ============   ===========  ===========
lo          127.0.0.1           255.0.0.0          up             up
eth1        172.16.113.215      255.255.0.0        up             up
eth1.2      -                   -                  up             up
eth1.100    -                   -                  up             up
eth2        -                   -                  up             down
eth2.2      -                   -                  up             down
eth2.90     -                   -                  up             down
eth2.100    -                   -                  up             down
eth2.200    -                   -                  up             down
eth2.2000   -                   -                  up             down
eth2.3000   -                   -                  up             down
eth2.4000   -                   -                  up             down
wlan0       -                   -                  up             down         lynsradio
wlan1       -                   -                  up             up
wlan4       -                   -                  up             up
wlm0        25.108.98.56        255.255.255.240    up             up
br10        -                   -                  up             down
tun10       -                   -                  up             up
vtun10      -                   -                  admin down     down
PerleRouter>
```

Related Commands

(config-if)#bvi

(config-if)#cellular

(config-if)#dialer

(config-if)#openvpn-tunnel

(config-if)#tunnel

(config-if)#dot11radio

show ip ssh

show ip ssh

{[*<filter/redirection options>*]}

Syntax Description	show ip ssh
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***

Command Modes	Perle>show ip ssh

Usage Guidelines

Use this command to display IP SSH information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays SSH information.

```
Perle>show ip ssh
SSH version: 2
SSH server: Enabled
Authentication timeout: 120 seconds
Authentication retries: 3
SSH public key:
ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAABAQCgAtvWaaM0CeMWoZV1H00sni2J8T
YalvSyysQGyBDIOAydaaKv1+s1Imj00FL2Boi3ke/
SoKhvuLJQ+bMVFXD7kXw2fk71Mo8f8Dd/
rOuuF4kE6hKV+LLl44kJKwCUC2w2m4L1lH8Zn8HuX89Qcv2oqPUdkBfO1nelU3g
c6gN4v1ckC069Tgg9hrhghCiBECCCYxmAJUhIy4dQcPwO1DQ6Acp2p3lW2RYdg
UvRAlr8oLiVdrEvT7zZECpYgCMYWmfsTtUhvv8yZpvNAhV9nRm5E93Yl0V2J15ql
mlISGKn0iiLRW42xjQ4MT5XmWdlXj+NpuMlQRtFzyYPkR2HMf+9
```

Related Commands

ip ssh

show ipv6

show ipv6

{**dhcp binding | interface client-mode | pool** |
interface |
neighbours [bvi *<1-9999>***] | [cellular** *<0-0>***] | [ethernet** *<1-5>***] | [tunnel** *<0-999>***]** |
[<*filter/redirection options*>**]**}

Syntax Description	show ipv6
{**dhcp binding | interface client-mode | pool** |	Shows DHCP parameters.
interface |	Shows interface configuration and status.
neighbours [bvi *<1-9999>***] | [cellular** *<0-0>***] | [ethernet** *<1-5>***] | [tunnel** *<0-999>***]** |	Shows neighbours cache entries.
[<*filter/redirection options*>**]**}	Output modifiers see ***Show Command Filtering and Redirection***

Command Modes	Perle>show ipv6

Usage Guidelines

Use this command to display IPv6 information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Show IPv6 interfaces.

Perle>show ipv6 interface

```
Interface   IPv6 Address                                  Admin Status   Link Status   Description
---------   ----------------------------------------     ------------   -----------   -----------
lo          ::1/128                                      up             up
eth1        -                                            up             up
eth1.2      -                                            up             up
eth1.100    -                                            up             up
eth2        -                                            up             down
eth2.2      -                                            up             down
eth2.90     -                                            up             down
eth2.100    -                                            up             down
eth2.200    -                                            up             down
eth2.2000   -                                            up             down
eth2.3000   -                                            up             down
eth2.4000   -                                            up             down
wlan0       -                                            up             down          lynsradio
wlan1       -                                            up             up
wlan4       -                                            up             up
wlm0        -                                            up             up
br10        fe80::3448:aeff:fe49:f14f/64                 up             down
tun10       -                                            up             up
vtun10      -                                            admin down     down
PerleRouter>
```

Related Commands

clear ipv6

ipv6

show ldap

show ldap

{**statistics [details]** |

[*<filter/redirection options>*]}

Syntax Description	show ldap
{**ldap statistics [details]** |	Shows LDAP statistics details.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ldap

Usage Guidelines

Use this command to display LDAP statistic details.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Shows LDAP statistics details.

Perle>show ldap statistic details

```
All:
                    Auth.          Acct.
Requests:                0              0
Responses:               0              0
Access Rejects:          0
```

Related Commands

ldap

show line

show line

{**console** ***<0–0>*** |

[***<filter/redirection options>***]}

Syntax Description	**show line**
{**console** ***<0–0>*** |	Applies only to models with serial and console ports. Shows whether the console is using the USB or serial port for console mode.
[***<filter/redirection options>***]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show line

Usage Guidelines

Use this command to display primary terminal line.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Shows line statuses.

Perle>show line

```
Console in use: Serial
Baud rate (TX/RX) is 9600/9600, parity none, 1 stop
bit, 8 data bits
```

Related Commands

line

show lldp

show lldp

{**interface ethernet** *<1-5>* |
neighbors interface [ethernet *<1-5>***] [detail | summary]** |
traffic summary] |
[*<filter/redirection options>***]**}

Syntax Description	show lldp
{**interface ethernet** *<1-5>* |	Displays LLDP interface configuration.
neighbors interface [ethernet *<1-5>***] [detail | summary]** |	Displays LLDP neighbors information.
traffic summary |	Displays LLDP statistics.
[*<filter/redirection options>***]**}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show lldp

Usage Guidelines

Use this command to display LLDP interface configuration, neighbors statistics and traffic statistics.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Show LLDP configuration for Ethernet port 2.

```
Perle>show lldp interface ethernet 2
Tx: enabled
Rx: enabled
Maximum Neighbors: 10
TLVs Advertised:
port-description, system-name, system-description, system-capabilities,
management-address mac-phy-cfg, max-frame-size
```

Related Commands

clear lldp

lldp

show mab

show mab

{**all details | statistics** |
interface ethernet *<1-5>* **details | statistics** |
radius statistics interface ethernet *<1-5>* |
[*<filter/redirection options>***]**}

Syntax Description	show mab

{**all details** | **statistics** |	Displays MAB information.
interface ethernet ***<1-5>*** **details** | **statistics** |	Displays interface MAB details.
radius statistics interface ethernet ***<1-5>*** |	Displays RADIUS MAB details.
[***<filter/redirection options>***]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show mab

Usage Guidelines

Use this command to display MAB (MAC Authentication Bypass) for the Ethernet interfaces or RADIUS.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples:

Shows the MAB interface details for Ethernet interface 1.

```
Perle>show mab interface ethernet 1 details
Interface          Mac-Auth-Bypass
------------------------------------
Ethernet3          Enabled
MAC Auth Bypass Client List
---------------------------
Supplicant          = 00:16:d3:2f:62:bb
 EAP Method         = None
 Port Control State  = Auto
 Auth SM State      = AUTHENTICATED
 Auth BkEnd SM State = IDLE
 Session ID         = B8B01A9D-00000001
 Session Time       = 855
 Identity           = 0016d32f62bb
Eapol Frame Counters:
 Frames Rx          = 2
 Frames Tx          = 0
 Start Frames Rx    = 2
Logoff Frames Rx   = 0
 RespId Frames Rx   = 0
 Resp Frames Rx     = 0
 ReqId Frames Tx    = 0
 Req Frames Tx      = 0
 Invalid Frames Rx  = 0
 Length Error Rx    = 0
 Last Frame Version = 1
 Last Frame Source = 00:16:d3:2f 62:bb
```

show mac

show mac

{**access-list [all] | [interfaces] | [list-name <*WORD*>]** |
address-table [address <*H.H.H*>] | [dynamic] | [interface ethernet <*1-5*>] |
[multicast] | [static] |
[<*filter/redirection options*>]}

Syntax Description	show mac
{**access-list [all] | [interfaces] | [list-name <*WORD*>]** |	Displays MAC access list by all, interfaces or list-name.
address-table [address <*H.H.H*>] | [dynamic] | [interface ethernet <*1-5*> | [multicast] | [static] |	Show MAC address details.
[<*filter/redirection options*>]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show mac

Usage Guidelines

Use this command to display a listing of MAC addresses and MAC access lists.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Show the dynamic MAC address table.

Perle>show mac address-table dynamic

```
 Mac Address Table
-----------------------------------------
Vlan   Mac Address      Type       Ports
----   --------------   -------    -----
  99   0016.3e08.2cbc   DYNAMIC    eth1
  99   0018.f37b.6bb0   DYNAMIC    eth1
  99   0024.c4a2.1762   DYNAMIC    eth1
  99   0080.d406.1df3   DYNAMIC    eth1
  99   00a0.45d9.56dc   DYNAMIC    eth1
  99   24b6.fd13.8885   DYNAMIC    eth1
  99   3085.a9a7.b59e   DYNAMIC    eth1
  99   3c97.0e37.120d   DYNAMIC    eth1
  99   588a.5a44.1903   DYNAMIC    eth1
  99   7071.bc23.1a8f   DYNAMIC    eth1
  99   80ce.62ee.8ab7   DYNAMIC    eth1
  99   80ce.62ee.8c2d   DYNAMIC    eth1
  99   e840.f24a.2cce   DYNAMIC    eth1
  99   f092.1ce3.5748   DYNAMIC    eth1
  99   f48e.3898.ee2c   DYNAMIC    eth1
Total Mac Addresses for this criterion: 15
```

Related Commands

mac

show mac

show ntp

show ntp

{**associations** |

status |

[*<filter/redirection options>*]}

Syntax Description	**show ntp**
{**associations** |	NTP clock associations information.
status |	NTP clock status.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ntp

Usage Guidelines

Use this command to display NTP associations and status.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

```
Perle>show ntp associations
remote          refid      st t when poll reach   delay   offset jitter
==============================================================
 172.16.55.77    .INIT.          16 u    - 1024    0    0.000    0.000   0.000
 172.16.113.55   .INIT.          16 s    -   32    0    0.000    0.000   0.000
Perle>show ntp status
Clock is not synchronized, stratum 16, no reference clock
Precision is 2**-18 s
Reference time is 00000000.00000000 (Thu, Feb 7 2036 2:28:16.000)
Clock offset is 0.000000 msec, root delay is 0.000 msec
Root dispersion is 1265.970 msec
System poll interval is 8 s
```

Related Commands

ntp

show nvram:

show nvram:

{[*<filter/redirection options>*]}

Syntax Description	**show nvram:**
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show nvram:

Usage Guidelines

Use this command to display the contents of nvram: file system.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

```
Perle>show nvram:
Directory of nvram:
89      -rw-    8436 Feb 16 2021 20:50 06:00 startup-config.log.2
 18     -rw-     285 Jan 9 2020 05:06 06:00 no-default-config
 21     -rw-    8950 Feb 19 2021 21:05 06:00 startup-config
 90     -rw-    9054 Feb 18 2021 23:37 06:00 startup-config.log.1
 81     -rw-    9054 Feb 19 2021 21:09 06:00 startup-config.log
 86     -rw-   12289 Nov 23 2020 22:24 06:00 y
 16     -rw-     636 Jan 9 2020 05:06 06:00 default-config

1372160 KBytes total (970752 KBytes free)
```

Related Commands

delete

dir

mkdir

rename

rmdir

pwd

cd

show radius

show radius

{**statistics [details]** |

[*<filter/redirection options>*]}

Syntax Description	show radius
{**statistics [details]** |	Show RADIUS server statistics.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show radius

Usage Guidelines

Use this command to show RADIUS details.

Examples

Use this command to display RADIUS statistics.

```
Perle>show radius statistics
All:
                Auth.          Acct.
Requests        3              3
Responses       3              3
Access Requests 3
```

Related Commands

clear radius

aaa

radius

radius-server

ip radius

show snmp

show snmp

{**contact** |

location |

[*<filter/redirection options>*]}

Syntax Description	show snmp
{**contact** |	Displays contact information
location |	Displays location information.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show snmp

Usage Guidelines

Use this command to show configured options for SNMP.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example show the contact information.

```
Perle>show snmp contact
Labarea
```

Related Commands

snmp-server

show ssh

show ssh

{[*<filter/redirection options>*]}

Syntax Description	show ssh
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show ssh

Usage Guidelines

Use this command to display users connected via SSH.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example show which users are connected.

```
Perle>show ssh
Line      User      Host            Idle      Location
 1   vty 1 admin     idle           00:28:26   172.16.113.31
```

Related Commands

show ip ssh

show tacacs

show tacacs

{**statistics [details]** |
[*<filter/redirection options>*]}

Syntax Description	show tacacs
{**statistics [details]** |	Displays TACACS+ statistics.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show tacacs

Usage Guidelines

Use this command to display TACACS+ server details.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Show TACACS+ statistics.

```
Perle>show tacacs statistics
All:
                Auth.          Acct.
Requests        3              3
Responses       3              3
Access Requests 3
```

Related Commands

clear tacacs

(config-sg-tacacs)

tacacs

(config-tacacs-server)

show terminal

show terminal

{[*<filter/redirection options>*]}

Syntax Description	show terminal
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show terminal

Usage Guidelines

Use this command to display terminal parameters length, width, history enabled, history size, and logging monitor.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This examples displays the parameter for terminal.

```
Perle>show terminal
  Terminal length = 24
  Terminal width = 79
  Terminal history is enabled
  Terminal history size = 11
  Terminal logging monitor is OFF
```

show users

show users

{**all**] |
[console] |
[rest-api] |
[vty] |
[web] |
[*<filter/redirection options>*]}

Syntax Description	show users
{**all**] |	Displays all users.
[console] |	Displays users connected to the console if your model supports a console port.
[rest-api] |	Displays RESTful API users.
[vty] |	Displays users connected via ssh or telnet.
[web] |	Displays web users (HTTP/HTTPS).
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show users

Usage Guidelines

Use this command to display active users.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This examples displays all attached web users.

```
Perle>show users web
User      IP Address          Idle
Lyn       172.16.113.215      00:11:59
```

Related Commands

show version

show version

{**[backup]** |
[flash:] |
[startup] |
[verbose]
[*<filter/redirection options>*]}

Syntax Description	**show version**
{**[backup]** |	Displays backup version of software.
[flash:] |	Displays versions of software in on flash:
[startup] |	Displays the version of software used for startup.
[verbose]}	Displays details about software running on your router.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle>show version

Usage Guidelines

Use this command to display software version information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the startup version of software.

```
Perle>show version
Perle IRG5000 Series Routers, Version: 4.5
```

ssh

ssh

{*<A.B.C.D>* *<X:X:X:X::X>* **[-c | -h | -l | -p** *<A.B.C.D>***]**}

Syntax Description	ssh
{*<A.B.C.D>* *<X:X:X:X::X>* **[-c | -h | -l | -p** *<A.B.C.D>***]**}	Configure a ssh session to a remote host. IPv4 or IPv6 address or hostname to connect to in *<A.B.C.D>* *<X:X:X:X::X>* format. • c–select the encryption method • h–select HMAC algorithm • l–log in using this user name • p–connect to this port
Command Modes	Perle>ssh

Usage Guidelines

Use this command to SSH from your router to a host supporting the SSH protocol.

Examples

This example connects to host (172.16.4.90) using lyn as the user.

```
Perle>ssh -l lyn 172.16.4.90
```

Related Commands

show ssh

telnet

telnet

{*<A.B.C.D>* | *<X:X:X:X::X>*}

Syntax Description	telnet
{*<A.B.C.D>* | *<X:X:X:X::X>*}	Configure a Telnet session to a remote host.
Command Modes	Perle>telnet

Usage Guidelines

Use this command to telnet from your router into a host that supports the telnet protocol.

Examples

This example telnets to host 172.16.4.90.

```
Perle>telnet 172.16.4.90
Trying 172.16.4.90...
Connected to 172.16.4.90.
Escape character is '^]'.
```

```
Red Hat Linux release 9 (Shrike)
Kernel 2.4.20-8custom on an i686
login:
```

Related Commands

telnet

terminal

terminal

{**history size** *<0–256>* |
length *<0–512>* |
monitor *<0–512>* |
width *<0–512>*}

Syntax Description	**terminal**
{**history size** *<0–256>* |	Configure the size of the history buffer.
length *<0–512>* |	Configure the length of the terminal screen
monitor *<0–512>* |	Copies debugging logging output to the current terminal line.
width *<0–512>*}	Configure width of the screen.
Command Default	length–24 width–132
Command Modes	Perle>terminal

Usage Guidelines

Use this command to configure parameters for your terminal session.

Examples

This example sets the terminal width to 132.

```
Perle>terminal width 132
```

Related Commands

show terminal

testemail

testemail

{**email address**}

Syntax Description	**testemail**

{**email address**}	Configure the email address. Format is user@company.com
Command Modes	Perle>testemail

Usage Guidelines

Use this command to send a test email message.

Examples

Perle>testemail ltest@bigshow.com
Email Test message sent to lfelton@perle.com

Related Commands

ping

testsms

testsms

{**phone number**}

Syntax Description	**testsms**
{**phone number**}	Configure the size of the history buffer.
Command Modes	Perle>testsms

Usage Guidelines

Use this command to send a SMS test text message.

Examples

Perle>testsms 6475554455
SMS Test message sent to 6475554455

Related Commands

ping

traceroute

traceroute

{***<A.B.C.D>*** **| hostname | icmp** ***<A.B.C.D>*** **| hostname**}

Syntax Description	**traceroute**
{***<A.B.C.D>*** **| hostname| icmp** ***<A.B.C.D>*** **| hostname**}	Destination hostname or address.
Command Modes	Perle>traceroute

Usage Guidelines

Use this command to trace network connections from one location to another. When a traceroute is run, it returns a list of network hops and displays the host name and IP address of each connection. It also returns the amount of time it took for each connection to take place (usually in milliseconds). This shows if there were any delays in establishing the connection. Therefore, if a network connection is slow or unresponsive, a traceroute can often explain why the problem exists and also show the location of the problem.

Examples

This example displays the hops it takes from the router to IP host address 172.16.4.90.

```
Perle>traceroute 172.16.4.90 (172.16.4.90), 30 hop max, 60 bytes packets
1 172.16.4.90 (172.16.4.90)   2.094ms    1.113 ms     0.826 ms
```

Related Commands

ping

two-factor

two-factor

{**email** ***<WORD>*** |
method email | **sms** | **phone** ***<LINE>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	two-factor
{**email** ***<WORD>*** |	Sends the security key to this email address. Valid format is llhin@yahoo.ca
method email | **sms** | **phone** ***<LINE>***}	Selects the method for sending the security key.
phone ***<LINE>***}	Specify the phone number to send the 2-factor pin number.
Command Modes	Perle>two-factor

Usage Guidelines

Only cellular models have SMS capabilities.

Use this command to configure for two-factor authentication (2FA). Two factor authentication is a method of establishing access to your router by requiring you to provide two different types of information. You will need to provide both a password and key to prove your identity to gain access. Your router supports 2-factor using SMS and Email authentication.

Examples

This example sets your router for 2-Factor authentication using email.

```
Perle>two-factor
Perle>email janedoe@yahoo.ca
```

Related Commands

3 Privileged EXEC mode

This chapter contains the CLI commands for Privileged EXEC mode. Some CLI commands may not be applicable to your model or running software.

archive

archive

{**config** |

download-sw [/force-reload] | [/no-version-check] | [/reload]
[flash:*perle-image-name.img*] |
[ftp:///*[[username:password]@location]/directory]/perle-image-name.img*] | [http://*[[username:password]@][hostname | host-ip] [directory] /perle-image-name.img*] |
[https://*[[username:password]@][hostname | host-ip] [directory] /perle-image-name.img*]
[scp://*[[username@location]/directory]/perle-image-name.img*] | [sftp://*[[//username:password]@location]/directory]/perle-image-name.img*] | [tftp:*[[//location]/directory]/perle-image-name.img*] |

[update-sw auto-download | check] |

[downgrade-sw local] |
[lte-firmware | download [<list> | <word>] | install <word> | update check <word>] |
[[upload-sw flash:image-file] | [ftp:[[//username[:password]@location]/directory]/perle-image-name.img] |
[http://*[[username:password]@][hostname | host-ip [directory] /perle-image-name.img*] |
[https://*[[username:password]@][hostname | host-ip [directory] /perle-image-name.img*] |
[scp:*[[username@location]/directory]/perle-image-name.img*] |
[sftp:*[[//username[:password]@location]/directory]/perle-image-name.img*] |
[tftp:*[[//location]/directory]/perle-image-name.img*]}

Syntax Description	archive
{**config** |	Archives the running configuration. This configuration is saved to a predefined location as specified in the archive command. See ***(config-archive)#*** to set up the path to where the configuration file is stored.

download-sw | **[flash:*perle-image-name.img*] |** **[ftp:///*[[username:password]@location]/directory]/perle-image-name.img*] | [http://*[[username:password]@][hostname | host-ip [directory] /perle-image-name.img*] |** **[https://*[[username:password]@][hostname | host-ip [directory] /perle-image-name.img*]** **[scp://*[[username:password@location]/directory]/perle-image-name.img*] | [sftp://*[[//username:password]@location]/directory]/perle-image-name.img*] | [tftp:*[[//location]/directory]/perle-image-name.img*] |**	Downloads firmware to your router. **/force-reload—**unconditionally forces a system reload after successfully downloading the software image. **/reload—**reloads the system (if no unsaved configuration changes have been made) after a successful upgrade. **/no-version-check—**download the software without verifying it's version compatibility with the image running.
lte-firmware | download [*<list>* | *<WORD>*] | install *<WORD>* | update check *<WORD>* |	LTE firmware files are stored on flash at /product/flash/lte-firmware/EM7455 and //EM7565. **Download list—**displays the available LTE firmware files. Specify **download file** to download a specific file to the LTE modem chip. **Install—i**nstall LTE firmware file operations. **Update—**check if any updates are available for all installed LTE firmware files.
[update-sw auto-download | check] |	Checks if a software update is available. **auto-download—**automatically download firmware if new version found during check. **check—**check to see if a software update is available.

[upload-sw flash:*image-file*] | [ftp:*[[// username[:password]@location]/directory]/perle-image-name.img*] | **[http://** ***[[username:password]@][hostn ame | host-ip [directory] / perle-image-name.img*] |** **[https://** ***[[username:password]@][hostn ame | host-ip [directory] /perle-image-name.img*] |** **[scp:*[[username@location]/ directory]/perle-image-name.img*] |** **[sftp:*[[// username[:password]@location]/directory]/perle-image-name.img*] |** **[tftp:*[[//location]/directory]/ perle-image-name.img*]}**	Uploads the firmware on the router to a server.
Command Modes	#archive

Usage Guidelines

Use this command to manage archive files.

Where a username or password is required it can be specified in the router configuration using the "scp | ftp | sftp | http" command to configure the username and password used instead of specifying it on the archive command.

flash:*image-file*

The syntax for FTP:

[ftp:*//[[username:password]@location]/directory]/perle-image-name.img*] \|

The syntax for an HTTP server:

http://*[[username:password]@][hostname | host-ip] [directory]/perle-image-name.img*

- The syntax for an HTTPS server:

https://*[[username:password]@][hostname | host-ip [directory]/perle-image-name.img*

- The syntax for an SCP server:

[scp:*//[[username:password@location]/directory]/perle-image-name.img*] \|

- The syntax for an SFTP server:

[sftp:*//[[//username:password]@location]/directory]/perle-image-name.img*] \|

- The syntax for an TFTP server:

[tftp:*[[//location]/directory]/perle-image-name.img*] \|

Examples

This example downloads software from a server with an IP address of 172.16.4.182 to your router using secure HTTP (https) and certificate named apache.crt

Step 1) Download a secure certificate to your router
(config)#crypto pki import server apache pem url
tftp://172.16.4.182/apache.crt

Step 2)
Configure your router with the certificate you just downloaded.
(config)#ip http client secure-trustpoint apache

Step 3)
Set validation off if you do not want to valid the certificate. (You must have created the certificate with validation if you want to valid the certificate)
#archive download-sw
https://172.16.4.182/public/router-software.img or .emg
depending on the running firmware.

The software is download using secure https.
This example upload software from a server with an IP address of 172.16.4.92 using scp.
This command is only supported on some models.

Perle#archive upload-sw
scp://lyn:mypassword@172.16.4.92/public//Router.img or .emg file
depending on the running firmware.

Related Commands

show archive
(config-archive)#

boot

boot

{**system backup**}

Syntax Description	**boot**
{**system backup**}	Boots the system with the backup image.
Command Modes	Perle#boot

Usage Guidelines

Use this command to boot the router using an older saved software version. Older software versions are stored as backup software using the archive command.

Examples

This example sets your router to boot using the backup software.

Perle#boot system backup

cd

cd

{**flash: | nvram:**}

Syntax Description	cd
{**flash: | nvram:**}	Change directory on flash: or nvram:
Command Modes	Perle#cd

Usage Guidelines

Use this command to change directory within the flash or nvram file systems.

Examples

This example changes to directory testdir under the flash file system.

Perle#cd flash:testdir

Related Commands

delete
pwd
mkdir
more
cd
rename

cellular

cellular {***<0-0>***
data-usage clear sim-slot ***<1 | 2>*** |
lte active-profile [alternative-profile | primary] | connect |
reset |
sms-log clear}

Syntax Description	cellular
{***<0-0>***	Configure parameters for cellular 0.
data-usage clear sim-slot ***<1 | 2>*** |	Clears data-usage for SIM 1 or SIM 2 card slots. Some product models may have more then one SIM slot.
lte active-profile [alternative-profile | primary] | connect |	Select the active profile. Some product models may have an alternate profile. Enables LTE.
reset	Reset the cellular module.
sms-log clear}	Clears the SMS log file.

Command Modes	Perle#cellular

Usage Guidelines

Use this command to set up LTE parameters.

Examples

This example clears the SMS log file.

Perler#cellular 0 sms-log clear

Related Commands

cellular

clear aaa

clear aaa

{**aaa local user [fail-attempts all | username <*WORD*>] | [lockout all | username <*WORD*>]**}

Syntax Description	clear aaa
{**aaa local user [fail-attempts all | username <*WORD*>] | [lockout all | username <*WORD*>]**}	Resets a locked out user. Resets this locked out user. Resets all locked out users. Resets this user using user name.
Command Modes	Perle#clear aaa

Usage Guidelines

Use this command to reset locked out users.

Examples

This example resets locked out user Marie.

#clear aaa local user lockout username Marie

Related Commands

clear arp-cache

clear arp-cache

{***<A.B.C.D>*** **[bvi *<1-9999>*] | cellular *<0-0>* | [dialer *<0-15>*] | [dot11radio *<0-4>*] | [ethernet *<1-5>* . *<1-4000>*] | [openvpn-tunnel *<0-999>*] | [tunnel *<0-999>*]**}

Syntax Description	clear arp-cache

[bvi *<1-9999>*] | cellular *<0-0>* | [dialer *<0-15>*] | [dot11radio *<0-4>*] | [ethernet *<1-5>* . *<1-4000>*] | [openvpn-tunnel *<0-999>*] | [tunnel *<0-999>*]}	Clears ARP cache on IP address or interface.
Command Modes	Perle#clear arp-cache

Usage Guidelines

Use this command to clear ARP entries from the ARP table.

Examples

This example clears all ARPs from the ARP table for Ethernet interface 1.

#clear arp-cache ethernet 1

Related Commands

show arp

arp

clear bridge

clear bridge {**spanning-tree counters interface [bvi *<1-9999>*] \| [ethernet *<1-5>* *<1-4000>*** }

Syntax Description	**clear bridge**
{**spanning-tree counters interface bvi *<1-9999>* | ethernet*<1-5>* . *<1-4000>*** }	Clears spanning tree counters.
Command Modes	Perle#clear bridge

Usage Guidelines

Use this command to clear spanning tree counters.

Examples

This example clears spanning tree counters on Ethernet interface 1.

Perle#clear bridge spanning-tree counters interface ethernet 1

Related Commands

show bridge

bridge

clear contact

clear contact

{***<2-2 >*** **pulse-counter** |

<A-B> **pulse-counter**}

Syntax Description	**clear contacts**

{*<2-2 >* **pulse-counter** |	Clears the digital input contact counters, also clears outstanding alarm.
<A-B> **pulse-counter**}	Clears the digital input contact counters, also clears outstanding alarm.
Command Modes	Perle#clear contacts

Usage Guidelines

Use this command to clear contacts and alarms. Input and output contacts are different or may not exist on some models.

Related Commands

show environment

clear counters

clear counters

{**[bvi** *<1-9999>***] | [dot11radio** *<0-4>***] | [ethernet** *<1-5>* **| [loopback] | [tunnel** *<0-999>***]**}

Syntax Description	clear counters
{**[bvi** *<1-9999>***]	[dot11radio** *<0-4>***]	[ethernet** *<1-24><1-5>***]	[loopback]	[tunnel** *<0-999>***]**}	Clears counters on specified interface.
Command Modes	Perle#clear counters

Usage Guidelines

Use this command to clear counters back to zero on the specified interface.

Examples

This example clears all counters for Ethernet interface 1.

```
Perle#clear counters ethernet 1
Clear "show interface" counters on this interface [confirm]
```

clear ip

clear ip

{**alg connections** |
bgp * | [*<1-4294967295>*] | *<A.B.C.D>* | [*<X:X:X:X::X:X>*] | **[external in | out | soft]** |
dhcp binding <* | *<A.B.C.D>* |
firewall *<WORD>* |
ospf process |
rip process |

route-policy name <*WORD*> counters | rule <*1-9998*> counters}

Syntax Description	clear ip
{**alg connections** |	Clears ALG connections.
bgp * | <*1-4294967295*> | <*A.B.C.D*> | <*X:X:X:X::X:X*> | **[external in | out | soft]** |	Type * to clear all BGP sessions or connections. Type the connection number, IPv4, or IPv6 address of the session or connection you want to reset. Configure whether it is an inbound or outbound session. No in/out parameters clears both in and outbound.
dhcp binding <* | <*A.B.C.D*> |	Type * to clear all automatic client bindings Type the ip address of the client you want to clear the DHCP binding.
firewall <*WORD*> |	Clears the specified firewall statistics.
ospf process |	Reset OSPF process.
rip process |	Reset RIP process.
route-policy name <*WORD*> **counters | rule** <*1-9998*> **counters**}	Clears counters for route policies.
Command Modes	Perle#clear ip

Usage Guidelines

Use this command to clear IP connections and statistics.

You can clear all DHCP bindings using the * parameter or clear only the binding for a specific IP address by entering in the IP address to clear.

You can also use this command to clear firewall statistics and counters for route policies.

Examples

This example clears all DHCP ip bindings from your DHCP router table.

Perle#clear ip dhcp bindings *

This example clears all BGP connections.

Perle#clear ip bgp *

clear ipv6

clear ipv6

{**firewall name** <*WORD*> |

neighbors <*X:X:X:X::X:X*> | **[bvi** <*1-9999*>**]** | **[cellular** <*0-0*>**]** | **[dialer** <*0-15*>**]** | **[dot11radio** <*0-4*>**]** | **[ethernet** <*1-5*> **.** <*1-4000*>**]** **[vrrp** <*1-255*>**]** | **[openvpn-tunnel** <*0-999*>**]** | **[tunnel** <*0-999*>**]** |

route-policy name <*WORD*> counters | rule}

Syntax Description	clear ipv6
{**firewall name <*WORD*>**|	Clears IPv6 firewalls.
neighbors <*X:X:X:X::X:X*> | [bvi <*1-9999*>] | [cellular <*0-0*>] | [dialer <*0-15*>] | [dot11radio <*0-4*>] | [ethernet <*1-5*> . <*1-4000*>] [vrrp <*1-255*>] | [openvpn-tunnel <*0-999*>] | [tunnel <*0-999*>] |	Clears IPv6 neighbors.
route-policy name <*WORD*> counters | rule}	Clears IPv6 route policies.
Command Modes	Perle#clear ipv6

Usage Guidelines

Use this command to clear IPv6 entries for IPv6 firewalls, neighbors, and route policies.

Examples

This example clears route policy warehouse.

Perle#clear ipv6 route-policy warehouse

Related Commands

show ipv6

ipv6

clear ldap

clear ldap

{**statistics**}

Syntax Description	clear ldap
{**statistics**}	Clears LDAP statistic information.
Command Modes	Perle#clear ldap

Usage Guidelines

Use this command to clear LDAP statistic information.

Examples

This example clears LDAP statistics information on your router.

Perle#clear ldap statistics

Related Commands

(config-ldap-server)

show ldap

clear line

clear line

{**console** *0-0* |
vty *<0-15* |
tty *<1-2>*}

Syntax Description	clear line
{**console** *0-0* |	Clears the console. Console and tty command only available on models with console ports/serial ports.
vty *<0-15>* |	Clears vty or tty sessions.
tty *<1-2>*}	Clears tty sessions. Console and tty command only available on models with console ports/serial ports.
Command Modes	Perle#clear line

Usage Guidelines

Use this command to clear the console, vty, or tty session. The session is disconnected and all statistics are cleared.

Examples

This example clears vty line 1.

```
Perle#clear line vty 1
[confirm]
[Dec 9 16:14:20 %REQHANDLE-6: Cleared VTY1 session
OK]
```

Related Commands

(config-line)#console

(config-line)#tty

clear lldp

clear lldp

{**counters | table**}

Syntax Description	clear lldp
{**counters | table**}	Clears LLDP counters or table.
Command Modes	Perle#clear lldp

Usage Guidelines

Use this command to clears LLDP counters and table.

Examples

This example clears the LLDP table.

```
Perle#clear lldp table
```

Related Commands

show lldp

lldp

clear logging

clear logging

{**logging**}

Syntax Description	clear logging
{**logging**}	Clears the logging buffer.
Command Modes	Perle#clear logging

Usage Guidelines

Use this command to clear logging buffer.

Examples

This example clears the logging buffer.

```
Perle#clear logging
Clear logging buffer[confirm]
```

Related Commands

show logging

clear radius

clear radius

{**radius statistics**}

Syntax Description	clear radius
{**radius statistics**}	Clears RADIUS statistics.
Command Modes	Perle#clear radius

Usage Guidelines

Use this command to clear RADIUS statistics.

Examples

This example clears RADIUS statistics.

Perle#clear radius statistics

Related Commands

radius

radius-server

(config-radius-server)

ip radius

clear tacacs

clear tacacs

{**tacacs statistics**}

Syntax Description	**clear tacacs**
{**tacacs statistics**}	Clears TACACS+ statistics.
Command Modes	Perle#clear tacacs

Usage Guidelines

Use this command to clear TACACS+ statistics.

Examples

This example clears TACACS+ statistical information.

Perle#clear tacacs statistics

Related Commands

tacacs

tacacs-server

ip tacacs

(config-tacacs-server)

clock

clock

{**set hh:mm:ss | 1-31 | month year 2001-2037**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**clock**

{**set hh:mm:ss | 1-31 | month | 2001-2037**}	Configure the current time and date. hh:mm:ss (hour, mins, secs) Day of the month 1-31 Month is • January • February • March, • April • May • June
	• July • August • September • November, • December Year is 2001-2037
Command Modes	Perle#clock

Usage Guidelines

Use this command to configure the clock.

Examples

This example configures the clock to 5 hours off from UTC.

Perle#clock set 12:30:10 28 jan 2020

Related Commands

show clock

configure

configure

{**confirm** |
revert now | **timer** *<1-120 >* | **idle** *<1-120>* |
terminal lock | **revert timer** *<1-120>* | **idle** *<1-120>*}

Syntax Description	configure
{**confirm** |	Cancels the revert timer.
revert now | **timer** *<1-120* > | **idle** *<1-120>* |	Configure the parameters for reverting this config using the rollback feature.
terminal lock | **revert timer** *<1-120>* | **idle** *<1-120>*}	Locks configuration mode. Revert timer.

Command Modes	Perle#configure

Usage Guidelines

Use this command to change from privileged level mode to configuration mode.

This command is also used to configure the parameters for the rollback and terminal lock features.

Examples

This example changes the user from privileged level mode to terminal configuration mode.

```
Perle#configure
Configuring from terminal, memory, or network [terminal]?
Perle(config)#
```

Related Commands

(config-archive)#

archive

container (OCI)

container

{connect *<WORD>* | exec *<WORD>* *<CMDLINE>* *<WORD>* |export-changes *<WORD>* flash:*<WORD>* |
image [add *<WORD>* *<WORD>* | load-from *flash:*] | delete *<WORD>* |
updatefilename *<WORD>* *<WORD>* |
restart *<WORD>* | force-remove *<WORD>* |
stop *<WORD>*}

Syntax Description	container
{connect *<WORD>* |	**Connect**–container instance name. You must have a valid image loaded in your container in order to connect. To escape container instance type <CTRL>-p <CTRL>-q.
exec *<WORD>* CMDLINE	Executes the given command and arguments then redirects the output to your CLI screen. <WORD>–container name <CMDLINE>–command line to execute
export-changes *<WORD>* flash:*<WORD>* |	Export changes made in a container from the base container. Filename will normally end with a “tar.gz” because it will be a compressed tar file, although this is not required. Export-changes must be based on the “same” container image(such as alpine to alpine, not alpine to ubuntu).

image [add *<WORD>* *<WORD>* | load-from flash:] | delete *<WORD>* | update filename *<WORD>* *<WORD>* |	Pull the specified image for a container or load a tar image from our flash: volume. If no tag/digest is specified then the tag of latest will be used. **Add**–container image path and name container image tag or digest load-from–flash: **Delete**–image name (tag can be included) **Update**–container image path and name container image tag or digest
restart *<WORD>* | force-remove *<WORD>* |	**Restart–**restart container instance **Forcefully–**remove the container instance forcibly
stop *<WORD>*}	**Stop–**container instance name
Command Modes	Perle#container

Usage Guidelines

Use this command to manage Open Container Initiative (OCI) containers images.

Your router supports the Open Container Initiative (OCI) software management container feature. Simply put, a software container bundles an application's code together with the related configuration files and libraries, and all dependencies required for a application to run. By using our OCI container management system, you are able to load images, create containers, and manage multiple containers, conveniently, and easily.

Your router allow you to deploy and run Open Containers Initiative (OCI) compatible containers from both public and private container registries, such as Open Containers, GitHub and Docker Hub. Your router supports the following OCI container specifications:

1. the Runtime Specification (runtime-spec),
2. the Image Specification (image-spec)
3. the Distribution Specification (distribution-spec).

Examples

This example shows you how to add an image to your container, then connect to that container.

```
Perle#container image add alpine
Pulling from library/alpine
Digest:sha256:bc41182d7ef5ffc53a40b044e725193bc10142a1243f395ee852a8d9
Status: Image is up to date for alpine:latest
#(config) container network test-network
(config-container-net)#network-interface bvi 1
#(config) container name test-container
#config) container network test-network
(config-container)#image alpine
#container restart test-container
#container connect test-container
/#
```

Related Commands

copy

copy

{**flash:***filename* | **ftp flash:** | **nvram:** | **running-config** | **startup-config :***filename* | **http:** *filename* | **https:***filename* | **nvram:** *filename* | **running-config** *filename* | **scp:** *filename* | **sftp:** *filename* | **startup-config** *filename* | **tftp:***filename*}

Syntax Description	**copy**
{**flash:***filename* | **ftp flash:** | **nvram:** | **running-config** | **startup-config :***filename* | **http:** *filename* | **https:***filename* | **nvram:** *filename* | **running-config** *filename* | **scp:** *filename* | **sftp:** *filename* | **startup-config** *filename* | **tftp:***filename*}	Copies from one file to another.
Command Modes	Perle#copy

Usage Guidelines

Use this command to copy a file from one location to another.

Examples

This example copies a file from the flash: directory to a TFTP server with an IPv4 address of 172.16.4.90.

```
Perle#copy flash:running-config-save tftp:
Address or name of remote host[ ]?172.16.4.90
Destination filename [ ]?backup-running-config<cr>
4922 bytes copied in 0.013 seconds
```

Related Commands

boot
delete
pwd
mkdir
more
cd
rename

debug

debug

{alarmmgr |
all |
bgp events | filters | fsm | keepalives | messages | rib | updates |
bridge spanning-tree packet |
cellular-gnss |
cellular-lte |
container-management |
clpd |
dialer |
dot11-ap |
dot11-station |
dot1x-authenticator |
dot1x-supplicant |
drmgrd |
email |
init |
ip dhcp client | relay-agent | server |
ip ospf events | ism | lsa | nsm | nssa | packets | rib |
ip rip events | packets |rib] |
ip-passthrough |
ipsec |
kernel |
lldp |
logging |
ntp |
rest-api |
snmp |
trapmgr |
tty |
vrrp |
vty |

wan-highavail |
wanifmgr}
Use the no form of this command to negate this command.

Syntax Description	debug
{**alarmmgr** |	Starts alarm manager debug logging
all |	Starts all debugging logging. Setting all debug On can seriously effect the speed of your router.
bgp events | **filters** | **fsm** | **keepalives** | **messages** | **rib** | **updates** |	Starts debug BGP messages.
bridge spanning-tree packet |	Starts debug spanning-tree packets.
cellular-gnss |	Starts debug cellular GNSS messages.
cellular-lte |	Starts debug LTE messages.
container-management |	Starts debug for container management.
clpd |	Starts debug clpd messages.
dialer |	Starts debug Dial on Demand messages.
dot11-station |	Starts debug dot11 station mode.
dot11-ap |	Starts debug for wireless access point.
dot1x-authenticator |	Starts debug dot1x authenticator mode messages.
dot1x-supplicant |	Starts debug for dot1x supplicant mode messages.
drmgrd |	Starts debug device remote manager daemon messages.
email |	Starts debug email messages.
init |	Starts debug init messages.
ip dhcp client | **relay-agent** | **server]** |	Starts debug dhcp client, relay agent and server messages.
ip ospf events | **ism** | **lsa** | **nsm** | **nssa** | **packets** | **rib** | **rip events** | **packets** | **rib** |	Starts debug OSPF messages.
ip rip events | **packets** | **rib** |	Starts debug RIP messages.

ip-passthrough |	Starts debug ip-passthrough messages.
ipsec |	Starts debug IPsec messages.
kernel |	Starts debug kernel messages.
lldp |	Starts debug for LLDP messages
logging |	Starts debug logging messages.
ntp |	Starts debug NTP messages.
rest-api |	Starts debug RESTful-api logging.
snmp |	Starts debug SNMP messages.
trapmgr |	Starts debug trapmgr messages.
tty |	Starts debug tty messages.
vrrp |	Starts debug for VRRP messages.
vty |	Starts debug for vty device messages.
wan-highavail |	Starts debug for WAN high available connections messages.
wanifmgr}	Starts debug for our internal WAN manager messages
Command Default	All debug off
Command Modes	Perle#debug

Usage Guidelines

Use this command to set debug On for features or functions. Setting debug On for all features seriously impacts system performance.

Examples

This example sets debug on for NTP.

```
Perle#debug ntp
```

This example sets debug on for dhcp server.

```
Perle##debug ip dhcp server
```

Related Commands

ping
undebug

delete

delete

{**flash:** ***<filename>*** |

nvram: <*filename*}

Syntax Description	delete
{**flash: <*filename*>** |	Type the filename to delete on the flash: file system.
nvram: <*filename*>}	Type the filename to delete on the nvram file system.
Command Modes	Perle#delete

Usage Guidelines

Use this command to delete a file on flash or the nvram file system.

Examples

This example deletes backup.config on flash.

Perle#delete flash:backup.config

Related Commands

boot
delete
pwd
mkdir
more
cd
rename
copy

dir

dir
{**flash:** |
nvram:}

Syntax Description	dir
flash: |	Displays the contents of flash.
nvram:}	Displays the contents of nvram.
Command Modes	Perle#dir

Usage Guidelines

Use this command to display the contents of a file system on flash or nvram.

Examples

```
Perle#dir
 34      -rw-      1992 Mar 25 2019 17:39 -04:00 running-config
39      -rw-      2016 Mar 27 2019 12:35 -04:00 -Mar-27-12-35-22-0
 24      -rw-      896 Jan  4 2001 16:46 -04:00 backup.config

 42      -rw-      2068 Mar 28 2019 15:33 -04:00 -Mar-28-15-33-44-3
 41      -rw-      2047 Mar 27 2019 16:24 -04:00 -Mar-27-16-24-31-2
 40      -rw-      2047 Mar 27 2019 16:24 -04:00 -Mar-27-16-24-26-1
```

Related Commands

boot

delete

pwd

mkdir

cd

copy

disable

disable

Syntax Description	**disable**
Command Modes	Perle#disable

Usage Guidelines

Use this command to leave privileged mode.

Examples

This example sets privileged level to user level.

```
Perle#disable<cr>
Perle>
```

Related Commands

enable

disconnect

disconnect

{**ssh vty** ***<0-15>***}

Syntax Description	**disconnect**
Command Modes	Perle#disconnect

Usage Guidelines

Use this command to disconnect an active ssh session.

Examples

This example disconnects active ssh session vty 1.

```
Perle#disconnect ssh vty 1
[confirm]
[OK]
```

Related Commands

line

dot1x

dot1x

{**initialize interface ethernet** *<1-5> . <1-4000>* |
re-authenticate interface ethernet*<1-5> . <1-4000>* |
test interface ethernet *<1-5> . <1-4000>* }

Syntax Description	dot1x
initialize interface ethernet *<1-5> . <1-4000>* |	Devices connected on this Ethernet interface are forced to authenticate. The connection is secured.
re-authenticate interface ethernet *<1-5> . <1-4000>* |	Devices connected on this Ethernet interface are forced to re-authenticate.
test interface ethernet *<1-5> . <1-4000>* }	Run a 802.1x readiness test to detect any 802.1x clients that are EAPoL capable.
Command Modes	Perle#dot1x

Usage Guidelines

Use this command to initialize, re-authenticate, and test connected dot1x devices.

Examples

This example forces devices on Ethernet interface 1to re-authenticate.

```
Perle>#enable
Perle#dot1x re-authenticate interface eth 1
```

This example tests for EAPol capable devices.

```
Perle>#enable
Perle#dot1x test eapol-capable interface eth 1
Perle#show logging
*Oct 18 02:41:15 %PORT-AUTH-6: eth2: STA 00:13:20:92:29:82 IEEE 802.1X:
INFO_EAPOL_PING_RESPONSE: The interface Ethernet1 has an 802.1x capable
client with MAC (00.13.20.92.29.82)
 *Oct 18 01 02:41:15 %PORT-AUTH-6: eth2: STA 00:16:d3:2f:62:bb IEEE 802.1X:
INFO_EAPOL_PING_RESPONSE: The interface Ethernet1 has an 802.1x capable
client with MAC (00.16.d3.2f.62.bb)
```

Related Commands

dot1x

show eap

exit

exit

Syntax Description	exit
Command Modes	Perle#exit

Usage Guidelines

Use this command to exit from EXEC mode.

Related Commands

disable

kill

kill

{**line tty** *<1-2>*|
usb *<1-8>*}

Syntax Description	kill
{**line tty** *<1-2>*}	Only available on models with serial ports. Resets the tty device.
usb *<1-8>*}	Resets the USB port.
Command Modes	Perle#kill

Usage Guidelines

Only available on models with serial ports.

Use this command to kill a serial line session.

Killing a line resets that serial line and loads any newly configured parameters.

Examples

This example resets (kills) the line for tty 1. Any users connected are disconnected.

```
Perle#kill line tty 1
```

Related Commands

line

line-attach

line-attach

{**tty***<1-2><WORD>* |
}

Syntax Description	line-attach
{**tty** *<1-2><WORD>* |	Only available on models with serial ports. Displays available serial ports configured for ssh or telnet protocol. If the user logs in, line access privileges are based on this authentication not the original authentication request. *<WORD>*SSH user name is optional. If it is not entered, the username which logged into the router's main session are used.
Command Modes	Perle#line-attach

Usage Guidelines

Use this command to connect to serial ports configured as Console Management ports. The available ports for both Telnet and SSH are displayed.

Examples

This example allows a user to connect to serial port 1using the SSH protocol and ssh user sshlyn.

Perle#line-attach tty 1 sshlyn

Related Command

(config-line)#tty

logout

logout

{**logout**}

Syntax Description	logout
{**logout**}	Logs you out of your router.
Command Modes	Perle#logout

Usage Guidelines

Use this command to log out of your router.

mkdir

mkdir

{**flash:**}

Syntax Description	mkdir
{**flash:**}	Makes a directory on the flash file system.
Command Modes	Perle#mkdir

Usage Guidelines

Use this command to make a new directory on the flash file system.

Examples

This example makes a directory under the flash file system.

```
Perle>#enable<cr>
Perle#mkdir flash:testing<cr>
Perle#dir
Directory of flash:
130307    drwx     4096 Jan 2 2019 19:58 -05:00 testdir
130306    -rw-     1508 Jan 2 2019 17:46 -05:00 test-config
130308    drwx     4096 Jan 3 2019 18:49 -05:00 testing
```

Related Commands

delete

pwd

mkdir

more

cd

boot

more

more

{**/ascii | /binary | flash: | nvram: | running-config | startup-config |**

Syntax Description	more
{**/ascii | /binary | flash: | nvram: | running-config | startup-config |**	Forces the file type to display in ASCII format. Forces the file type to display binary format. Displays the content of a file.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#more

Usage Guidelines

Use the more command to display a file contents. Specify whether to show the contents in ASCII or binary format.

Output modifiers (Pipe redirect)—allows you to pipe the output to the redirect options as specified.

Examples

This example views the file contents of nvram.

```
Perle#more nvram:no-default-config
no dot11 ssid Test123-0002f0
default interface Dot11Radio0
```

```
default interface ethernet 1
default interface ethernet 2
no ip nat inside source any interface cellualr 0 overload
no ip dns listen-address 192.168.0.1
no ip dhcp pool default pool
no interface BVI1
no bridge protocol ieee
```

password

password

Syntax Description	password
password	Changes password for current logged in user
Command Modes	Perle#password

Usage Guidelines

Use this command to change the password for the current user.

Examples

This example changes the password for the current logged in user.

```
Perle#password

Password must be less than 128 characters long
May not use 5 previous passwords
Enter Old Password:

Enter New Password:

Re-Enter Password:
Password Changed Successfully
```

ping

ping

{*<WORD>* **[data** *<HEX DIGITS>***]** | **[repeat** *<1-2147483647>***]** | **[size** *<36-18024>***]**}

Syntax Description	ping
{*<WORD>* **[data** *<HEX DIGITS>***]** | **[repeat** *<1-2147483647>***]** | **[size** *<36-18024>***]**}	Host name must be predefined in the host table. Data hex pattern is from 1 to 32 hex characters. Repeat count is from 1–2147483647. Datagram size is from 36–18024.
Command Modes	Perle#ping

Usage Guidelines

Use this command to ping a remote host.

Examples

This example pings a host with an ip address of 172.16.113.44 repeating the ping request 10 times.

```
Perle#ping 172.16.113.44 repeat 10
```

This example pings a host with an ip address of 172.16.113.44 with hex data pattern of f1f1f1f1f1.

```
Perle#ping perlehost data f1f1f1f1f1
```

This example pings a host with an ip address of 172.16.113.44 with a data packet size of 4o bytes.

```
Perle#ping perlehost size 40
```

Related Commands

undebug

pwd

pwd

Syntax Description	pwd
Command Modes	Perle#pwd

Usage Guidelines

Use this command to display your current file system.

Examples

This command displays the file system you are in.

```
Perle#cd nvram:
Perle#pwd<cr>
#nvram:
```

Related Commands

copy
boot
delete
pwd
mkdir
more
cd
rename

release

See *release*

reload

reload

{**at** ***hh:mm*** |
cancel | **in** ***mmm*** | [***hh:mm***]}

Syntax Description	reload
{**at** ***hh:mm*** |	Configure **at**—the time in hours and minutes when to reload the firmware on the router.
cancel |	Configure **cancel**—any pending reload commands.
in ***mmm*** | [***hh:mm***]}	Configure **in**—minutes 1-999 or hours minutes when to reload the firmware on the router.
Command Modes	Perle#reload

Usage Guidelines

Use this command to reload the router‘s firmware. The routerpowers off and then reboots. Any configuration not copied from running-config to startup-config is lost.

Examples

Reloads the firmware on the router in 10 hours and 20 mins.

```
Perle#reload 10:20
```

Cancels the previous reload command.

```
Perle#reload cancel
*****
***** ----SHUTDOWN ABORTED ---
******
```

Related Commands

show reload

Note: Before reloading the router, copy running config to startup config to save any changes that you want permanently saved.

rename

rename

{**flash: <*WORD*> | nvram: <*WORD*>**}

Syntax Description	rename
{**flash: <*WORD*> | nvram: <*WORD*>**}	Renames the file.
Command Modes	Perle#rename

Usage Guidelines

Use this command to rename a file on flash or nvram.

Examples

This example rename a file on flash from testdir to newdir.

```
Perle#rename flash:testdir flash:backup
Destination file name[backup]?
```

Related Commands

delete
pwd
mkdir
more
cd
rename
boot

renew

See ***renew***

reset

reset

{**factory [remove-container-management-images |clear-all | erase- vm-parition]**}

Syntax Description	reset
{**factory**	Resets the router to factory default—removing all configuration files, certificates and keys.

[remove-container-management-images clear-all | erase-vm-parition|]}	Remove container management images. Clear all container and Virtual Machine partitions. Erase Virtual Machine partition.
Command Modes	Perle#reset

Usage Guidelines

Use this command to set the router to factory defaults, as well as, remove container images, all container and virtual Machine partitions or erase Virtual Machine partitions.

Related Commands

boot

show container-management (OCI)

container (OCI)

(config-container)#

(config-container-net)#

rmdir

rmdir

{**flash:** ***<WORD> <WORD>***}

Syntax Description	**rename**
{**flash:** ***<WORD> <WORD>***}	Removes the directory on flash.
Command Modes	Perle#rmdir

Usage Guidelines

Use this command to remove a file on flash.

Examples

This example removes a directoy on flash.

```
#rmdir flash:testit
Remove Directory name [testit]?
```

Related Commands

boot

delete

pwd

renew

mkdir

serialt

serialt

{*<WORD>* #[mask] [...] [-full] [-size=# [-show]}

Syntax Description	serialt
{*<WORD>* #[mask] [...] [-full] [-size=# [-show]}	Only available on models with serial ports. Takes a serial line trace.
Command Modes	Perle#serialt

Usage Guidelines

Use this command to capture data on the serial line.

Examples

This example captures all data on serial port 1 and displays it to the screen.

```
Perle#serialt 1 -show
Tracing port 1=rx+tx+signals+special

To stop the trace press Ctrl-C
9
```

```
Use the "Space Bar" and the keys 1,2,3,4 to control the scrolling speed.
Please press the "Space Bar" to continue...............

Use the "Space Bar" and the keys 1,2,3,4 to control the scrolling speed.
Please press the "Space Bar" to continue...............

Decode Complete... 0 entries processed
```

```
SERIAL TRACE V1.00

To start a serial trace:
========================
serialt #[=mask] [...] [-full] [-size=#] [-show]
        |  |      |     |       |         |
        |  |      |     |       |         then show the trace file
        |  |      |     |       size in kilobytes (2-1024)
        |  |      |     stop when trace file full else wrap
        |  |      another port/mask to simultaneously trace
        |  optional trace mask any combination of:
        |  rx+tx+signals+special+ioctl or use: normal,all,same
        port number 1->max

Serial trace file utilities:
============================
serialt [-show] [-remove]
         |       |
         |       remove the trace file
         show the trace file
```

Related Commands

undebug

show aaa

show aaa

{**local user lockout** |
[*<filter/redirection options>*]}

Syntax Description	show aaa
{**aaa local user lockout** |	Displays users locked-out of the router.
[*filter/redirection options>*]	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show aaa

Usage Guidelines

Use this command to display the current locked-out users on the router.

Output modifiers (Pipe redirect)—allows you to pipe the output to the redirect options as specified.

Examples

This example shows you the current locked out users on the router.

```
Perle#show aaa local user lockout
Locked-out users: Lyn
```

Related Commands

aaa

show alarm

See ***show alarm***

show archive

show archive

{**config rollback timer** |
update-sw |
[*<filter/redirection options>*]}

Syntax Description	show archive
{**config rollback timer** |	Displays configuration rollback and timer information.
update-sw |	Displays the Check Software update option.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show archive

Usage Guidelines

Use this command to display config rollback and the update feature.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the config for the rollback feature.

```
Perle#show archive
The maximum archive configurations allowed is 14.
There are currently 9 archive configurations saved.
The next archive file is named flash:-<timestamp>-9
Archive #  Name
Archive #  Name
  1      flash:-May-19-14-14-16-0
  2      flash:-May-19-14-17-50-1
  3      flash:-May-1914-19-00-2 4      flash:-May-19-14-19-14-3
```

```
  4      flash:-May-19-14-19-14-3
  5      flash:-May-19-14-20-55-4
  6      flash:-May-19-14-24-31-5
  7      flash:-May-19-15-05-37-6
  8      flash:-May-19-03-37-55-7
  9      flash:-May-19-03-38-10-8 <- Most Recent
  10
  11
  12
  13
  14
```

Related Commands

archive

show arp

See *show arp*

show bgp

show bgp

{**community** |
community-list *<1-500 >* | *<WORD>* **exact-match** |
filter-list *<WORD>* |
memory |
neighbors *<A.B.C.D>* | *<X:X::X:X>* |
prefix-list *<WORD>* |
regexp *<LINE>* |
route-map *<LINE>*|
[*<filter/redirection options>*]}

Syntax Description **show bgp**

{**bgp community** |	Displays the routes matching the communities.
community-list *<1-500 >* | *<WORD>* **exact-match** |	Displays the routes matching the community list.
filter-list *<WORD>* |	Displays the routes conforming to the filter list.
memory |	Displays Global BGP memory statistics.
neighbors *<A.B.C.D>* | *<X:X::X:X>* |	Detailed list for TCP and BGP neighbor connections.
prefix-list *<WORD>*|	Displays the routes matching the prefix-list.
regexp *<LINE>* |	Displays the routes matching the AS path regular expression.
route-map *<LINE>* |	Displays the routes matching the route-map.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show bgp

Usage Guidelines

Use this command to show BGP information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays BGP neighbors.

```
Perle#show bgp neighbors
BGP neighbor is 172.16.39.2, remote AS 65537, local AS 65536, external link
  BGP version 4, remote router ID 172.16.39.2
  BGP state = Established, up for 00:14:28
  Last read 05:39:27, hold time is 180, keepalive interval is 60 seconds
  Neighbor capabilities:
    4 Byte AS: advertised and received
    Route refresh: advertised and received(old & new)
    Address family IPv4 Unicast: advertised and received
Message statistics:
    Inq depth is 0
    Outq depth is 0
          Sent       Rcvd
Opens:                1          0
    Notifications:        0          0
    Updates:              1          1
    Keepalives:          16         15
    Route Refresh:        0          0
Route Refresh:       0          0
    Capability:           0          0
    Total:               18         16
Minimum time between advertisement runs is 30 seconds

For address family: IPv4 Unicast
  Community attribute sent to this neighbor(both)
  1 accepted prefixes

Connections established 1; dropped 0
  Last reset never
Local host: 172.16.39.1, Local port: 179
Foreign host: 172.16.39.2, Foreign port: 38216
```

```
  Nexthop: 172.16.39.1
Nexthop global: 2011::2
Nexthop local: fe80::251:82ff:fe11:2201
BGP connection: non shared network
Read thread: on  Write thread: off
```

Related Commands

router

show bridge

show bridge

spanning-tree active | bridge | detail | interface ethernet *<1-5>. <1-4000>* | [mst *<WORD>* configuration | detail | interface *<1-5>. <1-4000>*] | root |

[*<filter/redirection options>*]}

Syntax Description	show bridge
spanning-tree active | bridge | detail | interface ethernet *<1-5>. <1-4000>* **| [mst** *<WORD>* **configuration | detail | interface** *<1-5>. <1-4000>* **] | root |**	Shows list of bridges and spanning-tree information.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show bridge

Usage Guidelines

Use this command to list bridge and spanning tree information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays bridge information.

```
Perle##show bridge
Bridge Name     Bridge ID              STP Enabled Interfaces
br10            8000.0040020002f9 no        wlan1
```

Related Commands

bridge

show cellular

show cellular

{**cellular** *<0-0>* **all** |
connection |
hardware |
network] **profile** *<NAME>* |**radio** |**security** |**sms-log** |

Syntax Description	show cellular
{**cellular interface** *<0-0>* **all** |	Displays all information.
connection |	Displays current active connections.
hardware |	Displays cellular modem information.
network |	Displays cellular network information.
profile *<NAME>* |	Displays profile information about the modem.

radio |	Displays cellular modem radio information.
security |	Displays modem security status.
sms-log |	Displays SMS log.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show cellular

Usage Guidelines

Displays information about your cellular connection.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

```
Perle#show cellular 0 profile
------------------------
Connection Information
=======================
Cellular Status:     Data connected
IP Address:          25.110.104.191
IPv6 Address:        ::
Connection Duration: 21 mins 7 secs
```

```
Data Usage:          5.14 GB
Hardware Information
=====================
Firmware Version:    SWI9X30C_02.32.11.00(9907721 001.000 Generic-M2M)
Active Firmware:     "Generic"
Hardware Version:    1.0
Device Model ID:     EM7455
IMEI:                359073061841023
Modem Temperature:   37 deg C
```

```
SIM 1
   Card Detected:   Yes
   ICCID:          89312720523049569464
   IMSI:           302720709109402
   Phone #:        Not available
SIM 2
Card Detected:   No
ICCID:          Not available
IMSI:           Not available
Phone #:        Not available
Network Information
===================
Network Status:      Registered. Home network.
Connected Network:   "ROGERS" (MCC:MNC=302:720)

Profile Information
===================
Active Profile:      Primary (test1)
Connected APN:       "lteinternet.apn"
Radio Information
===================
Radio Technology: LTE
Signal Strength: -62 dBm

Modem Security Information
===================
Active SIM     1
SIM Locked: No
PIN retry: 5
PUK Retry: 10
```

Related Commands

cellular

show clock

See ***show clock***

show container (OCI)

show container

{***<WORD>*** |

images |

log ***<WORD>*** |

name ***<WORD>*** |

network ***<WORD>*** |

stats |

storage-info |

[*<filter/redirection options>*]}

Syntax Description	show container
{*<WORD>* |	Show container instance name.
images |	Show container image information.
log *<WORD>* |	Show container log.
network *<WORD>* |	Show network container information.
name *<WORD>* |	Show name of container.
stats |	Show running container status.
storage-info |	Displays container storage information.
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show container

Usage Guidelines

Use this command to display OCI container information.

Examples

This example displays container information.

Perle#show container <cr>

```
Name            Image           Command      Created        Status       Description
--------------- --------------- ------------ -------------- ------------ ----------------
new             alpine          ps -aef /bin 4 days ago     exited
new1            alpine          /bin/sh -c d 5 days ago     exited
foo1            alpine          ps -aef      6 days ago     created
lyncontainer    alpine          /bin/sh      6 days ago     exited
lyneth#
```

#show container name new <cr>

```
lyneth#show container name new
Container name: new
  Image: alpine
  Container description:
  Command: ps -aef /bin/sh
  Created time: 4 days ago
  Status: exited     When: 6 minutes ago
  ExitCode: 0
  Memory Limit: 256.0MiB
  Restart: no
  Restarts: 0
  Network name: bridge
    MAC address:
    IPv4 address:
    IPv4 gateway:
    IPv6 address:
    IPv6 gateway:
```

container (OCI)

show container-management (OCI)

show container-management

[*<filter/redirection options>*]}

Syntax Description	show container
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show container-management

Usage Guidelines

Use this command to display the status of container management.

Examples

This example displays the status of container management.

Perle#show container-management <cr>

Container Management is currently active

container (OCI)

show debugging

show debugging

{**debugging** |

[*<filter/redirection options>*]}

Syntax Description	show debugging
{**debugging** |	Displays processes that are in debugging mode.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show debugging

Usage Guidelines

Use this command to show which functions or commands have debug enabled.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays which processes are set to debug.

```
Perle#show debugging
BGP events debugging is on
NTP debugging is on
```

show crypto

See ***show crypto***

show dhcp

show dhcp

{**lease** |

[*<filter/redirection options>*]}

Syntax Description	show dhcp
{**lease** |	Displays current devices with leases.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show dhcp lease

Usage Guidelines

Use this command to display all client dhcp leases with configured options.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays all dhcp leases.

```
Perle#show dhcp lease
dhcp-assigned-address 172.17.121.182
option subnet mask 255.255.0.0
option dhcp-lease time 86400 seconds
option dhcp-server-identifier 172.17.3.13
renew Mon Jan 01 08:44:00 EST 2021
rebind Mon Jan 01 19:02:16 EST 2021
expire Mon Jan 01 22:02:16 EST 2021
```

Related Commands

show ip dhcp

show dot11

show dot11
{**adjacent-ap** |
associations |
bssid |
operation-stats |
resource-infor |
station-info |
[*<filter/redirection options>*]}

Syntax Description	**show dot11**
{**adjacent-ap** |	Displays adjacent AP list.
associations |	Displays association information.
bssid |	Displays SSID mapping.
operation-stats |	Displays MAC operation attributes.
resource-infor |	Displays interface resource information.
station-info |	Displays Wireless-client mode information.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	#show dot11

Usage Guidelines

Use this command to show dot11 information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays interface resource information.

```
Perle#show dot11 resource-info
Product Version ManufacturerOUI   Manufacturer Name     Product Name
wlan0           00:40:02          Qualcomm Atheros       QCA988x 802.11g
```

Related Commands

dot1x

show dot1x

See ***show eap***

show eap

See ***show eap***

show eee

show eee

{**capabilities interface ethernet** ***<1-5>*** **.** ***<1-4000>*** |
status interface ethernet ***<1-5>*** **.** ***<1-4000>*** |
[***<filter/redirection options>***]}

Syntax Description	**show eee**
{**eee capabilities interface ethernet** ***<1-5>*** **.** ***<1-4000>*** |	Displays whether the remote Ethernet interface is capable of Energy Efficient Ethernet (EEE).
status ethernet ***<1-5>*** **.** ***<1-4000>*** |	Displays the current status. • Disagree—the remote interface cannot negotiate EEE • Link down—the remote interface is not connected • Operational—both sides have agreed on EEE capabilities • Disabled—EEE is disabled on this Ethernet interface
[***<filter/redirection options>***]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show eee

Usage Guidelines

Use this command to display Ethernet EEE port capabilities.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays EEE capabilities on the Ethernet ports.

```
Perle#show eee capabilities
Ethernet1
   EEE: no
Ethernet2
    EEE: yes
Ethernet3
    EEE: no
Ethernet4
    EEE: no
```

show email

show email

[*<filter/redirection options>*]}

Syntax Description	show email
{**email** |	Displays email configuration.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show email

Usage Guidelines

Use this command to display configured email parameters.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays email configuration.

```
Perle#show email
Email: Enabled
SMTP Server: 172.217.214.109:587
From: tfelton@gmail.com
Encryption: tls
Username: tfelton@gmail.com
Password: OHJJdoll564ggbTzMI
```

```
Validate Certificate: Disabled
Email Notifications:
Recipient                Notifications
Subject
tfelton@perle.com        alarms authentication entity envmon snmp ipsec
Tom's events from router
```

Related Commands

email

show environment

See *show environment*

show facility-alarm

See *show facility-alarm*

show flash:

See *show flash:*

show format

show format

[*<filter/redirection options>*]}

Syntax Description	show format
[*<filter/redirection options>*]}	Output modifiers see *Show Command Filtering and Redirection*
Command Modes	Perle#show format

Usage Guidelines

Use this command to list supported CLI show format commands.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the supported CLI show format commands.

```
Perle#show format
show aaa local user lockout
show alarm profile
show alarm profile %s
show alarm settings
show alarm settings enabled
show archive
show archive config rollback timer
show archive update-sw
show arp
```

```
show arp
show bgp memory
..........
```

show gnss

show {[**all** |

location |

profile
| **streams**]}

Syntax Description	show gnss
{[**all** |	Show all GNSS information.
location |	Show only GNSS location information.
profile |	Show GNSS profile information.
streams]}	Show GNSS streams information.
Command Modes	Perle#show gnss

Usage Guidelines

Shows information for GNSS.

Examples

This example shows gnss location.

```
Perle#show gnss location<cr>
GNSS Location Information:
   Fix        : Yes
   Longitude  : -79.363062
   Latitude   : 43.858360
   Altitude   : 192.300000
   Speed      : 0.000000 kph
   Heading    : 0.000000

GNSS Satellite Information:

   Number of satellites in fix    : 26
   In fix GPS Satellites          :  1  10  11  14  15  24  31  32
   In fix GLONASS Satellites      :  70  86  73  80  79  69  87  71
   In fix GALILEO Satellites      : 304 309 311 319 327 336
   In fix Beidou Satellites       : 214 226 227 230
   In fix QZSS Satellites         :
```

Related Commands

cellular

show hosts

See ***show hosts***

show hotspot

show hotspot
{**clients ssid** |
[*<filter/redirection options>*]}

Syntax Description	show hotspot

{**clients ssid** |	Displays configured clients SSIDs.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show hostspot

Usage Guidelines

Use this command to display client SSID information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows clients connected to the hotspot.

Perle#show hotspot client

show interfaces

show interfaces

{**bvi** *<1-9999>* |
cellular *<0-0>* |
dialer *<0-15>* |
dot11radio *<0-4>* |
ethernet *<1-5>* **.** *<1-4000>* **counters switch | description | stats | summary | vrrp** *<1-255>* |
loopback counters | description | stats | summary |
openvpn-tunnel *<0-999* |

tunnel *<0-999* |
counters |
description |
stats |
summary |
[*<filter/redirection options>*]}

Syntax Description	**show interfaces**
{**interfaces bvi** *<1-9999>* |	Displays Bridge-Group Virtual interfaces.
cellular *<0-0>* |	Displays Cellular WAN interfaces.
dialer *<0-15>* |	Displays Dialer interfaces.
dot11radio *<0-4>* |	Displays IEEE 802.3z interfaces.
ethernet *<1-5>*| [**vrrp** *<1-255>*] [**description** *<WORD>*] |	Displays Ethernet interfaces.

loopback counters | description | stats | summary |	Displays loopback interface.
openvpn-tunnel ***<0-999>*** **|**	Displays OpenVPN interfaces.
tunnel ***<0-999*** **|**	Displays tunnels.
counters |	Displays counters for all interfaces.
description |	Displays descriptions for all interfaces.
stats |	Displays stats for all interfaces.
summary |	Displays summary for all interfaces.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show interfaces

Usage Guidelines

Use this command to display interface details, including admin statuses, and link statuses.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows interface descriptions.

Perle#show interfaces description

```
Interface   Admin Status   Link Status  Description
---------   ------------   -----------  -----------
lo          up             up
eth1        up             up
eth1.2      up             up
eth1.10     up             up
eth1.100    up             up
eth1.200    up             up
eth2        up             down
eth2.100    up             down
eth2.200    up             down
eth2.400    up             down
wlan0       up             down         lynsradio
wlan1       up             up
wlan3       up             up
wlan4       up             up
wlm0        up             up
br10        up             down
tun1        up             up
tun2        up             up
tun10       up             up
vtun1       admin down     down
```

Related Commands

(config-if)#bvi

(config-if)#dialer

(config-if-ethernet)#

(config-if)#tunnel

(config-if)#openvpn-tunnel

show ip access-lists

show ip access-lists

{**extended** *<100-199> <2000-2699>* | **standard** *<1-99> <2000-2699>* | [*<filter/redirection options>*]}

Syntax Description	show ip access-lists
{**extended** *<100-199> <2000-2699>* | **standard** *<1-99> <2000-2699>* |	Displays Extended and standard IP access lists.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip access-lists

Usage Guidelines

Use this command to display configured access lists.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

```
Perle#show ip access-lists
Extended IP access list 100
10 permit any any
```

Related Commands

ip **access-list**

show ip alg

show ip alg {table | [*<filter/redirection options>*]}

Syntax Description	show ip alg
{**table** |	Displays ALG entries.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip alg table

Usage Guidelines

Use this command to display Application Level Gateway (ALG) entries.

Output modifiers (Pipe redirect)—allows you to pipe the output to the redirect options as specified.

Examples

This example displays ip alg table information.

Perle#show ip alg table

CONN-ID	Source	Destination	Protocol	Timeout	State
843977664	192.168.4.1	224.0.0.18	unknown [112]	599	
843977984	172.16.4.181:138	172.16.255.255:138	udp [17]	29	
843978304	172.16.22.3:138	172.16.255.255:138	udp [17]	29	
843978624	172.16.4.177:62992	255.255.255.255:62976	udp [17]	26	
843608192	172.16.60.2:137	172.16.255.255:137	udp [17]	11	
843807552	10.10.200.83:53864	172.16.78.229:23	tcp [6]	431999	ESTABLISHED
843977344	127.0.0.1:47292	127.0.0.1:13514	tcp [6]	431999	ESTABLISHED
843978944	127.0.0.1:57516	127.0.0.1:199	tcp [6]	431997	ESTABLISHED
843979264	127.0.0.1:57508	127.0.0.1:199	tcp [6]	431997	ESTABLISHED
843804992	172.16.23.124:17500	255.255.255.255:17500	udp [17]	2	
843979584	172.16.27.68:17500	172.16.255.255:17500	udp [17]	29	
843806912	172.16.78.229:123	68.69.221.61:123	udp [17]	10	
843979904	172.16.27.68:17500	255.255.255.255:17500	udp [17]	29	
683519104	10.10.200.11:50558	172.16.78.229:22	tcp [6]	431947	ESTABLISHED
843805632	172.16.21.1:137	172.16.255.255:137	udp [17]	1	
843977024	172.16.4.182:2049	172.16.78.229:807	udp [17]	179	
843807872	172.16.23.124:137	172.16.255.255:137	udp [17]	12	
946298880	127.0.0.1:57510	127.0.0.1:199	tcp [6]	431997	ESTABLISHED
843805312	172.16.23.124:17500	172.16.255.255:17500	udp [17]	2	
843960224	172.16.78.229:22	10.10.200.11:50512	tcp [6]	276	ESTABLISHED
843806592	172.16.28.22:137	172.16.255.255:137	udp [17]	6	

show ip arp

show ip arp {*<A.B.C.D>* | [*<filter/redirection options>*]}

Syntax Description	show ip arp
{*<A.B.C.D>* |	Displays the ARP entry for the specified IPv4 address.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip arp

Usage Guidelines

Use this command to display ARP table details.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Perle#show ip arp

Address	HWtype	HWaddress	Flags Mask	Iface
172.16.113.20	ether	78:2B:cb:a5:b4:0c	CM	eth1

show ip as-path-access-list

show ip as-path-access-list [*<filter/redirection options>*]}

Syntax Description	show ip as-path-access-list
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip as-path-access-list

Usage Guidelines

Use this command to show as-path access list.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays as-path access list.BGP neighbors.

```
Perle#show as-path-access-list
AS path access JoeAS-Path
permit def
deny abc
```

Related Commands

ip as-path

show ip bgp

{*<A.B.C.D>/nn <A.B.C.D>* |
cidr-only |
community |
community-info|
community-list *<1-500>* | *<WORD>* **exact-match** |
dampened-paths |
filter-list *<WORD>* |
flap-statistics |
ipv4 unicast |
neighbours *<A.B.C.D> <X:X:X:X::X>* | **advertised-routes** | **dampened-routes** |
flap-statistics | **prefix-count** | **[received prefix-filter]** | **received-routers** | **routes** |
paths |
prefix-list *<WORD>* |
regexp *<LINE>* |
route-map *<WORD>* |
summary |
[*<filter/redirection options>***]**}

Syntax Description	show ip bgp
{*<A.B.C.D>/nn <A.B.C.D>* |	Displays BGP network routing table.
cidr-only |	Displays only routes with non-natural netmasks.
community |	Displays routes matching the communities.
community-info |	Displays all BGP community information.

community-list ***<1-500>*** **|** ***<WORD>*** **exact-match |**	Displays routes matching the community list.
dampened-paths |	Displays paths suppressed due to dampening.
filter-list ***<WORD>*** **|**	Displays routes conforming to the filter list.
flap-statistics |	Displays flap statistics of routes.
ipv4 unicast |	Displays address family.
neighbours ***<A.B.C.D>*** ***<X:X:X:X::X>*** **| advertised-routes | dampened-routes | flap-statistics | prefix-count | [received prefix-filter] | received-routers | routes**	Displays detailed information on TCP and BGP neighbor connections.
paths |	Displays path information.
prefix-list ***<WORD>*** **|**	Displays routes matching the prefix list.
regexp ***<LINE>*** **|**	Displays routes matching the AS path regular expression.
route-map ***<WORD>*** **|**	Displays routes matching the route map.
summary |	Displays the summary of BGP neighbor statuses.
[*<filter/redirection options>***]**}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip bgp

Usage Guidelines

Use this command to display BGP information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays BGP information.

```
Perle#show ip bgp

BGP table version is 0, local router ID is 172.16.113.215
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, R Removed
Origin codes: i - IGP, e - EGP, ? - incomplete

   Network          Next Hop            Metric     LocPrf     Weight Path
*> 172.16.0.0       0.0.0.0                  1                 32768      i

Total number of prefixes 1
```

Related Commands

clear ip

show ip community-list

show ip community-list |
{[*<filter/redirection options>*]}

Syntax Description	**show ip community-list**
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip community-list

Usage Guidelines

Use this command to display IP community list information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the community lists.

```
Perle#show ip community-list
Community (expanded) access list 100
permit 50
```

Related Commands

ip community-list

show ip ddns

See ***show ip ddns***

show ip dhcp

See ***show ip dhcp***

show ip dns

show ip dns

[*<filter/redirection options>*]}

Syntax Description	show ip dns
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip dns

Usage Guidelines

Use this command to display IP DNS configuration and information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays all DNS settings.

```
Perle# show ip dns
```

```
IP DNS
======
DNS Lookup Enabled
Listen Addresses:
192.168.0.1
Cache Size          10000
Ignore Host File     Off
Negative TTL         3600
No Name Servers Configured
Name Servers obtained from DHCP on the following interfaces:
wlm0
 64.71.255.254
 64.71.255.253
```

Related Commands

ip dns

show ip extcommunity-list

show ip extcommunity-list

[*<filter/redirection options>*]}

Syntax Description	show ip extcommunity-list
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip extcommunity-list

Usage Guidelines

Use this command to display configured ip extcommunity lists.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays extcommunity lists.

```
Perle#show ip extcommunity-list
Extended community standard list 99
denyso0:0:1:30
```

Related Commands

ip community-list

show ip firewall

show ip firewall {[*<NAME>*] | [*<filter/redirection options>*]}

Syntax Description	show ip firewall
{[*<NAME>*]}	Displays firewall name.
[*<filter/redirection options>*]}	Output modifiers see *Show Command Filtering and Redirection*
Command Modes	Perle#show ip firewall

Usage Guidelines

Use this command to display IP firewall configuration.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays active firewalls.

```
Perle#show ip firewall
Active on
Rule   Packets Bytes  Action    Proto    Source       Destination   Rule Specs
-----    -------    -------     -------     -------     -----------        ------------------    ----------------
10      0       0       accept      ip          0.0.0.0/0         0.0.0.0/0
/* firewall1-10 */
10000   0       0       drop        ip          0.0.0.0/0         0.0.0.0/0
/* firewall1-10000 default-action drop */
```

Related Commands

ip firewall

clear ip

show ip health

show ip health

{**[interfaces]** |
[profiles] |
[status] |
[*<filter/redirection options>*]}

Syntax Description	show ip health
{**[interfaces | profiles | status]** |	Displays health profile configuration.
[profiles] |	Displays health profile configuration.
[status] |	Displays health interfaces runtime status.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip health

Usage Guidelines

Use this command to display health status for interfaces.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays health information for configured interfaces.

```
Perle#show ip health
IP Health Profiles and Tests Configuration:
==========================================
Profile Name   : health-pro
  Failure-count: 5
  Success-count: 5
    Test 10: Type: PING       Response Timeout:   1
Target: 8.8.8.8

Profile Name   : labhealth
  Failure-count: 1
  Success-count: 1

Profile Name   : testit
  Failure-count: 1
  Success-count: 1
IP Interface Health-Profile Configuration:
==========================================
eth1              health-pro

IP Interfaces Health Status:
============================

Interface:  eth1
  Status:  failed
  Last Status Change:  Sat Feb 20 08:05:12 2021
  -Test:  ping Target: 8.8.8.8
    Last Interface Success:  n/a
    Last Interface Failure:  0s
    # Interface Failure(s):  20178
```

Related Commands

(config-if)#dialer

(config-if)#bvi

(config-if-ethernet)#

(config-if)#openvpn-tunnel

(config-if)#tunnel

(config-if)#dot11radio

(config-if)#cellular

show ip host-group

show ip host-group {[*<WORD>*] | [*<filter/redirection options>*]}

Syntax Description **show ip host-group**

{[*<WORD>*] |	Displays IP host groups.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip host-group

Usage Guidelines

Use this command to display IP host groups.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays host group tables.

```
Perle#show ip host-group test
Host list:
  172.16.77.88
  1:2:3:4::5
```

Related Commands

ip host-group

show ip http

show ip http

{**[server status]** |
[*<filter/redirection options>*]}

Syntax Description	**show ip http**
{**[server status]** |	Displays HTTP server status.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip http

Usage Guidelines

Use this command to show status of HTTP server.

Output modifiers (Pipe redirect)—allows you to pipe the output to the redirect options as specified.

Examples

Shows status of HTTP server.

```
Perle#show ip http
Http server status: Enabled
HTTP server port : 80
User session idle timeout: 1440 seconds
HTTP secure server status: Enabled
HTTP secure server port: 443
```

Related Commands

ip http

show ip interface

See *show ip interface*

show ip nat

show ip nat

{**statistics** |

translations |

[*<filter/redirection options>*]}

Syntax Description	show ip nat
{**statistics** |	Displays the Network Address Translation (NAT) source statistics table.
translations |	Displays the pre-nat and post-nat translations. table.
[*<filter/redirection options>*]}	Output modifiers see *Show Command Filtering and Redirection*
Command Modes	Perle#show ip nat

Usage Guidelines

Use this command to display the router's‘s Network Address Translation Table (NAT) statistics and translations.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Example

This example displays IP NAT translations.

Perle#show ip nat translations

```
NAT Source Translations
Pre-NAT              Post-NAT             Prot     Timeout
192.168.30.1         10.10.200.229        tcp      431936
192.168.30.1         10.10.200.229        tcp      431936
192.168.30.1         10.10.200.229        tcp      431936
192.168.30.1         10.10.200.229        tcp      431935
192.168.30.1         10.10.200.229        tcp      431935
192.168.30.1         10.10.200.229        tcp      62
192.168.30.1         10.10.200.229        tcp      61
192.168.30.1         10.10.200.229        tcp      431995
192.168.30.1         10.10.200.229        tcp      431995
192.168.30.1         10.10.200.229        tcp      431995


NAT Destination Translations
Pre-NAT              Post-NAT             Prot     Timeout
10.10.200.229:2222   192.168.20.2:22      tcp      431825
```

Related Commands

ip nat

show ip ospf

show ip ospf

{**[border-routers]** |
[database] |
[interface] |
[neighbor] |
[route] |
[*<filter/redirection options>*]}

Syntax Description	show ip ospf
{**[border-routers]** |	Displays border and boundary router information.
[database] |	Displays database summary.
[interface] |	Displays interface information.
[neighbor] |	Displays neighbor list.

[neighbor] |	Displays OSFP routing table.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip ospf

Usage Guidelines

Use this command to show the router's OSPF routing processes.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

```
Perle#show ip ospf
OSPF Routing Process, Router ID: 172.16.39.2
Supports only single TOS (TOS0) routes
This implementation conforms to RFC2328
RFC1583Compatibility flag is disabled
Opaque Capability flag is disabled
Initial SPF scheduling delay 200 millisec(s)
Minimum hold time between consecutive SPFs 1000 millisec(s)
Maximum hold time between consecutive SPFs 10000 millisec(s)
Hold time multiplier is currently 1
SPF algorithm last executed 7m53s ago
SPF timer is inactive
Refresh timer 10 secs
Number of external LSA 0. Checksum Sum 0x00000000
Number of opaque AS LSA 0. Checksum Sum 0x00000000
Number of areas attached to this router: 1
Area ID: 0.0.0.0 (Backbone)
  Number of interfaces in this area: Total: 1, Active: 1
  Number of fully adjacent neighbors in this area: 0
  Area has no authentication
  SPF algorithm executed 1 times
  Number of LSA 1
  Number of router LSA 1. Checksum Sum 0x00001e7a
  Number of network LSA 0. Checksum Sum 0x00000000
  Number of summary LSA 0. Checksum Sum 0x00000000
  Number of ASBR summary LSA 0. Checksum Sum 0x00000000
```

```
  Number of NSSA LSA 0. Checksum Sum 0x00000000
  Number of opaque link LSA 0. Checksum Sum 0x00000000
  Number of opaque area LSA 0. Checksum Sum 0x00000000
```

Related Commands

router

show ip prefix-list

show ip prefix-list {[*WORD*] |
[*<filter/redirection options>*]}

Syntax Description	show ip prefix-list
{[*WORD*] |	Displays prefix list name.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip prefix-list

Usage Guidelines

Use this command to display prefix list table.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows the ip prefix list.

```
Perle#show ip prefix-list
ip prefix-list prefix-lab (for lab users)
seq 10 permit 172.17.0.0/16
```

Related Commands

ip prefix-list

show ip rip

show ip rip {[**status**] |
[*<filter/redirection options>*]}

Syntax Description	show ip rip status
{[**status**] |	Displays RIP information.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip rip status

Usage Guidelines

Use this command to display rip status information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows rip status information.

```
Perle#show ip rip
Routing Protocol is "rip"
Sending updates every 30 seconds with +/-50%, next due in 30 seconds
Timeout after 180 seconds, garbage collect after 120 seconds
Outgoing update filter list for all interface is not set
Incoming update filter list for all interface is not set
Default redistribution metric is 1
Redistributing:
Default version control: send version 2, receive any version
Interface        Send Recv   Key-chain
Routing for Networks:
Routing Information Sources:
Gateway          BadPackets BadRoutes Distance Last Update
Distance: (default is 120)
```

show ip route

show ip route {[table *<1-200>*] |
[*<filter/redirection options>*]}

Syntax Description	show ip route
{[table *<1-200>*] |	Displays ip routes or route table. Tables must be pre-defined by the user.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip route

Usage Guidelines

Use this command to show configured tables for ip routing.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Shows ip route table entries.

```
Perle#show ip route
table:200
```

Related Commands

ip route

show ip route-policy

show ip route-policy {[*<NAME>*] |

[<*filter/redirection options*>]}

Syntax Description	show ip route-policy
{[<*NAME*>] |	Show ip routes or route table. Tables must be pre-defined by the user.
[<*filter/redirection options*>]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip route-policy

Usage Guidelines

Use this command to display configured routing policies.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Shows ip route policies table.

```
Perle#show ip route-policy
IPv4 Route-policy route1
Active on
Rule    Packets Bytes   Action     Proto     Source          Destination          Rule
                                   Specs
-----   ------- ------- -------    -------    --------------    --------------    ---------------
20      0       0       rtable-254 ip        0.0.0.0/0        0.0.0.0/0
                                   /* route1-9999 */
10000   0       0       accept     ip        0.0.0.0/0        0.0.0.0/0
                                   /* route1-10000 default-action accept */
```

Related Commands

ip route-policy

show ip ssh

show ip ssh

[<*filter/redirection options*>]}

Syntax Description	show ip ssh
[<*filter/redirection options*>]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show ip ssh

Usage Guidelines

Shows configuration for ssh.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows ip ssh configuration.

```
Perle#show ip ssh
SSH version: 2
SSH server: Enabled
Authentication timeout: 120 seconds
Authentication retries: 3
SSH public key:
ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAABAQCgAtvWaaM0CeMWoZV1H00sni2J8T
alvSyysQGyBDIOAydaaKv1+s1Imj00FL2Boi3ke/SoKhvuLJQ+bMVFXD7kXw2fk7
Mo8f8Dd/rOuuF4kE6hKV+LLl44kJKwCUC2w2m4L1lH8Zn8HuX89Qcv2oqPUdkBf
1neIU3gc6gN4v1ckC069Tgg9hrhghCiBECCCYxmAJUhIy4dQcPwO1DQ6Acp2p3
W2RYdgUvRAlr8oLiVdrEvT7zZECpYgCMYWmfsTtUhvv8yZpvNAhV9nRm5E93YI
V2J15qlmIISGKn0iiLRW42xjQ4MT5XmWdlXj+NpuMlQRtFzyYPkR2H
```

Related Commands

ip ssh

show ipv6

See *show ipv6*

show ldap

See *show ldap*

show license

show license

[*<filter/redirection options>*]}

Syntax Description	show license
[*<filter/redirection options>*]}	Output modifiers see *Show Command Filtering and Redirection*
Command Modes	Perle#show license

Usage Guidelines

Use this command to display the GNU license information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

show line

show line

{[console *<0-0>*] |

tty *<1-2>* [modbus statistics master-tcp | master-udp | slave-tcp | slave-udp] | multihost | packet-forwarding | ppp | rlogin-client | settings | slip | ssh-client | ssl |

statistics | telnet-client | udp | vmodem] | **[<*filter/redirection options*>]**}	
Syntax Description	**show line**
{**[console <*0-0*>] |**	Only available on models with console ports. Displays configured console parameters.
tty <*1-2*> [modbus statistics master-tcp | master-udp | slave-tcp | slave-udp] | multihost | packet-forwarding | ppp | rlogin-client | settings | slip | ssh-client | ssl | statistics | telnet-client | udp | vmodem] |	Displays statistics for tty lines.
[<*filter/redirection options*>]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	#show line

Usage Guidelines

Use this command to display various line related configurations.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

Show line parameters for tty1.

Perle#show line tty 1

```
TTY
Service                        reverse raw
    Port                       10001
    Multihost                  none
Break                          Off
Break Delay                    0
Break Length                   0
Connection Method              direct connect
Data Logging                   Off
Dial Retries                   0
Dial Timeouts                  0
Discard Characters             0
Received with Error            Off
Echo Supression                Off
Hotkey Prefix                  0
Idle Timer                     0
Interface                      eia-232
Initiate Connection            any
Initiate Char                  0
address 0
Internet Address
Keepalive                      Off
Line Name
Line Termination               On
Lock                           Off
Map CR to CRLF                 Off
Modem Init String
Monitor DCD                    Off
Monitor DSR_DTR                Off
MOTD                           Off
Multisessions                  0
Pages                          0
Phone Number
Reset                          Off
Rev Sess Session               Off
RTS Toggle                     Off
RTS Toggle Initial Delay       0
RTS Toggle Final Delay         0
Send Name                      Off
Send Port ID                   Off
Session Strings
   Initiate
   Terminate
   Delay                       0
Terminal                       dumb
Tx Driver Control              auto
User
```

show lldp

See ***show lldp***

show logging

show logging

[*<filter/redirection options>*]}

Syntax Description	**show logging**
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show logging

Usage Guidelines

Use this command to display the logging buffer. Logging buffer output may be different on some models.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows the logging buffer.

```
Perle#show logging
Syslog logging: enabled (764643 messages processed, 0 messages rate-limited, 0
                                        overruns)
   Console logging: level debugging, 71 messages logged
   Monitor logging: level debugging, 71 messages logged
      Logging to:
   Buffer logging: level debugging, 1344 messages logged
   File logging: disabled
   Trap logging: level informational
      Logging Source-Interface:
 Log Buffer (16384 bytes):
 Sep 26 20:51:57 %REQHANDLERD-6: CONSOLE: initializing usb serial console
                                        mode
 Sep 26 20:52:02 %IPSEC_STARTER-6: Starting strongSwan 5.6.2 IPsec [starter]...
 Sep 26 20:52:02 %IPSEC_STARTER-6: charon is already running (/var/run/
                                        charon.pid exists) -- skipping daemon start
```

Related Commands

logging

show mab

See ***show mab***

show mac

See ***show mac***

show management-access

show management-access

[*<filter/redirection options>*]}

Syntax Description	show management-access
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show management-access

Usage Guidelines

Use this command to display management access and access restrictions from the LAN and WAN side.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows management access methods for LAN/WAN and TRUSTED interfaces.

Perle#show management-access

```
Management Access is disable

LAN:  eth1 eth1.2 eth1.10 eth1.100 eth1.200 eth2.400 wlan0 wlan1 wlan3 wlan4 br10
      HTTP      HTTPS     TELNET    SSH       SNMP      HTTP-RESTFUL   HTTPS-RESTFUL
      ENABLE    ENABLE    ENABLE    ENABLE    ENABLE    ENABLE         ENABLE

WAN:  wlm0 pppoe0 pppoe5 pppoe10
      HTTP      HTTPS     TELNET    SSH       SNMP      HTTP-RESTFUL   HTTPS-RESTFUL
      DISABLE   DISABLE   DISABLE   DISABLE   DISABLE   DISABLE        DISABLE

TRUSTED:  tun10
      HTTP      HTTPS     TELNET    SSH       SNMP      HTTP-RESTFUL   HTTPS-RESTFUL
      ENABLE    ENABLE    ENABLE    ENABLE    ENABLE    ENABLE         ENABLE
```

Related Commands

(management-access-LAN)

(management-access-WAN)

show nat66

show nat66

{**prefix** |

statistics |

[*<filter/redirection options>*]}

Syntax Description	**show nat66**
{**prefix** |	Display NAT66 prefixes.
statistics |	Display NAT66 statistics.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show nat66

Usage Guidelines

Use this command to display Network Address Translations (NAT) for IPv6 networks.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows NAT66 statistics

```
Perle#show nat66 statistics
Global Stats:
      ID:0
      Packets translated In -> Out
       1290003
      Packets translate Out -> In
       1290003
```

show network-watchdog

show network-watchdog

[*<filter/redirection options>*]}}

Syntax Description	**show network-watchdog**
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show network-watchdog

Usage Guidelines

Use this command to display network watchdog status and configuration.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example shows network-watchdog.

```
Perle#show network-watchdog
Network Watchdog Configuration/Status:
==========================================
Network-watchdog Modem
      Configuration:
        Watchdog: Enable
        Target: 172.16.23.100
        Interface:
        Interval: 10m
        Threshold: 3
        Ping Count: 1
        Ping Timeout: 5s
        Fail Action: notification-only
Test Status:
        Total Success Count: 10  Since last reset Success Count: 9
        Total Failed Count: 1 Failed Tests 1/3 Next Test 0:0 (Min:sec)
        Reset Count: 1
```

```
Network-watchdog Router
      Configuration:
        Watchdog: Enable
        Target: 172.16.23.100
        Interface: eth1
        Interval: 1m
        Threshold: 2
Ping Count: 1
        Ping Timeout: 2s
        Fail Action: notification-only
       Test Status:
Total Success Count: 10 Since last reset Success Count: 9
        Total Failed Count: 1 Failed Tests 1/2 Next Test 0:0 (Min:sec)
        Reset Count: 1
```

Related Commands

network-watchdog

show ntp

See ***show ntp***

show nvram:

See ***show nvram:***

show policy-map

{**incoming** |
queuing |
[*<filter/redirection options>*]}

Syntax Description	**show policy-map**
{**incoming** |	Displays input-policy information.
queueing |	Displays queuing information.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show policy-map

Usage Guidelines

Use this command to display configured policy maps.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

```
Perle#show policy-map incoming
Interface action Received Dropped Overlimit
eth0 limiter 32 10 0
eth2 redirect 64 0 0
```

Related Commands
policy-map

show processes

show processes

[*<filter/redirection options>*]}

Syntax Description	show processes
[*<filter/redirection options>*]}	Output modifiers see *Show Command Filtering and Redirection*
Command Modes	Perle#show processes

Usage Guidelines

Use this command to display processes running on your router.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Perle#show processes

```
USER       PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
root         1  0.0  0.6  92356  6280 ?        Ss   Mar15   0:09 /sbin/init
root         2  0.0  0.0      0     0 ?        S    Mar15   0:00 [kthreadd]
root         4  0.0  0.0      0     0 ?        I<   Mar15   0:00 [kworker/0:0H]
root         6  0.0  0.0      0     0 ?        I<   Mar15   0:00 [mm_percpu_wq]
root         7  0.0  0.0      0     0 ?        S    Mar15   0:06 [ksoftirqd/0]
root         8  0.4  0.0      0     0 ?        I    Mar15   0:59 [rcu_preempt]
root         9  0.0  0.0      0     0 ?        I    Mar15   0:00 [rcu_sched]
root        10  0.0  0.0      0     0 ?        I    Mar15   0:00 [rcu_bh]
root        11  0.0  0.0      0     0 ?        S    Mar15   0:00 [migration/0]
root        12  0.0  0.0      0     0 ?        S    Mar15   0:00 [cpuhp/0]
root        13  0.0  0.0      0     0 ?        S    Mar15   0:00 [cpuhp/1]
root        14  0.0  0.0      0     0 ?        S    Mar15   0:00 [migration/1]
root        15  0.0  0.0      0     0 ?        S    Mar15   0:01 [ksoftirqd/1]
root        17  0.0  0.0      0     0 ?        I<   Mar15   0:00 [kworker/1:0H]
root        18  0.0  0.0      0     0 ?        S    Mar15   0:00 [kdevtmpfs]
root        19  0.0  0.0      0     0 ?        I<   Mar15   0:00 [netns]
root        22  0.0  0.0      0     0 ?        S    Mar15   0:00 [khungtaskd]
root        23  0.0  0.0      0     0 ?        S    Mar15   0:00 [oom_reaper]
root        24  0.0  0.0      0     0 ?        I<   Mar15   0:00 [writeback]
root        25  0.0  0.0      0     0 ?        S    Mar15   0:00 [kcompactd0]
root        26  0.0  0.0      0     0 ?        SN   Mar15   0:00 [ksmd]
root        27  0.0  0.0      0     0 ?        SN   Mar15   0:00 [khugepaged]
root        28  0.0  0.0      0     0 ?        I<   Mar15   0:00 [crypto]
root        29  0.0  0.0      0     0 ?        I<   Mar15   0:00 [kintegrityd]
root        30  0.0  0.0      0     0 ?        I<   Mar15   0:00 [kblockd]
root        31  0.0  0.0      0     0 ?        I<   Mar15   0:00 [ata_sff]
root        32  0.0  0.0      0     0 ?        I<   Mar15   0:00 [a3700_otg_queue]
root        33  0.0  0.0      0     0 ?        I<   Mar15   0:00 [md]
root        34  0.0  0.0      0     0 ?        I<   Mar15   0:00 [watchdogd]
root        35  0.0  0.0      0     0 ?        I<   Mar15   0:00 [rpciod]
root        36  0.0  0.0      0     0 ?        I<   Mar15   0:00 [xprtiod]
root        73  0.0  0.0      0     0 ?        S    Mar15   0:00 [kauditd]
root        74  0.0  0.0      0     0 ?        S    Mar15   0:00 [kswapd0]
root        75  0.0  0.0      0     0 ?        I<   Mar15   0:00 [nfsiod]
root        91  0.0  0.0      0     0 ?        I<   Mar15   0:00 [kthrotld]
root        92  0.0  0.0      0     0 ?        I<   Mar15   0:00 [perle_genl_work]
root        93  0.0  0.0      0     0 ?        I<   Mar15   0:00 [perle_genl_irq_]
root        95  0.0  0.0      0     0 ?        I<   Mar15   0:00 [nvme-wq]
root        96  0.0  0.0      0     0 ?        S    Mar15   0:00 [spi0]
root        97  0.0  0.0      0     0 ?        S    Mar15   0:00 [xrm1280]
root        98  0.0  0.0      0     0 ?        S    Mar15   0:00 [irq/58-spi0.0]
root        99  0.0  0.0      0     0 ?        S    Mar15   0:00 [xrm1280]
root       100  0.0  0.0      0     0 ?        S    Mar15   0:00 [irq/59-spi0.1]
```

- - - - - - - - - -

show radius

See *show radius*

show reload

show reload

[*<filter/redirection options>*]}

Syntax Description	show reload
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show reload

Usage Guidelines

Use this command to display scheduled router reloads or reboots.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example show configured reloads.

```
Perle#show reload
Reload scheduled for 18:00:00 EDT Oct 17 2019 (in 59 minutes)
```

Related Commands

reload

show rest-api

show rest-api

{**jwt | server status |**
[*<filter/redirection options>*]}

Syntax Description	show rest-api
{**jwt | server status |**	Show RESTful API information.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show rest-api

Usage Guidelines

Use this command to display RESTful API information.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays RESTful API information.

```
Perle#show rest-api server status
RESTful API HTTP server status: Disabled
RESTful API HTTP server port: 8080
Cookie maximum age timeout: 1440 seconds
RESTful API HTTPS server status: Disabled
RESTful API HTTPS server port: 8443
```

Related Commands

remote-management

show route-map

show route-map {[*<WORD>*] | [*<filter/redirection options>*]}

Syntax Description	**show route-map**
{*<WORD>* |	Displays specified route map.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show route-map

Usage Guidelines

Use this command to display route map information.

Output modifiers (Pipe redirect)—allows you to pipe the output to the redirect options as specified.

Example

Shows route map details.

```
Perle#show route-map route1
RIB:
route-map route1, permit, sequence 2
  Match clauses:
  Set clauses:
  Call clause:
  Action:
    Exit routemap
RIP:
route-map route1, permit, sequence 2
Match clauses:
  Set clauses:
  Call clause:
  Action:
    Exit routemap
```

```
RIPV6:
route-map route1, permit, sequence 2
  Match clauses:
  Set clauses:
  Call clause:
  Action:
    Exit routemap
OSPF:
route-map route1, permit, sequence 2
  Match clauses:
  Set clauses:
  Call clause:
  Action:
    Exit routemap
OSPF6:
route-map route1, permit, sequence 2
  Match clauses:
  Set clauses:
  Call clause:
Action:
    Exit routemap
BGP:
route-map route1, permit, since
  Match clauses:
  Set clauses:
  Call clause:
  Action: Exit routemap
```

Related Commands

router

show running-config

show running-config

{**[all]** |
[*<filter/redirection options>*]}

Syntax Description	**show running-config**
{**[all]** |	Displays all config including defaults.
[*<filter/redirection options>*]}	Output modifiers see *Show Command Filtering and Redirection*
Command Modes	Perle#show running-config

Usage Guidelines

Use this command to display the router's current running config. To make this configuration permanent you must copy running config to startup config.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Related Commands

show startup-config

show sdm

show sdm

{**prefer** |
[*<filter/redirection options>*]}

Syntax Description	**show sdm**
{**prefer** |	Displays the value for sdm.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Default	Both IPv4 and IPv6
Command Modes	Perle#show sdm

Usage Guidelines

Use this command to display IPv4/IPv6 protocols running on your router

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the current value for sdm.

```
Perle#show sdm prefer
The current template is 'dual-ipv4-and-ipv6 default template
```

Related Command

sdm

show serial

show serial

{**advanced** |
[**modbus gateway**] |
[**port-buffering**] |
[**trueport remap**] |
[**username**] *<WORD>* |

[vmodem | vmodem-phone] |
[*<filter/redirection options>*]}

Syntax Description	show serial
{**advanced** |	Displays advanced configuration.
[modbus gateway] |	Displays modbus configuration.
[port-buffering] |	Displays port buffering information.
[trueport remap] |	Displays Trueport configuration.
[username] ***<WORD>*** |	Displays user configuration for serial port.
[vmodem | vmodem-phone] |	Displays virtual modem phone number.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show serial

Usage Guidelines

Use this command to view serial configuration.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays the advanced configuration for serial.

```
Perle#show serial advanced
Process Break Signals          off
Flush on Close                 off
Single Telnet                  off
Data Logging Buffer Size       4K
Monitor Connection Interval    180 Seconds
Monitor Connection Number of Retries 5
Monitor Connection Retry Timeout     5 Seconds
```

Related Command

serial

show snmp

show snmp

{**community** |
[contact] |
[engine-id] |
[group] |
[host] |

[location] |
[mib ifmib ifindex] |
[user] |
[view] |
[*<filter/redirection options>*]}

Syntax Description	show snmp
{**community** |	Displays community name.
[contact] |	Displays contact information
[engine-id] |	Displays SNMP engine-id.
[group] |	Displays SNMP groups.
[host] |	Displays host information
[location] |	Displays location information.
[mib ifmib ifindex] |	Displays SNMP ifmib information.
[user] |	Displays SNMP users.
[view] |	Displays SNMP views.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show snmp

Usage Guidelines

Use this command to display SNMP configured options.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example show the configured options for SNMP.

```
Perle#show snmp view
View name: router-view
  include: iso, exclude
```

Related Commands

snmp-server

show ssh

See ***show ssh***

show startup-config

show startup-config

[*<filter/redirection options>*]}

Syntax Description	show startup-config
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show startup-config

Usage Guidelines

Use this command to display the router‘s startup configuration. This is the configuration which is used when the device is first powered up or re-booted.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Related Commands

show running-config

show system

show system

{**[hardware]** |
[statuses] |
[uptime] |
[versions verbose] |
[*<filter/redirection options>*]}

Syntax Description	show system
{**[hardware]** |	Displays hardware details.
[statuses] |	Displays system statuses for alarms, memory, flash etc:
[uptime] |	Displays router’s uptime.
[versions verbose] |	Displays router’s software versions.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show system

Usage Guidelines

Use this command to displays information about software versions.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

This is a sample of the type of information presented. The specific information displayed on your system is model Dependant.

```
Perle#show system statuses

System Statuses:
 System Up Time............................... 7
```

```
hours 26 minutes 4 seconds
 System Date and Time (local time
zone)........ 2019-12-10 18:02:18

Startup-Configuration state................... In
Sync with
Running-configuration
 Digital Inputs:
    Contact A:AUX-IO: Digital Input A..........Closed
    Contact B:AUX-IO: Digital Input B..........Closed
    Contact 2:DC-POWER:GPIO................... Open
 Analog Inputs:
    Contact 1:DC-POWER:IGN.................... 0.29 Volts
    Contact 2:DC-POWER:GPIO................... 0.46 Volts
System Statuses:
 System Up Time............................... 7 hours 26 minutes 4 seconds
 System Date and Time (local time zone)........ 2019-12-10 18:02:18
Startup-Configuration state................... In Sync with
Running-configuration
Digital Inputs:
    Contact A:AUX-IO: Digital Input A......... Closed
    Contact B:AUX-IO: Digital Input B......... Closed
    Contact 2:DC-POWER: GPIO................... Open
 Analog Inputs:
    Contact 1:DC-POWER: IGN.................... 0.29 Volts
    Contact 2:DC-POWER: GPIO................... 0.46 Volts

 Last Alarm ................................... No Alarm
CPU Utilization............................... 4.55
 Memory (kBytes free)......................... 55420

 Flashdisk (Mbytes free)...................... 1008
```

show tacacs

See ***show tacacs***

show task-status

show task-status

{[*<filter/redirection options>*]}

Syntax Description **show task-status**

{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show task-status

Usage Guidelines

Use this command to display system running tasks.

Output modifiers (Pipe redirect)—allows you to pipe the output to the redirect options as specified.

Examples

Perle#show task-status

```
top - 22:28:58 up  4:15,  0 users,  load average: 0.04, 0.10, 0.18
Tasks: 158 total,   1 running, 108 sleeping,   0 stopped,   0 zombie
%Cpu(s):  2.9 us,  2.1 sy,  0.0 ni, 95.0 id,  0.0 wa,  0.0 hi,  0.0 si,  0.0 st
KiB Mem:   1014044 total,   975328 used,    38716 free,   107612 buffers
KiB Swap:        0 total,        0 used,        0 free.   412856 cached Mem

  PID USER      PR  NI    VIRT    RES    SHR S  %CPU %MEM     TIME+ COMMAND
20200 root      20   0   10284   3360   2940 R   6.0  0.3   0:00.08 top
    1 root      20   0   92556   6212   3740 S   0.0  0.6   1:26.83 systemd
    2 root      20   0       0      0      0 S   0.0  0.0   0:00.01 kthreadd
    4 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 kworker/0:+
    6 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 mm_percpu_+
    7 root      20   0       0      0      0 S   0.0  0.0   0:01.02 ksoftirqd/0
    8 root      20   0       0      0      0 I   0.0  0.0   0:14.45 rcu_preempt
    9 root      20   0       0      0      0 I   0.0  0.0   0:00.30 rcu_sched
   10 root      20   0       0      0      0 I   0.0  0.0   0:00.00 rcu_bh
   11 root      rt   0       0      0      0 S   0.0  0.0   0:00.09 migration/0
   12 root      20   0       0      0      0 S   0.0  0.0   0:00.00 cpuhp/0
   13 root      20   0       0      0      0 S   0.0  0.0   0:00.00 cpuhp/1
   14 root      rt   0       0      0      0 S   0.0  0.0   0:00.08 migration/1
   15 root      20   0       0      0      0 S   0.0  0.0   0:00.81 ksoftirqd/1
   17 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 kworker/1:+
   18 root      20   0       0      0      0 S   0.0  0.0   0:00.00 kdevtmpfs
   19 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 netns
   22 root      20   0       0      0      0 S   0.0  0.0   0:00.01 khungtaskd
   23 root      20   0       0      0      0 S   0.0  0.0   0:00.00 oom_reaper
   24 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 writeback
   25 root      20   0       0      0      0 S   0.0  0.0   0:00.00 kcompactd0
   26 root      25   5       0      0      0 S   0.0  0.0   0:00.00 ksmd
   27 root      39  19       0      0      0 S   0.0  0.0   0:00.46 khugepaged
   28 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 crypto
   29 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 kintegrityd
   30 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 kblockd
   31 root       0 -20       0      0      0 I   0.0  0.0   0:00.00 ata_sff
```

****

show tech-support

show tech-support

{[*<filter/redirection options>*]}

Syntax Description	**show tech-support**
{[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show tech-support

Usage Guidelines

Use this command to capture internal router information. It will capture a large range of information which you could send to Perle technical support to assist in resolving issues.

Output modifiers (Pipe redirect)—allows you to pipe the output to the redirect options as specified.

show terminal

See ***show terminal***

show username

show username

{[*<WORD>*] |
[*<filter/redirection options>*]}

Syntax Description	show username
{[*<WORD>*] |	Type the username to display.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show username

Usage Guidelines

Use this command to display information about a user.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

```
Perle#show username lyn
username      lyn
  privilegeLevel 15
  Password:     ********
  password created: Fri Sep 18 21:18:27 testtime zone 2020
  Two Factor    Disabled
```

Related Commands

show users

show users

See ***show users***

show version

See ***show version***

show vrrp

show vrrp

{**interface** |
[status] |
[*<filter/redirection options>*]}

Syntax Description	show vrrp
{**[interface]** |	Displays VRRP information for specified interface.
[status] |	Displays VRRP statistics.
[*<filter/redirection options>*]}	See ***Show Command Filtering and Redirection***
Command Modes	Perle#show vrrp

Usage Guidelines

Use this command to display VVRP interface information and statistics.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays VRRP information on Ethernet interface 1.

```
Perle#show vrrp interface 1
Interface: eth1
--------------
  Group: 10
  ----------
  State:     FAULT
  Last transition:  12m23s

  Priority:   100
  Advertisement interval: 1000 milli-sec
  Preempt:   enabled

  VIP count:   1
    172.16.44.55/16
```

Related Commands

vrrp

show wan

show wan

{**failover source-interface | status |wan-interface** |
high-availability |
load-sharing rules | status |

[*<filter/redirection options>*]}

Syntax Description	show wan
{**failover source-interface | status |wan-interface** |	Displays WAN source interface configuration and status.
high-availability |	Displays WAN management.
load-sharing rules | status |	Displays load sharing configuration and status.
[*<filter/redirection options>*]}	Output modifiers see ***Show Command Filtering and Redirection***
Command Modes	Perle#show wan

Usage Guidelines

Use this command to show wan configured features for fail over, high-availability and load sharing.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Examples

This example displays WAN management.

```
Perle#show wan high-availablity
WAN High Availability
=====================
  Mode: DISABLED

WAN Failover Primary Active Interface:
======================================
  DISABLED


WAN Load Failover Interfaces Health Status:
===========================================
  DISABLED

WAN Load Share Global Settings:
===============================
  Include Local Traffic:        enabled
  Source IP NAT:                disabled
  Track inbound Connections:    enabled
  Flush Connections on Failure: enabled
WAN Load Sharing Interfaces Health Status:
==========================================
  DISABLED
```

Related Commands

wan

show zone-policy

show zone-policy

{**zone** *<WORD>* |
[*<filter/redirection options>*]}

Syntax Description	show zone-policy
{**zone** *<WORD>* |	Displays specified zone policy.
[*<filter/redirection options>*]}	Output modifiers see *Show Command Filtering and Redirection*
Command Modes	Perle#show zone-policy

Usage Guidelines

Use this command to show zone policy for the specified zone.

Output modifiers (Pipe redirect)—allows you to redirect the output to the options as specified.

Related Commands

zone-pair

shutdown

shutdown

Syntax Description	shutdown
{**shutdown**}	Shutdown the router. The Reset button brings system backup.
Command Modes	Perle#shutdown

Usage Guidelines

Use this command to shutdown the router.

ssh

See *ssh*

standby

standby

{**resume-standby-configuration**}

Syntax Description	standby

{**resume-standby-configuration**}	Resumes current standby configuration.
Command Modes	Perle##standby

Usage Guidelines

Use this command to force standby mode or resume from forced standby mode.

Examples

This example displays how to resume standby configuration.

```
Perle#standby resume
Resuming all power standby-mode configuration.
```

Related Commands

show wan

wan

(config-smrt-stdby)

telnet

See ***telnet***

terminal

See ***terminal***

testemail

See ***testemail***

testsms

See ***testsms***

traceroute

See ***traceroute***

undebug

undebug

{**alarmgr** |

all |

bgp |

bridge spanning-tree packet |

cellular-gnss |

cellular-lte |

clpd |

dialer |

dot11-ap |

dot11-station |

dot1x-authenticator |

dot11-supplicant |

drmgrd |
email |
init |
ip |
ip-passthrough |
ipsec |
kernel |
lldp |
logging |
ntp |
rest-api |
snmp |
trapmgr |
tty |
vrrp |
vty |
wan-highavail |
wanifmgr}

Syntax Description	undebug
{**alarmgr** |	Turns off alarmgr debug.
all |	Turns all debug off.
bgp |	Turns off BGP debug.
bridge spanning-tree packet |	Turns off bridge spanning-tree debug.
cellular-gnss |	Turns off cellular-gnss debug.
cellular-lte |	Turns off cellualar debug.
clpd |	Turns off clpd debug.
dialer |	Turns off dialer debug.
dot11-ap |	Turns off dot11-ap debug.
dot11-station |	Turns off dot11 station debug.
dot1x-authenticator |	Turns off dot1x authenticator debug.
dot11-supplicant |	Turns off dot1x debug.
drmgrd |	Turns off drmgrd debug.
email |	Turns off email debug.
init |	Turns off init process debug.

ip |	Turns off ip process debug.
ip-passthrough |	Turns off ip-pass through debug.
ipsec |	Turns off IPsec debug.
kernel |	Turns off kernel debug.
lldp |	Turns off LLDP debug.
logging |	Turns off logging debug.
ntp |	Turns off NTP debug.
rest-api |	Turns off RESTful API debug.
snmp |	Turns off SNMP debug.
trapmgr |	Turns off trapmgr debug.
tty |	Turns off tty debug.
vrrp |	Turns off VRRP debug.
vty |	Turns off vty debug.
wan-highavail |	Turns off wan-highavail debug.
wanifmgr}	Turns off wanifmgr debug.

Command Modes Perle#undebug

Usage Guidelines

Use this command to turn debugging mode off for a process.

Examples

This example turns off debugging for alarmmgr.

```
Perle#undebug alarmgr
Alarm Manager debugging is off
```

Related Commands

copy
password
traceroute

|

vrrp

vrrp {**restart**}

Syntax Description	**vrrp**
{**restart**}	Restart VRRP process.

Command Modes	Perle#vrrp

Usage Guidelines

Use this command to restart VRRP.

Examples

This example restarts VRRP.

Perle#restart vrrp

Related Commands

show vrrp

vrrp

4 Global Configuration Mode

This chapter defines all the CLI commands in Global Configuration Mode. Some CLI commands may not be applicable to your model or running software.

aaa

aaa

{[accounting dot1x default start-stop group *<WORD>* radius | tacacs] | [exec *<WORD>* | default none | start-stop broadcast | group |radius | tacacs | stop-only broadcast | group |radius | tacacs] | [system default none | start-stop] |
authentication attempts login *<1-25>* | [dot1x default group *<WORD>* | radius] | [login *<WORD>* group *<WORD>* | ldap | local | none | radius | tacacs | default group *<WORD>* | group | ldap local | none | radius | tacacs] | [two-factor pin-attempts *<1-10>* | pin-size *<4-6>* | pi n-tries *<1-10>* | [wan-only off | on] |
authorization [console] | [exec *<WORD>* | group *<WORD>* if-authenticated | local | none | radius | tacacs] |
group server [ldap *<WORD>*] | [radius *<WORD>*] | [tacacs *<WORD>*] |
local [authentication attempts max-fail *<1-65535>*] | [username min-len *<1-32>*] | [lockout-time *<30-65535>*] |
password expiry *<1-999>* | pbkdf2 rounds *<1000-100000000>* | restriction enable | group [lower-case *<1-5>* | numeric *<1-5>* | special | upper-case *<1-5>* | max-len *<1-128>* | min-len *<1-64>* | reuse *<1-32>*]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	aaa
{[accounting dot1x default start-stop group *<WORD>* radius | tacacs] | [exec *<WORD>* | default none | start-stop broadcast | group |radius | tacacs | stop-only broadcast | group |radius | tacacs] | [system default none | start-stop] |	When AAA accounting is enabled, the router reports user activity to the TACACS+ or RADIUS security server (depending on which security method is selected) in the form of accounting records.This allows the AAA accounting feature to track the services that users are accessing and the amount of network resources that users are consuming. Each accounting record contains accounting attributes that are stored on the security server. This data can then be analyzed for network management, client billing, and auditing. If using groups a pre-defined group must have been previously created.
authentication attempts login *<1-25>* | [dot1x default group *<WORD>* | radius] | [login *<WORD>* group *<WORD>* | ldap | local | none | radius | tacacs | default	Configure authentication parameters. Authentication verifies users before they are allowed access to the network and network services (which are verified with authorization).

group *<WORD>* | group | ldap local | none | radius | tacacs] | [two-factor pin-attempts *<1-10>* | pin-size *<4-6>* | pi n-tries *<1-10>* | [wan-only off | on] |	The default method list is automatically applied to all interfaces except those that have a named method list explicitly defined. A defined method list overrides the default method list.The first listed method is used. If it fails to respond, the second one is used, and so on. **Two factor** authentication parameters for pin attempts, size, and retries. **WAN-only** **Off—**all admin users, (privilege 15), require two factor authentication. **On**—admin users (privilege 15), require two factor authentication only for remote network connections.
authorization [console] | [exec *<WORD>* | group *<WORD>* if-authenticated | local | none | radius | tacacs] |	Configure parameters for the authorization EXEC command. This determines if the user is allowed to run in EXEC mode. EXEC authorization applies to vty and tty lines.The first listed method is used. If it fails to respond, the second one is used, and so on.
group server [ldap *<WORD>*] | [radius *<WORD>*] | [tacacs *<WORD>*] |	Configure a group server for LDAP, RADIUS or TACACS+.
local [authentication attempts max-fail *<1-65535>*] | [username min-len *<1-32>*] | [lockout-time *<30-65535>*] |	Configure local user failed authentication attempts. Value is 1–65535 attempts Default is never lock the user out. On the FN router the default is 5 attempts, then the user is locked out for one hour. Configure the minimum length for user names. Values are 1 to 32 Default is minimum length of 1. Lock out time is 30 to 65535 in minutes.
password expiry *<1-999>* | pbkdf2 rounds *<1000-100000000>* | restriction enable | group [lower-case *<1-5>* | numeric *<1-5>* | special | upper-case *<1-5>* | max-len *<1-128>* | min-len *<1-64>* | reuse *<1-32>*]}	Configure password restrictions. • Password cannot be the same as User name • Cannot have 3 consecutive characters in the same password • No password is not allowed • Special character are any non alphanumeric character

	• Minimum number of lowercase characters is 1–5 • Minimum number of lowercase numeric numbers is 1–5 • Minimum number of special characters is 1–5 • Minimum number of uppercase characters is 1–5 • Number of times a password can be changed before it can be reused. Value is 1–32 times pbkdf2 round default is 100000 The larger number of rounds, the more secure password hashing, however slower logins will occurs.
Command Modes	Perle(config)#aaa

Usage Guidelines

Configure Authentication, Authorization, and Accounting parameters.

Examples

This example generates start and stop accounting records.

```
Perle(config)#aaa accounting network default start-stop group radius
```

This example configures authentication and authorization to RADIUS as the first method to authenticate/authorize, then local database as the second method for all users.

```
Perle(config)#aaa authentication login default group radius local
Perle(config)#aaa authorization exec default group radius local
```

This example sets two-factor authentication attempts to 2.

```
Perle(config)#aaa authentication two-factor pin-attempt 2
```

Related Commands

clear aaa
(config-ldap-server)
clear ldap
(config-sg-radius)
clear radius
(config-sg-tacacs)
clear tacacs
(config-user-2factor)

(config-sg-ldap)

{**server name** ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-sg-ldap)#**
{**server name** ***<WORD>***}	Configure LDAP server name.
Command Modes	Perle(config-sg-ldap)#

Usage Guidelines

Use this command to configure LDAP server name.

Examples

This example configures the LDAP server name to LDAP1.

```
Perle(config-sg-ldap)#server name ldap1
```

Related Commands

clear ldap
ldap
show ldap

(config-sg-radius)

{**server name** ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-sg-radius)#**
{**server name** ***<WORD>***}	Configure RADIUS server name.
Command Modes	Perle(config-sg-radius)#

Usage Guidelines

Use this command to configure the RADIUS server name.

Examples

This example configures the RADIUS server name to RADIUS1.

```
Perle(config-sg-radius)#server name radius1
```

Related Commands

clear radius
ip radius
show radius
(config-radius-server)

(config-sg-tacacs)

{**server name** ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-sg-tacacs)#
{**server name** *<WORD>*}	Configure TACACS+ server name.
Command Modes	Perle(config-sg-tacacs)#

Usage Guidelines

Use this command to configure the TACACS+ server name.

Examples

This example configures the TACACS+ server name to TACACS1.

Perle(config-sg-radius)#server name tacacs1

Related Commands

ip tacacs

tacacs

clear tacacs

show tacacs

alarm

alarm

{**contact** *<1-2> <1-1>* **analog [coefficient** *< -2147483.647 - 2147483.646>*] | [**offset** *< -2147483.647 - 2147483.6476*] | [**units** *<LINE>*] | **description** *<LINE>*] | [**severity major | minor | none**] *<2>* **analog coefficient** *< -2147483.647 - 2147483.646>* | **offset** *< -2147483.647 - 2147483.646>* | **units** *<LINE> <A-B>* | **description** *<LINE>* | [**digital power-source dry | wet**] | [**trigger closed | open**] | [**output sink**] | [**pulse-counter mode pulses | transitions**] | [**trigger open | closed**] | [**severity major | minor | none**] |

facility input-alarm *<1>* **analog [high** *< -2147483.647 - 2147483.6476*] | [**low** *< -2147483.647 - 2147483.646>*] | [**lte-data-disc**] | [**notifies**] | [**relay minor relay-mode energized**] | [**syslog**] | [**standby-mode disable** | [**lte-data-disc**] | [**notifies**] | [**relay minor**] | [**syslog**] | **temperature primary high** *<-150-300>* | **low** *<-200 -250>* | [**lte-data-disc**] | [**notifies**] | **relay** [**minor | major**] | [**syslog**] | **secondary high** *<-150-300>* | **low***<-200 -250>* | [**lte-data-disc**] | [**notifies**] | [**relay**] | [**syslog**] | [**profile** *<WORD>*] |

relay major relay-mode energizer | [minor relay-mode energized]}|

temperature primary | secondary high low lte-data-disc | notifies | relay **major relay-mode energizer | [minor relay-mode energized]**| syslog

Use the no form of this command to negate a command or set to defaults.

Syntax Description	alarm

{**contact** ***<1-2> <1-1>*** **analog [coefficient** ***< -2147483.647 - 2147483.646>*** **] | [offset** ***< -2147483.647 - 2147483.6476*** **] | [units** ***<LINE>*** **] | description** ***<LINE>*** **] | [severity major | minor | none]** {***<2>*** **analog coefficient** ***< -2147483.647 - 2147483.646>*** **| offset < -dry | wet] | [trigger closed | open] | [output sink] | [pulse-counter mode pulses | transitions] | [trigger open | closed] | [severity major | minor | none]** |	Configure the DC-Power alarm contact settings <1-2>. Configure the Analog Input AI settings <1-1>. Configure the AUX-IO alarm contact settings <A-B>. **Severity** • Major—immediate action needed • Minor—minor warning condition. **Note:** Relay Minor not available on the IRG5410 model, Relay Minor only available if GPIO is configured as an output. Some options not available on some models or running firmware. Set the alarm trigger closed— assert alarm with contact is closed open—assert alarm when the contact is open
facility input-alarm ***<1>*** **analog [high** ***< -2147483.647 - 2147483.6476*** **] | [low** ***< -2147483.647 - 2147483.646>*** **] | [lte-data-disc] | [notifies] | [relay minor relay-mode energized] | [syslog] | [standby-mode disable | [lte-data-disc] | [notifies] | [relay minor] | [syslog] | temperature primary high** ***<-150-300>*** **| low** ***<-200 -250>*** **| [lte-data-disc] | [notifies] | relay [minor | major] | [syslog] | secondary high** ***<-150-300>*** **| low***<-200 -250>* **| [lte-data-disc] | [notifies] | [relay] | [syslog]** |	Configure external input alarm for DC-Power <1-2> or AUX-IO <A-B> alarm contact. Dual power supplies supported on 5140 models only. Configure Power Standby-mode settings.
profile ***<WORD>*** |	See ***(config-alarm-profile)#*** for configuring parameters.
relay major relay-mode energizer | [minor relay-mode energized] |	Configure relay parameters. **Severity** • Major—immediate action needed • Minor——minor warning condition
Command Modes	alarm

Usage Guidelines

Use this command to configure parameters for alarms.

Examples

This example enables Input A digital to trigger an alarm on digital open.

PerleRouter(config)#alarm facilty input a digital enable

Related Commands

show alarm

(config-alarm-profile)#

(config-alarm-profile)#

{**alarm | link-fault | not-forwarding | not operating** |
notifies | **link-fault | not-forwarding | not operating** |
relay | [major link-fault | not forwarding | not operating] | [major | minor |
syslog link-fault | not-forwarding | not operating}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-alarm-profile)#**
{**alarm	link-fault	not-forwarding	not operating** |	Monitors for alarm type. • link-fault • port-not-forwarding • port-not-operating
**notifies	link-fault	not forwarding	not operating** |	Sends a trap/notification to the configured SNMP host trap receivers on the triggering and clearing of the alarms. • link-fault • port-not-forwarding • port-not-operating
**relay	[major link-fault	not forwarding	not operating]	[minor link fault	not-forwarding	not operating]** |	Energizes/de-energizes relay on the triggering and clearing of an alarm.
**syslog link-fault	not-forwarding	not operating**	Sends a syslog message to the configured syslog host on the triggering and clearing of these alarms. • link-fault • port-not-forwarding • port-not-operating
Command Modes	Perle(config-alarm-profile)#

Usage Guidelines

Use this command to configure alarm profile parameters.

Examples

This example configures an alarm profile to monitor for link fault and send a syslog message to the configured server.

```
Perle(config))#alarm profile test-alarm
Perle(config-alarm-profile)#alarm link-fault
Perle(config-alarm-profile)#syslog link-fault
```

Related Commands

show alarm

archive

(config-archive)#

{**maximum** ***1-14*** |
path flash: | ftp: | http: | https: | scp: | sftp | tftp: |
time-period ***<0-525600>*** |
update-sw check | auto-download |
write-memory}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-archive)#
{**maximum** ***1-14*** |	Configure the number of configuration archives to keep in the archive list. Archive list can contain between 1–14 configurations.
path flash: | ftp: | http: | https: | scp: | sftp | tftp: |	Configure the file system path for archived configurations. The path must exist.
time-period ***<0-525600>*** |	Configure the time period to automatically save the running configuration to an archive file.
update-sw check | auto-download |	Enables update-software check. Check default is Disabled Auto-download is enabled for FN models
write-memory}	Enables—saves the configuration to an archive file each time you copy running-config to start-up config.
Command Default	no path maximum 10 no time-period no write-memory
Command Modes	Perle(config-archive)#archive

Usage Guidelines

Use this command to configure the full path to store archive configuration files.

flash:*perle-image-name.img*

ftp:*[[//username[:password]@location]/directory]/perle-image-name.img* http://*[[username:password]@][hostname | host-ip [directory] /perle-image-name.img*

https://*[[username:password]@][hostname | host-ip [directory] /perle-image-name.img* |

scp:*[[username@location]/directory]/perle-image-name.img* | sftp:*[[//username[:password]@location]/directory]/perle-image-name.img* | tftp:*[[//location]/directory]/perle-image-name.img*

Examples

This example sets up an archive path for the write-memory command.

```
Perle(config-archive)#path flash:
Perle(config-archive)#write-memory
Perle(config-archive)#exit
Perle(config)#exit
```

If you do not supply a filename, then your running config is named with the current date and time. See below.

```
Perle#show flash:
Directory of flash:
78     -rw-     10764  Sep 22 2020 11:30 -06:00 -Sep-22-11-30-29-0130322   -rw-
5643 Perle
```

Related Commands

show archive

(config-archive)#

archive

arp

arp

{***<A.B.C.D> <H.H.H>* bvi *<1-9999>*] | [dot11radio *<0-4>*] |[ethernet *<1-5>* . *<1-4000>*]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	arp
{***<A.B.C.D> <H.H.H>* bvi *<1-9999>*] |[dot11radio *<0-4>*]	[ethernet *<1-5>*. *<1-4000>*]**}	Add static ARP entry to the ARP table.
Command Modes	Perle(config)#arp

Usage Guidelines

Use this command to add ARP entries to ARP table.

Examples

Add this ARP entry to the ARP table.

Perle(config)#arp 172.16.44.55 1234.1234.1234 bvi 2

Related Commands

show arp

banner

banner

{*<LINE>* |

login *<LINE>* |

motd *<LINE>* |

prompt-timeout}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	banner
{*<LINE>* |	Configure a delimiting character to indicate the start and end of the message. It cannot be a character that you use in the message. Do not use " or % as a delimiting character. No white space characters are allowed.
login *<LINE>* |	Configure the login banner.
motd *<LINE>* |	Configure the message of the day (MOTD) on login.
prompt-timeout *<LINE>*}	Configure the message for login authentication timeout.
Command Modes	Perle(config)#banner

Usage Guidelines

Use this command to configure a banner or message of the day to display to users.

delimiter character—indicates the start and end of the message and is not a character that you use in the message. Do not use " or % as a delimiting character. White space characters do not work.

banner text—the text is alphanumeric, case sensitive, and can contain special characters. It cannot contain the delimiter character you have chosen. The text has a maximum length of 80 characters and a maximum of 40 lines.

The banner has special macros that are inserted into the banner.

They are:

$(hostname) which is the hostname you configured on the switch and **$(domain)** which is the domain name you configured on the router.

login—set login banner

motd—set message of the day (motd)

prompt-timeout—login authentication timeout

Banner applies to all consoles and vty sessions.

Examples

Displays a message of the day at login.

```
Perle(config)#banner motd line
Enter text message. End with the character 'l'
Good morning crew

Enter configuration commands, one per line. End with CNTL/Z
```

This example sets the domain name to be used in the banner, then set a banner of Good morning and Welcome to your domain. Domain is replaced with the domain name of MYTEST-DOMAIN.

```
Perle(config)# ip domain-name MYTEST-DOMAIN
Perle(config)#banner hGood morning and Welcome to your h
$(domain)
```

Related Commands

(config-line)#console

boot

boot

{**host dhcp | [retry timeout** ***<600-65535>*****]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description **boot**

{**host dhcp | [retry timeout** ***<600-65535>***]}	Configure boot parameters. **host dhcp**—enables Zero Touch provisioning (ZTP). Download configuration via DHCP server. **host retry timeout**—sets the time in seconds to wait for ZTP to complete (including time to download config or software). **no boot host retry timeout**—waits indefinitely for ZTP to complete.
Command Modes	Perle(config)#boot

Usage Guidelines

Use this command to enable ZTP. This command allows you to download your config and firmware via your DHCP server.

Examples

This example configures ZTP so that configuration and firmware files are downloaded from your DHCP server.

```
Perle(config)#boot host dhcp
```

bridge

bridge

{**bridge** ***<1-4000>*** **spanning-tree | protocol ieee |**
spanning-tree logging}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**spanning-tree**
{**bridge** ***<1-4000>*** **| spanning-tree | protocol ieee |**	Configure the bridge range and spanning-tree. Values are 1 to 4000.
spanning-tree logging}	Configure spanning tree logging.
Command Modes	Perle(config)#spanning-tree bridge

Usage Guidelines

Use this command to configure a bridge range and enable spanning tree sub-menu. Spanning Tree Protocol (STP) is a loop free topology for an Ethernet local area network. If loops are detected, the protocol blocks one of the paths to eliminate the loop. STP prevents bridge loops and broadcast radiation. The spanning-tree protocol is applied to previously defined bridge interfaces.

Examples

This example configures bridge 10 with spanning-tree.

```
Perle(config)#bridge 10 spanning-tree
Perle(config-st-bridge)#
```

Related Commands

(config-st-bridge)#

(config-st-bridge)#

{**aging -time** ***<10-1000000>*** |
forward-time ***<4-30>*** |
hello-timer ***<1-10>*** |
loop-guard default |
max-age ***<10-1000000>*** |
max-hops ***<6-40>*** |
mode mstp | rstp | stp |
mst instance ***<0-4000>*** **| name** ***<WORD>*** **revision** ***<0-65535>*** |
port-fast disable | edge | network |
priority ***<0-61440>*** |
root |
transmit hold-count ***<1-10>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-st-bridge)#
{**aging -time** ***<10-1000000>*** |	Configure the timeout period in seconds, for aging out dynamically learned forwarding information. Values are 1 to 1000000 in seconds Default is 300 seconds
forward-time ***<4-30>*** |	Configure the forward delay timer. The forward delay timer is the time interval spent in the listening and learning state. Values are 4 to 30 seconds Default is 15 seconds.
hello-timer ***<1-10>*** |	Configure the hello timer. The hello timer is the time between each bridge protocol data unit (BPDU) sent on a port. Values are 1 to 10 seconds Default is 2 seconds.
loopguard default |	Configure the Spanning Tree Protocol (STP) loop guard feature which provides additional protection against Layer 2 forwarding loops (STP loops).

	An STP loop is created when an STP blocking port in a redundant topology erroneously transitions to the forwarding state. Default is Disabled
max-age ***<10-1000000>*** **|**	Configure the max age timer to control the maximum length of time that passes before a bridge port saves its configuration BPDU information. Value are 10 to 100000 seconds Default is 20 seconds
max-hops ***<6-40>*** **|**	Configure the number of possible hops in the region before a bridge protocol data unit (BPDU) is discarded. Value are 6 to 40 Default is 20
mode mstp | rstp | stp |	Set the spanning tree mode. • Spanning Tree Protocol (STP) • Rapid Spanning Tree Protocol (RSTP) • Multiple Spanning Tree Protocol (MSTP) Default is RSTP
mst instance ***<0-4000>*** **| name** ***<WORD>*** **revision** ***<0-65535>*** **|**	Configure MST instances for the region. Each region can have multiple instances. Map VLANs to an MST instance (0-63). Instance 0 cannot be deleted and is used to map/unmapped VLANs to instance 0. Each instance has a VLAN or range of VLANs which is associated with it. Name—define the name of the region. Revision—This setting must be the same for all MSTP switches in the same MST region
port-fast disable | edge | network |	A spanning tree normal port is one that functions in the default manner for spanning tree. Under normal circumstances it will transition from the Listening, Learning, Forwarding stages based on the default timers. PortFast causes a port to enter the spanning tree forwarding state immediately, bypassing the listening and learning states.

	STP enabled ports that are connected to devices such as a single switch, workstation, or a server can access the network only after passing all these STP states. Some applications need to connect to the network immediately, else they will timeout. **Disable**—go through normal learning/ forwarding and blocking states. **Network**—Interface goes into forward state immediately. Portfast network protects against loops by detecting unidirectional links in the STP topology. **Edge**—is used to configure a port on which an end device is connected such as a PC. All ports directly connected to end devices cannot create bridging loops in the network. Therefore, the edge port directly transitions to the forwarding state, and skips the listening and learning stages. However, the specific command configures a port such that if it receives a BPDU, it immediately loses its edge port status and becomes a normal spanning-tree port.
priority ***<0-61440>*** |	Every router participating in a Spanning Tree Protocol (STP) network is assigned with a numerical number called a bridge priority value. Priority values decide who will be elected as root. You can set the bridge priority in increments of 4096 only. When you set the priority, valid values are 0, 4096, 8192, 12288, 16384, 20480, 24576, 28672, 32768, 36864, 40960, 45056, 49152, 53248, 57344, and 61440. You set the priority value argument to 0 to make the router root. Default is 32768
root |	Configure the root bridge.The root bridge is the bridge with the smallest (lowest) bridge ID.
transmit hold-count ***<1-10>***}	Controls the number of BPDUs sent before pausing for 1 second. Range is 1 to 10 seconds Default is 6 seconds
Command Modes	Perle(config-st-bridge)#

Usage Guidelines

Configures the parameters for Spanning Tree Protocol.

Examples

This example sets mode to MSTP.

Perle(config-st-bridge)#spanning-tree mode mstp

Related Commands

standby

(config-st-bridge)#

cellular

cellular

{**profile** ***<WORD>*** **[5gband <auto> | 1 | 2 |3 | 5 | 28 | 41 | 48 | 66 | 71 |77 |78 | carrier-aggregation on | off | authentication chap | pap | none | [band 1 | 2 | 3 | 4 | 5 | 7 | 8 | 9 | 12 | 13 | 14 | 18 | 19 | 20 | 26 | 28 | 29 | 30 | 32 | 41 | 42 | 43 | 46 | 48 | 66 | auto] | data-apn access-point-name** ***<WORD>*** **| cid** ***<1-16>*** **| pdp-type ipv4 | ipv4ipv6 | ipv6 | data-limit action-on limit disable-lte | none| alert-on-limit off|on | alert-percentage** ***<0-99>*** **| bill-day** ***<1-31>*** **| mb-size** ***<0-100000>*** **| firmware att | generic | other | sim-select | verizon | [password 0** ***<LINE>*** **| 7** ***<LINE>*** **|** ***<LINE>*** **| 0** ***<LINE>*** **| 7** ***<LINE>*** **|** ***<LINE>*** **] | roaming on | off | sim-slot 1 | 2 | technology 5g |auto | lte | umts | username** ***<WORD>*** **|**

sms authentication method both | none | password | phone | user ***<WORD>*** **enable | password 0** ***<WORD>*** **| 7** ***<WORD>*** **|** ***<WORD>*** **| phone** ***<LINE>*** **| privilege admin | none | restricted**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	cellular
{**profile** ***<WORD>*** **[5gband <auto> | 1 | 2 | 3 | 5 | 28 | 41 | 48 | 66 | 71 |77 |78] | authentication chap | pap | none | [band 1 | 2 | 3 | 4 | 5 | 7 | 8 | 9 | 12 | 13 | 14 | 18 | 19 | 20 | 26 | 28 | 29 | 30 | 32 | 41 | 42 | 43 | 46 | 48 | 66 | auto] |data-apn access-point-name** ***<WORD>*** **| cid** ***<1-16>*** **| pdp-type ipv4 | ipv4ipv6 | ipv6 | data-limit action-on limit disable-lte | none | alert-on-limit off |on | alert-percentage** ***<0-99>*** **| bill-day** ***<1-31>*** **| mb-size** ***<0-100000>*** **| firmware att |**	Configure cellular profile parameters. Some bands may not be available on all models.

generic | other | sim-select | verizon | [password 0 *<LINE>* | 7 *<LINE>* | *<LINE>* | 0 *<LINE>* | 7 *<LINE>* | *<LINE>*] | roaming on | off | sim-slot 1 | 2 | technology 5g | auto | lte | umts | username *<WORD>* |	Depending on the product model you may have either 1 or 2 SIM slots.
sms authentication method both | none | password | phone | user *<WORD>* enable | password 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | phone *<LINE>* | privilege admin | none | restricted}	Configure SMS authentication parameters.
Command Default	SMS authentication default method is both.
Command Modes	Perle(config)#cellular

Usage Guidelines

Use this command to configure cellular profiles.

Examples

This example sets up a cellular connection using a profile test to browse the Internet.

```
Perle(config)#cellular profile test data-apn access-point-name ssid90 cid 10
```

Related Commands

(config-st-bridge)#

show bridge

(config-st-bridge-mst-instance)#

{**priority** ***0-61440>*** **|**

vlan ***<1-4000>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-st-bridge-mst-instance)#**
{**priority** ***0-61440>*** **|**	Every router participating in a Spanning Tree Protocol (STP) network is assigned with a numerical number called a bridge priority value.

{**priority** *0-61440>* |	Priority values decide who will be elected as root. You can set the bridge priority in increments of 4096 only. When you set the priority, valid values are 0, 4096, 8192, 12288, 16384, 20480, 24576, 28672, 32768, 36864, 40960, 45056, 49152, 53248, 57344, and 61440. You set the priority value argument to 0 to make the router. Default is 32768
vlan *<1-4000>*}	Configure the range of VLANs to add this instance mapping
Command Modes	Perle(config-st-bridge-mst)#

Usage Guidelines

Configures the priority parameters for Multiple Spanning Tree Protocol (MST).

Examples

This example sets the bridge priority to 28672.

Perle(config-st-bridge-mst)#priority 28672

Related Commands

standby

(config-st-bridge)#

(config-if-ethernet)#

class-map

class-map {*<1-4094>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**class-map**
{*<1-4094>*}	Configure a class-map number. Priority queues can only use class 1–7.
Command Modes	Perle(config)#class-map

Usage Guidelines

Use this command to classify inbound network traffic destined to, or passing through, the router based on a series of flow match criteria.The class map classifies network traffic based on various match criteria configured within a class map. In other words, it defines traffic classes. A class map can reference an ACL to be used as the criteria or specific criteria is applied to the class map. Class maps in turn are referenced by policy maps.

Examples

This example creates class map 1.

Perle(config)#class-map 1

Related Commands

policy-map

(config-cmap)#

{**description** ***<LINE>*** |
match-name ***<NAME>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-cmap)#**
{**description** ***<LINE>*** |	Configure a class-map match-name description.
match-name ***<NAME>***}	Configure a name for this classification.
Command Modes	Perle(config-cmap)#

Usage Guidelines

Use this command to create a classification. Classifications are separation of packets into traffic classes. Configure the device to take a specific action on the specified classified traffic, such as policing or marking down, or other actions.

Examples

In this example the name specified for this classification is match-icmp.

Perle(config-cmap)#match-name match-icmp

Related Commands

(config-cmap-match)#

policy-map

(config-cmap-match)#

match ethernet destination ***<H.H.H>*** **source type | type** ***<0-65535>*** |
interface [bvi ***<1-9999>*****] | [cellular** ***<0-0>*****] | [dialer** ***<0-15>*****] | [dot11radio** ***<0-4>*****] | [ethernet** ***<1-5>*** **] | [openvpn-tunnel** ***<0-999>*****] | [tunnel** ***<0-999>*****]** |
ip [destination address ***<A.B.C.D>*** ***<A.B.C.D>*** **| port** ***<0-65535>*****] | [dscp** ***<0-63>*** **| af11 | af12 | af13 | af21 | af22 | af23 | 31 | af32 | af33 | af41 | af42 | af43 |cs1 | cs2 | cs3 | cs4 | cs5 | cs6 | cs7 | default | ef] | [max-length** ***<0-65535>*****] |[protocol** ***<0-255>*** **| ah | dccp | dsr | egp | eigrp | encap | esp |etherip | ggp | gre | hmp | icmp | odpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipv6-icmp | ipv6-nonxt | opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | osfo | pim | rdp | roch | rsvp | sctp | sdrp | shim6 | skip |**

tcp | udp | udplite | vrrp | xns-idp] | [source address <*A,B.C.D*> <*A,B.C.D*>] | [port <*1-65535*>] | [tcp-flags ack | syn] |
ipv6 [destination <*X:X:X:X::X*>/<*0-128*> | port <*0-65535*>] | [dscp <*0-63*> | af11 | af12 | af13 | af21 | af22 | af23 | 31 | af32 | af33 | af41 | af42 | af43 |cs1 | cs2 | cs3 | cs4 | cs5 | cs6 | cs7 | default | ef] | [max-length <*0-65535*>*]* | [protocol <*0-255*> | ah | dccp | dsr | egp | eigrp | encap | esp |etherip | ggp | gre | hmp | icmp | odpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipv6-icmp | ipv6-nonxt | opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | osfo | pim | rdp | roch | rsvp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp] | [source address <*X:X:X:X::X/*<*0-128*>] | [port <*1-65535*>*]* | [tcp-flags ack | syn] |
mark <*1-214748748364*> |
vlan <*1-4000*>}
Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-cmap-match)#
{**description <*LINE*> |**	Description of class-map match-name.
match ethernet destination <*H.H.H*> source type | type <*0-65535*> |	Match Ethernet header.
interface [bvi <*1-9999*>] | [cellular <*0-0*>] | [dialer <*0-15*>] | [dot11radio <*0-4*>] | [ethernet <*1-5*> | [openvpn-tunnel <*0-999*>] | [tunnel <*0-999*>] |	Match interface.
ip [destination address <*A.B.C.D*> <*A.B.C.D*> | port <*0-65535*>] | [dscp <*0-63*> | af11 | af12 | af13 | af21 | af22 | af23 | 31 | af32 | af33 | af41 | af42 | af43 |cs1 | cs2 | cs3 | cs4 | cs5 | cs6 | cs7 | default | ef] | [max-length <*0-65535*>] | [protocol <*0-255*> | ah | dccp | dsr | egp | eigrp | encap | esp |etherip | ggp | gre | hmp | icmp | odpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipv6-icmp | ipv6-nonxt | opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | osfo | pim |	Match IPv4 protocol header.

rdp | roch | rsvp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp] | [source address *<A,B.C.D> <A,B.C.D>*] | [port *<1-65535>*] | [tcp-flags ack | syn] |	
ipv6 [destination *<X:X:X:X::X>/<0-128>* | port *<0-65535>*] | [dscp *<0-63>* | af11 | af12 | af13 | af21 | af22 | af23 | 31 | af32 | af33 | af41 | af42 | af43 |cs1 | cs2 | cs3 | cs4 | cs5 | cs6 | cs7 | default | ef] | [max-length *<0-65535>]* | [protocol *<0-255>* | ah | dccp | dsr | egp | eigrp | encap | esp |etherip | ggp | gre | hmp | icmp | odpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipv6-icmp | ipv6-nonxt | opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | osfo | pim | rdp | roch | rsvp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp] | [source address *<X:X:X:X::X/<0-128>*] | [port *<1-65535>]* | [tcp-flags ack | syn] | udplite | vrrp | xns-idp | source address *<X:X:X:X::X/<0-128>* | port *<1-65535>* | tcp-flags ack | syn |	Match IPv6 protocol header.
mark *<1-214748748364>* |	Match on mark applied by policing routing.
vlan *<1-4000>*}	Match on VLAN ID

Command Modes	Perle(config-cmap-match)#

Usage Guidelines

Use the match command to configure "rules" or matches to apply to the class-map. If the packet matches any of the criteria configured for this class map, then this class map is applied to the packet.

Examples

This example I have specified the name bridge-50-match and matched on ip source address of 172.16.88.88.

```
Perle(config-cmap)#match-name bridge50-map
Perle(config-cmap-match))#match ip source address 172.16.88.88 icmp
```

Related Commands

(config-cmap)#

policy-map

clock

clock

{**summer-time** *<WORD >* **date** *<1-31> <MONTH > <hh:mm> <1-31> <MONTH > < hh:mm >* [*<1-1440-in-minutes>*] | [*recurring* [*<1-4 >*] [*<FIRST >*]] [*<LAST>*] |
timezone *<WORD> <-23 - 23>* | [*<0-59>*]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	clock
{**summer-time** *<WORD >* **date** *<1-31> <MONTH > <hh:mm> <1-31> <MONTH > < hh:mm >* [*<1-1440-in-minutes>*] | [*recurring <1-4 >*] [*<FIRST >*] [*<LAST>*]	Configure the name of the summer time zone followed by start/end dates. **Configure start time:** • numeric value for the day of the month to start summer timezone 1–31 • numeric value for the day of the month to start summer timezone 1–31 • name of the month to start January, February, March, April, May, June, July, August, September, October, November, December • time to start in hours (24 hour clock) and minutes **Configure end time:** • numeric value for the day of the month to end summer timezone 1–31 • name of the month to end (January, February, March, April, May, June, July, August, September, October, November, December)
	• time to end in hours (24 hour clock) offset in minutes 1–1440
timezone *<WORD> <-23 - 23>* | [*<0-59>*]}	Configure the timezone as hours/minutes offset from Universal Time Clock (UTC).

Command Modes	Perle(config)#clock

Usage Guidelines

Use this command to configure the clock.

Examples

This example configures the clock 6 hours off from UTC.

Perle(config)#clock timezone ont-time-zone -6

Related Commands

show clock

container (OCI)

container

{**name** ***<LINE >*** |
network ***<WORD>*** |
registry - | [- | hostname:port username ***<WORD>*** **secret** ***<WORD>*** |}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	container
{**name** ***<LINE >*** |	Create container with this name.
network ***<WORD>***}	Create container with this network name.
registry - | hostname:port username ***<WORD>*** **secret** ***<WORD>***|}	Registry • - (use default docker registry) • - hostname:port Username–specify the user Secret–specify a password for this user
Command Modes	Perle(config)#container

Usage Guidelines

Use this command to configure container parameters.

Examples

This example creates container network new-container.

Perle(config)#container network new-container <cr>

Perle(config-container-net)#

This example show you how to supply registry credentials to add images from repositories that require a CA certificate, cert, and key file.

First add the host to the router host table
Perle(config)#ip host lab-debian 172.16.48.20

Second upload the registry keys that are need for this host.
Perle(config)#crypto pki import container-registry lab-debian:443 ca url http://lab-debian/certs/ca.crt

Perle(config)#crypto pki import container-registry lab-debian:443 cert url http://lab-debian/certs/myrouter.cert

Perle(config)#crypto pki import container-registry lab-debian:443 key url http://lab-debian/certs/myrouter.key

Perle(config)#container registry lab-debian:443 username admin secret perle1

Perle#container image add lab-debian:443/myimage

Related Commands

container (OCI)

(config-container)#

show container (OCI)

crypto

(config-container)#

{**arguments** ***<1-40> <LINE>***|
clean-restart |
description ***<LINE>*** |
disable |
environment ***<WORD> <LINE>*** |
image ***<WORD> <WORD>*** **[autoadd]** |
import-changes |
log max-size ***<100-10000>*** | **no-compress** |
memory ***<1-1024>*** |
network ***<WORD>*** **ip address** ***<A.B.C.D>*** | **ipv6 address** ***<X:X:X:X::X>*** |
restart-policy always | no | on-failure [*<0-9999>*]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description (config-container)#

{**arguments** ***<LINE> <1-40> <LINE>*** |	**Line**–arguments to be supplied to the image when the container runs, redirect the output to your CLI screen. **<1-40>**–order of the arguments passed to the container when it runs. Best practice is to add arguments in increments of 10, such as 10, 20, 30, so that you are able to insert arguments between numbers. **<LINE>**–arguments to be supplied to the container when it runs. **Note: your CLI prompt will not return until the program has finished running.**
clean-restart |	On bootup or restart container, container will be removed first before restarting.
description ***<LINE>*** |	**Description**–container description. Max is 32 characters.
disable	**Disable**–disable container instance.
environment ***<WORD> <LINE>*** |	**WORD**–add a custom environment variable. **LINE**–set environment variable.
image ***<WORD>*** **image** ***<WORD> <WORD>*** **[autoadd]** ||	**WORD**–image name. **WORD**–container image tag or digest **Autoadd**–automatically download image if required.
import-changes |	Run the image modified with the supplied file from an earlier export-changes.
log max-size ***<100-10000>*** **| no-compress** |	Specify the size of the log file. Maximum size of the log file is in KiB. Turn compress of the rotating log files off.
memory ***<1-1024>*** |	**Memory**–container memory in megabytes (MB).
network ***<WORD>*** **ip address** ***<A.B.C.D>*** **| ipv6 address** ***<X:X:X:X::X>*** |	**WORD**–creates a container with the given name **ip/ipv6**–assigns static ip or ipv6 address.

restart-policy always | no | on-failure [*<0-9999>*]}	**Restart–policy** **Always**–restart containers when they exit, regardless of status exit code, retrying indefinitely. **no**–do not restart containers on exit. **on-failure**–restart containers when they exit with a non-zero exit code, retrying <0-9999> times. Default is: on failure 100 retries, 0 for infinite.
Command Modes	(config-container)#

Usage Guidelines

Use this command to configure container parameters.

Examples

This example creates a container called test-container1 with a static IP address of 172.16.88.88.

```
(config-container)#network-container test ip address 172.16.88.88 <cr>
```

This example adds argument ps -aef to container test. On connect to the container this argument will be run on the container and output will be redirected to your CLI prompt.

```
(config)#container name test <cr>
(config-container)#image alpine <cr>
(config-container)#argument 1 ps <cr>
(config-container)#argument 2 -eaf <cr>
(config-container)#no disable <cr>

#show container test log <cr>
#   PID USER  TIME .....COMMAND
    1 root     0:00     ps-aef
```

Related Commands

(config-container)#

(config-container-net)#

container (OCI)

(config-container-net)#

{**description *<LINE>* | network-interface bvi *<1-9999>* dhcp | dhcpv6**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-container-net)#**
{**description *<LINE>* | network-interface bvi *<1-9999>* dhcp | dhcpv6**}	**Description**–container network description. **Network-interface**–select bridge interface 1-9999.
Command Modes	(config-container-net)#

Usage Guidelines

Use this command to configure container network parameters. Any changes to this setting requires a reboot to take effect.

Examples

This example creates BVI (Bridge-Group Virtual Interface) 10.

(config-container-net)#network-interface bvi 10 <cr>

Related Commands

(config-container)#

container (OCI)

container-management (OCI)

container-management

{**enable**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	container-management
{**enable**}	Starts container management services.
Command Modes	Perle(config)#container-management

Usage Guidelines

Use this command to enable container management.

Examples

This example enables container management process.

Perle(config)#container-management

Related Commands

(config-container)#

(config-container-net)#

container (OCI)

controller

controller

{**cellular** *<0-0>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	controller
{**cellular** *<0-0>*}	Enter sub-menu cellular mode.
Command Modes	Perle(config)#controller

Usage Guidelines

Use this command to enter sub-menu cellular mode.

Examples

This example enter sub-menu cellular mode.ass map 1.

Perle(config)#controller cellular 0

Related Commands

show bridge

(config-controller)#

(config-controller)#

{gnss antenna dedicated active | diversity | enable | receiver-disabled |
lte alternative-profile *<WORD>* | diversity | enable | [failover | connect-retires *<1-100>* | enable | revert-timer *<1-1500>* signal-loss-timer *<1-60>* | signal threshold *<-150-0>*] | primary-profile *<WORD>* | radio-disable | power-down}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-controller)#
{gnss antenna dedicated active | diversity | enable | receiver-disabled |	Set to enable. • the GNSS feature • set antenna to active • set receiver -disable to reset the modem. Your LTE connection is lost for 40 seconds, then recovers.
lte alternative-profile *<WORD>* | diversity | enable | [failover | connect-retires *<1-100>* | enable | revert-timer *<1-1500>* signal-loss-timer *<1-60>* | signal threshold *<-150-0>*] | primary-profile *<WORD>* | radio-disable |	Enable, configure and disable features on the LTE (cellular) interface.
power-down}	Power down cellular module
Command Modes	Perle(config-controller)#

Usage Guidelines

Use this command to configure LTE and GNSS parameters found under the config-controller sub-menu.

Examples

In this example we are going to activate the use of the diversity antenna.

Perle(config-controller)#lte diversity

Related Commands

(config-st-bridge-mst-instance)#

(config-cmap-match)#

policy-map

crypto

crypto

{**ipsec client** *<WORD>* | **enable** | [**esp-group** *<WORD>*] | [**ike-group** *<WORD>*] | [**import ipsec.conf terminal** | **flash:***filename*] |
ftp:*[[//username[:password]@location]/directory]/filename* |
http://*[[username:password]@][hostname* | *host-ip [directory] /filename* |
https://*[[username:password]@][hostname* | *host-ip [directory] /filename* |
scp:*[[username@location]/directory]/filename* |
sftp:*[[//username[:password]@location]/directory]/filename* |
tftp:*[[//location]/directory]/filename* |
l2tp |
nat-network *<A.B.C.D/N>* |
nat-transversal |

key [**export password-cryptkey terminal**] | [**rsa public** | **terminal 3des** *<LINE>* | **des** *<LINE>* | **flash:***filename*] | **ftp:***[[//username[:password]@location]/directory]/filename* | **http://***[[username:password]@][hostname* | *host-ip [directory] /filename* |
https://*[[username:password]@][hostname* | *host-ip [directory] /filename* |
scp:*[[username@location]/directory]/filename* | **sftp:***[[//username[:password]@location]/directory]/filename* | **tftp:***[[//location]/directory]/filename* |
generate [**password-cryptkey**] | **rsa modulus** *<1024-4096>* |

import [**client rsa pem** | **pkcs12 terminal password** *<LINE>* | **url**
flash:*filename* | **ftp:***[[//username[:password]@location]/directory]/filename* | **http://***[[username:password]@][hostname* | *host-ip [directory] /filename* |
https://*[[username:password]@][hostname* | *host-ip [directory] /filename* |
scp:*[[username@location]/directory]/filename* | **sftp:***[[//username[:password]@location]/directory]/filename* | **tftp:***[[//location]/directory]/filename*] | [**password-cryptkey terminal**]
ssh-host rsa terminal *<LINE>* | **url**
flash:*filename* | **ftp:***[[//username[:password]@location]/directory]/filename* |
http://*[[username:password]@][hostname* | *host-ip [directory] /filename* |
https://*[[username:password]@][hostname* | *host-ip [directory] /filename* |
scp:*[[username@location]/directory]/filename* |
ctory]/filename | **sftp:***[[//username[:password]@location]/directory]/filename* |
tftp:*[[//location]/directory]/filename*] |
[**zeroize password-cryptkey** | **rsa** |

openvpn connection <*WORD*> | enable | [generate secret <name>] | [import ca <*NAME*>] | [cert <*NAME*>] | dh <*WORD*> | key <*NAME*> | secret <*NAME*> | template <*NAME*>]

terminal | url flash:*filename* | ftp:*[[//username[:password]@location]/directory]/filename* | http://*[[username:password]@][hostname* | *host-ip [directory] /filename* |

https://*[[username:password]@][hostname* | *host-ip [directory] /filename* |

scp:*[[username@location]/directory]/filename* | sftp:*[[//username[:password]@location]/directory]/filename* | tftp:*[[//location]/directory]/filename*} |

zeroize ca <*NAME*> | cert <*NAME*> | key <*NAME*> |

pki import client | https pem | pkcs12} | {openvpn ca <*NAME*> | cert <*NAME*> | key <*NAME*>} | {server test pem | pkcs12} terminal | url flash:*filename* | ftp:*[[//username[:password]@location]/directory]/filename* | http://*[[username:password]@][hostname* | *host-ip [directory] /filename* |

https://*[[username:password]@][hostname* | *host-ip [directory] /filename* |

scp:*[[username@location]/directory]/filename* | sftp:*[[//username[:password]@location]/directory]/filename* | tftp:*[[//location]/directory]/filename* |

zeroize [container-registry <*WORD*> ca cert key | [https] | [openserver ca <*NAME*> | cert <*NAME*> | key <*NAME*>] | [server <*WORD*>] |

ssl algorithm encryption any | suite-b-tls | tls-1.2 | tls1.3}

Use the no form of this command to negate a command or set to defaults

Syntax Description **crypto**

{**[ipsec client** ***<WORD>*** **| enable | esp-group** ***<WORD>*** **| ike-group** ***<WORD>*** **| import ipsec.conf terminal | flash:*****filename*** **| ftp:*****[[// username[:password]@location]/directory]/filename*** **| http:**// ***[[username:password]@][hostn ame | host-ip [directory] / filename*** **|https:**// ***[[username:password]@][hostn ame | host-ip [directory] / filename*** **| scp:*****[[username@location]/ directory]/filename*** **| sftp:*****[[// username[:password]@location]/directory]/filename*** **| tftp:*****[[// location]/directory]/filename*** **|**	See ***(config-client)*** to configure parameters.
l2tp |	Enables or restarts IPsec.
nat-network ***<A>B>C>D/N>*** **|**	See ***(config-esp)#*** to configure parameters.
nat-transversal |	See ***(config-ike)#*** to configure parameters.
	Configure Specify where to import the ipcsec.conf file.
	See ***(config-12tp)*** to configure parameters.
	Configure a permitted IPsec Network Address Translation (NAT) network/ mask.
	Enables Network Address Translation (NAT) Transversal. NAT Transversal allows traffic to get to the specified destination when a device does not have a public IP address.
	This is usually the case if your ISP is doing NAT, or the external interface of your firewall is connected to a device that has NAT enabled.

key [export password-cryptkey terminal] | [rsa public | terminal 3des *<LINE>* | des *<LINE>* | flash:*filename*] | ftp:*[[// username[:password]@location]/directory]/filename* | http:// *[[username:password]@][hostn ame | host-ip [directory] / filename* | **https:**// ***[[username:password]@][hostn ame | host-ip [directory] / filename*** | **scp:*[[username@location]/ directory]/filename* | sftp:*[[// username[:password]@location]/directory]/filename* | tftp:*[[// location]/directory]/filename* | generate [password-cryptkey] | rsa modulus *<1024-4096>* | [import [client rsa pem | pkcs12 terminal password *<LINE>* | url flash:*filename* | ftp:*[[// username[:password]@location]/directory]/filename* | http:// *[[username:password]@][hostn ame | host-ip [directory] / filename*** | **https:**// ***[[username:password]@][hostn ame | host-ip [directory] / filename*** | **scp:*[[username@location]/ directory]/filename* | sftp:*[[// username[:password]@location]/directory]/filename* | tftp:*[[// location]/directory]/filename*] | [password-cryptkey terminal] ssh-host rsa terminal *<LINE>* | url flash:*filename* |**	Configure long term key operations.

ftp:*[[//*
username[:password]@location
]/directory]/filename | **http://**
[[username:password]@][hostn
ame | *host-ip [directory] /*
filename |

https://
[[username:password]@][hostn
ame | *host-ip [directory] /*
filename |
scp:*[[username@location]/*
directory]/filename |

ctory]/filename | **sftp:***[[//*
username[:password]@location
]/directory]/filename | **tftp:***[[//*
location]/directory]/filename] |

[zeroize password-cryptkey |
rsa

openvpn connection ***<WORD>*** **| enable | generate secret** ***<NAME>*** **| import ca** ***<NAME>*** **| cert** ***<NAME>*** **|** {**dh** ***<WORD>*** **| key** ***<NAME>*** **| secret** ***<NAME>*** **|template** ***<NAME>*****terminal | url flash:*****filename** **| ftp:*****[[// username[:password]@location]/directory]/filename*** **| http:**// ***[[username:password]@][hostn ame | host-ip [directory] / filename*** **|** **https:**// ***[[username:password]@][hostn ame | host-ip [directory] / filename*** **| scp:*****[[username@location]/ directory]/filename*** **| sftp:*****[[// username[:password]@location]/directory]/filename*** **|** **tftp:*****[[//location]/directory]/ filename***} **|**	See ***(config-connection)*** to configure parameters.
zeroize ca ***<NAME>*** **| cert** ***<NAME>*** **| key** ***<NAME>*** **|**	Configure public key components.
pki import client | https pem | pkcs12} | {openvpn ca ***<NAME>*** **| cert** ***<NAME>*** **| key** ***<NAME>*****} | {server test pem | pkcs12} terminal | url**	Configure local key or certificate filename.

flash:*filename* | **ftp:***[[// username[:password]@location]/directory]/filename* | **http:**// *[[username:password]@][hostn ame | host-ip [directory] / filename* | **https:**// *[[username:password]@][hostn ame | host-ip [directory] / filename* | **scp:***[[username@location]/ directory]/filename* | **sftp:***[[// username[:password]@location]/directory]/filename* | **tftp:***[[// location]/directory]/filename* | **zeroize [container-registry <WORD> ca cert key | [https] | [openvpn ca <NAME> | cert <NAME> | key <NAME>] | [server <WORD>]**	
ssl algorithm encryption any | suite-b-tls | tls-1.2 | tls1.3}	Configure the SSL encryption method.

Command Modes	Perle(config)#crypto

Usage Guidelines

Use this command to configure parameters for IPsec configuration, key, OpenVPN configuration, PKI, and SSL parameters.

Examples

This example exports the public key from the router to the terminal session.

```
Perle(config)# crypto key export rsa public terminal
ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAABAQDReknFjyYmPYATixxn1nGVe3xyncwk
hAbKO3JFUI5Vvnd50wT5gYNxd4vP4dJe4J5/mvzG7rcbZ4uCz/
dX8xMs18xUzpoqHbjOF5EUfBtPZzgI/IsDkwzfIaWj/
Qznau6TemWnR72RpzKaDRdFy0j4ghzvfUdXWz/EKPq/
5EJ97sdU97RzURfL8j4lwThanpLVi8kP8guNioYJdFgdrgcerKg6aUTehU7C2X9sai0
8e1WNcGA6Urmlzj4rtUsV0Enu+Tx47WM6kcPij423QlM0abnn4RWwRPnU4qINKTv
WR4gKZQUpYEFPvwtJgtpLGDOIYikMvZrc09X1D68Ttbx7
```

Related Commands

show crypto

(config-client)

{**authentication identify** *<WORD>* **[pre-shared-key** *<WORD>***]** | **[remote-identity** *<WORD>***]** | **[x509** *<LINE>* | **trustpoint** *<CA-FILE>***]** |
connection-type disable | **initiate** | **respond]** |
ike-group *<WORD>* |
local-address [*<A.B.C.D>* | *<X:X:X:X::X:X>* | **any]** |
tunnel *<1-429467295>* **[esp-group** *<WORD>***]** | **[local-address** *<A.B.C.D/N* | *X:X:X:X::X/N>***]** | **protocol** *<0-255>* | **[ah** | **all** | **ax.25** | **dccp** | **ddp** | **egp** | **eigrp** | **encap** | **exp** | **etherip** | **fc** | **ggp** | **gre** | **hip** | **hmp** | **hopopt** | **icmp** | **igp** | **ip** | **ipcomp** | **ipencap** | **ipip isis** | **iso--tp4** | **l2tp** | **manet** | **mobility-header** | **mpls-in-ip** | **ospf** | **pim** | **pup** | **rdp** | **rohc** | **rspf** | **rsvp** | **sctp** | **skip** | **st** | **tcp** | **tcp -udp** | **udp** | **udplite** | **vmtp** | **vrrp** | **wesp** | **xns-idp** |**xtp]** | | **[remote-address** *<A.B.C.D/N* | *X:X:X:X::X/N>***]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-client)
{**authentication identify** *<WORD>* **[pre-shared-key** *<WORD>***]**	**[remote-identity** *<WORD>***]**	**[x509** *<LINE>*	**trustpoint** *<CA-FILE>***]**		Configure the local authentication identity.
connection-type disable	**initiate**	**respond**		Sets the connection type: • initiate • respond • disable
ike-group *<WORD>*		Configure IPsec IKE configuration.
local-address [*<A.B.C.D>*	*<X:X:X:X::X:X>*	**any]**		Configure the local address interface.

tunnel ***<1-429467295>*** **[esp-group** ***<WORD>*****] | [local-address** ***<A.B.C.D/N | X:X:X:X::X/N>*****] | protocol** ***<0-255>*** **| [ah | all | ax.25 | dccp | ddp | egp | eigrp | encap | exp | etherip | fc | ggp | gre | hip | hmp | hopopt | icmp | igp | ip | ipcomp | ipencap | ipip isis | iso--tp4 | l2tp | manet | mobility-header | mpls-in-ip | ospf | pim | pup | rdp | rohc | rspf | rsvp | sctp | skip | st | tcp | tcp -udp | udp | udplite | vmtp | vrrp | wesp | xns-idp |xtp] | | [remote-address** ***<A.B.C.D/N | X:X:X:X::X/N>*****]**}	Configure the client tunnel parameters.
Command Modes	Perle(config-client)#

Usage Guidelines

Use this command to configure IPSEC parameters.

Examples

This example sets client connection to initiate.

```
Perle(config-client)#connection-type initiate
```

This example sets up the responder side of the connection.

```
Perle(config)#crypto ipsec client @myx509
Perle(config-client)#authentication x509 "C=CA, O=orgxdeb, CN=boxxdeb"
Perle(config-client)#authentication x509 trustpoint "CACert.pem"
Perle(config-client)# connection-type respond
Perle(config-client)# tunnel 0 local-address 192.168.51.111/32
Perle(config-client)# tunnel 0 remote-address 0.0.0.0/0crypto ipsec clinet @myx509
```

Related Commands

show crypto

(config-connection)

{**ca** ***<WORD>*** **|**

cert ***<NAME>*****|**

cipher aes-128-cbc | aes-128-gcm | aes-192-cbc | aes-192-gcm | aes-256-cbc | aes-256-gcm | bf-cbc | camellia-128-cbc | camellia-192-cbc | camellia-256-cbc | cast5-cbc | des-cbc | des-ede-cbc | des-ede3-cbc | des-cbc | rc2-40-cbc | rc2-64-cbc | rc2-cbc | seed-cbc |

client |

client-to-client |

comp-lzo [adaptive | no | yes |
dev *<0-999>* |
dh *<WORD>* |
ifconfig *<A.B.C.D> <WORD> <A.B.C.D><WORD>* |
keepalive *<1-65535> <1-65535>*|
key *<WORD>* |
lport *<1-65535>* |
persist-tun |
port *<1-65535>* |
pull |
remote [*<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X> <1-65535>***] | [tcp | udp]** |
remote-cert-tls client | server |
rport *<1-65535>* |
secret *<NAME>* |
server *<A.B.C.D> <A.B.C.D>* **[no pool]** |
server-bridge *<A.B.C.D> <A.B.C.D> <A.B.C.D> <A.B.C.D>* |
server-ipv6 *<X:X:X:X::X>* |
template *<WORD>* |
tls-auth |
tls-client |
tls-server |
user-pass *<WORD> <WORD>* **0 | 7** |
user-pass -verify |
verb *<0-11>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-connection)
{**ca** *<WORD>* |	Configure the PKI CA trustpoint name.
cert *<NAME>* |	Configure the PKI certificate name.
cipher aes-128-cbc | aes-128-gcm | aes-192-cbc | aes-192-gcm | aes-256-cbc | aes-256-gcm | bf-cbc | camellia-128-cbc | camellia-192-cbc | camellia-256-cbc | cast5-cbc | des-cbc | des-ede-cbc | des-ede3-cbc | des-cbc | rc2-40-cbc | rc2-64-cbc | rc2-cbc | seed-cbc |	Configure the cipher for this connection.
client |	Enables client mode if TCP mode is used with the remote command or if you receive the OpenVPN message "Options error: --proto tcp is ambiguous in this context. Please specify --proto tcp-server or --proto tcp-client

client-to-client |	Sets client to client mode for the connection. This lets connected clients see each other, not just the server.
comp-lzo [adaptive | no | yes] |	Configure compression. In cases where the OpenVPN server pushes the request "comp-lzo no" to connecting clients, the client side breaks with repeated "write to TUN/TAP : Invalid argument (code=22)" errors unless it too has already specified "comp-lzo no. If you are a client and are using `pull` to get settings from the server, the connection may fail with that same message. To overcome this issue `comp-lzo no` must be defined in your connection.
	Note: the "no comp-lzo" (the default) turns off the entire compression subsystem which is required for connections not using compression.
dev *<0-999>* |	Configure the OpenVPN interface number.
dh *<WORD>* |	Configure Diffie-Hellman parameters.
ifconfig *<A.B.C.D> <WORD> <A.B.C.D> <WORD>* |	Configure the local and the remote IP addresses for each side of the connection. Reverse the ip addresses when configuring "the other end".
keepalive *<1-65535> <1-65535>* |	Configure the keepalive interval (in seconds) and the keepalive timeout (in seconds).
key *<WORD>* |	Configure the PKI private key.
lport *<1-65535>* |	Configure the port on the local side. Default is 1194
persist-tun |	Keeps tun device between restarts.
port *<1-65535>* |	Configure the port on both sides of the connection.
pull |	Downloads the configuration from the server.
remote [*<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X> <1-65535>***] | [tcp | udp]** |	Configure the remote host for connection.

remote-cert-tls client | server |	Configure peer certificate checking as client or server. When this is used with a TLS connection, the peer's certificate credentials are validated using the CA certificate referred to by the "ca" command. This is recommended to mitigate man-in-the-middle attacks but can be left off if the signing CA certificate is not currently available.
rport *<1-65535>* |	Configure the port on the remote side.
secret *<NAME>* |	Configure the Pre-Shared secret key.
server *<A.B.C.D> <A.B.C.D>* **[no pool]** |	Configure OpenVPN IPv4 server parameters.
server-bridge *<A.B.C.D> <A.B.C.D> <A.B.C.D> <A.B.C.D>* |	Configure the gateway and IP pool addressing.
server-ipv6 *<X:X:X:X::X>* |	Configure OpenVPN IPv6 server parameters.
template *<WORD>* |	Configure the connection template.
tls-auth |	Sets a PSK to use for TLS authentication. The PSK previously defined via crypto openvpn generate secret name will be used. This can be used to add authentication to the TLS control channel to help reduce the chances of a DoS attack.
tls-client |	Sets the router to act as a TLS client.
tls-server |	Sets the router to act as a TLS server.
user-pass *<WORD> <WORD>* **0 | 7** |	Configure the remote user name and password.
user-pass -verify |	Enables or disables server username and password verification.
verb *<0-11>*}	Configure the verbosity level. (debug)
Command Modes	Perle(config-connection)#

Usage Guidelines

Use this command to configure parameters for OpenVPN connections.

Examples

Configure OpenVPN remote port to 1050.

Perle(config-connection)#rport 1050

Related Commands

show crypto

(config-esp)#

{**compression** |
lifetime ***<30-86400>*** |
mode transport | **tunnel** |
pfs |
proposal ***<1-65535>*** **[encryption 3des | aes128 | aes128gcm182 | aes256 | aes256gcm128 | chacha20poly1305] | [hash md5 | sha1 | sha256 | sha384 | sha512]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-esp) #**
{**compression** |	Configure compression for the IPsec connection.
lifetime ***<30-86400>*** |	Configure tunnel expire timer after no activity. Range is 30 to 86400 Default is 1800 seconds
mode transport | **tunnel** |	Configure the tunnel mode. **Transport mode**—payload encrypted; headers clear **Transport mode**—both headers and payload encrypted.
pfs |	Configure PFS On to improve security by forcing a new key exchange for each new session. Both sides of the VPN tunnel must be able to support this option. Enabling PFS by renewing keys more often has performance impact but provides further security.
proposal ***<1-65535>*** **[encryption 3des | aes128 | aes128gcm182 | aes256 | aes256gcm128 | ch**}	Configure the IKE/ESP proposal.
Command Modes	Perle(config-esp)#

Usage Guidelines

Use this command to configure IPsec parameters.

Examples

Configure esp group mode to transport.

Perle(config-esp)# mode transport

Related Commands

show crypto

(config-ike)#

{**aggressive-mode** |

dpd action clear | hold | restart | interval *<2-86400>* | **timeout** *<10-86400>*|

ike-version ike | ikev1 | ikev2 |

lifetime *<30-86400>* |

proposal [dh-group 2 | 5 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26] | [encryption 3des | aes128 | aes128gcm128 | aes256 | aes256gcm256 | chacha20poly1305] | [hash md5 | sha1 | sha256 | sha384 | sha512]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-ike) #
{**aggressive-mode** |	Enables or disables aggressive mode. Aggressive mode uses fewer packet exchanges, therefore it is faster then main mode. However, aggressive mode does not give identity protection of the two IKE peers, unless digital certificates are used.
	This means VPN peers exchange their identities without encryption (clear text). You must use aggressive mode if one or both peers have dynamic external IP addresses or if you use Network Address Translation Traversal (NAT-T) Default is Off

dpd action clear | hold | restart | interval *<2-86400>* | timeout *<10-86400>* |	Configure Dead Peer Detection (DPD). This is a method of detecting a dead Internet Key Exchange (IKE) peer. This method uses IPsec traffic patterns to minimize the number of messages required to confirm the availability of a peer. DPD is used to reclaim the lost resources in case a peer is found dead. • **Clear**—terminate the VPN connection over the detection timeout. You must manually re-initiate the VPN connection. We recommend that you use Clear when the remote peer uses dynamic IP address. • **Hold**—traffic from your local network to the remote network can trigger the routerto re-initiate the VPN connection over the detection timeout. We recommend that you use Hold when the remote peer uses a static IP address • **Restart**—re-initiate the VPN connection for three times over the detection timeout. Default Action is Hold Interval is 30 seconds Timeout is 120 seconds
ike-version ike | ikev1 | ikev2 |	Configure the IKE version. IKE uses IKEv2 but switches to IKEv1 depending on the peer. Default is IKEv2
lifetime *<30-86400>* |	Configure the connection keep alive timer. Range is 30 to 86400 Default is 3600 seconds
proposal [dh-group 2 | 5 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26] | [encryption 3des | aes128 | aes128gcm128 | aes256 | aes256gcm256 |	Configure the IKE/ESP proposal. Dh-default is 2 Encryption default is aes256 Hash default is SHA1

Command Modes	Perle(config-ike)#

Usage Guidelines

Use this command to configure IKE parameters.

Examples

Configures dead peer detection to restart.

```
Perle(config-ike)# dpd action restart
```

Related Commands

show crypto

(config-l2tp)

{**client-ip-pool** *<A.B.C.D> <A.B.C.D>* |
dns-server *<1-2> <A.B.C.D>* |
outside-address *<A.B.C.D>* |
pre-shared-key *<WORD>* |
username *<WORD>* **password** *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-l2tp)
{**client-ip-pool** *<A.B.C.D> <A.B.C.D>* |	Configure L2TP client IP pool addresses to be used by the clients.
dns-server *<1-2> <A.B.C.D>* |	Configure L2TP DNS servers.
outside-address *<A.B.C.D>* |	Configure the L2TP server remote address.
pre-shared-key *<WORD>* |	Configure the given pre-shared secret.
username *<WORD>* **password** *<WORD>*}	Configure L2TP user name and password for this connection.
Command Modes	Perle(config-l2tp)#

Usage Guidelines

Use this command to configure L2TP connection parameters.

Examples

Configure user name and password for L2TP connection.

```
Perle(config-l2tp)#username lyn password test
```

Related Commands

show crypto

dot11

dot11

{**ssid** *<LINE>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	dot11

{**ssid** ***<LINE>***}	Configure wireless profile name. (Radio service ID)

Command Modes	Perle(config)#dot11

Usage Guidelines

Use this command to configure a SSID name for a wireless channel profile.

Examples

This example configures the SSID name to Testfloor1.

Perle(config)#dot11 ssid testfloor1

Related Commands

show dot11

(config-ssid)#

{**authentication key-management wpa version 1 | 2 | both | open eap** ***<WORD>*** **|**
client-isolation |
encryption key size 108bit | 128bit | 40bit | 0 ***<hex-string>*** **| 7** ***<WORD>*** **|** ***<hex-string>*** **| mode cipher ccmp | tkip |**
guest-mode |
max-associations ***<1-2007>*** **|**
mgmt-frame-protection disable | mandatory | optional |
wpa-psk ascii 0 ***<LINE>*** **| 7** ***<WORD>*** **|** ***<LINE>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-ssid)#**
{**authentication key-management wpa version 1 | 2 | both | open eap** ***<WORD>*** **|**	Configure SSID parameters.
client-isolation |	Configure this option to prevent low level bridging of frames between associated clients.
encryption key size 108bit | 128bit | 40bit | 0 ***<hex-string>*** **| 7** ***<WORD>*** **|** ***<hex-string>*** **| mode cipher ccmp | tkip |**	Configure dot11 encryption parameters.
guest-mode |	Configure guest mode.
max-associations ***<1-2007>*** **|**	Configure the number of clients connecting at the same time to this SSID.

mgmt-frame-protection disable | mandatory | optional |	Configure Management Frame Protection (MFP). **Disabled**—no MFP negotiated **Mandatory**—clients must support MFP **Optional**—clients are allowed to associate only if MFP is negotiated (that is, if WPA2 is configured on the router and the client supports CCXv5 MFP and is also configured for WPA2)
wpa-psk ascii 0 *<LINE>* | 7 *<WORD>* | *<LINE>*}	Configure the wireless protected access pre-shared key.
Command Modes	Perle(config-ssid)#

Usage Guidelines

Use this command to configure parameters for IEE802.11 WLAN.

Examples

Configure the authentication method to allow WPA clients,

Perle(config-ssid)# authentication key-management wpa version both

Related Commands

dot1x

show dot11

dot1x

dot1x

{**credential *<WORD>*** |
logging |
system-auth-control |
test timeout *<1-65535>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	dot1x
{**credential *<WORD>*** |	Configure a dot1x credential profile.
logging |	Logs dot1x messages
system-auth-control |	Enables dot1x system-auth-control fort 802.1x access control on any port on the router. Set the port control command on each specific port you want 802.1x access control.
test timeout *<1-65535>*}	Use the readiness check before 802.1x is enabled on the router. Configure the EAPOL device timeout for the specified time frame.

Command Modes	Perle(config)#dot1x

Usage Guidelines

Use this feature to determine if connected devices are 802.1x-capable.

Examples:

This example creates a credential profile testcrd, Enable dotx1 authentication on Ethernet interfaces for multihost.

Note: You must enable system -auth-control if you want to authenticate dot1x devices.

```
Perle(config)#dot1x credential testcred
Perle(config)#interface ethernet 1
Perle(config-if)#authentication mult-auth
```

Related Commands

(config-dot1x-creden)

show eee

(config-dot1x-creden)

{**password 0** *<LINE>* | **7** *<LINE>* | *<LINE>* |
username *<name>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-dot1x-creden)
{**password** *< 0 > <LINE>* | *<7> <LINE>* |	Configure a password. 0–specifies that an unencrypted password follows. 7–specifies that an hidden password follows.
username *<WORD>*}	Configure a user name.
Command Modes	Perle(config-dot1x-creden)#

Usage Guidelines

Use this command to configure dot1x credentials.

Examples

This example configures the password "testing" to an encrypted password.

```
Perle(config)#dot1x credential testing
Perle(config-dot1x-creden)# password 7 DB0UeI1lynwOKW/j1
```

Related Commands

show eee

eap

eap

{**profile** ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	eap
{**profile** ***<WORD>***}	Configure EAP profiles.
Command Modes	Perle(config)#eap

Usage Guidelines

Use this command to create EAP profiles.

Related Commands

show eap

(config-eap-profile)

(config-eap-profile)

{**method gtc | leap | md5 | mschapv2 | peap | tls | [ttls chap | eap-gtc | eap-md5 | eap-mschapv2 | mschap | mschapv2 | pap]** |
pki-trustpoint ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-eap-profile)
{**method gtc | leap | md5 | mschapv2 | peap | tls | [ttls chap | eap-gtc | eap-md5 | eap-mschapv2 | mschap | mschapv2 | pap]** |	Configure the method of encapsulating sensitive information such as passwords to be authenticated from the router. The certificate authority you must trust. This is a self-signed certificate that you create here ***eap***
pki-trustpoint ***<WORD>***}	Configure the default pki trustpoint.
Command Modes	Perle(config-eap-profiles)#

Usage Guidelines

Use this command to configure parameters for EAP profiles.

EAP defines the transport and usage of identity credentials. EAP encapsulates the user names, passwords, certificates, and tokens for client authentication.

A trustpoint is a certificate authority you trust. Your router automatically trusts any other certificates signed with that trusted certificate

Create an eap profile before setting these parameters.

Examples

This example sets the method to gtc.

Perle(config-eap-profiles)#method gtc

Related Commands

show eap

email

email

{**enabled** |

encryption none | ssl | tls |

from *<WORD>* |

recipient *<WORD>* | **enable notifications-subject** *<LINE>* | **notifications alarms** | **authentication** | **bgp** | **bridge** | **cellular-gnss** | **cellular-lte** | **dot11** | **entity** | **envmon** | **interface-ip** | **ipsec** | **lldp** | **network-watchdog** | **openvpn** | **osfp** | **smnp** | **software-update** |

smtp-server *<WORD>* | *<A.B.C.D>* | *<X:X:X:X::X:X>* |

username *<WORD>* | **password 0** *<LINE>* | **7** *<WORD>* | *<LINE>* |

validate-certificate}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	email
{**enabled** |	Enables the email feature.
encryption none | ssl | tls |	Configure encryption. • none • ssl • tls
from *<WORD>* |	Configure from parameter. Format is user@company.com

recipient ***<WORD>*** **| enable notifications-subject** ***<LINE>*** **| notifications alarms | authentication | bgp | bridge | cellular-gnss | cellular-lte | dot11 | entity | envmon | interface-ip | ipsec | lldp | network-watchdog | openvpn | ospf | smnp | software-update** |	Configure the recipient and receive notifications Format is: user@company.com Specify the email notifications. • alarms • authentication • bgp • bridge • cellular-gnss • dot11 • entity • envmon • interface-ip • ipsec • lldp • network-watchdog • openvpn • ospf • snmp • software-update
smtp-server ***<WORD>*** **|** ***<A.B.C.D>*** **|** ***<X:X:X:X::X:X>*** |	Configure the SMNP server for mail requests.
username ***<WORD>*** **| password 0** ***<LINE>*** **| 7** ***<WORD>*** **|** ***<LINE>*** |	Configure the username for server authentication.
validate-certificate}	Configure the validation email certificate.
Command Modes	Perle(config)#email

Usage Guidelines

Use this command to configure email notification parameters.

Examples

This example enables the email feature and configures the smnp server for email requests.

```
Perle(config)#email enabled
Perle(config)#email snmp-server 172.16.55.77
```

Related Commands

show email

enable

enable

{**secret 0** *<LINE>* | **5** *<LINE>* | *<LINE>*}

Use the no form of this command to negate enable secret.

Syntax Description	enable
{**secret 0** *<LINE>* | **5** *<LINE>* | *<LINE>*}	Configure the enable password. 0—Specifies an unencrypted password to follow 5—Specifies a encrypted password to follow LINE—the unencrypted (cleartext) secret
Command Modes	Perle(config)#enable

Usage Guidelines

Use this command to configure the password to be used to enable privilege mode.

Examples

This example configures a password for enable mode.

Perle(config)#enable secret testsecret

Related Commands

gnss

gnss

{**maxcon** *<1-64>* |
profile *<1-16>* |
sid *<WORD>* |
stream-output-rate *<1-10>* |
streams [client *<1-64>*] | [**server** *<1-64>*] | [**tty** *<1-1>*] | [**usb**] |
system galileo | glonass | gps] |
vid *<0-9999>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	gnss
{**maxcon** *<1-64>* |	Configure maximum connections. 1 to 64 Default is 10
profile *<1-16>* |	Configure profile number. 1 to 16 profiles

sid *<WORD>* |	Configure system ID. This parameter is only used in TAIP stream profiles.
stream-output-rate *<1-10>* |	Configure the streaming output rate. 1 to 10 in seconds Default is 1
streams [client *<1-64>***] | [server** *<1-64>***] | [tty** *<1-1>***] | [usb]** |	Configure the GNSS streams. **Client mode** 1 to 64 streams **Server mode** 1 to 64 streams **tty** *<1-1>* stream **usb**–send stream to usb
systemgalileo | glonass | gps |	Configure the GNSS system streaming.
vid *<0 -9999>*}	Configure the vehicle ID.

Command Modes	Perle#(config)#gnss

Usage Guidelines

Configure GNSS parameters.

Examples

This example configures the gnss profile number.

Perle(config)# gnss profile 10

Related Commands

(config-gnss-profile)#

(config-gnss-client)

(config-gnss-server)

(config-gnss-tty)

(config-gnss-profile)#

{**language csv [cvs-header | gga | gll | rmc | vtg] | [nmea | gga | gll | gns | gsa | gsv | incsid | presid | rmc | vtg | zda] | [taip al | checkcum | cp | id | ln | newline | pv | st | tm | vehicleid] movdis** *<0-3600>* \|

movint *<1-3600>* \|

movres *<1-3600>* \|

name *<WORD>* \|

staint *<1-3600>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-gnss-profile)**

{**language [csv cvs-header | gga | gll | rmc | vtg] | [nmea gga | gll | gns | gsa |gsv | incsid | presid | rmc | vtg | zda] | taip al | checksum | cp | id | ln | newline | pv | st | tm |vechicleid]** |	Configure the language output. **csv** • csv_header • gga • gll • rmc • vtg **nmea** • gga • gll • gns • gsa • gsv • incsid • presid • rmc • vtg • zda **taip** • al • checksum • cp • id • ln • newline • pv • st • tm • vechicleid
movdis ***<0-3600>*** |	Configure the moving distance interval. Values are 0 to 3600 in meters Default is 0
movint ***<1-3600>*** |	Configure the moving time interval. Range is 1 to 3600 seconds Default is 10 seconds
movres ***<1-3600>*** |	Resumes moving state after this distance. Range is 1 to 3600 meters Default is 20 meters
name ***<WORD>*** |	Configure the profile name.

staint ***<1-3600>***}	Configure the stationary time interval. Range is 1 to 3600 in seconds Default is 3600

Command Modes	Perle#(config-gnss-profile)#

Usage Guidelines

Configure GNSS profile parameters.

Examples

This example specifics a name for the select profile number.

Perle# gnss profile delivery-truck

Related Commands

(config-gnss-profile)#
(config-gnss-client)
(config-gnss-server)
(config-gnss-tty)

(config-gnss-client)

{**client-name** ***<WORD>*** |
port ***<1-65535>*** |
profile ***<1-16>*** |
protocol tcp | udp |
schedule end-hour ***<0-23>*** **| end-minute** ***<0-59>*** **| start-hour** ***<0-23>*** **| start-minute** ***<0-59>*** |
server -name ***<A.B.C.D> <WORD> <X:X:X:X::X>*** |
single-sentence |
stored-sentence ***<1-999>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-gnss-client)**
{**client-name** ***<WORD>*** |	Configure the GNSS stream client name.
port ***<1-65535>*** |	Configure the port of the server to receive data.
profile ***<1-16>*** |	Configure the client profile. 1–16 profiles
protocol tcp | udp |	Configure the client protocol.
schedule end-hour ***<0-23>*** **| end-minute** ***<0-59>*** **| start-hour** ***<0-23>*** **| start-minute** ***<0-59>*** |	Configure the schedule.

server -name ***<A.B.C.D><WORD>*** ***<X:X:X:X::X>*** |	Configure the IPv4/IPv6 DNS server name.
single-sentence |	Configure for single sentence packet mode.
stored-sentence ***<1-999>***}	Configure the maximum number of sentences saved if the TCP connection is lost.
Command Modes	Perle#(config-gnss-client)#

Usage Guidelines

Configure client GNSS parameters.

Examples

This example specifies protocol tcp for this client GNSS configuration.

Perle(config-gnss-client)# protocol tcp

Related Commands

(config-gnss-profile)#

(config-gnss-client)

(config-gnss-server)

(config-gnss-server)

(config-gnss-tty)

(config-gnss-server)

{**name** ***<WORD>*** \|
port ***<1-65535>*** \|
profile ***<1-16>*** \|
single-sentence

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-gnss-server)**
{**name** ***<WORD>*** |	Configure the GNSS stream server name.
port ***<1-65535>*** |	Configure the TCP port number.
profile ***<1-16>*** |	Configure the server profile.
single-sentence}	Configure single sentence packet mode.
Command Modes	Perle#(config-gnss-server)#

Usage Guidelines

Use this command to configure server GNSS parameters.

Examples

This example configures the name of the GNSS stream server.

Perle(config-gnss-server)#name GNSS-ROAD

Related Commands

(config-gnss-profile)#

(config-gnss-client)

(config-gnss-server)

(config-gnss-tty)

(config-gnss-tty)

(config-gnss-tty)

{**databits** *<7-8>* | **enable** |**name** *<WORD>* |
parity even | mark | none | odd | space |
profile *<1-16>* | **schedule** *<0-23>* | **end-minute** *<0-59>* | **start-hour** *<0-23>* | **start-minute** *<0-59>*} |**speed 115200 19200 | 230400 | 38400 | 4800 | 57600 | 9600**} |**stop-bits 1 | 2** |**stored-sentence** *<1-999>*} Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-gnss-tty)
{**databits 7	8** |	Configure the data bits. 7 or 8
enable |	Enables the serial stream.
name *<WORD>* |	Configure the serial stream name.
**parity even	mark	none	odd	space** |	Configure the parity.
profile *<1-16>* |	Configure serial stream profile.
schedule end-hour *<0-23>* | **end-minute** *<0-59>* | **start-hour** *<0-23>* | **start-minute** *<0-59>* |	Configure GNSS schedule.
**speed 115200 19200	230400	38400	4800	57600	9600**} |	Set the speed for this interface. • 115200 • 19200 • 230400 • 38400 • 4800 • 57600 • 9600

stop-bits 1 | 2 |	Configure the stop bits.
stored-sentence *<1-999>*}	Configure the maximum sentences saved on connection loss.
Command Modes	Perle#(config-gnss-tty)#

Usage Guidelines

Use this command to configure GNSS TTY parameters.

Examples

This example configures of the interface speed.

Perle(config-gnss-tty)#speed19200

Related Commands

(config-gnss-profile)#

(config-gnss-client)

(config-gnss-server)

(config-gnss-tty)

(config-gnss-usb)

{**name *<WORD>* |**
profile *<1-16>* | schedule *<0-23>* | end-minute *<0-59>* | start-hour *<0-23>* | start-minute *<0-59>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-gnss-usb)**
{**name *<WORD>* |**	Configure the GNSS USB stream name.
profile *<1-16>* |	Configure the USB stream number.
schedule *<0-23>* | end-minute *<0-59>* | start-hour *<0-23>* | start-minute *<0-59>*}	Configure GNSS schedule parameters.
Command Modes	Perle#(config-gnss usb)

Usage Guidelines

Use this command to configure GNSS USB parameters.

Examples

This example configures the GNSS USB stream number.

Perle(config-gnss-usb)#profile 10

Related Commands

(config-gnss-profile)#
(config-gnss-client)
(config-gnss-server)
(config-gnss-tty)
(config-line)#tty

hostname

hostname {*<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	hostname
{*<WORD>*}	Configure the router name.
Command Modes	Perle(config)#hostname

Usage Guidelines

Use this command to configure the router's hostname.

Examples

This example configures the router name to TestHost.

```
Perle(config)#hostname TestHost
TestHost(config)#
```

interface

interface

{**bvi** *<1-9999>* |
cellular *<0-0>* |
dialer *<0-15>* |
dot11radio *<0-4>* |
ethernet *<1-5>* **.** *<1-4000>* |
openvpn-tunnel *<0-999>* **tap** | **tun** |
tunnel *<0-999>* |
range ethernet *<1-5>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	interface
{**bvi** *<1-9999>* |	Configure the bridge interface. See *(config-if)#bvi*
cellular *<0-0>* |	Configure the cellular interface. See *(config-if)#cellular*

dialer *<0-15>* |	Configure the dialer interface. See ***(config-if)#dialer***
dot11radio *<0-4>* |	Configure the wireless interface. See ***(config-if)#dot11radio***
ethernet *<1-5>.<1-4000>* |	Configure the Ethernet interface. See ***(config-if-ethernet)#***
openvpn-tunnel *<0-999>* **tap** | **tun** |	Configure an OpenVPN tunnel. See ***(config-if)#openvpn-tunnel***
tunnel *<0-999>* |	Configure the tunnel. See ***(config-if)#tunnel***
range ethernet *<1-5>*}	Configure an Ethernet range. See ***(config-if-range)#***
Command Modes	Perle(config)#interface ethernet 1 Perle(config-if)#

Usage Guidelines

Use this command to configure an interface.

Examples

This example configures parameters for Ethernet interface 1.

```
Perle(config)#interface ethernet 1
```

Related Commands

(config-if)#bvi
(config-if)#dialer
(config-if)#openvpn-tunnel
(config-if)#tunnel
(config-if-range)#
(config-subif)#
(config-if-vrrp)#

ip access-list

ip access-list {**extended** *<100-199>* | *<2000-2699>* \|
resequence extended *<100-199><1-65535>* | *<2000-2699> <1-65535>*] |
standard *<1-99>* | *<1300-1999>*}

Use the no form of this command to negate enable.

Syntax Description	ip access-list
{**extended** *<100-199>* | *<2000-2699>* |	Configure an IP access list number. See ***(config-ext-nacl)***

resequence extended *<100-199><1-65535>* | *<2000-2699> <1-65535>*| | **standard** *<1-99> <1-65535> <1300-1999> <1-65535>* |	Configure resequence IP Access list. Entries are numbered sequentially, starting from 10 and in intervals of 10.
standard *<1-99>* | *<1300-1999>*}	Configure an IP access list number. See ***(config-std-nacl)***
Command Modes	Perle(config)#ip access-list

Usage Guidelines

Use IP Access Control Lists (ACLs) to define rules for controlling the network traffic and reducing network attacks. You can filter traffic based on sets of rules defined for the incoming traffic or outgoing traffic. Access lists look from the top list entry to bottom list entry.. Be sure when creating access lists that the most important entries are at the top of the list.

Examples

Displays ACL definitions. You will note that there is no available space to add an entry within this list. Using the resequence command you can resequence these ACL entries.

Standard IP access list Moo.

10 deny host 1.1.1.1

20 deny host 2.2.2.2

30 permit 3.3.3.3

40 permit 4.4.4.4

To resequence this ACL list to start at 20 and then resequence each entry by 20's use:

Perle(config)#ip access-list resequence Moo 20 20

Standard IP access list Moo.

20 deny host 1.1.1.1

40 deny host 2.2.2.2

60 permit 3.3.3.3

80 permit 4.4.4.4

You now have space between the entries to add entries.

Note: Resequence numbering is lost on a reboot, therefore you must copy running-config to startup-config for these changes to be permanently saved.

Related Commands

(config-std-nacl)

(config-ext-nacl)

(config-std-nacl)

{*<1-65535>* **deny | permit** *<A.B.C.D>/hostname> <A.B.C.D>/hostname>* **| any | host** *<A.B.C.D>/hostname>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-std-nacl)
{*<1-2147483647>* **deny | permit** *<A.B.C.D>/hostname> <A.B.C.D>/hostname>* **| any | host***<A.B.C.D>/hostname>*}	Configure standard access lists.
Command Modes	Perle(config-std-nacl)#

Usage Guidelines

Configure packets to reject or accept.

Examples

This example permits packets from this host.

Perle(config-std-nacl)#permit host 172.16.77.88

(config-ext-nacl)

{*<1-65535>* | {**deny ip | permit ip** *<A.B.C.D>/hostname> <A.B.C.D>/hostname>* **| any | host** *<A.B.C.D>/hostname>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-ext-nacl)
{*<1-65535>* | {**deny ip | permit ip** *<A.B.C.D>/hostname> <A.B.C.D>/hostname>* **| any | host** *<A.B.C.D>/hostname>*}	Configure sequence numbers and permits or denies packets.
Command Modes	Perle(config-ext-nacl)#

Usage Guidelines

Configure sequence number and define packets to permit or deny.

Examples

This example permits packets from source host 172.16.77.88 and destination host any (host).

Perle(config-ext-nacl)#permit ip host 172.16.77.88 any

ip alg

ip alg

{**modules ftp | gre | h323 | nfs | pptp | sip | sqlnet | tftp | disable**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip alg
{**alg modules ftp | gre | h323 | nfs | pptp | sip | sqlnet | tftp | disable**}	Configure Application Level Gateway (ALG) modules. **Some parameters may not be available on some firmware versions or models.**
Command Modes	Perle(config)#ip alg

Usage Guidelines

Use this command to configure client applications to communicate with known ports used by server applications. ALG allows customized NAT traversal filters to be plugged into the gateway to support address and port translation for protocols such as FTP, BitTorrent, SIP, RTSP, and file transfer etc. In order for these protocols to work through NAT or a firewall, either the application has to know about an address/port number combination that allows incoming packets, or the NAT has to monitor the control traffic and open up port mappings (firewall pinhole) dynamically as required. Application data is passed through the security checks of the firewall or NAT that would have otherwise been restricted. Without an ALG, the ports would either get blocked, or the network administrator would need to open up a large number of ports in the firewall, weakening the network and allowing potential attacks on those ports.

By default all alg modules are enabled.

Examples

This example disables ALG module ftp.

Perle(config)#no ip alg modules ftp disable

ip as-path

ip as-path

{**access-list** ***<WORD>*** ***<1-65535>*** **deny | permit** ***<LINE>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip as-path
{**as-path access-list** ***<WORD>*** ***<1-65535>*** **deny | permit** ***<LINE>***}	Configure access list parameters.
Command Modes	Perle(config)#ip as-path

Usage Guidelines

Use this command to configure an access-list filters for Border Gateway Protocol (BGP) autonomous system (AS) numbers. You can use AS Path filters, either inbound or outbound, to filter either the routes you send or the routes you receive, respectively. You must apply these filters to each peer separately. Regular expressions are strings of special characters used to search and find character patterns.

Regular expression for *<LINE>* include:

CHAR	USAGE
^	Start of string
$	End of string
[]	Range of characters
-	Used to specify range (i.e [0-9])
( )	Logical Grouping
.	Any single character
*	Zero or more instances
+	On or more instance
?	Zero or more instance

Expression	Meaning
.*	Anything
^$	Locally originated routes
^100_	Learned from AS 100
_100$	Originated in AS 100
_100_	Any instance of AS 100
^[0-9]+$	Directly connected ASes

Examples

This example accepts prefixes that originated in AS 3299, all other prefixes won't be permitted.

Perle(config)#ip as-path access-list 1 permit ^3299$

Related Commands

(config-remote-mgmt)

show ip as-path-access-list

ip community-list

ip community-list

{**expanded** ***<100-500> <1-65535>*** **deny** ***<LINE>*** **| permit** ***<LINE>*** **|**
standard ***<1-99> <1-65535>*** **deny** ***<1-4294967295>*** **| internet | local-as |no-advertise | no-export | permit** ***<1-4294967295>*** **| internet | local-as | no-advertise | no-export | permit** ***<LINE>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip community-list
{**expanded** ***<100-500> <1-65535>*** **deny** ***<LINE>*** **| permit** ***<LINE>*** **|**	Configure an extended community list.You can configure up to 32 communities.

standard *<1-99>* *<1-65535>* deny *<1-4294967295>* | internet | local-as |no-advertise | no-export | permit *<1-4294967295>* | internet | local-as | no-advertise | no-export | permit *<LINE>*	Configure a standard community list. You can configure up to 16 communities.
Command Modes	Perle(config)#ip community-list

Usage Guidelines

Use this command to configure a BGP community list and to control which routes are permitted or denied based on their community values.

Standard community lists are used to configure well-known communities and specific community numbers. You can pick more than one of the optional community keywords.

Expanded community lists are used to filter communities using a regular expression. Regular expressions are used to configure patterns to match community attributes

CHAR	USAGE
^	Start of string
$	End of string
[]	Range of characters
-	Used to specify range (i.e [0-9])
( )	Logical Grouping
.	Any single character
*	Zero or more instances
+	On or more instance
?	Zero or more instance

Expression	Meaning
.*	Anything
^$	Locally originated routes
^100_	Learned from AS 100
_100$	Originated in AS 100
_100_	Any instance of AS 100
^[0-9]+$	Directly connected ASes

Examples

This example configures a standard community list that denies routes that carry communities from network 40 in autonomous system 65540 and from network 60 in autonomous system 65550. This example shows a logical AND condition; all community values must match in order for the list to be processed.

Perle(config)#ip community-list standard test1 deny 65540:40 65550:60

Related Commands

router

ip default-gateway

ip default-gateway

{**default-gateway** ***<A.B.C.D>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip default-gateway
{**default-gateway** ***<A.B.C.D>***}	Configure the IP address of the default gateway.
Command Modes	Perle(config)#ip default-gateway

Usage Guidelines

Use this command to configure a default gateway.

Examples

This example configures a gateway address of 172.16.1.1.

Perle(config)#ip default-gateway 172.16.1.1

ip dhcp

ip dhcp

{**dhcp excluded-address** ***<A.B.C.D>*** **| pool** ***<NAME>*** **|**
relay information hop-count ***<1-255>*** **| packet-size** ***<64-1400>*** **| policy drop | encapsulate | keep | replace | port** ***<1-655535>*** **| server** ***<A.B.C.D>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip dhcp
{**dhcp excluded-address** ***<A.B.C.D>*** **| pool** ***<NAME>*** **|**	Configure Dynamic Host Configuration Protocol (DHCP) to exclude an address range. Configure DHCP pools.
relay information hop-count ***<1-255>*** **| packet-size** ***<64-1400>*** **| policy drop | encapsulate | keep | replace | port** ***<1-655535>*** **| server** ***<A.B.C.D>***}	Configure Relay Agent parameters. **Some parameters may not be available on some firmware versions or models.**
Command Modes	Perle(config)#ip dhcp

Usage Guidelines

Use this command to have the DHCP server automatically assign an IP address and other IP parameters to devices on your network.

Examples

This example excludes ip address 172.16.55.99 from the DHCP pool.

Perle(config)#ip dhcp exclude address 172.16.55.99

Related Commands

(config-dhcp)

(config-dhcp)

{**address** *<A.B.C.D>* **hardware-address** *<H.H.H>* |
authoritative enable |
bootfile *<WORD>* |
default-router *<A.B.C.D>/hostname* |
description *<LINE>* |
dns-server *<A.B.C.D>/hostname* |
domain-name *<WORD>* |
enable |
lease *<0-365> <0-23> <0-59>* | **infinite** |
network *</nn | A.B.C.D>* **start** *<A.B.C.D>* **stop** *<A.B.C.D>* |
option *<1-254>* **ascii** *<LINE>* | **hex** *<hex-string>* | **ip** *<A.B.C.D>/hostname* |
static-route *<A.B.C.D> <A.B.C.D> <A.B.C.D>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-dhcp)
{**address** *<A.B.C.D>* **hardware-address** *<H.H.H>* |	Configure the IP address to reserve for this client. This IP address is only assigned to the client with this hardware address.
authoritative enable |	Configure the authoritative parameter. This parameter must be set to enable if this is the only DHCP server on your network. Authoritative mode allows roaming clients to get a new DHCP address even if their lease has been assigned from another network and is still valid (lease has not expired) This prevents a client lock out situation.
bootfile *<filename>* |	Configure the IP address or name of a TFTP server and boot file name to allow client auto-configuration.
default-router *<A.B.C.D>* |	Configure the default router to use after a DHCP client has booted. The IP address of the default router should be on the same subnet as the client.
description *<pool-name>* |	Configure DHCP pool name description.

dns-server *<A.B.C.D>* |	Configure a DNS server for use by clients using this DHCP pool. A DNS server needs to be specified if you want to browse the Internet.
domain-name *<A.B.C.D>* |	Configure a domain name.
enable |	Enables this dhcp pool.
lease *<0-365> <0-23> <0-59>* | **infinite** |	Configure a lease time for client connecting using this DHCP pool. Typically 24 lease times are suitable, however if your situation is a public hotspot then shorter time be warranted.
network *</nn | A.B.C.D>* **start** *<A.B.C.D>* **stop** *<A.B.C.D>* |	Configure the network, start and stop IP addresses for DHCP lease ranges.
option ascii *<string>* | **hex** *<hex-string>* | **ip** *<A.B.C.D>* |	Configure DHCP options to send to the client.
static-route *<A.B.C.D> <A.B.C.D> <A.B.C.D>*}	Configure a static route.
Command Modes	Perle(config-dhcp)#

Usage Guidelines

Use this command to configure DHCP parameters.

Examples

This example sets authoritative mode to enable.

Perle(config-dhcp)#ip authoritative enable

Related Commands

ip dhcp

ip dns

ip dns

{**dns cache-size** *<1-10000>* \| **domain** *<NAME>* **server** *<A.B.C.D> <X:X:X:X::X>* \| **ignore-hosts-file**
\| **listen-address** *<A.B.C.D>* \| *<X:X:X:X::X>*
\| **negative-ttl** *<0-7200>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip dns
{**dns cache-size** *<1-10000>* |	Configure the size of the DNS cache. Values are 1 to 10000 Default is 10000

domain ***<NAME>*** **server** ***<A.B.C.D>*** ***<X:X:X:X::X>*** |	Configure the domain name to forward to a custom DNS server.
ignore-hosts-file |	Configure the parameter—Do not use the local /etc/hosts file for name resolution.
listen-address ***<A.B.C.D>*** ***<X:X:X:X::X>*** |	Configure the parameter to listen for DNS addresses on the following IP addresses.
negative-ttl ***<0-7200>***}	Configure the seconds to cache NXDOMAIN entries. Values are 0–7200 seconds Default is 3600 seconds
Command Modes	Perle(config)#ip dns

Usage Guidelines

Use this command to configure parameters for DNS.

Examples

This example sets listen address to 172.16.77.88.

Perle(config)#ip dns listen-address 172.16.77.88

Related Commands

ip domain

ip domain-name

ip domain

ip domain

{**domain lookup**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**ip domain**
{**domain lookup**}	Enables DNS host name to IP address translation.
Command Modes	Perle(config)#ip domain

Usage Guidelines

Use the ip domain-lookup command to enable DNS host name-to-IP address translation on the router.

Examples

This example enables DNS host to IP address translation.

Perle(config)#ip domain

Related Commands

ip domain-name

ip domain-name

ip domain-name

{**domain-name** ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip domain-name
{**domain-name** ***<WORD>***}	Configure the domain name.
Command Modes	Perle(config)#ip domain-name

Usage Guidelines

Use this command to configure the default domain name.

Examples

This example sets domain name to testlab.

Perle(config)#ip domain-name testlab

Related Commands

ip domain

ip extcommunity-list

ip excommunity-list

{**extcommunity-list expanded** ***<100-500>*** ***<1-65535>*** **deny** ***<LINE>*** **| permit** ***<LINE>*** **|**
standard ***<1-99>*** ***<1-65535>*** **deny rt | soo | asn:nn**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip extcommunity-list
{**extcommunity-list expanded** ***<100-500>*** ***<1-65535>*** **deny** ***<LINE>*** **| permit** ***<LINE>*** **|**	Configure an extended community list entry.

standard ***<1-99> <1-65535>*** **deny rt | soo asn:nn**}	Configure a standard community list entry. **soo—**The site-of-origin (SoO) extended community is a BGP extended community attribute used to identify routes that have originated from a site so that the readvertisement of that prefix back to the source site is prevented. BGP uses the SoO value associated with a route to prevent routing loops. **rt—**The route target BGP Extended Community dictates the policies used by the Virtual routing and forwarding (VRF). The route target must be configured to specify the routes, which contain this specific route target value, that are imported into the VRF, and the route target that is added to the routes that are exported from the (VRF).
Command Modes	Perle(config)#ip extcommunity-list

Usage Guidelines

This command defines a new standard extcommunity-list.

Examples

This example configures a standard community list where the routes with this community are advertised to all peers (internal and external).

Perle(config)#ip extcommunity-list

Related Commands

show ip extcommunity-list

ip firewall

ip firewall

{**firewall** ***<WORD>*** |
all-ping enable |
broadcast-ping enable |
ip-src-route enable |
ipv6-receive-redirects enable |
ipv6-src-route |
log-martians enable |
receive-redirects enable |
send-redirects enable |
source-validation disable | loose | strict |

state-policy established accept | drop | reject invalid accept | drop | reject | related action accept | drop | reject |
syn-cookies enable |
twa-hazards-protection enable}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip firewall
{**firewall** ***<WORD>*** |	Creates a firewall set of rules. Firewall name cannot be the same as route-policy name.
all-ping enable |	Configure the handling of IPv4 ICMP Echo requests. **Enable**—system responses to IPv4 ICMP Echo requests. **Disable**—system does not respond to IPv4 ICMP Echo requests Default is Disabled
broadcast-ping enable |	Configure the handling of IPv4 ICMP echo and timestamps requests. **Enable**—system responses to broadcast IPv4 ICMP echo and timestamp requests **Disable**—system does not respond to IPv4 echo and timestamp requests Default is Disabled
ip-src-route enable |	Configure the handing of IPv4 packets with source route option. Default is Disabled
ipv6-receive-redirects enable |	Configure the handing of received IPv6 ICMP redirect messages. Default is Disabled
ipv6-src-route |	Configure the handling of IPv6 packets with routing extension header. Default is Disabled
log-martians enable |	Configure the handing of IPv6 packets with routing extension header. Default is Disabled
receive-redirects enable |	Configure the handing of received IPv4 ICMP redirect messages. Permits or denies IPv4 ICMP redirect messages. Default is Disabled

send-redirects enable |	Configure the sending of IPv4 only redirect messages. Default is enabled
source-validation disable | loose | strict |	Configure source validation (IPv4 only). **Disable**—no source validation is performed **Loose**—enable loose reverse path forwarding as defined by RFC3704 **Strict**—enable strict reverse path forwarding as defined in RFC3704 Default is Disabled
state-policy established accept | drop | reject invalid accept | drop | reject |related action accept | drop | reject |	Configure the global firewall state policy for both IPv4 and IPv6. By default, the firewall is stateless, configuring any of these options makes the firewall become stateful. • a firewall state policy is configured
state-policy established accept | drop | reject invalid accept | drop | reject |related action accept | drop | reject |	• NAT is configured • The transport web proxy service is enable • A load-balancing configuration is enable Default is none (not set)
syn-cookies enable |	Configure the policy for using TCP SYN cookies with IPv4. Default is enabled
twa-hazards-protection enable}	Configure for TCP TIME_WAIT assassination hazards protection per RFC 1337.
Command Modes	Perle(config)#ip firewall

Usage Guidelines

Use this command to configure firewall global configuration parameters.

Examples

This example configures the router to answer all incoming ping requests.

Perle(config)#ip firewall all-ping enable

Related Commands

show ip firewall

clear ip

show ipv6

(config-fw)

{**default-action accept | drop | reject** \|
description ***<LINE>*** \|
enable default-log \|

rule *<1-9999>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-fw)
{**default-action accept | drop | reject** |	Configure the default action for the entire firewall.
description *<LINE>* |	Configure firewall rule description.
enable default-log |	Enables log packets matching the default-action **Note:** To see logging, turn on kernel debug. <config># debug kernel
rule *<1-9999>*}	Configure the number for this rule, then enters sub-menu. (config-fw-rules).
Command Modes	Perle(config-fw)#

Usage Guidelines

Creates a firewall set of rules with the given name.

Examples

This example configures the default log action to enable. See show logging for output.

Perle(config-fw)#enable-default-action

This example create rule 1, then enters sub-menu mode (config-fw-rules).

Perle(config-fw)#rule 1

Perle(config-fw-rules)#

Related Commands

show ip firewall

clear ip

show ipv6

show lldp

(config-fw-rules)

ip firewall

(config-fw-rules)

{**description *<LINE>*** \|

disable *<LINE>* \|

log enabled \|

match destination address *<A.B.C.D> <A.B.C.D>* | not *<A.B.C.D> <A.B.C.D>* start *<A.B.C.D>* stop *<A.B.C.D>* port *<A.B.C.D> <A.B.C.D>* | not *<A.B.C.D> <A.B.C.D>* start *<A.B.C.D>* stop *<A.B.C.D>* | fragment | non-fragment | icmp type *<0-255>* code *<0-255>* | type-name tos-host-redirect | tos-network-redirect | address-mask-reply | address-mask-request | communication-prohibited |

destination-unreachable | echo-reply | echo-request | fragmentation needed | host-precedence-violation | host-redirect | host-unknown | host-unreachable | network-redirect | network-unknown | parameter-problem | port-unreachable | protocol-unreachable | redirect | required-option-missing | router-advertisement | router-solicitation | source-quench | source-route-failed | time-exceeded | timestamp-reply | timestamp-request | ipsec | non-ipsec | protocol *<0-255>* | ah | dccp | dsr | egp | eigrp | encap | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | ip | ipip | ipv6 | ipc6-frag | ipv6-icmp | ipv6-nonxt | ipv6-opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | pim | rdp | roch | rvsp | sctp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp || recent count *<1-255>* | time *<1-4294967295>* | source address *<A.B.C.D>* *<A.B.C.D>* not *<A.B.C.D>* *<A.B.C.D>* start *<A.B.C.D>* stop *<A.B.C.D>* | mac-address *<H.H.H>* not *<H.H.H>* | port *<1-65535>* not *<1-65535>* start *<1-65535>* stop *<1-65535>* | state established | invalid | new | related | tcp-flags ack | all | fin | sh | rst | syn | urg | not |

set action accept | drop | reject |

time monthdays *<1-31>* not *<1-31>* | startdate january | february | march | april | may | june | july | august | september |november | december day *<1-31>* year *<2001-2037>* | starttime *<hh:mm:ss>*| stopdate january | february | march | april | may | june | july | august | september |november | december | stoptime *<hh:mm:ss>* | utc | weekdays monday | tuesday | wednesday | thursday | friday | saturday | sunday | not monday | tuesday | wednesday | thursday | friday | saturday | sunday}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-fw-rules)**
{**description *<LINE>*** |	Configure a description for the policy rule.
disable *<LINE>* |	Disables policy rule.
log enabled |	Enables log packets matching the rule.

match destination address ***<A.B.C.D>*** ***<A.B.C.D>*** **| not** ***<A.B.C.D>*** ***<A.B.C.D>*** **start** ***<A.B.C.D>*** **stop** ***<A.B.C.D>*** **port** ***<A.B.C.D>*** ***<A.B.C.D>*** **| not** ***<A.B.C.D>*** ***<A.B.C.D>*** **start** ***<A.B.C.D>*** **stop** ***<A.B.C.D>*** **| fragment | non-fragment | icmp type** ***<0-255>*** **code** ***<0-255>*** **| type-name tos-host-redirect | tos-network-redirect | address-mask-reply |address-mask-request | communication-prohibited | destination-unreachable | echo-reply | echo-request | fragmentation needed | host-precedence-violation | host-redirect | host-unknown | host-unreachable | network-redirect | network-unknown | parameter-problem | port-unreachable | protocol-unreachable | redirect | required-option-missing | router-advertisement | router-solicitation | source-quench | source-route-failed | time-exceeded | timestamp-reply | timestamp-request | ipsec | non-ipsec | protocol** ***<0-255>*** **| ah | dccp | dsr | egp | eigrp | encap | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | ip | ipip | ipv6 | ipc6-frag | ipv6-icmp | ipv6-nonxt | ipv6-opts | ipv6-route | isis | l2tp |**	Configure firewall rules to match conditions for traffic and the action to be taken if the match conditions are satisfied. Traffic matches on a number of characteristics, including source IP address, destination IP address, source port, destination port, IP protocol, and ICMP type. Rules are executed in sequence, according to the rule number. If the traffic matches the characteristics specified by the rule, the rule's action is executed; if not, the system "falls through" to the next rule.

manet | mpls-in-ip | narp | pim | rdp | roch | rvsp | sctp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp || recent count *<1-255>* | time *<1-4294967295>* | source address *<A.B.C.D>* *<A.B.C.D>* not *<A.B.C.D>* *<A.B.C.D>* start *<A.B.C.D>* stop *<A.B.C.D>* | mac-address *<H.H.H>* not *<H.H.H>* | port *<1-65535>* not *<1-65535>* start *<1-65535>* stop *<1-65535>* | state estabished | invalid | new | related | tcp-flags ack | all | fin | sh | rst | syn | urg | not |	
set action accept | drop | reject	Action for packets. The action is one of the following: • Accept—Traffic is allowed and forwarded. • Drop—Traffic is silently discarded. • Reject—Traffic is discarded with an ICMP “Port Unreachable” message. • Inspect—Traffic is processed by the intrusion protection system (IPS).
time monthdays *<1-31>* not *<1-31>* | startdate january | february | march | april | may | june | july | august | september | november | december day *<1-31>* year *<2001-2037>* | starttime *<hh:mm:ss>*| stopdate january | february | march | april | may | june | july | august | september ||november | december | stoptime *<hh:mm:ss>* | utc | weekdays monday | tuesday | wednesday | thursday | friday saturday | sunday | not monday | tuesday | wednesday | thursday | friday | saturday | sunday|	Configure time schedule to match rules.
Command Modes	Perle(config-fw-rules)#

Usage Guidelines

Use this command to create firewalls filter packets on interfaces.

There are two steps to create a firewall.
1. You define a firewall instance and save it under a name. A firewall instance is also called a firewall rule set, where a rule set is just a series of firewall rules. You define the firewall instance and configure the rules for its rule set in the firewall configuration node.

2 After defining the instance and specifying the rules in the rule set, you apply the instance to an interface or a zone. You do this by configuring the interface configuration node for the interface or zone. Once the instance is applied to the interface or zone, the rules in the instance begin filtering packets.

Examples

The example below applies firewall name set test to the inbound traffic on BV1 (bridging eth1 and eth2). This firewall drops all ICMP traffic (generated by ping commands), but allows all other traffic such as TCP Web traffic) because the default action is accept.

```
Perle(config)#ip firewall test
Perle(config-fw)#default-action accept
Perle(config-fw)#rule 1
Perle(config-fw-rules)#set action drop
Perle(config-fw-rules)#match protocol icmp
```

```
Perle(config-fw)#rule 2
Perle(config-fw-rules)#set action accept
Perle(config-fw-rules)#match protocol tcp
Perle(config)#interface ethernet 1
Perle(config)#bridge-group 1
Perle(config)#interface ethernet 2
Perle(config)#bridge-group 1
```

Related Commands

show ip firewall

clear ip

show ipv6

(config-fw)

ip ftp

ip ftp

{**ftp passive | password 0 *<LINE>* | 7 *<WORD>* | *<LINE>* | username *<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description **ip ftp**

{**ftp passive** | **password 0** ***<LINE>*** | **7** ***<WORD>*** | ***<LINE>*** | **username** ***<WORD>***}	Configure File Transfer Protocol (FTP) parameters. Passive—indicates to the server that the client is opening the file transfer session. This option is used if the client is behind a firewall.
Command Modes	Perle(config)#ip ftp

Usage Guidelines

Use this command to configure File Transfer Protocol (FTP) parameters.

Examples

This example set username to labuser.

Perle(config)#ip ftp username labuser

ip health

ip health

{**profile** ***<WORD>*** }

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**ip health**
{**profile** ***<WORD>***}	Configure an IP Health Profile. See ***(config-health-prof)*** for more information.
Command Modes	Perle(config)#ip health

Usage Guidelines

Use this command to create a health profile. Health profiles are assigned to interfaces to monitor the heath of that interface.

Examples

This example creates a health profile called labhealth.

Perle(config)#ip health profile labhealth

Related Commands

(config-health-prof)

show ip health

(config-health-prof)

{**failure-count** ***<1-10>*** \| **success-count** \| **test** ***<1-100>*** **target** ***<hostname*** \| ***<A.B.C.D>*** **type ping response-timeout** ***<1-30>*** \| **traceroute limit** ***<1-254>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-health-prof)**

{**failure-count** ***<1-10>*** **| success-count | test target** ***<hostname | <A.B.C.D>*** **| type ping response-timeout** ***<1-30>*** **| traceroute limit** ***<1-254>***}	Test ***<1–100>***—Prioritize heath test 1=first. • Failure test count before marking failed • Count failure before marking as failed • Count successes before marking as active • Configure a health test
Command Modes	Perle(config-health-prof)#

Usage Guidelines

Use this command to configure health tests.

Examples

This example creates a health test to ping host 172.16.77.4 10 times

Perle(config-health-prof)#test target 10 172.16.77.4

ip host

ip host

{**host** ***<WORD> <A.B.C.D>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**ip host**
{**host** ***<WORD> <A.B.C.D>***}	Configure a host to add to the host table.
Command Modes	Perle(config)#ip host

Usage Guidelines

Use this command to add a host to the router internal host table.

Examples

This example adds host labhost with ip address of 172.16.99.10 to the host table.

Perle(config)#ip host labhost 172.16.99.10

Related Commands

show hosts

ip host-group

ip host-group

{**host** ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**ip host-group**

{**host** *<WORD>*}	Configure the host group name.
Command Modes	Perle(config)#ip host

Usage Guidelines

Use this command to create a host group. A host group is a list of hosts.

Examples

This example creates host group hosts_for_labs.

Perle(config)#ip host-group hosts_for_labs

Related Commands

(config-host-group)

(config-host-group)

{**host** *<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-host-group)**
{**host** *<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X>*}	Configure a host to add to the host group.
Command Modes	Perle(config-host-group)#

Usage Guidelines

Use this command to add a host to the host group.

Examples

This example adds host 172.17.55.90 to host group.

Perle(config-host-group)#host 172.17.55.90

Related Commands

ip host-group

ip http

ip http

{**accounting exec** *<WORD>* | **default]** |
authentication aaa login-authentication *<WORD>* | **default]** |
client password 0 *<LINE>* | **7** *<WORD>* | *<LINE>* **proxy-server** *<WORD>* **proxy-port** *<1-65535>* | **secure-trust-point** *<WORD>* | **username** *<WORD>* | **verify-server** |
local port *80* | *<1025-65535>* |
secure-port *443* | *<1025-65535>* |

secure-server |
server |
session-idle-timeout *<1-1440>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip http
{**accounting exec** *<WORD>* | **default]** |	Configure HTTP server accounting parameters.
authentication aaa login-authentication *<WORD>* | **default]** |	Configure HTTP server authentication method.
client password 0 *<LINE>* | **7** *<WORD>* | *<LINE>* **proxy-server** *<WORD>* **proxy-port** *<1-65535>* | **secure-trust-point** *<WORD>* | **username** *<WORD>* | **verify-server]** |	Configure HTTP client certificate secure trustpoint.
local port *80* | *<1025-65535>* |	Configure a HTTP server local port number for listening. Values are 1025 to 65535 Default is 80
secure-port *443* | *<1025-65535>* |	Configure a HTTPS server port for listening. Values are 1025 to 65535 Default is 4430
secure-server |	Enable HTTP secure server.
server |	Enable HTTP server.
session-idle-timeout *<1-1440>*}	Configure a HTTP server session idle timeout. Default session idle timeout is 1440 seconds.
Command Modes	Perle(config)#ip http

Usage Guidelines

Use this command to configure HTTP/S server parameters.

Examples

This example enables HTTP secure server.

```
Perle(config)#ip http secure-server
```

Related Commands

show ip http

ip name-server

ip name-server

{**name-server** *<A.B.C.D>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip name-server
{**name-server** *<A.B.C.D>*}	Configure the address of the name server.
Command Modes	Perle(config)#ip name-server

Usage Guidelines

Use this command to configure the nameserver. Nameserver is a server that handles queries regarding the location of a domain name's various services such as website, emails and so on. It is also a part of the Domain Name System (DNS) which maintains a directory of domain names and translate them to IP addresses. When you visit a domain, a DNS lookup first checks its name servers and reviews the DNS records for that domain accordingly.

Examples

This example set name-server to 172.16.44.55.

Perle(config)#ip name-server 172.16.44.55

ip nat

{**nat [inside source any | list** *<1-199>* **interface bvi** *<1-9999>* **| cellular** *<0-0>* **| dialer** *<0-15>* **| dot11radio** *<0-4>* **| ethernet** *<1-5>* **| openvpn** *<0-999>* **| tunnel** *<0-999>* **| over load | no-strict] | static [ip** *<A.B.C.D>* **| local-pool** *<WORD>* **global-pool** *<WORD>* **[address-mapping persistent | random] inbound-interface bvi** *<1-9999>* **| cellular** *<0-0>* **| dialer** *<0-15>* **| dot11radio** *<0-4>* **| ethernet** *<1-5>* **| openvpn** *<0-999>* **| tunnel** *<0-999> <1-65535> <A.B.C.D> <A.B.C.D>* **| tcp | tcp+udp | udp]** *<A.B.C.D> <1-65535>* **inbound-interface bvi** *<1-9999>* **| cellular** *<0-0>* **| dialer** *<0-15>* **| dot11radio** *<0-4>* **| ethernet** *<1-5>* **| openvpn** *<0-999>* **| tunnel** *<0-999> <1-65535> <A.B.C.D> <A.B.C.D>* **|**

pool *<WORD> <A.B.C.D> <A.B.C.D>* **netmask** *<A.B.C.D>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ip nat

{**nat [inside source any | list *<1-199>* interface bvi *<1-9999>* | cellular *<0-0>* | dialer *<0-15>* | dot11radio *<0-4>* | ethernet *<1-5>* | openvpn *<0-999>* | tunnel *<0-999>* | over load | no-strict] | static [ip *<A.B.C.D>* | local-pool *<WORD>* global-pool *<WORD>* [address-mapping persistent | random] inbound-interface bvi *<1-9999>* | cellular *<0-0>* | dialer *<0-15>* | dot11radio *<0-4>* | ethernet *<1-5>* | openvpn *<0-999>* | tunnel *<0-999>* *<1-65535>* *<A.B.C.D>* *<A.B.C.D>* | tcp | tcp+udp | udp] *<A.B.C.D>* *<1-65535>* inbound-interface bvi *<1-9999>* | cellular *<0-0>* | dialer *<0-15>* | dot11radio *<0-4>* | ethernet *<1-5>* | openvpn *<0-999>* | tunnel *<0-999>* *<1-65535>* *<A.B.C.D>* *<A.B.C.D>*** |	Configure Network Address Translation (NAT). **Address mapping** • **Random mode**–translation address is computed based on source and destination addresses of incoming packets on every connection • **Persistent mode**–translation address is computed based on source address of incoming packets on the first connection, and will be persistent for each connection there after Default translation mode is random **Global pool–**define the global pool **Local pool–**define the local pool **Note:** Global address pools cannot have overlapping addresses between multiple pools **No**—strict–do not turn on firewall to drop invalid connections
pool *<WORD>* *<A.B.C.D>* *<A.B.C.D>* netmask *<A.B.C.D>*}	Define DHCP address pool.

Command Modes	Perle(config)#ip nat

Usage Guidelines

One to One:

Use Source Network Address Translation (SNAT) to allow multiple host inside the network to reach a host outside the network.

One to Many:

Use Destination Address Translation (DNAT) to allow multiple hosts outside the network to reach a single host inside the network.

Examples

This example allows all local traffic to the Internet through ethernet port 1.

First you need to create an access-list, then you need to assign NAT.

```
Perle(config)#ip access-list standard 1
Perle(config-std-nacl)#permit any
Perle(config)#ip nat inside source list 1 interface ethernet 1 overload
```

Related Commands

show ip nat

ip passthrough

ip passthrough {enable | interface ethernet address <*A.B.C.D*> | hardware-address <*HEX-STRING.*>}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip passthrough
{**enable | interface ethernet address** <*A.B.C.D*> **| hardware-address** <*HEX-STRING.*>}	Enables IP passthrough.Your router's default IP address for IP passthrough is 192.168.0.1.
Command Modes	Perle(config)#ip passthrough

Usage Guidelines

Use this command so your attached device can access and administer the router until the LTE connection is established. In this mode, you can configure the LTE parameters for your connection. Once your LTE connection is established, the IP address of the attached device is the IP address obtained from the LTE network.

Examples

This example enables IP passthrough with user specified IP address 192.168.1.1.

Perle(config)#ip passthrough interface ethernet address 192.168.1.1

Perle(config)#ip passthrough enable

ip prefix-list

ip prefix-list

{<*WORD*> **deny** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*> **| description** <*LINE*> **| permit** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*> **| seq** <1-65535> **deny** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*> **| permit** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*>}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip prefix-list
{<*WORD*> **deny** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*> **| description** <*LINE*> **| permit** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*> **| seq** <1-65535> **deny** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*> **| permit** <*A.B.C.D*> <*/n* | *A.B.C.D*> **ge | le** <*1-32*>}	Configure prefix-list filter. **ge value** (optional) Specifies a prefix length greater than or equal to the value. It is the lowest value of a range of the length (the "from" portion of the length range) **le value** (optional) Specifiers a prefix length less then or equal to the value. It is the highest value of a range of the length (the "to" portion of the length range.
Command Modes	Perle(config)#ip prefix-list

Usage Guidelines

Use this command to create prefix lists Prefix lists are used in route maps and route filtering operations.The can be used as an alternative to access lists in many routing filtering commands. The most important difference is that a prefix-list allows you to filter networks based on their subnet mask.

Examples

This example shows how to accept a mask length of up to 24 bits in routes with the prefix 172.20.10.171/16.

Perle(config)#ip prefix list1 permit 172.20.10.171 /16 le 24

This example shows how to permit the prefix 172.17.0.0/16.

Perle(config)#ip prefix list2 permit 172.17.0.0 255.255.0.0

Related Commands

show ip access-lists

ip radius

ip radius

{**source-interface [bvi *<1-9999>*] | [cellular *<0-0>*] | [dialer *<0-15>*] | [dot11radio *<0-4>*] | [ethernet *<1-5>* . *<1-4000>*] | [openvpn-tunnel *<0-999>*] | [tunnel *<0-999>*]**}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip radius
{**source-interface [bvi *<1-9999>*] | [cellular *<0-0>*] | [dialer *<0-15>*] | [dot11radio *<0-4>*] | [ethernet *<1-5>*. *<1-4000>*] | [openvpn-tunnel *<0-999>*] | [tunnel *<0-999>*]**}	Configure an interface as the source IP address from which the RADIUS client sends RADIUS requests or receives responses.
Command Modes	Perle(config)#ip radius

Usage Guidelines

Use this command to configure Remote Authentication Dial-In User Service (RADIUS) authentication. RADIUS authenticates local and remote users on a company network. RADIUS is a client/server system that keeps the authentication information for users, remote access servers, VPN gateways, and other resources in one central database.

Examples

This example configures the source-interface as ethernet 1

Perle(config)#ip radius source-interface ethernet 1

Related Commands

clear radius

show radius

ip route

ip route

{*< A.B.C.D> <A.B.C.D> < A.B.C.D> <1-255>* | [bvi *<1-9999>*] | [ethernet*<1-5> <1-255>* dhcp | vrrp *<1-255>* | null *<1-255>*] | [table *<1-200> <A.B.C.D> <A.B.C.D> < A.B.C.D>*] | [bvi *<1-9999>*] | [cellular *<0-0>*] | [dialer *<0-15>*] | [dot11radio *<0-4>*] | [ethernet *<1-5>* dhcp | vrrp *<1-255>* | null *<1-255>*] | [openvpn *<0-999>*] | [tunnel *<0-999>* | *<1-255>* | dhcp]}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip route
< A.B.C.D> <A.B.C.D> < A.B.C.D> <1-255> | [bvi *<1-9999>*] | [cellular *<0-0>*] | [dot11radio *<0-4>*] | [ethernet *<1-5> <1-255>* dhcp | vrrp *<1-255>* | null *<1-255>*] | [table *<1-200> <A.B.C.D> <A.B.C.D> < A.B.C.D>*] | [bvi *<1-9999>*] | [cellular *<0-0>*] | [dialer *<0-15>*] | [dot11radio *<0-4>*] | [ethernet *<1-5>* dhcp	Configure static routes. Prefix—specifies the IP route prefix for the destination mask—specifies the prefix mask for the destination ip-address—specifies the IP address of the next hop used to reach that network metric—specifies the metric of the route. interface—apply this route to this interface dhcp—default gateway obtained from DHCP
| vrrp *<1-255>* | null *<1-255>*] | [openvpn *<0-999>*] | [tunnel *<0-999>* | *<1-255>* | dhcp]}	
Command Modes	Perle(config)#ip route

Usage Guidelines

Use this command to configure a static route.

Examples

This example routes packets from network 172.16.1.7 to a router at 172.17.23.20.

Perle(config)#ip route 172.16.1.7 255.255.0.0 172.17.23.20

Related Commands

ip route-policy

ip route-policy

ip route-policy

{route-policy *<WORD*}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip route-policy
{**route-policy** ***<WORD***}	Configure a route policy. See ***(config-pbr-rules)*** for more information.
Command Modes	Perle(config)#ip route-policy

Usage Guidelines

Use this command to create a route policy name.

Examples

This example creates route policy testlab.

Perle(config)#ip route-policy testlab

Related Commands

(config-pbr-rules)

(config-pbr)

{**description** ***<LINE>***
| **enable-default-log**
| **rule** ***<1-9998>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-pbr)
{**description** ***<LINE>*** |	Configure a policy rule.
enable-default-log |	Configure default log.
rule ***<1-9998>***}	Configure rule number.
Command Modes	Perle(config-pbr)#

Usage Guidelines

Use this command to create a policy rule.

Examples

This example configures rule number 10, then enter sub menu mode.

Perle(config-pbr)#rule 10
Perle(config-pbr-rules)#

(config-pbr-rules)

{**description** ***<LINE>*** |
log-enable |
match [destination address ***<A.B.C.D> <A.B.C.D>*** **| not** ***<A.B.C.D> <A.B.C.D>*** **|**
start ***<A.B.C.D>*** **stop** ***<A.B.C.D>*****] | [port** ***<1-65535>*****| not** ***<1-65535>*** **| start** ***<1-***

65535> stop<1-65535>] | [fragment | fragment | non-fragment] | [icmp type <0-255> code <0-255>] | [ipsec ipsec |non-ipsec] | [protocol <0-255> ah | dccp | dsr | egp | eigrp | encap | esp | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipc6-icmp | ipv6-nonxt | ipv6-opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | not | osfp | pim | rdp | rohc | rsvp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp] | [recent count <1-255> | time <1-4294967295>] | [source address <A.B.C.D> <A.B.C.D> | not <A.B.C.D> | start <A.B.C.D> stop <A.B.C.D> | mac-address <H.H.H> | not <A.B.C.D> | [state established disable | enable] | [invalid disable | enable] | [new disable | enable] | related tcp-flags ack | all | fin | psh | rst | syn | urg | not |

set action drop | [dscp af11 | af12 | af13 |af 21 | af22 | af 23 | af31 | af33 | af41 | af42 | af43 | cs1 | cs2 |cs3 | cs4 | cs5 | cs6 cs7 ef] | mark <1-2147483647> | [routing-table <1-200> | main] | tcp-mss <500-1460> | pmtu | <500-1460> |

time monthdays <1-31> | not <1-31> | startdate month <WORD> <1-31> <2001-2037>| [starttime <hh:mm:ss>] | stopdate month <WORD> <1-31> <2001-2037> | stoptime <hh:mm:ss> | utc | weekedays <DAY> | not <DAY>}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-pbr-rules)
{**description <LINE> |**	Configure policy rule description.
log-enable |	Logs packet matching the rule.
match [destination address <A.B.C.D> <A.B.C.D> | not <A.B.C.D> <A.B.C.D> | start <A.B.C.D> stop <A.B.C.D>] | [port <1-65535>| not <1-65535> | start <1-65535> stop <1-65535>] | [fragment | fragment | non-fragment] | [icmp type <0-255> code <0-255>] | [ipsec ipsec |non-ipsec] | [protocol <0-255> ah | dccp | dsr | egp | eigrp | encap | esp | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipc6-icmp | ipv6-nonxt | ipv6-opts |	Configure match values as define to the routing table.

ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | not | osfp | pim | rdp | rohc | rsvp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp] | [recent count *<1-255>* | time *<1-4294967295>*] | [source address *<A.B.C.D>* *<A.B.C.D>* | not *<A.B.C.D>* | start *<A.B.C.D>* stop *<A.B.C.D>* | mac-address *<H.H.H>* | not *<A.B.C.D>* | [state established disable | enable] | [invalid disable | enable] | [new disable | enable] | related tcp-flags ack | all | fin | psh | rst | syn | urg | not |	
set action drop | [dscp af11 | af12 | af13 | af21 | af22 | af23 | af31 | af32 | af33 | af41 | af42 | af43 cs1 | cws2 | cs3 | cs4 | cs5 | cs6 | cs7 ef] | mark *<1-2147483647>* | [routing-table *<1-200>* | main] | tcp-mss *<500-1460>* | pmtu | *<500-1460>*|	Sets action for policy rules.
time monthdays *<1-31>* | not *<1-31>*] | startdate month *<WORD>* *<1-31>* *<2001-2037>* | [starttime *<hh:mm:ss>*] | stopdate month *<WORD>* *<1-31>* *<2001-2037>* | stoptime *<hh:mm:ss>* | utc | weekedays *<DAY>* | not *<DAY>*}	Configure the time to match the rules.
Command Modes	Perle(config-pbr-rules)#

Usage Guidelines

Use these commands to set policy rules.

Examples

This example sets the action for the packets that match defined rule.

```
Perle(config-prb-rules)# set action drop
```

This example uses policy-based routing to route all HTTP traffic protocol tcp, destination port 80 through a policy route called http-firewall.

```
Perle(config)# ip route  0.0.0.0 0.0.0.0 10.10.200.9
Perle(config)#i p route table 2 0.0.0.0 0.0.0.0 172.16.0.8

Perle(config-prb)# ip route-policy http-firewall
Perle(config-prb))# rule 2
Perle(config-prb-rules)# set routing-table 2
Perle(config-prb-rules)# match protocol tcp
Perle(config-prb-rules)# match destination port 80

Perle(config)# interface ethernet 1
Perle(config-if)# ip address 192.168.2.1 255.255.255.0
Perle(config-if)# ip policy route-policy http-firewall
```

ip scp

ip scp

{**password 0** ***<LINE>*** **| 7** ***<WORD>*** **|** ***<LINE>*** **| username** ***<WORD>***}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip scp
{**scp password 0** ***<LINE>*** **| 7** ***<WORD>*** **|** ***<LINE>*** **| username** ***<WORD>***}	Configure SCP password and username.
Command Modes	Perle(config)#ip scp

Usage Guidelines

Use this command to configure the username and password to enable the router to securely copy files from a remote workstation.

Examples

This example configures the username for a connection to a remote host.

```
Perle(config)#ip scp username lynlab
```

ip sftp

ip sftp

{**username** ***<WORD>*** **| password <0** ***<LINE>*** **| 7** ***<LINE>*** **|** ***<LINE>***}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip sftp

{**username** ***<WORD>*** | **password <0** ***<LINE>*** | **7** ***<LINE>*** | ***<LINE>***}	SFTP configuration commands.

Command Modes	Perle(config)#ip stfp

Usage Guidelines

Use this command to create a SFTP secure connection to a remote host.

Examples

This example configures a username fred.

Perle(config)#ip sftp username fred

ip ssh

ip ssh

{**authentication-retries** ***<0-5>*** |

client algorithms mac hmac hmac-sha1 | hmac-sha1-etm@openssh.com | hmac-sha2-256 | hmac-sha2-256-etm@openssh.com | hmac-sha2-512 | hmac-sha2-512 -etm@openssh.com | umac-128-etm@openssh.com | umac-128@openssh.com | 64-etm@openssh.com | umac-64@openssh.com |

pubkey-chain |

server algorithm encryption 3des-cbc aes128-cbc aes128-ctr aes128-gcm@openshh.com aes192-cbc aes192-ctr aes256-cbc aes256-ctr aes256-gmc@openssh.com arcfour arcfour128 arcfour256 blowfish-cbc cast128-cbc | chacha2--poly1305@openssh.com rijndael-cbc@lysator.liu.se | mac hamc-md5 | hmac-md5-96 | hmac-md5-96-etm@openssh.com | hmac-md5-etm@openssh.com | hmac-ripemd160 | hmac-ripemd160-etm@openssh.com | hmac-sha1 | hmac-sha2-256 | hmac-sha2-256-etm@openssh.com |hmac-sha2-512 | hmac2-512-etm@openssh.com | umac-128-etm@openssh.com | umac-128@openssh.com | umac-64-etm@openssh.com | umac-64@openssh.com |

server [algorithm encryption 3-des-cbc aes128-cbc aes128-ctr aes128-gcm@openssh.com aes192-cbc aes192-ctr aes256-cbc aes256-ctr aes256-gcm@openssh.com chacha20-poly1305@openssh.com rijndael-cbc@lysator.liu.se] | authentication-method keyboard-interactive | password | public-key |

stricthostkeycheck |

time-out ***<120>***}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip ssh
{**authentication-retries** ***<0-5>*** |	Configure ssh authentication retires. Values are 1 to 5 Default is 3

client algorithms mac hmac hmac-sha1 | hmac-sha1-etm@openssh.com | hmac-sha2-256 | hmac-sha2-256-etm@openssh.com | hmac-sha2-512 | hmac-sha2-512 -etm@openssh.com | umac-128-etm@openssh.com | umac-128@openssh.com | 64-etm@openssh.com | umac-64@openssh.com |	Configure the SSH client parameters.
pubkey-chain |	Configure to use a public key-chain.
server algorithm encryption 3des-cbc | aes128-cbc | aes128-ctr | aes128-gcm@openshh.com | aes192-cbc | aes192-ctr | aes256-cbc | aes256-ctr | aes256-gmc@openssh.com | arcfour | arcfour128 | arcfour256 | blowfish-cbc | cast128-cbc | chacha2--poly1305@openssh.com | rijndael-cbc@lysator.liu.se | mac hamc-md5 | hmac-md5-96 | hmac-md5-96-etm@openssh.com | hmac-md5-etm@openssh.com | hmac-ripemd160 | hmac-ripemd160-etm@openssh.com | hmac-sha1 | hmac-sha2-256 | hmac-sha2-256-etm@openssh.com |hmac-sha2-512 | hmac2-512-	
etm@openssh.com | umac-128-etm@openssh.com | umac-128@openssh.com | umac-64-etm@openssh.com | umac-64@openssh.com |	Configure the SSH server parameters.

server [algorithm encryption 3-des-cbc aes128-cbc aes128-ctr aes128-gcm@openssh.com aes192-cbc aes192-ctr aes256-cbc aes256-ctr aes256-gcm@openssh.com chacha20-poly1305@openssh.com rijndael-cbc@lysator.liu.se] | authentication-method keyboard-interactive | password | public-key |	Configure algorithms used for SSH server. Specify the authentication method
stricthostkeycheck |	Enables SSH server authentication.
time-out *<120>*	Configure SSH login time out interval. Values are 1 to 120 seconds. Default is 20 seconds
Command Modes	Perle(config)#ip ssh

Usage Guidelines

The SSH protocol enables you to set up SSH connections. Yourrouter supports both client and server modes.

Examples

This example sets server mode for encryption hmac-md5.

Perle(config)#ip ssh server algorithm mac hmac-md5

Related Commands

telnet

ip ssh

show ssh

ip tacacs

ip tacacs

{**tacacs source-interface bvi *<1-9999>* | cellular *<0-0>* | dialer *<0-15>* |dot11radio*<0-4>* | ethernet *<1-5>* . *<1-4000>* | openvpn-tunnel *<0-999>* | tunnel *<0-999>***}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip tacacs
{**tacacs source-interface bvi *<0-9999>* | cellular *<0-0>* | dialer *<0-15>* | dot11radio*<0-4>* | ethernet *<1-5>* . *<1-4000>* | openvpn-tunnel *<0-999>* | tunnel *<0-999>***}	Configure the source interface for TACACS+ requests.

Command Modes	Perle(config)#ip tacacs

Usage Guidelines

Use this command to configure for Terminal Access Controller Access Control System (TACACS+) authentication.

Examples

This example configures the source-interface as ethernet 1

Perle(config)#ip tacacs source-interface ethernet 1

Related Commands

clear tacacs

tacacs

ip telnet

ip telnet

{**server**}

Use the no form of this command to negate or set to defaults.

Syntax Description	ip telnet
{**server**}	Enables Telnet server.
Command Modes	Perle(config)#ip telnet

Usage Guidelines

Use this command to config Telnet as the protocol to use for connections to a host. Telnet allows a user at one site to establish a TCP connection to a login server at another site and then pass the keystrokes from one device to the other.

Examples

This example enables telnet server.

Perle(config)#ip telnet server

Related Commands

telnet

show management-access

(management-access-LAN)

(management-access-WAN)

ipv6

ipv6

{**access-list** *<WORD>* |

dhcp pool *<WORD>* |

dns domain *<WORD>* **server** *<X:X:X:X::X>* | **listen-address** *<X:X:X:X::X>* |

firewall *<WORD>* | **ipv6-receive-redirects enable** | **ipv6-src-route enable** | **state-policy [established action accept** | **drop** | **reject]** | **[invalid action accept** | **drop** | **reject]** | **[related accept** | **drop** | **reject]** |
host *<WORD>* | *<X:X:X:X::X>* |
name-server *<X:X:X:X::X>* |
prefix-list *<WORD>* |
radius source-interface bvi *<1-9999>* | **cellular** *<0-0>* **dialer** *<0-15>* | **dot11radio** *<0-4>* | | **ethernet** *<1-5>* **.** *<1-4000>* **openvpn-tunnel** *<0-999>* **tunnel** *<0-999>* |
route *<A.B.C.D>* *<A.B.C.D>* | **bvi** *<1-9999>* **cellular** *<0-0>* **dot11radio** *<0-4>* | **dialer** *<0-15>* **dot11radio** *<0-4>* | **ethernet** *<1-5>.* *<1-4000>* | **open-vpn-tunnel** *<0-999>* | **tunnel** *<0-999>* *<X:X:x:X::X* *<1-255>* | **table** *<1-200>* *X:X:X:X::X/<0-128>* **bvi** *<1-9999>* **cellular** *<0-0>* | **dialer** *<0-15>* **dot11radio** *<0-4>* | **ethernet** *<1-5>.* *<1-4000>* | **null** | **open-vpn-tunnel** *<0-999>* | **tunnel** *<0-999>* *<X:X:x:X::X* *<1-255>* |
route-policy *<WORD>* |
router osfp | **rip** |
tacacs source-interface bvi *<1-9999>* **cellular** *<0-0>* | **dialer** *<0-15>* | **ethernet** *<1-5>.* *<1-4000>* **openvpn-tunnel** *<0-999>* **tunnel** *<0-999>* |
unicast-routing}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ipv6
{**access-list** *<WORD>* |	Configure access list name.
dhcp pool *<WORD>* |	Configure the dhcp pool name.
dns domain *<WORD>* **server** *<X:X:X:X::X>* | **listen-address** *<X:X:X:X::X>* |	Configure DNS domain parameters.
firewall *<WORD>* | **ipv6-receive-redirects enable** | **ipv6-src-route enable** | **state-policy [established action accept** | **drop** | **reject]** | **[invalid action accept** | **drop** | **reject]** | **[related accept** | **drop** | **reject]** |	Configure firewall options.
host *<WORD>* | *<X:X:X:X::X>* |	Configure static host names.
name-server *<X:X:X:X::X>* |	Configure the address of the name server.
prefix-list *<WORD>* |	Configure a prefix-list filter.

radius source-interface bvi ***<1-9999>*** **| cellular** ***<0-0>*** **| dot11radio** ***<0-4>*** **| dialer** ***<0-15>*** **| ethernet** ***<1-5>. <1-4000>*** **openvpn-tunnel** ***<0-999>*** **tunnel** ***<0-999>*** **|**	Configure RADIUS configuration parameters.
route ***<A.B.C.D> <A.B.C.D>*** **| bvi** ***<1-9999>*** **cellular** ***<0-0>*** **| dialer** ***<0-15>*** **dot11radio** ***<0-4>*** **| ethernet** ***<1-5>. <1-4000>*** **| open-vpn-tunnel** ***<0-999>*** **| tunnel** ***<0-999> <X:X:x:X::X <1-255>*** **|** ***table <1-200>*** **|**	Configure static routes.
route-policy ***<WORD>*** **|**	Configure IPv6 route policy name.
router osfp | rip |	Enablea IPv6 routing process.
tacacs source-interface bvi ***<1-9999>*** **| cellular** ***<0-0>*** **| dot11radio** ***<0-4>*** **| dialer** ***<0-15>*** **| ethernet** ***<1-5> . <1-4000>*** **openvpn-tunnel** ***<0-999>*** **tunnel** ***<0-999>*** **|**	Configure TACACS+ configuration parameters.
unicast-routing}	Enables unicast routing.
Command Modes	Perle(config)#ipv6

Usage Guidelines

Use this command to configure IPv6 parameters.

Examples

This example configures the DHCP pool name.

Perle(config)#ipv6 dhcp pool ipv6pool1

Related Commands

show ipv6

(config-ipv6-acl)

{***<1-65535>*** **\|**
deny \| *<X:X:X:X::X/0-128 \|any>* **\|**
permit *<X:X:X:X::X/0-128 \| any>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-ipv6-acl)**

{*<1-65535>* |	Configure the sequence number.
deny *<X:X:X:X::X/0-128 | any>* **exact-match** |	Configure to deny specified packets.
permit *<X:X:X:X::X/0-128 | any>* **exact-match**}	Configure to permit specified packets.

Command Modes Perle(config-ipv6-acl)#

Usage Guidelines

Use this command to configure network packets to deny or permit using Access Control Lists (ACLs).

Examples

This example denies packets from this network.

Perle(config-ipv6-acl)# deny 172.16.0.0/16 exact-match

Related Commands

show ipv6

(config-dhcpv6)

{**address prefix** *<X:X:X:X::X/0-128>* |
dns-server *<X:X:X:X::X>* |
domain-name *<WORD>* |
host *<WORD>* |
lifetime default *<0-4294967294>* **maximum** *<0-4294967294>* **minimum** *<0-4294967294>* |
nis address *<X:X:X:X::X>* | **domain-name** *<WORD>* |
nisp address *<X:X:X:X::X>* | **domain-name** *<WORD>* |
sip address *<X:X:X:X::X>* | **domain-name** *<WORD>* |
sntp address *<X:X:X:X::X>* |
subnet *<X:X:X:X::X/<1-128>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-dhcpv6)**
{**address prefix** *<X:X:X:X::X/0-128* |	Configure the IPv6 address prefix.
dns-server *<X:X:X:X::X>* |	Configure a DNS server for use by clients using this DHCP pool. A DNS server needs to be specified if you want to browse the Internet.

domain-name *<WORD>* |	Configure a domain name.
host *<WORD>* |	Configure the host name.
lifetime default *<0-4294967294>* **maximum** *<0-4294967294>* **minimum** *<0-4294967294>*|	Configure IPv6 DHCP parameters. Value is 0 to 4294967294 Max value is 0 to 4294967294 Min value is 0 to 4294967294
nis address *<X:X:X:X::X>* | **domain-name** *<WORD>* |	Configure the address and domain name of your nis server.
nisp address *<X:X:X:X::X>* | **domain-name** *<WORD>* |	Configure the address and domain name of your nisp server.
sip address *<X:X:X:X::X>* | **domain-name** *<WORD>* |	Configure the address and domain name of your sip server.
sntp address *<X:X:X:X::X>* |	Configure the address of your SNTP server.
subnet *<X:X:X:X::X/<1-128>*}	Configure the subnet.

Command Modes Perle(config)#

Usage Guidelines

Use this command to configure IPv6 DHCP parameters.

Examples

This example sets the dns-server address to 1:2:3:4:5::6.

```
Perle(dhcpv6-config)#dns-server 1:2:3:4:5::6
```

Related Commands

show ipv6

(config-fw6)

{**default-action accept** | **drop** | **reject** \|
description *<LINE>* \|
enable-default-logfile \|
rule *<1-9999>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-fw6)**
{**default-action accept** | **drop** | **reject** |	Configure default action for firewall rules.
description *<LINE>* |	Configure firewall rules description.

enable-default-logfile |	Logs packets matching default action.
rule ***<1-9999>***}	Creates rule number, then goes into sub menu mode.
Command Modes	Perle(config-fw6)#

Usage Guidelines

Use this command to configure IPv6 firewall options.

Examples

This example sets the default action for firewall rules.

```
Perle(config-fw6)# default-action drop
```

Related Commands

show ipv6

(config-fw6-rules)

{**description** ***<WORD>*** \|
disable \|
log-enable \|
match destination [address ***<X:X:X::X/0-128>*** **\| not** ***<X:X:X::X/0-128>*** **\| start** ***<X:X:X::X>*** **stop** ***<X:X:X::X>*****] \| port <1-65535> not** ***<X:X:X::X/0-128>*** **\| start** ***<X:X:X::X>*** **stop** ***<X:X:X::X>*****] \| [fragment fragment \| non-fragment] \| icmp type** ***<0-255>*** **code** ***<0-255>*** **\| typenane address-unreachable \| bad-header \| communication-prohibited \| destination-unreachable \| echo-reply \| echo-request \| neighbour-advertisement \| neighbour-solicitation \| no-route \| packet-too-big \| parameter-problem \| port-unreachable \| route-advertisement \| router-solicitation \| time-exceeded \| ttl-zero-during-reassembly \| ttl-zero-during-transit \| unknown-header-type \| unknown-option] \| ipsec ipsec \| non-ipsec \| [protocol <0-255> \| ah \|dccp \|dsr \| egp \| eigrp \| encap \| esp \| etherip \| ggp \| gre \| hmp \| icmp \| idpr \| igmp \| igp \| p \| ipip \| ipv6 \| ipv6-frag \| ipv6-icmp \| ipv6-nonxt \| ipv6-opts \| ipv6-route \| isis \| l2tp \| manet \| mpls-in-ip \| narp \| not \| ospf pim \| rdp \| roho \|rvsp \| sctp \| sdrp \| shim6 \| skip \| tcp \| udp \| udplite \| vrrp \| xnc-idp] \| [recent count** ***<1-255>*** **\| time** ***<1-4294967295>*****] \|** ***source*** **address** ***<X:X:X::X/0-128>*** **\| not** ***<X:X:X::X/0-128>*** **\| start** ***<X:X:X::X>*** **stop** ***<X:X:X::X>*****] \| [mac-address** ***<H.H.H>*** **not** ***<H.H.H>*****] \| [port** ***<1-65535>*** **\| not** ***<1-65535>*** **\| start** ***<1-65535>*** **\|** ***stop*** ***<1-65535>*****] \| state [established disable \| enable] \| [invalid disable \| enable] \| [new enable \| disable] \| [related disable \| enable] \| tcp-flags ack \| all \| fin \| psh \| rst \| syn \|urg \| not ack \| all \| fin \| psh \| rst \| syn \| urg] \|**
set action drop \| accept \| reject \|
time monthdays ***<1-31>*** **\| not** ***<1-31>*****] \| startdate** ***<MONTH>*** ***<1-31>*** ***<2001-2037>*** **\| stopdate** ***<MONTH>*** ***<1-31>*** ***<2001-2037>*****\| starttime** ***<hh:mm:ss>*** **\| stoptime** ***<hh:mm:ss>*** **\| utc \| weekdays** ***<DAY>*** **\| not** ***<DAY>*****]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-fw6-rules)
{**description** *<WORD>* |	Configure a description for the policy rule.
disable |	Disables the policy rule.
log-enable |	Logs packet matching the rule.
match destination [address *<X:X:X::X/0-128>* **| not** *<X:X:X::X/0-128>* **| start** *<X:X:X::X>* **stop** *<X:X:X::X>***] | port <1-65535> not**	Configure match values as define to the routing table.
<X:X:X::X/0-128> **| start** *<X:X:X::X>* **stop** *<X:X:X::X>***] | [fragment fragment | non-fragment] | icmp type** *<0-255>* **code** *<0-255>* **| typenane address-unreachable | bad-header | communication-prohibited | destination-unreachable | echo-reply | echo-request | neighbour-advertisement | neighbour-solicitation | no-route | packet-too-big | parameter-problem | port-unreachable | route-advertisement | router-solicitation | time-exceeded | ttl-zero-during-reassembly | ttl-zero-during-transit | unknown-header-type | unknown-option] | ipsec ipsec | non-ipsec | [protocol <0-255> | ah |dccp |dsr | egp | eigrp | encap | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | p | ipip | ipv6 | ipv6-frag | ipv6-icmp | ipv6-nonxt | ipv6-opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | not | ospf pim | rdp | roho |rvsp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xnc-idp] recent count** *<1-255>* **| time** *<1-4294967295>***] |** *source* **address** *<X:X:X::X/0-128>* **| not** *<X:X:X::X/0-128>* **| start**	

<*X:X:X::X*> stop <*X:X:X::X*>] | [mac-address <*H.H.H*> not <*H.H.H*>] | [port <*1-65535*> | not <*1-65535*> | start <*1-65535*> | *stop* <*1-65535*>] | state [established disable | enable] | [invalid disable | enable] | [new enable | disable] | [related disable | enable] | tcp-flags ack | all | fin | psh | rst | syn |urg | not ack | all | fin | psh | rst | syn | urg] |	Configure match values as define to the routing table.
set action drop | accept | reject |	Configure packet modifications.
time monthdays <*1-31*> | not <*1-31*>] | startdate <*MONTH*> <*1-31*> <*2001-2037*> | stopdate <*MONTH*> <*1-31*> <*2001-2037*>| starttime <*hh:mm:ss*> | stoptime <*hh:mm:ss*> | utc | weekdays <*DAY*> | not <*DAY*>]}	Configure time parameters.
Command Modes	Perle(config-fw6-rules)#

Usage Guidelines

Use this command to configure firewall rules for IPv6.

Examples

This example sets the action for matched packets.

Perle(config-fw6-rules)# set action accept

Related Commands

show ipv6

(config-pbr6)

{**description** <*LINE*> \|
enable-default-logfile \|
rule <*1-9998*>}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-pbr6)**
description <*LINE*> |	Configure firewall rules description.
enable-default-logfile |	Logs packets matching default action.

rule ***<1-9998>***}	Creates rule number, then goes into sub menu mode.

Command Modes	Perle(config-pbr6)#

Usage Guidelines

Use this command to configure IPv6 firewall options.

Examples

This example sets the default action for firewall rules.

Perle(config-fw6)# default-action drop

Related Commands

show ipv6

(config-pbr6-rules)#

{**description** ***<LINE>*** |
log-enable |
match [destination address ***<A.B.C.D> <A.B.C.D>*** **| not** ***<A.B.C.D> <A.B.C.D>*** **| start** ***<A.B.C.D>*** **stop** ***<A.B.C.D>*****] | [port** ***<1-65535>*****| not** ***<1-65535>*** **| start** ***<1-65535>*** **stop****<1-65535>*****] | [fragment | fragment | non-fragment] | [icmp type** ***<0-255>*** **code** ***<0-255>*****] | [ipsec ipsec |non-ipsec] | [protocol <0-255> ah | dccp | dsr | egp | eigrp | encap | esp | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipc6-icmp | ipv6-nonxt | ipv6-opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | not | osfp | pim | rdp | rohc | rsvp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp] | [recent count** ***<1-255>*** **| time** ***<1-4294967295>*****] | [source address** ***<A.B.C.D> <A.B.C.D>*** **| not** ***<A.B.C.D>*** **| start** ***<A.B.C.D>*** **stop** ***<A.B.C.D>*** **| mac-address** ***<H.H.H>*** **| not** ***<A.B.C.D>*** **| [state established disable | enable] | [invalid disable | enable] | [new disable | enable] | related tcp-flags ack | all | fin | psh | rst | syn | urg | not** |
set action drop | [dscp af11 | af12 | af13 | af21 | af22 | af23 | af31 | af32 | af33 | af41 | af42 | af43 | cs1 | cs2 | cs3 | cs4 | cs5 | cs6 | |cs7 ef] | mark ***<1-2147483647>*** **| [routing-table** ***<1-200>*** **| main] | tcp-mss** ***<500-1460>*** **| pmtu |** ***<500-1460>*** |
time monthdays ***<1-31>*** **| not** ***<1-31>*** **| startdate month** ***<WORD> <1-31> <2001-2037>*****| [starttime** ***<hh:mm:ss>*****] | stopdate month** ***<WORD> <1-31> <2001-2037>*** **| stoptime** ***<hh:mm:ss>*** **| utc | weekedays** ***<DAY>*** **| not** ***<DAY>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-pbr6-rules)#**
{**description** ***<LINE>*** |	Configure policy rule description.
log-enable |	Logs packet matching the rule.

match [destination address *<A.B.C.D>* *<A.B.C.D>* | not *<A.B.C.D>* *<A.B.C.D>* | start *<A.B.C.D>* stop *<A.B.C.D>*] | [port *<1-65535>*| not *<1-65535>* | start *<1-65535>* stop*<1-65535>*] | [fragment | fragment | non-fragment] |	Configure match values as define to the routing table.
[icmp type *<0-255>* code *<0-255>*] | [ipsec ipsec |non-ipsec] | [protocol *<0-255>* ah | dccp | dsr | egp | eigrp | encap | esp | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipc6-icmp | ipv6-nonxt | ipv6-opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | not | osfp | pim | rdp | rohc | rsvp | sctp | sdrp | shim6 | skip | tcp | udp | udplite | vrrp | xns-idp] | [recent count *<1-255>* | time *<1-4294967295>*] | [source address *<A.B.C.D>* *<A.B.C.D>* | not *<A.B.C.D>* | start *<A.B.C.D>* stop *<A.B.C.D>* | mac-address *<H.H.H>* | not *<A.B.C.D>* | [state established disable | enable] | [invalid disable | enable] | [new disable | enable] | related tcp-flags ack | all | fin | psh | rst | syn | urg | not |	
set action drop | [dscp af11 | af12 | af13 | af21 | af22 | af23 | af31 | af32 | af33 | af41 | af42 | af43 cs1 | cws2 | cs3 | cs4 | cs5 | cs6 | cs7 ef] | mark *<1-2147483647>* | [routing-table *<1-200>* | main] | tcp-mss *<500-1460>* pmtu | *<500-1460>* |	Sets action for policy rules.

time monthdays *<1-31>* | not *<1-31>* | startdate month *<WORD>* *<1-31>* *<2001-2037>*| [starttime *<hh:mm:ss>*] | stopdate month*<WORD>* *<1-31>* *<2001-2037>* | stoptime *<hh:mm:ss>* | utc | weekedays *<DAY>* | not *<DAY>*}	Configure the time to match the rules.

Command Modes	Perle(config-pbr-rules)#

Usage Guidelines

Use this command to set IPv6 routing rules.

Examples

This example sets rule to match icmp type 80 code 80.

Perle(config-prb-rules)#match icmp type 80 code 80.

Related Commands

show ipv6

(config-rtr)—OSPF

{**ospf [area *<0-4294967295>* \| *<A.B.C.D>*] \| export-list *<WORD>* \| import-list *<WORD>* \| nssa [default-information-originate no summary] \| range *<X:X:X:X::X>/<0-128>* \| stub no-summary \|**

interface bvi *<1-9999>* cellular <0-0> \| dialer *<0-15>*\| dot11radio <0-4> \| ethernet <1-5>. *<1-4000>* \| tunnel *<0-999>* \|

redistribute connected bgp route-map *<WORD>* \| connected route-map *<WORD>* kernel route-map *<WORD>* \| rip route-map *<WORD>* \| static route-map *<WORD>* \|

router-id *<A.B.C.D>* }

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-rtr)-OSPF**

{**ospf [area** ***<0-4294967295>*** **| <** ***A.B.C.D*** **> | export-list <** ***WORD*** **> | import-list <** ***WORD*** **> | nssa [default-information-originate no summary] | range <** ***X:X:X:X::X*** **>/<** ***0-128*** **> | stub no-summary |**	Configure OSPF area parameters. **Area**—OSPF area ID in decimal format or IP address format **NSSA** • default-information-originate–originate Type 7 default into NSSA area • No summary—NSSA ABBRs, the origination of the default route is conditioned to the existence of a default route in the RIB that wasn't learned via the OSPF protocol. **Range**—Summarize routes matching address/mask (border routers only) **Stub**–no-summary–do not send summary LSA into stub area
interface bvi < ***1-9999*** **> cellular <0-0> | dialer <** ***0-15*** **>| dot11radio <0-4> | ethernet <1-5>. <** ***1-4000*** **> | tunnel <** ***0-999*** **>** |	Specify the interface to use with OSFP.
redistribute connected bgp route-map < ***WORD*** **> | connected route-map <** ***WORD*** **> kernel route-map <** ***WORD*** **> | rip route-map <** ***WORD*** **> | static route-map <** ***WORD*** **>** |	Redistribute information from other routing protocol.
router-id < ***A.B.C.D*** **>**}	

Command Modes	Perle(config-router)#

Usage Guidelines

Use this command to configure OSPF protocol parameters.

Examples

This example sets ethernet 1 to OSPF.

Perle(config-rtr)#interface ethernet 1

Related Commands

show ip ospf

(config-rtr)—RIP

{**aggregate-address <** ***A.B.C.D*** **> <** ***A.B.C.D*** **> as-set summary-only** \|
exit-address-family \|

maximum-path *<1-255>* | **ibgp** *<1-255>* |

neighbour *<A.B.C.D>* *<X:X:X:X::X>* **advertisement-interval** *<0-600>* | **allowas-in** *<1-10>* | **[asoverride]** | **[attribute-unchanged as-path | med | next-hop]** | **[capability dynamic | orf prefix-list both | receive | send]** | **[default originate route-map** *<NAME>*] | **[description** *<LINE>*] | **[disable-connected-check** | **[distributed-list** *<1-99>* **in | out** *<1300-2699>* **in | out]** | **[dont't-capability-negotiate]** | **[ebgp-multihop** *<1-255>*] | **[filter-list** *<WORD>*] | **[local-as** *<1-4294967295>* **no-prepend]** | **[maximum-prefix** *<1-4294967295>*] | **[next-hop-self]** | **[override-capability]** | **[passive]** | **[password** *<LINE>*] | **[port** *<1-65535>*] | **[prefix-list** *<WORD>*] | **[remote-as** *<1-4294967295>*] | **remove-private-as** | **[route-map** *<WORD>* **in | out]** | **[route-reflector -client]** | **[route-server-client]** | **[send-community both | extended | standard]** | **[shutdown]** | **[soft-reconfiguration]** | **[strict-capability-match]** | **[timers** *<0-65535>* *<0-65535>* | **connect** *<0-65335>*] | **[ttl-security]** | **[unsuppress-map** *<WORD>*] | **update-source interface bvi** *<1-9999>* | **cellular** *<0-0>* | **dialer** *<0-15>* | **dot11radio** *<0-4>* | **ethernet** *<1-5>. <1-4000>* | **openvpn-tunnel** *<0-999>* | **tunnel** *<0-999>* | *<X:X:X:X::X>*] | **weight** *<1-65335>* |

network *<A.B.C.D>* **backdoor | mask** *<A.B.C.D>* | **route-map** *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-rtr)-RIP
{**aggregate-address** *<A.B.C.D>* *<A.B.C.D>* **as-set summary-only** |	Specifies the block of addresses to be aggregated. **as-set**—specifies that the routes resulting from the aggregation include the AS-set. **summary-only**—specifies that aggregated routes are summarized. These routes will not be advertised.
exit-address-family |	Exit family level menu.
maximum-path *<1-255>* | **ibgp** *<1-255>* |	Configure the maximum number of eBGP/iBGP paths to a destination. ebgp values are 1 to 255 Default is 1 ibgp values are 1 to 255 Default is 1

neighbour *<A.B.C.D>* *<X:X:X:X::X>* advertisement-interval *<0-600>* | allowas-in *<1-10>* | [asoverride] | [attribute-unchanged as-path | med | next-hop] | [capability dynamic | orf prefix-list both | receive | send] | [default originate route-map *<NAME>*] | [description *<LINE>*] | [disable-connected-check | [distributed-list *<1-99>* in | out *<1300-2699>* in | out] | [dont't-capability-negotiate] | [ebgp-multihop *<1-255>*] | [filter-list *<WORD>*] | [local-as *<1-4294967295>* no-prepend] | [maximum-prefix *<1-4294967295>*] | [next-hop-self] | [override-capability] |[passive] | [password	Configure neighbor configuration. **neighbor address**—specify an IPv4 or IPv6 address. **advertisement-interval**—configure the minimum interval between sending BGP routing updates. Values 0 to 600 Default eBGP is 30 secs Default iBGP peers is 5 seconds **allowas-in**—allows or disallows receiving BGP advertisements containing the AS path of the local router. Default readvertisement is disabled. Default is 3 **as-override**—override ASN's in outbound updates if AS–path equals remote–AS. Only applies to eBGP neighbor. Default is disable

***<LINE>*]| [port *<1-65535>*] | [prefix-list *<WORD>*] | [remote-as *<1-4294967295>*] | remove-private-as | [route-map *<WORD>* in | out] | [route-reflector -client] | [route-server-client] | [send-community both | extended | standard] | [shutdown] | [soft-reconfiguration] | [strict-capability-match] | [timers *<0-65535>* *<0-65535>* | connect *<0-65335>*] | [ttl-security] | [unsuppress-map *<WORD>*] |**	**attribute-unchange—**allows the router to send updates to a neighbor with unchanged attributes. Value is on for all if no option provided Default is disabled **capability**—advertise dynamic capability to this neighbor. Default is session is brought up with minimal capability on both sides **capability orf prefix-list [both | receive | send]—**advertises support for Outbound Route Filtering (OFR) for updating BGP capabilities advertised and received from this neighbor. Default is the session is brought up with minimal capability on both sides. **default-originate—**enables or disables forwarding of the default route to a BGP neighbor. Default is disabled **Description**—provide a description for a BGP neighbor. **disable-connected-check**—Enables a directly connected eBGP neighbor to peer using a loopback address without adjusting the default TTL of 1. Default is off **distributed-list**—applies an access list to filter inbound/outbound routing updates from this neighbor. Default is none **dont't capability-negotiate—**disables BGP capability negotiation Default is capability negotiation is performed. **ebgp-mulihop**—Allows you to establish eBGP peer relationships between routers that aren't directly connected to one another. Default is only directly connected neighbors are allowed **filter-list—**applies an AS–path list to routing updates to this neighbor Default is none

local-as—defines a local autonomous system number for eBGP peering
Default is none

maximum-prefixes—configure the maximum number of prefixes to accept from this neighbor before that neighbor is taken down.

Values are 1–4294967295
Default is none

next-hop-self—sets the local router as the next ho for this neighbor
Default is disable

over-ride-capability—overrides capability negotiation to allow a peering session to be established with a neighbor that does not support capabilities negotiation
Default is a session cant be established if the neighbor does not support capability negotiation

passive—directs the router not to initiate connections with this neighbor

password—Configure a BGP MD5 password
Default is none

port—specifies the port on which the neighbor is listening for BGP signals
Values are 1 to 65535
Default port is 179

prefix-list- applies this prefix list filter updates to/from this neighbor
Default is none

remote-as—Configure the autonomous system number of the neighbor.
Default is none

remove-private-as—directs the router to remove private AS numbers from updates sent to this neighbor (eBGP only)
Default is disable (do not remove)

route-map—applies a route map to filter updates to/from this neighbor
Default is none

route-reflector—specify this neighbor as a route reflector client (iBGP only)
Default is disabled

route-server-client—specify this neighbor as a route server client
Default is disable

send-community—enables or disables the sending of community attributes to the specified neighbor

Value— no type specified send standard attributes
Default is both
shutdown—administratively shuts down a BGP neighbor
Default is disabled

soft-reconfiguration—directs the router to store received routing updates

strict-capability-match—directs the router to strictly match the capabilities of the neighbor
Default is disable

timers—
keepalive interval
Values are 0–-65535
Default is 60 seconds

holdtime

Value are 0-65535
Default is 180 seconds

connect
Values are 0-65535
Default is 120 seconds

ttl-security—Configure the time-to-live (ttl) security hop count. This option and ebgp-multihop cannot be set at the same time
Values are 1 to 254 hops
Default is 1

unsupress-map—directs the router to selectively advertise routes suppressed by aggregating addresses, based on a route map

Value specify a router map
Default is none

update-source—specifies the source ip address or interface for routing updates
Default is none

	weight—defines a default weight for routes from this neighbor Values are 1-65335 Default is routes learned from a BGP neighbor have a weight of 0. Routes sourced by the local router have a weight of 32768
network *<A.B.C.D>* **backdoor | mask** *<A.B.C.D>* **| route-map** *<WORD>*}	Configure a network to be advertised by the BGP routing process. **Backdoor**—indicates that this network is reachable by a back door rote. A back door network is considered to be like a local network but is not advertised. **Route-map**—specifies a configured route map to be used when advertising the network Default is none

key

key

{**chain** *< WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**key**
{**chain** *< WORD>*}	Configure keychain management.
Command Modes	Perle(config)#key

Usage Guidelines

Use this command to create a key chain. Key chain management allows you to create and maintain key chains, which are sequences of keys (sometimes called shared secrets). You can use key chains with features that secure communications with other devices by using key-based authentication.

Examples

This example create key chain 1, then go into sub menu key.

```
Perle(config)#key chain key1
```

Related Commands

(config-keychain-key)

(config-key)

{**key** *<1-2147483647>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-key)**

{**key** *<1-2147483647>*}	Configure a number for this key.
Command Modes	Perle#(config-key)#

Usage Guidelines

Use this command in conjunction with (config-keychain-key) to set a key number.

Examples

Configures a key number.

Perle(config-key)# key 250

Related Commands

(config-pbr6-rules)#

(config-keychain-key)

(config-keychain-key)

{**string 0** *<WORD>* | **7** *<WORD>* | *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-keychain-key)**
{**string 0** *<WORD>* | **7** *<WORD>* | *<WORD>*}	Configure the key chain. 0–specifies an unencrypted password 7–specifies a hidden password with follow WORD–the unencrypted (cleartext) user password.
Command Modes	Perle(config-keychain-key)

Usage Guidelines

Use this command to configure a password for key chain.

Examples

Configure a password for key chain.

Perle(config-keychain-key)# string password123

Related Commands

(config-pbr6-rules)#

ldap

ldap

{**server** *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ldap
{**server** ***<WORD>***}	Configure LDAP server name.
Command Modes	Perle(config)#ldap

Usage Guidelines

Use this command configure an LDAP server.

Examples

This example configures a LDAP server name.

```
Perle(config)# ldap server testldap
```

Related Commands

(config-ldap-server)
clear ldap
show ldap

(config-ldap-server)

{**base-dn** ***<WORD>*** |
bind authenticate root-dn ***<WORD>*** **password 0** ***<WORD>*** | **7** ***<WORD>*** |
<WORD> |
ipv4 ***<WORD>*** | ***<A.B.C.D>*** |
ipv6 ***<WORD>*** | ***<X:X:X:X::X:X>*** |
mode server |
search-filter ***<WORD>*** |
secure cipher | **transport port** ***<1-65535>*** | **trustpoint** ***<WORD>*** |
timeout retransmission ***<1-65535>***
transport port ***<1-65535>*** |
user-attribute other ***<WORD>*** | **samaccountname** | **uid**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-ldap-server)
{**base-dn** ***<WORD>*** |	Configure the Base DN for LDAP. The Base DN is the starting point an LDAP server uses when searching for user authentication within your Directory.
bind authenticate root-dn ***<WORD>*** **password 0** ***<WORD>*** | **7**<***WORD***> | ***<WORD>*** |	Configure • An authenticated bind is performed when a root distinguished name (DN) and password are available • In the absence of a root DN and password, an anonymous bind is performed

ipv4 ***<WORD>*** **|** ***<A.B.C.D>*** **|**	Configure the IPv4 address of LDAP server.
ipv6 ***<WORD>*** **|** ***<X:X:X:X::X>*** **|**	Configure the IPv6 address of LDAP server.
mode secure |	Set the server mode. • secure – configures the LDAP to initiate the transport layer security (TLS) connection and specifies the secure mode • non-secure Default is non-secure
search-filter ***<WORD>*** **|**	Configure a search filter The search filter operation must be supported on the LDAP server. Filters are to restrict the numbers of users or groups that are permitted to access an application. In essence, the filter limits what part of the LDAP tree the application syncs from. A filter can and should be written for both user and group membership. This ensures that you are not flooding your application with users and groups that do not need access.
secure cipher | transport port ***<1-65535>*** **| trustpoint** ***<WORD>*** **|**	Configure • ciphers—adh, dh, dss, edh, high, medium, rsa, sslv3 • transport—listening port for secure connections • trustpoint Default listening port for secure transfer connections is 636
timeout retransmission ***<1-65535>*** **|**	Configure the timeout for retransmissions. Values are 1 to 65535 Default is 30 seconds
transport port ***<1-65535>***	Configure the listening port for unsecured connections. Default port is 389
user-attribute other ***<WORD>*** **| samaccountname | uid**}	Configure the user attribute. • other—configure custom usr attibute • sAMAccountName— Microsoft Active Directory • uid—OpenLDAP
Command Modes	Perle(config-ldap-server)#

Usage Guidelines

Use this command to configure LDAP server parameters.

Examples

Search filter for LDAP

For example, if your users are distinguished by having two objectClass attributes (one equal to 'person' and another to 'user'), this is the command to match for it.

Perle(config-ldap-server) #search-filter (&(objectClass=person)(objectClass=user))

Search filter for Microsoft Active Directory

This only synchronize users in the 'Warehouse' group—this should be applied to the User Object Filter:

Perle(config-ldap-server) #search-filter (&(objectCategory=Person)(sAMAccountName=*)(memberOf=cn=CaptainPlanet,ou=users,dc=company,dc=com))

Related Commands

aaa

show ldap

clear ldap

ldap

(config-sg-ldap)

line

line

{**console** *<0-0 >* |

tty *<1-2>* |

vty *<0-15>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	line
{**console** *<0-0>* |	Command for line console/tty only exist on models with serial ports. Primary terminal line. See ***(config-line)#console***
tty *<1-2>*	Terminal/serial. See ***(config-line)#tty***
vty *<0-15>*}	Virtual terminal.
Command Modes	Perle(config)#line

Usage Guidelines

Use this command to change to line mode configuration.

Examples

Go into line configuration mode for tty 2.

Perle(config)# tty 2

Related Commands
(config-line)#console
(config-line)#tty

lldp

lldp

{**hold-mult** *<2-10>* |
logging |
notification-interval |
optional-tlv port-info |
reinit *<1-10>* |
run |
timer |
tvl-select mac-phy-cfg| managemnt-address *<A.B.C.D>* | *<X:X:X:X:X>*| **max-frame-size | port-description | system capabilities | system description | system-name** |
tx-delay}

Syntax Description	lldp
{**hold-mult** *<2-10>* |	Configure a value for the LLDP hold multiplier. This is the time to cache learned LLDP information before discarding, measured in multiples of the timer parameter.
	For example, if the Timer is 30 seconds, and the Hold Multiplier is 4, then the LLDP packets are discarded after 120 seconds. Default is 4 Values are 2 to 10
logging |	Configure logging for LLDP neighbor discovery. Default is off.
notification-interval |	Configure the minimum interval between LLDP SNMP notifications. Default is 5 seconds Value is 5 to 3600 seconds
optional-tlv port-info |	Reverts to the previous setting of providing the interface name.

reinit ***<1-10>*** **|**	Configure the delay (in sec) for LLDP initializations on any interface. Default is 2 seconds Values are 1 to 10 seconds
run |	Enables LLDP. LLDP Disabled by default.
timer |	Configure the rate at which LLDP packets are sent. This parameter is used with the TX Hold multiplier parameter to determine when LLDP packets are discarded. Default is 30 seconds Values are 5 to 32768 seconds
tvl-select mac-phy-cfg | managemnt-address ***<A.B.C.D>*** **|** ***<X:X:X:X:X>*** **| max-frame-size | port-description | system capabilities | system description | system-name |**	Configure the LLDP TLVs to send. Default is all TLVs are sent. Maximum management addresses are 8. Default management addressees are automatically selected by LLDP.
tx-delay}	Configure the amount of time in seconds that passes between successive LLDP frame transmissions due to changes in the LLDP local systems MIB. Default is 30 seconds Values are 1 to 8192 seconds
Command Modes	Perle(config)#lldp

Usage Guidelines

Use this command to configure Link Layer Discovery Protocol (LLDP) parameters., LLDP allows network devices to advertise their identity and capabilities on a LAN. LLDP specifically defines a standard method for Ethernet network devices such as switches, routers, and wireless LAN access points to advertise information about themselves to other nodes on the network and store the information they discover. LLDP should be enabled in a multi-vendor network.

Examples

This example enables LLDP.

```
Perle(config)#lldp run
```

Related Commands

clear lldp

show lldp

logging

logging

{*<hostname>* | *<A.B.C.D>* |
alarm *<2-3>* | **major** | **minor** |
buffered *<0-7>* | *<4096-32768>* | **alert** | **critical]** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings** |
console *<0-7>* | *<4096-32768>* | **alert** | **critical]** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings** |
delimiter tcp |
facility auth | **cron** | **daemon** | **kern** | **local0** | **local1** | **local2** | **local3** | **local4** | **local5** | **local6** | **local7** | **lpr** | **mail** | **news** | **sys10** | **sys11** | **sys12** | **sys13** | **sys14** | **sys9** | **syslog** | **user** | **ucp** |
file flash: *<filename>* *<0-7>* | *<4096-32768>* | **alert** | **critical** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings** |
host *<A.B.C.D>* **transport tcp port** *<1-65535>* | **udp port** *<1-65535>* |
monitor *<0-7>* | *<4096-32768>* | **alert** | **critical]** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings** |
on |
origin-id hostname | **ip** | **ipv6** | **string** |
rate-limit *<1-10000>* **except** *<0-7>* | *<4096-32768>* | **alert** | **critical]** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings** |
source interface bvi *<1-9999>* | **cellular** *<0-0>* | **dot11radio** *<0-4>* | **ethernet** *<1-5>*| **openvpn-tunnel** *<0-999>* | **tunnel** *<0-999>* |
trap *<0-7>* | *<4096-32768>* | **alert** | **critical]** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	logging
{*<hostname>* | *<A.B.C.D>* |	Configure the address of the logging host.
alarm *<2-3>* | **major** | **minor** |	Sets the severity alarm level. **major**—immediate action needed (severity 2) **minor**—minor warning conditions (severity 3)
buffered *<0-7>* | *<4096-32768>* | **alert** | **critical]** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings** |	Configure buffered logging parameters.
console *<0-7>* | *<4096-32768>* | **alert** | **critical]** | **debugging** | **emergencies** | **errors** | **informational** | **notifications** | **warnings** |	Configure console logging parameters.

delimiter tcp |	Appends delimiter to syslog messages.
facility auth | cron | daemon | kern | local0 | local1 | local2 | local3 | local4 | local5 | local6 | local7 | lpr | mail | news | sys10 | sys11 | sys12 | sys13 | sys14 | sys9 | syslog | user | ucp |	Configure facility parameter for syslog messages.
file flash: ***<filename> <0-7>*** **|** ***<4096-32768>*** **| alert | critical | debugging | emergencies | errors | informational | notifications | warnings** |	Configure file logging parameters.
host ***<A.B.C.D>*** **transport tcp port <***1-65535***> | udp port <***1-65535***>** |	Configure the syslog server IP address and parameters.
monitor ***<0-7>*** **|** ***<4096-32768>*** **| alert | critical] | debugging | emergencies | errors | informational | notifications | warnings** |	Configure terminal line (monitor) logging parameters.
on |	Enables logging to all enabled destinations.
origin-id hostname | ip | ipv6 | string |	Adds origin ID to syslog messages.
rate-limit ***<1-10000>*** **except** ***<0-7>*** **|** ***<4096-32768>*** **| alert | critical] | debugging | emergencies | errors | informational | notifications | warnings** |	Configure message per second limit.
source interface bvi ***<1-9999>*** **| cellular** ***<0-0>*** **| dot11radio** ***<0-4>*** **| ethernet** ***<1-5>*** **| openvpn-tunnel** ***<0-999>*** **| tunnel** ***<0-999>*** |	Configure the interface for source address in logging transactions.
trap ***<0-7>*** **|** ***<4096-32768>*** **| alert | critical] | debugging | emergencies | errors | informational | notifications | warnings**}	Configure syslog server logging level.

Command Default	logging buffered 4096 debugging logging console debugging logging monitor debugging
Command Modes	Perle(config)#logging

Usage Guidelines

Use this command to enable logging settings.

Examples

This example enables logging to host 172.16.55.88.

Perle(config)#logging 172.16.55.88

Related Commands

show lldp

login

login

{**on-failure every *<1-65535>* | log every *<1-65535>*| trap every *<1-65535>* | [on-success every *<1-65535>* | log every *<1-65535>*| trap every *<1-65535>*]**}

Syntax Description	login
{**on-failure every *<1-65535>* | log every *<1-65535>*| trap every *<1-65535>* |**	Configure options for failed login attempt.
[on-success every *<1-65535>* | log every *<1-65535>*| trap every *<1-65535>*]}	Configure options for successful login attempt.
Command Modes	Perle(config)#login

Usage Guidelines

Use this command to set parameters for users log in attempts.

Examples

This example logs failed login attempts.

Perle(config)#login on-failure

Related Commands

logging

low-power-mode

{**low-power-mode** {**led enable** | **processor enable**}

Syntax Description	low-power-mode
{**led enable** |	Enables low power mode for the LEDs.
processor enable}	Enables low power mode for the processor.
Command Modes	Perle(config)#low-power-mode

Usage Guidelines

Set options for low power mode.

Examples

This example sets low power mode for the LEDs.
Perle(config)#low-power-mode led enable

mac

{**access-list** *<WORD>* |
export *<WORD>* **url flash:** | **ftp:** | **http:** | **https:** | **scp:** | **sftp:** | **tftp:** |
import *<WORD>* **interface bvi** *<1-9999>* | **dot11radio** *<1-4>* |**ethernet** *<1-5>* **.** *<1-4000>* | **url flash:** | **ftp:** | **http:** | **https:** | **scp:** | **stfp:** | **tftp:**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	mac access-list
{**access-list** *<WORD>* |	Configure a MAC access list name.
export *<WORD>* **url flash:** | **ftp:** | **http:** | **https:** | **scp:** | **sftp:** | **tftp:** |	Exports MAC access list to a server.
import *<WORD>* **interface bvi** *<1-9999>* | **dot11radio** *<1-4>* |**ethernet** *<1-5>* **.** *<1-4000>* | **url flash:** | **ftp:** | **http:** | **https:** | **scp:** | **stfp:** | **tftp:**}	Import formats are; • xxxx.xxxx.xxxx—Cisco format where xxxx is 1-4 digits • xx:xx:xx:xx:xx:xx—where xx is 1-2 digits • aabbccddeeff • Import from supported interface • ethernet interfaces • sub-ethernet (VLANs) interfaces • dot11radio (SSID 0-4 in AP mode) • bridge interfaces

Command Default	**Notes:** • There are no defaults when configuring the MAC access-group and policy, but the no/default policy after initial configuration, is Disabled • No and default commands operate the same for all interface types • If there is no MAC access-group specified, the no/default command REMOVES the MAC access-group and policy • If a MAC access-group is specified the default policy: disabled is configured and applied
Command Modes	Perle(config)#mac

Usage Guidelines

Use this command to create a host MAC address list.

Policy descriptions

Permit—allow all MAC addresses in this MAC access list, deny all MAC addressees not in this list.

Deny—deny all MAC addresses in this MAC access list, allow all others not in the list

Disable—not active

MAC address list can also be created by importing CSV files.

Examples

This example assigns access-list eth1-macs to interface ethernet 1with all addresses within the eth1-macs policy to be accepted or permitted on this interface.

```
Perle(config)#interface ethernet 1
Perle(config)#mac-access-list eth1-macs-static
Perle(config-mac-acl)#
```

This example imports a <mac-list-csv.txt> file from host 172.16.4.182 using http protocol.

```
Perle(config)#mac access-list import <mac-list-csv.txt> url http://172.16.4.182/pub/
<mac-list-csv.txt>
Connected to 172.16.4.182.
59 bytes copied in 0.009 seconds (6319 bytes/sec)
Waiting for download to complete . . .
% Successfully processed 4 properly formatted MAC addresses
```

This example exports a <mac-list-csv.txt> file tot 172.16.4.182 using tftp protocol.

```
Perle(config)#mac access-list export <mac-list-csv.txt> url tftp://172.16.4.182/<mac-
list-csv.txt>
Accessing tftp://172.16.4.182//<macs-export-file>
60 bytes copied in 0.003 seconds (21030 bytes/sec)
```

This example imports and permits MAC addresses from BVI interface 10 into bridge-mac-list.

```
Perle(config)#mac access-list import bridge-mac-list interface bvi 10
Perle(config)#interface bvi 10
Perle(config-if)#mac access-group bridge-mac-list permit
```

Related Commands

show mac

(config-mac-acl)

(config-mac-acl)

{**description** ***<LINE>*** |
host src-mac-address ***<H.H.H>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-mac-acl)#**
{**description** ***<LINE>*** |	Configure a MAC access-list description.
host src-mac-address ***<H.H.H>***}	Configure the source address of the host you want to add to this list.
Command Modes	Perle(config-mac-acl)#

Usage Guidelines

Use this command to enter MAC address to this MAC address list.

Examples

This example adds hsot mac address aaaa.bbbb.cccc to the list.

```
Perle(config-mac-acl)#host src-mac-addr aaaa.bbbb.cccc
```

Related Commands

show mac

management-access

management-access {**enable** | **from-lan** | **from-wan**}

Syntax Description	management-access
{**enable** |	Enables management access. Default is enabled
from-lan |	Enters the configuration menu for defining management access from the LAN.
from-wan |	Enters the configuration menu for defining management access from the WAN.
Command Default	LAN—all protocols enabled except SNMP WAN—all protocols are disabled.
Command Modes	Perle(config)#management-access

Usage Guidelines

Use this command to enter the configuration menu for the management access you wish to set.

With in the "from-LAN" and "from-WAN" sub menu, you will be able to enable/disable the following management access methods.

Management Methods are:

- Enable—All management Access methods for this interface
- HTTP—Enable HTTP (Web) management Access for this interface
- HTTPS—Enable HTTPS (Web) management access for this interface
- Telnet—Enable Telnet management access for this interface
- SSH—Enable SSH management access for this interface
- SNMP—Enable SNMP management access for this interface

Related Commands

(management-access-LAN)

(management-access-WAN)

(management-access-LAN)

{**http enable** |
https enable |
snmp enable |
ssh enable |
telnet enable}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(management-access-LAN)

{**http enable** |	Enables devices connected from the LAN side with Role set to LAN to use HTTP to connect to the router.
https enable |	Enables devices connected from the LAN side with Role set to LAN to use HTTPS to connect to therouter.
snmp enable |	Enables devices connected from the LAN side with Role set to LAN to use HTTPS to connect to the router.
ssh enable |	Enables devices connected from the LAN side with Role set to LAN to use ssh to connect to the router.
telnet enable}	Enables devices connected from the LAN side with Role set to LAN to use telnet to connect to the router.
Command Default	All methods are enabled on the LAN side. All methods are disabled on the WAN side.
Command Modes	Perle(config)#management-access-lan

Usage Guidelines

Use this comment to set protocols to allow entry from the LAN side to manage the router.

Examples

This example sets management access telnet for LAN devices.

```
Perle(config)#management-access from-LAN
Perle(management-access-lan)#telnet enable
```

Related Commands

(management-access-LAN)

(management-access-WAN)

(management-access-WAN)

{**http enable** |
https enable |
snmp enable |
ssh enable |
telnet enable}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(management-access-WAN)**

{**http enable** |	Enable devices connected from the WAN side with Role set to WAN to use HTTP to connect to the router.
https enable |	Enables devices connected from the WAN side with Role set to WAN to use HTTPS to connect to the router.
snmp enable |	Enables devices connected from the WAN side with Role set to WAN to use SNMP to connect to the router.
ssh enable |	Enables devices connected from the WAN side with Role set to WAN to use ssh to connect to the router.
telnet enable}	Enables devices connected from the WAN side with Role set to WAN to use telnet to connect to the router.
Command Default	All protocols are disabled.
Command Modes	Perle(config)#management-accessfrom-lan

Usage Guide

Use this command to set protocols to allow entry from the WAN side to manage the router.

Examples

Configure management access for wan devices using ssh.

```
Perle(config)# management-access from-WAN
Perle(config-management-access-WAN)#ssh enable
```

Related Commands

(config-mac-acl)

nat66

nat66

{**prefix outside** ***<X:X:X:X::X:X>***/***<0-128>*** **any inside** ***<X:X:X:X::X:X>***/***<0-128>*** **outside-interface cellular** ***<0-0>*** **\| no-strict**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	nat66
{**prefix outside** ***<X:X:X:X::X:X>***/***<0-128>*** **any inside** ***<X:X:X:X::X:X>***/***<0-128>*** **outside-interface cellular** ***<0-0>*** **| no-strict**}	Configure parameters for NAT66.

Command Modes	Perle(config)# nat66

Usage Guidelines

Use this command to configure NAT66 parameters. In its simplest form, a NAT66 device is attached to two network links, one of which is an "internal" network link and the other of which is an "external" network with connectivity to the global Internet. All of the hosts on the internal network use addresses from a single, locally-routed prefix, and those addresses are translated to/from addresses in a globally-route-able prefix as IP packets transit the NAT66 device.

Examples

This example sets any outside packets with an IPv6 header of 2001:db8:0:2::/64 to be converted to an IPv6 header of 2001:db8:0:12::/64 on outbound interface cellular 0.

nat66 prefix outside 2001:db8:0:2::/64 inside 2001:db8:0:12::/64 outside-interface cellular 0

Related Commands

show nat66

network-watchdog

network-watchdog

{**modem** |**router**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	network-watchdog
{**modem** | **router**}	Configure the watchdog timer.modem or
Command Modes	Perle(config)#network watchdog

Usage Guidelines

Use this command to enter sub-menu mode for watch dog timer. or modem,

Examples

This example takes you to sub-menu mode for watchdog timer feature.

Perle(config)#network-watchdog router

Related Commands

(config-network-watchdog)

(config-network-watchdog)

{**count** *<1-10>* | **enable** | [**fail-action notifications-only** | **notifications-reset**] | **interval** *<1-180>* | **response** *<1-3600>* | **source-interface** [**bvi** *<1-9999>*] | [**cellular** *<0-0>*] | [**dialer** *<0-15>*] | [**dot11radio** *<0-4>*] | [**ethernet** *<1-5>* | [**open-tunnel** *<0-*

999> **| [tunnel *<0-999>*] | [target *<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X>*] | [threshold-count *<1-30>*]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-network-watchdog)
{**count *<1-10>* | enable | [fail-action notifications-only | notifications-reset] | interval *<1-180>* | response *<1-3600>* | source-interface [bvi *<1-9999>*] | [cellular *<0-0>*] | [dialer *<0-15>*] | [dot11radio *<0-4>*] | ethernet *<1-14>*| [open-tunnel *<0-999>*] | [tunnel *<0-999>*] | [target *<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X>*] | [threshold-count *<1-30>*]**}	Configure parameters for network watchdog. **Fail-action** • notify only • notify and reboot **Interval** to wait between tests. Values are 1 to 180 minutes. Default modem is 10 minutes. Default: router is 20 minutes. **Interval** to wait between tests. Values are 1 to 180 minutes. Default modem is 10 minutes. Default router is 20 minutes. **Response**—Time to wait for a response to the ping request. Values are 1 to 3600 seconds. Default is 5 seconds. **Source-interface—**Specify the interface to send the ping request on (optional). Values are: • BVI 1–9999 • cellular 0–0 • dialer 1–15 • dot11radio 0–4 • ethernet ***<1-5>*** • openvpn 0–999 • tunnel 0–999 **Target—**Enter the target host IPv4, IPv6 or hostname address. **Threshold count—**The consecutive failed test count to trigger an Fail-action. Value is 1 to 30
Command Modes	Perle(config-network-watchdog)#

Usage Guidelines

Use this command to configure the Network Watchdog timeout action When configured, the watchdog feature runs continuous ping tests. Each ping test is be comprised of one or more ping attempts. If all of the pings in a test fail, the test has failed, if one ping test passes, the test is considered to have passed.

The watchdog feature is triggered after a successful connection, which is defined as one successful test. After which your tests will run as defined..

If any of the ping test fail, the router and modem notifies the user and/or can reset the router and modem.

Examples

This example configures the watchdog timer on Ethernet interface 2 to ping target host 172.16.1.1 with a count of 10.

Perle(config-network-watchdog)#count 10

Perle(config-network-watchdog)#target 172.16.1.1

Perle(config-network-watchdog)#source interface ethernet 2

Related Commands

show network-watchdog

ntp

ntp

{**authentication** |
authentication-key *<1-65534>* **md5** | **sha1** | **sha256** | **sha512** | *<WORD>* **0** | **7** |
broadcastdelay *<1-999999>* |
gnss |
logging |
lte |
master *<1-15>* | **peer** *<A.B.C.D>* *<WORD>* *<X:X:X:X::X>* **ip** <*hostname-of-peer>* **ipv6** <*hostname-of-peer>* | **key** *<1-65534>* | **maxpoll** *<4-17>* | **minpoll** *<4-17>* | **prefer** | **version** *<1-4>* |
server *<A.B.C.D>* *<WORD>* *<X:X:X:X::X>* **ip** <*hostname-of-peer>* **ipv6** <*hostname-of-peer>* | **key** *<1-65534>* | **maxpoll** *<4-17>* | **minpoll** *<4-17>* | **prefer** | **version** *<1-4>* |
trusted-key *1-65534*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	ntp
{**authentication** |	Configure authentication of time sources. The time sources must authenticate with each other before synchronizing clock time.

authentication-key ***<1-65534>*** **md5 | sha1 | sha256 | sha512 |** ***<WORD>*** **0 | 7 |**	Configure the authentication key to be exchanged between time sources before clock synchronizing begins. 0—unencrypted key 7—encrypted key
broadcastdelay ***<1-999999>*** **|**	Configure the broadcast delay timer. By default, the router sets broadcast delay to Auto-negotiate. Select the auto-negotiate broadcast delay off if you wish to set your own broadcast delay time in microseconds. Broadcast delay time is the estimated round-trip delay between the broadcast NTP server and the router.
gnss |	Configure to use GNSS (GPS) as a time source.
logging |	Logs NTP messages to the router's internal log.
lte |	Configure to use LTE as a time source.
master ***<1-15>*** **| peer** ***<A.B.C.D> <WORD> <X:X:X:X::X>*** **ip** ***<WORD>*** **ipv6** ***<WORD>>*** **| key** ***<1-65534>*** **| maxpoll** ***<4-17>*** **| minpoll** ***<4-17>*** **| prefer | version** ***<1-4>*** **|**	Configure master or peer as the source clock. The stratum defines how far away the clock is away from the Authoritative Time Source. The highest stratum is 1. It is reserved for atomic clocks, GPS clocks or radio clock which generates a very accurate time. This type of time source is defined as the "Authoritative time source". The stratum defines how many hops a node is from the "authoritative time source". Stratum x nodes are synchronized to stratum x-1 nodes.Stratum numbers range from 1 to 15. Configure the IPv4/IPv6 address or hostname of the NTP peer that you are getting the clock from. Select prefer to use this NTP source over another.
	A preferred peer's responses are discarded only if they vary greatly from the other time sources. Otherwise, the preferred peer is used for synchronization without consideration of the other time sources.

server ***<A.B.C.D> <WORD> <X:X:X:X::X>*** **ip** ***<WORD>*** **ipv6** ***<WORD>>*** **| key** ***<1-65534>*** **| maxpoll** ***<4-17>*** **| minpoll** ***<4-17>*** **| prefer | version** ***<1-4>*** **|**	Configure the IPv4/IPv6 address or hostname of the NTP peer that you are getting the clock from. Select prefer to use this NTP source over another. A preferred server's responses are discarded only if they vary greatly from the other time sources. Otherwise, the preferred server is used for synchronization without consideration of the other time sources. Changes to the polling interval is not recommended and is discouraged. NTP dynamically selects the optimal poll interval between the values of minpoll and maxpoll, which defaults to 64 and 1024 seconds respectively and are correct for most environments. Shorter values are used to correct large errors and larger values are to refine accuracy. Default is minimum poll 64. Versions 1 to 4 are supported
trusted-key ***1-65534***}	Configure a trusted key to be used for trusted time sources.
Command Modes	Perle(config)#ntp

Usage Guidelines

Use this command to distribute and maintain synchronization of time information between nodes in a network. NTP server uses UTC (Universal Coordinated Time). When initially launched, it can take NTP as much as 5 minutes to obtain an accurate time.This is due to the algorithm used to determine what NTP master(s) the router should synchronize with. NTP will not synchronize with nodes whose time is significantly off even if its stratum is lower. During this "settling" period, the router may not have the correct time. NTP can usually achieve time synchronization between two systems in the order of a few milliseconds. This is achieved with a time transmission rate of as little as one packet per minute.

Examples

Perle(config)#ntp server 172.16.4.181

```
23:40:31:  %NTPD-5: ntpd 4.2.8p6@1.3265-o Wed May 18 14:33:49 UTC 2016
(10): Starting
23:40:31:  %NTPD-6: Command line: ntpd -n -g
23:40:31:  %RSYSLOGD-6:LOGGINGHOST_STARTSTOP: Logging to UDP host
```

```
172.16.55.88 port 514 started
 23:40:31:  %NTPD-6: proto: precision = 3.840 usec (-18)
 23:40:31:  %NTPD-6: Listen and drop on 0 v6wildcard [::]:123
 23:40:31:  %NTPD-6: Listen and drop on 1 v4wildcard 0.0.0.0:123
 23:40:31:  %NTPD-6: Listen normally on 2 lo 127.0.0.1:123
 23:40:31:  %NTPD-6: Listen normally on 3 Vl1 172.16.113.77:123
 23:40:31:  %NTPD-6: Listen normally on 4 lo [::1]:123
23:40:31:  %NTPD-6: Listen normally on 5 Gi2 [fe80::6ac9:bff:fec1:58da%4]:123
 23:40:31:  %NTPD-6: Listen normally on 6 Gi1 [fe80::6ac9:bff:fec1:58d9%3]:123
 23:40:31:  %NTPD-6: Listen normally on 7 eth0 [fe80::6ac9:bff:fec1:58d8%2]:123
 23:40:31:  %NTPD-6: Listening on routing socket on fd #38 for interface updates
 23:40:31:  %NTPD-3: Unable to listen for broadcasts, no broadcast interfaces
available
 23:40:31:  %NTPD-6: 0.0.0.0 c01d 0d kern kernel time sync enabled
 23:40:31:  %NTPD-6: 0.0.0.0 c012 02 freq_set kernel 0.000 PPM
 23:40:31:  %NTPD-6: 0.0.0.0 c011 01 freq_not_set
 23:40:31:  %NTPD-6: 0.0.0.0 c016 06 restart
Perle(config)#ntp status
Clock is synchronized, stratum 12, reference is 172.16.4.180
Precision is 2**-18 s
Reference time is dae84dc5.33013328 (Thu, May 19 2016 10:35:49.199)
Clock offset is 7.595002 msec, root delay is 0.439 msec
Root dispersion is 7956.293 msec
```

Related Commands

show ntp

policy-map

{*<WORD>* |
priority-queue *<WORD>* |
rate-control *<WORD>* **bandwidth** *<1-2000000>* |
traffic-limit *<1-2000000>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	policy-map
{*<WORD>* |	Specifies the name of the policy map to be created or modified.
priority-queue *<WORD>*|	Configure priority-queue policy-map. See ***(config-pmapPQ)***
rate-control *<WORD>* **bandwidth** *<1-2000000>* |	Configure rate-control policy-map. See ***(config-pmapRC)***
traffic-limit *<1-2000000>*}	Configure traffic-limit policy-map. See (***(config-pmapTL)***
Command Modes	Perle(config)#policy-map

Usage Guidelines

Use this command to create a policy-map. A policy map references class maps and identifies a series of actions to perform based on the traffic match criteria. A policy map essentially defines a policy stating what happens to traffic that has been classified using class maps and ACLs.

Yourrouter provides you with three mechanisms for configuring Quality of Service (QOS).

1) Priority-queuing—packets are placed in queues, high priority packets are sent first.

2) Rate-control—rate control is a classless policy that limits the packet flow to a set rate. Traffic is filtered based on the expenditure of tokens. Tokens roughly correspond to bytes. Short bursts can be allowed to exceed the limit. On creation, the Rate-Control traffic is stocked with tokens which correspond to the amount of traffic that can be burst in one go. Tokens arrive at a steady rate, until the bucket is full.

3) Traffic-limiting—traffic limiting is a mechanism that can be used to "police" incoming traffic. The mechanism assign each traffic flow a bandwidth limit. All incoming traffic within a flow in excess of the bandwidth is dropped.This policy can be applied to both ingress and egress packets.

Examples

Creates a policy-map called test-policy.

```
Perle(config)# policy-map test-policy
Perle(config-pmap)#
```

Related Commands

(config-pmap)
(config-pmap-c)
(config-pmapRC)
(config-pmapPQ)
(config-pmapPQ-c)
(config-pmapTL)

(config-pmap)

{**bandwidth** ***<1-2000000>*** |
class ***<1-4094>*** | **default** |
description ***<LINE>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-pmap)
{**bandwidth** ***<1-2000000>*** |	Configure the available bandwidth in Kbps for this policy. Default is to match interface speed.
class ***<1-4094>*** | **default** |	Configure a class identifier. Values are 1–4094
description ***<LINE>***}	Configure policy map description.

Command Modes	Perle(config-pmap)#

Usage Guidelines

Configure parameters for his policy map.

Examples

Configures class identifier as 10.

```
Perle(config-pmap)#class 10
Perle(config-pmap-c)#
```

Related Commands

policy-map

(config-pmap-c)

(config-pmap-c)

{**bandwidth** ***<1-2000000>*** | **percent** ***<1-100>*** |
burst ***<1-20000>*** |
ceiling ***<1-2000000>*** | **percent** ***<1-100>*** |
codel-flows ***<1-4294967295>*** |
codel-interval ***<1-4294967295>*** |
codel-quantum ***<1-4294967295>*** |
codel-target ***<1-4294967295>*** |
description ***<LINE>*** |
queue-limit ***<1-4294967295>*** |
queue-type ***<1-4294967295>*** |
set-dscp ***<0-63>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-pmap-c)
{**bandwidth** ***<1-2000000>*** |	Configure the base guaranteed bandwidth for this traffic class (in Kbps or in percent). Bandwidth must be below the entire bandwidth set for this policy.
burst ***<1-20000>*** |	Configure the burst size for this class. Values are 1 to 20000 in Kbytes Default is 15 Kbytes

ceiling ***<1-2000000>*** **| percent** ***<1-100>*** **|**	Configure a bandwidth ceiling for a traffic class in Kbps. • Percentage based on interface physical rate • Must be equal or greater then specified bandwidth Default is 100 percent of bandwidth if no ceiling specified.
codel-flows ***<1-4294967295>*** **|**	Configure the number of flows into which the incoming packets are classified. Values are 1 to 4294967295 Default is 1024
codel-interval ***<1-4294967295>*** **|**	Configure the interval to the measured minimum delay as not to become stale. It should be set on the order of the worst-case round trip time (RTT) through the bottleneck to give endpoints sufficient time to react. Values are 1 to 4294967295 milliseconds. Default is 100 milliseconds.
codel-quantum ***<1-4294967295>*** **|**	Configure the maximum amount of bytes dequeued from a queue at once. Values are 1 to 4294967295 Default is 1514
codel-target ***<1-4294967295>*** **|**	Configure the minimum standing/persistent queue delay. Values are 1 to 4294967295 milliseconds Default is 5 milliseconds
description ***<LINE>*** **|**	Configure a description for this traffic class.
queue-limit ***<1-4294967295>*** **|**	Configure the maximum size for this traffic class. Values are 1 to 4294967295 milliseconds Default is none
queue-type |	Configure the type of queuing to use for this traffic class. • fq-code1 • fair-queue • drop-tail • priority • random-detect Default is fair-queue

set-dscp ***<0-63>***}	Rewrites the DSCP field in packets in this traffic class to the specified value. Values are 0–63

Binary value	Configured value	Drop rate	Description
101110	46	-	Expedited forwarding (EF)
000000	0	-	Best effort traffic, default
001010	10	Low	Assured Forwarding(AF) 11
001100	12	Medium	Assured Forwarding(AF) 12
001110	14	High	Assured Forwarding(AF) 13
010010	18	Low	Assured Forwarding(AF) 21
010100	20	Medium	Assured Forwarding(AF) 22
010110	22	High	Assured Forwarding(AF) 23
011010	26	Low	Assured Forwarding(AF) 31
011100	28	Medium	Assured Forwarding(AF) 32
011110	30	High	Assured Forwarding(AF) 33
100010	34	Low	Assured Forwarding(AF) 41
100100	36	Medium	Assured Forwarding(AF) 42
100110	38	High	Assured Forwarding(AF) 43

Default is none

Command Modes	Perle(config-pmap)#

Usage Guidelines

Use this command to specify the Quality of Service (QoS) settings applied to the default class. You configure your default traffic in the same way you do with a class. Default is considered a class as it behaves like that. It contains any traffic that did not match any of the defined classes, so it is like an open class, a class without matching filters.

Examples

Set the queue type for this traffic class to random-detect.

```
Perle(config-pmap)#class 10
Perle(config-pmap-c)#queue-type random-detect
```

Related Commands

policy-map

(config-pmap)

(config-pmapRC)

{**bandwidth** ***<1-2000000>*** |
burst ***<1-20000>*** |
description ***<LINE>*** |
latency ***<1-5000>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-pmapRC)**
{**bandwidth** ***<1-2000000>*** |	Changes configured bandwidth limit.

burst ***<1-20000>*** **|**	Configure a burst size in kbytes. Default is 15Kbps
description ***<LINE>*** **|**	Configure a Policy-Map Rate-Control description.
latency ***<1-5000>***}	Configure the limit on queue size. This is the maximum amount of time a packet can sit in the Token Bucket Filter. Packets with more latency then this value will be dropped since they are no longer considered useful. Value is 1 to 500 milliseconds Default is 50 milliseconds
Command Modes	Perle(config-pmapRC)#

Usage Guidelines

Use this command to configure parameters for Rate-control policy. This policy is egress only.

Rate Control is a classless policy that limits the packet flow to a set rate. It provides queuing on the Token Bucket filter algorithm. This algorithm only passes packets arriving at a rate which does not exceed an administratively set rate. Traffic is filtered based on the expenditure of these tokens.

Tokens roughly correspond to bytes. Short bursts can be allowed to exceed the limit. Once created, the rate control traffic is stocked with tokens which correspond to the amount of traffic that can be burst in one go. Tokens arrive at a steady rate, until the bucket is full—newly arriving tokens are discarded. To send a packet, the regulator must remove from the bucket a number of tokens equal in representation to the packet size.

Examples

Set the latency for this rate-control policy to 100 milliseconds.

```
Perle(config)#policy-map rate-control factory-RC bandwidth 2000
Perle(config-pmapRC)#latency 100
```

Related Commands

policy-map

(config-pmapPQ)

{**class** ***<1-7>*** **| default |**
description ***<LINE>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-pmapPQ)**
{**class** ***<1-7>*** **| default |**	Configure a priority queue class identifier.

description *<LINE>*}	Configure the description of this Priority Queue policy-map.

Command Modes	Perle(config-pmapPQ)#

Usage Guidelines

Use this command to create a Priority-Queue Policy map. This policy is egress only.

Your router has four types of outbound traffic queues based on priority: low, normal, medium, and high. These outbound traffic queues are divided into seven priority queues (see table below). The queue priority determines the order of exit for packets in the queue. For example, the packets in a high priority (6–7) queue leave the router before packets in other queues. If packets continually fill the higher priority queues, those waiting in lower priority queues will not be serviced until the higher priority traffics load finishes.

Priority Assigned to Packet	Port Queue	Priority	Order of Exit
6-7	6-7	High	1
4-5	4-5	Medium	2
0, 3	0, 3	Normal	3
1-2	1-2	Low	4

Examples

This example creates a priority queue called important with a class identifier of 7.

```
Perle(config)#policy-map priority-queue priority
Perle(config-pmapPQ)#class 7trricky sok
```

Related Commands

policy-map

(config-pmapPQ-c)

(config-pmapPQ-c)

{**codel-flows** *<1-4294967295>* |
codel-interval *<1-4294967295>* |
codel-quantum *<1-4294967295>* |
codel-target *<1-4294967295>* |
description *<LINE>* |
queue-limit *<1-4294967295>* |
queue-type drop-tail | fair-queue | fq-code1 | priority | random-detect |
set-dscp *<0-63>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-pmapPQ-c)**
{**codel-flows** *<1-4294967295>* |	Configure the number of flows into which the incoming packets are classified. Values are 1 to 4294967295 Default is 1024

codel-interval ***<1-4294967295>*** **|**	Configure the interval to the measured minimum delay so as not to become stale. It should be set on the order of the worst-case round trip time (RTT) through the bottleneck to give endpoints sufficient time to react. Values are 1 to 4294967295 milliseconds. Default is 100 milliseconds.
codel-quantum ***<1-4294967295>*** **|**	Configure the maximum amount of bytes dequeued from a queue at once. Values are 1 to 4294967295 Default is 1514
codel-target ***<1-4294967295>*** **|**	Configure the minimum standing/persistent queue delay. Values are 1–4294967295 milliseconds Default is 5 milliseconds
description ***<LINE>*** **|**	Configure a policy map class description.
queue-limit ***<1-4294967295>*** **|**	Configure maximum queue size in packets.
queue-type drop-tail | fair-queue | fq-code1 | priority | random-detect |	Specifies the type of queuing to use for this traffic class. • Drop Tail • Fair-queuing • fqcode1 • priority • random-detect
set-dscp ***<0-63>***}	Rewrites the DSCP field in packets in this traffic class to the specified value. Values are 0–63 Default is none

Binary value	Configured value	Drop rate	Description
101110	46	-	Expedited forwarding (EF)
000000	0	-	Best effort traffic, default
001010	10	Low	Assured Forwarding(AF) 11
001100	12	Medium	Assured Forwarding(AF) 12
001110	14	High	Assured Forwarding(AF) 13
010010	18	Low	Assured Forwarding(AF) 21
010100	20	Medium	Assured Forwarding(AF) 22
010110	22	High	Assured Forwarding(AF) 23
011010	26	Low	Assured Forwarding(AF) 31
011100	28	Medium	Assured Forwarding(AF) 32
011110	30	High	Assured Forwarding(AF) 33
100010	34	Low	Assured Forwarding(AF) 41
100100	36	Medium	Assured Forwarding(AF) 42
100110	38	High	Assured Forwarding(AF) 43

Command Modes	Perle(config-pmapPQ-c)#

Usage Guide

Use this command to set parameters for your defined priority queue policy map.

Examples

This example sets the queue-type to fair-queue.

```
Perle(config)#policy-map priority-queue priority-voice
Perle(config-pmapPQ)#class 1
```

Related Commands

policy-map

(config-pmapTL)

{**class** ***<1-4094>*** **bandwidth** ***<1-2000000>*** **| default |**
description ***<LINE>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-pmapTL)
{**class** ***<1-4094>*** **| default |**	Configure a priority queue class identifier or default.
description ***<LINE>***}	Configure the description of this Traffic Limiting policy-map.
Command Modes	Perle(config-pmapTL)#

Usage Guidelines

Use this command to configure the parameters for policy map.This traffic policy mechanism is to "police" in coming traffic. The mechanism assign each traffic flow a bandwidth limit. All incoming traffic within a flow in excess of the bandwidth is dropped.This policy can be applied to both ingress and egress packets.

Examples

Creates a policy-map called test-policy.

```
Perle(config)# policy-map test-policy
Perle(config-pmap
```

Related Commands

policy-map

(config-pmapTL-c)

{**class** *<1-4094>* **bandwidth** *<1-2000000>* | **default** |
description *<LINE>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-pmapTL-c)
{**bandwidth** *<1-2000000>* |	Specifies the base guaranteed bandwidth for this traffic class (in Kbps or in percent). Bandwidth must be below the entire bandwidth set for this policy.
burst *<1-20000>* |	Configure the burst size for this class. Values are 1 to 20000 in Kbytes Default is 15 Kbytes
description	Configure the description of this Traffic Limiting policy-map.
priority	Specifies the order of evaluation of matching rules (the higher the value, the lower the priority). Values are 0 to 20 Default is 20
Command Modes	Perle(config-pmapTL-c)#

Examples

This example sets the bandwidth to 20000 for this traffic class.

```
Perle(config)#policy-map traffic-class test-traffic
Perle(config-pmapTL-c)#class 10
Perle(config-pmapTL-c)#bandwidth 20000
```

Related Commands

policy-map

power

power

{**operation-mode ignition contact** *<1-2>* **standby-voltage** *<1.0-30.0>* **standby-delay** *<1-86400>* **wakeup-voltage** *<1.0-30.0>* **wakeup-delay** *<1-3600>* | **smart-standby** | **standard**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	power

{**operation-mode ignition contact** ***<1-2>*** **standby-voltage** ***<1.0-30.0>*** **standby-delay** ***<1-86400>*** **wakeup-voltage** ***<1.0-30.0>*** **wakeup-delay** ***<1-3600>*** |	Configure standby mode parameters. **Mode of Operation**: • Standard • **Ignition** • Smart Standby **Ignition Mode**—In this mode the router monitors an input to determine if the vehicle ignition switch is turned on or not (see Deployment documentation in the Hardware Installation Guide for your product on how to make appropriate connections). Basically, when the ignition is determined to be on, the router wakes from standby, and when the ignition is determined to be off, it goes into standby mode. **Contact**— The input used for monitoring the ignition voltage. • IGN–Ignition Input on power connector • GPIO–GPIO pin on the power connector Note: The GPIO pin needs to be configured to be an analog input. **Standby voltage—**set minimum voltage value in volts in which the router enters into a standby mode. **Standby delay—**set delay in seconds that voltage must remain below standby voltage before entering standby mode.**Wakeup** **Wakeup Voltage—**set maximum voltage value in volts in which the router wakes up from standby mode. **Wakeup delay—**Set the delay in seconds, in which voltage must remain above/below voltage wake-up before waking up from standby mode.
smart-standby |	Configure standby mode parameters. **Mode of Operation**: • Standard • Ignition • **Smart Standby** Configure Smart-Standby Mode—the router is in Smart Standby Mode based on the parameters configured for condition and expression. See ***(config-smrt-stdby)*** for configuration.

standard}	Configure standby mode parameters. **Mode of Operation**: • **Standard** • Ignition • Smart Standby By default, the router is configured for Standard Mode—no Smart-Standby Mode is configured.
Command Modes	Perle(config)#power

Examples

Configure operation mode of ignition to go into standby mode when voltage is below 1.0 and wakes up from standby mode when the voltage goes above 2.0.

```
Perle(config)# operation ignition contact 1 standby-voltage 1.0 wakeup-voltage 2.0
```

Related Commands

(config-smrt-stdby)

(config-smrt-stdby)

{**condition** ***<1-2>*** **[analog contact** ***<1-2>*** **standby-voltage** ***<1.0-30.0>*** **standby-delay** ***<1-30>*** **wakeup-voltage** ***<1.0-30.0>*** **wakeup-delay** ***<1-3600>*** **| digital |schedule daily wakeup-time** ***<hh:mm>*** **hourly** ***<0-59>*** **standby-time** ***<0-59>*** **recurring** ***<1-99>*** **] | [digital contact <2-2> wakeup-trigger closed | open] delay <1-30>] | schedule daily wakeup-time** ***<hh:mm>*** **| standby-time** ***<hh:mm>*** **| recurring** ***<1-7>*** **| hourly wakeup-time** ***<0-59>*** **| standby-time |**
expression condition ***<1 | 2>*** **and | or condition** ***<1 | 2>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-smrt-stdby)#
{**condition** ***<1-2>*** **[analog contact** ***<1-2>*** **standby-voltage** ***<1.0-30.0>*** **standby-delay** ***<1-30>*** **wakeup-voltage** ***<1.0-30.0>*** **wakeup-delay** ***<1-3600>*** **| digital |schedule daily**	Configure standby mode parameters. **Condition number**—set condition 1 or 2. **Analog**—monitor analog input contacts to trigger Smart Standby Mode **Digital**—monitor digital input contacts to trigger Smart Standby Mode **Schedule**—use the time schedule to trigger Smart Standby Mode.

wakeup-time *<hh:mm>* hourly *<0-59>* standby-time *<0-59>* recurring *<1-99>*] | [digital contact <2-2> wakeup-trigger closed | open] delay <1-30>] | schedule daily wakeup-time *<hh:mm>* | standby-time *<hh:mm>* | recurring *<1-7>* | hourly wakeup-time *<0-59>* | standby-time |	**Contact**— The input used for monitoring the ignition voltage. • IGN–Ignition Input on power connector • GPIO–GPIO pin on the power connector Note: The GPIO pin needs to be configured to be an analog input. **Standby voltage—**set minimum voltage value in volts in which the router enters into a standby mode. **Standby Delay**—If the router detects that the "contact voltage" has remained either "less then" or "greater then" the Standby voltage level for this number of seconds then the router goes into Standby Mode. Default is 30 seconds **Wakeup Voltage—**Set maximum voltage value in volts in which the router wakes up from standby mode. **Wakeup delay—**Set the delay in seconds, in which voltage must remain above/below voltage wake-up before waking up from Standby Mode
expression condition *<1 | 2>* and | or condition *<1 | 2>*}	Configure standby mode condition.
Command Default	Standard
Command Modes	Perle(config-smrt-stdby)#

Usage Guidelines

Use this command to configure parameters for Smart Standby mode.

Examples

Set Smart Standby condition to occur when analog 1 voltage minimum is 1.0 volts.

Perle(config-smrt-stdby)#condition 1 analog contact 1 standby-voltage 1.0

power-supply

power {dual}

This command is only available on IRG5140 models.

Use the no form of this command to negate a command or set to defaults.

Syntax Description	power-supply
{**dual**}	Enables the monitoring of both power supplies.
Command Modes	Perle(config)#power-supply dual

Examples

This example shows you how to configure to monitor for both power supplies.

Perle(config)# power-supply dual

Related Commands

show environment

radius

radius

{**server** *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	radius
{**server** *<WORD>*}	Configure RADIUS server name.
Command Modes	Perle(config)#radius

Usage Guidelines

Use this command to configure the RADUIS server name.

Examples

This example configures the RADIUS server name.

Perle(config)#radius server testrad

Related Commands

clear radius

show radius

(config-radius-server)

{**address ipv4** *<A.B.C.D>* | **acct-port** *<0-65536>* | **auth-port** *<0-65536>* |
key 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |
retransmit *<1-100>* |
timeout *<1-1000>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-radius-server)
{**address ipv4** *<A.B.C.D>* **acct-port** *<0-65536>* | **auth-port** *<0-65536>* |	Configure the RADIUS server address. Default port for authentication is 1812 Default port for accounting is 1813
key 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |	Configure an encryption key to be shared with the RADIUS servers.

retransmit *<1-100>* |	Configure the number of retries to the active RADIUS server. Values are
timeout *<1-1000>*}	Configure the time to wait for the RADIUS server to reply. Values are 1–1000 Default is 5 seconds
Command Modes	Perle(config-radius-server)#

Usage Guidelines

Use this command to configure RADUIS parameters.

Examples

This example sets the timeout to 30 seconds to wait for a reply from a RADIUS server.

```
Perle(config-radius-server)#timeout 5
```

Related Commands

clear radius

show radius

radius-server

radius {**deadtime** *<1-1440>* |
key 0 *<WORD>*7 *<WORD>* | *<WORD>* |
retransmit *<1-100>* |
timeout *<1-1000>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	radius-server
{**deadtime** *<1-1440>* |	Sets the time the router ignores unresponsive RADIUS servers.
key 0 *<WORD>*7 *<WORD>* | *<WORD>* |	Configure an encryption key to be shared with the RADIUS servers.
retransmit *<1-100>* |	Configure the number of retries to the active RADIUS server.
timeout *<1-1000>*	Configure the time to wait for the RADIUS server to reply.
Command Modes	Perle(config)#radius-server

Usage Guidelines

Use this command to configure RADUIS server parameters.

Examples

This example sets the radius server name.

Perle(config)#radius-server

Related Commands

clear radius

show radius

remote-management

remote-management

Syntax Description	remote-management
Command Modes	Perle(config)#remote-management

Usage Guidelines

Use this command to enter sub-command mode for remote management configuration.

Examples

This example enables remote management config mode.

Perle(config)#remote-management
Perle(config-remote-mgmt)#

Related Commands

(config-remote-mgmt)

(config-remote-mgmt)

{**restful-api cookie-max-age** |
http local-port *<80, 1025-65535>* |
https local-port *<443, 1025-65535>*|
jwt [claims aud *<WORD>* **| exp** *<1-3153600>* **| iat** *<WORD>* **| iss** *<WORD>* **| jti** *<WORD>* **| nbf** *<1-31336000>* **| sub** *<WORD>***] | jws [algorithum es256 | es384 | es512 | hs256 | hs356 | hs512 | ps256 | ps 384 | ps512 | rs256 | rs384 | rs512 | none] | key import terminal**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-remote-mgmt)
{**restful-api cookie-max-age** |	Enables set-cookie based authentication. Values are 1 to 20160 (14 days) Default is 1440 minutes (24 hours)

http local-port |	If enabled, the router accepts and responds to HTTP Restful client requests. Values for local port are 80, 1025 to 65535 Default local port is 8080 Default is Disabled
https local-port |	If enabled, the router accepts and responds to HTTPS Restful client requests. Values for the local port are 443, 1025 to 65535 Default is Disabled
jwt [claims aud ***<WORD>*** **| exp** ***<1-3153600>*** **| iat** ***<WORD>*** **| iss** ***<WORD>*** **| jti** ***<WORD>*** **| nbf** ***<1-31336000>*** **| sub** ***<WORD>*****] | jws algorithm es256 | es384 | es512 | hs256 | hs384 | hs512 | ps256 | ps 384 | ps512 | rs256 | rs384 | rs512 | none] | key import terminal**}	**Claim sets:** **aud: audience—**identifies the recipients that the JWT is intended for. This tends to be the "client id" or "client key" of the application that the JWT is intended to be used by. It allows the client to verify that the JWT was sent by someone who actually knows who they are. **exp: expiration time—**identifies the expiration time on and after which the JWT must not be accepted for processing Values are 1–3153600 seconds Default is 3153600 seconds

	iat: issued at—identifies the time on which the JWT will start to be accepted for processing **iss: issuer**—identifies principal that issued the JWT **jti: JWT ID**—case sensitive unique identifier of the token **nbf: not before**—JWT will start to be accepted for processing at this time Values are 1–3156000 seconds **sub: subject**—identifies the subject of the JWT **Algorithm types:** • es256 • es384 • es512 • hs256 • hs384 • hs512 • ps256 • ps384 • ps512 • none **key**—import the key via the terminal screen. To end entry type "quit" on a blank line by itself.
Command Modes	Perle(config-remote-mgmt)#

Usage Guidelines

Use this command to configure RESTful API options.

JSON Web Token (JWS) is an Internet standard way to securely transfer information between devices as a JSON object. This information can be verified and trusted because it is digitally signed. JSON Web Tokens (JWTs) can be signed using an algorithm or a public/private key pair.

Examples

This example sets the local port for HTTPS to 1025.

```
Perle(config-remote-mgmt)#restful-api https local-port 1025
```

route-map

route-map

{<*WORD*> <*1-65535*> **[deny** <*1-65535*> | **permit** <*1-65535*>**]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**route-map**

{<*WORD*> <*1-65535*> **[deny** <*1-65535*> **| permit** <*1-65535*>**]**}	Insert, delete, deny, or permit from existing route map table.

Command Modes	Perle(config)#route-map

Usage Guidelines

Use this command to create route maps or enter route map command mode.

Examples

This example creates a route map called test-route.

Perle(config)#route-map test-route

Related Commands

show route-map

(config-route-map)

(config-route-map)

{**call** <*WORD*> **|**
continue <*1-65535*> **|**
description <*LINE*> **|**
match | [as-path <*WORD*>**] | [community** <*1-500*>**] | [extcommunity** <*1-500*>**] | [interface bvi** <*1-9999*>**] | [cellular** <*0-0*>**] | [dialer** <*0-15*>**] | [dot11radio** <*0-4*>**] | [ethernet** <*1-5*>**.** <*1-4000*>**] | [openvpn-tunnel** <*0-999*>**] | [tunnel** <*0-999*>**] | [ip address** <*1-199*>**|** <*1300-2699*>**| prefix-list] | [ipv6** <*WORD*>**| prefix-list] | [metric** <*1-4294967295*>**] | [origin egp | igp | unknown] | [peer** <*A.B.C.D*>**] | [tag** <*1-65535*>**] |**
on-match goto <*1-65535*>**| next |**
set aggregator as <*1-4294967295*> <*A.B.C.D*>**] | [as-path exclude** <*1-4294967295*>**| prepend** <*1-4294967295*>**] | [atomic-aggregate] | comm-list** <*1-500*> **delete] | [community** <*1-4294967295*>**|** <*AA:NN*>**| internet | local-as | no-advertise | no export] | [ext-community rt** <*AA:NN*>**| soo** <*AA:NN*>**] | [ip nexthop** <*A.B.C.D*>**] | [ipv6 nexthop global** <*X:X:X:X::X*>**| local** <*X:X:X:X::X*>**] | local-preference** <*0-4294967295*>**| metric** <*1-4294967295*>**| [metric-type** <*type-1*>**|** <*type-2*>**] | [origin epg | igp | unknown] | [originator-id** <*A.B.C.D*>**] | [src** <*A.B.C.D*>**] | [tag** <*1-65535*>**] | [weight** <*0-4294967295*>**]**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-route-map)**
{**call** <*WORD*> **|**	Calls to another route map.

continue *<1-65535>* |	Calls to another rule within the current route map. The new route map rules is called after all set actions specified in the route map rule have been performed.
description *<LINE>* |	Configure a route map description.
match | [as-path *<WORD>***] | [community** *<1-500>***] | [extcommunity** *<1-500>***] | [interface bvi** *<1-9999>***] | [cellular** *<0-0>***] | [dialer** *<0-15>***] | [dot11radio** *<0-4>***] | [ethernet** *<1-5>. <1-4000>***] | [openvpn-tunnel** *<0-999>***] | [tunnel** *<0-999>***] | [ip address** *<1-199>* **|** *<1300-2699>* **| prefix-list] | [ipv6** *<WORD>* **| prefix-list] | [metric** *<1-4294967295>***] | [origin egp | igp | unknown] | [peer** *<A.B.C.D>***] | [tag** *<1-65535>***]** |	Defines a match condition based on parameter.
on-match goto *<1-65535>* **| next** |	Specifies an alternative exit policy for a route map.
set aggregator as *<1-4294967295> <A.B.C.D>***] | [as-path exclude** *<1-4294967295>* **| prepend** *<1-4294967295>***] | [atomic-aggregate] | comm-list** *<1-500>* **delete] | [community** *<1-4294967295>* **|** *<AA:NN>* **| internet | local-as | no-advertise | no export] | [ext-community rt** *<AA:NN>* **| soo** *<AA:NN>***] | [ip nexthop** *<A.B.C.D>***] | [ipv6 nexthop global** *<X:X:X:X::X>* **| local** *<X:X:X:X::X>***] | local-preference** *<0-4294967295>* **| metric** *<1-4294967295>* **| [metric-type** *<type-1>* **|** *<type-2>***] | [origin epg | igp | unknown] | [originator-id** *<A.B.C.D>***] | [src** *<A.B.C.D>***] | [tag** *<1-65535>***] | [weight** *<0-4294967295>***]**}	Configure values in destination routing protocol. **aggregator**—modifies the BGP aggregator attribute of a route. Specify the ASN number or the IP address of the aggregator. **as-path—excludes**—removes the AS path from a BGP AS-path attribute (up to 10 numbers) **as-path—prepend**—prepends to the AS path of the route (up to 10 numbers) **atomic-aggregate**—sets the atomic aggregate attribute in a route **comm-list**—set the BGP community list for deletion **community**— community number—configure the community number or AA:NN

	internet—internet (well know community) local-AS—do not send outside local AS no-advertise—do not advertise to any peer no-export—do not export to next AS **ip**—modifies the next hop destination of a route **ipv6**—modifies the IPv6 next-hop destination of a route. **ocal-preference**—modifies the BGP local-pref attribute in a route **metric**—modifies the metric of a route **metric-type**—specifies the OSPF external metric-type for a route **origin**—modifies the BGP origin code of a route **originator-id**—modifies the BGP originator ID attribute of a route **src**—modifies th BGP source address for the route **tag**—modifies the OSPF tag value of a route **weight**—modifies the BGP weight of a route
Command Modes	Perle(config-route-map)#

Usage Guidelines

Use this command to configure route map parameters.

Examples

This rule defines a match rule for community list BGP 50.

Perle(config-route-map)#match community 50

Related Commands

show route-map

router

router

{**bgp** ***<1-4294967295>*** |
ospf |
rip}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**router**

{**bgp** ***<1-4294967295>*** |	Configures Broader Gateway Protocol (BGP) routing protocol on the router. If using your router to connect to the Internet, BGP should be enabled. Configure the autonomous system number (ASN) is a unique number that's available globally to identify an autonomous system and which enables that system to exchange exterior routing information with other neighboring autonomous systems. Your service provider will assign you the first three digit for ASN, the last two digits should be unique. Values are 1–4294967295
ospf |	Configure OSPF routing protocol on the router. Open Shortest Path First (ospf) is a protocol used to find the best paths for packets as they pass through a set of connected networks. OSFP was designed to replace the RIP protocol as it optimizes the updating up of the routing table. OSPF should be enabled on your router.
rip}	Configure RIP routing protocol on the router. Routing Information Protocol (rip). Older protocol for finding the shortest path for routing information using a routing metric/ hop count algorithm. RIP should be enabled on your router if there are older routers on your network that need to use RIP.

Command Modes

Perle(config)#router

Usage Guidelines

Use this command to select the routing protocol for your router.

Examples

This example sets the routing protocol to BGP.

```
Perle(config)#router bgp 10
```

Related Commands

show ip ospf

show ip rip

(config-router)—BGP

{**bgp address-family ipv4 | ipv6 unicast** |

aggregate address *<A.B.C.D>* *<A.B.C.D>* **as-set | summary-only |**

bgp always-compare-med | [bestpath as-path | confed | ignore] | [compare-router-id | [med confed | missing-as-worst] | [client-to-client reflection] | [cluster-id *<1-4294967295>* *<A.B.C.D>***] | [confederation identifier** *<1-4294967295>* **| peers** *<1-4294967295>* *<1-4294967295>***] | [dampening** *<1-45>* **|** *<1-20000>* **|** *<1-20000>* **|** *<1-255>***] | [deterministic-med] | [enforce-first-as] | [fast-external-failover] | [graceful-restart stalepath-time** *<1-3600>***] | [log-neighbor-changes] | [network import-check] | [router-id** *<A.B.C.D>***] |**

distance *<1-255>* *<A.B.C.D>* *<A.B.C.D/nn>* **| bgp distance** *<1-255>* *<1-255>* *<1-255>* **|**

maximum-paths *<1-64>* **ibgp** *<1-64>* **|**

neighbour *<A.B.C.D>* *<X:X:X:X::X>* **advertisement-interval** *<0-600>* **| allowas-in** *<1-10>* **| [asoverride] | [attribute-unchanged as-path | med | next-hop] | [capability dynamic | orf prefix-list both | receive | send] | [default originate route-map** *<NAME>***] | [description** *<LINE>***] | [disable-connected-check | [distributed-list** *<1-99>* **in | out** *<1300-2699>* **in | out] | [dont't-capability-negotiate] | [ebgp-multihop** *<1-255>***] | [filter-list** *<WORD>***] | [local-as** *<1-4294967295>* **no-prepend] | [maximum-prefix** *<1-4294967295>***] | [next-hop-self] | [override-capability] | [passive] | [password** *<LINE>***] | [port** *<1-65535>***] | [prefix-list** *<WORD>***] | [remote-as** *<1-4294967295>***] | remove-private-as | [route-map** *<WORD>* **in | out] | [route-reflector -client] | [route-server-client] | [send-community both | extended | standard] | [shutdown] | [soft-reconfiguration] | [strict-capability-match] | [timers** *<0-65535>* *<0-65535>* **| connect** *<0-65335>***] | [ttl-security] | [unsuppress-map** *<WORD>***] | update-source interface bvi** *<1-9999>* **| cellular** *<0-0>* **| dialer** *<0-15>* **| dot11radio** *<0-4>* **| ethernet** *<1-5>. <1-4000>* **| openvpn-tunnel** *<0-999>* **| tunnel** *<0-999>* **|** *<X:X:X:X::X>***] | weight** *<1-65335>* **|**

network *<A.B.C.D>* *<A.B.C.D>* **| backdoor | route-map** *<WORD>* **|**

redistribute connected | kernel | ospf | rip | static | metric *<1-4294967295>* **|**

timers bgp *<0-65535>* *<0-65335>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-router)-BGP **Some parameters may not be available on some firmware versions or models.**
{**bgp address-family ipv4 | ipv6 unicast |**	Enters address family mode.
aggregate address *<A.B.C.D>* *<A.B.C.D>* **as-set | summary-only |**	Specifies the block of addresses to be aggregated. **as-set**—specifies that the routes resulting from the aggregation include the AS-set. **summary-only**—specifies that aggregated routes are summarized. These routes will not be advertised.

bgp always-compare-med | [bestpath as-path confed | ignore] | [compare-router-id] | [med confed | missing-as-worst] | [client-to-client reflection] | [cluster-id *<1-4294967295>* *<A.B.C.D>*] | [confederation identifier *<1-4294967295>* | peers *<1-4294967295>* *<1-4294967295>*] | [dampening *<1-45>* | *<1-20000>* | *<1-20000>* | *<1-255>*] | [deterministic-med] | [enforce-first-as] | [fast-external-failover] | [graceful-restart stalepath-time *<1-3600>*] | [log-neighbor-changes | network import-check | [router-id *<A.B.C.D>*] |	Configure BGP parameters. **always-compare**—directs the router to compare the MED for paths from neighbors in different autonomous systems. Default is disabled **best-path** **as-path** [confed | ignore]—directs the router to compare the AS paths during best-path selection Default is does not compare **compare-router-id**—directs the router to compare identical routes received from different external peers during best path selection Default is does not compare **med** confed | missing-as-worst—direct the router to compare the Multi Exit Discriminator (MED) among paths learned from confederation peers during best path selection **client-to-client reflection**—enables or disables route reflection from a BGP route reflector to clients. Default is disabled **cluster-id**—sets the cluster ID for a BGP route reflection cluster as a 32 bit number Values are 1–4294967295 or IP address Default is none **confederation identifier | peers**—Defines a BGP confederation. Values are AS number 1–4294967295 Peers range from 1–4294967295 to 1–4294967295 Values are 128 peers **dampening—**enables or disables route dampening and sets router dampening value. **half-life—**1 to 45 mins Default is 15 mins **reusing-route—**1 to 20000 Default is 750 **start-suppress-time—**to 20000 Default is 20000

max-suppress-time—1 to 255
Default is 4 x of half life

deterministic-med—enables of disables enforcing of deterministic MED

enforce first-as—forces eBGP peers to list AS number at the beginning of the AS_path attribute in coming updates
Default is disabled

fast-external-failover —immediately reset session if a link to a directly connected external peer goes down
Default is disabled

graceful-restart—enables or disables grateful restart of the BGP process

Default is enabled
Grateful stale-time is 1-3600 seconds
Graceful stale time default is 360 seconds

log-neighbor-changes—log neighbor up/down and reset reason
Default is disable

network import-check—check BGP network route exists in IGP
Default is enabled

router-id—configure a fixed BGP router ID for the router, overriding the automate ID selection process
Default automatically selected by BGP

distance ***<1-255> <A.B.C.D> <A.B.C.D/nn>*** **| bgp distance** ***<1-255> <1-255> <1-255>*** **|**	Enter an **Administrative Distance**. (AD) is a value that your router uses to select the best path when there are two or more different routes to the same destination from two different routing protocols. Administrative distance is the reliability of a routing protocol. A static route is normally set too 1. The smaller the administrative distance value, the more reliable the protocol. Administrative Distance is locally significant, it is not advertised to the network. Range is 1-255 (with 1 being the most reliable) and 255 is route not used or unknown Configure a source IP prefix address and mask. **BGP distance** Distance for external router to AS Values are 1 to 255 Default 20 Distance for internal outer to AS Values 1 to 255 Default is 200 Distance for local router Value 1 to 255 Default 200
maximum-paths ***<1-64>*** **ibgp** ***<1-64>*** **|**	Configure the maximum number of eBGP/iBGP paths to a destination. ebgp values are 1 to 255 Default is 1 ibgp values are 1 to 255 Default is 1

neighbour ***<A.B.C.D> <X:X:X:X::X>*** **[advertisement-interval** ***<0-600>*****] | [allowas-in** ***<1-10>*****] | asoverride | [attribute-unchanged as-path | med | next-hop] | [capability dynamic | orf prefix-list both | receive | send] | [default originate route-map** ***<NAME>*****] | [description** ***<LINE>*****] | [disable-connected-check] | [distributed-list** ***<1-99>*** **in | out** ***<1300-2699>*** **in | out] | [dont't-capability-negotiate] | [ebgp-multihop** ***<1-255>*****] | [filter-list** ***<WORD>*****] | [local-as** ***<1-4294967295>*** **no-prepend] | [maximum-prefix** ***<1-4294967295>*****] | [next-hop-self] | [override-capability] | [passive] | [password** ***<LINE>*****] | [port** ***<1-65535>*****] | [prefix-list** ***<WORD>*** **in | out] | [remote-as** ***<1-4294967295>*****] | [remove-private-as] | [route-map** ***<WORD>*** **in | out] | [route-reflector -client] | [route-server-client] | [send-community both | extended | standard] | [shutdown] | [soft-reconfiguration] | [strict-capability-match] | timers** ***<0-65535> <0-65535>*** **| connect** ***<0-65535>*****] | [ttl-security hops** ***<1-254>*** **| [unsuppress-map** ***<WORD>*** **| update-source interface bvi** ***<1-9999>*** **| cellular** ***<0-0>*** **| dialer** ***<0-15>*** **| dot11radio** ***<0-4>*** **| ethernet** ***<1-5>. <1-4000>*** **| openvpn-tunnel** ***<0-999>*** **| tunnel** ***<0-999>*** **|** ***<X:X:X:X::X>*****] | [weight** ***<1-65335>*****] |**	Configure neighbor configuration. **neighbor address**—specify an IPv4 or IPv6 address. **advertisement-interval**—configure the minimum interval between sending BGP routing updates. Values 0 to 600 Default eBGP is 30 secs Default iBGP peers is 5 seconds **allowas-in**—allows or disallows receiving BGP advertisements containing the AS path of the local router. Default readvertisement is disabled. Default is 3 **as-override**—override ASN's in outbound updates if AS–path equals remote–AS. Only applies to eBGP neighbor. Default is disable **attribute-unchange—**allows the router to send updates to a neighbor with unchanged attributes. Value is on for all if no option provided Default is disabled **capability**—advertise dynamic capability to this neighbor. Default is session is brought up with minimal capability on both sides **capability orf prefix-list [both | receive | send]—**advertises support for Outbound Route Filtering (OFR) for updating BGP capabilities advertised and received from this neighbor. Default is the session is brought up with minimal capability on both sides. **default-originate—**enables or disables forwarding of the default route to a BGP neighbor. Default is disabled **Description**—provide a description for a BGP neighbor. **disable-connected-check**—Enables a directly connected eBGP neighbor to peer using a loopback address without adjusting the default TTL of 1. Default is off

distributed-list—applies an access list to filter inbound/outbound routing updates from this neighbor.
Default is none

dont't capability-negotiate—disables BGP capability negotiation
Default is capability negotiation is performed.

ebgp-mulihop—Allows you to establish eBGP peer relationships between routers that aren't directly connected to one another.
Default is only directly connected neighbors are allowed

filter-list—applies an AS–path list to routing updates to this neighbor
Default is none

local-as—defines a local autonomous system number for eBGP peering
Default is none

maximum-prefixes—configure the maximum number of prefixes to accept from this neighbor before that neighbor is taken down.

Values are 1–4294967295
Default is none

next-hop-self—sets the local router as the next ho for this neighbor
Default is disable

over-ride-capability—overrides capability negotiation to allow a peering session to be established with a neighbor that does not support capabilities negotiation
Default is a session cant be established if the neighbor does not support capability negotiation

passive—directs the router not to initiate connections with this neighbor

password—Configure a BGP MD5 password
Default is none

port—specifies the port on which the neighbor is listening for BGP signals
Values are 1 to 65535
Default port is 179

prefix-list- applies this prefix list filter updates to/from this neighbor
Default is none

remote-as—Configure the autonomous system number of the neighbor.
Default is none

remove-private-as—directs the router to remove private AS numbers from updates sent to this neighbor (eBGP only)
Default is disable (do not remove)

route-map—applies a route map to filter updates to/from this neighbor
Default is none

route-reflector—specify this neighbor as a route reflector client (iBGP only)
Default is disabled

route-server-client—specify this neighbor as a route server client
Default is disable

send-community—enables or disables the sending of community attributes to the specified neighbor

Value— no type specified send standard attributes
Default is both

shutdown—administratively shuts down a BGP neighbor
Default is disabled

soft-reconfiguration—directs the router to store received routing updates

strict-capability-match—directs the router to strictly match the capabilities of the neighbor
Default is disable

timers—
keepalive interval
Values are 0–-65535
Default is 60 seconds

holdtime

Value are 0-65535
Default is 180 seconds

connect
Values are 0-65535
Default is 120 seconds

	ttl-security—Configure the time-to-live (ttl) security hop count. This option and ebgp-multihop cannot be set at the same time Values are 1 to 254 hops Default is 1 **unsupress-map—**directs the router to selectively advertise routes suppressed by aggregating addresses, based on a route map Value specify a router map Default is none **update-source—**specifies the source ip address or interface for routing updates Default is none **weight—**defines a default weight for routes from this neighbor Values are 1-65335 Default is routes learned from a BGP neighbor have a weight of 0. Routes sourced by the local router have a weight of 32768
network ***<A.B.C.D>*** ***<A.B.C.D>*** **| backdoor | route-map** ***<WORD>*** **|**	Configure a network to be advertised by the BGP routing process. **Backdoor**—indicates that this network is reachable by a back door route. A back door network is considered to be like a local network but is not advertised. **Route-map**—specifies a configured route map to be used when advertising the network Default is none
redistribute connected | kernel | ospf | rip | static | metric ***<1-4294967295>*** **| route-map** ***<WORD>*** **|**	Select route type for redistribution. BGP. Connected (directly attached subnet or host) • Kernel • OSPF • RIPng • Static Select a router map from the drop-down list.

	Configure the metric used by the routing protocol to calculate the best path to a given destination. Value range is 1-4294967295 A route map consists of a series of statements to check if the route matches the policy, then it permits or denies the route. Default is none
timers bgp ***<0-65535> <0-65335>***}	Configure BGP times globally for the local router. Keepalive interval Values are 0-65535 Default is 60 seconds Hold-time Values are 0-65535 Default is 180 seconds
Command Modes	Perle(config-router)#

Usage Guidelines

Use this command to configure BGP protocol parameters.

Examples

This example sets BGP timers keepalive to 10 seconds and hold time to 20 seconds.

```
Perle(config-router)#timers bgp 10 20
```

Related Commands

show bgp

(config-router-RIP)

{**rip default-information originate** |

default-metric ***<1-16>*** |

distance ***<1-255>*** |

distribution-list [*<WORD>* **| prefix** ***<WORD>*****] | [in | out] [bvi** ***<1-9999>*****] | [cellular** ***<0-0>*****] | [dialer** ***<0-15>*****] | [dot11radio** ***<0-4>*****] | [ethernet** ***<1-5> . <1-4000>*****] | [openvpn-tunnel** ***<0-999>*****] | [tunnel** ***<0-999>*****]** |

neighbor ***<A.B.C.D>*** |

network ***<A.B.C.D> <A.B.C.D>*** |

passive-interface bvi ***<1-9999>*** **| cellular** ***<0-0>*** **| dialer** ***<0-15>*** **| dot11radio** ***<0-4>*** **| ethernet** ***<1-5>. <1-4000>*****| openvpn-tunnel** ***<0-999>*** **| tunnel** ***<0-999>*** **| all** |

redistribute connected | kernel | ospf | rip | static | metric ***<1-16*** **| route-map** ***<WORD>*** **metric** ***<1-16> <WORD>*** |

route ***<X:X:X:X::X>/<0-128>*** |

timers basic *<5-2147483> <5-2147483> <5-2147483>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-rtr)
{**rip default-information originate** |	Controls distribution of default information
default-metric *<1-16>* |	Configure the metric for redistributed routes.
distance *<1-255>* |	Enter an **Administrative Distance**. (AD) is a value that your router uses to select the best path when there are two or more different routes to the same destination from two different routing protocols. Administrative distance is the reliability of a routing protocol. A static route is normally set too 1. The smaller the administrative distance value, the more reliable the protocol. Administrative Distance is locally significant, it is not advertised to the network. Range is 1-255 (with 1 being the most reliable) and 255 is route not used or unknown
distribution-list [*<WORD>* **| prefix** *<WORD>***] | [in | out] [bvi** *<1-9999>***] | [cellular** *<0-0>***] | [dialer** *<0-15>***] | [dot11radio** *<0-4>***] | [ethernet** *<1-5>. <1-4000>***] | [openvpn-tunnel** *<0-999>***] | [tunnel** *<0-999>***]** |	Filters networks in routing updates. Select the access list for IPv6 name or filter prefixes in routing updates. Specific whether the filter is for inbound or outbound. Specify the interface to apply this distribution list to.
network *<A.B.C.D> <A.B.C.D>* |	Enables routing on a network.
passive-interface bvi *<1-9999>* **| cellular** *<0-0>* **|dialer** *<0-15>* **| dot11radio** *<0-4>* **| ethernet** *<1-5>. <1-4000>***| openvpn-tunnel** *<0-999>* **| tunnel** *<0-999>* **| all** |	Suppress routing updates on an interface.
redistribute connected | kernel | ospf | rip | static | metric *<1-4294967295>* **| route-map** *<WORD>* |	Redistribute information from other routing protocol.
route *<X:X:X:X::X>/<0-128>* |	Static route setup.

timers basic ***<0-65535> <0-65535> <0-65535>***}	**Timers basic—** Update period 0-65535 Route timeout period 0-65535 Route hold down period in seconds 0-65535
Command Modes	Perle(config-rtr)#

Usage Guidelines

Use this command to configure RIP protocol parameters.

Examples

This example sets timer for RIP updates to every 5 seconds.

Perle(config-router)#timers basic 5

Related Commands

router

(config-router)—OSPF

{**ospf [area** ***<0-4294967295>*** **|** ***<A.B.C.D>*** **authentication message-digest] | [default-cost** ***<1-6777215>*****] | [nssa no-summary | translate |-always | translate-candidate | translate-never] | [range** ***<A.B.C.D> <A.B.C.D>*** **advertise | not-advertise cost** ***<0-16777215>*** **| substitute** ***<A.B.C.D> <A.B.C.D>*** **cost** ***<0-16777215>*****] | [shortcut enable | disable | default] | [stub no-summary] | [virtual-link** ***<A.B.C.D>*** **authentication-key** ***<WORD>*** **| message-digest message-digest-key** ***<1-255>*** **md5** ***<LINE>*** **| null] | [dead-interval** ***<1-65535>*****] | [hello-interval** ***<1-65535>*****] | [retransmit-interval** ***<1-65535>*****] | [transmit-delay****<1-65535>*****] |**

auto-cost reference-bandwidth ***<1-4294967>*** **|**

capability opaque |

compatibility rfc1583 |

default-information originate always | metric ***<0-16777214>*** **| metric-type** ***<1-2>*** **| route-map** ***<WORD>*** **|**

default-metric ***<0-16777214>*** **|**

max-metric router-lsa administrative | on-shutdown ***<5-86400>*** **| on-startup** ***<5-86400>*** **|**

neighbor poll-interval ***<1-65535>*** **| priority** ***<0-255>*** **|**

network ***<A.B.C.D> <A.B.C.D>*** **area** ***<0-4294967295>*** **|**

passive-interface bvi ***<1-9999>*** **| cellular** ***<0-0>*** **| dialer** ***<0-15>*** **| dot11radio** ***<0-4>*** **| ethernet** ***<1-5>. <1-4000>*** **| openvpn-tunnel** ***<0-999>*** **| tunnel** ***<0-999>*** **| all |**

redistribute connected | kernel | ospf | rip | static | metric ***<1-4294967295>*** **| route-map** ***<WORD>*** **|**

refresh timer ***<5-1800>*** **|**

router-id ***<A.B.C.D>*** |
timers throttle spf ***<1-600000> <1-600000><1-600000>***}
Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-router)-OSPF
{**ospf [area** ***<0-4294967295>*** | ***<A.B.C.D>*** **authentication message-digest | default-cost** ***<1-6777215>*** **| nssa no-summary | translate |-always | translate-candidate | translate-never] | [range** ***<A.B.C.D> <A.B.C.D>*** **advertise | not-advertise cost** ***<0-16777215>*** **| substitute** ***<A.B.C.D> <A.B.C.D>*** **cost** ***<0-16777215>*****] | [shortcut enable | disable | default] | [stub no-summary] | [virtual-link** ***<A.B.C.D>*** **authentication-key** ***<WORD>*** **|authentication-key** ***<WORD>*** **| message-digest message-digest-key** ***<1-255>*** **md5** ***<LINE>*** **| null] | [dead-interval** ***<1-65535>*****] | [hello-interval** ***<1-65535>*****] | [retransmit-interval** ***<1-65535>*****] | [transmit-delay****<1-65535>*****] | auto-cost reference-bandwidth** ***<1-4294967>*** **| capability opaque | compatibility rfc1583 |**	Configure OSPF area parameters. **Area**—OSPF area ID in decimal format or IP address format **Authentication**—enables message-digest authentication **Default-cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0 to 16777214 Default is none **NSSA** • No summary—Configure the OSFP VRF instance to not inject the inter-area routes into NSSA. • Candidate translate—Configure the NSSA-ABR always to translate election. Default is enabled • Always translate—Configure the NSSA-ABR never to translate. Default is enabled • Never translate—Configure the NSSA-ABR server never to translate. By default this is disabled **Range**—Configure a prefix specified as IP address and subnet mask. • **Advertise**—sets the address range status to advertise and generates a Type 3 summary LSA. • **Not-advertise**—sets the address range status to Do Not Advertise. The Type 3 summary LSA is suppressed and the component networks remain hidden from other networks. • **Substitute—**(network prefix to be announced instead of range). The default is advertise • **Cost**—Configure the metric for this area range. Range is 0 to 16777215
default-information originate always | metric ***<0-16777214>*** **| metric-type** ***<1-2>*** **| route-map** ***<WORD>*** **| default-metric** ***<0-16777214>*** **| max-metric router-lsa administrative | on-shutdown** ***<5-86400>*** **| on-startup** ***<5-86400>*** **|neighbor poll-interval** ***<1-65535>*** **| priority** ***<0-255>*** **|**	
network ***<A.B.C.D> <A.B.C.D>*** **area** ***<0-4294967295>*** **| capability opaque | compatibility rfc1583 |**	

capability opaque | **compatibility rfc1583** |

default-information originate always | **metric** *<0-16777214>* | **metric-type** *<1-2>* | **route-map** *<WORD>* | **default-metric** *<0-16777214>* | **max-metric router-lsa administrative** | **on-shutdown** *<5-86400>* | **on-startup** *<5-86400>* |**neighbor poll-interval** *<1-65535>* | **priority** *<0-255>* |

network *<A.B.C.D> <A.B.C.D>* **area** *<0-4294967295>* |

passive-interface bvi *<1-9999>* | **cellular** *<0-0>* | **dialer** *<0-15>* |**dot11radio** *<0-4>* | **ethernet** *<1-5>. <1-4000>* | **openvpn-tunnel** *<0-999>* | **tunnel** *<0-999>* | **all** | **redistribute connected** | **kernel** | **ospf** | **rip** | **static** | **metric** *<1-4294967295>* | **route-map** *<WORD>* |

refresh timer *<5-1800>* |

router-id *<A.B.C.D>* |

timers throttle spf *<1-600000> <1-600000><1-600000>*}

Shortcut—This parameter allows to "shortcut" routes (non-backbone) for inter-area routes.

- enable—use this area for shortcutting
- disable—never use this are for route shortcutting
- default—use this area for shortcutting—only if the ABR does not have a link to the backbone area or this link was lost

stub no-summary—no-summary option creates a totally stubby area. A totally stubby area keeps only the intra-area routes (the O routes), and for any inter-area routing, it has a default route

Virtual Link IP Address—IPv4 address of this virtual link.

Authentication—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Authentication-key—Configure an authentication key for simple password authentication.
- Message-digest—(Optional) Identifies the key ID and key (password) used between this router and neighboring routers for MD5 authentication.

Shortcut—This parameter allows to "shortcut" routes (non-backbone) for inter-area routes.

- enable—use this area for shortcutting
- disable—never use this are for route shortcutting.
- default—use this area for shortcutting—only if the ABR does not have a link to the backbone area or this link was lost

stub no-summary—no-summary option creates a totally stubby area. A totally stubby area keeps only the intra-area routes (the O routes), and for any inter-area routing, it has a default route

Virtual Link IP Address—IPv4 address of this virtual link.

Authentication—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Authentication-key—Configure an authentication key for simple password authentication.
- Message-digest—(Optional) Identifies the key ID and key (password) used between this router and neighboring routers for MD5 authentication.

The default is none.

Dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.

Default is 4 times the hello interval
Default is 40 seconds

Hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

Retransmit interval—Configure the time between link-state advertisement (LSA) retransmissions for adjacencies that belong to the virtual link.
Default is 5

Transmit delay—Before a link-state update packet is propagated out of an interface, the routing device increases the age of the packet. The transit delay sets the estimated time required to transmit a link-state update on the interface. By default, the transit delay is 1 second.You should never have to modify the transit delay time. To avoid LSAs from aging out during transmission, set an LSA retransmission delay especially for low speed links.

Default is 5 seconds.

auto-cost reference-bandwidth ***<1-4294967>*** **|**	Directs the router to use reference bandwidth method for calculating administrative costs. Default reference bandwidth is 108 Mbps.
capability opaque |	Enables support for opaque link-state advertisement as described in RFC2370. Default is disabled
compatibility rfc1583 |	Indicates whether handing of AS external routes should comply with RFC 1583. Default is disabled.
default-information originate always | metric ***<0-16777214>*** **| metric-type** ***<1-2>*** **| route-map** ***<WORD>*** **|**	Sets the characteristics of an external default route originated into an OSPF routing domain. Default is off
default-metric ***<0-16777214>*** **|**	Configure a default metric to be applied to routes being distributed into OSPF. Range is 0–16777214 Default is none
default-metric ***<0-16777214>*** **|**	Configure a default metric to be applied to routes being distributed into OSPF. Range is 0–16777214 Default is none
distance ***<1-255>*** **| [ospf external** ***<1-255>*** **] | [inter-area** ***<1-255>*** **] | [intra-area** ***<1-255>*** **] |**	Enter an **Administrative Distance**. (AD) is a value that your router uses to select the best path when there are two or more different routes to the same destination from two different routing protocols. Administrative distance is the reliability of a routing protocol. A static route is normally set too 1. The smaller the administrative distance value, the more reliable the protocol. Administrative Distance is locally significant, it is not advertised to the network. Range is 1-255 (with 1 being the most reliable) and 255 is route not used or unknown Value is 1-255 Default is 110

	OSPF External—Sets the OSPF for routes injected by redistribution. Range is 1–255 Default is 110 **OSFP inter-area routes**—Sets the OSPF administrative distance by route type. Routes from another area are inter-area. Range is 1–255 Default is 110 **OSFP intra-area routes**—Sets the OSPF administrative distance by route type. Routes within an area are intra-area. Range is 1–255 Default is 110
max-metric router-lsa administrative | on-shutdown *<5-86400>* | on-startup *<5-86400>* |	Enables or disables the OSFP maximum / infinite-distance metric. **Administratively**—administratively applied for an indefinite period **on shutdown**—advertise stub-router prior to full shutdown of OSPF **on-startup**—advertise a maximum metric at startup. on shutdown/on-startup value is 5–86400 seconds Range is 5 to 86400 seconds Default is 600 seconds
neighbor poll-interval *<1-65535>* | priority *<0-255>* |	Configure the dead-router polling interval for non-broadcast neighbor. Values are 1-65535 in seconds Default is 120 in seconds Priority of non-broadcast neighbor. Values are 0-255 Default is 1
max-metric router-lsa administrative | on-shutdown *<5-86400>* | on-startup *<5-86400>* |	Configure a default metric to be applied to routes being distributed into OSPF. Range is 0–16777214 Default is none

neighbor poll-interval *<1-65535>* | priority *<0-255>* |	Enter an **Administrative Distance**. (AD) is a value that your router uses to select the best path when there are two or more different routes to the same destination from two different routing protocols. Administrative distance is the reliability of a routing protocol. A static route is normally set too 1. The smaller the administrative distance value, the more reliable the protocol. Administrative Distance is locally significant, it is not advertised to the network. Range is 1-255 (with 1 being the most reliable) and 255 is route not used or unknown Value is 1-255 Default is 110 **OSPF External—**Sets the OSPF for routes injected by redistribution. Range is 1–255 Default is 110 **OSFP inter-area routes**—Sets the OSPF administrative distance by route type. Routes from another area are inter-area. Range is 1–255 Default is 110 **OSFP intra-area routes**—Sets the OSPF administrative distance by route type. Routes within an area are intra-area. Range is 1–255 Default is 110
network *<A.B.C.D>* *<A.B.C.D>* area *<0-4294967295>* *<A.B.C.D>* |	Configure IPv4 network address. Configure IPv4 wildcard address. Configure the area id or ip address.
passive-interface bvi *<1-9999>* | cellular *<0-0>* | dialer *<0-15>* | dot11radio *<0-4>* | ethernet *<1-14>. <1-4000>* | tunnel *<0-999>* | all |	Suppresses routing updates on an interface or all interfaces.
redistribute connected | kernel | ospf | rip | static | metric *<1-4294967295>* | route-map *<WORD>* |	Redistributes information from other routing protocols. Select the type of route: • BGP • Connected (directly attached subnet or host)

	• Kernel • OSPF • Static Select the route map.
refresh timer ***<5-1800>*** |	The router automatically updates link-state information with its neighbors. Only an obsolete information is updated when age has exceeded a specific threshold. Range is 10–1800 seconds Default is 1800 seconds
router-id ***<A.B.C.D>*** |	Configure a global OSPF router ID. If this command is not configured, OSFP chooses an IPv4 address as the router ID from one of its interfaces. If this command is used on an OSPF instance that has neighbors, OSFP uses the new router ID at the next reload or restart of OSFP.Router-ID for this OSPF process.
timers throttle spf ***<1-600000> <1-600000> <1-600000>***}	Delay between receiving a change to SPF calculation in milliseconds. Range is 1–600000 milliseconds Default is 1 milliseconds Delay between first and second SPF calculation. Range is 1–600000 milliseconds Default is 1 milliseconds Maximum wait time in milliseconds for SFP calculations. Range is 1–600000 milliseconds Default is 1 milliseconds
Command Modes	Perle(config-router)#

Usage Guidelines

Use this command to configure OSPF protocol parameters.

Examples

This example sets opaque feature for OSPF.

```
Perle(config-router)#capability opaque
```

Related Commands

show ip ospf

(config-router)—RIP

{**rip default-information originate** |
default-metric *<1-16>* |
distance *<1-255>* |
distribution-list [*<1-99>* | *<1300-2699>* | **prefix** *<WORD>***]** | **[in** | **out] [bvi** *<1-9999>***]** | **[cellular** *<0-0>***]** | **[dialer** *<0-15>***]** | **[dot11radio** *<0-4>***]** | **[ethernet** *<1-5>* **.** *<1-4000>***]** | **[openvpn-tunnel** *<0-999>***]** | **[tunnel** *<0-999>***]** |
neighbor *<A.B.C.D>* |
network *<A.B.C.D>* *<A.B.C.D>* |
passive-interface bvi *<1-9999>* | **cellular** *<0-0>* | **dialer** *<0-15>* | **dot11radio** *<0-4>* | **ethernet** *<1-5>. <1-4000>*| **openvpn-tunnel** *<0-999>* | **tunnel** *<0-999>* | **all** |
redistribute connected | **kernel** | **ospf** | **rip** | **static** | **metric** *<1-4294967295>* | **route-map** *<WORD>* |
timers basic *<5-2147483> <5-2147483> <5-2147483>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-router)
rip default-information originate |	Controls distribution of default information.
default-metric *<1-16>* |	Configure the metric for redistributed routes.
distance *<1-255>* |	Enter an **Administrative Distance**. (AD) is a value that your router uses to select the best path when there are two or more different routes to the same destination from two different routing protocols. Administrative distance is the reliability of a routing protocol. A static route is normally set too 1. The smaller the administrative distance value, the more reliable the protocol. Administrative Distance is locally significant, it is not advertised to the network. Range is 1-255 (with 1 being the most reliable) and 255 is route not used or unknown
distribution-list [*<1-99>* | *<1300-2699>* | **prefix** *<WORD>***]** | **[in** | **out] [bvi** *<1-9999>***]** | **[cellular** *<0-0>***]** | **[dialer** *<0-15>***]** | **[dot11radio** *<0-4>***]** | **[ethernet** *<1-5>. <1-4000>***]** | **[openvpn-tunnel** *<0-999>***]** | **[tunnel** *<0-999>***]** |	Filters networks in routing updates. Select the IP access list number or filter prefix list name. Specific whether the filer is for inbound or outbound. Specify the interface to apply this distribution list to.

neighbor ***<A.B.C.D>*** **|**	Configure a neighbor router.
network ***<A.B.C.D>*** ***<A.B.C.D>*** **|**	Enables routing on a specified interface or network.
passive-interface bvi ***<1-9999>*** **| cellular** ***<0-0>*** **|dialer** ***<0-15>*** **| dot11radio** ***<0-4>*** **| ethernet** ***<1-5>. <1-4000>*****| openvpn-tunnel** ***<0-999>*** **| tunnel** ***<0-999>*** **| all |**	Suppress routing updates on an interface.
redistribute connected | kernel | ospf | rip | static | metric ***<1-4294967295>*** **| route-map** ***<WORD>*** **|**	Redistribute information from other routing protocol.
timers basic ***<5-2147483> <5-2147483> <5-2147483>***}	**Timers basic—** Interval between updates for RIP Values are 5-2147483 in seconds Default is Invalid in secnds Values are 5–2147483 Default is Flush in seconds Values are 5-2147483

Command Modes	Perle(config-router)#

Usage Guidelines

Use this command to configure RIP protocol parameters.

Examples

This example sets timer for RIP updates to every 5 minutes.

Perle(config-router)#timers basic 5

Related Commands

router

sdm

sdm

{**prefer default | dual-ipv4-and-ipv6 default**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**sdm**

{**prefer default | dual-ipv4-and-ipv6 default**}	The sdm command is used to set IP protocols on your router.
Command Default	sdm prefer default (IPv4) (both IPV4 and IPV6 enabled)
Command Modes	Perle(config)#sdm

Usage Guidelines

By default the Router is set for IPv4. To enable both IPv4 and IPv6 see the example below.

Examples

This example sets your router for both IPv4 and IPv6 traffic.

Perle(config)# sdm prefer dual-ipv4-and-ipv6 default

serial

serial

{**accounting** ***<WORD>*** **| default |**
advanced [break off | on] | data_logging_buffer_size ***<1-2000>*** **| [flush-on-close off | on] | [line-menu-string** ***<WORD>*****] |[monitor-connection-every** ***<1-32767>*****] | monitor-connection-number** ***<1-32767>*****] | monitor-connection-timeout*****<1-32767>*** **| single-telnet off | on] |**
authentication aaa login-authentication ***<WORD>*** **| default |**
authorization exec ***<WORD>*** **| default |**
modbus gateway addr-mod embedded | re-mapped] | [broadcast on | off] | char-timeout ***<10-10000>*** **| [exceptions off | on] | [idle-timer** ***<0-300>*****] | [ip-aliasing off | on] | mess-timeout** ***<10-10000>*** **| next-req-delay** ***<0-1000>*** **| port** ***<1-65535>*** **| remapped-id** ***<1-247>*** **| [req- off | on] | [ssl on | off] |**
port buffering key-stroke-buffering on | off] | mode both | local | off | remote | nsf-directory ***<WORD>*** **| nfs-encryption off | on | [nfs-host** ***<A.B.C.D>*** ***<WORD>*** ***<X:X:X:X::X>*****] | syslog [level alert | critical | emergency | error | info | notice | warning] | off | on] | [time-stamp off | on] | view-port-buffer-string** ***<WORD>*** **|**
trueport [remap 110 | 1200 | 134 | 150 | 1800 | 19200 | 200 | 2400 | 300 | 38400 | 4800 | 50 | 600 | 75 | 9600] | [|115200 | 1200 | 1800 | 19200 | 23400 | 2400 | 38400 | 4800 | 57600 | 600 | 9600 | custom |
vmodem-phone entry ***<1-8>*** **phone-number** ***<phone -number>*** **| host** ***<A.B.C.D>*** ***<WORD>*** ***<X:X:X:X::X>*** ***<tcp-port>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**serial**
{**accounting** ***<WORD>*** **| default |**	Configure accounting parameters.

advanced [break off | on] | data_logging_buffer_size *<1-2000>* | [flush-on-close off | on] | [line-menu-string *<WORD>*] | [monitor-connection-every *<1-32767>*] | monitor-connection-number *<1-32767>*] |	Configure advanced features for serial devices. Default for line-menu-string is ~menu
monitor-connection-timeout *<1-32767>* | single-telnet off | on] |	
authentication aaa login-authentication *<WORD>* | default |	Configure authentication parameters.
authorization exec *<WORD>* | default |	Configure authorization parameters.
modbus gateway addr-mod embedded | re-mapped] | [broadcast on | off] | char-timeout *<10-10000>* | [exceptions off | on] | [idle-timer *<0-300>*] | [ip-aliasing off | on] | mess-timeout *<10-10000>* | next-req-delay *<0-1000>* | port *<1-65535>* | remapped-id *<1-247>* | [req-off | on] | [ssl on | off] |	Configure modbus gateway parameters.
port buffering key-stroke-buffering on | off] | mode both | local | off | remote | nsf-directory *<WORD>* | nfs-encryption off | on | [nfs-host *<A.B.C.D> <WORD> <X:X:X:X::X>*] | syslog [level alert | critical | emergency | error | info | notice | warning] | off | on] | [time-stamp off | on] | view-port-buffer-string *<WORD>* |	Configure port buffering parameters.

trueport [remap 110 | 1200 | 134 | 150 | 1800 | 19200 | 200 | 2400 | 300 | 38400 | 4800 | 50 | 600 | 75 | 9600] | 115200 | 1200 | 1800 | 19200 | 23400 | 2400 | 38400 | 4800 | 57600 | 600 | 9600 | custom |	Configure remap baud rates for Trueport devices.
vmodem-phone entry *<1-8>* phone-number *<phone -number>* | host *<A.B.C.D>* *<WORD>* *<X:X:X:X::X>* *<tcp-port>*}	Configure parameters for virtual modem.

Command Modes	Perle(config)#serial

Usage Guidelines

Serial advanced feature settings

Examples

This example sets the vmodem phone number to 416-666-9900 for host 172.16.77.88.

```
Perle(config)#serial vmodem entry 1 phone-number 416-666-9900 host 172.16.77.88
```

Related Commands

serial

show serial

service

service

{**dhcp relay-agent | server** |
dhcpv6 server |
[**sequence-numbers**] |
[**timestamps log datetime | localtime | msec | show-time-zone | year**] | **uptime**]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**service**
{**dhcp relay-agent | server** |	Enables DHCP server or relay agent.
dhcpv6 server |	Enables DHCPv6 server.
[**sequence-numbers**] |	Stamps the logger messages with a sequence number.
[**timestamps log datetime | localtime | msec | show-time-zone | year**] | **uptime**]}	Time stamp with date, time, and system uptime.

Command Modes	Perle(config)#service

Usage Guidelines

Use this command to configure parameters for DHCP relay agent or server.

Examples

This example sets date, time, and year to DHCP log messages.

Perle(config)#service timestamp log datetime localtime year

Related Commands

logging

snmp-server

smnp-server

{**community** *<WORD>* **ip-access** *<A.B.C.D>* | **network** *<A.B.C.D>* *<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X:X>* | **ro** | **rw** |

contact *<LINE>* |

enable traps | [**alarms** *<2* | *3>* | **major** | **minor**] | **authentication** | **bgp** | **cellular-gnss** | **cellular-lte** | **dot11** | **entity** | **envmon** | **interface-ip** | **ipsec** | **lldp** | **network-watchdog** | **openvpn** | **ospf** | [**snmp authentication** | **coldstart** | **linkdown** | **linkup** | **warmstart**] | **software-update** |

engine-id local *<TEXT>* |

group *<WORD>* |

host *<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X]* *<WORD>* | [**version 2c** *<WORD>* **udp-port** *<0-65535>* | **version 2c** *<WORD>* **udp-port** *<0-65535>* | **version 3 engine-id** *<WORD>* | **informs engine-id** *<WORD>* | **traps engine-id** *<WORD>* | **user** *<WORD>* **auth md5 0** *<WORD>* **priv** [**aes 0** | **7** | *<WORD>* | **sha 0** *<WORD>* **priv** [**aes 0** | **7** | *<WORD>* | **des 0** | **7** | *<WORD>* | **udp-port** *<0-65535>* | *<WORD>* *<WORD>* **auth md5 0** *<WORD>* **priv** [**aes 0** | **7** | *<WORD>* | **sha 0** *<WORD>* **priv** [**aes 0** | **7** | *<WORD>* | **des 0** | **7** | *<WORD>* |

listen-address *<A.B.C.D>* | *<X:X:X:X::X:X>* **udp-port** *<0-65535>* |

location *<WORD>* |

user *<WORD>* *<WORD>* **v3** [**auth encrypted** | **sha** *<WORD>* **priv aes** | **des** *<WORD>*] | [**encrypted auth md5** *<WORD>* **priv aes** *<WORD>* | **sha** *<WORD>*] |

view *<WORD>* **excluded** *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	snmp-server

{**community** *<WORD>* **ip-access** *<A.B.C.D>* | **network** *<A.B.C.D>* *<A.B.C.D>* | *<WORD>* | *<X:X:X:X::X:X>* **ro** |	Configure community strings and access privileges. IP-access • *<A.B.C.D>* IPv4 address of SNMP client allowed to contact system • **network** *<A.B.C.D>* *<A.B.C.D>* subnet of SNMP clients allow to contact the system • *<WORD>* host name of the SNMP client allow to contact the system • *<X:X:X:X::X:X>* IPv6 address of the host allow to contact the system
	ro–read only access with this community string rw–community access with this community string
contact *<LINE>* |	Configure the contact name. (mib object sysContact).
enable traps | [**alarms** *<2* | *3>* | **major** | **minor**] | **authentication** | **bgp** | **cellular-gnss** | **cellular-lte** | **dot11** | **entity** | **envmon** | **interface-ip** | **ipsec** | **lldp** | **network-watchdog** | **openvpn** | **ospf** | [**snmp authentication** | **coldstart** | **linkdown** | **linkup** | **warmstart**] | **software-update** |	Enables SNMP traps and inform messages.
engine-id *<text>* |	Configure the default engine-id. Your Router uses the MAC address of the Ethernet interface to ensure that the Engine-id is unique to this agent. To set the engine id back to default, enter "".
group *<WORD>* |	Configure a SNMPv3 user security model.

host [<*A.B.C.D*> | <*WORD*> | <*X:X:X:X::X*] <*WORD*> | [version 2c <*WORD*> udp-port <*0-65535*> | version 2c <*WORD*> udp-port <*0-65535*> | version 3 engine-id <*WORD*> | informs engine-id <*WORD*> | traps engine-id <*WORD*> | user <*WORD*> auth md5 0 <*WORD*> priv [aes 0 | 7 | <*WORD*> | sha 0 <*WORD*> priv [aes 0 | 7 | <*WORD*> | des 0 | 7 | <*WORD*> | udp-port <*0-65535*> | <*WORD*> <*WORD*> auth md5 0 <*WORD*> priv [aes 0 | 7 | <*WORD*> | sha 0 <*WORD*> priv [aes 0 | 7 | <*WORD*> | des 0 | 7 | <*WORD*> |	Configure hosts to receive SNMP notifications. Engine ID is the remote Engine ID.
listen-address <*A.B.C.D*> | <*X:X:X:X::X:X*> udp-port <*0-65535*> |	Configure the listen address for incoming requests.
location <*LINE*> |	Configure the name for MIB object sysLocation. This is the physical location of this node.
user <*WORD*> <*WORD*> v3 [auth md5 | sha <*WORD*> priv aes | des <*WORD*>] [encrypted auth md5 <*WORD*> priv aes <*WORD*> | sha <*WORD*> |	Configure options for SNMP V3 user.
view <*WORD*> excluded <*WORD*>}	Configure a SNMPv3 MIB family view, Excludes this family MIB from the view.
Command Modes	Perle(config)#snmp-server

Usage Guidelines

Use this command to configure SNMP server parameters.

Examples

This example sets community name to public and contact person to admin, then enable trap messages for authentication.

```
Perle(config)#community public
Perle(config)#snmp-server contact admin
Perle(config)#snmp-server enable traps authentication
```

Related Commands

show snmp

standby

standby

{[**low-voltage contact** *<1-2>* **standby-voltage** *<5.8-29.4>* **standby-delay** *<30-3600>* | **wakeup-voltage** *<6.8-30.0>* **wakeup-delay** *<1-30>* **enable**]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	standby
{**low-voltage contact** *<1-2>* **standby-voltage** *<5.8-29.4>* **standby-delay** *<30-3600>* | **wakeup-voltage** *<6.8-30.0>* **wakeup-delay** *<1-30>* **enable**}	Configure standby mode parameters.
Command Default	standard
Command Modes	Perle(config)#standby

Usage Guidelines

Use this command to configure power management standby settings. Standby mode exists on some models only.

Examples

This example monitors low-voltage

Perle(config)#standby low-voltage enable<cr>

Related Commands

alarm

standby

(config-smrt-stdby)

tacacs

tacacs

{**server** *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	tacacs
{**server** *<WORD>*}	Configure TACACS+ server name.
Command Modes	Perle(config)#tacacs

Usage Guidelines

Use this command to configure TACACS+ server name.

Examples

This example specifies the name of the TACACS+ server as TACTEST.

Perle(config)#tacacs server TACTEST

Related Commands

clear tacacs

show tacacs

(config-tacacs-server)

{**address ipv4** *<hostname* | *<A.B.C.D>* | **ipv6** *<hostname* | *X:X:X:X::X>* |
key 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |
timeout *<1-1000>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-tacacs-server)
{**address ipv4** *<hostname* | *<A.B.C.D>* | **ipv6** *<hostname* | *X:X:X:X::X>* |	Configure the IPv4 or IPv6 address for your TACACS server.
key 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |	Configure the encryption key to be shared with the TACACS server.
timeout *<1-1000>*}	Configure the timeout if the TACACS server doesn't respond,
Command Modes	Perle(config-tacacs-server)#

Usage Guidelines

Use this command to configure TACACS+ server parameters.

Examples

This example sets the IPv4 address for your TACACS+ server to 172.17.88.99.

Perle(config-tacacs-server)# address ipv4 172.17.88.99

Related Commands

tacacs

clear tacacs

show tacacs

tacacs-server

tacacs-server

{**deadtime** *<1-1440>* |
key 0 *<WORD>*7 *<WORD>* | *<WORD>* |
retransmit *<1-100>* |
timeout *<1-1000>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	tacacs-server
{**deadtime** *<1-1440>* |	Sets the time the router ignores unresponsive TACACS+ servers.
key 0 *<WORD>***7** *<WORD>* | *<WORD>* |	Configure an encryption key to be shared with the TACACS+ servers.
retransmit *<1-100>* |	Configure the number of retries to the active TACACS+ server.
timeout *<1-1000>*	Configure the time to wait for the TACACS+ server to reply.
Command Modes	Perle(config)#tacacs-server

Usage Guidelines

Use this command to configure TACACS+ server parameters.

Examples

This example sets the TACACS+ server name.

```
Perle(config)#tacacs-server
```

tty

tty

{*<1-2>* **mode console | disable | gnss | line**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	tty
{**tty** *<1-2>* **modeconsole	disable	gnss	line**}	Command only exists on models with serial ports. Configure serial port mode.
Command Modes	Perle(config)#tty

Usage Guidelines

Use this command to configure the mode for the tty port.

Examples

This example set tty port 1 to line mode.

Perle(config)#tty 1 mode line

usb

usb

{**mode console | disable | ethernet | gnss**}

Use the no form of this command to negate tty parameters.

Syntax Description	usb
{**mode console	disable	ethernet	gnss**}	Configure usb port mode. Mode Ethernet is not available on some models.
Command Modes	Perle(config)#usb

Usage Guidelines

Use this command to configure the USB port mode.

Examples

This example sets the usb port to be used for console mode.

Perle(config)#usb console

Related Commands

(config-line)#console

(config-gnss-usb)

(config-if-ethernet)#

(config-if)#bvi

username

username

{*<WORD>* |
access schedule *<1-10>* *<hh:mm>* *<hh:mm>* **friday | monday | saturday | sunday | thursday | tuesday | wednesday** |
nopassword |
openvpn-user |
privilege 1 | 10 | 11 | 15 |
secret 0 *<LINE>* **| 5** *<WORD>* **|** *<LINE>* |
serial |
two-factor |
web-access dashboard | diagnostics | logging | monitor-statistics | reset}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	username
{*<WORD>* **nopassword** | |	Configure local user names and passwords
access schedule *<1-10>* *<hh:mm>* *<hh:mm>* **friday | monday | saturday | sunday | thursday | tuesday | wednesday** |	Configure date and time the user is allow access. Note: the user must exist to see this option.
nopassword |	No password is required for user to log in.
openvpn-user |	Configure user as an openVPN user.
privilege 1 | 10 | 11 | 15 |	**Privilege levels** • 1—User Level (User Exec Only) • 10—User Privilege Level (Web only) • 11—User Privilege Level (Restful API only) • 15—User Privilege Level, EXEC, Web, and REST API)
secret 0 *<LINE>* **| 5** *<WORD>* **|** *<LINE>* |	Configure a secret or password for this user. • 0—The unencrypted password follows • 5—An encrypted password follows • LINE—The unencrypted (cleartext) user password
serial |	This user is a serial user. Define more parameters for this user here ***(config-user-serial)***. Note: user must exist to see this option.

two-factor |	This user uses 2–factor authentication. Define more parameters for this user here ***(config-user-2factor)***. Note: User must exist to see this option
web-access dashboard | diagnostics | logging | monitor-statistics | reset}	10—User Privilege Level (Web only), select the information that can be accessed by this user.
Command Modes	Perle(config)#username

Usage Guidelines

Use this command to set user parameters.

Privilege level

- 1— Specifies user privilege level (user exec)
- 10—User Privilege Level (Web only)
- 11—User Privilege Level Restful API only)
- 15—Specifies privilege exec level (privilege exec)

Secret

- 0—Specifies that an UNENCRYPTED password follows.
- 5— Specifies an ENCRYPTED password follows.
- LINE – the UNENCRYPTED (cleartxt) password.

Examples

This example creates a user with user exec privileges and a clear text password.

```
Perle(config)#username lyn privilege 1 secret password123
```

Related Commands

show username

(config-user-serial)

(config-user-2factor)

(config-user-serial)

{**callback off** | **on** |
framed-compression off | **on** |
framed-interface-id *<ipv6 interfac id>* |
framed-ip *<A.B.C.D>* |
framed-mtu *<64-1500>* |
host-ip *<Hostname>* | *<A.B.C.D>* | *<X:X:X:X::X>* |
hotkey-prefix *<1-ff>* |
idle-timer *<0-4294967>* |
line-access readin *<1-8> <17-24>* | **readout** *<1-8> <17-24>* | **readwrite** *<1-8> <17-24>* |
netmask *<A.B.C.D>* |
phone-number *<phone-number> <A.B.C.D>*] |
port ssh *<1-65535>*| **ssl_raw** *<1-65535>* | **tcp-clear** *<1-65535>* | **telnet** *<1-65535>*] |

routing listen | none | send | send-and-listen |
service dsprompt | ppp | rlogin | slip | ssh | ssl-raw | tcp-clear | telnet] |
sess-timer *<0-4294967>* |
session *<1-4>* **[auto off | on] | [rlogin-options host** *<hostname>* **|** *<A.B.C.D>* **|** *<X:X:X:X::X>***| termtype** *<WORD>***] | ssh-options | telnet-options echo** *<0-0x7f>* **| eof** *<0-0x7f>* **| erase** *<0-0x7f>* **| escape** *<0-0x7f>* **| host** *<hostname>* **|** *<A.B.C.D>* **|** *<X:X:X:X::X>* **| intr** *<0-0x7f>* **| [line-mode off | on] | [local-echo off | on] | [map-cr-crlf on | off] | port** *<1-65535>***| quit** *<0-0x7f>* **| termtype** *<WORD>* |
type [off | rlogin | ssh | telnet]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-user-serial)
{**callback off	on** |	Set the port for callback mode. • on • off
**framed-compression off	on** |	Configure Van Jacobson Compression. • on • off
framed-interface-id *<ipv6 interface id>* |	Configure the IPv6 interface identifier. The second part of an IPv6 unicast or anycast address is typically a 64-bit interface identifier used to identify a host's network interface. For example, if the MAC address of a network card is 00:BB:CC:DD:11:22 the interface ID would be 02BBCCFFFEDD1122
framed-ip *<A.B.C.D>* |	Configure the IPv4 address
framed-mtu *<64-1500>* |	Configure Maximum Transmission Unit (mtu) size. Default is 1500 Values are 64 to 1500
host-ip *<Hostname>* | *<A.B.C.D>* | *<X:X:X:X::X>* |	Configure a hostname, IPv4 or IPv6 address.
hotkey-prefix *<1-ff>* |	The prefix that a user types to control the current session. • Data Options: ^a number—To switch from one session to another, press ^a (Ctrl-a) and then the required session number. For example, ^2 would switch you to session 2. Pressing ^a 0 returns you to the Router Menu.

	• ^a n—Display the next session. The current session remains active. The lowest numbered active session is displayed. • ^a p—Display the previous session. The current session remains active. The highest numbered active session is displayed. • ^a m—To exit a session and return to the router. You are returned to the menu. The session is left running. • ^a l—(Lowercase L) Locks the serial port until the user unlocks it. The user is prompted for a password (any password, excluding spaces) and the serial port is locked. The user must retype the password to unlock the serial port. • ^r—When you switch from a session back to the Menu, the screen may not be redrawn correctly. If this happens, use this command to redraw it properly. This is always Ctrl R, regardless of the Hotkey Prefix. The User Hotkey Prefix value overrides the Serial Port Hotkey Prefix value. You can use the Hotkey Prefix keys to lock a serial port only when the serial port's Allow Port locking parameter is enabled. Default is Hex 01 (Ctrl -a or ^a)
idle-timer ***<0-4294967>*** **|**	Configure a session inactivity timer in seconds. Default is 0 seconds so the port never times out. Values are 0 to 4294967 seconds
line-access readin ***<1-8> <17-24>*** **| readout** ***<1-8> <17-24>*** **| readwrite** ***<1-8> <17-24>*** **|**	Configure the access for the serial lines.
netmask ***<A.B.C.D>*** **|**	Configure the IPv4 netmask
phone-number ***<phone-number> <A.B.C.D>*** **|**	Configure the call back phone number.

port ssh ***<1-65535>*****| ssl_raw** ***<1-65535>*** **| tcp-clear** ***<1-65535>*** **| telnet** ***<1-65535>*** **|**	Configure the service to be used for outbound sessions on this port. • ssh • ssl-raw • tcp-clear • telnet
routing listen | none | send | send-and-listen |	Configure the routing mode (RIP, Routing Information Protocol) used on the PPP/SLIP interface. • listen—enable PPP/SLIP receiving of RIP • none—disable PPP/SLIP sending and receiving of RIP • send—enable PPP/SLIP sending and receiving of RIP • send-and-listen—enable PP/SLIP sending and receiving of RIP
service dsprompt | ppp | rlogin | slip | ssh | ssl-raw | tcp-clear | telnet |	Configure the service for outbound sessions. • dsprompt • ppp • rlogin • slip • ssh • ssl-raw • tcp-clear • telnet
sess-timer ***<0-4294967>*** **|**	Configure the maximum session time. Default is 0 seconds so the port never times out. Values are 0 to 4294967 seconds
session ***<1-4>*** **[auto off | on] | [rlogin-options host** ***<hostname>*** **|** ***<A.B.C.D>*** **|** ***<X:X:X:X::X>*****| termtype** ***<WORD>*****] | ssh-options | telnet-options echo** ***<0-0x7f>*** **| eof** ***<0-0x7f>*** **| erase** ***<0-0x7f>*** **| escape** ***<0-0x7f>*** **| host** ***<hostname>*** **|** ***<A.B.C.D>*** **|** ***<X:X:X:X::X>*** **| intr** ***<0-0x7f>*** **| [line-mode off | on] |**	Configure user session parameters.

[local-echo off | on] | [map-cr-crlf on | off] | port *<1-65535>*| quit *<0-0x7f>* | termtype *<WORD>* | type [off | rlogin | ssh | telnet]}	
Command Modes	Perle(config-user-serial)#

Usage Guidelines

Use this command to configure serial parameters for the user.

Examples

This example sets outbound telnet session for user fred.

```
Perle(config)#username fred serial
Perle(config-user-serial)# service telnet
```

(config-user-2factor)

{**email *<WORD>*** | **method email | sms** | **phone *<LINE>***]}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-user-2factor)**
{**email *<WORD>*** |	Configure the email address to receive the 2factor authentication request.
method email | sms |	Configure the method to send 2factor authentication by E–mail or SMS message.
phone *<LINE>*]}	ConfigureConfigure the phone number to send 2Factor authentication requests.
Command	Perle(config-user-2factor)#

Usage Guidelines

Use this command to configure 2factor authentication parameters for a user.

Examples

This example sets email authentication for 2factor authentication for user fred

```
Perle(config)#username fred two-factor
Perle(config-user-2factor)#email fred@yahoo.ca
Perle(config-user-2factor)#method email
Perle(config-user-2factor)#enable
```

Related Commands

email

wan

wan

{**failover** |
high-availability disable | failover | load-sharing] |
load-sharing flush-connections | local traffic | rule ***<1-9999>*** **| source-nat | sticky-inbound**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	wan
{**failover** |	Configure failover. Failover is defined as a mode where 2 or more WAN interfaces are configured, but only 1 interface is active at a time. Once IP HEALTH has detected that a WAN interface no longer has Internet connectivity, it will "failover" to the next active (via IP HEALTH status) WAN interface. **Note:** IP HEALTH profile(s) (ie. Ping or traceroute tests) and IP-HEALTH on EACH of the WAN interfaces, must be configured when using Wan high-availability. The IP HEALTH feature is used to determine whether an WAN interface has Internet connectivity (one or more of the ping or traceroute tests MUST pass).
high-availability disable | failover | loadsharing |	Configure the action for the High-availability feature.
load-sharing}	Configure Load Sharing. Load Sharing defines how routed traffic is sent over one or more configured active WAN interfaces. Unlike Failover mode where ALL routed traffic is cut over to the next highest priority active WAN interface, this mode defines how specific or all traffic is to be shared or divided over multiple active WAN interfaces. This is accomplished by defining one or more Load Sharing rules. **Flush-connections—**enables flushing to flush data on WAN interface outage. **Local traffic—**enables all local traffic in the rule. **Rule—**Configure a load–sharing rule.

	Source-nat—enables/disables source address translation on this rule. **Sticky-inbound**—enables/disables inbound connection tracking.
Command Modes	Perle(config)#wan

Usage Guidelines

Use this command to configure High Availability, Failover and Load Sharing features.

Examples

This example sets disables the High Availability feature.

Perle(config)#wan high-availability disable

Related Commands

(config-wan-failover)

{**source-interface bvi** ***<1-9999>*** | **cellular** ***<0-0>*** | **dialer** ***<0-15>*** | **dot11radio** ***<0-4>*** | **ethernet** ***<1-5>*** **.** ***<1-4000>*** | **openvpn-tunnel** ***<0-999>*** | **tunnel** ***<0-999>*** |

wan-interface bvi ***<1-9999>*** | **cellular** ***<0-0>*** | **dialer** ***<0-15>*** |**dot11radio** ***<0-4>*** | **ethernet** ***<1-5>*** **.** ***<1-4000>*** | **openvpn-tunnel** ***<0-999>*** | **tunnel** ***<0-999>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-wan-failover**
{**source-interface bvi** ***<1-9999>*** |**cellular** ***<0-0>*** | **dialer** ***<0-15>*** | **dot11radio** ***<0-4>*** | **ethernet** ***<1-5>*** **.** ***<1-4000>*** | **openvpn-tunnel** ***<0-999>*** | **tunnel** ***<0-999>*** |	Configure the source interface.
wan-interface bvi ***<1-9999>*** | **cellular** ***<0-0>*** | **dialer** ***<0-15>*** | **dot11radio** ***<0-4>*** | **ethernet** ***<1-5>*** **.** ***<1-4000>*** | **openvpn-tunnel** ***<0-999>*** | **tunnel** ***<0-999>***	Configure the WAN interface.
Command	Perle(config-wan-failover)#

Usage Guidelines

Use this command to configure source and WAN interfaces for failover.

Examples

This example configures source interface ethernet 1for failover mode.

Perle(config-wan-failover)#source-interface ethernet 1

Related Commands

show ip route

show wan

(config-loadshare-rule)

{**description** ***<LINE>*** |

exclude-rule |

limit burst ***<0-4294967295>*** | **period hour minute** | **second** | **rate** ***<0-4294967295>*** | **threshold above** | **below** |

match protocol ***<1-255>*** | **ah** | **dccp** | **dsr** | **egp** | **eigrp** | **encap** | **esp** | **etherip** | **ggp** | **gre** | **hmp** | **icmp** | **idpr** | **igmp** | **igp** | **ip** | **ipip** | **ipv6** | **ipv6-frag** | **ipv6-icmp** | **ipv6-nonxt** | **ipv6-opts** | **ipv6-route** | **isis** | **l2tp** | **manet** | **mpls-in-ip** | **narp** | **not** | **ospf** | **pim** | **rdp** | **rohc** | **rsvp** | **sctp** | **sdrp** | **skim6** | **skip** | **tcp** | **udp** | **udplite** | **vrrp** | **xns-idp** |

per-packeting-sharing |

source-interface bvi ***<1-9999>*** | **cellular** ***<0-0>*** | **dialer** ***<0-15>*** | **dot11radio** ***<0-4>*** | **ethernet** ***<1-5><1-24> . <1-4000>*** | **openvpn-tunnel** ***<0-999>*** | **tunnel** ***<0-999>*** |

wan-interface bvi ***<1-9999>*** **weight** ***<1-255>***| **cellular** ***<0-0>*** **weight** ***<1-255>*** | **dialer** ***<0-15>*** **weight** ***<1-255>*** | **dot11radio** ***<0-4>*** **weight** ***<1-255>*** | **ethernet** ***<1-5><1-24>*** **weight** ***<1-255> . <1-4000>*** **weight** ***<1-255>*** | **openvpn-tunnel** ***<0-999>*** **weight** ***<1-255>*** | **tunnel** ***<0-999>*** **weight** ***<1-255>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-loadshare-rule
{**description** ***<LINE>*** |	Configure the description for this rule.
exclude-rule |	Enable or disable this rule.
limit burst ***<0-4294967295>*** | **period hour minute** | **second** | **rate** ***<0-4294967295>*** | **threshold above** | **below** |	Configure packet limit for this rule.

match protocol *<1-255>* **| ah | dccp | dsr | egp | eigrp | encap | esp | etherip | ggp | gre | hmp | icmp | idpr | igmp | igp | ip | ipip | ipv6 | ipv6-frag | ipv6-icmp | ipv6-nonxt | ipv6-opts | ipv6-route | isis | l2tp | manet | mpls-in-ip | narp | not | ospf | pim | rdp | rohc | rsvp | sctp | sdrp | skim6 | skip | tcp | udp | udplite | vrrp | xns-idp**	Matches the criteria for this rule.
per-packeting-sharing |	Enables or disables per packet load sharing.
source-interface bvi *<1-9999>* **| cellular** *<0-0>* **|dialer** *<0-15>* **| dot11radio** *<0-4>* **| ethernet** *<1-5>* **.** *<1-4000>* **| openvpn-tunnel** *<0-999>* **| tunnel** *<0-999>* **|**	Select the source interface for matching criteria.
wan-interface bvi *<1-9999>* **weight** *<1-255>***| cellular** *<0-0>* **weight** *<1-255>* **| dialer** *<0-15>* **weight** *<1-255>* **| dot11radio** *<0-4>* **weight** *<1-255>* **| ethernet** *<1-5>* **weight** *<1-255>* **.** *<1-4000>* **weight** *<1-255>* **| openvpn-tunnel** *<0-999>* **weight** *<1-255>* **| tunnel** *<0-999>* **weight** *<1-255>*}	Select WAN interface and weight for participating in this load sharing rule.

Command	Perle(config-load-sharing-rules)#

Usage Guidelines

Use this command to configure load sharing rules.

Examples

This example configures the BVI interface 10 to be part of WAN load sharing.

Perle(config-loadshare-rule)#wan bvi 10

Related Commands

show ip route

show wan

(config-import-disk)

zone

zone

{**security** *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	zone
{security <*WORD*>}	Name of security zone.
Command Modes	Perle(config)#zone

Usage Guidelines

Use this command to create a security zone.

Examples

This example creates a zone with the name secure1.

```
Perle(config)#zone security secure1
```

Related Commands

zone-pair

show zone-policy

(config-sec-zone)

{**default-action drop | reject** | **description** <*WORD*> | **local-zone**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-sec-zone)
{**default-action drop	reject** |	Configure the default action for traffic coming into this zone. • Drop packets—silently drop the packets • Reject—drops packets and notifies the source Enter a zone description. Zone to be local-zoned.
description <*WORD*> |	Configure security zone description.
local-zone}	Sets zone to be local.
Command Modes	Perle(config-sec-zone)#

Usage Guidelines

Use this command to setup a default action for zone firewall.

Examples

This example rejects all incoming packets to this zone.

```
Perle(config)# default-action reject
```

Related Commands

show zone-policy

(config-import-disk)

zone-pair

zone-pair

zone-pair

{**from** ***<WORD>*** **to** ***<WORD>*** **firewall** ***<WORD>*** **| ipv6-firewall** ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	zone-pair
{**from** ***<WORD>*** **to** ***<WORD>*** **firewall** ***<WORD>*** **| ipv6-firewall** ***<WORD>***}	Configure parameters for zone pair firewalls. • From—zone from which to filter traffic • To—zone to which to filter traffic • Firewall—select firewall to be used to filter traffic (IPv4 or IPv6)
Command Modes	Perle(config)#zone-pair

Usage Guidelines

Use this command to create zone-pair firewalls.

Examples

This example filters traffic from lab-zone to office-z using secure zone 1.

```
Perle(config)#zone-pair from lab-zone to office-zone firewall secure1
```

Note: Secure zone 1 needs to be created first.

Related Commands

show zone-policy

(config-import-disk)

5 Interface configuration

This chapter defines all the CLI commands in Interface Configuration Mode. Some CLI commands may not be applicable to your model or running software.

Interface

interface

{**bvi** *<1-9999>* |
cellular *<0-0>* |
dialer *<0-15>* |
dot11radio *<0-4>* |
ethernet *<1-5>.<1-4000>* |
loopback |
openvpn-tunnel *<0-999>* | **tap** | **tun** |
tunnel *<0-999>* |
range ethernet *<1-5>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	interface
{**bvi** *<1-9999>* |	Configure for a bridge interface. See ***(config-if)#bvi***.
cellular *<0-0>* |	Configure for a cellular interface. See ***(config-if)#cellular***.
dialer *<0-15>* |	Configure for a dialer interface. See ***(config-if)#dialer***
dot11radio *<0-4>* |	Configure for a wireless interface. See ***(config-if)#dot11radio***
ethernet *<1-5>.<1-4000>*|	Configure for an Ethernet interface. See ***(config-if-ethernet)#***
loopback |	Configure for a loopback interface.
openvpn-tunnel *<0-999>* **tap** | **tun** |	Configure for an OpenVPN tunnel interface. See ***(config-if)#openvpn-tunnel***
tunnel *<0-999>* |	Configure for a tunnel interface. See ***(config-if)#tunnel***
range ethernet *<1-5>*}	Configure an Ethernet range. ***(config-if-range)#***
Command Modes	Perle(config) #interface ethernet 1 Perle(config-if)#

Usage Guidelines

Use this command to configure the interface type and number.

Examples

This example enter sub-menu configuration for Ethernet interface 1.

Perle(config)#interface ethernet 1

Related Commands

(config-if)#bvi

(config-if)#openvpn-tunnel

(config-if)#tunnel

(config-if)#dot11radio

(config-if)#cellular

(config-if)#dialer

(config-if)#bvi

{arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp | timeout *<1-2147483>* |

description *<LINE>* |

ip [address *<A.B.C.D>* *<A.B.C.D>* secondary | dhcp] | [ddns service dyndns login *<WORD>* password *<WORD>* | host *<WORD>* | host-group *<WORD>*] |[use-web skip *<WORD>* | url *<WORD>*] | [dhcp client class-id *<LINE>* | auto | client-id ethernet *<1-5>*| ascii *<WORD>* | auto | hex *<Hex-String>* | hostname *<WORD>*] | [dhcp-relay] | [dns dhcp] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop [*<A.B.C.D>* | dhcp] vrrp *<1-255>*] [bvi *<1-9999>*] | [ethernet *<1-5>*] good-prio *<1-255>* bad-prio *<1-255>*] | [ospf authentication message-digest | null | authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [cost *<1-65535>* | [dead-interval *<1-65535>*] | [hello-interval *<1 -65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-multipoint point-to-point] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | split-horizon disable | poison-reverse] |

ipsec restrict |

ipv6 [address [*<X:X:X:X::X/<0-128>* eui-64] | dhcp | autoconfig] | [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempts *<0-600>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128>* *<0-4294967294>* | no-autoconfig | no-onlink | infinite] | [ra dns server *<X:X:X:X::X>*] | [hop-limit *<1-255>* | unspecified | interval *<4-1800>* *<3-1350>*] | [lifetime *<0>* *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low | medium] | [ospf cost *<1-65535>* | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] | [instance-id *<0-255>*] | [mtu-ignore] | [network broadcast | point-to-point] | [passive] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon | disable poisoned-reverse] |

logging event interface-ip | link-status |

mac access-group *<WORD>* deny | disable | permit |

mtu *<68-1500>* |

ntp [broadcast client | destination <*A.B.C.D*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] | [disable] | [multicast [<*A.B.C.D*> | <*X:X:X:X::X*> | [client <*A.B.C.D*> | <*X:X:X:X::X*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] |

role lan |trusted | wan |

service-policy in <*WORD*> | out <*WORD*> |

shutdown |

snmp trap interface-ip | link-status |

zone-member security <*WORD*>}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if)#bvi
{**arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp | timeout <*1-2147483*>** |	Configure ARP parameters. **Disable ARP filter**—If enabled the router responds to the same ARP requests coming from multiple interfaces. **Enable ARP Accept**—Define behavior for gratuitous ARP frames who's IP is not already present in the ARP table: • 0—don't create new entries in the ARP table • 1—create new entries in the ARP table **Enable ARP Announce**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface. • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **Enable ARP Ignore**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface. • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **ARP Timeout**—If an ARP entry is not used for a specific amount of time the entry is removed from the caching table.
description <*LINE*> |	Configure interface description.

ip [address *<A.B.C.D>* *<A.B.C.D>* secondary] | [ddns service dyndns login *<WORD>* password *<WORD>* | host *<WORD>* | host-group *<WORD>* | use-web skip *<WORD>* | url *<WORD>*] | [dhcp client class-id *<LINE>* | auto | client-id ethernet *<1-5>*| ascii *<WORD>* | auto | hex *<Hex-String>* | hostname *<WORD>*] | [dhcp-relay] | [dns dhcp] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop [*<A.B.C.D>* | *<dhcp>* vrrp *<1-255>* [bvi *<1-9999>*] | [ethernet *<1-5>*] good-prio *<1-255>* bad-prio *<1-255>*] | [ospf authentication message-digest | null | authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>]* | [cost *<1-65535>* | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>* | *<WORD>]* | [mtu-ignore] | [network broadcast | non-broadcast | point-to-multipoint point-to-point] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | split-horizon disable | poison-reverse] |	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface. **secondary**—add secondary or ip aliasing address for this interface. **DHCP—**your address is assigned from a DHCP server. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server. **Host/host-group—**Hostname/list of hostnames registered with the DDNS service. **skip**—skip everything before this on the given URL. **Use-web URL**—This field should be left blank. **DHCP client —** **Class ID**: ● Auto ● Line Specify a Class-id string, truncated to 200 characters. This same string or text will be configured on the server side and associated with an address to give the client. **Client ID:** This can be configured to be the Ethernet interface number, ASCII text, Hex string or set to Auto. option—60—Vendor class identifier<oem-name>:<model>:<serial#> in ASCII Router example: Perle:IRG5541:350-01T00003 **Hostname:** Specify a value for hostname option. **DHCP–relay—**set DHCP-relay for this interface. **DNS dhcp—**use DNS servers received from DHCP server for specified interface **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic.

health-profile—use this health profile for this interface, configure a nexthop and priority and interface.

OSPF—
authentication/authentication-key— enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD>.

cost—Configure a default metric to be applied to routes being distributed into OSPF.
Range is 0 to 16777214
Default is none

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.
Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
Default is 10 seconds

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5

authentication

  - 0-unencrypted key will follow
  - specifies a hidden key will follow
  - specifies a password (key) will follow (max 16 characters).
    The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this

command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.
- non-broadcast—use this type of network on networks having no broadcast/multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts

priority—a router with a high priority will always win the DR/BDR election process.
Priority Range is 0-255
Default is 1

retransmit-interval—Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network.
Range is 1–65535
Default is 5 seconds

	transmit-delay—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled
ipsec restrict |	Restricts IPsec on this interface.

ipv6 [address *<X:X:X:X::X/ <0-128>* eui-64 | dhcp] | [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempts *<0-600>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite| no-autoconfig | no-onlink] | ra dns server *<X:X:X:X::X>* | hop-limit *<1-255>* | unspecified | interval *<4-1800> <3-1350>* | lifetime *<0> <4-9000>* | suppress | reachable time *<0-3600000>* | retransmission-time *<0-3600000>* | [router-preference high | low | medium] | [ospf cost *<1-65535>* | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] | instance-id *<0-255>*] | [mtu-ignore] | [network broadcast | point-to-point] | [passive] | priority *<0-255>* | [retransmit-interval *<1-65535>* | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon | disable poisoned-reverse |	Configure IPv6 parameters. **IPv6 address/eui-64 or DHCP**—configure the IPv6 address and prefix length or obtain an IPv6 address using DHCP **enable**—enable IPv6 on this interface. **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **nd**—IPv6 Interface Neighbor Discovery sub-commands • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured. Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information. Default is disabled (hosts use stateless auto-configuration of no-address information

- prefix—specifies the IPv6 prefix advertised on the interface
  Configure the prefix length.
  Range is 0–128

no-autoconfig—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination.
Default is off

no-onlink—The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix.
Default is off

ra—Router Advertisement Control

dns server—specify the name server in RA

hop-limit—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets.
Range is 1–255
Default is 64

interval—Specifies the maximum/minimum time allowed between sending unsolicited multicast router advertisements.

Range of minimum is 3 to *0.75 max (dynamic range)
Default maximum 600 seconds, minimum is 0.33*max
Range is 1–1800 in seconds

lifetime—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list. The router lifetime applies only to the router's usefulness as a default router; it does not apply to information contained in other message fields or options.
Range is 4-1800 seconds

Minimum interval is 3-1350 in seconds
Default is 1800 seconds
0 = not a default route

suppress—enable or disable IPv6 Router advertisements.
Default is send router advertisements

reachable time—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation
Default is 0 (unspecified by this router)
Range is 0-360000 milliseconds

retransmission-time—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE).
Range 0–3600000 in milliseconds
Default is 0

router-preference—set the default router preference. A High value means this router will be preferred.

- **High**
- **Medium**
- **Low**

Default is medium

policy route-policy—enable this policy route for this interface.

Range is 0 to 16777214
Default is none

Default is 40 seconds

with the MTU value set on the interface.
rip—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received.

Default is enabled

OSPF—
cost—Configure a default metric to be applied to routes being distributed into OSPF.
Range is 0 to 16777214
Default is none

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead). As with the hello interval, this value must be the same for all routers attached to a common network.
Default is 4 times the hello interval

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

ifmtu—The range is dynamic (depending on the interface type) and it will match.
instance-id—instance ID for this interface.
Values are 0–255

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast—Specify OSPF broadcast multi-access network
- point-to-point—Specify OSPF point-to-point network

passive—no adjacency will be formed on this interface.

priority—A router with a high priority will always win the DR/BDR election process.
Priority Range is 0-255
Default is 1

	retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network Range is 1–65535 Default is 5 second **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. Range is 1–65535 Default is 1 second
logging event interface-ip | link-status |	Configure interface logging events and link status.
mac access-group *<WORD>* deny | disable | permit |	Configure mac access-group parameters for this interface.
mtu *<68-1500>* |	Configure maximum transmission unit (MTU). Values are 68-1500 bytes Default is 1500 bytes

ntp [broadcast client | destination <*A.B.C.D*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] | [disable] | [multicast [<*A.B.C.D*> | <*X:X:X:X::X*> | client <*A.B.C.D*> | <*X:X:X:X::X*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network. The router can provide the time to NTP/ SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the ruter. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts **destination broadcast**—Configure broadcast destination address **multicast** client—listens to NTP multicasts **destination multicast**—multicast IPv4 or IPv6 address **key**—Configure broadcast authentication key **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side **WAN—**management access is from the WAN side **Trusted—**management access from either the LAN or WAN side
service-policy in <*WORD*> | out <*WORD*>|	Assigns interface service policy. Configure for the policy for inbound or outbound traffic.
shutdown |	Shutdown this interface.
snmp trap interface-ip | link-status |	Configure interface SNMP traps and link status.
zone-member security <*WORD*>}	Configure this interface as a member of this zone security.

Command Modes	Perle(config-if)#

Usage Guidelines

Use this command to configure parameters for the bridge interface.

Examples

This example enables an IP address on bvi 10.

```
Perle>enable
Perle#config
Perle#interface bvi 10
(config-if)#ip address 172.16.113.45 255.255.0.0
```

Related Commands

(config-if)#openvpn-tunnel
(config-if)#tunnel
(config-if-ethernet)#
(config-if)#dialer
(config-if)#dot11radio
(config-if)#cellular

(config-if)#cellular

{**alarm profile** *<WORD>* |
description *<LINE>* |
idle-time *<LINE>* |
ip [ddns service dyndns login *<WORD>* **password** *<WORD>* **host** *<WORD>* | **host-group** *<WORD>* | **use-web skip**
ipsec restrict |
ipv6 [autoconfig] | [enable] | [firewall in | out | local *<WORD>***] | [ospf cost** *<1-65535>* | **dead-interval** *<1-65535>* | **hello-interval** *<1-65535>* | **ifmtu | instance-id** *<0-255>* | **mtu-ignore | network broadcast | point-to-point | passive | priority** *<0-255>* | **retransmit-interval** *<1-65535>* | **transmit-delay** *<1-65535>***] | [policy route-policy** *<WORD>***] |[rip enable | split-horizon | disable poisoned-reverse]** |
logging event interface-ip | link-status |
monitor traffic both receive | transmit |
mtu *<64-9000>*
ntp [broadcast client | destination *<A.B.C.D>***] | [key** *<1-65534>***] | [minpoll** *<4-17>***] | [version** *<1-4>***] | [disable] | [multicast [**<*A.B.C.D*> | <*X:X:X:X::X*> | **client** <*A.B.C.D*> | <*X:X:X:X::X*>**] | [key** *<1-65534>]* | **[minpoll** *<4-17>***] | [version** *<1-4>***]** |
on-demand |
start-connected |
service-policy in *<WORD>* | **out** *<WORD>* |
snmp trap interface-ip | link-status | start-connected |
zone-member security *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if)#cellular
{**alarm profile** ***<WORD>*** |	Use this alarm profile for this interface.
description ***<LINE>*** |	Configure interface description.
idle-time ***<LINE>*** |	Configure time to drop the "on demand" connection.
ip [ddns service dyndns login ***<WORD>*** **password** ***<WORD>*** **host** ***<WORD>*** **| host-group** ***<WORD>*** **| use-web skip** ***<WORD>*** **| url** ***<WORD>*****] | [dhcp-relay] | [dns dhcp] | [firewall in | local | out** ***<WORD>*****] | [health-profile** ***<WORD>*** **nexthop** ***<A.B.C.D>*****] | [ospf authentication message-digest | null | [authentication-key 0** ***<WORD>*** **| 7** ***<WORD>*** **|** ***<WORD>*****] | [cost** ***<1-65535>*****] | [dead-interval** ***<1-65535>*****] | [hello-interval** ***<1-65535>*****] | [message-digest-key** ***<1-255>*****md5 0** ***<WORD>*** **| 7** ***<WORD>*** **|** ***<WORD>*****] | [mtu-**	Configure IP parameters. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server. **Host/host-group—**Hostname/list of hostnames registered with the DDNS service. **skip—**skip everything before this ont he given URL. **DHCP–relay—**set DHCP-relay for this interface. **DNS dhcp—**use DNS servers received from DHCP server for specified interface. **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic.

ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | split-horizon disable | poison-reverse] |	Configure IP parameters. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server. **Host/host-group—**Hostname/list of hostnames registered with the DDNS service. **skip—**skip everything before this ont he given URL. **DHCP–relay—**set DHCP-relay for this interface. **DNS dhcp—**use DNS servers received from DHCP server for specified interface. **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic. **health-profile—**use this health profile for this interface, configure a nexthop, priority and interface. **OSPF—** **authentication/authentication-key—**enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD>. **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0 to 16777214 Default is none **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network. Default is 4 times the hello interval Default is 40 seconds **hello interval—**Configure the hello packet time interval for hello packets sent on an interface. The default is 10 seconds. **message-digest-key**—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value. • None—no password • Key-ID—Configure an authentication key

- md5—Identifies the key (password) used between this router and neighboring routers for MD5 authentication

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.
- non-broadcast—use this type of network on networks having no broadcast/multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts

priority—a router with a high priority will always win the DR/BDR election process.
Priority Range is 0-255
Default is 1

retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network.

	Range is 1–65535 Default is 5 second Default is 1 seconds **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. Range is 1–65535 **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled
ipsec restrict |	Restrict IPsec on this interface.

ipv6 [autoconfig] | [enable] | [firewall in | out | local *<WORD>*] | [ospf cost *<1-65535>* | dead-interval *<1-65535>* | hello-interval *<1-65535>* | ifmtu | instance-id *<0-255>* | mtu-ignore | passive | priority *<0-255>* | retransmit-interval *<1-65535>* | transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon | disable poisoned-reverse] |	Configure IPv6 parameters. **auto-config**—obtains an address using autoconfiguration **enable**—enable IPv6 on this interface **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **OSPF—** **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0–16777214 Default is none **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network. Default is 4 times the hello interval Default is 40 seconds **hello interval—**Configure the hello packet time interval for hello packets sent on an interface. The default is 10 seconds. **ifmtu**—The range is dynamic (depending on the interface type) and it will match with the MTU value set on the interface. **instance-id—**instance ID for this interface. Values are 0–255

	mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors. **network**— • broadcast–Specify OSPF broadcast multi-access network • point-to-point–Specify OSPF point-to-point network **passive**—no adjacency will be formed on this interface. **priority**—A router with a high priority will always win the DR/BDR election process. Priority Range is 0-255 Default is 1 **retransmit-interval**—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. Range is 1–65535 Default is 5 second **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled
logging event interface-ip | link-status |	Configure interface logging events and link status.

monitor-traffic both | receive | transmit] |	Monitors the traffic for on demand feature. Traffic can be monitored for: • in • out • both
mtu ***<64-9000>*** **|**	Sets Maximum Transmission Unit. (MTU). Values are 64-9000 bytes Default is 1460 bytes
ntp [broadcast client | destination ***<A.B.C.D>*****] | [key** ***<1-65534>*****] | [minpoll** ***<4-17>*****] | [version** ***<1-4>*****] | [disable] | [multicast [***<A.B.C.D>*** |** ***<X:X:X:X::X>*** **| client** ***<A.B.C.D>*** **|** ***<X:X:X:X::X>*****] | [key** ***<1-65534>*****] | [minpoll** ***<4-17>*****] | [version** ***<1-4>*****] |**	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network The router can provide the time to NTP/SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts. **destination broadcast**—Configure broadcast destination address. **multicast** client—listens to NTP multicasts. **destination multicast**—multicast IPv4 or IPv6 address. **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s). Default is 6
on-demand |	On demand feature brings up the interface when there is data to be sent or received only.
service-policy in ***<WORD>*** **| out** ***<WORD>*** **|**	Assigns traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
snmp trap interface-ip | link-status |	Sets interface SNMP traps and link status.
start-connected |	Establishes LTE data connection after reload or power up.
zone-member security ***<WORD>***}	This interface is a member of this zone security.

Command Modes	Perle(config-if)#

Usage Guidelines

Use this command to configure cellular profile parameters.

Examples

This example starts cellular connection after the router reboots.

```
Perle(config)# interface cellular 0
Perle(config-if)#start-connected
```

Related Commands

Interface

show bridge

(config-if)#dialer

{**default-route auto | none | force** |

description *<LINE>* |

encapsulation ppp |

ip [address *<A.B.C.D> <A.B.C.D>***] | [ddns service dyndns login** *<WORD>* **password** *<WORD>* **| host** *<WORD>* **| host-group** *<WORD>* **| use-web skip** *<WORD>* **| url** *<WORD>***] | [dhcp-relay] | [firewall in | out | local** *<WORD>***] | [health-profile** *<WORD>* **nexthop** *<A.B.C.D>***] | [ospf authentication message-digest | null | authentication-key 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>]* **| [cost** *<1-65535>***] | [dead-interval** *<1-65535>***] | [hello-interval** *<1-65535>***] | [message-digest-key** *<1-255>* **md5 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>***] | [mtu-ignore | network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority** *<0-255>***] | [retransmit-interval** *<1-65535>***] | [transmit-delay** *<1-65535>***] | [policy route-policy** *<WORD>***] | [rip authentication key-chain** *<WORD>* **| mode md5 | text string 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>* **| split-horizon disable | poison-reverse]** |

ipsec restrict |

ipv6 [address autoconfig] | [enable] | [firewall in | out | local *<WORD>***] | [ospf [cost** *<1-65535>***] | [dead-interval** *<1-65535>***] | [hello-interval** *<1-65535>***] | ifmtu | [instance-id] | [mtu-ignore] | [network broadcast | point-to-point] |[priority** *<0-255>***] | [retransmit-interval** *<1-65535>***] | [transmit-delay** *<1-65535>***] | [policy route-policy** *<WORD>***] | [rip enable | split-horizon | disable poisoned-reverse** |

logging event interface-ip | link-status] |

mtu *<64-1500>* |

ntp [broadcast client | destination *<A.B.C.D>***] | [key** *<1-65534>***] | [minpoll** *<4-17>***] | [version** *<1-4>***] | [disable] | [multicast [**<*A.B.C.D>* | *<X:X:X:X::X>* **| client** *<A.B.C.D>* | *<X:X:X:X::X>***] | [key** *<1-65534>***] | [minpoll** *<4-17>***] | [version** *<1-4>***]** |

ppp access-concentrator *<LINE>* **| chap hostname** *<WORD>* **| password 0** *<LINE>* **| 7** *<LINE>* **|** *<LINE>* **| timeout idle** *<1-4294967>* |

role lan | trusted | wan |

service-policy in ***<WORD>*** **| out** ***<WORD>*** **|**
shutdown |
snmp trap interface-ip | link-status |
zone-member security ***<WORD>***}
Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if)#dialer
{**default-route auto | none | force |**	Default-route—enable/disable default route to peer. • auto—install default route when link comes up • none—don't install default route when link comes up
	• none—don't install default route when link comes up
description ***<LINE>*** **|**	Configure interface name.
encapsulation ppp |	Sets encapsulation type.

ip [address *<A.B.C.D>* *<A.B.C.D>*] | [ddns service dyndns login *<WORD>* password *<WORD>* | host *<WORD>* | host-group *<WORD>* | use-web skip *<WORD>* | url *<WORD>*] | [dhcp-relay] | [firewall in | out | local *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>*] | [ospf authentication message-digest | null | authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>]* | [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [mtu-ignore | network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority*<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | split-horizon disable | poison-reverse]	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server. **Host/host-group—**Hostname/list of hostnames registered with the DDNS service. **skip—**skip everything before this ont he given URL. **Use-web URL**—Enter the URL that you want to obtain an IP address from. This allows the router to be seen on the Internet as a public address. **DHCP–relay—**set DHCP-relay for this interface. **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic **health-profile—**use this health profile for this interface, configure a nexthop interface. **OSPF—** **authentication/authentication-key—** enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD>. **cost**—Configure a default metric to be applied to routes being distributed into

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.

Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5

authentication.

  - 0-unencrypted key will follow
  - specifies a hidden key will follow
  - specifies a password (key) will follow (max 16 characters).
    The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all.

- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship.
- Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.
- non-broadcast—use this type of network on networks having no broadcast/ multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts

priority—a router with a high priority will always win the DR/BDR election process.
Priority Range is 0-255
Default is 1

retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network.
Range is 1–65535
Default is 5 second

transmit-delay—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission.
Range is 1–65535
Default is 1 seconds

policy route-policy—enable this policy route for this interface.

rip—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received.

Default is enabled

ipsec restrict |	Restrict IPsec on this interface.

ipv6 [address autoconfig] | [enable] | [firewall in | out | local *<WORD>*] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | ifmtu | [instance-id] | [mtu-ignore] |[network broadcast | point-to-point] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon disable | poisoned-reverse] |	Configure IPv6 parameters. **auto-config**—obtains an address using autoconfiguration. **enable**—enable IPv6 on this interface **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **OSPF—** **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0–16777214 Default is none **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network. Default is 4 times the hello interval Default is 40 seconds **hello interval—**Configure the hello packet time interval for hello packets sent on an interface. The default is 10 seconds. **ifmtu**—The range is dynamic (depending on the interface type) and it will match with the MTU value set on the interface. **instance-id—**instance ID for this interface. Values are 0–255 **mtu-ignore**—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors. **Network—** • broadcast–Specify OSPF broadcast multi-access network • point-to-point–Specify OSPF point-to-point **passive**—no adjacency will be formed on this interface. **priority**—A router with a high priority will always win the DR/BDR election process. Priority Range is 0-255 Default is 1

	retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. Range is 1–65535 Default is 5 second **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. Range is 1–65535 **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received Default is enabled
logging event interface-ip | link-status |	Configure interface logging events and link status.
mtu *<64-1500>* |	Sets Maximum Transmission Unit (MTU). Values are 64-1500 bytes Default is 1492
ntp [broadcast client | destination *<A.B.C.D>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] | [disable] | [multicast [*<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network. The router can provide the time to NTP/SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface.

	broadcast client—listens to NTP broadcasts. **destination broadcast**—Configure broadcast destination address. **multicast** client—listens to NTP multicasts. **destination multicast**—multicast IPv4 or IPv6 address. **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
ppp access-concentrator ***<LINE>*** **| chap hostname** ***<WORD>*** **| password 0** ***<LINE>*** **| 7** ***<LINE>*** **|** ***<LINE>*** **| timeout idle** ***<1-4294967>*** **|**	Configure Point to Point protocol parameters.
role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side **WAN—**management access is from the WAN side **Trusted—**management access from either the LAN or WAN side
service-policy in ***<WORD>*** **| out** ***<WORD>*** **|**	Assigns a traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
shutdown |	Shut down this interface.
snmp trap interface-ip | link-status	Configure for SNMP traps for interface and link status.
zone-member security ***<WORD>***}	This interface is a member of this zone security.
Command Modes	Perle(config-if)#

Usage Guidelines

Sets parameters for dialer interface.

Examples

This example sets the role for this interface to WAN.

Perle(config-if)role wan

Related Commands

(config-if)#bvi

(config-if)#dialer

(config-if)#tunnel

(config-if)#openvpn-tunnel

(config-if)#cellular

(config-if)#dot11radio

(config-if)#dot11radio

{**arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp** |

bridge-group *<1-9999>* |

channel *<1-11>* |

dot11ac [antenna-pattern-fixed] | [center-channel-frequency *<34-173>*] | [**channel-width vht40 | vht80] | [ldpc] | [max-mpdu** *<11454> <7991>*] | [**max-mpdu-exp** *<1-7>*] | [**require-vht] | [short-gi** *<20 | 40 | 80>*] | [**stbc rx-stbc rx-stbc-1 | tx-stbc]** |

dot11n [40mhz-incapable] | [a-msdu *<7935>*] | [**auto-power-save] | [channel-width ht40+ | ht40-] | [dsss-cck-40mhz] | [ldpc] | [require-ht] | [short-gi** *<20 | 40>*] | [**stbc rx-stbc rx-stbc-1 | tx-stbc]** |

ip [address *<A.B.C.D> <A.B.C.D>* **secondary | dhcp] | [ddns service dyndns login** *<WORD>* **password** *<WORD>* **host** *<WORD>* **host-group** *<WORD>* **| use-web skip** *<WORD>* **| url** *<WORD>*] | [**dhcp client class-id** *<LINE>* **| auto | client-id ethernet** *<1–5>*| **ascii** *<WORD>* **| auto | hex** *<Hex-String>* **| hostname** *<WORD>*] | [**dhcp-relay] | [dns dhcp] | [firewall in | out | local** *<WORD>*] | [**health-profile** *<WORD>* **nexthop** *<A.B.C.D>*] | [**ospf authentication message-digest | null] | [authentication-key 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>*] | [**cost** *<1-65535>]* | [**dead-interval** *<1-65535>*] | [**hello-interval** *<1-65535>*] | [**message-digest-key** *<1-255>* **md5 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>*] | [**mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority** *<0-255>*] | [**retransmit-interval** *<1-65535>*] | [**transmit-delay** *<1-65535>*] | [**policy route-policy** *<WORD>*] | [**rip authentication key-chain** *<WORD>* **| mode md5 | text string 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>* **| split-horizon disable | poison-reverse]** |

ipsec restrict |

ipv6 [address dhcp] | [enable] | [firewall in | out | local *<WORD>*] | [**nd dad attempts** *<0-600>* **| managed config-flag | other-config-flag | prefix** *<X:X:X:X::X/<0-128> <0-4294967294>* **| infinite | no-autoconfig | no-onlink] | [ra dns server** *<X:X:X:X::X>* **| [hop-limit** *<1-255>* **| unspecified | interval** *<4-1800> <3-1350>]* | [**lifetime** *<0><4-9000>]* | [**suppress] | [reachable time** *<0-3600000>]* | [**retransmission-time** *<0-3600000>*] | [**router-preference high | low |medium] | [ospf cost** *<1-65535>* **| [dead-interval** *<1-65535>*] | [**hello-interval** *<1-65535>*] | [**ifmtu] | [instance-id** *<0-255>*] | [**mtu-ignore] | [network broadcast | point-to-point] | [mtu-ignore] | [passive] | [priority** *<0-255>*] | [**retransmit-interval** *<1-65535>*] | [**transmit-delay** *<1-65535>*] | [**policy route-policy** *<WORD>*] | [**rip authentication key-chain** *<WORD>* **| mode md5 | text string 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>* **| split-horizon disable | poison-reverse]** |

logging event interface-ip | link-status |
mtu *<256-1500>* |
ntp [broadcast client | destination *<A.B.C.D>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] | [disable] | [multicast [*<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>*] | [key *<1-65534>]* | [minpoll *<4-17>*] | [version *<1-4>*] | |
radio-mode *<0-1>* |
role lan | trusted | wan |
service-policy in *<WORD>* | out *<WORD>* |
shutdown |
snmp trap interface-ip | link-status |
ssid *<LINE>* dot11radio *<1-4>* |
station-role non-root | root |
world mode dot11d country-code *<WORD>* |
zone-member security *<WORD>*}
Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if)#dot11radio)
{**arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp |**	Configure ARP parameters. **Disable ARP filter**—If enabled the router responds to same ARP requests coming from multiple interfaces. **Enable ARP Accept**—Define behavior for gratuitous ARP frames who's IP is not already present in the ARP table: 0—don't create new entries in the ARP table 1—create new entries in the ARP table. **Enable ARP Announce**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface. • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **Enable ARP Ignore**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface. • 0—(default) Use any local address, configured on any interface

	• 1—Try to avoid local addresses that are not in the target's subnet for this interface • **Enable Proxy ARP**—Enable Proxy ARP if you need your router to respond to local networks with its MAC address. Default is Disabled **Enable ARP Ignore**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface. • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **Enable Proxy ARP**—Enable Proxy ARP if you need your router to respond to local networks with its MAC address. Default is Disabled
bridge-group ***<1-9999>*** **|**	Sets transparent bridging interface parameters.
channel ***<1-11>*** **|**	Sets the radio frequency.
description ***<LINE>*** **|**	Description for this interface.
dot11ac [antenna-pattern-fixed] | [center-channel-frequency ***<34-173>*** **] | [channel-width vht40 | vht80] | [ldpc] | [max-mpdu** ***<11454> <7991>*** **] | [max-mpdu-exp** ***<1-7>*** **] | [require-vht] | [short-gi** ***<20 | 40 | 80>*** **] | [stbc rx-stbc rx-stbc-1 | tx-stbc] |**	Configure dot11ac vht mode.
dot11n [40mhz-incapable] | [a-msdu ***<7935>*** **] | [auto-power-save] | [channel-width ht40+ | ht40-] | [dsss-cck-40mhz] | [ldpc] | [require-ht] | [short-gi** ***<20 | 40>*** **] | stbc rx-stbc rx-stbc-1 | tx-stbc] |**	Configure dot11n ht mode.

ip [address *<A.B.C.D>* *<A.B.C.D>* | dhcp] | [ddns service dyndns login *<WORD>* password *<WORD>* host *<WORD>* host-group *<WORD>* | use-web skip *<WORD>* | url *<WORD>*] | [dhcp client class-id *<LINE>* | auto | client-id ethernet *<1–5>*| ascii *<WORD>* | auto | hex *<Hex-String>* | hostname *<WORD>*] | [dhcp-relay] | [dns dhcp] | [firewall in | out | local *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>*] | [ospf authentication message-digest | null] | [authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [cost *<1-65535>]* | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>*| *<WORD>*] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | split-horizon disable | poison-reverse] |	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface. **secondary**—add secondary or ip aliasing address for this interface. **DHCP—**your address is assigned from a DHCP server. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server. **Host/host-group—**Hostname/list of hostnames registered with the DDNS service. **skip—**skip everything before this on the given URL. **Use-web URL**—Enter the URL that you want to obtain an IP address from. This allows the router to be seen on the Internet as a public address. **DHCP client—** **Class ID:** • Auto • Line Specify a Hex string or ASCII text. This same hex string or text would be configured on the server side and associated with an address to give the client. **Client ID:** This can be configured to be the Ethernet interface number, ASCII text, Hex string or set to Auto. option—60—Vendor class identifier<oem-name>:<model>:<serial#> in ASCII Router example: Perle:IRG5541:350-01T00003 **Hostname:** Specify a value for hostname option. **DHCP–relay—**set DHCP-relay for this interface. **DNS dhcp—**use DNS servers received from DHCP server for specified interface **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic. **health-profile—**use this health profile for this interface, configure a nexthop interface. **skip—**skip everything before this on the given URL

Use-web URL—Enter the URL that you want to obtain an IP address from. This allows the router to be seen on the Internet as a public address.

OSPF—

authentication/authentication-key—enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD>.

cost—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0 to 16777214
Default is none

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.

Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5 authentication
  - 0-unencrypted key will follow
  - specifies a hidden key will follow
  - specifies a password (key) will follow (max 16 characters).
    The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.
- non-broadcast—use this type of network on networks having no broadcast/ multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts

retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network.
Range is 1–65535
Default is 5 second

transmit-delay—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission.

	Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled
ipsec restrict |	Restrict IPsec on this interface.
ipv6 [address dhcp] | [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempts *<0-600>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite] | [ra dns server *<X:X:X:X::X>* | [hop-limit *<1-255>* | unspecified | interval *<4-1800> <3-1350>*] | [lifetime *<0><4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low |medium] | [ospf cost *<1-65535>* | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] | [instance-id *<0-255>]* | [mtu-ignore]| [passive] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon | disable poisoned-reverse] |	Configure IPv6 parameters. **address**—use DHCP to obtain address. **enable**—enable IPv6 on this interface. **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **nd**—IPv6 Interface Neighbor Discovery sub-commands • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information. Default is disabled (hosts use stateless auto-configuration of no-address information • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128

no-autoconfig—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination.
Default is off

no-onlink—The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix.
Default is off

ra—Router Advertisement Control

dns server—specify the name server in RA.

hop-limit—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets.
Range is 1–255
Default is 64

interval—Specifies the maximum/minimum time allowed between sending unsolicited multicast router advertisements.

Range of minimum is 3 to *0.75 max (dynamic range)
Default maximum 600 seconds, minimum is 0.33*max
Range is 1–1800 in seconds

lifetime—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list. The router lifetime applies only to the router's usefulness as a default router; it does not apply to information contained in other message fields or options.
Range is 1–9000 seconds
Default is 1800 seconds
0 = not a default route

suppress—enable or disable IPv6 Router advertisements.
reachable time—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation
Default is 0 (unspecified by this router)
Range is 0-360000 milliseconds

retransmission-time—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE).
Range 1–3600000 in milliseconds
Default is 0

router-preference—set the default router preference. A High value means this router will be preferred.

- **High**
- **Medium**
- **Low**

Default is medium

OSPF—
cost—Configure a default metric to be applied to routes being distributed into OSPF.
dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).

As with the hello interval, this value must be the same for all routers attached to a common network.

Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

ifmtu—The range is dynamic (depending on the interface type) and it will match with the MTU value set on the interface.
instance-id—instance ID for this interface.
Values are 0–255

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network–

- broadcast–Specify OSPF broadcast multi-access network
- point-to-point–Specify OSPF point-to-point network

passive—no adjacency will be formed on this interface.

	priority—A router with a high priority will always win the DR/BDR election process. Priority Range is 0-255 Default is 1 **retransmit-interval**—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. Range is 1–65535 Default is 5 second **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled
logging event interface-ip | link-status |	Configure interface logging events and link status.
mtu *<256-1500>* |	Configure Maximum Transmission Unit (MTU) size. Values are 256-1500 bytes Default is 1500 bytes
ntp [broadcast client | destination *<A.B.C.D>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] | [disable] | [multicast [*<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>*] | [key *<1-65534>]* | [minpoll *<4-17>*] | [version *<1-4>*] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network The router can provide the time to NTP/SNTP capable client devices (or other Perle routers and IOLAN's etc).You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the route.

	Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts. **destination broadcast**—Configure broadcast destination address. **multicast** client—listens to NTP multicasts. **destination multicast**—multicast IPv4 or IPv6 address. **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
radio-mode ***<0-1>*** **|**	Select 0 for 2.4Ghz and 1 for 5Ghz. Default is 2.4Ghz
role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side **WAN—**management access is from the WAN side **Trusted—**management access from either the LAN or WAN side
service-policy in ***<WORD>*** **| out** ***<WORD>*** **|**	Assign traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
shutdown |	Shutdown this interface.
snmp trap interface-ip | link-status |	Configure SNMP traps for interface and link status.
ssid ***<LINE>*** **dot11radio** ***<1-4>*** **|**	Configure radio service set parameters.
station-role non-root | root |	Configure role of the radio.
world mode dot11d country-code ***<WORD>*** **|**	Configure an ISO 3166-1 Alpha-2 code. Two characters. Default is ac (United States)
zone-member security ***<WORD>***}	This interface is a member of this zone security.
Command Modes	Perle(config-if)#

Usage Guidelines

Setup options for Dot11Radio.

Examples

This example sets up this interface to use DHCP.

Perle(config-if)# ip address dhcp

Related Commands

show hosts

(config-if-ssid)#

{**bridge-group** *<1-9999>* |

description *<WORD>* |

hotspot |

ip [address *<A.B.C.D> <A.B.C.D>* **secondary] | [ddns service dyndns login** *<WORD>* **password** *<WORD>* **host** *<WORD>* **| host-group** *<WORD>* **| use-web skip** *<WORD>* **| url** *<WORD>]* **| [firewall in | out | local** *<WORD>]* **| [health-profile** *<WORD>* **nexthop** *<A.B.C.D>]* **| [ospf authentication message-digest | null] | [authentication-key 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>]* **| [cost** *<1-65535>]* **| [dead-interval** *<1-65535>]* **| [hello-interval** *<1-65535>]* **| [message-digest-key** *<1-255>* **md5 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>]* **| [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint]| [priority** *<0-255>]* **| [retransmit-interval** *<1-65535>]* **| [transmit-delay** *<1-65535>]* **| [policy route-policy** *<WORD>]* **| [rip authentication key-chain | mode** *<WORD>]* |

ipsec restrict |

ipv6 [address *X:X:X:X::X/<2-128>* **eui-64] | [enable] | [firewall in | out | local** *<WORD>]* **| [nd dad attempts** *<0-600>* **| managed-config-flag-other-config-flag | prefix** *<X:X:X:X::X/<0-128> <0-4292967294>* **| infinite | no-autoconfig | no-onlink] | [ra dns server** *<X:X:X:X::X>* **| [hop-limit** *<1-255>* **| unspecified | interval** *<4-1800> <3-1350>]* **| [lifetime** *<0><4-9000>]* **| [suppress] | [reachable time** *<0-3600000>]* **| [retransmission-time** *<0-3600000>]* **| [router-preference high | low |medium] | [ospf [cost** *<1-65535>]* **| [dead-interval** *<1-65535>]* **| [hello-interval** *<1-65535>]* **| [ifmtu] | [instance-id** *<0-255>]* **| [mtu-ignore] | [network broadcast | point-to-point] | [passive] | [priority** *<0-255>]* **| [retransmit-interval** *<1-65535>]* **| [transmit-delay** *<1-65535>]* **| [policy route-policy** *<WORD>]* **| [rip enable | split-horizon | disable poisoned-reverse]** |

logging event interface-ip | link-status |

mac access-group *<WORD>* **deny | disable | permit** |

mtu *<256-1500>* |

ntp [broadcast client | destination *<A.B.C.D>]* **| [key** *<1-65534>]* **| [minpoll** *<4-17>]* **| [version** *<1-4>]* **| [disable] | [multicast [***<A.B.C.D>* **|** *<X:X:X:X::X>* **| client** *<A.B.C.D>* **|** *<X:X:X:X::X>]* **| [key** *<1-65534>]* **| [minpoll** *<4-17>]* **| [version** *<1-4>]* |

role lan | trusted | wan |

service-policy in *<WORD>* | out *<WORD>* |
shutdown |
snmp trap interface-ip | link-status |
spanning-tree [bpdufilter enable | disable] | [bpduguard [disable | enable] | [cost *<1-200000000>*] | [guard loop | none | root | topology-change] | [link-type auto | point-to-point | shared] | mcheck | [mst cost *<1-200000000>*] | [port-priority *<0-240>*] | [portfast disable | edge | network] |
vrrp *<1-255>* |
zone-member security *<WORD>*}
Use the no form of this command to negate a command or set to defaults.(config-

Syntax Description	(config-if-ssid)#
{**bridge-group *<1-9999>*** |	Configure a bridge group number.
description *<LINE>* |	Configure a SSID description.
hotspot |	Configure hotspot parameters.
ip [address *<A.B.C.D>* *<A.B.C.D>*] | [ddns service dyndns login *<WORD>* password *<WORD>* host *<WORD>* | host-group *<WORD>* | use-web skip | url *<WORD>*] | [firewall in | out | local *<WORD>*] | [health-	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface. **secondary**—add secondary or ip aliasing address for this interface. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server.

profile *<WORD>* nexthop *<A.B.C.D>*] |[ospf [authentication message-digest | null] | authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain | mode *<WORD>*] |	**Host/host-group—**Hostname/list of hostnames registered with the DDNS service. **skip—**skip everything before this on the given URL. **Use-web URL**—Enter the URL that you want to obtain an IP address from. This allows the router to be seen on the Internet as a public address. **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic. **Health-profile—**use this health profile for this interface, configure a nexthop interface. **OSPF—authentication/authentication-key—** enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD>. **cost**—Configure a default metric to be applied to routes being distributed into OSPF.

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.
Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5

authentication

- 0-unencrypted key will follow
- specifies a hidden key will follow
- specifies a password (key) will follow (max 16 characters).
  The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all

- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type) point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.
- non-broadcast—use this type of network on networks having no broadcast/ multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts

priority—a router with a high priority will always win the DR/BDR election process.
Priority Range is 0-255
Default is 1

retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network.
Range is 1–65535
Default is 5 second

transmit-delay—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface.Link state advertisements in the update packet have their age incremented by this amount before transmission.
Range is 1–65535
Default is 1 seconds

policy route-policy—enable this policy route for this interface.

rip—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received.

Default is enabled

ipsec restrict |	Restrict IPsec on this interface.

ipv6 [address *X:X:X:X::X/<2-128>* eui-64] | [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempts *<0-600>* | managed-config-flag-other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4292967294>* | infinite] | [ra dns server *<X:X:X:X::X>* | [hop-limit *<1-255>* | unspecified | interval *<4-1800> <3-1350>*] | [lifetime *<0><4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low |medium] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] | [instance-id *<0-255>*] | [mtu-ignore] | [network broadcast | point-to-point | [passive] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain | mode *<WORD>*] dns server *<X:X:X:X::X>* | [hop-limit *<1-255>* | unspecified | interval *<4-1800> <3-1350>*] | [lifetime *<0><4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low |medium] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] |[instance-id *<0-255>*] | [mtu-ignore] | [passive] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon | disable poisoned-reverse] |	Configure IPv6 parameters. **IPv6 address**—configure the IPv6 address eui-64. **enable**—enable IPv6 on this interface. **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **nd**—IPv6 Interface Neighbor Discovery sub-commands. • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information. Default is disabled (hosts use stateless auto-sconfiguration of no-address information • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128

ra—Router Advertisement Control

dns server—specify the name server in RA.

hop-limit—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets.
Range is 1–255
Default is 64

Interval—Specifies the advertisements. maximum/minimum time allowed between sending unsolicited multicast router advertisements.
Range of minimum is 3 to *0.75 max (dynamic range)
Default maximum 600 seconds, minimum is 0.33*max
Range is 1–1800 in seconds

lifetime—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list.
Range is 1–9000 seconds
Default is 1800 seconds
0 = not a default route
suppress—enable or disable IPv6 Router advertisements.
Default is send router advertisements

reachable time—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation
Default is 0 (unspecified by this router)
Range is 0-360000 milliseconds

retransmission-time—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE).
Range 1–3600000 in milliseconds
Default is 0

router-preference—set the default router preference. A High value means this router will be preferred.

- **High**
- **Medium**
- **Low**

Default is medium

OSPF—
cost—Configure a default metric to be applied to routes being distributed into OSPF.
dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).

As with the hello interval, this value must be the same for all routers attached to a common network.

Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

– **ifmtu**—The range is dynamic (depending on the interface type) and it will match with the MTU value set on the interface.
instance-id—instance ID for this interface. Values are 0–255

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command

to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

Network—

- broadcast–Specify OSPF broadcast multi-access network
- point-to-point–Specify OSPF point-to-point network

passive—no adjacency will be formed on this interface.

priority—A router with a high priority will always win the DR/BDR election process.
Priority Range is 0-255
Default is 1

retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network.
Range is 1–65535
Default is 5 second

transmit-delay—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission.
Range is 1–65535
Default is 1 seconds

policy route-policy—enable this policy route for this interface.

rip—enable split horizon to prevent a routing loop in your network. Basically**,** information about the routing for a particular packet is never sent back in the direction from which it was received.
Default is enabled

logging event interface-ip | link-status |	Configure interface logging events and link status.
mac access-group *<WORD>* deny | disable | permit |	Configure mac access-group parameters for this interface.
mtu *<256-1500>* |	Sets maximum transmission unit (MTU)
ntp [broadcast client | destination *<A.B.C.D>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] | [disable] | [multicast [*<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>*] | [key *<1-65534>]* | [minpoll *<4-17>*] | [version *<1-4>*] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network. The router can provide the time to NTP/ SNTP capable client devices (or other Perle routers and IOAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts. **destination broadcast**—Configure broadcast destination address. **multicast** client—listens to NTP multicasts. **destination multicast**—multicast IPv4 or IPv6 address. **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side **WAN—**management access is from the WAN side **Trusted—**management access from either the LAN or WAN side
service-policy in *<WORD>* | out *<WORD>*|	Assigns traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.

shutdown |	Shutdown this interface.
snmp trap interface-ip | link-status |	Configure SNMP traps for interface and link status
spanning-tree [bpdufilter enable | disable] | [bpduguard [disable | enable] | [cost *<1-200000000>*] | [guard loop | none | root | topology-change] | [link-type auto | point-to-point | shared] | mcheck | [mst cost *<1-200000000>*] | [port-priority *<0-240>*] | [portfast disable | edge | network] |	Configure interface parameters for spanning tree. **bpdufilter**—don't send or receive BPDUs on this interface. Default is Disabled **bpduguard**—don't accept BPDUs on this interface. Default is Disabled **cost**—change port path cost. Value is 1 to 200000000 Default is auto (defined by STP protocol) • loop • none • root • topology-change **link-type** • auto—this interface is point-to-point if configured for full duplex operation • point-to-point • shared **mcheck—**force the mode from STP to RSTP/MSTP mode. **mst—**change path cost and port priority for multiple spanning tree mode. **port-priority—**change the port priority for an instance. (increments of 16) Default is 128 **portfast network—**this feature causes the router to enter the STP forwarding-state immediately or upon a linkup event, thus passing the listening and learning states. Some applications need to connect to the network immediately, else they will timeout. **portfast edge—**is used to configure a port on which an end device is connected, such as a PC. All ports directly connected to end devices cannot create bridging loops in the network.

	Therefore, the edge port directly transitions to the forwarding state, and skips the listening and learning stages. **portfast disable**—when enabled an interface will jump to the forwarding state of spanning-tree.
vrrp *<1-255>* |	This interface is part of VRRP group number.
zone-member security *<WORD>*}	This interface is a member of this zone security.
Command Modes	Perle(config-if-ssid)#

Usage Guidelines

Use this command to configure SSID sub menu commands.

Examples

This example restricts IPsec to this interface. All interfaces are used if no restrictions are in place.

Perle(config-if-ssid)# ipsec restrict

Related Commands

show ip interface

hotspot)#

{**address** *<A.B.C.D> <A.B.C.D>* |
authentication local | none | radius | uam |
bandwidth-down *<1-4294967295>* |
bandwidth up *<1-4294967295>* |
dns1 *<A.B.C.D>* |
dns2 *<A.B.C.D>* |
enable |
file footer flash: | icon flash: | login flash: | login-footer flash: | title flash: | tos flash: |
heartbeat enable | interval *<15-60>* **| url** *<WORD>* |
idle-time *<1-240>* |
location name *<WORD>* |
login-url *<WORD>*
mac-allow *<H.H.H>*
nasid *<WORD>* |
organizational-name *<WORD>* |
profile hotspotsystem.com |
radacct *<1-65535>* |

radauth *<1-65535>* |
radius *<A.B.C.D>* |
radius2 *<A.B.C.D>* |
radsecret 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |
session-time *<1-240>* |
uamport *<1025-65535>* |
uamsecret 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |
uamuiport *<1025-65535>* |
nmp trap interface-ip | **link-status** |
user *<WORD>* **0** *<WORD>* | **7** *<WORD>* | *<WORD>* | *<WORD>* |
walled-garden domain *<WORD>* | **url** *hostname/<A.B.C.D>*}
Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-hotspot)#
{**address** *<A.B.C.D>* *<A.B.C.D>* |	Enter the hotspot name on the subscriber network and the netmask.
authentication local | **none** | **radius** | **uam** |	Authentication method: • local • none • radius • uam
bandwidth-down *<1-4294967295>* |	Configure maximum bandwidth down stream in bps. (bits per second) Values are 1–4294967295 bps
bandwidth up *<1-4294967295>* |	Configure maximum bandwidth up stream in bps. Values are 1–4294967295
dns1 *<A.B.C.D>* |	DNS server address 1.
dns2 *<A.B.C.D>* |	DNS server address 2.
enable |	Enable hotspot.

file footer flash: | icon flash: | login flash: | login-footer flash: | title flash: | tos flash: |	**Specify**—the file to use for the footer that displays below every page. **Specify**—the file that contains the icon image. **Specify**—the file that contains the login message between the header and the form on the login page. **Specify**—the file that contains the login footer between the form the footer on the login. **Specify**—the file that contains the title for the page. **Specify**—the file that contains the terms of service agreement.
heartbeat enable | interval *<15-30>* | url *<WORD>* |	When enable, the heartbeat sends: • mac—the MAC address of your router • nasid—the NAS/Gateway ID of the router which should be entered in the UAM • os_date—in string format the type of router and firmware version running • uptime—the uptime and system load average of your router Interval value is 15-30 minutes. Default: URL.https://tech.hotspotsystem.com/up.php
idle-time *<1-240>* |	If the user is idle for this amount of time make them re-authenticate. Value 1–240 in seconds
location name *<WORD>* |	Configure the location name.
login-url *<WORD>* |	Login URL to use on UAM server.
mac-allow *<H.H.H>*	Allows these MAC addresses without authentication. H.H.H (xxxx.xxxx.xxxx)
nasid *<WORD>* |	Configure the network access server identifier.
organizational-name *<WORD>* |	Configure organizational name.
profile hotspotsystem.com |	Loading this profile overwrites your current configuration. You must configure a valid nasid for this service. Valid nasid IDs are obtained from your hotspot provider.

radacct *<1-65535>* |	Configure the UDP port number for RADIUS accounting messages. Values are 1–65535 Default port is 1813
radauth *<1-65535>* |	Configure the UDP port number for RADIUS authenticating requests. Values are 1–65535 Default port is 1812
radius *<A.B.C.D>* |	Configure the address of the RADIUS server.
radius2 *<A.B.C.D>* |	Configure the address of the second RADIUS server.
radsecret 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |	Configure shared secret between the RADIUS server and your router. 0—unencrypted password follows 7—encrypted password follows WORD—shared secret
session-time *<1-240>* |	Configure the amount of time before users are forced to authenticate again. Value are 1–240 in seconds
uamport *<1025-65535>* |	Configure the TCP port number to authenticate clients
uamsecret 0 *<WORD>* | **7** *<WORD>* | *<WORD>* |	Configure shared secret between uamserver and your router. 0—unencrypted password follows 7—encrypted password follows WORD—shared secret
uamuiport *<1025-65535>* |	Configure the TCP port to bind to for downloading user content interface screens.
user *<WORD>* **0** *<WORD>* | **7** *<WORD>* | *<WORD>* | *<WORD>* |	Adds or modifies the user in the hotspot database.
walled-garden domain *<WORD>* | **url** *hostname/ <A.B.C.D>*}	Configure domains and URLs to allow access without authenticating first.
Command Modes	PerleRouter(config-hotspot)#

Usage Guidelines

Use this command to configure the Hotspot feature. Also knows as Captive Portal, it is a method of securing access to the Internet from within your wireless network. Users must enter authentication credentials before their wireless client devices can access the Internet.

Examples

This example sets session time for the users to 10 minutes. After no activity for 10 minutes, the user needs to re-authenticate with your router to gain access to the internet.

Perle(config-hotspot)#session-time 600

Related Commands

show hosts

(config-if-ethernet)#

{**alarm profile** *<WORD>* |

arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp | timeout *<1-2147483>* |

authentication [host-mode | multi-auth | multi-host | single-host] | [periodic] | [port-control auto | forced-authorized | force-unauthorized] | [timer reauthenticate *<1-65535>* **| restart** *<1-65535>***]** |

bridge-group *<1-9999>* |

description *<LINE>* |

dot1x [credential *<WORD>***] | [max-auth-req** *<1-10>***] | [max-req** *<1-10>***] | [pae authenticator | supplicant] | [supplicant eap profile** *<WORD>***] | [timeout quiet-period** *<1-65535>* **| supp-period** *<1-65535>* **| tx-period** *<1-65535>***]** |

duplex auto | half | full |

ip address [<*A.B.C.D*> <*A.B.C.D*> **secondary | dhcp] | [ddns service dyndns | use-web skip** *<WORD>* **| url** *<WORD>***] | [dhcp client class-id** *<LINE>* **| auto | client-id ethernet** *<1-5>***| acsii** *<WORD>* **| auto | hex** *<HEX-STRING* **| hostname** *<WORD>***] | [dhcp-relay] | [dns dhcp] | [firewall in | local | out** *<WORD>***] | [health-profile** *<WORD>* **nexthop** *<A.B.C.D>***] | [ospf authentication message-digest | null | authentication-key 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>* **| [cost** *<1-65535>]* **| [ead-interval** *<1-65535>***] | [hello-interval** *<1-65535>***] | [message-digest-key** *<1-255>* **md5 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>***] | [mtu-ignore | network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority** *<0-255>***] | [retransmit-interval** *<1-65535>***] | [transmit-delay** *<1-65535>***] | [policy route-policy** *<WORD>***] | [rip authentication key-chain** *<WORD>* **| mode md5 | text string 0** *<WORD>* **| 7** *<WORD>* **|** *<WORD>* **| split-horizon disable | poison-reverse]** |

ipsec restrict |

ipv6 [address *<X:X:X:X::X/<0-128>* **| autoconfig | dhcp] [enable] | [firewall in | out | local** *<WORD>***] | [nd dad attempt** *<0-500>* **| managed config-flag | other-config-flag | prefix** *<X:X:X:X::X/<0-128> <0-4294967294>* **| infinite | no-autoconfig | no-onlink] | [ra dns server** *<X:X:X:X::X>***] | [hop-limit** *<1-255>* **| unspecified] |**

[interval *<4-1800>* *<3-1350* | **[lifetime *<0>*** | ***<4-9000>*]** | **[suppress]** | **[reachable time *<0-3600000>*]** | **[retransmission-time *<0-3600000>*]** | **[router-preference high** | **low** |**medium]** | **[ospf cost *<1-65535>*** | **dead-interval *<1-65535>*** | **hello-interval *<1-65535>*** | **ifmtu** | **instance-id *<0-255>*** | **mtu-ignore** | **[network broadcast** | **point-to-point]** | **passive** | **priority *<0-255>*** | **retransmit-interval *<1-65535>*** | **transmit-delay *<1-65535>*** | **[policy route-policy *<WORD>*]** | **[rip enable** | **split-horizon** | **disable poisoned-reverse]** |

lldp max-neighbors *<1-50>* | **receive** | **tvl-select mac-phy-cfg** | **management-address** | **max-frame-size** | **port-description** | **system -capabilities** | **system-description** | **system-name** | **transmit** |

logging event interface-ip | **link-status** |

mab eap |

mac access-group <word> deny | **disable** | **permit** |

mtu *<64-9000>* |

ntp [broadcast client | **destination *<A.B.C.D>*]** | **[key *<1-65534>*]** | **[minpoll *<4-17>*]** | **[version *<1-4>*]** | **[disable]** | **[multicast [*<A.B.C.D>*** | ***<X:X:X:X::X>*** | **client *<A.B.C.D>*** | ***<X:X:X:X::X>*]** | **[key *<1-65534>]*** | **[minpoll *<4-17>*]** | **[version *<1-4>*]** |

power efficient-ethernet auto |

role lan | **trusted** | **wan** |

service-policy in | **out** |

shutdown |

snmp trap interface-ip | **link-status** |

spanning-tree [bpdufilter enable | **disable]** | **[bpduguard [disable** | **enable]** | **[cost *<1-200000000>*]** | **[guard loop** | **none** | **root** | **topology-change]** | **[link-type auto** | **point-to-point** | **shared]** | **mcheck** | **[mst cost *<1-200000000>*]** | **[port-priority *<0-240>*]** | **[portfast disable** | **edge** | **network]** |

speed 10 |**100** | **1000** | **auto10** |**100** | **1000** | **auto** |

vrrp *<1-255>* |

zone-member security *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if-ethernet)#
{**alarm profile *<WORD>*** |	Use this alarm profile for this interface.

arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp | timeout *<1-2147483>* |	Configure ARP parameters. **Disable ARP filter**—If enabled the router responds to same ARP requests coming from multiple interfaces. **Enable ARP Accept**—Define behavior for gratuitous ARP frames who's IP is not already present in the ARP table: 0–don't create new entries in the ARP table 1–create new entries in the ARP table **Enable ARP Announce**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0–(default) Use any local address, configured on any interface • 1–Try to avoid local addresses that are not in the target's subnet for this interface
	Enable ARP Ignore—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0–(default) Use any local address, configured on any interface • 1–Try to avoid local addresses that are not in the target's subnet for this interface **ARP Timeout**—If an ARP entry is not used for a specific amount of time the entry is removed from the caching table. **Enable Proxy ARP**—Enable Proxy ARP if you need your router to respond to local networks with its MAC address. Default is Disabled

authentication [host-mode | multi-auth | multi-host | single-host] | [periodic] | [port-control auto | forced-authorized | force-unauthorized] | [timer reauthenticate *<1-65535>* | restart *<1-65535>*] |	Selects authentication mode to use on this interface when using Dot1x devices. **Host Mode** **Single host** • Only one device can authenticate and connect on the port This is the default mode of operation. **Multiple host** • Unlimited number of devices can connect on the port once a single device has been authenticated on the port. This single device must be a data (as opposed to voice) device **Multiple authentication** • Each device connecting to your router is required to authenticate. • No limit as to the number of devices which can authenticate on the port **periodic reauthentication—**When enabled, the supplicant will be asked to re-authenticated based on the Advanced setting -> re-authentication timeout value. **Port control** • Auto—the port is locked expecting authentication from either a connected 802.1X client or if MAB is enabled, it will authenticate the MAC to the RADIUS server.

	• Force authorized—the port is unsecure/unlocked meaning normal operation where no 802.1X client or MAB authentication via RADIUS is required. This is the default setting. • Force unauthorized – the port is secured/locked and will NEVER allow any traffic to ingress into our Ethernet port/s. **Timer** **Maximum re-authentication retries**—Set the number of times the authenticator will attempt to re-authenticate a supplicant. Range is 1-10 seconds Default is 2 seconds **Restart timeout—** Interval in seconds after which an attempt should be made to authenticate an unauthorized port. If the parameter "server" is specified, the time is derived from the "Session-Timeout value" (RADIUS Attribute 27). Range is 1-65535 seconds Default is 60 seconds
bridge-group ***<1-9999>*** **|**	Adds this interface to the specified bridge-group.
description ***<LINE>*** **|**	Description for this interface.
dot1x [credential ***<WORD>*****] | [max-auth-req** ***<1-10>*****] | [max-req** ***<1-10>*****] | [pae authenticator | supplicant] | [supplicant eap profile** ***<WORD>*****] | [timeout quiet-**	Sets the Port Access Entity (PAE) type. **Supplicant—**The interface acts only as a supplicant and does not respond to messages that are meant for an authenticator.
period ***<1-65535>*** **| supp-period** ***<1-65535>*** **| tx-period** ***<1-65535>*****] |**	**Authenticator—**The interface acts only as an authenticator and does not respond to any messages meant for a supplicant. **Both—**The interface behaves both as a supplicant and as an authenticator and thus does respond to all dot1x messages.
duplex auto | half | full |	Select duplex for this interface. In most cases this parameter should be left at auto.

ip address [*<A.B.C.D>* *<A.B.C.D>* secondary | dhcp] | [ddns service dyndns | use-web skip *<WORD>* | url *<WORD>*] | [dhcp client class-id *<LINE>* | auto | client-id ethernet *<1-5>* | acsii *<WORD>* | auto | hex *<HEX-STRING* | hostname *<WORD>*] | [dhcp-relay] | [dns dhcp] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>*] | [ospf authentication message-digest | null | authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | [cost *<1-65535>]* | [ead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | split-horizon disable | poison-reverse] |	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface. **secondary**—add secondary or ip aliasing address for this interface. Max secondary address-1-128 You must define a primary address before secondary IP addresses Primary and secondary address can be on the same of different subnets of the primary address **DHCP—**your address is assigned from a DHCP server. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns serve.r **Host/host-group—**Hostname/list of hostnames registered with the DDNS service. **skip—**skip everything before this ont he given URL. **Use-web URL**—Enter the URL that you want to obtain an IP address from. This allows the router to be seen on the Internet as a public address. **DHCP client —** **Class ID:** • Auto • Line Specify a Hex string or ASCII text. This same hex string or text would be configured on the server side and associated with an address to give the client. **Client ID:** This can be configured to be the Ethernet interface number, ASCII text, Hex string or set to Auto. option—60—Vendor class identifier<oem-name>:<model>:<serial#> in ASCII Router example: Perle:IRG5541:350-01T00003

Firewall—set firewall for inbound, traffic destined for this router or outbound traffic.

Hostname:
Specify a value for hostname option.

DHCP–relay—set DHCP-relay for this interface.

DNS dhcp—use DNS servers received from DHCP server for specified interface.

health-profile—use this health profile for this interface, configure a nexthop interface.

OSPF—
authentication/authentication-key— enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD>.

cost—Configure a default metric to be applied to routes being distributed into OSPF.
Range is 0 to 16777214
Default is none

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.

Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5

authentication.

- 0-unencrypted key will follow
- specifies a hidden key will follow
- specifies a password (key) will follow (max 16 characters). The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—Configure the network type

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.
- non-broadcast—use this type of network on networks having no broadcast/multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts

priority—a router with a high priority will always win the DR/BDR election process
Priority Range is 0-255
Default is 1

	retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. Range is 1–65535 Default is 5 **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission Range is 1–65535 **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled Default is 1 seconds
ipsec restrict |	Restrict IPsec on this interface.

ipv6 [address *<X:X:X:X::X/<0-128>* | autoconfig | dhcp] [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempt *<0-500>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite | no-autoconfig | no-onlink] | [ra dns server *<X:X:X:X::X>*] | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800> <3-1350* | [lifetime *<0>* | *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low |medium] | [ospf cost *<1-65535>* | dead-interval *<1-65535>* | hello-interval *<1-65535>* | ifmtu | instance-id *<0-255>* | mtu-ignore | [network broadcast | point-to-point] | passive | priority *<0-255>* | retransmit-interval *<1-65535>* | transmit-delay *<1-65535>* | [policy route-policy *<WORD>*] | [rip enable | split-horizon | disable poisoned-reverse] |	Configure IPv6 parameters. **IPv6 address**—configure the IPv6 address eui-64, autoconfig, or dhcp. **enable**—enable IPv6 on this interface. **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **nd**—IPv6 Interface Neighbor Discovery sub-commands. dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information.

Default is disabled (hosts use stateless auto-configuration of no-address information

prefix—specifies the IPv6 prefix advertised on the interface

Configure the prefix length.
Range is 0–128

no-autoconfig—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination.
Default is off

no-onlink—The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix.
Default is off

ra—Router Advertisement Control

dns server—specify the name server in RA.

hop-limit—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets.
Range is 1–255
Default is 64

interval—Specifies the maximum/minimum time allowed between sending unsolicited multicast router advertisements.
Range of minimum is 3 to *0.75 max (dynamic range)
Default maximum 600 seconds, minimum is 0.33*max
Range is 1–1800 in seconds

lifetime—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list.
Range is 1–9000 seconds
Default is 1800 seconds
0 = not a default route

suppress—enable or disable IPv6 Router advertisements.
Default is send router advertisements

	reachable time—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation Default is 0 (unspecified by this router) Range is 0-360000 milliseconds
	router-preference—set the default router preference. A High value means this router will be preferred. • **High** • **Medium** • **Low** Default is medium **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received Default is enabled
lldp max-neighbors *<1-50>* | receive | tvl-select mac-phy-cfg | management-address | max-frame-size | port-description | system -capabilities | system-description | system-name | transmit |	Configure LLDP parameters.
logging event interface-ip | link-status |	Configure logging events for interface and link status.
mab eap |	Sets MAC authentication bypass interface commands.
mac access-group <word> deny | disable | permit |	Sets interface MAC access-list parameters.

mtu ***<64-9000>*** **|**	Sets maximum transmission unit (MTU). Values are 64 t 9000 bytes Default is 1500 bytes
ntp [broadcast client | destination ***<A.B.C.D>*****] | [key** ***<1-65534>*****] | [minpoll** ***<4-17>*****] | [version** ***<1-4>*****] | [disable] | [multicast [****<A.B.C.D>*** **|** ***<X:X:X:X::X>*** **| client** ***<A.B.C.D>*** **|** ***<X:X:X:X::X>*****] | [key** ***<1-65534>]*** **| [minpoll** ***<4-17>*****] | [version** ***<1-4>*****] |**	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network. The router can provide the time to NTP/ SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts. **destination broadcast**—Configure broadcast destination address. **multicast** client—listens to NTP multicasts. **destination multicast**—multicast IPv4 or IPv6 address. **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
power efficient-ethernet auto |	Configure interface power settings.
role lan |trusted | wan |	Select the role for this interface. **LAN—** management access is from the LAN side **WAN—**management access is from the WAN side **Trusted—**management access from either the LAN or WAN side
service-policy in | out |	Assigns traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
shutdown |	Shutdown this interface.

snmp trap interface-ip | link-status |	Configure SNMP traps for interface and link status.
spanning-tree [bpdufilter enable | disable] | [bpduguard [disable | enable] | [cost *<1-200000000>*] | [guard loop | none | root | topology-change] | [link-type auto | point-to-point | shared] |mcheck | [mst cost *<1-200000000>* | [port-priority *<0-240>*] | [portfast disable | edge | network] |	Configure interface parameters for spanning tree. **bpdufilter**—don't send or receive BPDUs on this interface. Default is Disabled **bpduguard**—don't accept BPDUs on this interface. Default is Disabled **cost**—change port path cost. Value is 1 to 200000000 Default is auto (defined by STP protocol) • loop • none • root • topology-change **link-type** • auto—this interface is point-to-point if configured for full duplex operation • point-to-point • shared **mcheck—**force the mode from STP to RSTP/MSTP mode. **mst—**change path cost and port priority for multiple spanning tree mode. **port-priority—**change the port priority for an instance. (increments of 16) Default is 128 **portfast network—**this feature causes the router to enter the STP forwarding-state immediately or upon a linkup event, thus passing the listening and learning states. Some applications need to connect to the network immediately, else they will timeout. **portfast edge—**is used to configure a port on which an end device is connected, such as a PC. All ports directly connected to end devices cannot create bridging loops in the network.

	Therefore, the edge port directly transitions to the forwarding state, and skips the listening and learning stages. **portfast disable**—when enabled an interface will jump to the forwarding state of spanning-tree.
speed 10 |100 | 1000 |auto |	Configure the Ethernet speed.. • 10 • 100 • 100010 • 100 • 1000 • auto
vrrp *<1-255>* |	This interface is part of VRRP group number.
zone-member security *<WORD>*}	This interface is a member of zone security.
Command Modes	Perle(config-if)#

Usage Guidelines

Set up Ethernet parameters for this interface.

Examples

This example sets the speed for this interface to 1000.

Perle(config-if)#speed 1000

Related Commands

(config-if)#bvi
(config-if)#openvpn-tunnel
(config-if)#tunnel
(config-if-ethernet)#
(config-if)#dot11radio
(config-if)#cellular

(config-subif)#

{**arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp | timeout *<1-2147483>* |**
bridge-group *<1-9999>* |
description *<LINE>* |
ip [address *<A.B.C.D>* < *A.B.C.D>* secondary | dhcp] | [dhcp client class-id *<LINE>* | auto | client-id ethernet *<1-5>* | acsii *<WORD>* | auto | hex *<HEX-STRING* | hostname *<WORD>*] | [dhcp-relay] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>*] | [ospf authentication message-

digest | null | authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5| text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>*| split-horizon disable | poison-reverse] |

ipsec restrict |

ipv6 [address *<X:X:X:X::X/<0-128>* | autoconfig | dhcp] [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempt *<0-500>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite | no-autoconfig | no-onlink | [ra dns server *<X:X:X:X::X>*] | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800> <3-1350>*] | [lifetime *<0>* | *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low | medium] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] | [instance-id *<0-255>*] | [mtu-ignore] | [network braodcast | point-to-point] | [mtu-ignore] | [passive] | [priority *<0-255>*] | [retransmit-interval *<1-65535>]* | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon disable | poisoned-reverse] |

lldp max-neighbors *<1-50>* | receive | tvl-select mac-phy-cfg | management-address | max-frame-size | port-description | system -capabilities | system-description | system-name | transmit |

logging event interface-ip | link-status |

mac access-group <word> deny | disable | permit |

mtu *<64-9000>* |

ntp [broadcast client | destination *<A.B.C.D>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] | [disable] | [multicast [*<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>*] | [key *<1-65534>]* | [minpoll *<4-17>*] | [version *<1-4>*] |

role lan | trusted | wan |

service-policy in | out |

shutdown |

snmp trap interface-ip | link-status |

spanning-tree [bpdufilter enable | disable] | [bpduguard [disable | enable] | [cost *<1-200000000>*] | [guard loop | none | root | topology-change] | link-type aut | point-to-point | shared] | mcheck | [mst cost *<1-200000000>* | port-priority *<0-240>* | [portfast disable | edge | network] |

vrrp *<1-255>* |

zone-member security *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description **(config-subif)#**

{**arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp | timeout** ***<1-2147483>*** **|**	Configure ARP parameters. **Disable ARP filter**—If enabled the router responds to same ARP requests coming from multiple interfaces.
	Enable ARP Accept—Define behavior for gratuitous ARP frames who's IP is not already present in the ARP table: 0—don't create new entries in the ARP table 1—create new entries in the ARP table **Enable ARP Announce**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **Enable ARP Ignore**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **ARP Timeout**—If an ARP entry is not used for a specific amount of time the entry is removed from the caching table. **Enable Proxy ARP**—Enable Proxy ARP if you need your router to respond to local networks with its MAC address. Default is Disabled
bridge-group ***<1-9999>*** **|**	Add this interface to the specified bridge group.
description |	Configure sub-interface description.

ip [address *<A.B.C.D>* < *A.B.C.D>* | dhcp] | [dhcp client class-id *<LINE>* | auto | client-id ethernet *<1-5>* | acsii *<WORD>* | auto | hex *<HEX-STRING* | hostname *<WORD>*] | [dhcp-relay] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>*] | [ospf authentication message-digest | null | authentication-key 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 0 *<WORD>* | 7 *<WORD>* | *<WORD>*] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5| text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>*| split-horizon disable | poison-reverse] |	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface **secondary**—add secondary or ip aliasing address for this interface **DHCP—**your address is assigned from a DHCP server **DHCP client —** **Class ID:** • Auto • Line Specify a Hex string or ASCII text. This same hex string or text would be configured on the server side and associated with an address to give the client. **Client ID:** This can be configured to be the Ethernet interface number, ASCII text, Hex string or set to Auto. option—60—Vendor class identifier<oem-name>:<model>:<serial#> in ASCII Router example: Perle:IRG5541:350-01T00003 **Hostname:** Specify a value for hostname option **DHCP–relay—**set DHCP-relay for this interface. **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic **health-profile—**use this health profile for this interface, configure a nexthop interface **OSPF—** **authentication/authentication-key—**enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD> **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0 to 16777214 Default is none **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead). As with the hello interval, this value must be the same for all routers attached to a common network Default is 4 times the hello interval Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key

md5—Identifies the key (password) used between this router and neighboring routers for MD5 authentication.

  - 0-unencrypted key will follow
  - specifies a hidden key will follow
  - specifies a password (key) will follow (max 16 characters).
    The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints send broadcasts/ multicasts

	• non-broadcast—use this type of network on networks having no broadcast/ multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts **priority**—a router with a high priority will always win the DR/BDR election process Priority Range is 0-255 Default is 1 **retransmission-time**—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE). Range 1–3600000 in milliseconds Default is 0 **router-preference**—set the default router preference. A High value means this router will be preferred. • **High** • **Medium** • **Low** Default is medium **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received.Default is enabled
ipsec restrict |	Restrict IPv6 on this interface.

ipv6 [address *<X:X:X:X::X/<0-128>* | autoconfig | dhcp] [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempt *<0-500>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite | [ra dns server *<X:X:X:X::X>*] | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800> <3-1350>*] | [lifetime *<0>* | *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low | medium] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] |	Configure IPv6 parameters. **IPvV6 address or DHCP**—configure the IPv6 address and prefix length or obtain an IPv6 address using DHCP **enable**—enable IPv6 on this interface **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic **nd**—IPv6 Interface Neighbor Discovery sub-commands • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured. before this address can be configured. Range 1–600 Default is 1

[instance-id *<0-255>*] | [mtu-ignore] | [network broadcast | point-to-point] | [passive] | [priority *<0-255>]* | [retransmit-interval *<1-65535>]* | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip enable | split-horizon disable | poisoned-reverse] |	• managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information. Default is disabled (hosts use stateless auto-configuration of no-address information • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128 **no-autoconfig**—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination. Default is off **no-onlink—**The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix. Default is off **ra**—Router Advertisement Control **dns server**—specify the name server in RA. **hop-limit**—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets. Range is 1–255 Default is 64 **interval**—Specifies the maximum/minimum time allowed between sending unsolicited multicast router advertisements. Range of minimum is 3 to *0.75 max (dynamic range) Default maximum 600 seconds, minimum is 0.33*max Range is 1–1800 in seconds

lifetime—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list.
Range is 1–9000 seconds
Default is 1800 seconds
0 = not a default route

suppress—enable or disable IPv6 Router advertisements.
Default is send router advertisements
reachable time—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation
Default is 0 (unspecified by this router)
Range is 0-360000 milliseconds

retransmission-time—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE).
Range 1–3600000 in milliseconds
Default is 0

router-preference—set the default router preference. A High value means this router will be preferred.

- **High**
- **Medium**
- **Low**

Default is medium

OSPF—
cost—Configure a default metric to be applied to routes being distributed into OSPF.
Range is 0–16777214

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.
Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
Default is none
The default is 10 second

ifmtu—The range is dynamic (depending on the interface type) and it will match with the MTU value set on the interface.
instance-id—instance ID for this interface
Values are 0–255

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

Network—

- broadcast–Specify OSPF broadcast multi-access network
- point-to-point–Specify OSPF point-to point network

passive—no adjacency will be formed on this interface

priority—a router with a high priority will always win the DR/BDR election process
Priority Range is 0-255
Default is 1

retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface,

The expected round-trip delay between any two routers in the attached network.
Range is 1–65535
Default is 5 second

transmit-delay—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission
Range is 1–65535
Default is 1 seconds

policy route-policy—enable this policy route for this interface.

	rip—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received Default is enabled
logging event interface-ip | link-status |	Configure logging events for interface and link status.
mtu *<64-9000>* |	Configure Maximum Transmission Unit (MTU). Values are 64-9000 bytes Default is 1500 bytes
ntp [broadcast client | destination *<A.B.C.D>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] | [disable] | [multicast [*<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>*] | [key *<1-65534>]* | [minpoll *<4-17>*] | [version *<1-4>*] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network The router can provide the time to NTP/SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts **destination broadcast**—Configure broadcast destination address **multicast** client—listens to NTP multicasts **destination multicast**—multicast IPv4 or IPv6 address **key**—Configure broadcast authentication key **versions—**1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
role lan | trusted | wan |	Select the role for this interface. **LAN**—management access is from the LAN side **WAN—**management access is from the WAN side **Trusted—**management access from either the LAN or WAN side

service-policy in | out |	Assign traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
shutdown |	Shut down this interface.
snmp trap interface-ip | link-status |	Set SNMP traps for interface and link status.

spanning-tree [bpdufilter enable | disable] | [bpduguard [disable | enable] | [cost *<1-200000000>*] | [guard loop | none | root | topology-change] | link-type aut | point-to-point | shared] | mcheck | [mst cost *<1-200000000>* | port-priority *<0-240>* | [portfast disable | edge | network] |	Set interface parameters for spanning tree. **bpdufilter**—don't send or receive BPDUs on this interface. Default is Disabled **bpduguard**—don't accept BPDUs on this interface. Default is Disabled **cost**—change port path cost. Value is 1 to 200000000. Default is auto (defined by STP protocol) **guard** • loop • none • root • topology-change **link-type** • auto—this interface is point-to-point if configured for full duplex operation • point-to-point • shared **mcheck—**force the mode from STP to RSTP/MSTP mode **mst—**change path cost and port priority for multiple spanning tree mode **port-priority—**change the port priority for an instance. (increments of 16) Default is 128 **portfast network—**this feature causes the router to enter the STP forwarding-state immediately or upon a linkup event, thus passing the listening and learning states. Some applications need to connect to the network immediately, else they will timeout. **portfast edge—**is used to configure a port on which an end device is connected, such as a PC. All ports directly connected to end devices cannot create bridging loops in the network. Therefore, the edge port directly transitions to the forwarding state, and skips the listening and learning stages.
	Portfast disable—when enabled an interface will jump to the forwarding state of spanning-tree.

vrrp ***<1-255>*** |	This interface is part of VRRP group number.
zone-member security ***<WORD>***}	Set interface to be a member of this security zone.
Command Modes	Perle(config)#interface ethernet 1.100 Perle(config-subif)#

Usage Guidelines

Set a sub interface within an Ethernet interface.

Examples

This example sets a sub interface of 100 on Ethernet 1interface.

Perle(config)# interface ethernet 1.100

Related Commands

(config-if-ethernet)#

(config-if-range)#

{**alarm profile** ***<WORD>*** |

arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp | timeout ***<1-2147483>*** |

authentication host-mode | multi-auth | multi-host | single-host | periodic | port-control auto | forced-authorized | force-unauthorized | timer reauthenticate ***<1-65535>*** **| restart** ***<1-65535>*** |

bridge-group ***<1-9999>*** |

description ***<LINE>*** |

dot1x [credential ***<WORD>*****] | [max-auth-req** ***<1-10>*****] | [max-req** ***<1-10>*****] | [pae authenticator | supplicant] | [supplicant eap profile** ***<WORD>*****] | [timeout quiet-period** ***<1-65535>*** **| supp-period** ***<1-65535>*** **| tx-period** ***<1-65535>*****]** |

duplex auto | half | full |

ip [address ***<A.B.C.D>*** **| dhcp secondary] | [ddns service dyndns | use-web skip** ***<WORD>*** **| url** ***<WORD>*****] | [dhcp client class-id** ***<LINE>*** **| auto | client-id ethernet** ***<1-5>*** **| acsii** ***<WORD>*** **| auto | hex** ***<HEX-STRING*** **| hostname** ***<WORD>*****] | [dhcp-relay] | [firewall in | local | out** ***<WORD>*****] | [health-profile** ***<WORD>*** **nexthop** ***<A.B.C.D>*** **| dhcp] | [ospf authentication [message-digest | null | authentication-key** ***<LINE>*****] | [cost** ***<1-65535>*** **| dead-interval** ***<1-65535>*** **| hello-interval** ***<1-65535>*** **| message-digest-key** ***<1-255>*** **md5** ***<LINE>*****] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority** ***<0-255>*****] | [retransmit-interval** ***<1-65535>*****] | [transmit-delay** ***<1-65535>*****] | [policy route-policy** ***<WORD>*****] | [rip authentication key-chain** ***<WORD>*** **| mode md5 | text string** ***<0*** **|** ***7*** **|** ***WORD>*** **| split-horizon disable | poisoned-reverse]** |

ipsec restrict |

ipv6 address *<X:X:X:X::X/<0-128>* **| autoconfig | dhcp] [enable] | [firewall in | out | local** *<WORD>***] | [nd dad attempt** *<0-500>* **| managed config-flag | other-config-flag | prefix** *<X:X:X:X::X/<0-128> <0-4294967294>* **| infinite | no-autoconfig | no-onlink] | [ra dns server** *<X:X:X:X::X>* **| [hop-limit** *<1-255>* **| unspecified] | [interval** *<4-1800> <3-1350>***] | [lifetime** *<0>* **|** *<4-9000>***] | [suppress] | [reachable time** *<0-3600000>***] | retransmission-time** *<0-3600000>* **| router-preference high | low |medium] | [ospf [cost** *<1-65535>***] | [dead-interval** *<1-65535>***] | [hello-interval** *<1-65535>***] | [ifmtu] | [instance-id** *<0-255>***] | [mtu-ignore] | [network broadcast | point-to-point] | [mtu-ignore] | [network broadcast | point-to-point] | [passive | priority** *<0-255>***] | [retransmit-interval** *<1-65535>***] | [transmit-delay** *<1-65535>***] | [policy route-policy** *<WORD>***] | [rip | split-horizon disable | poisoned-reverse]** |

lldp max-neighbors *<1-50>* **| receive | tvl-select mac-phy-cfg | management-address | max-frame-size | port-description | system -capabilities | system-description | system-name | transmit** |

logging event interface-ip | link-status |

mab eap |

mtu *<64-9000>* |

ntp [broadcast client | destination *<A.B.C.D>***] | [key** *<1-65534>***] | [minpoll** *<4-17>***] | [version** *<1-4>***] | [disable] | [multicast [**<*A.B.C.D>* **|** *<X:X:X:X::X>* **| client** *<A.B.C.D>* **|** *<X:X:X:X::X>***] | [key** *<1-65534>]* **| [minpoll** *<4-17>***] | [version** *<1-4>***]** |

power efficient-ethernet auto |

role lan | trusted | wan |

service-policy in *<WORD>* **| out** *<WORD>* |

shutdown |

snmp trap interface-ip | link-status |

spanning-tree [bpdufilter enable | disable] | [bpduguard [disable | enable] | [cost *<1-200000000>***] | [guard loop | none | root | topology-change] | [link-type auto | point-to-point | shared] | [mcheck] | [mst cost** *<1-200000000>***] | port-priority** *<0-240>* **| [portfast disable | edge | network]** |

speed 10 |100 | 1000 |auto |

vrrp *<1-255>* |

zone-member security *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if-range)#
{**alarm profile** *<WORD>* |	Use this alarm profile for this interface.

arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable proxy-arp | timeout *<1-2147483>* |	Configure ARP parameters. **Disable ARP filter**—If enabled the router responds to same ARP requests coming from multiple interfaces. **Enable ARP Accept**—Define behavior for gratuitous ARP frames who's IP is not already present in the ARP table: 0—don't create new entries in the ARP table 1—create new entries in the ARP table **Enable ARP Announce**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **Enable ARP Ignore**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **ARP Timeout**—If an ARP entry is not used for a specific amount of time the entry is removed from the caching table. **Enable Proxy ARP**—Enable Proxy ARP if you need your router to respond to local networks with its MAC address. Default is Disabled
authentication host-mode | multi-auth | multi-host | single-host | periodic | port-control auto | forced-authorized | force-unauthorized | timer reauthenticate *<1-65535>* | restart *<1-65535>* |	Configure authentication parameters to use on this interface when using Dot1x devices. Selects authentication mode to use on this interface when using Dot1x devices. **Host Mode** **Single host** • Only one device can authenticate and connect on the port. • This is the default mode of operation.

	Multiple host • Unlimited number of devices can connect on the port once a single device has been authenticated on the port. This single device must be a data (as opposed to voice) device. **Multiple authentication** • Each device connecting to your router is required to authenticate. • No limit as to the number of devices which can authenticate on the port. **Multiple authentication** • Each device connecting to your router is required to authenticate. • No limit as to the number of devices which can authenticate on the port. **Port control** • Auto—the port is locked expecting authentication from either a connected 802.1X client or if MAB is enabled, it will authenticate the MAC to the RADIUS server. • Force authorized—the port is unsecure/ unlocked meaning normal operation where no 802.1X client or MAB authentication via RADIUS is required. This is the default setting. • Force unauthorized – the port is secured/ locked and will NEVER allow any traffic to ingress into our Ethernet port/s. **Timer** **Maximum re-authentication retries**— Set the number of times the authenticator will attempt to re-authenticate a supplicant. Range is 1-10 seconds Default is 2 seconds **Restart timeout—** Interval in seconds after which an attempt should be made to authenticate an unauthorized port. If the parameter “server” is specified, the time is derived from the “Session-Timeout value” (RADIUS Attribute 27) Range is 1-65535 seconds Default is 60 seconds
bridge-group ***<1-9999>*** |	Add this interface to the specified bridge-group.

description *<LINE>* |	Add this interface to the specified bridge-group.
dot1x [credential *<WORD>*] | [max-auth-req *<1-10>*] | [max-req *<1-10>*] | [pae authenticator | supplicant] | [supplicant eap profile *<WORD>*] | [timeout quiet-period *<1-65535>* | supp-period *<1-65535>* | tx-period *<1-65535>*] |	Sets the Port Access Entity (PAE) type. **Supplicant**—The interface acts only as a supplicant and does not respond to messages that are meant for an authenticator. **Authenticator**—The interface acts only as an authenticator and does not respond to any messages meant for a supplicant. **Both**—The interface behaves both as a supplicant and as an authenticator and thus does respond to all dot1x messages
duplex auto | half | full |	Select duplex for this interface. In most cases this parameter should be left at auto
ip [address *<A.B.C.D>* | dhcp] | [ddns service dyndns | use-web skip *<WORD>* | url *<WORD>*] | [dhcp client class-id *<LINE>* | auto | client-id ethernet *<1-5>* | acsii *<WORD>* | auto | hex *<HEX-STRING* | hostname *<WORD>*] | [dhcp-relay] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>* | dhcp] | [ospf authentication [message-digest | null | authentication-key *<LINE>*] | [cost *<1-65535>* | dead-interval *<1-65535>* | hello-interval *<1-65535>* | message-digest-key *<1-255>* md5 *<LINE>*] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string *<0* | *7* | *WORD>* | split-horizon disable | poisoned-reverse] |	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface **secondary—**add secondary addresses (IP aliasing) to this interface **DHCP—**your address is assigned from a DHCP server **DHCP client —** **DNS dhcp—**use DNS servers received from DHCP server for specified interface **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic **health-profile—**use this health profile for this interface, configure a nexthop interface. **OSPF—** **authentication/authentication-key—** enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD> **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0 to 16777214 Default is none **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5 authentication.
  - 0-unencrypted key will follow
  - specifies a hidden key will follow
  - specifies a password (key) will follow (max 16 characters).
    The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—Configure the network type

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship.

	• Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts • non-broadcast—use this type of network on networks having no broadcast/ **priority**—a router with a high priority will always win the DR/BDR election process Priority Range is 0-255 Default is 1 **retransmit-interval**—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. Range is 1–65535 Default is 5 second **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. Default is enabled Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Link state advertisements in the update packet have their age incremented by this amount before transmission. Default is enabled Range is 1–65535 Default is 1 seconds
ipsec restrict |	Restrict IPsec on this interface.

ipv6 address *<X:X:X:X::X/<0-128>* | autoconfig | dhcp] [enable] | [firewall in | out | local *<WORD>*] | [nd dad attempt *<0-500>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite | no-autoconfig | no-onlink] | [ra dns server *<X:X:X:X::X>* | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800> <3-1350>*] | [lifetime *<0>* | *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | retransmission-time *<0-3600000>* | router-preference high | low |medium] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [ifmtu] | [instance-id *<0-255>*] | [mtu-ignore] | [network broadcast | point-to-point] | [passive | priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip | split-horizon disable | poisoned-reverse]|	Configure IPv6 parameters. |**IPvV6 address or DHCP**—configure the IPv6 address and prefix length or obtain an IPv6 address using DHCP **enable**—enable IPv6 on this interface **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic **nd**—IPv6 Interface Neighbor Discovery sub-commands • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured. Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information. Default is disabled (hosts use stateless auto-configuration of no-address information • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128

policy <*WORD*>] | [rip authentication key-chain | mode <*WORD*>] |	**no-autoconfig**—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination. Default is off **no-onlink—**The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix. Default is off **ra**—Router Advertisement Control **dns server**—specify the name server in RA. **hop-limit**—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets. Range is 1–255 Default is 64 **Interval**—Specifies the maximum/minimum time allowed between sending unsolicited multicast router advertisements. Range of minimum is 3 to *0.75 max (dynamic range) Default maximum 600 seconds, minimum is 0.33*max Range is 1–1800 in seconds **lifetime**—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list. The router lifetime applies only to the router's usefulness as a default router; it does not apply to information contained in other message fields or options. Range is 1–9000 seconds Default is 1800 seconds 0 = not a default route **suppress**—enable or disable IPv6 Router advertisements. Default is send router advertisements **reachable time**—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation Default is 0 (unspecified by this router) Range is 0-360000 milliseconds

retransmission-time—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE).
Range 1–3600000 in milliseconds
Default is 0

router-preference—set the default router preference. A Hgh value means this router will be preferred.

- **High**
- **Medium**
- **Low**

Default is medium

OSPF—
authentication/authentication-key— enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD>

cost—Configure a default metric to be applied to routes being distributed into OSPF.
Range is 0 to 16777214
Default is none

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—

- broadcast–Specify OSPF broadcast multi-access network
- point-to-point–Specify OSPF point-to-point network

	priority—a router with a high priority will always win the DR/BDR election process Priority Range is 0-255 Default is 1 Range is 1–65535 Default is 5 second Default is enabled Range is 1–65535 Default is 1 seconds **retransmit-interval**—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission. **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled
lldp max-neighbors *<1-50>* | receive | tvl-select mac-phy-cfg | management-address | max-frame-size | port-description | system -capabilities | system-description | system-name | transmit |	Configure LLDP parameters.
logging event interface-ip | link-status |	Configure logging events for interface and link status.
mab eap |	Sets MAC authentication bypass interface commands.
mtu *<64-9000>* |	Configure maximum transmission unit (MTU). Values are 64-9000 Default is

ntp [broadcast client | destination <*A.B.C.D*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] | [disable] | [multicast [<*A.B.C.D*> | <*X:X:X:X::X*> | client	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network. The router can provide the time to NTP/SNTP capable client devices (or other Perle routers and IOLAN's etc)
<*A.B.C.D*> | <*X:X:X:X::X*>] | [key <*1-65534*>*]* | [minpoll <*4-17*>] | [version <*1-4*>] |	You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network The router can provide the time to NTP/ SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts **destination broadcast**—Configure broadcast destination address **multicast** client—listens to NTP multicasts **destination multicast**—multicast IPv4 or IPv6 address **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s). Default is 6
power efficient-ethernet auto |	Configure Ethernet interface power settings.

role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side. **WAN—**management access is from the WAN side. **Trusted—**management access from either the LAN or WAN side.
service-policy in <*WORD*> | out <*WORD*>|	Assign traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
shutdown |	Shutdown this interface.
snmp trap interface-ip | link-status |	Set SNMP traps for interface and link status.

spanning-tree [bpdufilter enable | disable] | [bpduguard [disable | enable] | [cost *<1-200000000>*] | [guard loop | none | root | topology-change] | [link-type auto | point-to-point | shared] | mcheck] | [mst cost *<1-200000000>*] | [port-priority *<0-240>*] | [portfast disable | edge | network] |	Configure interface parameters for spanning tree. **bpdufilter**—don't send or receive BPDUs on this interface. Default is Disabled **bpduguard**—don't accept BPDUs on this interface. Default is Disabled **cost**—change port path cost. Value is 1 to 200000000. Default is auto (defined by STP protocol) **guard** • loop • none • root • topology-change **link-type** • auto—this interface is point-to-point if configured for full duplex operation • point-to-point • shared **mcheck—**force the mode from STP to RSTP/MSTP mode **mst—**change path cost and port priority for multiple spanning tree mode **port-priority—**change the port priority for an instance. (increments of 16) Default is 128 **portfast network—**this feature causes the router to enter the STP forwarding-state immediately or upon a linkup event, thus passing the listening and learning states. Some applications need to connect to the network immediately, else they will timeout
	portfast edge—is used to configure a port on which an end device is connected, such as a PC. All ports directly connected to end devices cannot create bridging loops in the network. Therefore, the edge port directly transitions to the forwarding state, and skips the listening and learning stages.

speed 10 |100 | 1000 |auto |	Configure the Ethernet speed • 10 • 100 • 1000 • auto
vrrp *<1-255>* |	This interface is part of VRRP group number.
zone-member security *<WORD>*}	This interface is a member of zone security.
Command Modes	Perle**(config-if-range)**#

Usage Guidelines

Set parameters for multiple Ethernet ports.

Examples

This example restricts IPv6 on Ethernet port range 1-2.

```
Perle(config)#interface range ethernet 1 , 2
Perle(config-if-range)#ipsec restrict
```

Related Commands

(config-if)#bvi
(config-if)#dialer
(config-if)#openvpn-tunnel
(config-if)#tunnel
(config-if)#dot11radio
(config-if)#cellular

(config-if)#openvpn-tunnel

{*<0-999>* tap | tun |
bridge-group *<1-9999>* |
description *<LINE>* |
ip [ddns service dyndns | use-web skip *<WORD>* | url *<WORD>*] | [dhcp-relay] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>* | dhcp] | [ospf authentication message-digest | null] | [authentication-key *<LINE>*] | [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 *<LINE>*] | [mtu-ignore] | network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain *<WORD>* | mode md5 | text string *<0* | *7* | *WORD>* | split-horizon disable | poisoned-reverse] |
ipv6 [enable] | [firewall in | local |out] | | [nd dad attempt *<0-500>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite | no-autoconfig | no-onlink | [ra dns server *<X:X:X:X::X>* | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800> <3-1350*] | [lifetime *<0>* | *<4-9000>*] |

[suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low |medium] | [ifmtu] | [instance-id *<0-255>*] | [mtu-ignore] | [passive] | [priority *<0-255>*] | [retransmit -interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [ospf cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [instance-id *<0-255>*] | [mtu-ignore] | [network broadcast | point-to-point] | [passive] | [priority*<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip | split-horizon disable | poisoned-reverse] |

logging event interface-ip | link-status |

ntp [broadcast client | destination *<A.B.C.D>*] | [key *<1-65534>*] | [minpoll *<4-17>*] | [version *<1-4>*] | [disable] | [multicast [*<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>*] | [key *<1-65534>]* | [minpoll *<4-17>*] | [version *<1-4>*] |

role lan | trusted | wan |

service-policy in *<WORD>* | out *<WORD>* |

snmp trap interface-ip | link-status |

zone-member security *<WORD>*}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if)# openvpn-tunnel
{***<0-999>* tap	tun	**	Tunnel interface number. Choose tap or tun device. tap (L2 link layer) tun (L3 network layer)
bridge-group *<1-9999>* |	Sets transparent bridging interface parameters.
description *<LINE>* |	Description for this interface.
**ip [ddns service dyndns	use-web skip *<WORD>*	url *<WORD>*]	[dhcp-relay]	[firewall in	local	out *<WORD>*]	[health-profile *<WORD>* nexthop *<A.B.C.D>*	dhcp]	[ospf authentication**	Configure IP parameters. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server **Host/host-group—**Hostname/list of hostnames registered with the DDNS service

message-digest | null] | [authentication-key *<LINE>*] | [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 *<LINE>*] | [mtu-ignore | network broadcast | non-broadcast | point-to-point | point-to-multipoint] | [priority*<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain*<WORD>* | mode md5 | text string *<0 | 7 | WORD>* | split- horizon disable | poisoned-reverse] |	Configure IP parameters. **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server **Host/host-group—**Hostname/list of hostnames registered with the DDNS service **skip—**skip everything before this ont he given URL **Use-web URL**—Enter the URL that you want to obtain an IP address from. This allows the router to be seen on the Internet as a public address **DHCP–relay—**set DHCP-relay for this interface **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic **health-profile—**use this health profile for this interface, configure a nexthop interface **OSPF—** **authentication/authentication-key—**enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD> **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0 to 16777214 Default is none **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network. Default is 4 times the hello interval Default is 40 seconds **hello interval—**Configure the hello packet time interval for hello packets sent on an interface. The default is 10 seconds. **message-digest-key**—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters.

There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5

authentication.

  - 0-unencrypted key will follow
  - specifies a hidden key will follow
  - specifies a password (key) will follow (max 16 characters).
    The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—Configure the network type

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)
- point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. Point-to-Multipoint networks advertise a hot route for all the frame-relay endpoints.
- non-broadcast—use this type of network on networks having no broadcast/ multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts

priority—a router with a high priority will always win the DR/BDR election process
Priority Range is 0-255
Default is 1

retransmit-interval—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface,
The expected round-trip delay between any two routers in the attached network.
Range is 1–65535
Default is 5 second

transmit-delay—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface.

route-policy—enable this policy route for this interface

rip—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received

Default is enabled

ipv6 [enable] | [firewall in | local |out] | | [nd dad attempt *<0-500>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite | [ra dns server *<X:X:X:X::X>* | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800> <3-1350>*] | [lifetime *<0>* | *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low |medium] | [ifmtu] | [instance-id *<0-255>*] | [mtu-ignore] | [passive] | [priority *<0-255>*] | [retransmit -interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [instance-id *<0-255>*] | [mtu-ignore] | [passive] | [priority *<0-255>*] | [retransmit -	Configure IPv6 parameters. **enable**—enable IPv6 on this interface **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **nd**—IPv6 Interface Neighbor Discovery sub-commands • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured. Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128

interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [ospf [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [instance-id *<0-255>*] | [mtu-ignore] | [passive] | [priority*<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip | split-horizon disable | poisoned-reverse] |	**no-autoconfig**—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination. Default is off **no-onlink—**The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix. Default is off **ra**—Router Advertisement Control **dns server**—specify the name server in RA. **hop-limit**—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets. Range is 1–255 Default is 64 **Interval**—Specifies the maximum/minimum time allowed between sending unsolicited multicast router advertisements. Range of minimum is 3 to *0.75 max (dynamic range) Default maximum 600 seconds, minimum is 0.33*max Range is 1–1800 in seconds **lifetime**—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list. The router lifetime applies only to the router's usefulness as a default router,it does not apply to information contained in other message fields or options. Range is 1–9000 seconds Default is 1800 seconds 0 = not a default route **suppress**—enable or disable IPv6 Router advertisements. Default is send router advertisements **reachable time**—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation Default is 0 (unspecified by this router) Range is 0-360000 milliseconds

retransmission-time—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE).
Range 1–3600000 in milliseconds
Default is 0

router-preference—set the default router preference. A High value means this router will be preferred.

- **High**
- **Medium**
- **Low**

Default is medium

OSPF—
cost—Configure a default metric to be applied to routes being distributed into OSPF.
Range is 0 to 16777214
Default is none

dead-interval—Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network.

Default is 4 times the hello interval
Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

ifmtu—The range is dynamic (depending on the interface type) and it will match with the MTU value set on the interface.
instance-id—instance ID for this interface
Values are 0–255

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

	network— • broadcast–Specify OSPF broadcast multi-access network • point-to-point–Specify OSPF point-to-point network **passive**—no adjacency will be formed on this interface **priority**—a router with a high priority will always win the DR/BDR election process Priority Range is 0-255 Default is 1 **retransmit-interval**—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. Range is 1–65535 Default is 5 second **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. **route-policy**—enable this policy route for this interface **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received
logging event interface-ip | link-status |	Configure logging events for interface and link status.

ntp [broadcast client | destination <*A.B.C.D*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] | [disable] | [multicast [<*A.B.C.D*> | <*X:X:X:X::X*> | client <*A.B.C.D*> | <*X:X:X:X::X*>] | [key <*1-65534*>*]* | [minpoll <*4-17*>] | [version <*1-4*>] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network The router can provide the time to NTP/ SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts **destination broadcast**—Configure broadcast destination address **multicast** client—listens to NTP multicasts **destination multicast**—multicast IPv4 or IPv6 address. **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s). Default is 6
role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side. **WAN—**management access is from the WAN side. **Trusted—**management access from either the LAN or WAN side.
service-policy in <*WORD*>| out <*WORD*> |	Assign traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
snmp trap interface-ip | link-status	Set SNMP traps for interface and link status.
zone-member security <*WORD*>}	This interface is a member of this zone security.
Command Modes	(config-if)#

Usage Guidelines

Set configuration parameters for OpenVPN tunnel.

Examples

This example sets SNMP to trap for link-status.

(config-if)#snmp trap link-status

Related Commands

(config-if)#bvi

(config-if)#tunnel

(config-if)#cellular

(config-if-ethernet)#

(config-if)#tunnel

{***<0-999>*** **mode [gre | ipv6ip]** |

arp disable-arp-filter | enable-arp-accept | enable-arp-announce | enable-arp-ignore | enable-proxy-arp |

ip [address ***<A.B.C.D> <A.B.C.D>*** **secondary] | [ddns service dyndns | use-web skip** ***<WORD>*** **| url** ***<WORD>*****] | [dhcp-relay] | [firewall in | local | out** ***<WORD>*****] | [health-profile** ***<WORD>*** **nexthop** ***<A.B.C.D>*****] | [ospf authentication message-digest | null] | [authentication-key** ***<LINE>*****] | [cost** ***<1-65535>*****] | [dead-interval** ***<1-65535>*****] | [hello-interval** ***<1-65535>*****] | [message-digest-key** ***<1-255>*** **md5** ***<LINE>*****] | [mtu-ignore] | [network broadcast | non-broadcast | point-to-point] | point-to-multipoint] | [priority** ***<0-255>*****] | [retransmit-interval** ***<1-65535>*****] | [transmit-delay** ***<1-65535>*****] | [policy route-policy** ***<WORD>*****] | [rip authentication key-chain** ***<WORD>*** **| mode md5 | text string 0** ***<WORD>*** **| 7** ***<WORD>*** **|** ***<WORD>*** **| [split-horizon disable | poisoned-reverse]** |

ipsec restrict |

ipv6 [address ***<X:X:X:X::X/<2-128>*****] | [enable] | [firewall in | local | out** ***<WORD>*****] | [nd dad attempts** ***<0-600>*** **| managed config-flag | other-config-flag | prefix** ***<X:X:X:X::X/<0-128> <0-4294967294>*** **| infinite |no-autoconfig | on-onlink] | [ra dns server** ***<X:X:X:X::X>*** **| hop-limit** ***<1-255>*** **| unspecified] | interval** ***<4-1800> <3-1350*****] | [lifetime** ***<0> <4-9000>*****] | [suppress] | [reachable time** ***<0-3600000>*****] | [retransmission-time** ***<0-3600000>*****] | [router-preference high | low | medium] | [ospf cost** ***<1-65535>*** **| [dead-interval** ***<1-65535>*****] | [hello-interval** ***<1-65535>*****] | [ifmtu] | [instance-id** ***<0-255>*****] | [mtu-ignore] | [passive] | [priority** ***<0-255>*****] | [retransmit-interval** ***<1-65535>*****] | [transmit-delay** ***<1-65535>*****] | [policy route-policy** ***<WORD>*****] | [rip | split-horizon disable | poisoned-reverse]** |

logging event interface-ip | link-status |

mtu ***<64-1500>*** |

ntp broadcast client | destination ***<A.B.C.D>*** **| key****<1-65534>*** **| minpoll** ***<4-17>*** **| version** ***<1-4>*** **| disable | multicast** ***<A.B.C.D>*** **|** ***<X:X:X:X::X>*** **| client** ***<A.B.C.D>*** **|** ***<X:X:X:X::X>*** **| key** ***<1-65534>*** **| minpoll** ***<4-17>*** **| version** ***<1-4>*****]** |

role lan | trusted | wan |

service-policy in ***<WORD>*** **| out** ***<WORD>*** |

shutdown |

snmp interface-ip | link-status |

tunnel destination <*A.B.C.D*> | multicast source <*A.B.C.D*> source <A.B.C.D> | cellular <*0-0*> | dot11radio <*0-4*> | ethernet <*1-5*> . <*1-4000*> | tos <*0-99*> | ttl <*1-255*> |

zone-member security <*WORD*>}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if)# tunnel
{**tunnel <*0-999*> mode [gre ip	ipv6ip 6in4]	**	Sets mode gre and ipv6up tunnel interface parameters.
**arp disable-arp-filter	enable-arp-accept	enable-arp-announce	enable-arp-ignore	enable-proxy-arp	timeout <*1-2147483*> |**	Configure ARP parameters. **Disable ARP filter**—If enabled the router responds to same ARP requests coming from multiple interfaces. **Enable ARP Accept**—Define behavior for gratuitous ARP frames who's IP is not already present in the ARP table: 0—don't create new entries in the ARP table 1—create new entries in the ARP table **Enable ARP Announce**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface. **Enable ARP Ignore**—Define different restriction levels for announcing the local source IP address from IP packets in ARP requests sent on interface • 0—(default) Use any local address, configured on any interface • 1—Try to avoid local addresses that are not in the target's subnet for this interface **ARP Timeout**—If an ARP entry is not used for a specific amount of time the entry is removed from the caching table. **Enable Proxy ARP**—Enable Proxy ARP if you need your router to respond to local networks with its MAC address. Default is Disabled

ip [address *<A.B.C.D>* *<A.B.C.D>*] | [ddns service dyndns | use-web skip *<WORD>* | url *<WORD>*] | [dhcp-relay] | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>*] | [ospf authentication message-digest | null] | [authentication-key *<LINE>*] | [cost *<1-65535>*] | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>*] | [message-digest-key *<1-255>* md5 *<LINE>*] | [mtu-ignore] |	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface **secondary**—add secondary addresses) IP aliasing) for this interface **DHCP—**your address is assigned from a DHCP server **DDNS—** **Service—**use dyndns login/password—configure the login id and password for the dnydns server **Host/host-group—**Hostname/list of hostnames registered with the DDNS service **skip—**skip everything before this ont he given URL

[network broadcast | non-broadcast | point-to-point] | point-to-multipoint] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip authentication key-chain*<WORD>* | mode md5 | text string 0 *<WORD>* | 7 *<WORD>* | *<WORD>* | [split-horizon disable | poisoned-reverse]	**Use-web URL**—Enter the URL that you want to obtain an IP address from. This allows the router to be seen on the Internet as a public address **DHCP client —** **Class ID:** • Auto • Line Specify a Hex string or ASCII text. This same hex string or text would be configured on the server side and associated with an address to give the client. **Client ID:** This can be configured to be the Ethernet interface number, ASCII text, Hex string or set to Auto. option—60—Vendor class identifier<oem-name>:<model>:<serial#> in ASCII Router example: Perle:IRG5541:350-01T00003 **Hostname:** Specify a value for hostname option **DHCP–relay—**set DHCP-relay for this interface **DNS dhcp—**use DNS servers received from DHCP server for specified interface **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic. **health-profile—**use this health profile for this interface, configure a nexthop interface **OSPF—** **authentication/authentication-key—**enables message-digest authentication, text, or null. Authentication-key 0 | 7 <WORD> **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0 to 16777214 Default is none **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead). As with the hello interval, this value must be the same for all routers attached to a common network. Default is 4 times the hello interval Default is 40 seconds

hello interval—Configure the hello packet time interval for hello packets sent on an interface.
The default is 10 seconds.

message-digest-key—Configure a password used by neighboring routers for simple password authentication. It can be any continuous string of up to eight characters. There is no default value.

- None—no password
- Key-ID—Configure an authentication key
- md5—Identifies the key (password) used between this router and neighboring routers for MD5

authentication.

  - 0-unencrypted key will follow
  - specifies a hidden key will follow
  - specifies a password (key) will follow (max 16 characters).
    The default is none

mtu-ignore—By default, OSPF checks whether neighbors are using the same MTU on a common interface. Use this command to disable this check and allow adjacencies when the MTU value differs between OSPF neighbors.

network—Configure the network type

- broadcast—a designated router and backup designated router are elected using OSPF multicasting capabilities point-to-multipoint— configures selected routers with neighbor/cost parameters, identifying a specific cost for the connection to the specified peer neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all
- point-to-point—there are only two neighbors and multicast is not required. Routers on an interface becoming neighbors should match the network type all. (most common type)

	• point-to-multipoint—directs the network to treats point-to-multipoint networks as a collective of point-to-point links. Point-to-Multipoint networks do not maintain a DR/BDR relationship. , ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/ multicasts • non-broadcast—use this type of network on networks having no broadcast/ multicast capability, such as frame-relay, ATM, SMDS, & X.25. The key point is that these layer 2 protocols are unable to send broadcasts/multicasts **priority**—a router with a high priority will always win the DR/BDR election process Priority Range is 0-255 Default is 1 **retransmit-interval**—configure the time between retransmitting lost link advertisements) Time in seconds between link state advertisement retransmissions for adjacencies belonging to the interface, The expected round-trip delay between any two routers in the attached network. Range is 1–65535 Default is 5 second **transmit-delay**—configure the transmit delay. The estimated time in seconds required to transmit a link state update packet on the interface. Link state advertisements in the update packet have their age incremented by this amount before transmission Range is 1–65535 Default is 1 seconds **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received. Default is enabled
ipsec restrict |	Restrict IPsec on this interface.

ipv6 [address *<X:X:X:X::X/<2-128>* eui-64] | [enable] | [firewall in | local | out *<WORD>*] | [nd dad attempts *<0-600>* | managed config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128> <0-4294967294>* | infinite] | [ra dns server *<X:X:X:X::X>* | hop-limit *<1-255>* | unspecified] | interval *<4-*	**address—**specify an IPv6 address. **enable**—enable IPv6 on this interface. **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic **nd**—IPv6 Interface Neighbor Discovery sub-commands • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages.

***1800> <3-1350* | lifetime *<0> <4-9000>* | suppress | reachable time *<0-3600000>* | retransmission-time *<0-3600000>* | router-preference high | low | medium] | [ospf cost *<1-65535>* | [dead-interval *<1-65535>*] | [hello-interval *<1-65535>]* | [ifmtu] | [instance-id *<0-255>*] | [mtu-ignore] | [network broadcast | point-to-point | [passive] | [priority *<0-255>*] | [retransmit-interval *<1-65535>*] | [transmit-delay *<1-65535>*] | [policy route-policy *<WORD>*] | [rip | split-horizon disable | poisoned-reverse] |**	• Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured. Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information. Default is disabled (hosts use stateless auto-configuration of no-address information • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128 **no-autoconfig**—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination. Default is off **no-onlink—**The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix. Default is off **ra**—Router Advertisement Control **dns server**—specify the name server in RA. **hop-limit**—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets. Range is 1–255 Default is 64 **ra**—Router Advertisement Control **dns server**—specify the name server in RA.

hop-limit—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets.
Range is 1–255
Default is 64

Interval—Specifies the maximum/minimum time allowed between sending unsolicited multicast router advertisements.
Range of minimum is 3 to *0.75 max (dynamic range)
Default maximum 600 seconds, minimum is 0.33*max
Range is 1–1800 in seconds

lifetime—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list. The router lifetime applies only to the router's usefulness as a default router; it does not apply to information contained in other message fields or options.
Range is 1–9000 seconds
Default is 1800 seconds
0 = not a default route

suppress—enable or disable IPv6 Router advertisements.
Default is send router advertisements
reachable time—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation
Default is 0 (unspecified by this router)
Range is 0-360000 milliseconds

retransmission-time—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE).
Range 1–3600000 in milliseconds
Default is 0

router-preference—set the default router preference. A High value means this router will be preferred.

- **High**
- **Medium**
- **Low**

Default is medium

	OSPF— **cost**—Configure a default metric to be applied to routes being distributed into OSPF. Range is 0–16777214 Default is 4 times the hello interval Default is 40 seconds **dead-interval—**Configure the interval during which at least one hello packet must be received from a neighbor before the router declares that neighbor as down (dead).) As with the hello interval, this value must be the same for all routers attached to a common network. **hello interval—**Configure the hello packet time interval for hello packets sent on an interface. Default is none Default is enabled The default is 10 second **ifmtu**—The range is dynamic (depending on the interface type) and it will match with the MTU value set on the interface. **instance-id—**instance ID for this interface Values are 0–255 **passive**—no adjacency will be formed on this interface **network**— broadcast– **priority**—a router with a high priority will always win the DR/BDR election process Priority Range is 0-255 Default is 1 **policy route-policy**—enable this policy route for this interface. **rip**—enable split horizon to prevent a routing loop in your network. Basically, information about the routing for a particular packet is never sent back in the direction from which it was received
logging event interface-ip | link-status |	Configure logging events for interface and link status.
mtu ***<64-9000>*** **|**	Configure maximum transmission unit (MTU). Values are 64-9000 Default is 1476

ntp [broadcast client | destination <*A.B.C.D*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] | [disable] | [multicast [<*A.B.C.D*> | <*X:X:X:X::X*> | client <*A.B.C.D*> | <*X:X:X:X::X*>] | [key <*1-65534*>*]* | [minpoll <*4-17*>] | [version <*1-4*>] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network The router can provide the time to NTP/SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the Router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts **destination broadcast**—Configure broadcast destination address **multicast** client—listens to NTP multicasts **destination multicast**—multicast IPv4 or IPv6 address **key**—Configure broadcast authentication key **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side **WAN—**management access is from the WAN side **Trusted—**management access from either the LAN or WAN side
service-policy in <*WORD*> | out <*WORD*> |	Assign traffic policy to this interface. Select whether the policy will apply to inbound or outbound traffic.
shutdown |	Shutdown this interface.
snmp interface-ip | link-status |	Configure SNMP traps for interface and link status.

tunnel destination *<A.B.C.D>* | multicast source *<A.B.C.D>* source *<A.B.C.D>* | cellular *<0-0>* | dot11radio *<0-4>* | ethernet *<1-5>* . *<1-4000>* | tos *<0-99>* | ttl *<1-255>* |	Configure tunnel parameters.
zone-member security *<WORD>*}	This interface is a member of this zone security.

Command Modes

Perle(config-if)#

Usage Guidelines

Use this command to configure tunnel interface parameters.

Examples

This example enables ARP accepts on this interface.

Perle(config-if)# arp enable-accepts

Related Commands

(config-if)#bvi

(config-if)#dialer

(config-if)#openvpn-tunnel

(config-if-ethernet)#(config-if)#dot11radio

(config-if)#cellular

(config-if-vrrp)#

{[authentication 0 *<WORD>* | 7 *<WORD>*] | [md5 key-string 0 *<WORD>* | text] | [text 0 *<WORD>* | 7 *<WORD>*] |

description *<LINE>* |

ip *<A.B.C.D>* *<A.B.C.D>* | [firewall in | local | out *<WORD>*] | [health-profile *<WORD>* nexthop *<A.B.C.D>*] | [policy route-policy *<WORD>*] |

ipsec restrict |

ipv6 [address *<X:X:X:X::X/<0-128>*] | [enable] | [firewall in | out | local] | [nd dad attempts <0-600>| managed-config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128>* | *<0-4294967294>* | infinite] | no-autoconfig | no-onlink] | [ra dns server *<X:X:X:X::X>*] | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800>* *<3-1350>*] | [lifetime *<0>* | *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preference high | low |medium] | [policy route-policy *<WORD>*] | [rip enable | split-horizon disable | poisoned-reverse] |

logging event interface-ip | link-status |

mtu *<68-1500>* |

ntp broadcast client | destination ***<A.B.C.D>*** **| key*<1-65534>* | minpoll *<4-17>* | version *<1-4>* | disable | multicast *<A.B.C.D>* | *<X:X:X:X::X>* | client *<A.B.C.D>* | *<X:X:X:X::X>* | key *<1-65534>* | minpoll *<4-17>* | version *<1-4>* |**
peer-address ***<A.B.C.D>*** **|**
preempt delay ***<0-1000>*** **|**
priority ***<1-254>*** **|**
role lan | trusted | wan |
shutdown |
snmp trap interface-ip | link status |
sync-group |
timers advertise ***<10-255000>*** **|**
version ***<2-3>*** **|**
zone-member security ***<WORD>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-if-vrrp)#
{**[authentication 0 <*WORD*> | 7 <*WORD*>] | [md5 key-string 0 <*WORD*> | text] | [text 0 <*WORD*> | 7 <*WORD*>] |**	Configure VRRP authentication parameters. Configure the VRRP authentication clear text/ cipher password for the VRRP group on an interface. If this option is not set, the interface is not required to authenticate to the VRRP group.
description <*LINE*> |	Configure VRRP description.
ip <*A.B.C.D*> <*A.B.C.D*> | [firewall in | local | out <*WORD*>] | [health-profile <*WORD*> nexthop <*A.B.C.D*>] | [policy route-policy <*WORD*>] |	Configure IP parameters. **IP address/IP mask—**Configure the IP address/mask of this interface **Firewall—**set firewall for inbound, traffic destined for this router or outbound traffic **health-profile—**use this health profile for this interface, configure a nexthop interface **policy route-policy**—enable this policy route for this interface.
ipsec restrict |	Restrict IPsec on this interface.

ipv6 [address *<X:X:X:X::X/<0-128>*] | [enable] | [firewall in | out | local] | [nd dad attempts <0-600>| managed-config-flag | other-config-flag | prefix *<X:X:X:X::X/<0-128>* | *<0-4294967294>* | infinite] | no-autoconfig | no-onlink] | [ra dns server *<X:X:X:X::X>*] | [hop-limit *<1-255>* | unspecified] | [interval *<4-1800> <3-1350>*] | [lifetime *<0>* | *<4-9000>*] | [suppress] | [reachable time *<0-3600000>*] | [retransmission-time *<0-3600000>*] | [router-preferencehigh | low |medium] | [policy route-policy *<WORD>*] | [rip enable | split-horizon disable | poisoned-reverse] |	Configure IPv6 parameters. **IPv6 address/IP mask—**Configure the IP address/mask of this interface **enable**—enable IPv6 on this interface. **firewall**—set firewall for inbound, traffic destined for this router or outbound traffic. **nd**—IPv6 Interface Neighbor Discovery sub-commands. • dad (duplicate address detection) attempts—To check the uniqueness of an IPv6 address, a node sends Neighbor Solicitation messages. Use this command to specify the number of consecutive Neighbor Solicitation messages (dad_attempts) to be sent before this address can be configured. Range 1–600 Default is 1 • managed config flags—specify whether hosts use the administrated protocol for address auto-configuration. Default is disabled (host uses stateless) • other-config-flags—specify whether hosts use the administrated protocol for non-address auto-configuration information. Default is disabled (hosts use stateless auto-configuration of no-address information • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128 **no-autoconfig**—A prefix is onlink when it is assigned to an interface on a specified link. Enable or disable prefix for onlink determination. Default is off Default is disabled (hosts use stateless auto-configuration of no-address information • prefix—specifies the IPv6 prefix advertised on the interface Configure the prefix length. Range is 0–128

no-onlink—The sending router can indicate that a prefix is to be used for address autoconfiguration by setting the autonomous flag and specifying a nonzero Valid Lifetime value for the prefix.

ra—Router Advertisement Control

dns server—specify the name server in RA.

hop-limit—Specifies the Hop Count field of the IP header for outgoing (unicast) IP packets.
Range is 1–255
Default is 64

interval—The maximum time interval between sending unsolicited multicast router advertisements from the interface, in seconds.
Range is 4-1800 seconds
minimum 3-1350
Default is 1800 seconds
0 = not a default route

lifetime—The lifetime associated with the default router in seconds. A value of 0 indicates that the router is not a default router and doesn't appear on the default router list. The router lifetime applies only to the router's usefulness as a default router; it does not apply to information contained in other message fields or options.
Range is 4-9000 seconds
Default is 3 x the max-interval
0 = not a default route

suppress—enable or disable IPv6 Router advertisements.
Default is send router advertisements

	reachable time—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation Default is 0 (unspecified by this router) Range is 0-360000 milliseconds **retransmission-time**—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE). Range 1–3600000 in milliseconds Default is 0 **reachable time**—specifies the length in time (milliseconds) a node assumes a neighbor is reachable after receiving a reachability confirmation Default is 0 (unspecified by this router) Range is 0-360000 milliseconds **retransmission-time**—The retransmission timer is used to control the time (in milliseconds) between retransmissions of neighbor solicitation messages from the user equipment (UE). Range 1–3600000 in milliseconds Default is 0 **router-preference**—set the default router preference. A High value means this router will be preferred. • **High** • **Medium** • **Low** Default is medium **policy route-policy**—enable this policy route for this interface.
logging event interface-ip | link-status |	Configure logging events for interface and link status.
mtu ***<64-9000>*** **|**	Configure maximum transmission unit (MTU). Values are 64 to 9000 bytes Default is 1500 bytes

ntp [broadcast client | destination <*A.B.C.D*>] | [key <*1-65534*>] | [minpoll <*4-17*>] | [version <*1-4*>] | [disable] | [multicast [<*A.B.C.D*> | <*X:X:X:X::X*> | client <*A.B.C.D*> | <*X:X:X:X::X*>] | [key <*1-65534*>*]* | [minpoll <*4-17*>] | [version <*1-4*>] |	Network Time Protocol (NTP) is used distribute and maintain synchronization of time information between nodes in a network The router can provide the time to NTP/SNTP capable client devices (or other Perle routers and IOLAN's etc). You can run the SNTP client and the NTP server concurrently on your system. Therefore you can obtain time from an outside source and serve that time to the devices connected to the router. Configure Network Time Protocol (NTP) for this interface. **broadcast client**—listens to NTP broadcasts **destination broadcast**—Configure broadcast destination address. **multicast** client—listens to NTP multicasts. **destination multicast**—multicast IPv4 or IPv6 address. **key**—Configure broadcast authentication key. **versions** 1 to 4 are support. **minimum poll interval** is 4(16s), 5(32 s), 6 (1m 4s), 7(2m,8s), 8(4m,16s), 9(8m, 32s), 10 (17,m, 4s), 11 (34,m,8s) Default is 6
peer-address <*A.B.C.D*> |	Configure an unicast VRRP peer IP address.
preempt delay <*0-1000*> |	By default, the preemption delay is 0, indicating immediate preemption. In immediate preemption mode, a backup immediately switches to the master when detecting that its priority is higher than the master's priority. Delay is 0 to 1000 in seconds. Disabled—Even if a VRRP router with a higher priority than the current master is up, it does not replace the current master. Only the original master (when it becomes available) replaces the backup. Values 1-000 seconds Default is 0 (no delay)
priority <*1-255*> |	The priority value for the VRRP router that owns the IP address(es) associated with the virtual router. Values are 1-255 Default is 100

role lan | trusted | wan |	Select the role for this interface. **LAN—**management access is from the LAN side. **WAN—**management access is from the WAN side. **Trusted—**management access from either the LAN or WAN side.
shutdown |	Shutdown this interface.
snmp trap interface-ip | link status |	Configure SNMP traps for interface and link status.
sync-group *<WORD>* |	Adds this sync VRRP group to a sync group. Sync groups are used to link VRRP groups together in order to propagate transition changes from one group to another group.
sync-group *<WORD>* |	Assign this interface to a sync group. Adds this sync VRRP group to a sync group. Sync groups are used to link VRRP groups together in order to propagate transition changes from one group to another group. To clarify, in a VRRP synchronization group (“sync group”) are synchronized such that, if one of the interfaces in the group fails over to backup, all interfaces in the group fail over to backup. For example, if one interface on a master router fails, **Note:** VRRP groups in a sync group must have similar priority and preemption configurations. Before enabling a sync-group you should verify that one routeris master of both groups and the other is backup of both groups. If both side think they are master of the same group, then enabling a sync group can cause endless transitioning to get in sync.
timers *<10-255000>* |	Configure the time interval between the advertisement packets that are being sent to other Virtual Router Redundancy Protocol (VRRP) routers in the same group Values are 10–255000 milliseconds Default is 1000 milliseconds
version |	Configure the version number. Values are 2–3 Default is 3

zone-member security ***<WORD>***}	This interface is a member of this zone security.
Command Modes	Perle(config-if-vrrp)#

Usage Guidelines

Use this command to configure VRRP parameters.
Your router supports the Virtual Router Redundancy Protocol (VRRP).

VRRP is an election and redundancy protocol that dynamically assigns the responsibility of a virtual router to one of the physical routers on a LAN.

This increase the availability and reliability of routing paths in the network.
In VRRP, one physical router in a virtual router is elected as the master, with the other physical router of the same virtual router acting as backups in case the master fails. The physical routers are referred as VRRP routers.

The default gateway of a participating host is assigned to the virtual router instead of a physical router. If the physical router is routing packets on behalf of the virtual router fails, another physical router is selected to automatically replace it. The physical router forwarding packets at any given time is called the master router.

Examples

This example sets VRRP for version 2.

```
Perle(config)#interface ethernet 2
Perle(config-if)#vrrp 10
Perle(config-if-vrrp)#version 2
```

Related Commands

show vrrp

6 Interface line mode

This chapter defines all the CLI commands associated with configuring the console and tty ports. Some CLI commands may not be applicable to your model or running software.

line

line {**console** *<0-0>* | **tty** *<1-2>* | **vty**}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	line
{**console** *<0-0>* |	Applies only to models with serial ports. Configure console port parameters.
tty *<1-2>*|	Applies only to models with serial ports. Configure tty port parameters.
vty}	Configure vty port parameters.
Command Modes	Perle>enable Perle>config Perle#line

Usage Guidelines

Use this command to change to line mode.

Examples

This example set terminal width to 80.

```
Perle(config)#line vty
Perle(config-line)#width 80
```

Related Commands

(config-line)#tty

(config-line)#console

{**accounting exec** *<WORD>* | **default** |
authorization exec *<WORD>* | **default** |
databits 7 | **8** |
exec |
exec-timeout *<0-35791> <0-2147483>* |
history size *<0-256>* |
length <*0-512>* |
login authentication *<WORD>* | **default** |
media-interface null | **tty** | **usb** | **parity even** | **odd** | **none** |
speed | **115200** | **19200** | **38400** | **57600** | **9600** |
stopbits 1 | **2** |

timeout login response *<1-300>* |
transport output all | none | ssh | telnet |
width *<0-512>*}
Use the no form of this command to negate a command or set to defaults.

Syntax Description	(config-line)#console This command applies only to models with console port/s.
{**accounting exec** *<WORD>* | **default** |	Use an accounting list with a specified name or default list.
authorization exec *<WORD>* | **default** |	Use an authorization with a specified name or default list.
databits 7 | 8 |	Type 7 or 8 to set data bits.
exec |	Enables EXEC CLI session
exec-timeout *<0-35791> <0-2147483>* |	Configure the console session CLI timeout. Values are 0 to 35791 in minutes Default is 5 minutes
history size *0-256>* |	Configure the size of the history buffer.
length *0-512>* |	Configure the number of lines displayed on the screen. Type 0 for no pausing at end of page.
login authentication *<WORD>* | **default** |	Use the specified list for authentication requests or use the default list.
media-interface null | tty | usb |	Configure media interface type. • use null for no console port • use tty for serial port as the console port • use usb as the console port
parity even | odd | none |	Configure parity for console mode.
speed | 115200 | 19200 | 38400 | 57600 | 9600 |	Set the speed for this interface. • 115200 • 19200 • 38400 • 57600 • 9600
stopbits 1 | 2 |	Configure stop bits for console mode.
timeout login response *<1-300>* |	Configure timeout for user responses during the login sequence.

transport output all | none | ssh | telnet |	Allows the user on the console port to telnet or ssh out of the .
width ***<0-512>***}	Configure the width of the terminal display.

Command Default	console 0 timeout login response 30 login authentication default databits 8 parity none stopbits 1 speed 9600
Command Modes	Perle>enable Perle>config Perle(config)#line config 0 Perle(config-line)#

Usage Guidelines

Use these commands to set parameters for console mode.

Examples

These commands sets your console to speed 38400, databits 7 and stopbits 2.

```
Perle(config-line)#speed 38400
Perle(config-line)#databits 7
Perle(config-line)#stopbits 2
```

Related Commands

(config-line)#tty

(config-line)#tty

{**break break-interrupted | local | off | remote |**
break-delay ***<1-65535>*** **|**
break-length ***<1-65535>*** **|**
connection-method dial-in | dial-out | dial-in-out | direct-connect | ms-direct-guest | ms-direct-host |
cts-toggle off | on |
cts-toggle-final-delay ***<0-1000>*** **|**
cts-toggle-inital-delay ***<0-1000>*** **|**
databits 5 | 6 | 7 | 8 |
data-logging off | on |
dial-retries ***<0-99>*** **|**
dial-timeouts ***<0-99>*** **|**
discard-characters-rxd-with-errors off | on |
echo-suppression off | on |
flow both | hard | none | soft |

flowin off | on |
flowout off | on |
hotkey-prefix *<0-ff>* |
idle-timer *<0-4294967>* |
initiate-connection any-char | specific-char *<0-ff>* |
internet address *<A.B.C.D>* | *<X:X:X::X>* |
keepalive off | on |
line-termination off | on |
lock off | on |
map-cr-crlf off | on |

modbus [master crlf | entry | protocol] | [slave cflf | protocol | uid-range |
modem-init-string *<WORD>* |
monitor-dsr-dtr on | off |
motd off | on |
multihost entry *<1-49> <A.B.C.D>* | *<X:X:X::X>* port *<1-65535>* |
multisessions *<1-8>* |
name *<WORD>* |
packet-forwarding delay-between-messages *<1-65535>* | [enable-end-tigger1 on | off] | [enable-end-tigger2 on | off] | [enable-eof1 on | off] | [enable-eof2 on | off] | [enable-sof1 on | off] | [enable-sof2 on | off] | end-trigger1 *<0-0xff>* | end-trigger2 *<0-0xff>* | eof1*<0-0xff>* | eof2*<0-0xff>* | force-transmit-timer *<1-65535>* | [forwarding-rule strip-trigger | trigger | trigger+1 | trigger+2] | idle-timer *<1-65535>* | [mode custom-on-frame-definition | custom-on-specific-events | minimize-latency | optimize-network-throughput | prevent-message-fragmentation] | packet-size *<1-1024>* | sof1*<0-0xff>* | sof2*<0-0xff>* | start-frame-transmit off | on|
pages *<1-7>* |
parity even | mark | none | odd | space |
phone -number *<WORD>* |
ppp accm *<8 hex digits>* | [address-comp on | off] | auth-tmout *<1-255>* | [authentication chap | pap | none] | challenge-interval *<0-255>* | cr-retry *<0-255>* | cr-timeout *<1-255>* | [dynamic-dns on | off | hostname | password | username *<WORD>*] echo-retry *<0-255>* | echo-timeout *<0-255>* | [ipaddr-neg on | off] | ipv6-global-network-prefix *<WORD>* | ipv6-local-interface *<WORD >* | ipv6-remote interface *<WORD>* | lipaddr *<A.B.C.D>* | magic-neg on | off | mtu *<64-1500>* | [ms-direct host | guest] | nak-retry *<0-255>* | netmask *<A.B.C.D>* | password *<WORD>* | [proto-comp off | on] | ripaddr *<A.B.C.D>* | [roaming-callback off | on] | [routing listen | none | send | send-and-listen] | rpassword *<WORD>* | ruser *<WORD>* | tr-retry *<0-255>* | tr-timeout *<1-255>* | user *<WORD>* | vj-comp on | off] |
reset off | on |
rev-session-security off | on |
rlogin-client termtype *<WORD>* |
rts-toggle off | on |
rts-toggle-final-delay *<0-1000>* |
rts-toggle-inital-delay *<0-1000>* |
send-name off | on|

send-port-id off | on |
service bidir *<A.B.C.D> <1-65535> <1-65535>* |
service client-tunnel *<A.B.C.D> <1-65535>* |
service direct raw *<A.B.C.D>* | rlogin *<A.B.C.D>* | ssh *<1-65535>* | telnet *<A.B.C.D> <1-65535>* |
service dslogin |
service modbus-master |
service modbus-slave |
service ppp |
service printer |
service reverse raw [multihost on | off | tcp-port *<1-65535>* | multihost] | ssh *<1-65535>* | telnet *<1-65535>* |
service server-tunnel *<1-65535>* | [service silent raw *<1-65535>* | multihost all | backup < *A.B.C.D> <1-65535> <1-65535>* | none |
service slip |
service trueport client-initiated off *<A.B.C.D> <1-65535>* [multihost all | backup | none] signal-active off | on] | on *<1-65535>* [multihost all | backup | none] | signal-active off | on] |
service udp *<1-65535>* |
service vmodem *<1-65535>* |
sess-timer *<0-4294967>* |
session-strings delay*<0-65535>* | initiate *<WORD>* | terminate *<WORD>* |
slip lipaddr | mtu |*<A.B.C.D>* | netmask *<A.B.C.D>* | ripaddr *<A.B.C.D>* routing listen | none | send | send-and-listen | vj-comp on | off |
speed 115200 | 1200 | 1800 | 19200 | 230400 | 2400 | 28800 | 300 | 38400 | 4800 | 57600 | 600 | 9600 | custom |
ssh-client authentication [dsa on | off] | [keyboard-interactive on|off] | [rsa on | off] | [compression on | off] | [login on | off] | name *<WORD>* | password *<WORD>*|
ssh-2-cipher-list [3des aes-cbc aes-ctr aes-gcm chacha20-poly1305 rijndael-cbc] [3des aes aes-ctr aes-gcm arcfour blowfish cast chacha20-poly1305] | strict-host-key-checking on | off | termtype *<WORD>* | verbose on | off |
ssl cipher-suite option *<1-5>* | [encryption 3des | aes | aes-gcm | any | arcfour | arctwo | des min-key-size 128 | 168 | 256 | 40 | 56 | 64] | [max-key-size 128 | 168 | 256 | 40 | 56 | 64] | [key-exchange adh | any | ecdh-ecdsa | edh-dss | edh-rsa | rsa] | [hmac any | md5 | sha1 | sha256 | sha384] | [enable on | off] | [type client | server] | validation-criteria common-name *<WORD>* | country *<WORD>*| | email *<WORD>*| | locality *<WORD>*| | organisaton *<WORD>* | organisation-unit *<WORD>* | state-province *<WORD>* | [verify-peer off | on] | [version any suite-b-tls | tlsv1 | tlsv1.1 | tlsv1.2 | tlsv1.3 | use-global] |
stop-bits 1 | 2 |
telnet-client echo *<0-0x7f>* | eof *<0-0x7f>* | erase *<0-0x7f>* | escape *<0-0x7f>* | intr *<0-0x7f>* | line-mode off | on | local-echo off | on | map-cr-crlf on | off | quit *<0-0x7f>* |
termtype ansi | dumb | hp700 | ibm3151te | term1 | term2 | term3 | tvi925 | vt100 | vt320 | wyse60 |
tx-driver-control auto | rts |
udp entry *<1-4>* | both auto-learn *<A.B.C.D>* | *<X:X:X:X::X>* specific *<1-65535> <WORD>*| in any-port *<A.B.C.D>* | *<X:X:X:X::X>* | *<A.B.C.D>* | *<X:X:X:X::X>* |

none | out *<1-65535>* **|** *<A.B.C.D>* **|** *<X:X:X:X::X>* **|**
user *<WORD>* **|**
vmodem echo off | on] | [failure-string *<WORD>***] | [host** *<A.B.C.D>* **|**
*<X:X:X:X::X>***] | [init-string** *<WORD>* **| mode [auto | manual] | port** *<1-65535>* **|**
response-delay *<1-999>* **| [signals cts always-high | represent-ri] | dcd always-high |**
follow-connection] | [style numeric | verbose] | success-string *<WORD>* **| suppress**
off | on}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-line)#tty** Applies only to models with serial ports.
{**break break-interrupted	local	off	remote |**	Configure how the break signal is interpreted from the peer. Data Range: • None—The router ignores the break key completely and it is not passed through to the host. • Local—The router deals with the break locally. If the user is in a session, the break key has the same effect as a hot key. • Remote—When the break key is pressed, the router translates this into a telnet break signal which it sends to the host machine. • Break Interrupt—On some systems such as SunOS, XENIX, and AIX, a break received from the peripheral is not passed to the client properly. If the client wishes to make the break act like an interrupt key (for example, when the stty options—ignbrk and brkintr are set. Default is None
break-delay *<1-65535>* **|**	This parameter defines the delay between the termination of a a break condition and the time data is sent out the serial port. Default is 0 ms (no delay).
break-length *1-65535>* **|**	When the router receives a command from its peer to issue a break signal, this parameters defines the length of time the break condition is asserted on the serial port Default is 1000ms (1 second)

connection-method dial-in | dial-out | dial-in-out | direct-connect | ms-direct-guest | ms-direct-host |	**Dial in**—Enable this parameter if the device is remote and is dialing via a modem or ISDN TA Default is Disabled **Dial out**—Enable this parameter if the device if you want the modem to dial a number when the serial port is started. Default is Disabled
cts-toggle off | on |	Configure CTS toggle. Default is Off
cts-toggle-final-delay *<0-1000>* |	Configure CTS final delay in milliseconds. Value is 1–1000
cts-toggle-inital-delay *<0-1000>* |	Configure CTS initial delay in milliseconds. Value is 1–1000
databits 5 | 6 | 7 | 8 |	Configure the data bits for this connection. Data bit options are
data-logging off | on |	When enabled, serial data is buffered if the TCP connection is lost. When the TCP connection is re-established, the buffered serial data is sent to its destination. If using the Trueport profile, data logging is only supported in Lite mode. When the data buffer fills, incoming serial data overwrites the oldest data. The minimum data buffer size is 4K. The maximum data buffer size is 256K. **Note:** A kill line or a reboot of the router causes all buffered data to be lost. Some profile features are not compatible with the data logging feature.
dial-retries *<0-99>* |	Configure the number of times the router attempts to re-establish a connection with a remote modem. Range is 0–99 Default is 2

dial-timeouts ***<0-99>*** **|**	Configure the number of seconds the router waits to establish a connection to a remote modem. Range is 1–99 Default is 45 seconds
discard-characters-rxd-with-errors off |on |	When enabled, therouter discards characters received with a parity or framing error. Default is Disabled
echo-suppression off | on |	This parameter applies to EIA-485 half-duplex mode, all characters are echoed to the user and transmitted across the serial ports. Some EIA-485 applications require local echo to be enabled in order to monitor the loopback data to determine that line contention has occurred. If your application cannot handle loopback data, echo suppression should be enabled. Default is Off
flow both | hard | none | soft |	Configure handling of the data flow. Choose software (soft), hardware (hard), both or none. If you are using SLIP, set to Hard only. If you are using PPP set to either soft or hard (hard is recommended). If you select soft with PPP, you must set the ACCM parameter when you configure PPP for the serial port. Default is None
flowin off | on |	Configure for flowin control. Default is On
flowout off on |	Configure for flowout control. Default is On
hotkey-prefix ***<0-ff>*** **|**	Configure the prefix that a user types to lock a serial port or redraw the Menu. Data Range: • ^a l—(Lowercase L) Locks the serial port until the user unlocks it.

	• ^a l—(Lowercase L) Locks the serial port until the user unlocks it. The user is prompted for a password (any password, excluding spaces) and locks the serial port. Next, the user must retype the password to unlock the serial port. • ^r—When you switch from a session back to the Menu, the screen may not be redrawn correctly. If this happens, use this command to redraw it properly. This is always Ctrl R, regardless of the Hot Key prefix. You can use the Hotkey Prefix to lock a serial port only when the Allow Port Locking parameter is enabled. Default is hexadecimal 01 (Ctrl-a, ^a)
idle-timer ***<0-4294967>*** **|**	Configure the inactivity timer to close a connection due to inactivity. When the idle timeout expires, the router ends the connection. Range is 0–4294967 seconds (about 49 days) Default is 0 seconds so the port never times out.
initiate-connection any-char | specific-char ***<0-ff>*** **|**	Configure the initiate a connection parameter • Initiates a connection to the specified host when any data is received on the serial port. • Initiates a connection to the specified host only when the specified character is received on the serial port. Default is Disabled Default is Disabled
internet address ***<A.B.C.D>*** **|** ***<X:X:X::X>*** **|**	Configure the Internet address of this serial port.
keepalive off | on |	Configure the TCP keepalive option. This parameter is used in conjunction with the Monitor Connection Status Interval parameter found under config ***serial***.

	The connection is monitored based on the monitor connection status interval timer. This timer specifies the inactivity period before "testing" the connection. Should the end device not respond, the connection will be dropped. Note: If a network connection is accidentally dropped, it can take as long as the specified interval before reconnecting to the serial port. Default is Off
lock off | on |	When enabled, the user can lock his terminal with a password using the hotkey prefix (ctrl-a) ^a (lowercase L). The router prompts the user for a password and a confirmation. Default is Off.
map-cr-crlf off | on |	Configure to map carriage returns (CR) to carriage return line feed (CRLF). Default is off
modbus [master crlf | entry | protocol] | [slave cflf | protocol | uid-range] |	Configure Modus master/ slave parameters. Default is enabled
modem-init-string *<WORD>* |	Configure the initialization string to send to the modem.
monitor-dsr-dtr on | off |	Configure monitor for dsr-dtr signals.
motd off | on |	Configure enables/disables the message of the day. Default is Disabled
multihost entry *<1-49>* *<A.B.C.D>* | *<X:X:X::X>* port *<1-65535>* |	Adds a multihost entry to the multihost table. Range 1 to 49 Port number 1 to 65535
multisessions *<1-8>* |	Configure the number of extra network connections available on a serial port, in addition to the single session that is always available. Enabling multisessions permits multiple users to monitor the same console port. Range is 1 to 8 Default is 0
name *<WORD>* |	Configure a name.

packet-forwarding delay-between-messages ***<1-65535>*** **| [enable-end-tigger1 on | off] | [enable-end-tigger2 on | off] | [enable-eof1 on | off] | [enable-eof2 on | off] | [enable-sof1 on | off] | [enable-sof2 on | off] | end-trigger1** ***<0-0xff>*** **| end-trigger2** ***<0-0xff>*** **| eof1*****<0-0xff>*** **| eof2*****<0-0xff>*** **| force-transmit-timer** ***<1-65535>*** **| [forwarding-rule strip-trigger | trigger | trigger+1 | trigger+2] | idle-timer** ***<1-65535>*** **| [mode custom-on-frame-definition | custom-on-specific-events | minimize-latency | optimize-network-throughput | prevent-message-fragmentation] | packet-size** ***<1-1024>*** **| sof1*****<0-0xff>*** **| sof2*****<0-0xff>*** **| start-frame-transmit off | on |**	Configure packet forwarding rules. The packet is transmitting on the first criteria that is met. For example, if you set a force transmit timer of 1000 ms and a packet size of 100 bytes whichever criteria is first causes the packet to be transmitted. Default is Disabled
pages ***<1-7>*** **|**	Configure the number of video pages the terminal supports. Range: 1 to 7 Default is 5 pages
parity even | mark | none | odd | space |	Configure the parity type. Data Options are: • Even • Odd • Mark • space • none
phone-number ***<number>*** **|**	Configure the phone number to use when Dial Out is enabled.
ppp accm ***<8 hex digits>*** **| [address-comp on | off] | auth-tmout** ***<1-255>*** **| [authentication chap | pap | none] | challenge-interval** ***<0-255>*** **| cr-retry** ***<0-255>*** **| cr-timeout** ***<1-255>*** **| [dynamic-dns on | off hostname | password | username** ***<WORD>*****]**	Configure PPP parameters. **SLIP—**The IPv4 address of the router end of the SLIP link. For routing to work you must enter an IP address in this field. Choose an address that is part of the same network or subnetwork as the remote end; for example, if the remote end is address

echo-retry ***<0-255>*** **| echo-timeout** ***<0-255>*** **| [ipaddr-neg on | off] | ipv6-global-network-prefix** ***<WORD>*** **| ipv6-local-interface** ***<WORD >*** **| ipv6-remote interface** ***<WORD>*** **| lipaddr** ***<A.B.C.D>*** **| magic-neg on | off | mtu** ***<64-1500>*** **| [ms-direct host | guest] | nak-retry** ***<0-255>*** **| netmask** ***<A.B.C.D>*** **| password** ***<word>*** **| [proto-comp off | on] | ripaddr** ***<A.B.C.D>*** **| [roaming-callback off | on] | [routing listen | none | send | send-and-listen] | rpassword** ***<WORD>*** **| ruser** ***<WORD>*** **| tr-retry** ***<0-255>*** **| tr-timeout** ***<1-255>*** **| user** ***<WORD>*** **| vj-comp on | off |**	192.101.34.146, your local IP address can be 192.101.34.145. Do not use the router's (main) IP address in this field; if you do so, routing does not take place correctly. **MTU—**The Maximum Transmission Unit (MTU) parameter restricts the size of individual SLIP packets being sent by the router. Enter a value between 256 and 1500. The default value is 256. If your user is authenticated by Radius, this value is overwritten when you have set a Framed MTU in the RADIUS server.
reset off | on |	When enabled, resets the terminal definition connected to the serial port when a user logs out. Default is Disabled
rev-session-security off | on |	Configure reverse telnet session authentication.
rlogin-client termtype ***<WORD>*** **|**	Configure the terminal type for rlogin sessions.
rts-toggle off | on |	Configure RTS toggle. Default is Off
rts-toggle-final-delay ***<0-1000>*** **|**	Configure RTS final delay in milliseconds. Value is 1–1000
rts-toggle-inital-delay ***<0-1000>*** **|**	Configure RTS initial delay in milliseconds. Value is 1–1000
send-name off | on |	Configure the port name to be sent to the host when session is initiated. This is done before any other data is sent or received to/from the host. Default is Disabled
send-port-id off | on |	Configure port-id to send.

service bidir ***<A.B.C.D> <1-65535> <1-65535>*** **|**	Configure service type for bidir. Use bidir for TCP Sockets, Reverse and Silent connections. Configure the host to connect to, server port number and host port number.
service client-tunnel ***<A.B.C.D> <1-65535>*** **|**	Configure service type to client-tunnel. Configure the Enter the host to connect to and host port number.
service direct raw ***<A.B.C.D>*** **| rlogin** ***<A.B.C.D>*** **| ssh** ***<1-65535>*** **| telnet** ***<A.B.C.D> <1-65535>*** **|**	Configure service type as direct raw.
service dslogin |	Connects to the serial port in Command Line Interface (CLI) mode on this port.
service modbus-master |	Configure service type as modbus master.
service modbus-slave |	Configure service type as modbus slave.
service ppp |	Configure service type as PPP for this serial port.
service printer |	Configure service type as printer.
service reverse raw [multihost on | off | tcp-port ***<1-65535>*** **| multihost] | ssh** ***<1-65535>*** **| telnet** ***<1-65535>*** **|**	Configure parameters for a reverse raw connection.
service server-tunnel ***<1-65535>*** **|**	Configure service to server tunnel connection.
service silent raw ***<1-65535>*** **| multihost all | backup <** ***A.B.C.D> <1-65535> <1-65535>*** **| none |**	Configure service type as silent raw parameters. **Multihost**–used for connections coming from the network to the serial port for Trueport or Raw. Multihost all allows multiple hosts to connect to the serial port. **Backup**–Multihost in primary backup mode.

service silent raw ***<1-65535>*** **| multihost all | backup <** ***A.B.C.D> <1-65535> <1-65535>*** **| none |**	Configuration service type as silent raw parameters. **Multihost**–used for connections coming from the network to the serial port for Trueport or Raw. Multihost all, allows multiple hosts to connect to the serial device. **Backup**–used for connections going from the serial port to the network for Trueport or Silent Raw connections to either all the hosts in the multi-host list or a primary/ backup host.
service slip |	Configure service type as slip.
service trueport client-initiated off ***<A.B.C.D> <1-65535>*** **[multihost all | backup | none] signal-active off | on] | on** ***<1-65535>*** **[multihost all | backup | none] | signal-active off | on |**	Configure service type as trueport.
service udp ***<1-65535>*** **|**	Configure service type as udp.
service vmodem ***<1-65535>*** **|**	Configure service type as modem.
sess-timer ***<0-4294967>*** **|**	Configure session timer to forcibly close the session/connection when the Session Timeout expires. Default is 0 seconds so that the port never timeouts. Range is 0 to 294967 seconds (about 49 days)

session-strings delay*<0-65535>* | initiate *<WORD>* | terminate *<WORD>* |	Configure session string delay options. **Delay after Send—**If configured, a delay time is sent to the device. This delay is used to provide the serial device time to process the string before the session is initiated. **Initiate at Start—**If configured, this string is sent to the serial device on the power-up of the router or when a kill line command is issued on this serial port. If the "monitor DSR" or "monitor DCD" options are set, the string is also sent when the monitored signal is raised. **Range is** 0–127 alpha-numeric characters. Non printable ascii characters must be entered in this format <027>. The decimal numbers within the brackets must be 3 digits long (example 003 not 3) **Send at Terminate—**If configured, this string is sent to the serial device when the TCP session on the LAN is terminated. If multi-host is configured, this string is only sent in listen mode to the serial device when all multi-host connections are terminated.
	Range is 0–127 alpha-numeric characters. Non printable ascii characters must be entered in this format <027>. The decimal numbers within the brackets must be 3 digits long (example 003 not 3)
slip lipaddr | mtu |*<A.B.C.D>* | netmask *<A.B.C.D>* | ripaddr *<A.B.C.D>* | routing listen | none | send | send-and-listen | vj-comp on | off	Configure SLIP parameters.

speed 115200 | 1200 | 1800 | 19200 | 230400 | 2400 | 28800 | 300 | 38400 | 4800 | 57600 | 600 | 9600 | custom |	Configure the speed for this interface. • 115200 • 1200 • 1800 • 19200 • 230400 • 2400 • 28800 • 300 • 38400 • 4800 • 57600 • 600 • 9600 • custom
ssh-client authentication [dsa on | off] | [keyboard-interactive on|off] | [rsa on | off] | [compression on | off] | [login on | off] | name *<WORD>* | password *<WORD>*| [ssh-2-cipher-list 3des | aes | aes-ctr | aes-gcm | arcfour | blowfish | cast | chacha20-poly1305] | strict-host-key-checking on | off | termtype *<WORD>* | verbose on | off |	Configure SSH client parameters.
ssl [cipher-suite | enable | type | validation-criterial | verify-peer| version]|	Enables or disables SSL
enable on | off |	Enables or disables SSL
type client | server |	Select mode for SSL • client • server
verify-peer off | on |	Configure for peer validation.
version any tlsv1 | tlsv1.1 | tlsv1.2 |	Configure TLSV version.
stop-bits 1 | 2 |	Configure the stop bits. • 1 • 2

telnet-client echo *<0-0x7f>*| eof *<0-0x7f>* | erase *<0-0x7f>* | escape *<0-0x7f>* | intr *<0-0x7f>* | line-mode off | on | local-echo off | on | map-cr-crlf on | off | quit *<0-0x7f>* | termtype *<WORD>* |	**echo—**toggles between local echo of entered characters and suppressing local echo. Local echo is used for normal processing, while suppressing the echo is convenient for entering text that should not be displayed on the screen, such as passwords. This parameter can be used only when Enable Line mode is enabled. Default is Disabled **eof—**Defines the end-of-file character. When enabled Line mode is enabled, entering the EOF character as the first character on a line sends the character to the remote host. This value is in hexadecimal. Default is 4 (ASCII value ^D) This parameter can be used only when Enable Line mode is enabled. Default is Disabled **erase—**Defines the erase character. When Line mode is off, typing the erase character erases one character. This value is in hexadecimal. Default is 8 (ASCII value ^H) **escape—**Defines the escape character. Returns you to the command line mode. This value is hexadecimal. Default is 1d (ASCII value GS) **line mode—**When enabled, keyboard input is not sent to the remote host until Enter is pressed, otherwise input is sent every time a key is pressed. Default is Disabled

	local echo—Toggles between local echo of entered character and suppressing local echo Local echo is used for normal processing, while suppressing the echo is convenient for entering text that should not be display on the screen such as passwords. This parameter can only be used when Enable Line Mode is enabled. Default is Disabled **map cr to crlf—**When enabled, maps carriage return (CR) to carriage return/ line feed (CR/LF). Default is Disabled **quit**—defines the quit character. Typing the quit character closes and exits the current telnet session. This value is in hexadecimal. Default is 1c (ASCII value FS)
termtype ansi | dumb | hp700 | ibm3151te | term1 | term2 | term3 | tvi925 | vt100 | vt320 | wyse60 |	Configure a terminal type.
tx-driver-control auto | rts |	Used for RS-485 to determine what controls the Tx data envelop. auto - driver controls rts - application controls by manipulating the rts signal. Default is auto
tx-driver-control auto | rts |	Configure tx driver control to either auto or RTS.
udp entry *<1-4>* | [both | in | out | none] | auto-learn *<A.B.C.D>* | *<X:X:X:X::X>* specific *<1-65535>* *<A.B.C.D>* | *<X:X:X:X::X>*| in any-port *<A.B.C.D>* | *<X:X:X:X::X>* *<A.B.C.D>* | *<X:X:X:X::X>* | none | out *<1-65535>* *<A.B.C.D>* | *<X:X:X:X::X>* |	Configure a udp entry— For each entry you specify a different IP address range, udp port, and the direction of data flow. **both | in | out | none** The direction in which information is received or relayed: **both—**both directions **in—**LAN to serial. The router listens on the port value configured in the DS Port parameter for messages coming from the learned or configured port.

	out—Serial to LAN. The router forwards data received on the serial port to the IP address range, UDP port configured for this entry. **none—**UDP service not enabled. **auto-learn—**The router only listens to the first port that it receives a UDP packet from. Auto learn is applicable when direction is set to In or Both. **any-port**—The router receives messages from any port sending UDP packets Applicable when direction is set to In. **specific—**The port that the router listens for UDP packets, configured using the DS port parameter. ***<start_IP_address>*** The first host IP address in the range of IP addresses (for IPV4 or IPV6) that the router listens for messages from and/or send messages to. ***<end_IP_address>*** The last host IP address in the range of IP addresses (for IPV4, not required for IPV6) that the router listens for messages from and/or send messages to.
user *<WORD>* |	Configure a user name.
vmodem echo off | on] | [failure-string *<WORD>*] | [host *<A.B.C.D>* | *<X:X:X:X::X>*] | [init-string *<WORD>* | mode [auto | manual] | port *<1-65535>* | response-delay *<1-999>* | [signals cts always-high | represent-ri] | dcd always-high | follow-connection] | [style numeric | verbose] | success-string *<WORD>* | suppress off | on}	**echo—**Configure echoes to have the terminal echo back typed characters. (equivalent to ATE0/ATE1 commands). Disabled by default **failure String—**Configure the string sent to the serial device when a connection fails. If no string is entered, the string NO CARRIER is sent. **host—**Configure the target host name. **init-string—**Configure additional vmodem commands that affects how vmodem starts. The following commands are supported: ATQn, ATVn, ATEn, ATS0, AT&Z1, AT&Sn, AT&Rn, AT&Cn, AT&F, ATS2, ATS12, and ATDS1.

See *VModem Initialization Commands* in the *Router's User's Guide* for a more detailed explanation of the supported initialization commands.

mode—Configure auto mode to establish the connection when the line becomes active. You must supply the AT command or phone number to start the connection.

port—Configure the port number the target host is listening on for messages.

response-delay—The amount of time, in milliseconds, before an AT response is sent to the requesting device. The default is 250 ms.

signals dcd
Controls the state of the DCD signal.

- always-high—DCD signal always stays high
- follow-connection— DCD signal is high when an end to end connection is established and low when it is not

Since the router does not have a physical DCD pin, you need to re-map the DTR or RTS signal to DCD to have the signal present. (see next option).

signals dtr—You can specify how the DTR signal pin acts during your modem application
connection, as itself (DTR), as DCD, or as RI.

signals rts—You can specify how the RTS signal pin acts during your modem application connection, as itself (RTS), as DCD, or as RI.

style
One of the following:

- **Verbose—**Return codes (strings) are sent to the connected device.
- **Numeric—**The following characters are sent to the connected device:
- **0** OK
- 1 CONNECTED

	• **2** RING • **3** NO CARRIER • **4** ERROR • **6** INTERFACE DOWN • **7** CONNECTION REFUSED • 8 NO LISTENER **success-string** String that is sent to the serial device when a connection succeeds. If no string is entered, then the string CONNECT is sent with the connecting speed. For example CONNECT 9600 • **suppress** When enabled, the connection success/failure indication strings are sent to the connected device, otherwise, these indications are suppressed. The default is Disabled
Command Modes	Perle(config-line)#

Usage Guidelines

Use this command to configure line tty parameters.

Examples

This example disables CLI mode for tty 2.

Perle(config)#tty 2 mode disable

Related Commands

(config-line)#console

(config-line)#tty

(config-line)#vty

{**accounting exec** ***<WORD>*** **| default | authorization exec** ***<WORD>*** **| default | | exec-timeout** ***<0-35791> <0-2147483>*** **| history size** ***0-256>*** **| length** ***0-512>*** **| login** ***<WORD>*** **default | width** ***<0-512>***}

Use the no form of this command to negate a command or set to defaults.

Syntax Description	**(config-line)#vty**
accounting exec ***<WORD>*** **| default |**	Configure accounting parameters.
authorization exec ***<WORD>*** **| default**] **|**	Configure authorization parameters.

exec-timeout ***<0-35791> <0-2147483>*** **|**	Configure the time in minutes and seconds for CLI to timeout on the vty session.
history size ***<0-256>*** **|**	Configure the size of the history buffer.
length ***<0-512>*** **|**	Configure the number of lines displayed on the screen. Type 0 for no pausing at end of page.
login ***<WORD>*** **default |**	Configure login authentication parameters.
width ***<0-512>***}	Configure terminal screen width.

Command Modes

Perle>enable
Perle>config
Perle(config)#line vty
Perle(config-line)#

Usage Guidelines

Configure vty line parameters.

Examples

Configure the terminal width to 132.

```
Perleconfig)#line vty
Perle(config-line)#width 132
```

Related Commands

(config-line)#tty
(config-line)#console