



TEST REPORT

Report Reference No.....	TZ0070260405TRF01
Prepared by (+signature)	Lena Wen
Supervised by (+signature)	Allen Lai
Approved by (+signature)	Max Zhang (Authorized Officer)
Date of issue	2026-05-19
Testing Laboratory Name	Shenzhen Tongzhou Testing Co., Ltd.
Address.....	1st Floor, Building 1, Haomai High-tech Park, Huating Road 387, Dalang Street, Longhua, Shenzhen, China
Applicant's name	Dongguan Hele Electronics Co., Ltd
Address.....	Room 101, Block 1, No. 38, Daojiao Daohou Road, Daojiao Town, Dongguan City, Guangdong Province, China
Manufacturer's name	Dongguan Hele Electronics Co., Ltd
Address.....	Room 101, Block 1, No. 38, Daojiao Daohou Road, Daojiao Town, Dongguan City, Guangdong Province, China
Test specification	
Standard	MIC Notice No.88 Appendix No.43 Article 2, paragraph 1, item 19
TRF Originator	SZTZ
Master TRF	Dated 2024-08
Shenzhen Tongzhou Testing Co.,Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Tongzhou Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Tongzhou Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.	
Test item description	Bluetooth Headphone
Trade Mark	/
Model/Type reference.....	BH26H5GMA
Ratings.....	DC 3.7V by battery or DC 5V by adapter
Result.....	PASS





**** Report Revise Record ****

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	2026-05-19	Valid	Initial release





Contents

1. TEST STANDARDS AND DESCRIPTION	4
1.1. Test Standards	4
1.2. Test description	4
2. SUMMARY.....	5
2.1. General Remarks.....	5
2.2. Product Description.....	5
2.3. Wireless Function Tested in this report	5
2.4. EUT operation mode	6
2.5. Test Voltage.....	6
2.6. EUT configuration.....	7
2.7. Modifications	7
3. TEST ENVIRONMENT	8
3.1. Address of the test laboratory	8
3.2. Statement of the measurement uncertainty	8
3.3. Equipments Used during the Test.....	9
4. TEST CONDITIONS AND RESULTS	10
4.1. Antenna Power	10
4.2. Frequency Error	12
4.3. Interference Prevention Function.....	16
4.4. Occupied Bandwidth (99%).....	17
4.5. Spurious emission intensity	22
4.6. Limit of secondary radiated emissions	49
4.7. Transmission Antenna Gain (EIRP antenna power) Measurement	63
4.8. Transmission Radiation Angle Width (3db Beamwidth) Measurement.....	65
4.9. Dwell Time	66
5. TEST SETUP PHOTOS OF THE EUT	69
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	70





1. Test Standards and description

1.1. Test Standards

The tests were performed according to following standards:

Regulation: Item I of Article 49-20 and the relevant Articles of the ordinance of Regulatory Radio Equipment.

Test Method: (1)the test method suppressed on is equal to Appendix No.43 of MIC Nofication No 88

1.2. Test description

Test Item	Test Method	Result
Antenna Power	Appendix No.43 of MIC Nofication No 88 section 6	Pass
Frequency Error	Appendix No.43 of MIC Nofication No 88 section 3	Pass
Interference prevention function	Appendix No.43 of MIC Nofication No 88 section 12	Pass
99% Occupied bandwidth	Appendix No.43 of MIC Nofication No 88 section 4	Pass
Spurious Emissions Intensity	Appendix No.43 of MIC Nofication No 88 section 5	Pass
Limit of secondary radiated emissions	Appendix No.43 of MIC Nofication No 88 section 7	Pass
Dwell Time	Appendix No.43 of MIC Nofication No 88 section 13	Pass
Transmission Antenna Gain (EIRP antenna power)	Appendix No.43 of MIC Nofication No 88 section 10	Pass
Transmission Radiation Angle Width (3db Beamwidth)	Appendix No.43 of MIC Nofication No 88 section 11	N/A

N/A: means not applicable





2. Summary

2.1. General Remarks

Date of receipt of test sample : 2026-04-27
Testing commenced on : 2026-04-27
Testing concluded on : 2026-05-18

2.2. Product Description

Name of EUT	: Bluetooth Headphone
Trade Mark	: /
Model/Type reference	: BH26H5GMA
Test Model	: BH26H5GMA
Hardware Version	: V1
Software Version	: V1
Power supply	: DC 3.7V by battery or DC 5V by adapter

2.3. Wireless Function Tested in this report

Bluetooth	
Modulation	: BR ☒ GFSK:1Mbps; EDR ☒ π /4-DQPSK:2Mbps ☐ 8DPSK:3Mbps
Operation frequency	: 2402MHz~2480MHz
Channel number	: 79
Channel separation	: 1MHz
Antenna type	: PCB antenna
Antenna gain	: 3.6dBi

Operation Frequency List:

Channel No.	Frequency (GHz)	Channel No.	Frequency (GHz)	Channel No.	Frequency (GHz)
00	2.402	28	2.430	56	2.458
01	2.403	29	2.431	57	2.459
02	2.404	30	2.432	58	2.460
03	2.405	31	2.433	59	2.461
04	2.406	32	2.434	60	2.462
05	2.407	33	2.435	61	2.463
06	2.408	34	2.436	62	2.464
07	2.409	35	2.437	63	2.465
08	2.410	36	2.438	64	2.466
09	2.411	37	2.439	65	2.467
10	2.412	38	2.440	66	2.468
11	2.413	39	2.441	67	2.469
12	2.414	40	2.442	68	2.470
13	2.415	41	2.443	69	2.471





14	2.416	42	2.444	70	2.472
15	2.417	43	2.445	71	2.473
16	2.418	44	2.446	72	2.474
17	2.419	45	2.447	73	2.475
18	2.420	46	2.448	74	2.476
19	2.421	47	2.449	75	2.477
20	2.422	48	2.450	76	2.478
21	2.423	49	2.451	77	2.479
22	2.424	50	2.452	78	2.480
23	2.425	51	2.453		
24	2.426	52	2.454		
25	2.427	53	2.455		
26	2.428	54	2.456		
27	2.429	55	2.457		

2.4. EUT operation mode

The EUT has been tested under typical operating condition. The Applicant provides software(FCC_assist_1.0.4 at power level 4) to control the EUT for staying in continuous transmitting and receiving mode for testing.

2.5. Test Voltage

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	DC 3.7V	DC 4.2V	DC 3.5V





2.6. EUT configuration

(1) The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	/	Model:	/
		Input:	/
		Output:	/

(2) Protective Structure

- ☐ The exterior cover was sealed by Special screws, it can not be easily open.
- ☐ The enclosure was sealed with strong adhesive glue, it can not be easily open.
- ☐ All high-frequency section and modulation section was packaged in one IC, and shield by metal shield, it can not be easily open.
- ☐ The top and the bottom is connected with strong Buckles, it can not be easily open.
- ☒ Others: The top and the bottom is connected with strong Buckles (Multiple internal snap-fit latches), So We can not open the it easily at the normal condition. The high-frequency section and modulation section can not be capable of being opened easily



2.7. Modifications

No modifications were implemented to meet testing criteria.





3. Test Environment

3.1. Address of the test laboratory

Shenzhen Tongzhou Testing Co.,Ltd

1st Floor, Building 1, Haomai High-tech Park, Huating Road 387, Dalang Street, Longhua, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2014) and CISPR Publication 22.

3.2. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Tongzhou Testing Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Tongzhou Testing Co.,Ltd is reported:

Test Items	Measurement Uncertainty	Notes
Frequency stability	$U_c = \pm 25 \text{ Hz}$	(1)
Transmitter power conducted	$U_c = \pm 0.57 \text{ dB}$	(1)
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$	(1)
Uncertainty of RF Power Density, Conducted	$U_c = \pm 2.6 \text{ dB}$	(1)
Uncertainty of Spurious Emissions, Conducted (30MHz-1GHz)	$U_c = \pm 2.7 \text{ dB}$	(1)
Uncertainty of Spurious Emissions, Conducted (1GHz-26GHz)	$U_c = \pm 3.2 \text{ dB}$	(1)
Uncertainty of Dwell Time	$U_c = \pm 2\%$	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.





3.3. Equipments Used during the Test

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Latest Cal.	Next Cal.
1	MXA Signal Analyzer	Keysight	N9020A	MY52091623	2025-12-31	2026-12-30
2	EMI Test Receiver	R&S	ESCI	100849/003	2025-12-31	2026-12-30
3	DC power supply	Chroma	RXN-305D	62012PD02811	2025-12-31	2026-12-30
4	Power Meter	Agilent	NRVD	835843/014	2025-12-31	2026-12-30
5	Wideband Radio Communication Tester	R&S	CMW500	101855	2025-12-31	2026-12-30
6	Oscilloscope	Tektronix	TDS2024C	C044925	2025-12-31	2026-12-30
7	Signal Generator	Keysight	N5182A	MY4620709	2025-12-31	2026-12-30

Full Name of calibration company: Guangzhou Lisai Metrology & Test co., Ltd.

Calibration by the calibration agencies listed in the table correspond to paragraph 4 (ii) (c) of Article 24-2 in the Radio Law.

- ☐ (a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) or a designated calibration agency under Article 102-18-1 of the Radio Act
- ☐ (b) Calibration conducted based on the regulations of Article 135 or 144 of the Measurement Act
- ☒ (c) Calibration conducted in foreign countries, which is equivalent to calibration conducted by the NICT or a designated calibration agency under Article 102-18-1 of the Radio Act
- ☐ (d) Calibration, etc. conducted by using measuring instruments and other facilities listed at the bottom of appended table 3 of the Radio Act, which is to have been calibrated as described in (a) through (c) above






4. Test conditions and Results

4.1. Antenna Power

TEST CONFIGURATION



TEST PROCEDURE

1. EUT have transmitted continuous maximum power..
2. Frequency hopping system or combined systems of direct spread and frequency hopping
 - i. Connect the high frequency Power Meter or Spectrum Analyzer to the output of the attenuator and measure the total power (without bandwidth limitation)
 - ii. Divide the total power by the spread bandwidth to find the "average" power per MHz.
The average power per MHz is equal to the power meter value dBm + cable loss dB.
 - iii. Set the antenna power as follows:
 - Continuous waves: value in ii.

LIMIT

Item	Limits
Antenna Power Density	$\leq 3\text{mW/MHz}$ (FH form 2400~2483.5MHz)
	$\leq 10\text{mW/MHz}$ (OFDM,DS from 2400~2483.5MHz)
	$\leq 10\text{mW}$ (Other from 2400~2483.5MHz)
Antenna Power Error	$\leq 20\%$ (Base on manufacturer declare antenna power density)





TEST RESULTS

Antenna Power								
Test Condition	Test Mode	Antenna	Channel	Total Power [mW]	Spread BW [MHz]	Result (mW/MHz)	Limit (mW/MHz)	Verdict
NTNV	DH5	Ant1	Hop	37.422	71.867	0.5207	≤3	PASS
	2DH5	Ant1	Hop	19.327	71.921	0.2687	≤3	PASS
NTLV	DH5	Ant1	Hop	37.506	71.884	0.5218	≤3	PASS
	2DH5	Ant1	Hop	19.551	71.859	0.2721	≤3	PASS
NTHV	DH5	Ant1	Hop	37.079	71.843	0.5161	≤3	PASS
	2DH5	Ant1	Hop	23.450	72.005	0.3257	≤3	PASS

Tolerance								
Test Condition	Test Mode	Antenna	Channel	Power (mW/MHz)	Rated Power (mW/MHz)	Result (%)	Limit (%)	Verdict
NTNV	DH5	Ant1	Hop	0.5207	3	-82.64	≤20	PASS
	2DH5	Ant1	Hop	0.2687	3	-91.04	≤20	PASS
NTLV	DH5	Ant1	Hop	0.5218	3	-82.61	≤20	PASS
	2DH5	Ant1	Hop	0.2721	3	-90.93	≤20	PASS
NTHV	DH5	Ant1	Hop	0.5161	3	-82.80	≤20	PASS
	2DH5	Ant1	Hop	0.3257	3	-89.14	≤20	PASS

Remark:


- 1, The item was tested at 25°C and 55% humidity condition;
- 2, Result = the power meter value + cable loss





4.2. Frequency Error

TEST CONFIGURATION



TEST PROCEDURE

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: non-modulation

Spectrum Condition:

Frequency: test frequency

Span:1MHz

Rbw:10KHz

Vbw:10KHz

Sweep time:Auto

Dectector mode: Positive peak

Indication mode: max hold

LIMIT

Tolerance of frequency shall be ± 50 ppm.


TEST RESULTS


Test Condition	Test Mode	Antenna	Frequency [MHz]	Result [ppm]	Limit [ppm]	Verdict
NTNV	CW	Ant1	2402	9.99167	± 50	PASS
			2441	10.24170	± 50	PASS
			2480	10.08065	± 50	PASS
NTLV	CW	Ant1	2402	9.99167	± 50	PASS
			2441	10.24170	± 50	PASS
			2480	10.08065	± 50	PASS
NTHV	CW	Ant1	2402	9.99167	± 50	PASS
			2441	10.24170	± 50	PASS
			2480	10.08065	± 50	PASS

- Note: 1. The test results including the cable lose.
2. The item was tested at 25 °C and 55% humidity condition;
3.All condition has been testd,list the worst case in this item

Test plot as follows:











4.3. Interference Prevention Function

The device consists of the Antenna and transmitter module. Component transmitter module also can use the protocol function to protect interference come from outside.

TEST EQUIPMENT

CMW500

TEST SOFTWARE

N/A

TEST PROCEDURE

1. Open the software
2. Scan for EUT, and read the MAC address.

TEST RESULTS


The unit does meet the requirements.
MAC Address:65:F5:EA:4F:2F:9E





4.4. Occupied Bandwidth (99%)

TEST CONFIGURATION



TEST PROCEDURE

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: Center frequency in the band to be used

Span:200MHz

RBW:100MHz

VBW:100MHz

Sweep time:Auto

Dectector mode: Positive peak

Indication mode: max hold

LIMIT

Permissible value for occupied bandwidth using the FH system, a hybrid system combining DS and FH systems, or a hybrid system combining FH and OFDM systems shall be 83.5 MHz or less, while necessary bandwidth (minimum occupied bandwidth sufficient to ensure information transmission of required quality at a required transmission rate for the system used under specified conditions for a given emission type) using a system other than any of the above shall be 26 MHz or less.

TEST RESULTS


Test Condition	Test Mode	Antenna	Channel	Result [MHz]	Limit [MHz]	Verdict
NTNV	DH5	Ant1	Hop	78.994	≤83.5	PASS
	2DH5	Ant1	Hop	79.051	≤83.5	PASS
NTLV	DH5	Ant1	Hop	79.018	≤83.5	PASS
	2DH5	Ant1	Hop	79.098	≤83.5	PASS
NTHV	DH5	Ant1	Hop	79.028	≤83.5	PASS
	2DH5	Ant1	Hop	79.118	≤83.5	PASS


- Note: 1. The test results including the cable lose.
2. The item was tested at 25℃ and 55% humidity condition;
3.All condition has been testd, list the worst case in this item

TestCondition	TestMode	Antenna	Channel	Spread Bandwidth [MHz]
NTNV	DH5	Ant1	Hop	71.867
	2DH5	Ant1	Hop	71.921
NTLV	DH5	Ant1	Hop	71.884
	2DH5	Ant1	Hop	71.859
NTHV	DH5	Ant1	Hop	71.843
	2DH5	Ant1	Hop	72.005

Test plot as follows:








NTHV DH5 Ant1 Hop




NTHV 2DH5 Ant1 Hop







複製禁止

Spread Bandwidth






NTHV_DH5_Ant1_Hop




NTHV_2DH5_Ant1_Hop





4.5. Spurious emission intensity

TEST CONFIGURATION



TEST PROCEDURE

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-13GHz

RBW: 1MHz (30MHz-1GHz), 1MHz(1GHz-13GHz)

VBW: 1MHz (30MHz-1GHz), 1MHz(1GHz-13GHz)

Sweep time:Auto

Dectector mode: Positive peak

Indication mode: max hold

LIMIT

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows:

- $2,387 \text{ MHz} \leq f \leq 2,400 \text{ MHz}$ and $2,483.5 \text{ MHz} < f \leq 2,496.5 \text{ MHz}$ $25 \mu\text{W/MHz}(-16\text{dBm/MHz})$ or less
- $2,387 \text{ MHz} > f$ and $2,496.5 \text{ MHz} < f$ $2.5 \mu\text{W/MHz} (-26\text{dBm/MHz})$ or less

TEST RESULTS

Test Condition	Test Mode	Antenna	Freq (MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm/MHz]	Limit [dBm/MHz]	Result [$\mu\text{W/MHz}$]	Limit [$\mu\text{W/MHz}$]	Verdict
NTNV	DH5	Ant1	2402	30~2387	2210.81	-47.24	≤ -26	0.01888	≤ 2.5	PASS
				2387~2400	2399.01	-38.59	≤ -16	0.13836	≤ 25	PASS
				2483.5~2496.5	2485.45	-39.60	≤ -16	0.10965	≤ 25	PASS
				2496.5~13000	9602.47	-33.73	≤ -26	0.42364	≤ 2.5	PASS
			2441	30~2387	2250.00	-47.15	≤ -26	0.01928	≤ 2.5	PASS
				2387~2400	2398.96	-40.66	≤ -16	0.08590	≤ 25	PASS
				2483.5~2496.5	2496.27	-40.13	≤ -16	0.09705	≤ 25	PASS
				2496.5~13000	9758.46	-33.87	≤ -26	0.41020	≤ 2.5	PASS
			2480	30~2387	2288.89	-45.84	≤ -26	0.02606	≤ 2.5	PASS
				2387~2400	2389.15	-40.91	≤ -16	0.08110	≤ 25	PASS
				2483.5~2496.5	2484.02	-39.54	≤ -16	0.11117	≤ 25	PASS
				2496.5~13000	9914.97	-33.91	≤ -26	0.40644	≤ 2.5	PASS
	2DH5	Ant1	2402	30~2387	1965.39	-48.05	≤ -26	0.01567	≤ 2.5	PASS





				2387~2400	2399.81	-36.18	≤-16	0.2409 9	≤25	PASS
				2483.5~2496 .5	2491.88	-39.55	≤-16	0.1109 2	≤25	PASS
				2496.5~1300 0	9603.00	-33.35	≤-26	0.4623 8	≤2.5	PASS
			2441	30~2387	2250.00	-46.26	≤-26	0.0236 6	≤2.5	PASS
				2387~2400	2397.69	-40.71	≤-16	0.0849 2	≤25	PASS
				2483.5~2496 .5	2484.56	-39.76	≤-16	0.1056 8	≤25	PASS
				2496.5~1300 0	9758.98	-33.50	≤-26	0.4466 8	≤2.5	PASS
			2480	30~2387	2288.89	-46.57	≤-26	0.0220 3	≤2.5	PASS
				2387~2400	2391.19	-40.85	≤-16	0.0822 2	≤25	PASS
				2483.5~2496 .5	2489.73	-40.25	≤-16	0.0944 1	≤25	PASS
				2496.5~1300 0	9914.97	-34.32	≤-26	0.3698 3	≤2.5	PASS
NTLV	DH5	Ant1	2402	30~2387	1912.65	-47.79	≤-26	0.0166 3	≤2.5	PASS
				2387~2400	2398.85	-38.98	≤-16	0.1264 7	≤25	PASS
				2483.5~2496 .5	2489.46	-40.15	≤-16	0.0966 1	≤25	PASS
				2496.5~1300 0	9602.47	-33.91	≤-26	0.4064 4	≤2.5	PASS
			2441	30~2387	2249.70	-46.55	≤-26	0.0221 3	≤2.5	PASS
				2387~2400	2387.12	-40.84	≤-16	0.0824 1	≤25	PASS
				2483.5~2496 .5	2484.41	-39.20	≤-16	0.1202 3	≤25	PASS
				2496.5~1300 0	9758.98	-33.86	≤-26	0.4111 5	≤2.5	PASS
			2480	30~2387	2289.18	-45.69	≤-26	0.0269 8	≤2.5	PASS
				2387~2400	2390.58	-40.27	≤-16	0.0939 7	≤25	PASS
				2483.5~2496 .5	2493.00	-39.86	≤-16	0.1032 8	≤25	PASS
				2496.5~1300 0	9914.44	-33.85	≤-26	0.4121 0	≤2.5	PASS
	2DH5	Ant1	2402	30~2387	1993.97	-48.67	≤-26	0.0135 8	≤2.5	PASS
				2387~2400	2399.99	-38.09	≤-16	0.1552 4	≤25	PASS
				2483.5~2496 .5	2491.98	-40.04	≤-16	0.0990 8	≤25	PASS
				2496.5~1300 0	9602.47	-33.68	≤-26	0.4285 5	≤2.5	PASS
			2441	30~2387	2249.70	-47.23	≤-26	0.0189 2	≤2.5	PASS
				2387~2400	2388.70	-40.10	≤-16	0.0977 2	≤25	PASS
				2483.5~2496 .5	2491.15	-39.73	≤-16	0.1064 1	≤25	PASS
				2496.5~1300 0	9758.46	-33.80	≤-26	0.4168 7	≤2.5	PASS
			2480	30~2387	2288.60	-46.86	≤-26	0.0206 1	≤2.5	PASS
				2387~2400	2399.55	-40.42	≤-16	0.0907 8	≤25	PASS






NTHV	DH5	Ant1	2402	2483.5~2496.5	2496.46	-39.81	≤-16	0.10447	≤25	PASS
				2496.5~13000	9914.44	-33.97	≤-26	0.40087	≤2.5	PASS
				30~2387	1937.11	-47.49	≤-26	0.01782	≤2.5	PASS
				2387~2400	2399.98	-35.52	≤-16	0.28054	≤25	PASS
			2441	2483.5~2496.5	2494.01	-40.35	≤-16	0.09226	≤25	PASS
				2496.5~13000	9602.47	-33.44	≤-26	0.45290	≤2.5	PASS
				30~2387	2250.00	-45.91	≤-26	0.02564	≤2.5	PASS
				2387~2400	2394.11	-39.80	≤-16	0.10471	≤25	PASS
	2DH5	Ant1	2480	2483.5~2496.5	2493.61	-40.24	≤-16	0.09462	≤25	PASS
				2496.5~13000	9758.46	-33.95	≤-26	0.40272	≤2.5	PASS
				30~2387	2288.89	-47.26	≤-26	0.01879	≤2.5	PASS
				2387~2400	2387.14	-41.02	≤-16	0.07907	≤25	PASS
			2402	2483.5~2496.5	2487.16	-39.98	≤-16	0.10046	≤25	PASS
				2496.5~13000	9914.97	-33.99	≤-26	0.39902	≤2.5	PASS
				30~2387	1912.06	-47.73	≤-26	0.01687	≤2.5	PASS
				2387~2400	2399.98	-36.14	≤-16	0.24322	≤25	PASS
			2441	2483.5~2496.5	2491.05	-39.25	≤-16	0.11885	≤25	PASS
				2496.5~13000	9602.47	-33.58	≤-26	0.43853	≤2.5	PASS
				30~2387	2249.70	-47.23	≤-26	0.01892	≤2.5	PASS
				2387~2400	2393.01	-39.54	≤-16	0.11117	≤25	PASS
			2480	2483.5~2496.5	2489.16	-40.35	≤-16	0.09226	≤25	PASS
				2496.5~13000	9758.98	-34.03	≤-26	0.39537	≤2.5	PASS
				30~2387	2288.89	-46.45	≤-26	0.02265	≤2.5	PASS
				2387~2400	2389.33	-40.19	≤-16	0.09572	≤25	PASS
			2441	2483.5~2496.5	2486.42	-40.38	≤-16	0.09162	≤25	PASS
				2496.5~13000	9914.44	-33.84	≤-26	0.41305	≤2.5	PASS
				30~2387	1912.06	-47.73	≤-26	0.01687	≤2.5	PASS
				2387~2400	2399.98	-36.14	≤-16	0.24322	≤25	PASS


Note: 1. The product was tested at 25 °C and 55% humidity condition;


2. All condition has been tested, list the worst case in this item

3. SA set to from 2.4965GHz to 13GHz, plot shows from 2.497GHz to 13GHz as of SA's default format











NTNV_DH5_Ant1_2441_2496.5~13000



NTNV_DH5_Ant1_2480_30~2387



NTNV_DH5_Ant1_2480_2387~2400



