



TEST REPORT

Test item description: 2002A1 8K Dongle
Trademark(s): AIM1
Model/Type reference: 2002DGA1
Applicant's name: AndGAMER Inc.
Address: Vits TOYOTA Town B1, 5-5, Nishimachi, Toyota-shi, Aichi 471-0025, Japan
Manufacturer: AndGAMER Inc.
Address: Vits TOYOTA Town B1, 5-5, Nishimachi, Toyota-shi, Aichi 471-0025, Japan
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinh Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Jul. 09, 2026
Sample tested Date: Jul. 09, 2026 to Jul. 21, 2026
Issue Date: Jul. 21, 2026
Report No.: CTB26070911402RF01
Test Standards: MIC Public Notice 88:2004, annex 1 and annex 43
Ordinance Article 2 paragraph 1 item (19)
Test Results: PASS
Remark: This is 2.4G radio test report.
Compiled by: Reviewed by: Approved by:

Kai Chen

Kai Chen

Martin Feng

Martin FengBin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. The tested sample(s) and the sample information are provided by the applicant. The authenticity, accuracy, and completeness of the provided information are the sole responsibility of the applicant. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The result decision rules of our laboratory are based solely on the direct comparison between the actual measured values of test results and the standard limits, without considering the measurement uncertainty. "★" indicates the testing items were fulfilled by subcontracted lab. "✖" indicates the items are not in CNAS accreditation scope.

Table of Contents Page

1	TEST SUMMARY	4
1.1	VERSION	4
1.2	TEST DESCRIPTION	5
1.3	MEASUREMENT UNCERTAINTY	6
2	GENERAL INFORMATION	7
2.1	GENERAL DESCRIPTION OF EUT	7
2.2	DESCRIPTION OF TEST MODES	8
2.3	ENVIRONMENTAL CONDITIONS	9
2.4	BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5	DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	11
2.6	MEASUREMENT EQUIPMENT LIST	12
3	TEST CONDITIONS AND RESULTS	14
3.1	FREQUENCY ERROR	14
3.1.1	Limit	14
3.1.2	Test configuration	14
3.1.3	Test procedure	14
3.1.4	Test results	15
3.2	ANTENNA OUTPUT POWER AND OUTPUT POWER TOLERANCE	17
3.2.1	Limit	17
3.2.2	Test configuration	17
3.2.3	Test procedure	17
3.2.4	Test results	18
3.3	OCCUPIED BANDWIDTH AND SPREADING BANDWIDTH	20
3.3.1	Limit	20
3.3.2	Test configuration	20
3.3.3	Test procedure	20
3.3.4	Test results	21
3.4	UNWANTED EMISSION STRENGTH	23
3.4.1	Limit	23
3.4.2	Test configuration	23
3.4.3	Test procedure	23
3.4.4	Test results	24
3.5	SECONDARY RADIATED EMISSION STRENGTH	28
3.5.1	Limit	28
3.5.2	Test configuration	28

3.5.3 Test procedure	28
3.5.4 Test results	28
3.6 TRANSMISSION ANTENNA GAIN (EIRP ANTENNA POWER) MEASUREMENT	32
3.6.1 Limit	32
3.6.2 Test Procedure	32
3.6.3 Test results	32
3.7 CONSTRUCTION PROTECTION METHOD	33
3.7.1 Requirement	33
3.7.2 Confirmation method	33
3.7.3 The photos of construction protection	33
3.8 INTERFERENCE PREVENTION FUNCTION	34
3.8.1 Limit	34
3.8.2 Measuring ID code software	34
3.8.3 Test setup	34
3.8.4 Test procedure	34
3.8.5 Test result	34
4 TEST SETUP PHOTOS OF EUT	35

1 TEST SUMMARY

1VERSION

Report No.	Issue Date	Description	Approved
CTB26070911402RF01	Jul. 21, 2026	Original	Valid

1.2 Test description

Part	Rule Section	Description	Result
4.1	3	Frequency Error	Complies
4.2	4	Occupied Bandwidth (99%) and Spread-spectrum (90%)	Complies
4.3	5	Unwanted Emission Intensity	Complies
4.4	6	Antenna Power Error	Complies
4.5	7	Limitation of Collateral Emission of Receiver	Complies
4.6	8	Transmission Antenna Gain(EIRP Antenna Power)	Complies
4.7	9	Transmission Radiation Angle Width (3dB Beam width)	N/A
4.8	10	Radio Interference Prevention Capability	Complies
4.9	Note 1	Carrier Sense Capability	N/A
4.10	Note 2	Construction Protection Confirmation	Complies

Note:

1. "N/A" denotes test is not applicable in this Report.
2. "Note 1" is MIC Notice No.88 Appendix No.43.
3. "Note 2" is MIC Ordinance Regulating Radio Equipment Section 4.17 of Article 49.20.

1.3 Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Item	Uncertainty
Occupancy bandwidth	54.3kHz
Conducted output power Above 1G	0.9dB
Conducted output power below 1G	0.9dB
Power Spectral Density , Conduction	0.9dB
Conduction spurious emissions	2.0dB
Out of band emission	2.0dB
3m chamber Radiated spurious emission(30MHz-1GHz)	4.6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5.1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB
Frequency Error	54.3Hz
Adjacent channel power below 1G	2.6dB
Adjacent channel power Above 1G	2.8dB
humidity uncertainty	5.5%
Temperature uncertainty	0.63℃
frequency	1×10^{-7}

2 GENERAL INFORMATION

2.1 General description of EUT

Model/Type reference: 2002DGA1

Model Description: N/A

Hardware Version: V1.0

Software Version: V5.00

Operation Frequency: 2403-2480MHz

Max. RF output power: 1mW

Type of Modulation: GFSK

Antenna installation: PCB antenna

Antenna Gain: -1.66dBi

Ratings: DC 5V by notebook

Note: For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 Description of test modes

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2403	2	2472	3	2466	4	2458
5	2450	6	2462	7	2442	8	2468
9	2424	10	2474	11	2446	12	2464
13	2480	14	2444	15	2470	16	2452

Note: Test performed at the lowest/middle/highest frequencies selected in the list above for EUT supported while working on specified mode.

Pretest Mode	Description
Transmitting mode	Low channel: 2403MHz
	Middle channel: 2442MHz
	High channel: 2480MHz
Receiver mode	Low channel: 2403MHz

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Supply Voltage			
	supply power V	Rated module power V	Tolerance (%)
Normal	5	3.3	
+10%	5.5	3.3	0
-10%	4.5	3.3	0
Others			
Temperature (°C)		20-25	
Relative humidity		54 %.	
ATM Pressure:		1010 mbar	
Note 1: When the input voltage is reduced or increased by 10%, the regulator voltage changes of less than 1%. So the following test items are conducted in the normal voltage.			

2.4 Block diagram showing the configuration of system tested

Transmitting mode



2.5 Description of support units (conducted mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Test item description	Trademark(s)	Model/Type reference	Note
1	2002A1 8K Dongle	AIM1	2002DGA1	EUT

Note:

1. The support equipment was authorized by Declaration of Confirmation.
2. For detachable type I/O cable should be specified the length in cm in 『Length』 column.
3. “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 Measurement equipment list

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2027/5/13
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2027/5/13
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2027/5/13
4	Communication test set	R&S	CMW500	108058	V3.5.80	2027/5/13
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2027/5/13
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2027/5/13
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2027/5/13
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2027/5/13
9	2.4 GHz Filter	Shenxiang	MSF2400-24 83.5MS-1154	20181015001	/	2027/5/15
10	5 GHz Filter	Shenxiang	MSF5150-58 50MS-1155	20181015001	/	2027/5/15
11	Filter	Xingbo	XBLBQ-DZA 120	190821-1-1	/	2027/5/16
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	/	/
13	Temperature humidity chamber	Huihao	HT-HW-1000 L	/	/	2027/7/11
14	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/
15	966 chamber	C.R.T.	966	/	/	2027/6/21
16	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2027/5/14
17	Amplifier	HP	8447E	2945A02747	/	2027/5/14
18	Amplifier	Agilent	8449B	3008A01838	/	2027/5/13

19	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2027/5/16
20	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2027/5/14
21	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
22	Power Meter	KEYSIGHT	N1912AP	N/A	A.05.00	2027/5/14
23	DC power supply	Agilent	E3640A	MY53050046	/	2027/5/14

Remark: Calibration institution "GRG METROLOGY & TEST GROUP Co., LTD."

Remark: Calibration based on Article 24-2, paragraph 4 of the Radio Act method c.


3 TEST CONDITIONS AND RESULTS

3.1 Frequency error

3.1.1 Limit

Item	Limits
Frequency Error	+/-50ppm

3.1.2 Test configuration



3.1.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: non-modulation

Spectrum Condition:

Frequency: test frequency

Span: 2000 kHz

RBW: 10 kHz

VBW: 10 kHz

Sweep time: Auto

Detector mode: Positive peak


Indication mode: max hold

3.1.4 Test results


Test voltage (V)	Frequency (MHz)	Read (MHz)	Deviation (MHz)	Tolerance (ppm)	Limit (ppm)	Result
Normal Voltage	2403	2402.965	-0.035	-14.565	+/-50.00	Pass
	2442	2441.965	-0.035	-14.333		
	2480	2479.964	-0.036	-14.516		

Note: Below test graph is the worst data.


Normal Voltage



2403MHz



2442MHz




2480MHz

3.2 Antenna output power and output power tolerance

3.2.1 Limit

Item	Limits
Antenna Power Density	$\leq 3\text{mW/MHz}$ (FH form 2427 - 2470.75MHz) $\leq 10\text{mW/MHz}$ (OFDM, DS-SS, OFDM, DS-SS, OFDM, DS-SS) $\leq 10\text{mW}$ (Other from 2400~2483.5MHz)
Antenna Power Error	+20% (Base on manufacturer declare antenna power density)

3.2.2 Test configuration



3.2.3 Test procedure

Step 1:

Connect the UUT to the spectrum analyzer as TEST CONFIGURATION and use the following settings:

- Centre Frequency: The centre frequency of the channel under test.
- RBW: 1 MHz
- VBW: 1 MHz
- Span: Wide enough to cover the complete power envelope of the signal of the UUT.
- Detector: Peak
- Trace Mode: Max Hold

Step 2:

When the trace is complete, find the peak value of the power envelope and record the frequency.

Step 3:

Make the following changes to the settings of the spectrum analyzer:

- Centre Frequency: Equal to the frequency recorded in step 2.
- Span: 0 MHz
- RBW: 1 MHz
- VBW: 1 MHz
- Detector: RMS
- Trace Mode: Max Hold

3.2.4 Test results

Test voltage	Channel (MHz)	Average burst power(dBm)	Output power (mW)	Limit (mW)	Rated output power (mW)	Tolerance (%)	Limit	Result
Normal Voltage	2403	-1.481	0.711	10	1	-28.895	20%	Pass
	2442	-1.76	0.667	10	1	-33.319		
	2480	-2.091	0.618	10	1	-38.213		




3.3 Occupied bandwidth and spreading bandwidth

3.3.1 Limit

Item	Limits
Occupied Bandwidth:	FH≤83.5 MHz; OFDM≤40MHz, DS≤26 MHz; Others≤26 MHz

3.3.2 Test configuration



3.3.3 Test procedure

1. Setting of SA is following as follow:

RBW: 300 kHz

VBW: 300 kHz

Sweep time: Auto

Sweep Mode: Continuous sweep

Detect mode: Positive peak


Trace mode: Max hold

- EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 99% of occupied bandwidth to measure occupied bandwidth.
- EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 90% of occupied bandwidth to measure spread bandwidth.
- Spread Factor=Spread Bandwidth/modulation rate. The modulation rate: MR=1.375Mbps for 2.4g


3.3.4 Test results

Test voltage (V)	Channel (MHz)	Occupy 99% Bandwidth (MHz)	Limit (MHz)	Result
Normal Voltage	2403	1.8992	<26	Pass
	2442	1.9126		
	2480	1.8936		


Normal Voltage: 99% Bandwidth



2403MHz



2442MHz



2480MHz

Test voltage (V)	Channel (MHz)	Spread 90% Bandwidth(MHz)	Spread Factor	Spread Bandwidth Limit (MHz)	Spread Factor Limit	Result
Normal Voltage	2403	0.8748	N/A	>0.5	N/A	Pass
	2442	0.8736				
	2480	0.8655				

Note: N/A means not applicable to this modulation type.

Normal Voltage: 90% Bandwidth




3.4 Unwanted emission strength

3.4.1 Limit

Item	Limits
TX Spurious Emission	$\leq 2.5 \mu\text{W/MHz}$ ($30\text{MHz} \leq f \leq 1000\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($1000\text{MHz} < f \leq 2387\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2387\text{MHz} < f \leq 2400\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2483.5\text{MHz} \leq f < 2496.5\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($2496.5\text{MHz} \leq f < 12500\text{MHz}$)

3.4.2 Test configuration



3.4.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.5GHz

RBW: 100 kHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

VBW: 100 kHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

Sweep time: Auto



Detector mode: Positive peak

Indication mode: max hold


3.4.4 Test results

Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
Low	30MHz≤f≤1000MHz	765.26	-54.05	0.039	2.5	PASS
	1000MHz < f≤2387MHz	2277.43	-41.18	0.076	2.5	PASS
	2387MHz < f≤2400MHz	2399.88	-33.53	0.444	25	PASS
	2483.5MHz≤f < 2496.5MHz	2492.09	-42.25	0.060	25	PASS
	2496.5MHz≤f < 12750MHz	12165.55	-40.56	0.088	2.5	PASS
Middle	30MHz≤f≤1000MHz	841.89	-53.76	0.004	2.5	PASS
	1000MHz < f≤2387MHz	2366.19	-42.43	0.057	2.5	PASS
	2387MHz < f≤2400MHz	2398.63	-43.27	0.047	25	PASS
	2483.5MHz≤f < 2496.5MHz	2494.94	-42.81	0.052	25	PASS
	2496.5MHz≤f < 12750MHz	2527.26	-40.17	0.096	2.5	PASS
High	30MHz≤f≤1000MHz	799.21	-53.14	0.005	2.5	PASS
	1000MHz < f≤2387MHz	2056.89	-42.54	0.056	2.5	PASS
	2387MHz < f≤2400MHz	2394.73	-42.74	0.053	25	PASS
	2483.5MHz≤f < 2496.5MHz	2483.53	-34.86	0.327	25	PASS
	2496.5MHz≤f < 12750MHz	5962.18	-41.25	0.075	2.5	PASS


Test channel: 2403MHz




30MHz~1GHz



1GHz~2.387GHz





2.387GHz~2.4 GHz



2.4835GHz~2.4965GHz



2.4965GHz~12.5GHz

Test channel: 2442MHz




30MHz~1GHz

1GHz~2.387GHz





2.387GHz~2.4 GHz

2.4835GHz~2.4965GHz




2.4965GHz~12.5GHz


Test channel: 2480MHz




30MHz~1GHz



1GHz~2.387GHz



2.387GHz~2.4 GHz



2.4835GHz~2.4965GHz


2.4965GHz~12.5GHz

3.5 Secondary radiated emission strength

3.5.1 Limit

Item	Limits
RX Spurious Emission:	$\leq 4\text{nW}$ ($f < 1\text{GHz}$)
	$\leq 20\text{nW}$ ($1\text{GHz} \leq f$)

3.5.2 Test configuration



3.5.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.75GHz

RBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.75GHz)

VBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.75GHz)

Sweep time: Auto


Detector mode: Positive peak

Indication mode: max hold

3.5.4 Test results

Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
L	30MHz≤f≤1000MHz	845.77	-73.91	0.041	4	PASS
	1000MHz<f≤12750MHz	5206.5	-60.52	0.887	20	PASS

30MHz~1GHz




1GHz~12.75GHz




Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
M	30MHz≤f≤1000MHz	895.24	-74.16	0.038	4	PASS
	1000MHz<f≤12750MHz	5194.75	-57.51	1.774	20	PASS

30MHz~1GHz




1GHz~12.75GHz




Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
H	30MHz≤f≤1000MHz	868.08	-73.56	0.044	4	PASS
	1000MHz<f≤12750MHz	2668.5	-60.69	0.853	20	PASS

30MHz~1GHz



1GHz~12.75GHz



3.6 Transmission Antenna Gain(EIRP Antenna Power) Measurement

3.6.1 Limit

Ltem	Limits
EIRP Power Density	$\leq 12.14\text{dBm/MHz}$ (OFDM.DS from 2400-2483.5MHz) $\leq 12.14\text{dBm}$ (Other from 2400-2483.5MHz)
Remark: This test item will not be applied to Antenna gain is lower than 2.14dBi.	

3.6.2 Test Procedure

1. Set EUT ad measuring antenna at the same height and roughly facing aech other.
2. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of EUT height and swing it to find the maximum output of the measuring antenna. The output level at the spectrum analyzer is read sa "E".
3. Remove the EUT from the turn table and put the replacing antenna facing to measuring antenna at same height. Set the standard signal generator (SSG) at same frequency and transmit on then receive the signal.
4. Swing the replacing antenna give a maximum receiving level.
5. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of replacing antenna height and swing it to find the maximum receiving level.
6. Set SSG output power at Pt to give the equivalent output level of "E" or caluate Pt with SSG output which gives the nearest of "E" and difference ($\pm 1\text{dB}$).Record the Pt.
7. Calculate EIRP by the formula below $\text{EIRP} = G_t - L + P_t$
Gt: gain of replacing antenna (dBi)
L: feeder loss between SSG and replacing antenna
Pt: Output power of the SSG
8. If the antenna for the EUT has circular polarization. Sum of V-field and H-field will be result if measuring antenna is linear polarization.

3.6.3 Test results

N/A

3.7 Construction protection method

3.7.1 Requirement

The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily

3.7.2 Confirmation method

☐	Sealed with special screws.
☐	Plastic chassis is being welded using ultrasonic waves.
☐	Chassis is glued using a special adhesive.
☐	Metal covers are spot-fused.
☐	Cover is specially interlocked.
☐	RF and Modulation components are covered with shielding case and this shielding case is soldered.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is welded using BGA Method.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is glued at its lead with a special adhesive.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is glued with a non-transparent laminating agent.
☒	Other: All RF and modulation section packet in one IC, and IC is welded using BGA Method, and RF module is welded on the main board, end-User can't open it easily.

3.7.3 The photos of construction protection

The red circle is welding point.



3.8 Interference prevention function


3.8.1 Limit

Item	Limits
Identification code	≥ 48 bits

3.8.2 Measuring ID code software

Item	Limits
MAC IP List	MAC Scan

3.8.3 Test setup



3.8.4 Test procedure


1. In the case that the EUT has the function of automatically transmitting the identification code:
 - a. Transmit the predetermined identification codes from EUT.
 - b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code:
 - a. Transmit the predetermined identification codes from the counterpart.
 - b. Check if communication is normal.
 - c. Transmit the signals other than predetermined ID codes from the counterpart.
 - d. Check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

3.8.5 Test result

PASS

Bluetooth Device Address: 2222C88A0249

4 TEST SETUP PHOTOS OF EUT



***** END OF REPORT *****