NCC Test Report

Equipment	:	**Bluetooth speakerphone**
Model No.	:	**SP 30** **(Refer to item 1.1.1 for more details)**
Brand Name	:	**SENNHEISER**
Applicant	:	**Sennheiser Communications A/S**
Address	:	**Industriparken 27, Ballerup 2750 , Denmark**
Standard	:	**LP0002 Section 3.10.1 (2018-01-10)**
Received Date	:	**Oct. 29, 2018**
Tested Date	:	**Oct. 31 ~ Nov. 20, 2018**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Along Chen / Assistant Manager

Approved by:

Gary Chang / Manager

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 8
1.3 Test Setup Chart 8
1.4 The Equipment List 9
1.5 Test Standards 10
1.6 Measurement Uncertainty 10

2 TEST CONFIGURATION 11

2.1 Testing Condition 11
2.2 The Worst Test Modes and Channel Details 11

3 TRANSMITTER TEST RESULTS 13

3.1 Conducted Emissions 13
3.2 Unwanted Emissions into Restricted Frequency Bands 16
3.3 Unwanted Emissions into Non-Restricted Frequency Bands 32
3.4 Conducted Output Power 37
3.5 Number of Hopping Frequency 40
3.6 20dB and Occupied Bandwidth 43
3.7 Channel Separation 48
3.8 Number of Dwell Time 53

4 TEST LABORATORY INFORMATION 68

Release Record

Report No.	Version	Description	Issued Date
TR8O2901AD	Rev. 01	Initial issue	Dec. 14, 2018

Summary of Test Results

NCC Rules	Test Items	Measured	Result
2.3	Conducted Emissions	[dBuV]: 0.369MHz 30.82 (Margin -17.70dB) - AV	Pass
3.10.1.5 2.8	Radiated Emissions	[dBuV/m at 3m]: 7440.00MHz 53.07 (Margin -0.93dB) - AV	Pass
3.10.1.5	Band Edge	Meet the requirement of limit	Pass
3.10.1.2(1)(B)	Conducted Output Power	Power [dBm]: 8.47	Pass
3.10.1.6(1)(A)	Number of Hopping Channels	Meet the requirement of limit	Pass
3.10.1.6(1)(A)	Hopping Channel Separation	Meet the requirement of limit	Pass
3.10.1.6(1)(A)	Dwell Time	Meet the requirement of limit	Pass
3.10.1.4	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:
The judgement of conformity in the report is based on the measurement results excluding the measurement uncertainty.
Comments and Explanations:
None

1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
SENNHEISER	SP 30	Bluetooth speakerphone	2 microphones
	SP 40		1. 3 microphones 2. Extra button for BT connecting to another SP 40

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	**Bluetooth Mode**	**Ch. Frequency (MHz)**	**Channel Number**	**Data Rate**
2400-2483.5	BR V5.0	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR V5.0	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR V5.0	2402-2480	0-78 [79]	3 Mbps
Note 1: RF output power specifies that Maximum Peak Conducted Output Power. Note 2: Bluetooth BR uses a GFSK. Note 3: Bluetooth EDR uses a combination of π/4-DQPSK and 8DPSK.				

1.1.3 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	IFA	N/A	4.8	---

1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc, 1.3A from host 3.7Vdc from battery

1.1.5 Accessories

Accessories		
No.	**Equipment**	**Description**
1	Battery	Brand: SYNERGY Model: AHB723938PCT-01 Power Rating: 3.7Vdc, 1110mAh
2	USB cable (Undetachable)	0.75m shielded without core
3	USB-C to -A adapter	---

1.1.6 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

1.1.7 Test Tool and Duty Cycle

Test Tool	CBT Test	
Modulation Mode	**Duty Cycle Of Test Signal (%)**	**Duty Factor (dB)**
DH5	78.76%	1.04
3DH5	79.15%	1.02

1.1.8 Power Setting

Modulation Mode	Test Frequency (MHz)		
	2402	**2441**	**2480**
GFSK/1Mbps	default	default	default
π/4-DQPSK /2Mbps	default	default	default
8DPSK/3Mbps	default	default	default

1.2 Local Support Equipment List

Support Equipment List					
No.	**Equipment**	**Brand**	**Model**	**FCC ID**	**Remarks**
1	Notebook	DELL	Latitude E5470	DoC	---

1.3 Test Setup Chart

Test Setup Diagram



No.	Signal cable / Length (m)
1	USB, 0.75m shielded without core (Undetachable).

1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Nov. 08, 2018				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Receiver	R&S	ESR3	101657	Jan. 05, 2018	Jan. 04, 2019
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 05, 2018	Nov. 04, 2019
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 18, 2017	Dec. 17, 2018
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Oct. 31 ~ Nov. 01, 2018				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101498	Dec. 04, 2017	Dec. 03, 2018
Receiver	R&S	ESR3	101658	Nov. 20, 2017	Nov. 19, 2018
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 18, 2018	Jul. 17, 2019
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 20, 2017	Dec. 19, 2018
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 23, 2017	Nov. 22, 2018
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2017	Nov. 12, 2018
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 07, 2017	Dec. 06, 2018
Preamplifier	EMC	EMC02325	980225	Jul. 20, 2018	Jul. 19, 2019
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	May 09, 2018	May 08, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 07, 2017	Dec. 06, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 07, 2017	Dec. 06, 2018
LF cable 1M	EMC	EMCCFD400-NM-NM-1000	16052	Dec. 07, 2017	Dec. 06, 2018
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 07, 2017	Dec. 06, 2018
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 07, 2017	Dec. 06, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Nov. 20, 2018				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101063	Apr. 16, 2018	Apr. 15, 2019
Power Meter	Anritsu	ML2495A	1241002	Oct. 09, 2018	Oct. 08, 2019
Power Sensor	Anritsu	MA2411B	1207366	Oct. 09, 2018	Oct. 08, 2019
DC POWER SOURCE	GW INSTEK	GPC-6030D	EM892433	Oct. 25, 2018	Oct. 24, 2019
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

LP0002 Section 3.10.1 (2018-01-10)
ANSI C63.10-2013
ANSI C63.4-2014
FCC KDB 558074 D01 15.247 Meas Guidance v05

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	**Uncertainty**
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.90 dB
Radiated emission ≤ 1GHz	±3.66 dB
Radiated emission > 1GHz	±5.63 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	20°C / 60%	Alex Tsai
Radiated Emissions	03CH01-WS	24-25°C / 62-65%	Akun Chung Roger Lu
RF Conducted	TH01-WS	23°C / 66%	Felix Sung

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Mode
Conducted Emissions	8DPSK	2480	3Mbps	Tx
Radiated Emissions ≤ 1GHz	8DPSK	2480	3Mbps	Tx
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	Tx
Conducted Output Power	GFSK π/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	Tx
Number of Hopping Channels	GFSK π/4 DQPSK 8DPSK	2402~2480 2402~2480 2402~2480	1Mbps 2Mbps 3Mbps	Tx
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK π/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	Tx
Dwell Time	GFSK π/4 DQPSK 8DPSK	2441 2441 2441	1Mbps 2Mbps 3Mbps	Tx

NOTE:
1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** result was found as the worst case and was shown in this report.
2. Model SP 30 and SP 40 had been pretested and found that **SP 40** was the worst case and was selected for final testing.

Test item	Mode	Test Frequency (MHz)	Data Rate	Mode
AC Power Line Conducted Emissions	8DPSK	2480	3Mbps	Rx
Radiated Emissions	8DPSK	2480	3Mbps	Rx

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** result was found as the worst case and was shown in this report.
2. Model SP 30 and SP 40 had been pretested and found that **SP 40** was the worst case and was selected for final testing.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	8DPSK	Test Freq. (MHz)	2480
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.183	18.23	54.33	-36.10	18.18	0.03	0.02	Average
2	0.183	29.53	64.33	-34.80	29.48	0.03	0.02	QP
3	0.334	21.32	49.35	-28.03	21.27	0.03	0.02	Average
4	0.334	32.06	59.35	-27.29	32.01	0.03	0.02	QP
5*	0.369	30.82	48.52	-17.70	30.77	0.03	0.02	Average
6	0.369	39.64	58.52	-18.88	39.59	0.03	0.02	QP
7	2.225	11.26	46.00	-34.74	11.09	0.05	0.12	Average
8	2.225	25.46	56.00	-30.54	25.29	0.05	0.12	QP
9	7.407	14.79	50.00	-35.21	14.36	0.14	0.29	Average
10	7.407	30.05	60.00	-29.95	29.62	0.14	0.29	QP
11	22.180	10.75	50.00	-39.25	10.09	0.30	0.36	Average
12	22.180	19.18	60.00	-40.82	18.52	0.30	0.36	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	8DPSK	Test Freq. (MHz)	2480
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.150	23.95	56.00	-32.05	23.91	0.03	0.01	Average
2	0.150	38.18	66.00	-27.82	38.14	0.03	0.01	QP
3	0.183	18.43	54.33	-35.90	18.38	0.03	0.02	Average
4	0.183	31.39	64.33	-32.94	31.34	0.03	0.02	QP
5	0.369	28.61	48.52	-19.91	28.56	0.03	0.02	Average
6*	0.369	39.10	58.52	-19.42	39.05	0.03	0.02	QP
7	0.890	13.19	46.00	-32.81	13.12	0.04	0.03	Average
8	0.890	23.73	56.00	-32.27	23.66	0.04	0.03	QP
9	2.285	11.21	46.00	-34.79	11.03	0.06	0.12	Average
10	2.285	26.21	56.00	-29.79	26.03	0.06	0.12	QP
11	6.951	10.68	50.00	-39.32	10.27	0.13	0.28	Average
12	6.951	25.49	60.00	-34.51	25.08	0.13	0.28	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. Radiated emission above 1GHz / Peak value
   RBW=1MHz, VBW=3MHz and Peak detector
3. Radiated emission above 1GHz / Average value
   RBW=1MHz, VBW=1/T and Peak detector

3.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	8DPSK	**Test Freq. (MHz)**	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	74.62	24.66	40.00	-15.34	36.58	-11.92	Peak	---	---
2	173.56	26.55	43.50	-16.95	35.63	-9.08	Peak	---	---
3	257.95	29.35	46.00	-16.65	38.54	-9.19	Peak	---	---
4	320.03	27.20	46.00	-18.80	34.61	-7.41	Peak	---	---
5	418.97	32.82	46.00	-13.18	37.63	-4.81	Peak	---	---
6	551.86	29.75	46.00	-16.25	31.68	-1.93	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	39.70	26.12	40.00	-13.88	34.43	-8.31	Peak	---	---
2	145.43	22.58	43.50	-20.92	31.09	-8.51	Peak	---	---
3	311.30	23.53	46.00	-22.47	31.21	-7.68	Peak	---	---
4	360.77	26.00	46.00	-20.00	32.30	-6.30	Peak	---	---
5	408.30	32.78	46.00	-13.22	37.91	-5.13	Peak	---	---
6	603.27	29.32	46.00	-16.68	30.19	-0.87	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.21	54.00	-15.79	41.58	-3.37	Average	249	131
2	2390.00	49.10	74.00	-24.90	52.47	-3.37	Peak	249	131
3	4804.00	48.74	54.00	-5.26	44.85	3.89	Average	107	260
4	4804.00	52.84	74.00	-21.16	48.95	3.89	Peak	107	260
5	12010.00	42.47	54.00	-11.53	29.09	13.38	Average	100	50
6	12010.00	54.80	74.00	-19.20	41.42	13.38	Peak	100	50

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.97	54.00	-15.03	42.34	-3.37	Average	100	149
2	2390.00	49.27	74.00	-24.73	52.64	-3.37	Peak	100	149
3	4804.00	42.85	54.00	-11.15	38.96	3.89	Average	166	135
4	4804.00	49.03	74.00	-24.97	45.14	3.89	Peak	166	135
5	12010.00	42.74	54.00	-11.26	29.36	13.38	Average	100	124
6	12010.00	54.16	74.00	-19.84	40.78	13.38	Peak	100	124

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.20	54.00	-15.80	41.57	-3.37	Average	255	117
2	2390.00	48.94	74.00	-25.06	52.31	-3.37	Peak	255	117
3	2483.50	39.18	54.00	-14.82	42.14	-2.96	Average	255	117
4	2483.50	50.58	74.00	-23.42	53.54	-2.96	Peak	255	117
5	4882.00	48.87	54.00	-5.13	44.74	4.13	Average	100	260
6	4882.00	53.07	74.00	-20.93	48.94	4.13	Peak	100	260
7	7323.00	52.12	54.00	-1.88	43.47	8.65	Average	183	133
8	7323.00	58.33	74.00	-15.67	49.68	8.65	Peak	183	133

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.27	54.00	-15.73	41.64	-3.37	Average	137	161
2	2390.00	48.21	74.00	-25.79	51.58	-3.37	Peak	137	161
3	2483.50	39.27	54.00	-14.73	42.23	-2.96	Average	137	161
4	2483.50	49.88	74.00	-24.12	52.84	-2.96	Peak	137	161
5	4882.00	43.24	54.00	-10.76	39.11	4.13	Average	188	149
6	4882.00	49.07	74.00	-24.93	44.94	4.13	Peak	188	149
7	7323.00	45.33	54.00	-8.67	36.68	8.65	Average	117	182
8	7323.00	53.94	74.00	-20.06	45.29	8.65	Peak	117	182

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	38.81	54.00	-15.19	41.77	-2.96	Average	243	121
2	2483.50	51.03	74.00	-22.97	53.99	-2.96	Peak	243	121
3	4960.00	47.15	54.00	-6.85	42.78	4.37	Average	100	262
4	4960.00	51.70	74.00	-22.30	47.33	4.37	Peak	100	262
5	7440.00	53.07	54.00	-0.93	44.25	8.82	Average	179	133
6	7440.00	58.62	74.00	-15.38	49.80	8.82	Peak	179	133

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	38.93	54.00	-15.07	41.89	-2.96	Average	120	162
2	2483.50	50.91	74.00	-23.09	53.87	-2.96	Peak	120	162
3	4960.00	42.29	54.00	-11.71	37.92	4.37	Average	188	149
4	4960.00	49.14	74.00	-24.86	44.77	4.37	Peak	188	149
5	7440.00	44.21	54.00	-9.79	35.39	8.82	Average	123	186
6	7440.00	53.64	74.00	-20.36	44.82	8.82	Peak	123	186

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK

Modulation	8DPSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.87	54.00	-16.13	41.24	-3.37	Average	251	131
2	2390.00	48.77	74.00	-25.23	52.14	-3.37	Peak	251	131
3	4804.00	42.43	54.00	-11.57	38.54	3.89	Average	101	261
4	4804.00	50.77	74.00	-23.23	46.88	3.89	Peak	101	261
5	12010.00	42.02	54.00	-11.98	28.64	13.38	Average	101	55
6	12010.00	54.71	74.00	-19.29	41.33	13.38	Peak	101	55

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.21	54.00	-15.79	41.58	-3.37	Average	100	159
2	2390.00	49.12	74.00	-24.88	52.49	-3.37	Peak	100	159
3	4804.00	38.20	54.00	-15.80	34.31	3.89	Average	185	152
4	4804.00	45.87	74.00	-28.13	41.98	3.89	Peak	185	152
5	12010.00	42.07	54.00	-11.93	28.69	13.38	Average	100	129
6	12010.00	55.26	74.00	-18.74	41.88	13.38	Peak	100	129

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.78	54.00	-17.22	40.15	-3.37	Average	253	136
2	2390.00	46.99	74.00	-27.01	50.36	-3.37	Peak	253	136
3	2483.50	37.62	54.00	-16.38	40.58	-2.96	Average	253	136
4	2483.50	48.28	74.00	-25.72	51.24	-2.96	Peak	253	136
5	4882.00	43.50	54.00	-10.50	39.37	4.13	Average	100	262
6	4882.00	51.21	74.00	-22.79	47.08	4.13	Peak	100	262
7	7323.00	43.21	54.00	-10.79	34.56	8.65	Average	193	129
8	7323.00	53.39	74.00	-20.61	44.74	8.65	Peak	193	129

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.71	54.00	-17.29	40.08	-3.37	Average	100	161
2	2390.00	47.65	74.00	-26.35	51.02	-3.37	Peak	100	161
3	2483.50	37.25	54.00	-16.75	40.21	-2.96	Average	100	161
4	2483.50	48.27	74.00	-25.73	51.23	-2.96	Peak	100	161
5	4882.00	39.46	54.00	-14.54	35.33	4.13	Average	183	151
6	4882.00	46.49	74.00	-27.51	42.36	4.13	Peak	183	151
7	7323.00	39.22	54.00	-14.78	30.57	8.65	Average	115	178
8	7323.00	51.34	74.00	-22.66	42.69	8.65	Peak	115	178

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.66	54.00	-13.34	43.62	-2.96	Average	247	138
2	2483.50	54.86	74.00	-19.14	57.82	-2.96	Peak	247	138
3	4960.00	43.93	54.00	-10.07	39.56	4.37	Average	111	260
4	4960.00	51.94	74.00	-22.06	47.57	4.37	Peak	111	260
5	7440.00	43.96	54.00	-10.04	35.14	8.82	Average	195	131
6	7440.00	66.36	74.00	-7.64	57.54	8.82	Peak	195	131

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.91	54.00	-13.09	43.87	-2.96	Average	100	158
2	2483.50	55.47	74.00	-18.53	58.43	-2.96	Peak	100	158
3	4960.00	40.41	54.00	-13.59	36.04	4.37	Average	184	152
4	4960.00	47.35	74.00	-26.65	42.98	4.37	Peak	184	152
5	7440.00	39.40	54.00	-14.60	30.58	8.82	Average	100	180
6	7440.00	51.19	74.00	-22.81	42.37	8.82	Peak	100	180

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures

Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.3.3 Test Setup



3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands

BT-BR(1Mbps) **CSE NdB**

2402MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.402G	5.66	-14.34	2.10822G	-46.12	2.39998G	-42.09	2.48355G	-44.16	24.44277G	-46.96	1

BT-BR(1Mbps) **CSE NdB**

2441MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44103G	5.91	-14.09	2.12479G	-45.84	2.39924G	-45.15	2.48392G	-44.50	17.65746G	-45.39	1

BT-BR(1Mbps) **CSE NdB**

2480MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.48017G	7.26	-12.74	1.62574G	-46.07	2.39967G	-45.06	2.48427G	-44.18	16.95107G	-46.18	1

BT-EDR(2Mbps) **CSE NdB**

2402MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.402G	5.17	-14.83	2.14522G	-46.03	2.39999G	-33.10	2.484G	-43.57	17.06082G	-46.37	1

BT-EDR(2Mbps) **CSE NdB**

2441MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44096G	5.13	-14.87	2.14166G	-46.69	2.39953G	-45.53	2.48489G	-43.97	24.78893G	-45.52	1

BT-EDR(2Mbps) **CSE NdB**

2480MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.48017G	6.65	-13.35	2.09786G	-46.43	2.39963G	-44.36	2.48464G	-44.01	24.87617G	-46.08	1

BT-EDR(3Mbps) **CSE NdB**

2402MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.40201G	4.96	-15.04	2.10881G	-46.45	2.39999G	-33.34	2.4851G	-44.47	24.74108G	-46.14	1

BT-EDR(3Mbps) **CSE NdB**

2441MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44096G	5.01	-14.99	2.1239G	-45.97	2.3993G	-45.31	2.48449G	-43.71	24.89587G	-45.88	1

BT-EDR(3Mbps) **CSE NdB**

2480MHz



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.47998G	6.77	-13.23	2.15321G	-46.07	2.39962G	-45.23	2.48401G	-44.26	16.35162G	-45.59	1

BT-BR(1Mbps)

2441MHz

Hopping Ch Bandedge (Non-restricted Band)



Limit(dBm)	Ref(Hz)	Ref(dBm)	BE-l(Hz)	BE-l(dBm)	BE-h(Hz)	BE-h(dBm)
-12.26	2.47417G	7.74	2.39968G	-46.81	2.49298G	-57.16

BT-EDR(2Mbps)

2441MHz

Hopping Ch Bandedge (Non-restricted Band)



Limit(dBm)	Ref(Hz)	Ref(dBm)	BE-l(Hz)	BE-l(dBm)	BE-h(Hz)	BE-h(dBm)
-12.58	2.468005G	7.42	2.399995G	-33.56	2.483515G	-53.29

BT-EDR(3Mbps)

2441MHz

Hopping Ch Bandedge (Non-restricted Band)



Limit(dBm)	Ref(Hz)	Ref(dBm)	BE-l(Hz)	BE-l(dBm)	BE-h(Hz)	BE-h(dBm)
-12.63	2.465995G	7.37	2.399815G	-38.84	2.483515G	-54.71

3.4 Conducted Output Power

3.4.1 Limit of Conducted Output Power

☐ 1 Watt
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.

☒ 0.125 Watt
For all other frequency hopping systems in the 2400–2483.5 MHz band.

☐ 0.125 Watt
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power senor and meter is 50MHz
2 If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup

3.4.4 Test Result of Conducted Output Power

Peak Power Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	7.99	0.00630
BT-EDR(2Mbps)	8.20	0.00661
BT-EDR(3Mbps)	**8.47**	0.00703

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	4.80	6.42	21.00
2441MHz	Pass	4.80	7.03	21.00
2480MHz	Pass	4.80	7.99	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	4.80	6.92	21.00
2441MHz	Pass	4.80	7.18	21.00
2480MHz	Pass	4.80	8.20	21.00
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	4.80	7.26	21.00
2441MHz	Pass	4.80	7.48	21.00
2480MHz	Pass	4.80	**8.47**	21.00

Average Power Summary

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	7.60	0.00575
BT-EDR(2Mbps)	6.16	0.00413
BT-EDR(3Mbps)	6.17	0.00414

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	4.80	6.04	-
2441MHz	Pass	4.80	6.72	-
2480MHz	Pass	4.80	7.60	-
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	4.80	4.64	-
2441MHz	Pass	4.80	5.05	-
2480MHz	Pass	4.80	6.16	-
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	4.80	4.65	-
2441MHz	Pass	4.80	5.06	-
2480MHz	Pass	4.80	6.17	-

Note: Average power is for reference only.

3.5 Number of Hopping Frequency

3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2 Allow trace to stabilize.

3.5.3 Test Setup



3.5.4 Test Result of Number of Hopping Frequency

Summary

Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(2Mbps)	79
BT-EDR(3Mbps)	79

Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2441MHz	Pass	79	15

BT-BR(1Mbps) **Hopping Ch**

2441MHz



Hopping No	Limit
79	15

BT-EDR(2Mbps) **Hopping Ch**

2441MHz



Hopping No	Limit
79	15

BT-EDR(3Mbps) **Hopping Ch**

2441MHz



Hopping No	Limit
79	15

3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures

20dB Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Peak , Trace max hold
2 Allow trace to stabilize
3 Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Sample , Trace max hold
2 Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup



3.6.3 Test result of 20dB and Occupied Bandwidth

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	920.29k	871.925k	872KF1D	920.29k	868.307k
BT-EDR(2Mbps)	1.322M	1.201M	1M20G1D	1.301M	1.183M
BT-EDR(3Mbps)	1.319M	1.212M	1M21G1D	1.293M	1.201M

Max-N dB = Maximum 20dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 20dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	920.29k	871.925k
2441MHz	Pass	Inf	920.29k	868.307k
2480MHz	Pass	Inf	920.29k	868.307k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.322M	1.187M
2441MHz	Pass	Inf	1.301M	1.183M
2480MHz	Pass	Inf	1.319M	1.201M
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.312M	1.201M
2441MHz	Pass	Inf	1.293M	1.212M
2480MHz	Pass	Inf	1.319M	1.212M

Port X-N dB = Port **X** 20dB down bandwidth; **Port X-OBW** = Port **X** 99% occupied bandwidth;

BT-BR(1Mbps) **EBW**

2402MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
920.29k	2.401543G	2.402464G	871.925k	2.401559G	2.402431G	Inf	1

BT-BR(1Mbps) **EBW**

2441MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
920.29k	2.440543G	2.441464G	868.307k	2.440551G	2.44142G	Inf	1

BT-BR(1Mbps) **EBW**

2480MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
920.29k	2.479543G	2.480464G	868.307k	2.479551G	2.48042G	Inf	1

BT-EDR(2Mbps) **EBW**

2402MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.322M	2.40133G	2.402652G	1.187M	2.401396G	2.402582G	Inf	1

BT-EDR(2Mbps) **EBW**

2441MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.301M	2.440344G	2.441645G	1.183M	2.440399G	2.441582G	Inf	1

BT-EDR(2Mbps) **EBW**

2480MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.319M	2.479333G	2.480652G	1.201M	2.479389G	2.48059G	Inf	1

BT-EDR(3Mbps) **EBW**

2402MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.312M	2.401326G	2.402638G	1.201M	2.401381G	2.402582G	Inf	1

BT-EDR(3Mbps) **EBW**

2441MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.293M	2.44033G	2.441623G	1.212M	2.440378G	2.44159G	Inf	1

BT-EDR(3Mbps) **EBW**

2480MHz



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.319M	2.479322G	2.480641G	1.212M	2.479378G	2.48059G	Inf	1

3.7 Channel Separation

3.7.1 Limit of Channel Separation

☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

1. Set RBW=30kHz, VBW=100kHz,Sweep time = Auto, Detector=Peak Trace max hold
2 Allow trace to stabilize
3 Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup



3.7.4 Test result of Channel Separation

Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1M	1M
BT-EDR(2Mbps)	1.004348M	995.652174k
BT-EDR(3Mbps)	1.008696M	1M

Result

Mode	Result	Fl (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.401991G	2.402991G	1M	612.91314k
2441MHz	Pass	2.440991G	2.441991G	1M	612.91314k
2480MHz	Pass	2.478991G	2.479991G	1M	644.282406k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.401991G	2.402996G	1.004348M	880.452k
2441MHz	Pass	2.440996G	2.441991G	995.652174k	866.466k
2480MHz	Pass	2.478996G	2.479996G	1M	878.454k
BT-EDR(3Mbps)	-	-	-	-	-
2402MHz	Pass	2.401987G	2.402996G	1.008696M	873.792k
2441MHz	Pass	2.440991G	2.441991G	1M	861.138k
2480MHz	Pass	2.478991G	2.479996G	1.004348M	878.454k

BT-BR(1Mbps) **Channel Separation**

2.402G/2.403GHz

Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.401991G	2.402991G	1M	612.91314k

BT-BR(1Mbps) **Channel Separation**

2.441G/2.442GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440991G	2.441991G	1M	612.91314k

BT-BR(1Mbps) **Channel Separation**

2.48G/2.479GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478991G	2.479991G	1M	644.282406k

BT-EDR(2Mbps) **Channel Separation**

2.402G/2.403GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.401991G	2.402996G	1.004348M	880.452k

BT-EDR(2Mbps) **Channel Separation**

2.441G/2.442GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440996G	2.441991G	995.652174k	866.466k

BT-EDR(2Mbps) **Channel Separation**

2.48G/2.479GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478996G	2.479996G	1M	878.454k

BT-EDR(3Mbps) **Channel Separation**

2.402G/2.403GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.401987G	2.402996G	1.008696M	873.792k

BT-EDR(3Mbps) **Channel Separation**

2.441G/2.442GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.440991G	2.441991G	1M	861.138k

BT-EDR(3Mbps) **Channel Separation**

2.48G/2.479GHz



Fl(Hz)	Fh(Hz)	Ch.Space(Hz)	Limit(Hz)
2.478991G	2.479996G	1.004348M	878.454k

3.8 Number of Dwell Time

3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

1. Set RBW=300kHz,VBW=1MHz,Sweep time = 10 ms, Detector=Peak, Span=0Hz,Trace max hold
2 Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots.
   Non AFH mode
   The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.
   AFH mode
   The hopping rate is 800 hops/second so the maximum dwell time is 1/800 seconds. DH1 Packet permit maximum 800 /20/2 = 20 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 20 x 8 = 160 within 8 seconds.
4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots.
   Non AFH mode
   The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
   AFH mode
   The hopping rate is 800hops/second so the maximum dwell time is 3/800 seconds. DH3 Packet permit maximum 800 / 20 / 4 = 10 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 10 x 8 = 80 within 8 seconds.
5 The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots.
   Non AFH mode
   The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds
   AFH mode
   The hopping rate is 800 hops/second so the maximum dwell time is 5/800 seconds. DH5 Packet permit maximum 800/20 / 6 =6.667 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times6.667 x 8 = 53.33 within 8 seconds

3.8.3 Test Setup



3.8.4 Test Result of Dwell Time

Summary

Mode	Max-Dwell (s)
2.4-2.4835GHz	-
BT-BR(1Mbps)	310.530435m_DH5
BT-EDR(2Mbps)	312.075362m_DH5
BT-EDR(3Mbps)	312.075362m_DH5

Result/ Non AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	266.666667m_DH3	400m	1.666667m
2441MHz	Pass	31.6	134.492754m_DH1	400m	420.289855u
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	312.075362m_DH5	400m	2.927536m
2441MHz	Pass	31.6	271.304348m_DH3	400m	1.695652m
2441MHz	Pass	31.6	139.130435m_DH1	400m	434.782609u
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	312.075362m_DH5	400m	2.927536m
2441MHz	Pass	31.6	268.985507m_DH3	400m	1.681159m
2441MHz	Pass	31.6	134.492754m_DH1	400m	420.289855u

Result/ AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	133.3334m_DH3	400m	1.666667m
2441MHz	Pass	8	67.24638m_DH1	400m	420.289855u
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	8	156.1255m_DH5	400m	2.927536m
2441MHz	Pass	8	135.6522m_DH3	400m	1.695652m
2441MHz	Pass	8	69.56522m_DH1	400m	434.782609u
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	8	156.1255m_DH5	400m	2.927536m
2441MHz	Pass	8	134.4927m_DH3	400m	1.681159m
2441MHz	Pass	8	67.24638m_DH1	400m	420.289855u

BT-BR(1Mbps) **Dwell**

2441MHz



DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	310.530435m_[	400m	2.913043m

BT-BR(1Mbps) **Dwell**

2441MHz



DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	266.666667m_[	400m	1.666667m

BT-BR(1Mbps) **Dwell**

2441MHz



DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	134.492754m_[	400m	420.289855u

BT-EDR(2Mbps) **Dwell**

2441MHz



DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	312.075362m_[	400m	2.927536m

BT-EDR(2Mbps) **Dwell**

2441MHz



DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	271.304348m_[	400m	1.695652m

BT-EDR(2Mbps) **Dwell**

2441MHz



DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	139.130435m_[	400m	434.782609u

BT-EDR(3Mbps) **Dwell**

2441MHz



DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	312.075362m_[	400m	2.927536m

BT-EDR(3Mbps) **Dwell**

2441MHz



DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	268.985507m_[	400m	1.681159m

BT-EDR(3Mbps) **Dwell**

2441MHz



DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	134.492754m_[	400m	420.289855u

4 Receiver Test Results

4.1 Conducted Emissions

4.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

4.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

4.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.4 Test Result of Conducted Emissions

Modulation	8DPSK	Test Freq. (MHz)	2480
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.334	21.33	49.35	-28.02	21.28	0.03	0.02	Average
2	0.334	32.09	59.35	-27.26	32.04	0.03	0.02	QP
3	0.369	29.08	48.52	-19.44	29.03	0.03	0.02	Average
4*	0.369	39.53	58.52	-18.99	39.48	0.03	0.02	QP
5	1.111	14.04	46.00	-31.96	13.96	0.04	0.04	Average
6	1.111	25.31	56.00	-30.69	25.23	0.04	0.04	QP
7	2.285	11.90	46.00	-34.10	11.72	0.06	0.12	Average
8	2.285	26.95	56.00	-29.05	26.77	0.06	0.12	QP
9	7.290	12.36	50.00	-37.64	11.93	0.14	0.29	Average
10	7.290	29.79	60.00	-30.21	29.36	0.14	0.29	QP
11	22.416	10.04	50.00	-39.96	9.37	0.30	0.37	Average
12	22.416	17.79	60.00	-42.21	17.12	0.30	0.37	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation	8DPSK	Test Freq. (MHz)	2480
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.150	23.71	56.00	-32.29	23.67	0.03	0.01	Average
2	0.150	38.03	66.00	-27.97	37.99	0.03	0.01	QP
3	0.183	18.06	54.33	-36.27	18.01	0.03	0.02	Average
4	0.183	31.12	64.33	-33.21	31.07	0.03	0.02	QP
5	0.369	28.96	48.52	-19.56	28.91	0.03	0.02	Average
6*	0.369	39.36	58.52	-19.16	39.31	0.03	0.02	QP
7	2.110	15.62	46.00	-30.38	15.45	0.06	0.11	Average
8	2.110	28.63	56.00	-27.37	28.46	0.06	0.11	QP
9	6.988	10.27	50.00	-39.73	9.86	0.13	0.28	Average
10	6.988	25.44	60.00	-34.56	25.03	0.13	0.28	QP
11	24.922	10.50	50.00	-39.50	9.82	0.29	0.39	Average
12	24.922	17.55	60.00	-42.45	16.87	0.29	0.39	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

4.2 Unwanted Emissions into Restricted Frequency Bands

4.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

4.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=3MHz and RMS detector is for average measured value of radiated emission above 1GHz.

4.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



4.2.4 Receiver Radiated Unwanted Emissions

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	74.59	24.59	40.00	-15.41	36.51	-11.92	Peak	---	---
2	173.56	26.69	43.50	-16.81	35.77	-9.08	Peak	---	---
3	257.88	29.22	46.00	-16.78	38.41	-9.19	Peak	---	---
4	320.12	27.23	46.00	-18.77	34.64	-7.41	Peak	---	---
5	418.97	32.77	46.00	-13.23	37.58	-4.81	Peak	---	---
6	551.79	29.56	46.00	-16.44	31.49	-1.93	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	39.61	26.23	40.00	-13.77	34.55	-8.32	Peak	---	---
2	145.39	22.41	43.50	-21.09	30.92	-8.51	Peak	---	---
3	311.29	23.46	46.00	-22.54	31.14	-7.68	Peak	---	---
4	360.77	26.12	46.00	-19.88	32.42	-6.30	Peak	---	---
5	408.20	32.61	46.00	-13.39	37.75	-5.14	Peak	---	---
6	603.33	29.27	46.00	-16.73	30.14	-0.87	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

4.2.5 Receiver Radiated Unwanted Emissions (Above 1GHz)

Modulation	8DPSK	**Test Freq. (MHz)**	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1194.00	24.32	54.00	-29.68	33.54	-9.22	Average	100	1
2	1194.00	35.25	74.00	-38.75	44.47	-9.22	Peak	100	1
3	1760.00	26.19	54.00	-27.81	32.15	-5.96	Average	100	187
4	1760.00	36.73	74.00	-37.27	42.69	-5.96	Peak	100	187
5	2023.00	26.97	54.00	-27.03	32.00	-5.03	Average	100	58
6	2023.00	36.97	74.00	-37.03	42.00	-5.03	Peak	100	58

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1194.00	25.43	54.00	-28.57	34.65	-9.22	Average	100	48
2	1194.00	34.99	74.00	-39.01	44.21	-9.22	Peak	100	48
3	1760.00	26.45	54.00	-27.55	32.41	-5.96	Average	100	322
4	1760.00	37.93	74.00	-36.07	43.89	-5.96	Peak	100	322
5	2023.00	30.66	54.00	-23.34	35.69	-5.03	Average	100	127
6	2023.00	42.62	74.00	-31.38	47.65	-5.03	Peak	100	127

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

5 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

═END═