

TEST REPORT

Application No.: SHCR2602000358HS
Applicant: AISE Health Digital Technology (Hainan) Co., Ltd.
Address of Applicant: 323, Floor 3, Building 5, Yabulun Industrial Park, Yazhou Bay Science and Technology City, Yazhou District, Sanya City, Hainan Province
Manufacturer: Shenzhen CTB Testing Technology Co., Ltd.
Address of Manufacturer: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xingjiao Street, Bao'an District, Shenzhen, Guangdong, China
Factory: Shenzhen CTB Testing Technology Co., Ltd.
Address of Factory: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xingjiao Street, Bao'an District, Shenzhen, Guangdong, China
Equipment Under Test (EUT):
EUT Name: 2.4G Module
Model No.: DKL 1613_V.1
Standard(s) : MIC Item 19 of Article 2 Paragraph 1
Test Method: MIC Notice No.88 Appendix No.43
Date of Receipt: 2026-02-09
Date of Test: 2026-02-09 to 2026-03-31
Date of Issue: 2026-04-15

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Member of the SGS Group (SGS SA)

Revision Record			
Version	Description	Date	Remark
00	Original	2026-04-15	/

Authorized for issue by:			
Tested By	Bill Wu		
	Bill Wu/Project Engineer		
Approved By	Parlam Zhan		
	Parlam Zhan/Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	MIC Item 19 of Article 2 Paragraph 1	N/A	MIC Item 19 of Article 2 Paragraph 1	Pass
Interference prevention capability		MIC Notice No.88 Appendix No.43	MIC Item 19 of Article 2 Paragraph 1	Pass
RF accessibility		N/A	MIC Item 19 of Article 2 Paragraph 1	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Frequency Error	MIC Item 19 of Article 2 Paragraph 1	MIC Notice No.88 Appendix No.43	MIC Item 19 of Article 2 Paragraph 1	Pass
Occupied Bandwidth(99%)		MIC Notice No.88 Appendix No.43	MIC Item 19 of Article 2 Paragraph 1	Pass
Antenna Power		MIC Notice No.88 Appendix No.43	MIC Item 19 of Article 2 Paragraph 1	Pass
Spurious emission Intensity		MIC Notice No.88 Appendix No.43	MIC Item 19 of Article 2 Paragraph 1	Pass
Limit of secondary radiated emissions		MIC Notice No.88 Appendix No.43	MIC Item 19 of Article 2 Paragraph 1	Pass

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Test Conditions	6
4.3 Description of Support Units	6
4.4 Measurement Uncertainty & Decision Rule	6
4.5 Test Location	7
4.6 Test Facility	8
4.7 Deviation from Standards	8
4.8 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
6.2 Interference prevention capability	11
6.2.1 Test Requirement:	11
6.2.2 Conclusion	11
6.3 RF accessibility	12
6.3.1 Test Requirement:	12
6.3.2 Conclusion	12
7 Radio Spectrum Matter Test Results	13
7.1 Frequency Error	13
7.1.1 E.U.T. Operation	13
7.1.2 Test Mode Description	13
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data	14
7.2 Occupied Bandwidth(99%)	15
7.2.1 E.U.T. Operation	15
7.2.2 Test Mode Description	15
7.2.3 Test Setup Diagram	15
7.2.4 Measurement Procedure and Data	16
7.3 Spread spectrum Bandwidth(90%)	17
7.3.1 E.U.T. Operation	17
7.3.2 Test Mode Description	17
7.3.3 Test Setup Diagram	17
7.3.4 Measurement Procedure and Data	18
7.4 Antenna Power	19
7.4.1 E.U.T. Operation	19
7.4.2 Test Mode Description	19
7.4.3 Test Setup Diagram	19
7.4.4 Measurement Procedure and Data	20
7.5 Spurious emission Intensity	21

7.5.1	E.U.T. Operation	21
7.5.2	Test Mode Description	21
7.5.3	Test Setup Diagram	21
7.5.4	Measurement Procedure and Data	22
7.6	Limit of secondary radiated emissions	23
7.6.1	E.U.T. Operation	23
7.6.2	Test Mode Description	23
7.6.3	Test Setup Diagram	23
7.6.4	Measurement Procedure and Data	24
8	Test Setup Photo	25
9	EUT Constructional Details (EUT Photos)	25
10	Appendix	37

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 24V By adapter Adapter: Model:W&T-AD120W240500T Input:AC 100-240V,50/60Hz Output:24V 5A
Test Voltage:	AC 100V/60Hz
Operation Frequency:	2478MHz
Modulation Type:	GFSK
Number of Channels:	1
Antenna Type:	Integral Antenna
Antenna Gain:	-3.1dBi (Provided by manufacturer)

4.2 Test Conditions

EUT Power by AC 100V/60Hz

The RF unit is supplied DC 3.30V. The fluctuation of input voltage to the circuit of RF unit of test equipment is under $\pm 1\%$, when input voltage from AC 100V/60Hz to the test equipment is fluctuated by $\pm 10\%$, So, all measurement has been conducted by only rated voltage.

The measurement result of the voltage fluctuation at RF circuit when 100V/60Hz +/- 10%.	
DC Input	DC
AC 100V/60Hz	3.30V
AC 110V/60Hz	3.31V(+0.3%)
AC 90V/60Hz	3.29V(-0.3%)

5 -35.0 °C

45-85 % RH

1000 -1010 mbar

Note:

VN: Normal Voltage

TN: Normal Temperature

TL: Low Extreme Test Temperature

TH: High Extreme Test Temperature

If the EUT can be set to 3 or more different (carrier) frequencies in 1 allocated band, testing shall be performed using the Lowest, Middle and the Highest frequency (L, M and H). If there are 2 or fewer frequencies, testing shall be performed with the available frequencies.

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	LENOVO	L460	-

4.4 Measurement Uncertainty & Decision Rule

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}

2	Timeout	2s
3	Duty cycle	0.4%
4	Occupied Bandwidth	3%
5	RF conducted power	0.6dB
6	RF power density	2.9dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	5.2dB (Below 1GHz) 5.9dB (Above 1GHz)
9	Radiated Spurious emission test	4.2dB (Below 30MHz) 4.5dB (30MHz-1GHz) 5.1dB (1GHz-6GHz) 5.4dB (6GHz-18GHz)
10	Temperature test	1°C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

- **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 8617A

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date	Cal body	Certifier
Spectrum Analyzer	Agilent	N9020A	MY49100060	2025/07/30	2026/07/29	JEPSI*	(c)
Spectrum Analyzer	Keysight	N9020B	MY58100087	2025/12/17	2026/12/16	JEPSI*	(c)
Signal Generator	R&S	SMR20	101113	2025/07/30	2026/07/29	JEPSI*	(c)
Signal Generator	Agilent	N5182A	MY50143776	2025/07/30	2026/07/29	JEPSI*	(c)
Communication Tester	R&S	CMW270	101162	2025/05/22	2026/05/21	JEPSI*	(c)
Switcher+ Power Sensor	Tonscend / Keysight	JS0806 U2021XA*4	JS0806-2	2025/07/30	2026/07/29	JEPSI*	(c)
EMI Test Receiver	R&S	ESU40	100109	2025/12/17	2026/12/16	JEPSI*	(c)
High-low Temp Cabinet	Suzhou Zhihe	TL-40	20090917	2025/11/05	2026/11/04	SGS SHCAL	(c)
AC Power Stabilizer	APC	KDF-31020T-V0-F0	F317060067	2025/12/17	2026/12/16	JEPSI*	(c)
DC Power Supply	HP	6010A	SHEM222-1	2025/12/17	2026/12/16	JEPSI*	(c)

Remark:

- (a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) in Japan (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1) in JRL.
- (b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Act (Act No. 51 of 1992) .
- (c) Calibration conducted in countries except Japan, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
- (d) Calibration, etc. conducted by using measuring instruments and other equipment listed in the right column of appended table No. 3, which shall have been given any type of calibration, etc. listed above from (a) to (c).

From JRL Article 24-2, paragraph 4, Item 2

Notice:

- 1) (C) is applicable for equipment calibration above.
- 2) Calibration duration for above equipments is 1 year.

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

MIC Item 19 of Article 2 Paragraph 1

6.1.2 Conclusion

Standard requirement:

Applicable for equipment with an antenna terminal, including testing terminals. If an antenna connector is available, all relevant tests will be carried out conducted. If not, tests will be carried out in an anechoic room or with a suitable test-fixture.


EUT Details:

The antenna is Integral antenna and no consideration of replacement.

The best case gain of the Antenna is -3.1dBi.

Result:

An antenna connector is available, all relevant tests will be carried out conducted.



6.2 Interference prevention capability

6.2.1 Test Requirement:

MIC Item 19 of Article 2 Paragraph 1

Limit:

Article 2, Item (19) Notice 88 Appendix 43

The EUT shall be constructed in such a way that sensitive RF parts, (like modulation and oscillator parts) cannot be reached easily by the user. These parts shall be covered by soldered metal caps or glue or by other mechanical covers. If the covers are fixed with screws, these shall be not the common type(s) like a Phillips, but special versions like Torx, so that the user cannot open the device with common tools.

6.2.2 Conclusion

Standard Requirement:

1) Measurement system diagram as shown above and test equipment keep transmitting identification code.

2) Condition of measuring instrument

(1) Demodulator must be able to demodulate the transmitting signal emitted by test equipment and to indicate the identification code.

3) Condition of test equipment The mode of normal use.

4) Measuring operation procedure

(1) When test equipment has the function to transmit identification code automatically:

A) Transmit the predetermined identification code from test equipment.

B) Confirm the transmitted identification code by demodulator.

EUT Details:

The unit does meet the requirements (Good).

Mac Address:

BC351EF38600

6.3 RF accessibility

6.3.1 Test Requirement:

MIC Item 19 of Article 2 Paragraph 1

6.3.2 Conclusion


Standard Requirement:

The EUT shall be constructed in such a way that sensitive RF parts, (like modulation and oscillator parts) cannot be reached easily by the user. These parts shall be covered by soldered metal caps or glue or by other mechanical covers. If the covers are fixed with screws, these shall be not the common type(s) like a Phillips, but special versions like Torx, so that the user cannot open the device with common tools.

Protective Structure:

☐	1.Sealed with special screws.
☐	2.Plastic chassis is being welded using ultrasonic waves.
☐	3.Chassis is glued using a special adhesive.
☐	4.Metal covers are spot-fused.
☐	5.Cover is specially interlocked
☐	6.RF and Modulation components are covered with shielding case and this shielding case is soldered.
☐	7.Shield case is welded at RF and modulation parts, and ID-ROM is welded using the BGA Method.
☐	8.Shield case is welded at RF and modulation parts, and ID-ROM is glued at its lead with a special adhesive.
☐	9.Shield case is welded at RF and modulation parts, and ID-ROM is glued with a non-transparent laminating agent.
☒	10.RF and Modulation parts are mounted on PCB with surface mount technology, and there is no any adjustable parts on PCB or adjustable parts are not exposed.

EUT Details:



7 Radio Spectrum Matter Test Results

7.1 Frequency Error

Test Requirement	MIC Item 19 of Article 2 Paragraph 1
Test Method:	MIC Notice No.88 Appendix No.43
Limit:	Tolerance of frequency: $\pm 50E-6$


7.1.1 E.U.T. Operation

Operating Environment:					
Temperature:	22 °C	Humidity:	50 % RH	Atmospheric Pressure:	1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

1. Test Conditions:

Spectrum Analyzer is used for measurement.

2. EUT conditions:

Modulation/Spread/Hopping OFF, CW Tx

3. Spectrum Analyzer conditions:

Frequency: Test Frequency

Span 1MHz

RBW 10 kHz (Modulation OFF),

VBW 10 kHz (Modulation OFF),

Sweep Time Auto

Detector mode Positive peak

Indication mode Max hold

Alternative method:

Frequency: Test Frequency

Span 2 times channel bandwidth

RBW 100 kHz (Modulation ON),

VBW 100 kHz (Modulation ON),

Sweep Time Auto

Detector mode Positive peak

Indication mode Max hold

Please Refer to Appendix for Details

7.2 Occupied Bandwidth(99%)

Test Requirement MIC Item 19 of Article 2 Paragraph 1

Test Method: MIC Notice No.88 Appendix No.43

Limit:

FH: 83.5MHz or less

FH + DS: 83.5MHz or less

FH + OFDM: 83.5MHz or less

OFDM: 40MHz or less

DS: 26MHz or less

Others: 26MHz or less

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_ Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

1. Test Conditions:

Spectrum Analyzer is used for measurement.

2. EUT conditions:

Modulation/Spread/Hopping ON, Modulation Tx

For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.

3. Spectrum Analyzer conditions:

Frequency: Test Frequency

Span 83.5 MHz (FHSS); 40/60 MHz (OFDM; DSSS); 2-5 times OBW (Others)

RBW 1 MHz (FHSS); 300kHz (OFDM; DSSS); 3% OBW (Others)

VBW 1 MHz (FHSS); 300kHz (OFDM; DSSS); 3 times RBW (Others)

Sweep Time Auto

detector mode Positive peak

Indication mode Max hold

OBW 99%

Please Refer to Appendix for Details

7.3 Spread spectrum Bandwidth(90%)

Test Requirement MIC Item 19 of Article 2 Paragraph 1

Test Method: MIC Notice No.88 Appendix No.43

Limit:

DS, FH, FH+DS, FH+OFDM: 500kHz or more

For DS system;(Spreading bandwidth) / (Frequency corresponding to transmission rate) ≥ 5

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_ Keep the EUT in continuously transmitting mode with GFSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

1. Test Conditions:

Spectrum Analyzer is used for measurement.

2. EUT conditions:

Modulation/Spread/Hopping ON, Modulation Tx

For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.

3. Spectrum Analyzer conditions:

Frequency: Test Frequency

Span 83.5 MHz (FHSS); 40/60 MHz (OFDM; DSSS)

RBW 1 MHz (FHSS); 300kHz (OFDM; DSSS)

VBW 1 MHz (FHSS); 300kHz (OFDM; DSSS)

Sweep Time Auto

detector mode Positive peak

Indication mode Max hold

OBW 90%

Please Refer to Appendix for Details

7.4 Antenna Power

Test Requirement MIC Item 19 of Article 2 Paragraph 1

Test Method: MIC Notice No.88 Appendix No.43

Limit:

Designated value

(1) FH, FH+DS, FH+OFDM: 3mW/MHz

(used in the range of 2427 - 2470.75 MHz)

(2) OFDM, DS other than (1) 10mW/MHz

(3) Other than (1) & (2) 10mW

(4) OFDM OBW 26 - 40MHz: 5mW/MHz

Tolerance: +20%, -80%

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_ Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

1. Test Conditions:

Spectrum Analyzer is used for measurement.

2. EUT conditions:

Modulation/Spread/Hopping ON, Modulation Tx

For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.

3. Spectrum Analyzer conditions:

Frequency: Test Frequency

Span 25 MHz(FHSS); 40/60 MHz (OFDM; DSSS); Enough to capture the emission (Others)

RBW 1 MHz (FHSS; OFDM; DSSS); More than OBW (Others)

VBW 1 MHz (FHSS; OFDM; DSSS); More than RBW (Others)

Sweep Time Auto

detector mode RMS

Indication mode Max hold

Please Refer to Appendix for Details

7.5 Spurious emission Intensity

Test Requirement MIC Item 19 of Article 2 Paragraph 1

Test Method: MIC Notice No.88 Appendix No.43

Limit:

- (1) Below 2387 MHz: $2.5 \mu\text{W/MHz}$
- (2) 2387 to 2400 MHz: $25 \mu\text{W/MHz}$
- (3) 2483.5 through 2496.5 MHz: $25 \mu\text{W/MHz}$
- (4) Over 2496.5 MHz: $2.5 \mu\text{W/MHz}$

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

1. Test Conditions:

Spectrum Analyzer is used for measurement.

2. EUT conditions:

Modulation/Spread/Hopping ON, , Modulation Tx

For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.

3. Spectrum Analyzer conditions:

Step 1

All spurious are measured from 30 MHz to 13 GHz by peak mode.

Step 2

IF the value measured by Step1 is 2 dB or less, measure in average mode.

Test setup for Step 1:

Frequency: 30 MHz - 2400 MHz , 2483.5 MHz -13 GHz

RBW 1 MHz

VBW 1 MHz

Sweep Time Auto

detector mode Positive peak

Indication mode Max hold

Test setup for Step 2:

Frequency: Spurious Frequency

RBW 1 MHz

VBW 1 MHz

Sweep Time Auto

detector mode Sample

Indication mode Max hold

Please Refer to Appendix for Details

7.6 Limit of secondary radiated emissions

Test Requirement MIC Item 19 of Article 2 Paragraph 1

Test Method: MIC Notice No.88 Appendix No.43

Limit:

(1) Below 1 GHz : 4 nW or less

(2) 1 GHz and over : 20 nW or less

7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	RX mode_Keep the EUT in receiving mode.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

1. Test Conditions:

Spectrum Analyzer is used for measurement.

2. EUT conditions:

Modulation/Spread/Hopping ON

For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.

3. Spectrum Analyzer conditions:

Step 1

All spurious are measured from 30 MHz to 13 GHz by peak mode.

Step 2

IF the value measured by Step1 is 2 dB or less, measure in average mode.

Test setup for Step 1:

Frequency: 30 MHz - 2400 MHz , 2483.5 MHz -13 GHz

RBW 100 kHz (30 - 1GHz) , 1 MHz (over 1GHz)

VBW 100 kHz (30 - 1GHz) , 1 MHz (over 1GHz)

Sweep Time Auto

detector mode Positive peak

Indication mode Max hold

Test setup for Step 2:

Frequency: Spurious Frequency

Span 0 Hz

RBW 100 kHz (30 - 1GHz) , 1 MHz (over 1GHz)

VBW 100 kHz (30 - 1GHz) , 1 MHz (over 1GHz)


Sweep Time Auto

detector mode Sample


Indication mode Max hold


Please Refer to Appendix for Details



8 Test Setup Photo





9 EUT Constructional Details (EUT Photos)




































10 Appendix

1. Frequency Error


1.1 Test Result

1.1.1 Ant1

Ant1							
ENV	Mode	TX Type	Frequency (MHz)	Measured Frequency (MHz)	Tolerance (ppm)		Verdict
					Result	Limit	
NTNV	Carrier Wave	SISO	2478	2477.980	-8.07	-50 to 50	Pass

1.2 Test Graph

1.2.1 Ant1



2. Occupied Bandwidth


2.1 Test Result

2.1.1 OBW

ENV	Mode	TX Type	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Verdict
				ANT1	Limit	
NTNV	1	SISO	2478	1.306	≤ 26	Pass

2.2 Test Graph

2.2.1 OBW



3. Antenna Power


3.1 Test Result

3.1.1 Power

ENV	Mode	TX Type	Frequency (MHz)	ANT	Antenna Power (mW)		Nominal Power (mW)	Tolerance (%)		Verdict
					Measured	Limit		Measured	Limit	
NTNV	1	SISO	2478	1	2.263	≤ 10.00	2.300	-1.61	≤ 20	Pass

3.2 Test Graph

3.2.1 Power



4. Spurious Emission Intensity

4.1 Test Result


4.1.1 TxSe_NTNV

NTNV												
Mode	TX Type	Freq. (MHz)	ANT	Freq. Range		Marker					Limit (uW /MHz)	Verdict
				Start (MHz)	Stop (MHz)	Freq. (MHz)	PK Power (dBm /MHz)	PK Power (uW /MHz)	AV Power (dBm /MHz)	AV Power (uW /MHz)		
1	SISO	2478	1	30	2387	2083	-57.15	0.002	/	/	2.5	Pass
				2387	2400	2399.48	-51.03	0.008	/	/	25	Pass
				2483.5	2496.5	2483.864	-24.79	3.319	/	/	25	Pass
				2496.5	12500	2529	-44.67	0.034	/	/	2.5	Pass

Note: The measurement just shows the test results, expressed in dBm units, which has the same meaning as uW/MHz.

4.2 Test Graph

4.2.1 TxSe_NTNV



5. Secondary Radiated Emission

5.1 Test Result

5.1.1 RxSe_NTNV

NTNV												
Mode	TX Type	Freq. (MHz)	ANT	Freq. Range		Marker					Limit (nW)	Verdict
				Start (MHz)	Stop (MHz)	Freq. (MHz)	PK Power (dBm)	PK Power (nW)	AV Power (dBm)	AV Power (nW)		
1	SISO	2478	1	30	1000	890.75	-78.69	0.014	/	/	4	Pass
				1000	12500	12487.5	-60.26	0.942	/	/	20	Pass

Note: The measurement just shows the test results, expressed in dBm units, which has the same meaning as uW/MHz.

5.2 Test Graph

5.2.1 RxSe_NTNV

