



Test report No:

2640583R.701

MIC TEST REPORT

Product Name	Pirelli Vehicle Receiver - CAN
Trademark	Pirelli
Model and /or type reference	PVR-C
Applicant's name / address	Pirelli Japan KK Sumitomo Fudosan, Shibakoen First Buiding 20F, 3-8-2 Shiba, Minato-ku, Tokyo, Japan 105-0014
Test method requested, standard	Notification No. 88 Annex 43 Article 2 paragraph 1 item 19
Verdict Summary	IN COMPLIANCE
Documented by (name / position & signature)	Tim Cao / Project Manager 
Approved by (name / position & signature)	Frank He / Technical Manager 
Date of issue	2026-06-10
Report Version	V1.0
Report template No	Template_MIC-2.4G-RF-V1.0

INDEX

	page
Competences and Guarantees.....	4
General conditions	4
Environmental conditions	4
Possible test case verdicts	5
Abbreviations	5
Document History	6
Remarks and Comments.....	6
Used Equipment	7
Uncertainty	8
1 General Information.....	9
2 Description of Test Setup	10
2.1 Test Voltage.....	11
3 Verdict summary section	12
3.1 Standards.....	12
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	12
3.3 Overview of results.....	13
4 Test Results.....	14
4.1 Antenna Power Antenna Power Tolerance and E.I.R.P.....	14
4.1.1 Limit	14
4.1.2 Test Set up.....	14
4.1.3 Test Procedure.....	14
4.2 Occupied Bandwidth.....	15
4.2.1 Limit	15
4.2.2 Test Setup.....	15
4.2.3 Test Procedure.....	15
4.3 Frequency Tolerance.....	16
4.3.1 Limit	16
4.3.2 Test Setup.....	16
4.3.3 Test Procedure.....	16
4.4 Transmitter Spurious Emission.....	18
4.4.1 Limit	18
4.4.2 Test Setup.....	18
4.4.3 Test Procedure.....	18
4.5 Receiver Spurious Emission.....	20

4.5.1	Limit	20
4.5.2	Test Setup	20
4.5.3	Test Procedure	20
4.6	Interference Prevention Function Measurement	22
4.6.1	Limit	22
4.6.2	Test Setup	22
4.6.3	Test Procedure	22
5	Conforming the structure that is difficult to open	23
6	Setup photo and EUT photo	24
7	Test Result	25
Appendix A: Antenna Power Tolerance and E.I.R.P		25
Appendix B: Occupied Bandwidth		26
Appendix C: Frequency Tolerance		30
Appendix D: Transmitter Spurious Emissions		32
Appendix E: Receiver Spurious Emissions		40
Appendix F: Interference Prevention Function		44

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Apr. 22, 2026
Date (start test)	May. 06, 2026
Date (finish test)	May. 13, 2026

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	24°C
Relative Humidity air	60%

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2640583R.701	V1.0	Initial issue of report.	2026-06-10

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with Article 2 paragraph 1 item 19.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1 General Information

USED EQUIPMENT

Conducted Test/ TR8

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version	Calibration Body	Calibration Method
Wireless Connectivity Tester	R&S	CMW 270	102593	2025.05.10	2026.05.09	V 4.0.60	N/A	CEPREI	c
Wireless Connectivity Tester	R&S	CMW 270	102593	2026.05.10	2027.05.09	V 4.0.60	N/A	CEPREI	c
Temperature/Humidity Meter	RTS	RTS-8S	RF07	2025.06.17	2026.06.16	N/A	N/A	CEPREI	c

Test system

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version	Calibration Body	Calibration Method
MAX Signal Analyzer	Keysight	N9010A	MY48030494	2025.09.20	2026.09.19	A.14.03	N/A	CEPREI	c
RF Control Unit	Tonscend	JS0806-2	22G8060594	2026.01.26	2027.01.25	N/A	N/A	CEPREI	c
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	2026.03.23	2027.03.22	B.01.96	N/A	CEPREI	c
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	2026.03.23	2027.03.22	N/A	N/A	CEPREI	c
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	2025.05.10	2026.05.09	B.01.95	N/A	GRGTES T	c
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	2026.05.10	2027.05.09	B.01.95	N/A	GRGTES T	c

Calibration Method:

- (a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) in Japan (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1) in JRL.
- (b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Act (Act No. 51 of 1992).
- (c) Calibration conducted in countries except Japan, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
- (d) Calibration, etc. conducted by using measuring instruments and other equipment listed in the right column of appended table No. 3, which shall have been given any type of calibration, etc. listed above from (a) to (c).

the calibration corresponds to C described above.

From TBL Article 87, paragraph 1, item 2

Notice: Calibration duration for above equipments is 1 year.

CEPREI : China ceprei laboratory calibration & testing centre.

DEKRA : DEKRA Testing and Certification (Suzhou) Co., Ltd.

GRGTES T: Grg Metrology&Test (WuXi) Co.,Ltd.

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test item	Uncertainty
Antenna Power Antenna Power Tolerance and E.I.R.P	± 1.3 dB
Occupied Bandwidth	± 0.15 kHz
Frequency Tolerance	± 0.15 kHz
Transmitter Spurious Emissions	± 1.3 dB
Receiver Spurious Emissions	± 1.3 dB

1 GENERAL INFORMATION

Product Name..... :	Pirelli Vehicle Receiver - CAN
Model No. :	PVR-C
Trademark :	Pirelli
HW Version..... :	1.0
SW Version..... :	x.y
Manufacturer..... :	Pirelli Tyre S.p.A.
Manufacturer address	Viale Piero e Alberto Pirelli 25 - 20126 Milano - Italy
Power Supply..... :	12Vdc
Test SN..... :	000017
Wireless specification..... :	Bluetooth BLE
Operating frequency range(s)	2402~2480MHz
Type of Modulation..... :	GFSK
PHYs :	LE 1M
Data Rate :	1Mbit/s
Number of channels	40
Antenna Type :	External Antenna
Antenna Gain..... :	2.5dBi
Declared Power	2 mW

Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

2 DESCRIPTION OF TEST SETUP

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) Notebook	Think pad x220	Lenovo	Adapter
(2) USB Control Cable	N/A	N/A	N/A
N/A	N/A	N/A	N/A
software	Type / Version	Manufacturer	Supplied by
PCAN-View	N/A		

Accessories Information	Cable		
	Length used during test [m]	Attached during test	Shielded
(2)USB Control Cable	1	☒	☒

2.1 Test Voltage

Power supply voltage fluctuation test

Voltage Fluctuation Test	Normal Voltage	High Voltage Normal Voltage +10% of	Low Voltage Normal Voltage -10% of
Input To EUT	DC12V	DC 13.2V	DC 10.8V
Test Result	3.32V	3.32V	3.32V
Voltage Variation	Reference	0%	0%

Note:

Changing the supply voltage of the EUT will not change the voltage of the RF module.

During the input supply voltage to the EUT from the external power source is varied by +/- 10%, if output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/-1%. Exempt extremely high and low supply voltage condition test, EUT only operated in normal voltage to test all regulations.

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
Article 2 paragraph 1 item (19)	2023	2.4GHz Band Advanced Low Power Data Communication System
Notification No. 88 Annex 43.	2004	Test methods for radio equipment listed in Article 2, Paragraph 1, Item 19 and Item 19-2-2 of Certification Ordinance
--	--	--

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

No deviation

3.3 Overview of results

Test Item - MIC notification 88 Annex 43				
Performed Test Item	Normative References	Test Performed	Verdict	Remark
Antenna Power Tolerance and E.I.R.P	MIC notification 88 Annex 43 section 6	Yes	PASS	Test data please refer to Appendix A
Occupied Bandwidth	MIC Notification 88 Annex 43 section 4	Yes	PASS	Test data please refer to Appendix B
Frequency Tolerance	MIC Notification 88 Annex 43 section 3	Yes	PASS	Test data please refer to Appendix C
Transmitter Spurious Emissions	MIC Notification 88 Annex 43 section 7	Yes	PASS	Test data please refer to Appendix D
Receiver Spurious Emissions	MIC Notification 88 Annex 43 section 7	Yes	PASS	Test data please refer to Appendix E
Interference Prevention Function	MIC Notification 88 Annex 43 section 12	Yes	PASS	Test data please refer to Appendix F

4 TEST RESULTS

4.1 Antenna Power Antenna Power Tolerance and E.I.R.P

VERDICT: PASS

4.1.1 Limit

Standard Article 2 paragraph 1 item 19


Output Power

- | | |
|-------------------------------------|--|
| ☒ | Max EIRP $\leq 12.14\text{dBm}$ |
| ☒ | Antenna power $\leq 10\text{mW}$ |
| ☐ | Max antenna gain = Max EIRP - declared power Max declared conductive power |
| ☐ | Antenna power = Max EIRP - Antenna gain |

Output Power Tolerance

- | | |
|-------------------------------------|------------------------------|
| ☒ | Output Power Tolerance: +20% |
|-------------------------------------|------------------------------|

4.1.2 Test Set up



4.1.3 Test Procedure

References Rule

- | | |
|-------------------------------------|-------------------------------------|
| ☒ | Method 1: MIC Notice 88 Appendix 43 |
|-------------------------------------|-------------------------------------|


Step 1

- (a) Connect a high-frequency power meter to the output of the dummy load (attenuator) and measure the total power.
- (b) Antenna power shall be as follows.
- Value of a for continuous wave
 - Burst wave The average power in the burst is calculated from the value of (a) and the transmission time rate.

4.2 Occupied Bandwidth**VERDICT: PASS****4.2.1 Limit****Standard**

Article 2 paragraph 1 item 19

- | | |
|-------------------------------------|--|
| ☐ | Channel Power of DSSS, the limit should $\leq 26\text{MHz}$ |
| ☐ | Channel Power of FHSS, the limit should $\leq 83.5\text{MHz}$ |
| ☐ | Channel Power of OFDM |
| ☐ | Nominal Bandwidth=20MHz, the limit should $\leq 26\text{MHz}$ |
| ☐ | Nominal Bandwidth=40MHz, the limit should $\leq 38\text{MHz}$ |
| ☒ | Channel Power of other situation, the limit should $\leq 26\text{MHz}$ |

4.2.2 Test Setup**4.2.3 Test Procedure****References Rule**

- | | |
|-------------------------------------|-------------------------------|
| ☒ | Notification No. 88 Annex 43. |
|-------------------------------------|-------------------------------|

Step 1


1. Set spectrum analyzer to following setting:

- Center frequency: Equal to center frequency of test signal
- Span: Between 2 times and 3.5 times the limited bandwidth.
- RBW: Less than 3% of the limited bandwidth
- VBW: Equal to RBW
- Sweep mode: Continuous sweep
- Detect mode: Positive peak
- Trace mode: Max hold

2. The integrated 99% power bandwidth function may be used to measure the spread bandwidth.

4.3 Frequency Tolerance**VERDICT: PASS****4.3.1 Limit****Standard**

Article 2 paragraph 1 item 19

 $\leq \pm 50$ ppm**4.3.2 Test Setup****4.3.3 Test Procedure****References Rule**☒ Notification No. 88 Annex 43.**Step 1**☒ Unmodulation Wave (CW signal)

1. Set spectrum analyzer as following setting:

Center frequency: Equal to center frequency of signal under test

Span: Widest enough to see the entire waveform

RBW: 10kHz

VBW: 10kHz

Detect mode: Positive Peak

Trace mode: Max hold

Sweep time: Auto

2. Use the peak search function to find the highest level frequency and record data.

☐ Modulation Wave

1. Set spectrum analyzer to following setting:

Center frequency: Equal to center frequency of signal under test

Span: Widest enough to see the entire waveform

RBW: 100kHz

VBW: 100kHz

Detect mode: Positive Peak

Trace mode: Max hold


Sweep time: Auto

2. Use the peak search function to find the highest level frequency, record maximum level.
3. Setting display line to 10dB lower than the maximum level.
4. Mark the lowest and highest frequency where the test signal intersect the display line, record the frequency F_L , F_H .
5. The Center frequency of test $F_C = (F_L + F_H)/2$

4.4 Transmitter Spurious Emission**VERDICT: PASS****4.4.1 Limit****Standard**

Article 2 paragraph 1 item 19

- | | |
|-------------------------------------|--|
| ☒ | Frequency between 30 - 2387 MHz, $\leq 2.5\mu\text{W}/\text{MHz}$ |
| ☒ | Frequency between 2387 - 2400 MHz, $\leq 25\mu\text{W}/\text{MHz}$ |
| ☒ | Frequency between 2483.5 - 2496.5 MHz, $\leq 25\mu\text{W}/\text{MHz}$ |
| ☒ | Frequency between 2496.5 - 12500, $\leq 2.5\mu\text{W}/\text{MHz}$ |

4.4.2 Test Setup**4.4.3 Test Procedure**

References Rule

- | | |
|-------------------------------------|-------------------------------|
| ☒ | Notification No. 88 Annex 43. |
|-------------------------------------|-------------------------------|

Step 1

1. Set the spectrum analyzer as follows when searching.

Sweep frequency width	30MHz to 5 times the carrier frequency
Resolution bandwidth	100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz
Video bandwidth	Same as resolution bandwidth
Sweep time	Minimum time for guaranteed measurement accuracy
Sweep mode	Single sweep
Detection mode	positive peak

2. Set the spectrum analyzer for secondary emission measurement as follows.


Center frequency	Secondary emission frequency
Sweep frequency width	0Hz
Resolution bandwidth	100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz
Video bandwidth	Same as resolution bandwidth
Sweep time	Minimum time for guaranteed measurement accuracy
Sweep mode	Single sweep
Detection mode	sample

4.5 Receiver Spurious Emission**VERDICT: PASS****4.5.1 Limit****Standard**

Article 2 paragraph 1 item 19

<= 4nW for 30 - 1000 MHz

<= 20nW for 1000 - 12500 MHz

4.5.2 Test Setup**4.5.3 Test Procedure**

References Rule

☒ Notification No. 88 Annex 43.

Step 1

1. Set the spectrum analyzer as follows when searching.

Sweep frequency width 30MHz to 5 times the carrier frequency

Resolution bandwidth 100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz

Video bandwidth Same as resolution bandwidth

Sweep time Minimum time for guaranteed measurement accuracy

Sweep mode Single sweep

Detection mode positive peak

2. Set the spectrum analyzer for secondary emission measurement as follows.


Center frequency Secondary emission frequency

Sweep frequency width	0Hz
Resolution bandwidth	100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz
Video bandwidth	Same as resolution bandwidth
Sweep time	Minimum time for guaranteed measurement accuracy
Sweep mode	Single sweep
Detection mode	sample

4.6 Interference Prevention Function Measurement**VERDICT: PASS****4.6.1 Limit****Standard**

Article 2 Paragraph 1 of item 19

The one automatically to transmit and to receive identification code with the wireless equipment of the wireless station used in the same premises.

4.6.2 Test Setup**4.6.3 Test Procedure**

References Rule

☒ Notification No. 88 Annex 43.

Step 1

1. Establish communication between EUT and auxiliary equipment, auxiliary must have an ability to parse and display the identifier code.
2. When the test equipment has the function of automatically transmitting the identification code.
 - A. The test equipment sends the identification code specified in the equipment rules.
 - B. Check the identification code sent by the demodulator.
3. When the test equipment has the function of automatically receiving the identification code.
 - A. The opposite device transmits the identification code specified in the device rules.
 - B. Verify that a dedicated fixture is used to communicate with the test equipment.
 - C. Send a code from the counter that differs from the identification code specified in the equipment rules.
 - D. Verify that the test equipment stops transmitting or displays a different ID.
4. If the encoding specified in the device rules is the same as the demodulated encoding, recorded as "Good", otherwise record as "No".

5 CONFORMING THE STRUCTURE THAT IS DIFFICULT TO OPEN

The Radio Equipment:	
☐	Use Special Screw
☐	Metal Shielding is Soldered
☐	Use Ball Grid Array (BGA)
☒	RF module/Chip Pins > 20
☒	RF module/Chip Pins distance < 1.5 mm

The high-frequency section and modulation section (except for the antenna system) are not capable of being opened easily.

6 SETUP PHOTO AND EUT PHOTO

Remark: The test setup photo and EUT Photo please see appendix.

7 TEST RESULT

APPENDIX A: ANTENNA POWER TOLERANCE AND E.I.R.P

Output Power And E.I.R.P

Mode	Frequency (MHz)	Output Power		EIRP (dBm)	Limit		Pass/Fail
		(dBm)	(mW)		Output Power (mW)	EIRP (dBm)	
BLE1M	2402	2.75	1.88	5.25	10.00	12.14	Pass
	2440	3.07	2.03	5.57	10.00	12.14	Pass
	2480	2.65	1.84	5.15	10.00	12.14	Pass


Output Power Tolerance


Mode	Frequency (MHz)	Declared Power	Output Power	Tolerance (%)	Limit	Pass/Fail
		(mW)	(mW)		Tolerance (%)	
BLE1M	2402	2	1.88	-5.82%	+20	Pass
	2440	2	2.03	1.38%	+20	Pass
	2480	2	1.84	-7.96%	+20	Pass

APPENDIX B: OCCUPIED BANDWIDTH


Test Result

TestCondition	TestMode	Antenna	Freq(MHz)	Result [MHz]	Limit [MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	1.266	≤26	PASS
NTNV	BLE_1M	Ant1	2440	1.278	≤26	PASS
NTNV	BLE_1M	Ant1	2480	1.282	≤26	PASS






NTNV-BLE_1M-Ant1-2440-PASS




NTNV-BLE_1M-Ant1-2480-PASS


TestCondition	TestMode	Antenna	Freq(MHz)	Result [MHz]	Limit [MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	0.843	≥0.5	PASS
NTNV	BLE_1M	Ant1	2440	0.840	≥0.5	PASS
NTNV	BLE_1M	Ant1	2480	0.843	≥0.5	PASS



NTNV-BLE_1M-Ant1-2402-PASS




NTNV-BLE_1M-Ant1-2440-PASS




APPENDIX C: FREQUENCY TOLERANCE


TestCondition	TestMode	Antenna	Freq(MHz)	CenterFreq [MHz]	Result[ppm]	Limit[ppm]	Verdict
NTNV	BLE_1M	Ant1	2402	2402.06	24.97918	±50	PASS
NTNV	BLE_1M	Ant1	2440	2440.051	20.90164	±50	PASS
NTNV	BLE_1M	Ant1	2480	2480.06	24.19355	±50	PASS

Test Graphs





NTNV-BLE_1M-Ant1-2440-PASS




NTNV-BLE_1M-Ant1-2480-PASS


APPENDIX D: TRANSMITTER SPURIOUS EMISSIONS


Test Result

TestCondition	TestMode	Antenna	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm/MHz]	Limit [dBm/MHz]	Result [μW/MHz]	Limit [μW/MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	30~1000	320.03	-58.59	≤-26	0.00138	≤2.5	PASS
NTNV	BLE_1M	Ant1	2402	1000~2387	2387.00	-40.26	≤-26	0.09419	≤2.5	PASS
NTNV	BLE_1M	Ant1	2402	2387~2400	2399.99	-27.78	≤-16	1.66725	≤25	PASS
NTNV	BLE_1M	Ant1	2402	2483.5~2496.5	2489.90	-49.16	≤-16	0.01213	≤25	PASS
NTNV	BLE_1M	Ant1	2402	2496.5~13000	6956.29	-51.36	≤-26	0.00731	≤2.5	PASS
NTNV	BLE_1M	Ant1	2440	30~1000	320.03	-58.79	≤-26	0.00132	≤2.5	PASS
NTNV	BLE_1M	Ant1	2440	1000~2387	2344.00	-49.97	≤-26	0.01007	≤2.5	PASS
NTNV	BLE_1M	Ant1	2440	2387~2400	2392.26	-45.19	≤-16	0.03027	≤25	PASS
NTNV	BLE_1M	Ant1	2440	2483.5~2496.5	2487.95	-45.53	≤-16	0.02799	≤25	PASS
NTNV	BLE_1M	Ant1	2440	2496.5~13000	2551.64	-50.70	≤-26	0.00851	≤2.5	PASS
NTNV	BLE_1M	Ant1	2480	30~1000	113.91	-58.65	≤-26	0.00136	≤2.5	PASS
NTNV	BLE_1M	Ant1	2480	1000~2387	2368.28	-48.98	≤-26	0.01265	≤2.5	PASS
NTNV	BLE_1M	Ant1	2480	2387~2400	2399.98	-47.22	≤-16	0.01897	≤25	PASS
NTNV	BLE_1M	Ant1	2480	2483.5~2496.5	2495.86	-38.25	≤-16	0.14962	≤25	PASS
NTNV	BLE_1M	Ant1	2480	2496.5~13000	8481.92	-51.83	≤-26	0.00656	≤2.5	PASS


Test Graphs









NTNV-BLE_1M-Ant1-2402-2483.5~2496.5-PASS




NTNV-BLE_1M-Ant1-2496.5~13000-PASS




NTNV-BLE_1M-Ant1-2440-30~1000-PASS




NTNV-BLE_1M-Ant1-2440-1000~2387-PASS




NTNV-BLE_1M-Ant1-2440-2387~2400-PASS




NTNV-BLE_1M-Ant1-2440-2483.5~2496.5-PASS




NTNV-BLE_1M-Ant1-2440-2496.5~13000-PASS




NTNV-BLE_1M-Ant1-2480-30~1000-PASS




NTNV-BLE_1M-Ant1-2480-1000~2387-PASS



NTNV-BLE_1M-Ant1-2480-2387~2400-PASS



NTNV-BLE_1M-Ant1-2480-2483.5~2496.5-PASS




NTNV-BLE_1M-Ant1-2480-2496.5~13000-PASS


APPENDIX E: RECEIVER SPURIOUS EMISSIONS

Test Result


TestCondition	TestMode	Antenna	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	BLE_1M	Ant1	2402	30~1000	43.82	-88.52	≤-54	0.00141	≤4	PASS
NTNV	BLE_1M	Ant1	2402	1000~12500	8519.76	-73.93	≤-47	0.04046	≤20	PASS
NTNV	BLE_1M	Ant1	2440	30~1000	89.87	-88.08	≤-54	0.00156	≤4	PASS
NTNV	BLE_1M	Ant1	2440	1000~12500	9846.22	-73.42	≤-47	0.04550	≤20	PASS
NTNV	BLE_1M	Ant1	2480	30~1000	69.02	-88.42	≤-54	0.00144	≤4	PASS
NTNV	BLE_1M	Ant1	2480	1000~12500	8794.02	-73.73	≤-47	0.04236	≤20	PASS

Test Graphs







NTNV-BLE_1M-Ant1-2402-1000~12500-PASS




NTNV-BLE_1M-Ant1-2440-30~1000-PASS



NTNV-BLE_1M-Ant1-2440-1000~12500-PASS



NTNV-BLE_1M-Ant1-2480-30~1000-PASS



APPENDIX F: INTERFERENCE PREVENTION FUNCTION

Test Item	:	Interference Prevention Function Measurement
Test Site	:	TR8
Test Mode	:	Normal Mode
EUT MAC Address	:	FF:FF:FF:FF:FF:FF
Test Results	:	PASS

The End