TEST REPORT

Applicant	Zound Industries International AB
Address	Centralplan 15 SE-111 20 Stockholm Sweden

Manufacturer or Supplier	Zound Industries International AB
Address	Centralplan 15 SE-111 20 Stockholm Sweden
Product	WIRELESS SPORT HEADPHONES
Brand Name	adidas
Model	RPD-01
Additional Model & Model Difference	N/A
Date of tests	Nov. 27, 2019 ~ Dec. 23, 2019

the tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Ryan Lu Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
Ryan	Date: Jan. 19, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD **4**
1 SUMMARY OF TEST RESULTS **5**
2 MEASUREMENT UNCERTAINTY **5**
3 GENERAL INFORMATION **6**
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST 8
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 10
3.4 DESCRIPTION OF SUPPORT UNITS 10
4 TEST TYPES AND RESULTS **11**
4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT 11
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 11
4.1.2 TEST INSTRUMENTS 12
4.1.3 TEST PROCEDURES 13
4.1.4 DEVIATION FROM TEST STANDARD 14
4.1.5 TEST SETUP 14
4.1.6 EUT OPERATING CONDITIONS 15
4.1.7 TEST RESULTS 16
4.2 NUMBER OF HOPPING FREQUENCY USED 24
4.2.1 LIMIT OF HOPPING FREQUENCY USED 24
4.2.2 TEST SETUP 24
4.2.3 TEST INSTRUMENTS 24
4.2.4 TEST PROCEDURES 25
4.2.5 DEVIATION FROM TEST STANDARD 25
4.2.6 TEST RESULTS 25
4.3 DWELL TIME ON EACH CHANNEL 28
4.3.1 LIMIT OF DWELL TIME USED 28
4.3.2 TEST SETUP 28
4.3.3 TEST INSTRUMENTS 28
4.3.4 TEST PROCEDURES 28
4.3.5 DEVIATION FROM TEST STANDARD 29
4.3.6 TEST RESULTS 29
4.4 CHANNEL BANDWIDTH 32

4.4.1 LIMITS OF CHANNEL BANDWIDTH 32
4.4.2 TEST SETUP 32
4.4.3 TEST INSTRUMENTS 32
4.4.4 TEST PROCEDURE 32
4.4.5 DEVIATION FROM TEST STANDARD 32
4.4.6 EUT OPERATING CONDITION 32
4.4.7 TEST RESULTS 33
4.5 HOPPING CHANNEL SEPARATION 37
4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION 37
4.5.2 TEST SETUP 37
4.5.3 TEST INSTRUMENTS 37
4.5.4 TEST PROCEDURES 37
4.5.5 DEVIATION FROM TEST STANDARD 37
4.5.6 TEST RESULTS 38
4.6 CONDUCTED OUTPUT POWER 42
4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 42
4.6.2 TEST SETUP 42
4.6.3 TEST INSTRUMENTS 42
4.6.4 TEST PROCEDURES 42
4.6.5 DEVIATION FROM TEST STANDARD 42
4.6.6 EUT OPERATING CONDITION 42
4.6.7 TEST RESULTS 43
4.7 OUT OF BAND EMISSION MEASUREMENT 44
4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 44
4.7.2 TEST INSTRUMENTS 44
4.7.3 TEST PROCEDURE 44
4.7.4 DEVIATION FROM TEST STANDARD 44
4.7.5 EUT OPERATING CONDITION 44
4.7.6 TEST RESULTS 44
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 50
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 51

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF191127N045-1	Original release	Jan. 19, 2020

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	N/A	Power by Battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	2.90 dB
	30MHz ~ 1GMHz	3.47 dB
	1GHz ~ 18GHz	4.84 dB
	18GHz ~ 40GHz	4.62 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WIRELESS SPORT HEADPHONES
MODEL NO.	RPD-01
ADDITIONAL MODEL	N/A
FCC ID	2AAGF-RPD01
POWER SUPPLY	DC 3.7V from Li-ion Battery Charging: DC 5V from USB Host Unit
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, π/4 DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
AVERAGE OUTPUT POWER	0.256 mW (Max. Measured)
ANTENNA TYPE	Chip Antenna, 5.19dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 191127N045) for detailed product photo.
4. When the EUT charging that wireless function cann't working. The charging mode was tested in the FCC Part 15B(sDoC) report. (Report no.: FS191127N045)

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	**2402**	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	**78**	**2480**
19	2421	**39**	**2441**	59	2461		

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports
The worst case was found when positioned on X axis for radiated emission.
Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	Powered By Fully Battery with BT link

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 55%RH	DC 3.7V from Fully Battery	Tank
RE≥1G	25deg. C, 55%RH	DC 3.7V from Fully Battery	Tank
PLC	-	-	-
APCM	25deg. C, 60%RH	DC 3.7V from Fully Battery	Tank

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247
558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessory or support units.

4 TEST TYPES AND RESULTS

4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
EMI Test Receiver Rohde&Schwarz	ESCI 7	100962	2019-7-16	2020-7-15
Broadband antenna Schwarzbeck	VULB 9168	00937	2019-10-18	2020-10-17
3m Semi-anechoic Chamber MAORUI	9m*6m*6m	NSEMC003	2018-10-20	2020-10-19
Signal Amplifier Com-power	PAM-103	18020051	2019-10-18	2020-10-17
Attenuator Rohde&Schwarz	TS2GA-6dB	18101101	N/A	N/A
Test software FARAD	FARAD	EZ_EMCV1.1.4.2	N/A	N/A
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	2019-10-18	2020-10-17
Loop Antenna	HLA 6121	45745	2019-10-18	2020-10-17
Preamplifier EMCI	EMC001340	980201	2019-10-18	2020-10-17
Digital Multimete FLUKE	15B+	43512617WS	2019-10-18	2020-10-17
Horn Antenna Schwarzbeck	BBHA 9170	01959	2019-10-18	2020-10-17
Spectrum Analyzer Rohde&Schwarz	FSV-40N	101783	2019-10-18	2020-10-17
Broadband Coaxial Preamplifier Schwarzbeck	BBV 9718	00025	2019-10-18	2020-10-17

NOTE:

1. The test was performed in 966 Chamber and was witness in Hwa-Hsing (Dongguan) Testing Co., Ltd.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup



Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.

b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

c. The necessary accessories enable the EUT in full functions.

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

GFSK DH5

CHANNEL	Channel 39	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	51.1208	18.90	40.00	-21.10	200	86	33.10	-14.20
2	159.2250	20.30	43.50	-23.20	200	226	32.68	-12.38
3	379.9141	22.69	46.00	-23.31	200	359	32.48	-9.79
4	517.2480	24.78	46.00	-21.22	200	184	31.60	-6.82
5	651.9416	29.01	46.00	-16.99	200	268	33.22	-4.21
6	912.8619	33.01	46.00	-12.99	200	49	31.22	1.79

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.



CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	51.4806	21.86	40.00	-18.14	100	4	36.10	-14.24
2	132.6850	28.26	43.50	-15.24	100	129	42.79	-14.53
3	138.3873	31.28	43.50	-12.22	100	129	45.69	-14.41
4	582.7424	28.16	46.00	-17.84	100	188	33.75	-5.59
5	729.3582	30.43	46.00	-15.57	100	292	31.87	-1.44
6	912.8619	33.94	46.00	-12.06	100	115	32.15	1.79

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.



ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	43.65PK	74.00	-30.35	213	167	44.42	-0.77
2	2390.00	13.55AV	54.00	-40.45	213	167	14.32	-0.77
3	*2402.00	92.20 PK			213	167	92.95	-0.75
4	*2402.00	62.10 AV			213	167	62.85	-0.75
5	4804.00	56.72 PK	74.00	-17.28	196	272	51.36	5.36
6	4804.00	26.62 AV	54.00	-27.38	196	272	21.26	5.36
7	#7206.00	54.25 PK	74.00	-19.75	223	146	42.50	11.75
8	#7206.00	24.15 AV	54.00	-29.85	223	146	12.40	11.75
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	41.42 PK	74.00	-32.58	148	235	42.19	-0.77
2	2390.00	11.32 AV	54.00	-42.68	148	235	12.09	-0.77
3	*2402.00	89.76 PK			148	235	90.51	-0.75
4	*2402.00	59.66 AV			148	235	60.41	-0.75
5	4804.00	52.93 PK	74.00	-21.07	138	272	47.57	5.36
6	4804.00	22.83 AV	54.00	-31.17	138	272	17.47	5.36
7	#7206.00	51.57 PK	74.00	-22.43	168	214	39.82	11.75
8	#7206.00	21.47 AV	54.00	-32.53	168	214	9.72	11.75

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	93.46 PK			227	158	94.10	-0.64
2	*2441.00	63.36 AV			227	158	64.00	-0.64
3	4882.00	57.14 PK	74.00	-16.86	148	196	50.87	6.27
4	4882.00	27.04 AV	54.00	-26.96	148	196	20.77	6.27
5	7323.00	54.68 PK	74.00	-19.32	155	269	42.54	12.14
6	7323.00	27.04 AV	54.00	-26.96	155	269	14.90	12.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	90.16 PK			100	142	90.91	-0.75
2	*2441.00	60.06 AV			100	142	60.81	-0.75
3	4882.00	52.74 PK	74.00	-21.26	127	298	47.38	5.36
4	4882.00	22.64 AV	54.00	-31.36	127	298	17.28	5.36
5	7323.00	52.45 PK	74.00	-21.55	175	253	40.70	11.75
6	7323.00	22.35 AV	54.00	-31.65	175	253	10.60	11.75

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.74 PK			189	134	93.26	-0.52
2	*2480.00	62.64 AV			189	134	63.16	-0.52
3	2483.50	43.81 PK	74.00	-30.19	189	134	44.32	-0.51
4	2483.50	13.71 AV	54.00	-40.29	189	134	14.22	-0.51
5	4960.00	56.93 PK	74.00	-17.07	201	265	50.84	6.09
6	4960.00	26.83 AV	54.00	-27.17	201	265	20.74	6.09
7	7440.00	54.87 PK	74.00	-19.13	215	132	42.34	12.53
8	7440.00	24.77 AV	54.00	-29.23	215	132	12.24	12.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	90.15 PK			166	204	90.67	-0.52
2	*2480.00	60.05 AV			166	204	60.57	-0.52
3	2483.50	41.98 PK	74.00	-32.02	166	204	42.49	-0.51
4	2483.50	11.88 AV	54.00	-42.12	166	204	12.39	-0.51
5	4960.00	52.87 PK	74.00	-21.13	124	253	46.78	6.09
6	4960.00	22.77 AV	54.00	-31.23	124	253	16.68	6.09
7	7440.00	51.69 PK	74.00	-22.31	177	225	39.16	12.53
8	7440.00	21.59 AV	54.00	-32.41	177	225	9.06	12.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	42.69 PK	74.00	-31.31	140	238	43.46	-0.77
2	2390.00	12.59 AV	54.00	-41.41	140	238	13.36	-0.77
3	*2402.00	93.21 PK			140	238	93.96	-0.75
4	*2402.00	63.11 AV			140	238	63.86	-0.75
5	4804.00	55.43 PK	74.00	-18.57	180	246	50.07	5.36
6	4804.00	25.33 AV	54.00	-28.67	180	246	19.97	5.36
7	#7206.00	56.28 PK	74.00	-17.72	117	168	44.53	11.75
8	#7206.00	26.18 AV	54.00	-27.82	117	168	14.43	11.75
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	40.14 PK	74.00	-33.86	195	94	40.91	-0.77
2	2390.00	10.04 AV	54.00	-43.96	195	94	10.81	-0.77
3	*2402.00	88.30 PK			195	94	89.05	-0.75
4	*2402.00	58.20 AV			195	94	58.95	-0.75
5	4804.00	54.23 PK	74.00	-19.77	142	114	48.87	5.36
6	4804.00	24.13 AV	54.00	-29.87	142	114	18.77	5.36
7	#7206.00	56.44 PK	74.00	-17.56	168	235	44.69	11.75
8	#7206.00	26.34 AV	54.00	-27.66	168	235	14.59	11.75

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	93.59 PK			137	244	94.23	-0.64
2	*2441.00	63.49 AV			137	244	64.13	-0.64
3	4882.00	55.85 PK	74.00	-18.15	196	227	49.58	6.27
4	4882.00	25.75 AV	54.00	-28.25	196	227	19.48	6.27
5	7323.00	57.01 PK	74.00	-16.99	120	179	44.87	12.14
6	7323.00	26.91 AV	54.00	-27.09	120	179	14.77	12.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	89.62 PK			201	110	90.26	-0.64
2	*2441.00	59.52 AV			201	110	60.16	-0.64
3	4882.00	54.58 PK	74.00	-19.42	139	121	48.31	6.27
4	4882.00	24.48 AV	54.00	-29.52	139	121	18.21	6.27
5	7323.00	57.64 PK	74.00	-16.36	172	228	45.50	12.14
6	7323.00	27.54 AV	54.00	-26.46	172	228	15.40	12.14

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.55 PK			150	68	93.07	-0.52
2	*2480.00	62.45 AV			150	68	62.97	-0.52
3	2483.50	43.45 PK	74.00	-30.55	150	68	43.96	-0.51
4	2483.50	13.35 AV	54.00	-40.65	150	68	13.86	-0.51
5	4960.00	52.01 PK	74.00	-21.99	153	234	45.92	6.09
6	4960.00	21.91 AV	54.00	-32.09	153	234	15.82	6.09
7	7440.00	54.97 PK	74.00	-19.03	128	134	42.44	12.53
8	7440.00	24.87 AV	54.00	-29.13	128	134	12.34	12.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	89.14 PK			174	203	89.66	-0.52
2	*2480.00	59.04 AV			174	203	59.56	-0.52
3	2483.50	41.52 PK	74.00	-32.48	174	203	42.03	-0.51
4	2483.50	11.42 AV	54.00	-42.58	174	203	11.93	-0.51
5	4960.00	52.15 PK	74.00	-21.85	165	111	46.06	6.09
6	4960.00	22.05 AV	54.00	-31.95	165	111	15.96	6.09
7	7440.00	54.29 PK	74.00	-19.71	192	263	41.76	12.53
8	7440.00	24.19 AV	54.00	-29.81	192	263	11.66	12.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.2.2 TEST SETUP



4.2.3 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Spectrum Keysight	N9020A	MY51240612	2019/10/18	2020/10/17
Spectrum Analyzer Rohde&Schwarz	FSV-40N	101783	2019/10/18	2020/10/17
Power Meter10Hz~18GHz Tonscend	JS0806-2	188060126	2019/10/18	2020/10/17
Signal generator Keysight	N5182A	GB40051020	2019/10/18	2020/10/17
Signal generator Keysight	N5182A	MY47420944	2019/10/18	2020/10/17
Test Software Tonscend	JS0806-2	NA	NA	NA
Hygrothermograph Yuhuaze	HTC-1	NA	2019/10/18	2020/10/17

NOTES:

1. The test was performed in RF Oven room in Hwa-Hsing (Dongguan) Testing Co., Ltd..
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.2.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were completed.

4.2.5 DEVIATION FROM TEST STANDARD

No deviation.

4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441750000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 20 dB
#Avg Type: RMS
09:20:18 PM Dec 09, 2019
Ref Offset 9.27 dB
10 dB/div
Ref 10.00 dBm
Log
Start 2.40000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.48350 GHz
Sweep 8.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.441750000 GHz
Start Freq
2.400000000 GHz
Stop Freq
2.483500000 GHz
CF Step
8.350000 MHz
Auto
Man
Freq Offset
0 Hz

8DPSK


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441750000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 20 dB
#Avg Type: RMS
10:58:51 PM Dec 09, 2019
Ref Offset 9.27 dB
10 dB/div
Ref 10.00 dBm
Log
0.00
-10.0
-20.0
-30.0
-40.0
-50.0
-60.0
-70.0
-80.0
Start 2.40000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.48350 GHz
Sweep 8.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.441750000 GHz
Start Freq
2.400000000 GHz
Stop Freq
2.483500000 GHz
CF Step
8.350000 MHz
Auto
Man
Freq Offset
0 Hz
MSG
STATUS

4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.3.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

GFSK:

Accumulated Transmit Time								
Mode	Number of Hopping Channel	Number of transmission in a period (channel number*0.4 sec)			Length of transmission time (ms)	Result (ms)	Limit (ms)	Pass / Fail
		Sweep time (Sec)	Number in 3.16 Sec	Total Number in 31.6 Sec				
DH1	79	3.16	32	320	0.380	121.60	400	Pass
DH3	79	3.16	17	170	1.638	278.46	400	Pass
DH5	79	3.16	11	110	2.884	317.24	400	Pass

8DPSK:

Accumulated Transmit Time								
Mode	Number of Hopping Channel	Number of transmission in a period (channel number*0.4 sec)			Length of transmission time (ms)	Result (ms)	Limit (ms)	Pass / Fail
		Sweep time (Sec)	Number in 3.16Sec	Total Number in 31.6 Sec				
3DH1	79	3.16	33	330	0.393	129.69	400	Pass
3DH3	79	3.16	17	170	1.637	278.29	400	Pass
3DH5	79	3.16	11	110	2.887	317.57	400	Pass

NOTE: Test plots of the transmitting time slot are shown as below.

GFSK

DH1





DH3





DH5





8DPSK

3DH1





3DH3





3DH5





4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.4.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.098
39	2441	1.113
78	2480	1.101

CH 0



CH 39

Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 20 dB
#Avg Type: RMS
09:00:57 PM Dec 09, 2019
Ref Offset 9.16 dB
10 dB/div
Ref 10.00 dBm
ΔMkr3 1.113 MHz
-0.02 dB
-26.81 dBm
Center 2.441000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.440 448 GHz -27.45 dBm
2 N 1 f 2.441 180 GHz -6.81 dBm
3 Δ1 1 f (Δ) 1.113 MHz (Δ) -0.02 dB
Frequency
Auto Tune
Center Freq 2.441000000 GHz
Start Freq 2.439500000 GHz
Stop Freq 2.442500000 GHz
CF Step 300.000 kHz
Auto Man
Freq Offset 0 Hz

CH 78

Agilent Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 20 dB
#Avg Type: RMS
09:02:26 PM Dec 09, 2019
Ref Offset 9.16 dB
10 dB/div
Ref 10.00 dBm
ΔMkr3 1.101 MHz
0.23 dB
-26.03 dBm
Center 2.480000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.479 448 GHz -26.73 dBm
2 N 1 f 2.480 168 GHz -6.03 dBm
3 Δ1 1 f (Δ) 1.101 MHz (Δ) 0.23 dB
Frequency
Auto Tune
Center Freq 2.480000000 GHz
Start Freq 2.478500000 GHz
Stop Freq 2.481500000 GHz
CF Step 300.000 kHz
Auto Man
Freq Offset 0 Hz

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.089
39	2441	1.098
78	2480	1.083

CH 0



CH 39


Agilent Spectrum Analyzer - Swept SA
Marker 1 2.440451000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 16 dB
#Avg Type: RMS
05:21:12 AM Dec 27, 2019
Ref Offset 9.66 dB
10 dB/div
Ref 6.00 dBm
Log
ΔMkr3 1.098 MHz
-0.08 dB
-22.53 dBm
Center 2.441000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.440 451 GHz -22.58 dBm
2 N 1 f 2.441 168 GHz -2.53 dBm
3 Δ1 1 f (Δ) 1.098 MHz (Δ) -0.08 dB
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

CH 78


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 16 dB
#Avg Type: RMS
05:22:08 AM Dec 27, 2019
Ref Offset 9.66 dB
10 dB/div
Ref 6.00 dBm
Log
ΔMkr3 1.083 MHz
-0.02 dB
-22.13 dBm
Center 2.480000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.479 466 GHz -22.32 dBm
2 N 1 f 2.480 168 GHz -2.13 dBm
3 Δ1 1 f (Δ) 1.083 MHz (Δ) -0.02 dB
Frequency
Auto Tune
Center Freq
2.480000000 GHz
Start Freq
2.478500000 GHz
Stop Freq
2.481500000 GHz
CF Step
300.000 kHz
Auto
Man
Freq Offset
0 Hz

4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.5.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.999	1.098	0.732	PASS
39	2441	0.993	1.113	0.742	PASS
78	2480	0.998	1.101	0.734	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0

CH 39

Agilent Spectrum Analyzer - Swept SA
Marker 2 2.442166000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 22 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
03:26:33 AM Dec 27, 2019
Mkr2 2.442 166 GHz
-7.907 dBm
10 dB/div
Ref 11.00 dBm
Center 2.441500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.441 173 GHz -7.93 dBm
2 N 2 f 2.442 166 GHz -7.907 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

CH 78

Agilent Spectrum Analyzer - Swept SA
Marker 1 2.479167000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 10 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
03:43:26 AM Dec 09, 2019
Mkr1 2.479 167 GHz
-6.899 dBm
10 dB/div
Ref 0.00 dBm
Center 2.479500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.479 167 GHz -6.899 dBm
2 N 2 f 2.480 166 GHz -6.891 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.999	1.089	0.726	PASS
39	2441	0.999	1.098	0.732	PASS
78	2480	0.999	1.083	0.722	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0

CH 39

Agilent Spectrum Analyzer - Swept SA
Marker 1 2.441167000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 22 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
03:27:38 AM Dec 27, 2019
Mkr1 2.441 167 GHz
-12.144 dBm
10 dB/div
Ref 11.00 dBm
Center 2.441500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.441 167 GHz -12.144 dBm
2 N 2 f 2.442 166 GHz -12.025 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

CH 78

Agilent Spectrum Analyzer - Swept SA
Marker 2 2.480169000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 10 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
03:46:06 AM Dec 09, 2019
Mkr2 2.480 169 GHz
-11.653 dBm
10 dB/div
Ref 0.00 dBm
Center 2.479500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.479 170 GHz -11.427 dBm
2 N 2 f 2.480 169 GHz -11.653 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

4.6 CONDUCTED OUTPUT POWER

4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the average power level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

MAXIMUM AVERAGE OUTPUT POWER

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)	AVERAGE POWER LIMIT (mW)	PASS/FAIL
0	2402	-8.12	0.154	125	PASS
39	2441	-6.54	0.222	125	PASS
78	2480	-5.91	0.256	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)	AVERAGE POWER LIMIT (mW)	PASS/FAIL
0	2402	-11.98	0.063	125	PASS
39	2441	-10.63	0.086	125	PASS
78	2480	-10.51	0.089	125	PASS

4.7 OUT OF BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –30dB of the highest emission level of operating band (in 100KHz RBW).

4.7.2 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.7.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation.

4.7.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK

Low Channel	High Channel
	
	

8DPSK

Low Channel	High Channel
	
	

GFSK

Hopping on Low Channel	Hopping on High Channel
	
	





8DPSK

Hopping on Low Channel



Hopping on High Channel




Agilent Spectrum Analyzer - Swept SA
Sweep Time 94.0 ms
Trig: Free Run
#Atten: 20 dB
#Avg Type: RMS
Avg|Hold: 10/10
Ref Offset 9.77 dB
10 dB/div Ref 19.77 dBm
Mkr1 861.00 MHz
-60.306 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 94.00 ms (30001 pts)
Sweep/Control
Sweep Time
94.0 ms
Sweep Setup
Gate
[Off,LO]
Points
30001
Agilent Spectrum Analyzer - Swept SA
Marker 1 810.138666667 MHz
Ref Offset 9.66 dB
10 dB/div Ref 19.66 dBm
Mkr1 810.14 MHz
-60.499 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 94.00 ms (30001 pts)
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Agilent Spectrum Analyzer - Swept SA
Sweep Time 2.44 s
Ref Offset 9.77 dB
10 dB/div Ref 19.77 dBm
Mkr1 7.248 35 GHz
-44.019 dBm
Start 1.00 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 26.50 GHz
Sweep 2.438 s (30001 pts)
Sweep/Control
Sweep Time
2.44 s
Sweep Setup
Gate
[Off,LO]
Points
30001
Agilent Spectrum Analyzer - Swept SA
Marker 1 7.250900000000 GHz
Ref Offset 9.66 dB
10 dB/div Ref 19.66 dBm
Mkr1 7.250 90 GHz
-43.672 dBm
Start 1.00 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 26.50 GHz
Sweep 2.438 s (30001 pts)
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---