

Prüfbericht-Nr.: Test report no.:		CN25P9AK 002	Auftrags-Nr.: Order no.:		168572937	Page 1 of 14 Seite 1 von 14	
Kunden-Referenz-Nr.: Client reference no.:		N/A	Auftragsdatum: Order date:		2025-09-01		
Auftraggeber: Client:		Harman International Industries, Incorporated 8500 Balboa Blvd, Northridge, California, 91329, United States					
Prüfgegenstand: Test item:		Partybox Wireless Mic					
Bezeichnung / Typ-Nr.: Identification / Type no.:		EASYSING MICS TM (Trademark: JBL)					
Auftrags-Inhalt: Order content:		Type test					
Prüfgrundlage: Test specification:		Article 2 Section 1 Item 19, Radio Equipment Regulation: Article 49-20 MIC notice No. 88 Appendix No. 43 (Test method)					
Wareneingangsdatum: Date of sample receipt:		2025-08-08					
Prüfmuster-Nr.: Test sample no.:		A004063311					
Prüfzeitraum: Testing period:		2025-08-08 – 2025-09-09					
Ort der Prüfung: Place of testing:		TÜV Rheinland (Shenzhen) Co., Ltd.					
Prüflaboratorium: Testing laboratory:		TÜV Rheinland (Shenzhen) Co., Ltd.					
Prüfergebnis*: Test result*:		Pass					
geprüft von: tested by:				genehmigt von: authorized by:			
Datum: Date:		2025-10-31		Ausstellungsdatum: Issue date:		2025-10-31	
Position / Stellung:		Project Manager		Position / Stellung:		Authorizer	
Sonstiges / Other:		This test report is for Dongle part.					
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged					
* Legende: * Legend:		P(ass) = entspricht o.g. Prüfgrundlage(n) P(ass) = passed a.m. test specification(s) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) F(ail) = failed a.m. test specification(s) N/A = nicht anwendbar N/A = not applicable N/T = nicht getestet N/T = not tested					
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>							

Prüfbericht-Nr.: CN25P9AK 002
Test report no.:

Page 2 of 14
Seite 2 von 14

Remarks
Anmerkungen

- | | |
|---|--|
| 1 | <p>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</p> <p><i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</i></p> <p><i>Detaillierte Informationen bezüglich Prüfbedingungen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i></p> |
| 2 | <p>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</p> <p><i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i></p> |
| 3 | <p>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</p> <p><i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i></p> |
| 4 | <p>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</p> <p><i>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</i></p> |

Contents

1	TEST SITES.....	4
1.1	TEST FACILITIES.....	4
1.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	4
1.3	UNCERTAINTY OF MEASUREMENT.....	4
2	GENERAL PRODUCT INFORMATION.....	5
2.1	PRODUCT FUNCTION AND INTENDED USE.....	5
2.2	RATINGS AND SYSTEM DETAILS.....	5
2.3	TEST CONDITIONS.....	6
2.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	6
2.5	ANTENNA SPECIFICATIONS.....	7
2.5.1	ANTENNA GAIN.....	7
2.5.2	ANTENNA PATTERN.....	7
3	TEST RESULTS.....	8
3.1	FREQUENCY TOLERANCE MEASUREMENT.....	8
3.1.1	LIMITS OF FREQUENCY TOLERANCE MEASUREMENT.....	8
3.1.2	TEST SETUP.....	8
3.1.3	TEST RESULTS.....	8
3.2	OCCUPIED BANDWIDTH MEASUREMENT (99% POWER BANDWIDTH).....	9
3.2.1	LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT.....	9
3.2.2	TEST SETUP.....	9
3.2.3	TEST RESULTS.....	9
3.3	ANTENNA POWER MEASUREMENT.....	10
3.3.1	LIMITS OF ANTENNA POWER.....	10
3.3.2	TEST SETUP.....	10
3.3.3	TEST RESULTS.....	10
3.4	SPURIOUS EMISSIONS FOR TRANSMITTER MEASUREMENT.....	11
3.4.1	LIMITS OF SPURIOUS EMISSIONS.....	11
3.4.2	TEST SETUP.....	11
3.4.3	TEST RESULT.....	11
3.5	SPURIOUS EMISSIONS FOR RECEIVER.....	12
3.5.1	LIMITS OF SPURIOUS EMISSIONS FOR RECEIVER.....	12
3.5.2	TEST SETUP.....	12
3.5.3	TEST RESULT.....	12
3.6	INTERFERENCE PREVENTION FUNCTION.....	13
3.6.1	LIMITS OF Interference Prevention Function.....	13
3.6.2	TEST SETUP.....	13
3.6.3	TEST RESULTS.....	13
4	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	14

Prüfbericht-Nr.: CN25P9AK 002
Test report no.:

Seite 4 von 14
Page 4 of 14

1 TEST SITES

1.1 TEST FACILITIES

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

1.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Table 1: List of Test and Measurement Equipment

TÜV Rheinland (Shenzhen) Co., Ltd.

Equipment	Manufacturer	Model	Serial No.	Calibration Company	Date calibrated	Cal. until	Note (Radio Law)
Wireless Connectivity Tester	R&S	CMW270	101375	GRGTEST	26.09.2024	25.09.2025	24-2-4-2-(ha)
EXA Signal Analyzer	Keysight	N9010B	MY60241175	GRGTEST	26.09.2024	25.09.2025	24-2-4-2-(ha)
Power Meter	R&S	NRP2	107105	GRGTEST	31.10.2024	30.10.2025	24-2-4-2-(ha)
Power Sensor	R&S	NRP-Z81	105677	GRGTEST	26.09.2024	25.09.2025	24-2-4-2-(ha)
DC Power Supply	Keysight	E3642A	MY61276100	GRGTEST	22.02.2025	21.02.2026	24-2-4-2-(ha)
Digital Multi Meter	FLUKE	F15B	44350845WS	GRGTEST	24.02.2025	23.02.2026	24-2-4-2-(ha)

1.3 UNCERTAINTY OF MEASUREMENT

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

ITEM	UNCERTAINTY
Occupied Bandwidth	206.50 Hz
Spurious emissions	$\pm 3.93\text{dB}$
Output power density	1.37dB
Out of band radiated power	2.52 dB
Frequency Tolerance	0.104 ppm

Prüfbericht-Nr.:

CN25P9AK 002

Test report no.:

Seite 5 von 14

Page 5 of 14

2 GENERAL PRODUCT INFORMATION

2.1 PRODUCT FUNCTION AND INTENDED USE

The EUT is a Partybox Wireless Mic, which consists of two microphones, a Dongle and a USB-C to USB-A Connector. The microphones and Dongle support 2.4GHz SRD wireless technology.

Two microphones are identical in electrical circuit design and PCB layout.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 RATINGS AND SYSTEM DETAILS

Table 2: Technical Specification of EUT

General Information of EUT		Description
Kind of Equipment:		Partybox Wireless Mic
Type Designation:		JBL EASYSING MICS
Trademark:		JBL
Operating Voltage		DC 5V, 0.5A via Type C interface
Extreme Temperature Range		0°C to +45°C
Technical Specification of Dongle		
Characteristic		Description
Operating Frequency band		2404 ~ 2478 MHz
Channel Number		37 channels
Channel separation		2MHz
Modulation		GFSK
Antenna Type		MIC antenna
Antenna Gain		1.79 dBi (Provided by the Client)

Prüfbericht-Nr.: CN25P9AK 002
Test report no.:

Seite 6 von 14
Page 6 of 14

Table 3: RF Channel and Frequency

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2404.00	10	2424.00	20	2446.00	30	2466.00
01	2406.00	11	2428.00	21	2448.00	31	2468.00
02	2408.00	12	2430.00	22	2450.00	32	2470.00
03	2410.00	13	2432.00	23	2452.00	33	2472.00
04	2412.00	14	2434.00	24	2454.00	34	2474.00
05	2414.00	15	2436.00	25	2456.00	35	2476.00
06	2416.00	16	2438.00	26	2458.00	36	2478.00
07	2418.00	17	2440.00	27	2460.00		
08	2420.00	18	2442.00	28	2462.00		
09	2422.00	19	2444.00	29	2464.00		

2.3 TEST CONDITIONS

Test conditions	Voltage (Vac)
V_{normal}	5.00
V_{max}	5.50
V_{min}	4.50

Test conditions	Unit
Temperature	24.0 deg °C
Humidity	50.3 %

2.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	T480	PF-16A6N8	N/A

Prüfbericht-Nr.: **CN25P9AK 002**
Test report no.:

Seite 7 von 14
Page 7 of 14

2.5 ANTENNA SPECIFICATIONS

2.5.1 ANTENNA GAIN

Ant. Type	Connector Type	Highest Peak Gain (dBi) 2.4GHz ~ 2.5GHz
MIC antenna	N/A	1.79 dBi

2.5.2 ANTENNA PATTERN

Please refer to the attached file (Antenna report).

Prüfbericht-Nr.:
Test report no.:

CN25P9AK 002

Seite 8 von 14
Page 8 of 14


3 TEST RESULTS

3.1 FREQUENCY TOLERANCE MEASUREMENT

3.1.1 LIMITS OF FREQUENCY TOLERANCE MEASUREMENT

Tolerance of frequency shall be +/- 50ppm

3.1.2 TEST SETUP



3.1.3 TEST RESULTS

For the measurement records, refer to the appendix A.

Prüfbericht-Nr.: CN25P9AK 002
Test report no.:


Seite 9 von 14
Page 9 of 14

3.2 OCCUPIED BANDWIDTH MEASUREMENT (99% POWER BANDWIDTH)

3.2.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

ITEM	LIMIT	REMARK
Occupied bandwidth	<26MHz	For 802.11b, g & 802.11n (HT20)
Occupied bandwidth	<26MHz	For BT-LE (GFSK)

3.2.2 TEST SETUP



3.2.3 TEST RESULTS

For the measurement records, refer to the appendix A.

Prüfbericht-Nr.: **CN25P9AK 002**
Test report no.:

Seite 10 von 14
Page 10 of 14

3.3 ANTENNA POWER MEASUREMENT


3.3.1 LIMITS OF ANTENNA POWER

Modulation system	Frequency band used	Antenna power (max.)	EIRP (max)	
			Omni-directional case	Directional case
DS.OFDM (Narrow-Band)	2,400 – 2,4835 MHz	10mW/MHz	12.14 dBm/MHz (16.367 mW/MHz)	22.14 dBm/MHz (163.682 mW/MHz)
OFDM (Wide-Band)	2,400 – 2,4835 MHz	5mW/MHz	9.13dBm/MHz (8.185mW/MHz)	19.13dBm/MHz (81.846mW/MHz)
DTS	2,400 – 2,4835 MHz	10mW	12.14 dBm 16.367 mW	22.14 dBm 163.682 mW

Tolerance of antenna power shall be +20% (upper value) and –80% (lower value).

According article 49.20 f(2) The angular width of the principal radiation in the horizontal and vertical planes of the transmitting antenna shall not exceed the value obtained by the following expression. $360/A$ degree
A represents the value determined by dividing an equivalent isotropically radiated power by the value obtained by applying an antenna power with the mean power of 10 mW to the transmitting antenna with its absolute gain being 2.14 dB, and shall be 1 when it is lower than 1

3.3.2 TEST SETUP



3.3.3 TEST RESULTS

For the measurement records, refer to the appendix A.

Prüfbericht-Nr.: CN25P9AK 002
Test report no.:


Seite 11 von 14
Page 11 of 14

3.4 SPURIOUS EMISSIONS FOR TRANSMITTER MEASUREMENT

3.4.1 LIMITS OF SPURIOUS EMISSIONS

FREQUENCIES (MHz)	LIMIT
Operating frequency 2400 to 2483.5MHz	
30.0MHz to 2387MHz	$\leq 2.5\mu\text{W/MHz}$
2387.0MHz to 2400.0MHz	$\leq 25\mu\text{W/MHz}$
2483.5MHz to 2496.5MHz	$\leq 25\mu\text{W/MHz}$
2496.5MHz to 12500.0MHz	$\leq 2.5\mu\text{W/MHz}$

3.4.2 TEST SETUP



3.4.3 TEST RESULT

For the measurement records, refer to the appendix A.

Prüfbericht-Nr.: CN25P9AK 002
Test report no.:

Seite 12 von 14
Page 12 of 14

3.5 SPURIOUS EMISSIONS FOR RECEIVER

3.5.1 LIMITS OF SPURIOUS EMISSIONS FOR RECEIVER

FREQUENCIES (MHz)	LIMIT
Below 1GHz	$\leq 4\text{nW}$ (-54dBm)
Above 1GHz	$\leq 20\text{nW}$ (-47dBm)

3.5.2 TEST SETUP



3.5.3 TEST RESULT

For the measurement records, refer to the appendix A.

Prüfbericht-Nr.:

CN25P9AK 002

Test report no.:

Seite 13 von 14


Page 13 of 14

3.6 INTERFERENCE PREVENTION FUNCTION

3.6.1 LIMITS OF Interference Prevention Function

N/A

3.6.2 TEST SETUP



3.6.3 TEST RESULTS

ENVIRONMENTAL CONDITIONS	24.4 deg.C, 50.3% RH
LINK MODE	TEST RESULT
2.4G SDR	PASS


MAC address: 0x35601615

Prüfbericht-Nr.:
Test report no.:

CN25P9AK 002

Seite 14 von 14
Page 14 of 14

4 PHOTOGRAPHS OF THE TEST CONFIGURATION



---END---

Appendix A

Test results of Dongle

1	APPENDIX A.1 : FREQUENCY TOLERANCE.....	2
2	APPENDIX A.2 : OCCUPIED BANDWIDTH.....	6
3	APPENDIX A.3 : ANTENNA POWER	10
4	APPENDIX A.4: SPURIOUS EMISSIONS FOR TRANSMITTER	11
5	APPENDIX A.5: SPURIOUS EMISSIONS FOR RECEIVER	30

1 Appendix A.1 : FREQUENCY TOLERANCE


Note:


NTNV means: Normal Temperature & Normal Voltage, NTHV means: Normal Temperature & Max. Voltage,

NTLV means: Normal Temperature & Min. Voltage.

TestCondition	TestMode	Antenna	Freq(MHz)	Result[ppm]	Limit[ppm]	Verdict
NTNV	TX	Ant1	2404	-4.11814	±50	PASS
			2440	-4.18033	±50	PASS
			2478	-4.23729	±50	PASS
NTLV	TX	Ant1	2404	-4.11814	±50	PASS
			2440	-4.18033	±50	PASS
			2478	-4.23729	±50	PASS
NTHV	TX	Ant1	2404	-4.11814	±50	PASS
			2440	-4.18033	±50	PASS
			2478	-4.23729	±50	PASS







2 Appendix A.2 : OCCUPIED BANDWIDTH

TestCondition	TestMode	Antenna	Freq(MHz)	Result [MHz]	Limit [MHz]	Verdict
NTNV	TX	Ant1	2404	2.116	≤26	PASS
			2440	2.115	≤26	PASS
			2478	2.111	≤26	PASS
NTLV	TX	Ant1	2404	2.121	≤26	PASS
			2440	2.115	≤26	PASS
			2478	2.109	≤26	PASS
NTHV	TX	Ant1	2404	2.122	≤26	PASS
			2440	2.113	≤26	PASS
			2478	2.110	≤26	PASS







3 Appendix A.3 : ANTENNA POWER

Antenna Power							
TestCondition	TestMode	Antenna	Freq(MHz)	Result(dBm)	Result(mW)	Limit(mW)	Verdict
NTNV	TX	Ant1	2404	7.40	5.4954	≤10	PASS
			2440	7.28	5.3456	≤10	PASS
			2478	7.02	5.0350	≤10	PASS
NTLV	TX	Ant1	2404	7.41	5.5081	≤10	PASS
			2440	7.29	5.3580	≤10	PASS
			2478	7.02	5.0350	≤10	PASS
NTHV	TX	Ant1	2404	7.40	5.4954	≤10	PASS
			2440	7.28	5.3456	≤10	PASS
			2478	7.02	5.0350	≤10	PASS

Tolerance								
Test Condition	Test Mode	Antenna	Freq(MHz)	Power (mW)	RatedPower (mW)	Result (%)	Limit (%)	Verdict
NTNV	TX	Ant1	2404	5.4954	10	-45.05	-80 to +20	PASS
			2440	5.3456	10	-46.54	-80 to +20	PASS
			2478	5.0350	10	-49.65	-80 to +20	PASS
NTLV	TX	Ant1	2404	5.5081	10	-44.92	-80 to +20	PASS
			2440	5.3580	10	-46.42	-80 to +20	PASS
			2478	5.0350	10	-49.65	-80 to +20	PASS
NTHV	TX	Ant1	2404	5.4954	10	-45.05	-80 to +20	PASS
			2440	5.3456	10	-46.54	-80 to +20	PASS
			2478	5.0350	10	-49.65	-80 to +20	PASS

EIRP							
TestCondition	TestMode	Antenna	Freq(MHz)	Power (dBm)	EIRP(dBm)	Limit(dBm)	Verdict
NTNV	TX	Ant1	2404	7.40	9.19	≤12.14	PASS
			2440	7.28	9.07	≤12.14	PASS
			2478	7.02	8.81	≤12.14	PASS
NTLV	TX	Ant1	2404	7.41	9.20	≤12.14	PASS
			2440	7.29	9.08	≤12.14	PASS
			2478	7.02	8.81	≤12.14	PASS
NTHV	TX	Ant1	2404	7.40	9.19	≤12.14	PASS
			2440	7.28	9.07	≤12.14	PASS
			2478	7.02	8.81	≤12.14	PASS

4 Appendix A.4: SPURIOUS EMISSIONS FOR TRANSMITTER

TestCondition	TestMode	Antenna	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [μW]	Limit [μW]	Verdict
NTNV	TX	Ant1	2404	30~500	455.00	-45.52	≤-26	0.02805	≤2.5	PASS
				500~1000	773.88	-45.07	≤-26	0.03112	≤2.5	PASS
				1000~2387	2252.11	-42.15	≤-26	0.06095	≤2.5	PASS
				2387~2400	2387.08	-32.11	≤-16	0.61518	≤25	PASS
				2483.5~2496.5	2495.53	-30.54	≤-16	0.88308	≤25	PASS
				2496.5~13000	3704.40	-39.72	≤-26	0.10666	≤2.5	PASS
			2440	30~500	487.43	-45.64	≤-26	0.02729	≤2.5	PASS
				500~1000	884.63	-44.85	≤-26	0.03273	≤2.5	PASS
				1000~2387	2296.85	-42.58	≤-26	0.05521	≤2.5	PASS
				2387~2400	2399.50	-32.05	≤-16	0.62373	≤25	PASS
				2483.5~2496.5	2486.81	-32.02	≤-16	0.62806	≤25	PASS
				2496.5~13000	3775.30	-39.21	≤-26	0.11995	≤2.5	PASS
			2478	30~500	460.05	-45.87	≤-26	0.02588	≤2.5	PASS
				500~1000	859.00	-45.12	≤-26	0.03076	≤2.5	PASS
				1000~2387	2370.36	-42.53	≤-26	0.05585	≤2.5	PASS
				2387~2400	2396.59	-32.30	≤-16	0.58884	≤25	PASS
				2483.5~2496.5	2492.32	-31.43	≤-16	0.71945	≤25	PASS
				2496.5~13000	3848.83	-37.91	≤-26	0.16181	≤2.5	PASS
NTLV	TX	Ant1	2404	30~500	470.39	-45.41	≤-26	0.02877	≤2.5	PASS
				500~1000	755.88	-45.05	≤-26	0.03126	≤2.5	PASS
				1000~2387	2321.46	-41.64	≤-26	0.06855	≤2.5	PASS
				2387~2400	2387.34	-31.58	≤-16	0.69502	≤25	PASS
				2483.5~2496.5	2490.96	-32.07	≤-16	0.62087	≤25	PASS
				2496.5~13000	3746.42	-38.50	≤-26	0.14125	≤2.5	PASS
			2440	30~500	472.27	-45.47	≤-26	0.02838	≤2.5	PASS
				500~1000	802.00	-44.95	≤-26	0.03199	≤2.5	PASS
				1000~2387	2378.33	-42.36	≤-26	0.05808	≤2.5	PASS
				2387~2400	2394.04	-31.57	≤-16	0.69663	≤25	PASS
				2483.5~2496.5	2487.74	-31.85	≤-16	0.65313	≤25	PASS
				2496.5~13000	3851.45	-38.17	≤-26	0.15241	≤2.5	PASS
			2478	30~500	437.73	-45.76	≤-26	0.02655	≤2.5	PASS
				500~1000	904.50	-44.66	≤-26	0.03420	≤2.5	PASS
				1000~2387	2378.68	-42.64	≤-26	0.05445	≤2.5	PASS
				2387~2400	2395.18	-31.68	≤-16	0.67920	≤25	PASS
				2483.5~2496.5	2486.08	-31.56	≤-16	0.69823	≤25	PASS
				2496.5~13000	3870.88	-38.51	≤-26	0.14093	≤2.5	PASS
NTHV	TX	Ant1	2404	30~500	426.09	-45.80	≤-26	0.02630	≤2.5	PASS
				500~1000	955.63	-45.29	≤-26	0.02958	≤2.5	PASS
				1000~2387	2288.87	-42.73	≤-26	0.05333	≤2.5	PASS
				2387~2400	2393.18	-31.99	≤-16	0.63241	≤25	PASS
				2483.5~2496.5	2491.35	-31.01	≤-16	0.79250	≤25	PASS
				2496.5~13000	3809.96	-39.35	≤-26	0.11614	≤2.5	PASS
			2440	30~500	285.09	-45.76	≤-26	0.02655	≤2.5	PASS
				500~1000	975.75	-44.37	≤-26	0.03656	≤2.5	PASS
				1000~2387	2339.50	-42.35	≤-26	0.05821	≤2.5	PASS
				2387~2400	2388.42	-32.13	≤-16	0.61235	≤25	PASS
				2483.5~2496.5	2487.59	-31.50	≤-16	0.70795	≤25	PASS
				2496.5~13000	3889.26	-39.27	≤-26	0.11830	≤2.5	PASS
			2478	30~500	481.08	-45.23	≤-26	0.02999	≤2.5	PASS
				500~1000	759.25	-45.00	≤-26	0.03162	≤2.5	PASS
				1000~2387	2379.37	-42.28	≤-26	0.05916	≤2.5	PASS
				2387~2400	2398.82	-32.21	≤-16	0.60117	≤25	PASS
				2483.5~2496.5	2489.67	-31.86	≤-16	0.65163	≤25	PASS
				2496.5~13000	5121.85	-39.24	≤-26	0.11912	≤2.5	PASS

Appendix A
CN25P9AK 002





Appendix A
CN25P9AK 002





Appendix A
CN25P9AK 002





Appendix A
CN25P9AK 002





Appendix A
CN25P9AK 002



Appendix A CN25P9AK 002



Prüfbericht - Produkte
Test Report - Products

Page 21 of 39



Appendix A
CN25P9AK 002





Appendix A
CN25P9AK 002



Appendix A
CN25P9AK 002



Appendix A
CN25P9AK 002





Appendix A
CN25P9AK 002



Appendix A CN25P9AK 002



Prüfbericht - Produkte
Test Report - Products

Page 29 of 39



5 Appendix A.5: SPURIOUS EMISSIONS FOR RECEIVER


TestCondition	TestMode	Antenna	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	RX	Ant1	2404	30~500	253.72	-76.74	≤-54	0.02118	≤4	PASS
				500~1000	863.50	-76.50	≤-54	0.02239	≤4	PASS
				1000~12500	2473.15	-55.30	≤-47	2.95121	≤20	PASS
			2440	30~500	275.34	-77.55	≤-54	0.01758	≤4	PASS
				500~1000	857.75	-76.80	≤-54	0.02089	≤4	PASS
				1000~12500	2474.3	-54.32	≤-47	3.69828	≤20	PASS
			2478	30~500	265.94	-77.56	≤-54	0.01754	≤4	PASS
				500~1000	848.50	-76.74	≤-54	0.02118	≤4	PASS
				1000~12500	2476.6	-54.63	≤-47	3.44350	≤20	PASS
NTLV	RX	Ant1	2404	30~500	303.31	-77.44	≤-54	0.01803	≤4	PASS
				500~1000	980.25	-76.23	≤-54	0.02382	≤4	PASS
				1000~12500	2473.15	-52.13	≤-47	6.12350	≤20	PASS
			2440	30~500	463.81	-77.94	≤-54	0.01607	≤4	PASS
				500~1000	884.00	-76.16	≤-54	0.02421	≤4	PASS
				1000~12500	2474.88	-53.53	≤-47	4.43609	≤20	PASS
			2478	30~500	436.08	-77.28	≤-54	0.01871	≤4	PASS
				500~1000	859.00	-76.77	≤-54	0.02104	≤4	PASS
				1000~12500	2476.03	-54.26	≤-47	3.74973	≤20	PASS
NTHV	RX	Ant1	2404	30~500	471.57	-77.26	≤-54	0.01879	≤4	PASS
				500~1000	839.50	-76.90	≤-54	0.02042	≤4	PASS
				1000~12500	2475.45	-53.84	≤-47	4.13048	≤20	PASS
			2440	30~500	499.53	-77.55	≤-54	0.01758	≤4	PASS
				500~1000	969.75	-77.03	≤-54	0.01982	≤4	PASS
				1000~12500	2475.45	-55.02	≤-47	3.14775	≤20	PASS
			2478	30~500	448.54	-77.66	≤-54	0.01714	≤4	PASS
				500~1000	879.50	-76.99	≤-54	0.02000	≤4	PASS
				1000~12500	3831.88	-59.24	≤-47	1.19124	≤20	PASS

Appendix A CN25P9AK 002



Prüfbericht - Produkte
Test Report - Products

Page 31 of 39















Appendix A CN25P9AK 002



Prüfbericht - Produkte
Test Report - Products

Page 38 of 39

