



TEST REPORT

Product Name: Mouse
Trademark: SaikoMausu
Model Number: 189B
Prepared For: Shenzhen Yuanhexing e-commerce Co., LTD
118-02, Bidg. L08, Huanan International Leather Goods Raw Materials
Address: Logistics Zone (Phase I), No. 1 Huanan Ave., Hehua Comm., Pinghu St.,
Longgang Dist., Shenzhen CHINA
Manufacturer: Shenzhen Yuanhexing e-commerce Co., LTD
118-02, Bidg. L08, Huanan International Leather Goods Raw Materials
Address: Logistics Zone (Phase I), No. 1 Huanan Ave., Hehua Comm., Pinghu St.,
Longgang Dist., Shenzhen CHINA
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an
District, Shenzhen, Guangdong, China
Sample Received Date: Jul. 22, 2025
Sample tested Date: Jul. 22, 2025 to Jul. 31, 2025
Issue Date: Jul. 31, 2025
Report No.: CTB25072208501RF01
Test Standards: MIC Public Notice 88:2004, annex 1 and annex 43
Ordinance Article 2 paragraph 1 item (19)
Test Results: PASS
Remark: This is 2.4G radio test report.
Compiled by: Reviewed by: Approved by:

Zhou Kui

Arron Liu

ZhouKuiArron LiuBin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

Table of Contents Page

1	TEST SUMMARY	4
1	VERSION	4
1.2	TEST DESCRIPTION	5
1.3	MEASUREMENT UNCERTAINTY	6
2	GENERAL INFORMATION	7
2.1	GENERAL DESCRIPTION OF EUT	7
2.2	DESCRIPTION OF TEST MODES	8
2.3	ENVIRONMENTAL CONDITIONS	9
2.4	BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5	DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	11
2.6	MEASUREMENT EQUIPMENT LIST	12
3	TEST CONDITIONS AND RESULTS	14
3.1	FREQUENCY ERROR	14
3.1.1	Limit	14
3.1.2	Test configuration	14
3.1.3	Test procedure	14
3.1.4	Test results	15
3.2	ANTENNA OUTPUT POWER AND OUTPUT POWER TOLERANCE	17
3.2.1	Limit	17
3.2.2	Test configuration	17
3.2.3	Test procedure	17
3.2.4	Test results	18
3.3	OCCUPIED BANDWIDTH AND SPREADING BANDWIDTH	20
3.3.1	Limit	20
3.3.2	Test configuration	20
3.3.3	Test procedure	20
3.3.4	Test results	21
3.4	UNWANTED EMISSION STRENGTH	23
3.4.1	Limit	23
3.4.2	Test configuration	23
3.4.3	Test procedure	23
3.4.4	Test results	24
3.5	SECONDARY RADIATED EMISSION STRENGTH	28
3.5.1	Limit	28
3.5.2	Test configuration	28

3.5.3 Test procedure	28
3.5.4 Test results	28
3.6 TRANSMISSION ANTENNA GAIN (EIRP ANTENNA POWER) MEASUREMENT	32
3.6.1 Limit	32
3.6.2 Test Procedure	32
3.6.3 Test results	32
3.7 CONSTRUCTION PROTECTION METHOD	33
3.7.1 Requirement	33
3.7.2 Confirmation method	33
3.7.3 The photos of construction protection	33
3.8 INTERFERENCE PREVENTION FUNCTION	34
3.8.1 Limit	34
3.8.2 Measuring ID code software	34
3.8.3 Test setup	34
3.8.4 Test procedure	34
3.8.5 Test result	34
4 TEST SETUP PHOTOS OF EUT	35



1 TEST SUMMARY

1 VERSION

Report No.	Issue Date	Description	Approved
CTB25072208501RF01	Jul. 31, 2025	Original	Valid

1.2 Test description

Part	Rule Section	Description	Result
4.1	3	Frequency Error	Complies
4.2	4	Occupied Bandwidth (99%) and Spread-spectrum (90%)	Complies
4.3	5	Unwanted Emission Intensity	Complies
4.4	6	Antenna Power Error	Complies
4.5	7	Limitation of Collateral Emission of Receiver	Complies
4.6	8	Transmission Antenna Gain(EIRP Antenna Power)	Complies
4.7	9	Transmission Radiation Angle Width (3dB Beam width)	N/A
4.8	10	Radio Interference Prevention Capability	Complies
4.9	Note 1	Carrier Sense Capability	N/A
4.10	Note 2	Construction Protection Confirmation	Complies

Note:

1. "N/A" denotes test is not applicable in this Report.
2. "Note 1" is MIC Notice No.88 Appendix No.43.
3. "Note 2" is MIC Ordinance Regulating Radio Equipment Section 4.17 of Article 49.20.

1.3 Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Item	Uncertainty
Occupancy bandwidth	54.3kHz
Conducted output power Above 1G	0.9dB
Conducted output power below 1G	0.9dB
Power Spectral Density , Conduction	0.9dB
Conduction spurious emissions	2.0dB
Out of band emission	2.0dB
3m camber Radiated spurious emission(30MHz-1GHz)	4.6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5.1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB
Frequency Error	54.3Hz
Adjacent channel power below 1G	2.6dB
Adjacent channel power Above 1G	2.8dB
humidity uncertainty	5.5%
Temperature uncertainty	0.63℃
frequency	1×10^{-7}

2 GENERAL INFORMATION

2.1 General description of EUT

Model(s):	189B
Model Description:	All the model are the same circuit and RF module, only the name and labels are different. Test sample model: 189B
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402-2480MHz
Max. RF output power:	2mW
Type of Modulation:	GFSK
Antenna installation:	PCB antenna
Antenna Gain:	2.34dBi
Ratings:	DC 5V charging from adapter DC 3.7V by Battery

Note: For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 Description of test modes

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2402 MHz	21	2422 MHz	41	2442 MHz	61	2462 MHz
2	2403 MHz	22	2423 MHz	42	2443 MHz	62	2463 MHz
3	2404 MHz	23	2424 MHz	43	2444 MHz	63	2464 MHz
4	2405 MHz	24	2425 MHz	44	2445 MHz	64	2465 MHz
5	2406 MHz	25	2426 MHz	45	2446 MHz	65	2466 MHz
6	2407 MHz	26	2427 MHz	46	2447 MHz	66	2467 MHz
7	2408 MHz	27	2428 MHz	47	2448 MHz	67	2468 MHz
8	2409 MHz	28	2429 MHz	48	2449 MHz	68	2469 MHz
9	2410 MHz	29	2430 MHz	49	2450 MHz	69	2470 MHz
10	2411 MHz	30	2431 MHz	50	2451 MHz	70	2471 MHz
11	2412 MHz	31	2432 MHz	51	2452 MHz	71	2472 MHz
12	2413 MHz	32	2433 MHz	52	2453 MHz	72	2473 MHz
13	2414 MHz	33	2434 MHz	53	2454 MHz	73	2474 MHz
14	2415 MHz	34	2435 MHz	54	2455 MHz	74	2475 MHz
15	2416 MHz	35	2436 MHz	55	2456 MHz	75	2476 MHz
16	2417 MHz	36	2437 MHz	56	2457 MHz	76	2477 MHz
17	2418 MHz	37	2438 MHz	57	2458 MHz	77	2478 MHz
18	2419 MHz	38	2439 MHz	58	2459 MHz	78	2479 MHz
19	2420 MHz	39	2440 MHz	59	2460 MHz	79	2480 MHz
20	2421 MHz	40	2441 MHz	60	2461 MHz		

Note: Test performed at the lowest/middle/highest frequencies selected in the list above for EUT supported while working on specified mode.

Pretest Mode	Description
Transmitting mode	Low channel: 2402MHz
	Middle channel: 2440MHz
	High channel: 2480MHz
Receiver mode	Low channel: 2402MHz

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Supply Voltage			
	supply power V	Rated module power V	Tolerance (%)
Normal	3.7	3.3	
+10%	4.07	3.3	0
-10%	3.33	3.3	0
Others			
Temperature (°C)		20-25	
Relative humidity		54 %.	
ATM Pressure:		1010 mbar	
Note 1: When the input voltage is reduced or increased by 10%, the regulator voltage changes of less than 1%. So the following test items are conducted in the normal voltage.			

2.4 Block diagram showing the configuration of system tested

Transmitting mode



2.5 Description of support units (conducted mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
1	Mouse	SaikoMausu	189B	EUT

Note:

1. The support equipment was authorized by Declaration of Confirmation.
2. For detachable type I/O cable should be specified the length in cm in 『Length』 column.
3. “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 Measurement equipment list

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2026/6/27
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2026/6/27
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2026/6/27
4	Communication test set	R&S	CMW500	108058	V3.5.80	2026/6/27
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2026/6/27
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2026/6/27
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2026/6/27
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2026/6/27
9	2.4 GHz Filter	Shenxiang	MSF2400-24 83.5MS-1154	20181015001	/	2026/6/29
10	5 GHz Filter	Shenxiang	MSF5150-58 50MS-1155	20181015001	/	2026/6/29
11	Filter	Xingbo	XBLBQ-DZA 120	190821-1-1	/	2026/6/29
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2026/6/27
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2026/6/27
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	/	2027/6/21
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2026/6/27
18	Amplifier	HP	8447E	2945A02747	/	2026/6/27

19	Amplifier	Agilent	8449B	3008A01838	/	2026/6/27
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2026/6/27
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2026/6/27
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2026/6/27
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2026/6/27
26	Amplifier	AEROFLEX	Aeroflex	097	/	2026/6/27
27	Power Metter	KEYSIGHT	N1912AP	N/A	A.05.00	2026/6/27
28	DC power supply	Agilent	E3640A	MY53050046	/	2026/6/27

Remark: Calibration institution "Guangzhou Lisai Measurement and Testing Co., LTD."


3 TEST CONDITIONS AND RESULTS

3.1 Frequency error

3.1.1 Limit

Item	Limits
Frequency Error	+/-50ppm

3.1.2 Test configuration



3.1.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: non-modulation

Spectrum Condition:

Frequency: test frequency

Span: 2000 kHz

RBW: 10 kHz

VBW: 10 kHz

Sweep time: Auto

Detector mode: Positive peak


Indication mode: max hold

3.1.4 Test results


Test voltage (V)	Frequency (MHz)	Read (MHz)	Deviation (MHz)	Tolerance (ppm)	Limit (ppm)	Result
Normal Voltage	2402	2402.016	0.016	6.661	+/-50.00	Pass
	2440	2440.016	0.016	6.557		
	2480	2480.017	0.017	6.855		

Note: Below test graph is the worst data.


Normal Voltage



2402MHz



2440MHz




2480MHz

3.2 Antenna output power and output power tolerance

3.2.1 Limit

Item	Limits
Antenna Power Density	$\leq 3\text{mW/MHz}$ (FH form 2427 - 2470.75MHz) $\leq 10\text{mW/MHz}$ (OFDM, DS-SS from 2400~2483.5MHz) $\leq 10\text{mW}$ (Other from 2400~2483.5MHz)
Antenna Power Error	+20% (Base on manufacturer declare antenna power density)

3.2.2 Test configuration



3.2.3 Test procedure

Step 1:

Connect the UUT to the spectrum analyzer as TEST CONFIGURATION and use the following settings:

- Centre Frequency: The centre frequency of the channel under test.
- RBW: 1 MHz
- VBW: 1 MHz
- Span: Wide enough to cover the complete power envelope of the signal of the UUT.
- Detector: Peak
- Trace Mode: Max Hold

Step 2:

When the trace is complete, find the peak value of the power envelope and record the frequency.




Step 3:

Make the following changes to the settings of the spectrum analyzer:

- Centre Frequency: Equal to the frequency recorded in step 2.
- Span: 0 MHz
- RBW: 1 MHz
- VBW: 1 MHz
- Detector: RMS
- Trace Mode: Max Hold

3.2.4 Test results

Test voltage	Channel (MHz)	Average burst power(dBm)	Output power (mW)	Limit (mW)	Rated output power (mW)	Tolerance (%)	Limit	Result
Normal Voltage	2402	1.482	1.407	10	2	-29.665	20%	Pass
	2440	1.656	1.464	10	2	-26.790		
	2480	1.140	1.300	10	2	-34.992		


Test condition:	Normal Voltage	Test graph
		
2402MHz		
		
2480MHz		

3.3 Occupied bandwidth and spreading bandwidth

3.3.1 Limit

Item	Limits
Occupied Bandwidth:	FH $\leq$ 83.5 MHz; OFDM $\leq$ 40MHz, DS $\leq$ 26 MHz; Others $\leq$ 26 MHz

3.3.2 Test configuration



3.3.3 Test procedure

1. Setting of SA is following as follow:

RBW: 300 kHz

VBW: 300 kHz

Sweep time: Auto

Sweep Mode: Continuous sweep

Detect mode: Positive peak


Trace mode: Max hold

- EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 99% of occupied bandwidth to measure occupied bandwidth.
- EUT have transmitted the maximum modulation signal and fixed channelize. SA set to 90% of occupied bandwidth to measure spread bandwidth.
- Spread Factor=Spread Bandwidth/modulation rate. The modulation rate: MR=1.375Mbps for 2.4g


3.3.4 Test results

Test voltage (V)	Channel (MHz)	Occupy 99% Bandwidth (MHz)	Limit (MHz)	Result
Normal Voltage	2402	1.0433	<26	Pass
	2440	1.0441		
	2480	1.0468		


Normal Voltage: 99% Bandwidth



2402MHz



2440MHz



2480MHz

Test voltage (V)	Channel (MHz)	Spread 90% Bandwidth(MHz)	Spread Factor	Spread Bandwidth Limit (MHz)	Spread Factor Limit	Result
Normal Voltage	2402	0.6578	N/A	>0.5	N/A	Pass
	2440	0.6647				
	2480	0.8200				

Note: N/A means not applicable to this modulation type.

Normal Voltage: 90% Bandwidth




3.4 Unwanted emission strength

3.4.1 Limit

Item	Limits
TX Spurious Emission	$\leq 2.5 \mu\text{W/MHz}$ ($30\text{MHz} \leq f \leq 1000\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($1000\text{MHz} < f \leq 2387\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2387\text{MHz} < f \leq 2400\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2483.5\text{MHz} \leq f < 2496.5\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($2496.5\text{MHz} \leq f < 12500\text{MHz}$)

3.4.2 Test configuration



3.4.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.5GHz

RBW: 100 kHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

VBW: 100 kHz (30MHz-1GHz), 1MHz (1GHz-12.5GHz)

Sweep time: Auto



Detector mode: Positive peak

Indication mode: max hold


3.4.4 Test results

Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
Low	30MHz≤f≤1000MHz	912.7	-53.55	0.044	2.5	PASS
	1000MHz < f≤2387MHz	2367.58	-42.4	0.058	2.5	PASS
	2387MHz < f≤2400MHz	2399.66	-27.11	1.945	25	PASS
	2483.5MHz≤f < 2496.5MHz	2491.53	-42.83	0.052	25	PASS
	2496.5MHz≤f < 12750MHz	3132.22	-40.98	0.080	2.5	PASS
Middle	30MHz≤f≤1000MHz	988.36	-53.6	0.004	2.5	PASS
	1000MHz < f≤2387MHz	2144.28	-42.47	0.057	2.5	PASS
	2387MHz < f≤2400MHz	2397.56	-42.02	0.063	25	PASS
	2483.5MHz≤f < 2496.5MHz	2483.71	-42.34	0.058	25	PASS
	2496.5MHz≤f < 12750MHz	8956.21	-41.04	0.079	2.5	PASS
High	30MHz≤f≤1000MHz	928.22	-52.75	0.005	2.5	PASS
	1000MHz < f≤2387MHz	2288.52	-41.14	0.077	2.5	PASS
	2387MHz < f≤2400MHz	2392.11	-42.56	0.055	25	PASS
	2483.5MHz≤f < 2496.5MHz	2483.79	-39.86	0.103	25	PASS
	2496.5MHz≤f < 12750MHz	12657.72	-40.89	0.081	2.5	PASS


Test channel: 2402MHz



30MHz~1GHz




1GHz~2.387GHz





2.387GHz~2.4 GHz

2.4835GHz~2.4965GHz





2.4965GHz~12.5GHz

Test channel: 2440MHz




30MHz~1GHz

1GHz~2.387GHz





2.387GHz~2.4 GHz

2.4835GHz~2.4965GHz





2.4965GHz~12.5GHz

Test channel: 2480MHz




30MHz~1GHz

1GHz~2.387GHz



2.387GHz~2.4 GHz

2.4835GHz~2.4965GHz




2.4965GHz~12.5GHz

3.5 Secondary radiated emission strength

3.5.1 Limit

Item	Limits
RX Spurious Emission:	$\leq 4\text{nW}$ ($f < 1\text{GHz}$)
	$\leq 20\text{nW}$ ($1\text{GHz} \leq f$)

3.5.2 Test configuration



3.5.3 Test procedure

The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

EUT Condition: modulation

Spectrum Condition:

Frequency: 30MHz-12.75GHz

RBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.75GHz)

VBW: 100 KHz (30MHz-1GHz), 1MHz (1GHz-12.75GHz)

Sweep time: Auto


Detector mode: Positive peak

Indication mode: max hold

3.5.4 Test results

Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
L	30MHz≤f≤1000MHz	790.48	-73.71	0.043	4	PASS
	1000MHz < f≤12750MHz	4560.25	-57.81	1.656	20	PASS

30MHz~1GHz




1GHz~12.75GHz




Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
M	30MHz≤f≤1000MHz	697.36	-73.43	0.045	4	PASS
	1000MHz < f≤12750MHz	11751.25	-61.1	0.776	20	PASS

30MHz~1GHz




1GHz~12.75GHz




Test channel	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
H	30MHz≤f≤1000MHz	939.86	-72.91	0.051	4	PASS
	1000MHz < f≤12750MHz	2680.25	-61.25	0.750	20	PASS

30MHz~1GHz



1GHz~12.75GHz



3.6 Transmission Antenna Gain(EIRP Antenna Power) Measurement

3.6.1 Limit

Ltem	Limits
EIRP Power Density	$\leq 12.14 \text{ dBm/MHz}$ (OFDM.DS from 2400-2483.5MHz) $\leq 12.14 \text{ dBm}$ (Other from 2400-2483.5MHz)
Remark: This test item will not be applied to Antenna gain is lower than 3.55dBi.	

3.6.2 Test Procedure

1. Set EUT ad measuring antenna at the same height and roughly facing aech other.
2. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of EUT height and swing it to find the maximum output of the measuring antenna. The output level at the spectrum analyzer is read sa "E".
3. Remove the EUT from the turn table and put the replacing antenna facing to measuring antenna at same height. Set the standard signal generator (SSG) at same frequency and transmit on then receive the signal.
4. Swing the replacing antenna give a maximum receiving level.
5. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of replacing antenna height and swing it to find the maximum receiving level.
6. Set SSG output power at Pt to give the equivalent output level of "E" or caluate Pt with SSG output which gives the nearest of "E" and difference ($\pm 1\text{dB}$).Record the Pt.
7. Calculate EIRP by the formula below $\text{EIRP} = G_t - L + P_t$
 Gt: gain of replacing antenna (dBi)
 L: feeder loss between SSG and replacing antenna
 Pt: Output power of the SSG
8. If the antenna for the EUT has circular polarization. Sum of V-field and H-field will be result if measuring antenna is linear polarization.

3.6.3 Test results

Test voltage	Test modulation	Output power (dBm/MHz)	Gain (dBi)	EIRP (dBm/MHz)	Result
Normal Voltage	GFSK	1.656	2.34	3.996	Pass

3.7 Construction protection method

3.7.1 Requirement

The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily

3.7.2 Confirmation method

☐	Sealed with special screws.
☐	Plastic chassis is being welded using ultrasonic wavs.
☐	Chassis is glued using a special adhesive.
☐	Metal covers are spot-fused.
☐	Cover is specially interlocked.
☐	RF and Modulation components are covered with shielding case and this shielding case is soldered.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is welded using BGA Method.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is glued at its lead with a special adhesive.
☐	Shield case is welded ant RF and modulations parts, and ID-ROM is glued with a non-transparent laminating agent.
☒	Other: All RF and modulation section packet in one IC, and IC is welded using BGA Method, and RF module is welded on the main board, end-User can't open it easily.

3.7.3 The photos of construction protection

The red circle is welding point.



3.8 Interference prevention function


3.8.1 Limit

Item	Limits
Identification code	≥ 48 bits

3.8.2 Measuring ID code software

Item	Limits
MAC IP List	MAC Scan

3.8.3 Test setup



3.8.4 Test procedure


1. In the case that the EUT has the function of automatically transmitting the identification code:
 - a. Transmit the predetermined identification codes from EUT.
 - b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code:
 - a. Transmit the predetermined identification codes from the counterpart.
 - b. Check if communication is normal.
 - c. Transmit the signals other than predetermined ID codes from the counterpart.
 - d. Check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

3.8.5 Test result

PASS

Bluetooth Device Address: 2222C88A0249

4 TEST SETUP PHOTOS OF EUT



***** END OF REPORT *****