NCC Test Report

Equipment	:	**HD 4.40BT** **(Refer to item 1.1.1 for more details)**
Model No.	:	**SCBT6** **(Refer to item 1.1.1 for more details)**
Brand Name	:	**Sennheiser**
Applicant	:	**Sennheiser Communications A/S**
Address	:	**Industriparken 27, Ballerup 2750, Denmark**
Standard	:	**LP0002 Section 3.10.1 (2018-01-10)**
Received Date	:	**Aug. 29, 2016**
Tested Date	:	**Sep. 08 ~ Sep. 21, 2016**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: **Approved by:**

Along Chen / Assistant Manager **Gary Chang / Manager**

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 8
1.3 Test Setup Chart 8
1.4 Test Equipment List and Calibration Data 9
1.5 Test Standards 10
1.6 Deviation from Test Standard and Measurement Procedure 10
1.7 Measurement Uncertainty 10

2 TEST CONFIGURATION 11

2.1 Testing Condition 11
2.2 The Worst Test Modes and Channel Details 11

3 TRANSMITTER TEST RESULTS 12

3.1 Conducted Emissions 12
3.2 6dB and Occupied Bandwidth 15
3.3 RF Output Power 17
3.4 Power Spectral Density 19
3.5 Emissions in Restricted Frequency Bands 21
3.6 Emissions in non-restricted Frequency Bands 33

4 RECEIVER TEST RESULTS 36

4.1 Radiated Emissions 36

5 TEST LABORATORY INFORMATION 42

Release Record

Report No.	Version	Description	Issued Date
TR682901-06AE	Rev. 01	Initial issue	Mar. 19, 2019

Summary of Test Results

NCC Rules	Test Items	Measured	Result
2.3	AC Power Line Conducted Emissions	[dBuV]: 0.369MHz 39.33 (Margin -9.19dB) - AV	Pass
3.10.1.5 2.8	Radiated Emissions	[dBuV/m at 3m]: 7320.00MHz 49.32 (Margin -4.68dB) - AV	Pass
3.10.1.2(1)(C)	Maximum Output Power	Power [dBm]: 9.58	Pass
3.10.1.6(2)(A)	6dB Bandwidth	Meet the requirement of limit	Pass
3.10.1.6(2)(B)	Power Spectral Density	Meet the requirement of limit	Pass
3.10.1.4	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared values of gain for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of the gain.

1 General Description

1.1 Information

This is a Class II Permissive Change report (C2PC).
This report is issued as a supplementary report to original ICC report no. TR682901AE. The difference is concerned with following items:

✧ Addition of product name, MB 360

Due to no affect any test items, all test results remain unchanged.

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
Sennheiser	SCBT6	HD 4.40BT	---
	SCBT7	HD 4.50BTNC	Having components for Active Noise Cancellation
		MB 360	Office version

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	V4.0 LE	2402-2480	0-39 [40]	1 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

1.1.3 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	PIFA	2	---	---

1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from host 3.7Vdc from battery

1.1.5 Accessories

Accessories		
No.	**Equipment**	**Description**
1	Battery	Brand Name: SYNergy ScienTech Corp. Model Name: AHB622540PCT-02 Power Rating: Typical Voltage: 3.7Vdc, 630mAh Charging Voltage: 4.2Vdc, 262mAh
2	Audio cable	1.4m non-shielded without core
3	USB cable (for charging use)	1.07m shielded cable without core.

1.1.6 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.7 Test Tool and Duty Cycle

Test tool	Blue Tool, ver. 2.5
Duty cycle of test signal (%)	68.52%
Duty Factor (dB)	1.64

1.1.8 Power Setting

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	Default	Default	Default

1.2 Local Support Equipment List

Support Equipment List					
No.	**Equipment**	**Brand**	**Model**	**FCC ID**	**Signal cable / Length (m)**
1	Notebook	DELL	Latitude E6430	DoC	USB, 1.07m shielded.
2	Notebook	DELL	Latitude E6430	DoC	---

1.3 Test Setup Chart

Test Setup Diagram (Battery mode)



Note: The support notebook is disconnected from EUT and removed from test table when EUT is set to transmit continuously.

Test Setup Diagram (Charging mode)



1. USB, 1.07m shielded

1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
EMC Receiver	R&S	ESCS 30	100169	Oct. 21, 2015	Oct. 20, 2016
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2015	Nov. 12, 2016
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 21, 2015	Dec. 20, 2016
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101498	Dec. 13, 2015	Dec. 12, 2016
Receiver	Agilent	N9038A	MY53290044	Oct. 14, 2015	Oct. 13, 2016
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 26, 2016	Apr. 25, 2017
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 24, 2016	Feb. 23, 2017
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Preamplifier	EMC	EMC02325	980225	Aug. 05, 2016	Aug. 04, 2017
Preamplifier	Agilent	83017A	MY53270014	Aug. 22, 2016	Aug. 21, 2017
Preamplifier	EMC	EMC184045B	980192	Aug. 24, 2016	Aug. 23, 2017
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 05, 2016	Feb. 04, 2017
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 05, 2016	Feb. 04, 2017
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 05, 2016	Feb. 04, 2017
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 05, 2016	Feb. 04, 2017
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 05, 2016	Feb. 04, 2017
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 05, 2016	Feb. 04, 2017
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 16, 2015	Nov. 15, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2016	Feb. 16, 2017
Power Meter	Anritsu	ML2495A	1218007	Oct. 14, 2015	Oct. 13, 2016
Power Sensor	Anritsu	MA2411B	1207367	Oct. 14, 2015	Oct. 13, 2016
DC POWER SOURCE	GW INSTEK	GPC-3060D	EM884797	Oct. 20, 2015	Oct. 19, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

LP0002 Section 3.10.1 (2018-01-10)
ANSI C63.10-2013
ANSI C63.4-2014
FCC KDB 558074 D01 15.247 Meas Guidance v05r01

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.130 Hz
Conducted power	±0.808 dB
Power density	±0.583 dB
Conducted emission	±2.715 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.96 dB
Radiated emission > 1GHz	±5.51 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	25°C / 55%	Howard Huang
Radiated Emissions	03CH03-WS	23°C / 66%	Aska Huang
RF Conducted	TH01-WS	23°C / 65%	Brad Wu

- FCC site registration No.: 207696
- IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Mode	Test Configuration
AC Power Line Conducted Emissions	Charging	---	---	TX	2
Radiated Emissions ≤ 1GHz	BT LE Charging	2402 ---	1Mbps ---	TX	1 2
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	TX	1
Maximum Output Power	BT LE	2402, 2440, 2480	1Mbps	TX	1
6dB bandwidth					
Power spectral density					

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
2. The EUT had been tested by following test configurations.
   1) Configuration 1: Model SCBT7, Battery mode
   2) Configuration 2: Model SCBT7, Charging mode

Test item	Mode	Test Frequency (MHz)	Data Rate	Mode
Radiated Emissions	BT LE	2402	1Mbps	1

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
2. The EUT had been tested by following test configurations.
   Configuration 1: Model SCBT7, Battery mode

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Configuration 2: Model SCBT7, Charging mode

3.1.4 Test Result of Conducted Emissions

Mode	Charging	**Test Freq. (MHz)**	---
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.294	31.66	50.41	-18.75	31.51	0.12	0.03	Average
2	0.294	34.48	60.41	-25.93	34.33	0.12	0.03	QP
3@	0.369	38.07	48.52	-10.45	37.91	0.13	0.03	Average
4	0.369	40.98	58.52	-17.54	40.82	0.13	0.03	QP
5	1.829	11.47	46.00	-34.53	11.23	0.16	0.08	Average
6	1.829	25.50	56.00	-30.50	25.26	0.16	0.08	QP
7	2.554	9.29	46.00	-36.71	9.03	0.17	0.09	Average
8	2.554	23.02	56.00	-32.98	22.76	0.17	0.09	QP
9	4.478	12.71	46.00	-33.29	12.39	0.20	0.12	Average
10	4.478	26.23	56.00	-29.77	25.91	0.20	0.12	QP
11	7.329	18.47	50.00	-31.53	18.10	0.22	0.15	Average
12	7.329	33.79	60.00	-26.21	33.42	0.22	0.15	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Mode	Charging	Test Freq. (MHz)	---
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.150	32.31	56.00	-23.69	32.16	0.13	0.02	Average
2	0.150	38.90	66.00	-27.10	38.75	0.13	0.02	QP
3@	0.369	39.33	48.52	-9.19	39.16	0.14	0.03	Average
4	0.369	42.82	58.52	-15.70	42.65	0.14	0.03	QP
5	0.885	22.54	46.00	-23.46	22.35	0.13	0.06	Average
6	0.885	29.52	56.00	-26.48	29.33	0.13	0.06	QP
7	1.610	20.04	46.00	-25.96	19.81	0.16	0.07	Average
8	1.610	30.38	56.00	-25.62	30.15	0.16	0.07	QP
9	4.746	14.60	46.00	-31.40	14.28	0.19	0.13	Average
10	4.746	26.27	56.00	-29.73	25.95	0.19	0.13	QP
11	7.486	9.92	50.00	-40.08	9.53	0.24	0.15	Average
12	7.486	24.79	60.00	-35.21	24.40	0.24	0.15	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures

6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 30 kHz, Video bandwidth = 100 kHz.
2. Detector = Sample, Trace mode = max hold.
3 Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.709	1.03	500
BT LE	2440	0.700	1.03	500
BT LE	2480	0.696	1.03	500

Worst Plots	
6dB Bandwidth	**99% Occupied Bandwidth**
	

3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

☒ Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

☐ Antenna gain > 6dBi

☐ Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB

☐ Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

☒ Maximum Peak Conducted Output Power

☐ **Spectrum analyzer**

1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.

☒ **Power meter**

1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

☒ Maximum Conducted Average Output Power (For reference only)

☒ **Power meter**

1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup

3.3.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	Peak Power			Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
		Power (mW)	Power (dBm)	Limit (dBm)			
BT LE	2402	6.97	8.43	30	2	10.43	36
BT LE	2440	8.38	9.23	30	2	11.23	36
BT LE	2480	9.08	**9.58**	30	2	11.58	36

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	6.59	8.19	---
BT LE	2440	8.20	9.14	---
BT LE	2480	8.81	**9.45**	---

Note: Average power is for reference only

3.4 Power Spectral Density

3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

☒ Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.

1. Set the RBW = 3kHz, VBW = 10kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

☐ Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.

1. Set the RBW = 100kHz, VBW = 300 kHz.
2. Detector = RMS, Sweep time = auto couple.
3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
4. Perform the measurement over a single sweep.
5. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-8.08	8
BT LE	2440	-6.90	8
BT LE	2480	-6.55	8

Worst Plot


3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



Configuration 1: Model SCBT7, Battery mode

3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2480
Polarization	Horizontal	**Test Configuration**	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	22.39	40.00	-17.61	30.45	-8.06	Peak	---	---
2	159.98	21.83	43.50	-21.67	29.90	-8.07	Peak	---	---
3	245.34	22.08	46.00	-23.92	31.57	-9.49	Peak	---	---
4	423.82	27.41	46.00	-18.59	31.91	-4.50	Peak	---	---
5	534.40	27.55	46.00	-18.45	29.98	-2.43	Peak	---	---
6	588.72	31.01	46.00	-14.99	32.16	-1.15	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	38.73	22.63	40.00	-17.37	31.27	-8.64	Peak	---	---
2	167.74	22.15	43.50	-21.35	30.54	-8.39	Peak	---	---
3	377.26	25.99	46.00	-20.01	31.74	-5.75	Peak	---	---
4	477.17	27.85	46.00	-18.15	31.26	-3.41	Peak	---	---
5	560.59	29.14	46.00	-16.86	31.00	-1.86	Peak	---	---
6	701.24	31.20	46.00	-14.80	30.72	0.48	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal	**Test Configuration**	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.71	54.00	-15.29	39.82	-1.11	Average	166	296
2	2390.00	51.74	74.00	-22.26	52.85	-1.11	Peak	166	296
3	2498.00	39.99	54.00	-14.01	40.53	-0.54	Average	166	296
4	2498.00	51.61	74.00	-22.39	52.15	-0.54	Peak	166	296
5	4804.00	41.72	54.00	-12.28	36.46	5.26	Average	224	264
6	4804.00	49.75	74.00	-24.25	44.49	5.26	Peak	224	264

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.86	54.00	-15.14	39.97	-1.11	Average	169	0
2	2390.00	51.38	74.00	-22.62	52.49	-1.11	Peak	169	0
3	2498.00	39.96	54.00	-14.04	40.50	-0.54	Average	169	0
4	2498.00	51.31	74.00	-22.69	51.85	-0.54	Peak	169	0
5	4804.00	41.83	54.00	-12.17	36.57	5.26	Average	238	265
6	4804.00	49.64	74.00	-24.36	44.38	5.26	Peak	238	265

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2336.00	38.94	54.00	-15.06	40.31	-1.37	Average	177	299
2	2336.00	51.13	74.00	-22.87	52.50	-1.37	Peak	177	299
3	2491.00	40.18	54.00	-13.82	40.76	-0.58	Average	177	299
4	2491.00	51.60	74.00	-22.40	52.18	-0.58	Peak	177	299
5	4880.00	40.78	54.00	-13.22	35.34	5.44	Average	171	286
6	4880.00	48.74	74.00	-25.26	43.30	5.44	Peak	171	286
7	7320.00	49.32	54.00	-4.68	39.05	10.27	Average	169	230
8	7320.00	57.85	74.00	-16.15	47.58	10.27	Peak	169	230

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2336.00	39.80	54.00	-14.20	41.17	-1.37	Average	148	14
2	2336.00	51.10	74.00	-22.90	52.47	-1.37	Peak	148	14
3	2491.00	41.43	54.00	-12.57	42.01	-0.58	Average	148	14
4	2491.00	51.98	74.00	-22.02	52.56	-0.58	Peak	148	14
5	4880.00	42.50	54.00	-11.50	37.06	5.44	Average	245	22
6	4880.00	50.15	74.00	-23.85	44.71	5.44	Peak	245	22
7	7320.00	46.56	54.00	-7.44	36.29	10.27	Average	172	129
8	7320.00	56.12	74.00	-17.88	45.85	10.27	Peak	172	129

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2375.00	40.00	54.00	-14.00	41.18	-1.18	Average	162	291
2	2375.00	51.00	74.00	-23.00	52.18	-1.18	Peak	162	291
3	2483.50	42.94	54.00	-11.06	43.56	-0.62	Average	162	291
4	2483.50	54.37	74.00	-19.63	54.99	-0.62	Peak	162	291
5	4960.00	41.22	54.00	-12.78	35.58	5.64	Average	154	284
6	4960.00	49.57	74.00	-24.43	43.93	5.64	Peak	154	284
7	7440.00	48.64	54.00	-5.36	38.09	10.55	Average	172	244
8	7440.00	57.69	74.00	-16.31	47.14	10.55	Peak	172	244

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2375.00	39.94	54.00	-14.06	41.12	-1.18	Average	161	357
2	2375.00	51.18	74.00	-22.82	52.36	-1.18	Peak	161	357
3	2483.50	44.69	54.00	-9.31	45.31	-0.62	Average	161	357
4	2483.50	55.66	74.00	-18.34	56.28	-0.62	Peak	161	357
5	4960.00	44.15	54.00	-9.85	38.51	5.64	Average	236	266
6	4960.00	50.88	74.00	-23.12	45.24	5.64	Peak	236	266
7	7440.00	45.54	54.00	-8.46	34.99	10.55	Average	162	134
8	7440.00	55.05	74.00	-18.95	44.50	10.55	Peak	162	134

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Configuration 2: Model SCBT7, Charging mode

3.5.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Mode	Charging	**Test Freq. (MHz)**	---
Polarization	Horizontal	**Test Configuration**	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	55.22	28.29	40.00	-11.71	36.67	-8.38	Peak	---	---
2	165.80	27.03	43.50	-16.47	35.34	-8.31	Peak	---	---
3	232.73	28.77	46.00	-17.23	38.92	-10.15	Peak	---	---
4	332.64	34.65	46.00	-11.35	41.61	-6.96	Peak	---	---
5	415.09	33.57	46.00	-12.43	38.31	-4.74	Peak	---	---
6	798.24	38.36	46.00	-7.64	36.14	2.22	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Mode	Charging	Test Freq. (MHz)	---
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	55.22	32.46	40.00	-7.54	40.84	-8.38	Peak	---	---
2	165.80	26.77	43.50	-16.73	35.08	-8.31	Peak	---	---
3	232.73	27.69	46.00	-18.31	37.84	-10.15	Peak	---	---
4	332.64	29.37	46.00	-16.63	36.33	-6.96	Peak	---	---
5	427.70	33.25	46.00	-12.75	37.64	-4.39	Peak	---	---
6	796.30	39.76	46.00	-6.24	37.58	2.18	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures

Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement

1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.6.3 Test Setup



3.6.4 Test Result of Emissions in non-restricted Frequency Bands

TX Freq 2402MHz / 30MHz~25GHz (down 20dBc)	TX Freq 2440MHz / 30MHz~25GHz (down 20dBc)
	
	

TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)	---
	---
	---

4 Receiver Test Results

4.1 Radiated Emissions

4.1.1 Limit of Radiated Emissions

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

4.1.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=3MHz and RMS detector is for average measured value of radiated emission above 1GHz.

4.1.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



4.1.4 Receiver Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	45.52	22.41	40.00	-17.59	30.50	-8.09	Peak	---	---
2	150.28	23.23	43.50	-20.27	31.44	-8.21	Peak	---	---
3	377.26	25.49	46.00	-20.51	31.24	-5.75	Peak	---	---
4	432.55	26.96	46.00	-19.04	31.21	-4.25	Peak	---	---
5	474.26	28.38	46.00	-17.62	31.83	-3.45	Peak	---	---
6	627.52	30.65	46.00	-15.35	31.22	-0.57	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	38.73	21.79	40.00	-18.21	30.43	-8.64	Peak	---	---
2	170.65	22.36	43.50	-21.14	30.92	-8.56	Peak	---	---
3	342.34	23.96	46.00	-22.04	30.63	-6.67	Peak	---	---
4	424.79	26.02	46.00	-19.98	30.50	-4.48	Peak	---	---
5	534.40	28.19	46.00	-17.81	30.62	-2.43	Peak	---	---
6	639.16	30.28	46.00	-15.72	30.73	-0.45	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

4.1.5 Receiver Emissions (Above 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1398.00	23.66	54.00	-30.34	29.05	-5.39	Average	100	282
2	1398.00	36.41	74.00	-37.59	41.80	-5.39	Peak	100	282
3	2223.00	25.45	54.00	-28.55	27.36	-1.91	Average	100	118
4	2223.00	37.56	74.00	-36.44	39.47	-1.91	Peak	100	118
5	3080.00	27.83	54.00	-26.17	26.82	1.01	Average	100	260
6	3080.00	40.23	74.00	-33.77	39.22	1.01	Peak	100	260

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1398.00	24.21	54.00	-29.79	29.60	-5.39	Average	100	320
2	1398.00	36.35	74.00	-37.65	41.74	-5.39	Peak	100	320
3	2223.00	26.24	54.00	-27.76	28.15	-1.91	Average	100	241
4	2223.00	39.15	74.00	-34.85	41.06	-1.91	Peak	100	241
5	3080.00	27.65	54.00	-26.35	26.64	1.01	Average	100	196
6	3080.00	40.48	74.00	-33.52	39.47	1.01	Peak	100	196

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

5 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

═END═