

NCC RADIO TEST REPORT

Product name	LORA通信調度中控/LoRa Central Control device
Applicant	深圳市普渡科技有限公司
Manufacture	深圳市普渡科技有限公司
Rating(s)	DC5V from adapter
Trademark	PUDU
Model and/or type reference	PMC1-H9
Standard	LP0002:2020
Test Result	Pass

Date of receipt : 07-09-2021

Date of Issue : 08-18-2021


Signature :



NCC RADIO TEST REPORT**Report Reference No.** M210818N2-01

Compiled by (+ signature) Kevin Bothmann

Approved by (+ signature) Jay Gandhi



Date of issue 2021-08-18

Applicant's name 深圳市普渡科技有限公司Address 深圳市南山區西麗街道西麗社區打石一路深圳國際創新谷 1 棟 A 座
501**Manufacture's Name** 深圳市普渡科技有限公司Address 深圳市南山區西麗街道西麗社區打石一路深圳國際創新谷 1 棟 A 座
501**Test specification:**

Standard LP0002: 2020

Test procedure EIA 603、ANSI、FCC/47 CFR/2.1046、2.1047、2.1049、2.1051、2.1053
and 2.1055

Non-standard test method... N/A

Test item description

Product name 通信調度中控/LoRa Central Control device

Trademark PUDU

Model and/or type reference PMC1-H9

Rating(s) DC5V from adapter

Testing Laboratory information

Testing Laboratory Name Electro Magnetic Test, Inc.

Address 1547 Plymouth Street, Mountain View, CA 94043

CAB Identifier Number US0036

Tel..... (650) 965-4000

Fax..... (650) 965-3000

E-mail jgandhi@emtlabs.com

Testing

Date of receipt of test item..... Jul. 09, 2021

Date (s) of performance of tests Jul. 13~ Jul. 23, 2021

Date of Issue Aug. 18, 2021

Test Result..... **Pass**

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Electro Magnetic Test, Inc., which is an independent testing and consulting firm. The test report is based on testing performed Electro Magnetic Test, Inc. personnel according to the measurement procedure described in the test specification given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Federal Government.

Electro Magnetic Test, Inc. is recognized by the following agencies for performing EMI/EMC testing:

COUNTRY	AGENCY	IDENTIFYING #
USA	Federal Communications Commission (FCC) (EMT's test site is recognized by the FCC)	Registration Number: 90576
USA, Canada, Taiwan, Australia/New Zealand, European Community	National Voluntary Lab Accreditation Program (NVLAP) (EMT is accredited by NVLAP. A copy of the NVLAP Scope Of Accreditation is available upon request.)	Lab Code: 200147-0
Canada	Industry Canada	File No.: IC 2804
Japan	Voluntary Control Council For Interference (VCCI)	See Below
	Open Field Test Site "A"	R-589
	Mains Conducted Emissions Test Site "A"	C-604
	Telecom Conducted Emissions Test Site "A"	T-1655
	3 Meter Semi-Anechoic Chamber Site "E"	R-3227
	3 Meter Semi-Anechoic Chamber Site "E" (1GHz – 6GHz)	G-219
	Mains Conducted Emissions Test Site "E"	C-35793
	Telecom Conducted Emissions Test Site "E"	T-1715
Korea	Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (A copy of the Scope Of Accreditation is available upon request)	US0036
Taiwan	Bureau Of Standards, Metrology and Inspection (BSMI)	Reference Number: SL2-IN-E-1024
Australia / New Zealand	Australian Communications Authority (AUSTEL)	*

***THESE AGENCIES DO NOT ISSUE AN IDENTIFYING NUMBER TO TEST LABS.**

Table of Contents	Page
GENERAL REPORT SUMMARY	3
1 . SUMMARY OF TEST RESULTS	6
1.1 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . EMC EMISSION TEST	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
3.1.2 TEST PROCEDURE	16
3.1.3 DEVIATION FROM TEST STANDARD	16
3.1.4 TEST SETUP	16
3.1.5 TEST RESULTS	17
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 RADIATED EMISSION LIMITS	19
3.2.2 TEST PROCEDURE	20
3.2.3 TEST SETUP	20
3.2.4 EUT OPERATING CONDITIONS	21
3.2.5 TEST RESULTS (BLOW 30 MHZ)	22
3.2.6 TEST RESULTS (BETWEEN30 – 1000 MHZ)	22
3.2.7 TEST RESULTS (ABOVE 1000 MHZ)	24
3.2.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	30
4 . OCCUPIED BANDWIDTH TEST	32
4.1 APPLIED PROCEDURES / LIMIT	32
4.1.1 TEST PROCEDURE	32
4.1.2 TEST SETUP	32
4.1.3 EUT OPERATION CONDITIONS	32
4.1.4 TEST RESULTS	33
5 . NUMBER OF HOPPING CHANNEL	35
5.1 APPLIED PROCEDURES / LIMIT	35
5.1.1 TEST PROCEDURE	35
5.1.2 TEST SETUP	35

Table of Contents	Page
5.1.3 EUT OPERATION CONDITIONS	35
5.1.4 TEST RESULTS	36
6 . AVERAGE TIME OF OCCUPANCY	37
6.1 APPLIED PROCEDURES / LIMIT	37
6.1.1 TEST PROCEDURE	37
6.1.2 TEST SETUP	37
6.1.3 EUT OPERATION CONDITIONS	37
6.1.4 TEST RESULTS	38
7 . HOPPING CHANNEL SEPARATION MEASUREMENT	42
7.1 APPLIED PROCEDURES / LIMIT	42
7.1.1 TEST PROCEDURE	42
7.1.2 TEST SETUP	42
7.1.3 EUT OPERATION CONDITIONS	42
7.1.4 TEST RESULTS	43
8 . PEAK OUTPUT POWER TEST	45
8.1 APPLIED PROCEDURES / LIMIT	45
8.1.1 TEST PROCEDURE	45
8.1.2 DEVIATION FROM STANDARD	45
8.1.3 TEST SETUP	45
8.1.4 EUT OPERATION CONDITIONS	45
8.1.5 TEST RESULTS	46
9 . ANTENNA CONDUCTED SPURIOUS EMISSION	48
9.1 APPLIED PROCEDURES / LIMIT	48
9.1.1 TEST PROCEDURE	48
9.1.2 TEST SETUP	48
9.1.3 EUT OPERATION CONDITIONS	48
9.1.4 TEST RESULTS	49
10. ANTENNA REQUIREMENT	53
10.1 STANDARD REQUIREMENT	53
10.2 EUT ANTENNA	53
11. EUT TEST PHOTO	54

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

LP0002 : 2020			
Standard Section	Test Item	Judgment	Remark
3.3	Conducted Emission	PASS	None
3.6	Radiated Spurious Emission	PASS	None
5.8.1.2	Peak Output Power	PASS	None
5.8.1.5	Occupied Bandwidth	PASS	None
5.8.1.5	Hopping Channel Separation	PASS	None
5.8.1.5	Number of Hopping Frequency	PASS	None
5.8.1.5	Dwell Time	PASS	None
5.8.1.4	Restricted Bands	PASS	None
3.2	Antenna Requirement	PASS	None

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	1.38dB
2	Radiated Emission Test	3.17dB
3	RF power,conducted	0.16dB
4	Spurious emissions,conducted	0.21dB
5	All emissions,radiated(<1G)	4.68dB
6	All emissions,radiated(>1G)	4.89dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	通信調度中控/LoRa Central Control device	
Trade Name	PUDU	
Model Name	PMC1-H9	
Serial Model Name	N/A	
Model Difference	N/A	
Product Description	The EUT is a 通信調度中控/LoRa Central Control device	
	Operation Frequency:	920-925 MHz
	Modulation Type:	SSC
	Bandwidth:	125KHz
	Number Of Channel	11CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain(Peak)	5.0 dBi
	Output Power:	13.293dBm (Max.)
Channel List	Please refer to the Note 2.	
Power Rating	DC5.0V from adapter	
Connecting I/O Port(s)	Please refer to the User's Manual	
Products Covered	N/A	
EUT Modification(s)	N/A	
Model difference	N/A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	920.6	09	924.2	--	--
01	921.0	10	924.4	--	--
02	921.4	11	--	--	--
03	922.2	12	--	--	--
04	922.4	13	--	--	--
05	922.6	14	--	--	--
06	923.0	15	--	--	--
07	923.4	16	--	--	--
08	923.8	17	--	--	--

3.

Table for Filed Antenna

Manufacture	Model Name	Antenna Type	Connector	Gain (dBi)
深圳市普渡科技有限公司	DD600449	RG174 Wire 863-928MHZ External suction cup antenna L=0.3 m	N/A	5.0dBi

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00/ CH06/ CH10

For Conducted Emission	
Final Test Mode	Description
Mode 1	CH00/ CH06/ CH10

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00/ CH06/ CH10

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Power Set	17		
Test software Version	V1.0	Test program:	Lora開道固件燒錄工具
Frequency	920.4 MHz	922.4MHz	924.6MHz
Parameters	Default	Default	Default

1. Install a serial debugging tool;
2. USB port for computer connection.
3. Debugging assistant software selected serial port, Baud rate and other data.
4. Browse and select burning files corresponding to test frequency points
5. After the file is sent successfully, the watch can be rebooted for testing, press the volume up button to launch.

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


Block diagram of EUT configuration

CONDUCTED EMISSION

Test mode: mode 1

Non-Conductive Table


10 cm above Ground Plane



Test mode: mode 1

Non-Conductive Table

80 cm above Ground Plane



2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	通信調度中控 /LoRa Central Control device	PUDU	PMC1-H9	N/A	N/A	EUT
E-2	Adapter	Shenzhen GaoFanDe Technology Co.,Ltd	GFD12-0502000 UL	N/A	N/A	AE

Item	Equipment	Mfr/Brand	Model/Type No.	Note
1	RJ45 Line	UGREEN	11268-1m	Test Accessory*

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” or “with ferrite core”; “NO” means “unshielded” or “without ferrite core”
- (4) “*”: In this report, the applicant did not provide the accompanying accessories with the equipment. The accessories were provided by the laboratory (or the applicant) and inspected simultaneously.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
Spectrum Analyzer	Keysight	N9020A	MY53300466	April 29, 2021	1 Year
RF Preselector	Hewlett Packard	85685A	3010A01157	April 29, 2021	1 Year
Quasi-Peak Adapter	Hewlett Packard	85650	2521A00584	April 29, 2021	1 Year
Preamplifier	Com Power	PA-102	1482	April 29, 2021	1 Year
RF Attenuator	Mini-Circuits	CAT-10	Asset #1000	December 08, 2020	1 Year
LISN	Com Power	LI-200	12012	September 09, 2020	1 Year
LISN	Com Power	LI-200	12214	September 09, 2020	1 Year
LISN	Com Power	LI-200	1767	September 09, 2020	1 Year
LISN	Com Power	LI-200	1768	September 09, 2020	1 Year
Biconical Antenna	Com Power	AB-100	01557	December 28, 2020	1 Year
Log Periodic Antenna	Com Power	AL-100	16037	December 21, 2020	1 Year
Horn Antenna	Com Power	AHA-118	711054	December 21, 2020	1 Year
Antenna Mast	Com Power	AM-400	N/A	N/A	N/A
Turntable	Com Power	TT-100	N/A	N/A	N/A
Computer	Dell, Inc.	DHS	DNSV641	N/A	N/A

EMI Test Equipment (Continued)

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
EMI Receiver	Rohde & Schwarz	ESU40	100127	June 12, 2021	1 Year
BiConiLog Antenna	ETS-Lindgren	3142D	00102183	August 13, 2020	1 Year
Horn Antenna (1GHz-18GHz)	ETS-Lindgren	3117	00109294	May 6, 2021	1 Year
Preamplifier	Rohde & Schwarz	TS-PR18	100056	June 12, 2021	1 Year
Pre-Amplifier	Agilent	8449B	3008A00409	June 12, 2021	1 Year
Antenna Mast	ETS-Lindgren	2175	00095727	N/A	N/A
Turntable	ETS-Lindgren	2187-3.0	00118231	N/A	N/A
Computer	Acer	Aspire 8930	85100050123	N/A	N/A
Multi-Function Controller	ETS-Lindgren	2090	00102270	N/A	N/A
Loop Antenna	ARA	PLA-1030/B	1029	May 19, 2021	1 Year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Quasi-peak	Average	Standard
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	LP0002
0.50 -5.0	56.00	46.00	LP0002
5.0 -30.0	60.00	50.00	LP0002

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP




Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 TEST RESULTS

EUT :	通信調度中控/LoRa Central Control device	Model Name. :	PMC1-H9
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2021-07-16
Test Mode :	TX920.4MHz (Low CH-worst case)	Phase :	L
Test Voltage :	AC 110V/60Hz for Adapter		




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss + Pulse limit.
3. '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1539	33.01	9.78	42.79	65.79	-23.00	peak	P
2	0.1695	16.84	9.77	26.61	54.98	-28.37	AVG	P
3	0.2046	29.20	9.75	38.95	63.42	-24.47	peak	P
4	0.2162	14.53	9.75	24.28	52.96	-28.68	AVG	P
5	0.6219	22.88	9.78	32.66	56.00	-23.34	peak	P
6 *	0.6219	18.94	9.78	28.72	46.00	-17.28	AVG	P
7	1.0353	13.37	9.79	23.16	46.00	-22.84	AVG	P
8	1.0431	19.18	9.79	28.97	56.00	-27.03	peak	P
9	3.4212	15.87	9.86	25.73	56.00	-30.27	peak	P
10	3.4680	8.77	9.86	18.63	46.00	-27.37	AVG	P
11	9.5013	13.86	19.64	33.50	60.00	-26.50	peak	P
12	9.5013	2.12	19.64	21.76	50.00	-28.24	AVG	P

EUT :	通信調度中継/LoRa Central Control device	Model Name. :	PMC1-H9
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2021-07-16
Test Mode :	TX920.4MHz (Low CH-worst case)	Phase :	N
Test Voltage :	AC 110V/60Hz for Adapter		



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss + Pulse limit.
3. '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1734	30.77	9.77	40.54	64.80	-24.26	peak	P
2	0.1773	13.60	9.77	23.37	54.61	-31.24	AVG	P
3	0.2280	27.71	9.75	37.46	62.52	-25.06	peak	P
4	0.2280	11.34	9.75	21.09	52.52	-31.43	AVG	P
5	0.6219	10.96	9.78	20.74	46.00	-25.26	AVG	P
6 *	0.6297	25.77	9.78	35.55	56.00	-20.45	peak	P
7	1.5540	19.06	9.80	28.86	56.00	-27.14	peak	P
8	1.5540	4.02	9.80	13.82	46.00	-32.18	AVG	P
9	4.3884	18.63	9.90	28.53	56.00	-27.47	peak	P
10	4.3884	3.04	9.90	12.94	46.00	-33.06	AVG	P
11	9.0879	16.48	19.20	35.68	60.00	-24.32	peak	P
12	9.0879	-0.60	19.20	18.60	50.00	-31.40	AVG	P

Test result: The unit does meet the NCC requirements.

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 3.5, then the 3.6 limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	LIMITS (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to LP0002.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Frequency measurement range:

1 The spectrum shall be measured from the lowest radio frequency signal generated in the device (without going below 9 kHz), and the upper limit of the measurement range shall be decided according to the maximum operating frequency.

1.1 Maximum operating frequency less than 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

1.2 Maximum operating frequency between 10 GHz~30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.

1.3 Maximum operating frequency over 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower.

2 Particular attention should be paid to harmonics and subharmonics of the carrier frequency as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.

Spectrum Parameter		Setting	
Attenuation		Auto	
Start Frequency		1000 MHz	
Stop Frequency		10th carrier harmonic	
Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3MHz
AV	$\geq 98\%$	1MHz	10Hz
	$< 98\%$	1MHz	1/T


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters (For frequencies above 1GHz, table 1.5 meters) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 TEST RESULTS (BLOW 30 MHZ)

There is no detected blow 30MHz

3.2.6 TEST RESULTS (BETWEEN30 – 1000 MHZ)


EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	TX920.6MHz (Low CH-worst case)	Polarization :	Horizontal
Test Power :	DC5V from battery		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	150.007	28.40	-17.03	43.5	-15.10	Peak	Horizontal	Pass
2	249.893	38.67	-12.08	46.0	-7.33	Peak	Horizontal	Pass
3	349.778	38.94	-9.35	46.0	-7.06	Peak	Horizontal	Pass
4	399.963	34.40	-8.57	46.0	-11.60	Peak	Horizontal	Pass
5	550.032	37.32	-6.36	46.0	-8.68	Peak	Horizontal	Pass
6	750.045	36.60	-3.43	46.0	-9.40	Peak	Horizontal	Pass

EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	TX920.6MHz (Low CH-worst case)	Polarization :	Vertical
Test Power :	DC5V from battery		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	49.880	25.74	-11.36	40.0	-14.26	Peak	Vertical	Pass
2	149.765	32.15	-17.05	43.5	-11.35	Peak	Vertical	Pass
3	399.963	30.16	-8.57	46.0	-15.84	Peak	Vertical	Pass
4	449.905	38.20	-8.01	46.0	-7.80	Peak	Vertical	Pass
5	550.032	33.47	-6.36	46.0	-12.53	Peak	Vertical	Pass
6	649.918	34.58	-4.66	46.0	-11.42	Peak	Vertical	Pass

Test result: The unit does meet the NCC requirements.


3.2.7 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	Mode 1(920.4MHz)	Polarization :	Vertical
Test Power :	DC5V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1840.80	65.89	-9.42	56.47	74	-17.53	peak
1840.80	56.60	-9.42	47.18	54	-6.82	AVG
2761.20	54.62	-3.12	51.50	74	-22.50	peak
2761.20	46.64	-3.12	43.52	54	-10.48	AVG
7015.94	44.39	6.20	50.59	74	-23.41	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	Mode 1(920.4MHz)	Polarization :	Horizontal
Test Power :	DC5V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1840.80	66.15	-9.42	56.73	74	-17.27	peak
1840.80	56.59	-9.42	47.17	54	-6.83	AVG
2761.20	58.02	-3.12	54.90	74	-19.10	peak
2761.20	48.61	-3.12	45.49	54	-8.51	AVG
7613.50	42.80	8.78	51.58	74	-22.42	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	Mode 1(922.4MHz)	Polarization :	Vertical
Test Power :	DC5V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1844.80	64.85	-9.42	55.43	74	-18.57	peak
1844.80	55.68	-9.42	46.26	54	-7.74	AVG
2767.20	56.88	-3.09	53.79	74	-20.21	peak
2767.20	48.32	-3.09	45.23	54	-8.77	AVG
7262.53	44.95	7.28	52.23	74	-21.77	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	Mode 1(922.4MHz)	Polarization :	Horizontal
Test Power :	DC5V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1844.80	65.80	-9.42	56.38	74	-17.62	peak
1844.80	55.75	-9.42	46.33	54	-7.67	AVG
2767.20	56.56	-3.09	53.47	74	-20.53	peak
2767.20	48.53	-3.09	45.44	54	-8.56	AVG
7545.75	40.81	8.50	49.31	74	-24.69	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	Mode 1(924.6MHz)	Polarization :	Vertical
Test Power :	DC5V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1849.20	66.67	-9.43	57.24	74	-16.76	peak
1849.20	57.68	-9.43	48.25	54	-5.75	AVG
2773.80	58.91	-3.05	55.86	74	-18.14	peak
2773.80	49.24	-3.05	46.19	54	-7.81	AVG
7937.65	42.88	10.11	52.99	74	-21.01	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-16
Test Mode :	Mode 1(924.6MHz)	Polarization :	Horizontal
Test Power :	DC5V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1849.20	67.64	-9.43	58.21	74	-15.79	peak
1849.20	57.86	-9.43	48.43	54	-5.57	AVG
2773.80	59.68	-3.05	56.63	74	-17.37	peak
2773.80	50.79	-3.05	47.74	54	-6.26	AVG
7666.75	43.07	9.01	52.08	74	-21.92	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.

No any other emissions detected which are tested to compliance with the limit. No recording in the test report.


Test result: The unit does meet the NCC requirements.

3.2.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)


EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC5V from battery
Test Mode :	Mode 1(920.6MHz/924.4MHz)		
Test Date :	2021-07-16		
Note :	1. The transmitter was setup to transmit at the lowest channel (CH00). Then the field strength was measured at 920-925 MHz. 2. The transmitter was setup to transmit at the highest channel (CH10). Then the field strength was measured at 920-925 MHz.		

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant/CF CF(dB)	Act		Limit		Note
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)	
920	H	28.54	--	-1.84	26.70	--	46.00	--	CH00
920	V	27.48	--	-1.84	25.64	--	46.00	--	CH00
925	H	27.85	--	-1.78	26.07	--	46.00	--	CH10
925	V	30.30	--	-1.78	28.52	--	46.00	--	CH10

Horizontal



Vertical



Test result: The unit does meet the NCC requirements.

4. OCCUPIED BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
5.8.1.5	Bandwidth	N/A	920-925	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	3 kHz
VB	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 3KHz, VBW=10KHz, Sweep time = Auto, Span=500KHz.

4.1.2 TEST SETUP



4.1.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.4 TEST RESULTS


EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC5V from battery
Test Mode :	CH00 / CH06/ CH10		
Test Date :	2021-07-12		

Frequency	20dB Bandwidth (kHz)	Result
920.6	135.6	Pass
922.6	132.7	Pass
924.4	139.1	Pass


CH 00



CH 06



CH 10



5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

LP0002			
Section	Test Item	Frequency Range (MHz)	Result
5.8.1.5	Number of Hopping Channel	920-925	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	51kHz
VB	150kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 51KHz, VBW=150kHz, Sweep time = Auto.

5.1.2 TEST SETUP




5.1.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.4 TEST RESULTS

EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC5V from battery
Test Mode :	Hopping Mode		
Test Date :	2021-07-12		

Number of Hopping Channel	Limit
11	≥ 10



6. AVERAGE TIME OF OCCUPANCY


6.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
5.8.1.5	Average Time of Occupancy	0.4sec	920-925	PASS

6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.

6.1.2 TEST SETUP



6.1.3 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.4 TEST RESULTS



EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC5V from battery
Test Mode :	CH00/CH06/CH10		
Test Date :	2021-07-12		

Frequency	Pulse Duration (ms)	Average Time of Occupancy (ms)	Limits (ms)
920.6	99.0	198.0	400
922.6	99.0	198.0	400
924.4	99.01	198.02	400



CH 00



CH 06



CH 10



Note:

1. $99.0 \times 2 = 198.0$ ms; $99.0 \times 2 = 198.0$ ms; $99.01 \times 2 = 198.02$ ms

2. $0.4 \times 11 = 4.4$ s 時間內，占用之平均時間小於 0.4 秒

7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT


Frequency hopping systems operating in the 920-925 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	10 kHz (20dB Bandwidth) / 10 kHz (Channel Separation)
VB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 10 kHz and the video bandwidth of 30 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 10 kHz and the video bandwidth of 30 kHz were utilised for channel separation measurement.

7.1.2 TEST SETUP



7.1.3 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.


7.1.4 TEST RESULTS

EUT :	通信調度中継/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC5V from battery
Test Mode :	CH00 / CH06 / CH10		
Test Date :	2021-07-12		


Frequency MHz	Ch. Separation (KHz)	Limit (20dB bandwidth) (kHz)	Result
920.6	378	135.6	PASS
922.6	378	132.7	PASS
924.4	380	139.1	PASS

Ch. Separation >(20dB bandwidth)


CH 00



CH 06



CH 10



8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
5.1.8.2	Peak Output Power	0.5 watt or 27dBm	920-925	PASS

8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW=300kHz, VBW= 1MHz, Span= 2MHz , Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP




8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


8.1.5 TEST RESULTS

EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC5V from battery
Test Mode :	CH00/ CH06/ CH10		
Test Date :	2021-03-23		


Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
920.6	12.153	27
922.6	12.038	27
924.4	13.292	27



CH 06



CH10



9. ANTENNA CONDUCTED SPURIOUS EMISSION

9.1 APPLIED PROCEDURES / LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in Section 3.6.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

9.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

9.1.2 TEST SETUP



9.1.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.1.4 TEST RESULTS


EUT :	通信調度中控/LoRa Central Control device	Model Name :	PMC1-H9
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC5V from battery
Test Mode :	CH00 / CH10		
Test Date :	2021-07-12		

in any 100kHz bandwidth outside the low frequency band	in any 100 kHz bandwidth outside the high frequency band
Pass	Pass
Result	
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.	

CH00




CH 10



[illegible][illegible]

CH10




10. ANTENNA REQUIREMENT



10.1 STANDARD REQUIREMENT

4.10.3.1.1 requirement: Systems operating in the 920-925 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

10.2 EUT ANTENNA

The antenna is a RG174 Wire 863-928MHZ External suction cup antenna L=0.3 m and no consideration of replacement. Antenna max gain is 5.0 dBi from 920MHz to 925MHz.

11. EUT TEST PHOTO**Radiated Measurement Photos
30MHz-1GHz**

**Radiated Measurement Photos
Above 1GHz****Conducted Measurement Photos**

****End of the report****