NCC RADIO TEST REPORT

Equipment	:	**Smartwatch**
Brand Name	:	**Fitbit**
Model Name	:	**FB511**
Applicant	:	**Fitbit, Inc.** **199 Fremont Street, 14th Floor, San Francisco, CA 94105 USA**
Manufacturer	:	**Fitbit, Inc.** **199 Fremont Street, 14th Floor, San Francisco, CA 94105 USA**
Standard	:	**NCC LP0002 (2018-01-10)**

The product was received on Mar. 20, 2020 and testing was started from Apr. 07, 2020 and completed on Jul. 06, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures NCC LP0002 (2018-01-10) and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Reviewed by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 12
2.6 Measurement Results Explanation Example 12
3 Test Result **13**
3.1 Number of Channel Measurement 13
3.2 Hopping Channel Separation Measurement 15
3.3 Dwell Time Measurement 21
3.4 20dB and 99% Bandwidth Measurement 23
3.5 Output Power Measurement 34
3.6 Conducted Band Edges Measurement 35
3.7 Conducted Spurious Emission Measurement 42
3.8 Radiated Band Edges and Spurious Emission Measurement 52
3.9 AC Conducted Emission Measurement 57
3.10 Antenna Requirements 59
4 List of Measuring Equipment **60**
5 Uncertainty of Evaluation **62**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission
Appendix D. Radiated Spurious Emission Plots
Annex A. Receiver Radiated Emission
Appendix E. Duty Cycle Plots
Appendix F. Setup Photographs

History of this test report

Report No.	Version	Description	Issued Date
TR032014A	01	Initial issue of report	Jul. 22, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	LP0002 3.10.1.6 (1)(A)	Number of Channels	Pass	-
3.2	LP0002 3.10.1.6 (1)(A)	Hopping Channel Separation	Pass	-
3.3	LP0002 3.10.1.6 (1)(A)	Dwell Time of Each Channel	Pass	-
3.4	LP0002 3.10.1.6 (1)(A)	20dB Bandwidth	Pass	-
3.4	-	99% Occupied Bandwidth	Reporting only	-
3.5	LP0002 3.10.1.6 (1)(A)	Peak Output Power	Pass	-
3.6	LP0002 3.10.1.5	Conducted Band Edges	Pass	-
3.7	LP0002 3.10.1.5	Conducted Spurious Emission	Pass	-
3.8	LP0002 3.10.1.5	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 8.54 dB at 45.520 MHz
3.9	LP0002 2.3	AC Conducted Emission	Pass	Under limit 12.48 dB at 0.299 MHz
3.10	LP0002 2.2 3.10.1.3 3.10.1.4	Antenna Requirement	Pass	-
Annex A	LP0002 2.11	Receiver Radiated Emission	Pass	Please refer to Annex A

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Celery Wei

1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, NFC, and GNSS

Product specification subjective to this standard	
Sample 1	Iron strap
Sample 2	Cloth strap
Sample 3	Plastic strap
Antenna Type	WLAN: Ring slot Antenna Bluetooth: Ring slot Antenna GPS: Metal split-ring Antenna NFC: Loop Antenna

Antenna Information				
Bluetooth Antenna	**Brand Name**	N/A	**Peak gain**	-5.8dBi
	Model Name	N/A	**Type**	Ring slot Antenna

Specification of Accessory		
Battery	**Brand Name**	Lishen
	Model Name	SP332427SF-1S1P-PCM
USB Cable	**Brand Name**	N/A
	Model Name	N/A

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- NCC LP0002 (2018-01-10)
- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 2Mbps mode, and recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	**Data Rate / Modulation**		
	Bluetooth BR 1Mbps GFSK	**Bluetooth EDR 2Mbps π/4-DQPSK**	**Bluetooth EDR 3Mbps 8-DPSK**
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	**Bluetooth EDR 2Mbps n/4-DQPSK**		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		

Summary table of Test Cases	
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + GPS Rx + Vibrate + Screen flicker + Battery + USB Cable (Charging from Notebook) for Sample 1 Mode 2: WLAN (2.4GHz) Idle + GPS Rx + Battery + USB Cable (Data Link with Notebook) for Sample 1 Mode 3: Bluetooth Link + MP3 + GPS Rx + Battery + USB Cable (Charging from Adapter) for Sample 1 Mode 4: Bluetooth Idle + GPS Rx + Battery + USB Cable (Charging from Adapter) for Sample 1
Remark: 1. For radiated test cases, the worst mode data rate 2Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 2Mbps, and no other significantly frequencies found in conducted spurious emission. 2. The worst case of conducted emission is mode 1; only the test data of it was reported. 3. For Radiated Test Cases, the tests were performed with Sample 1. 4. Data Link with Notebook means data application transferred mode between EUT and Notebook.	

2.3 Connection Diagram of Test System

<AC Conducted Emission with Notebook Mode>



<AC Conducted Emission with Bluetooth Mode>



<Bluetooth Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	SonyErricsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	Apple	MacBook Pro(A1502)	QDS-BRCM 1080	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	iPod	Apple	A1199	FCC DoC	Shielded, 1.0 m	N/A
6.	LCD Monitor	Dell	PB27UQ	FCC DoC	N/A	Unshielded,1.8m
7.	Adapter	DVE	DSA-5PFM-05 FUS	N/A	N/A	N/A

Remark: Applicant has ensured accessory would not be attached with the product on the market, accessory is provided by lab or applicant for testing.

2.5 EUT Operation Test Setup

The RF test items, utility “Ters Term v.4.102” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.
Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

Number of Hopping Channel Plot on Channel 00 - 78



Date: 11.JUN.2020 12:38:35



Date: 11.JUN.2020 12:40:28

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peaks of two adjacent channels;
   RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 11.JUN.2020 11:16:08

Channel Separation Plot on Channel 39 - 40



Date: 11.JUN.2020 11:53:16

Channel Separation Plot on Channel 77 - 78



Date: 11.JUN.2020 11:43:59

<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 11.JUN.2020 12:22:15

Channel Separation Plot on Channel 39 - 40



Date: 11.JUN.2020 12:24:40

Channel Separation Plot on Channel 77 - 78



Date: 11.JUN.2020 12:26:59

<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 11.JUN.2020 12:28:58

Channel Separation Plot on Channel 39 - 40



Date: 11.JUN.2020 12:31:27

Channel Separation Plot on Channel 77 - 78



Date: 11.JUN.2020 12:33:39

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

Package Transfer Time Plot



Date: 29.MAY.2020 16:40:57

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.

2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.

3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
   Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
   RBW ≥ 1% of the 20 dB bandwidth; VBW ≥ RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
   Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
   RBW ≥ 1-5% of the 99% bandwidth; VBW ≥ 3 * RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup

3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.JUN.2020 11:33:45

20 dB Bandwidth Plot on Channel 39



Date: 19.JUN.2020 11:37:17

20 dB Bandwidth Plot on Channel 78



Date: 19.JUN.2020 11:39:36

<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.JUN.2020 11:41:20

20 dB Bandwidth Plot on Channel 39



Date: 19.JUN.2020 11:42:49

20 dB Bandwidth Plot on Channel 78



Date: 19.JUN.2020 11:44:27

<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.JUN.2020 11:46:16

20 dB Bandwidth Plot on Channel 39



Date: 19.JUN.2020 11:48:17

20 dB Bandwidth Plot on Channel 78



Date: 19.JUN.2020 11:49:51

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 19.JUN.2020 11:55:32

99% Occupied Bandwidth Plot on Channel 39



Date: 19.JUN.2020 11:57:12

99% Occupied Bandwidth Plot on Channel 78



Date: 19.JUN.2020 11:59:44

<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 19.JUN.2020 13:34:31

99% Occupied Bandwidth Plot on Channel 39



Date: 19.JUN.2020 13:42:25

99% Occupied Bandwidth Plot on Channel 78



Date: 19.JUN.2020 13:48:01

<3Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 19.JUN.2020 13:51:23

99% Occupied Bandwidth Plot on Channel 39



Date: 19.JUN.2020 13:54:08

99% Occupied Bandwidth Plot on Channel 78



Date: 19.JUN.2020 13:56:13

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

<1Mbps>

Low Band Edge Plot on Channel 00



Date: 19.JUN.2020 11:54:55

High Band Edge Plot on Channel 78



Date: 19.JUN.2020 11:59:05

<2Mbps>

Low Band Edge Plot on Channel 00



Date: 19.JUN.2020 13:33:48

High Band Edge Plot on Channel 78



Date: 19.JUN.2020 13:47:26

<3Mbps>

Low Band Edge Plot on Channel 00



Date: 19.JUN.2020 13:50:36

High Band Edge Plot on Channel 78



Date: 19.JUN.2020 13:55:16

3.6.6 Test Result of Conducted Hopping Mode Band Edges

<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 11.JUN.2020 12:52:03

Hopping Mode High Band Edge Plot



Date: 11.JUN.2020 12:55:37

<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 11.JUN.2020 13:01:07

Hopping Mode High Band Edge Plot



Date: 11.JUN.2020 13:03:11

<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 11.JUN.2020 14:44:21

Hopping Mode High Band Edge Plot



Date: 11.JUN.2020 14:46:54

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 9.JUL.2020 17:59:26

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 9.JUL.2020 18:00:17

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 9.JUL.2020 18:01:53

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 9.JUL.2020 18:02:30

CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 9.JUL.2020 18:03:19

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 9.JUL.2020 18:04:31

<2Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 19.JUN.2020 13:39:27

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 19.JUN.2020 13:40:05

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 19.JUN.2020 13:45:04

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 19.JUN.2020 13:46:37

CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 19.JUN.2020 13:48:58

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 19.JUN.2020 13:49:31

<3Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 9.JUL.2020 18:08:51

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 9.JUL.2020 18:10:47

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 9.JUL.2020 18:12:53

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 9.JUL.2020 18:14:35

CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 9.JUL.2020 18:16:13

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 9.JUL.2020 18:18:05

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the NCC LP0002 section 2.8 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

See list of measuring equipment of this test report.

3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz, RBW=1MHz for f>1GHz ; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
   (3) For average measurement: use duty cycle correction factor method per 15.35(c).
   Duty cycle = On time/100 milliseconds
   On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$
   Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
   Average Emission Level = Peak Emission Level + 20*log(Duty cycle)
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



For radiated emissions above 18GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per NCC LP0002 section 5.13 was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.8.7 Duty Cycle

Please refer to Appendix E.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the LP0002 Section 2.2, Section 3.10.1.3, and Section 3.10.1.4.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	HTC-1	2	N/A	Mar. 02, 2020	May 29, 2020~ Jun. 19, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO36	10MHz~6GHz	Jan. 22, 2020	May 29, 2020~ Jun. 19, 2020	Jan. 21, 2021	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSQ26.5	200578/026	20Hz-26.5GHz	Jul. 10, 2019	May 29, 2020~ Jun. 19, 2020	Jul. 09, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-1405-0	EC1900157	N/A	Aug. 15, 2019	May 29, 2020~ Jun. 19, 2020	Aug. 14, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 23, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jun. 23, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Jun. 23, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Jun. 23, 2020	Nov. 19, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jun. 23, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 23, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jun. 23, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jun. 23, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Preamplifier	EMCE	EMC184045B	980192	18GHz ~ 40GHz	Aug. 01, 2019	Apr. 07, 2020~ Jul. 06, 2020	Jul. 31, 2020	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 03, 2019	Apr. 07, 2020~ Jul. 06, 2020	Dec. 02, 2020	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 12, 2019	Apr. 07, 2020~ Jul. 06, 2020	Oct. 11, 2020	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Nov. 04, 2019	Apr. 07, 2020~ Jul. 06, 2020	Nov. 03, 2020	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 09, 2020	Apr. 07, 2020~ Jul. 06, 2020	Jan. 08, 2021	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY532700080	1GHz~26.5GHz	Nov. 13, 2019	Apr. 07, 2020~ Jul. 06, 2020	Nov. 12, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004886	10Hz ~ 44GHz	Oct. 28, 2019	Apr. 07, 2020~ Jul. 06, 2020	Oct. 27, 2020	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Apr. 07, 2020~ Jul. 06, 2020	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Apr. 07, 2020~ Jul. 06, 2020	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Apr. 07, 2020~ Jul. 06, 2020	N/A	Radiation (03CH11-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054002	1GHz~18GHz	Aug. 06, 2019	Apr. 07, 2020~ Jul. 06, 2020	Aug. 05, 2020	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz- 40GHz	May 22, 2020	Apr. 07, 2020~ Jul. 06, 2020	May 21, 2021	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004886	10Hz~44GHz	Oct. 28, 2019	Apr. 07, 2020~ Jul. 06, 2020	Oct. 27, 2020	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Apr. 07, 2020~ Jul. 06, 2020	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 12, 2020	Apr. 07, 2020~ Jul. 06, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 12, 2020	Apr. 07, 2020~ Jul. 06, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 12, 2020	Apr. 07, 2020~ Jul. 06, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 12, 2020	Apr. 07, 2020~ Jul. 06, 2020	Mar. 11, 2021	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1.53G Low Pass	Sep. 15, 2019	Apr. 07, 2020~ Jul. 06, 2020	Sep. 14, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	3GHz High Pass Filter	Sep. 15, 2019	Apr. 07, 2020~ Jul. 06, 2020	Sep. 14, 2020	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Nov. 07, 2019	Apr. 07, 2020~ Jul. 06, 2020	Nov. 06, 2020	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP161237	N/A	Oct. 25, 2019	Apr. 07, 2020~ Jul. 06, 2020	Oct. 24, 2020	Radiation (03CH11-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.3**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.2**

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.2**

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.3**

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Jacob Yu	Temperature:	21~25	°C
Test Date:	2020/5/29-2020/6/19	Relative Humidity:	51~54	%

TEST RESULTS DATA
20dB and 99% Occupied Bandwidth and Hopping Channel Separation

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	1.035	0.984	1.000	0.6902	Pass
DH	1Mbps	1	39	2441	1.035	0.987	1.010	0.6902	Pass
DH	1Mbps	1	78	2480	1.038	0.984	1.014	0.6923	Pass
2DH	2Mbps	1	0	2402	1.337	1.189	1.005	0.8910	Pass
2DH	2Mbps	1	39	2441	1.341	1.192	1.005	0.8942	Pass
2DH	2Mbps	1	78	2480	1.341	1.196	0.995	0.8942	Pass
3DH	3Mbps	1	0	2402	1.284	1.176	1.000	0.8558	Pass
3DH	3Mbps	1	39	2441	1.288	1.183	1.000	0.8590	Pass
3DH	3Mbps	1	78	2480	1.288	1.183	0.995	0.8590	Pass

TEST RESULTS DATA
Dwell Time

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.94	0.31	0.4	Pass
AFH	20	53.33	2.94	0.16	0.4	Pass

TEST RESULTS DATA
Peak Power Table

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result	Power Setting
DH1	0	1	**11.83**	30.00	Pass	Default
	39	1	11.78	30.00	Pass	
	78	1	10.15	30.00	Pass	
2DH1	0	1	**15.52**	20.97	Pass	Default
	39	1	14.79	20.97	Pass	
	78	1	14.11	20.97	Pass	
3DH1	0	1	**15.50**	20.97	Pass	Default
	39	1	15.20	20.97	Pass	
	78	1	14.42	20.97	Pass	

TEST RESULTS DATA
Average Power Table
(Reporting Only)

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	**11.61**	4.56
	39	1	11.54	4.56
	78	1	9.89	4.56
2DH1	0	1	**12.70**	5.07
	39	1	12.27	5.07
	78	1	11.59	5.07
3DH1	0	1	**12.69**	5.07
	39	1	12.49	5.07
	78	1	11.49	5.07

TEST RESULTS DATA
Number of Hopping Frequency

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Tom Lee and Howard Huang	**Temperature :**	23~25℃
		Relative Humidity :	42~50%

EUT Information

Report NO :	032014
Test Mode :	Mode 1
Test Voltage :	Power From System
Phase :	Line

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	29.86	56.00	26.14	L1	OFF	19.5
0.150000	41.76	---	66.00	24.24	L1	OFF	19.5
0.302010	---	32.53	50.19	17.66	L1	OFF	19.5
0.302010	40.24	---	60.19	19.95	L1	OFF	19.5
0.350250	---	20.33	48.96	28.63	L1	OFF	19.5
0.350250	35.42	---	58.96	23.54	L1	OFF	19.5
0.944250	---	28.88	46.00	17.12	L1	OFF	19.5
0.944250	36.80	---	56.00	19.20	L1	OFF	19.5
1.238640	---	26.87	46.00	19.13	L1	OFF	19.6
1.238640	33.91	---	56.00	22.09	L1	OFF	19.6
6.051750	---	34.56	50.00	15.44	L1	OFF	19.7
6.051750	40.00	---	60.00	20.00	L1	OFF	19.7
17.915910	---	21.03	50.00	28.97	L1	OFF	19.8
17.915910	25.50	---	60.00	34.50	L1	OFF	19.8

EUT Information

Report NO :	032014
Test Mode :	Mode 1
Test Voltage :	Power From System
Phase :	Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	29.23	55.63	26.40	N	OFF	19.5
0.156750	38.00	---	65.63	27.63	N	OFF	19.5
0.298590	---	37.80	50.28	12.48	N	OFF	19.5
0.298590	45.89	---	60.28	14.39	N	OFF	19.5
0.346830	---	35.54	49.04	13.50	N	OFF	19.5
0.346830	38.25	---	59.04	20.79	N	OFF	19.5
1.235040	---	25.62	46.00	20.38	N	OFF	19.6
1.235040	35.56	---	56.00	20.44	N	OFF	19.6
6.272340	---	28.66	50.00	21.34	N	OFF	19.7
6.272340	35.97	---	60.00	24.03	N	OFF	19.7
18.235500	---	21.18	50.00	28.82	N	OFF	19.9
18.235500	25.32	---	60.00	34.68	N	OFF	19.9

Appendix C. Radiated Spurious Emission

Test Engineer :	Cookie Ku, Fu Chen and Troye Hsieh	Temperature :	19.1~21.6°C
		Relative Humidity :	63.1~68.9%

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2350.32	42.95	-31.05	74	41.94	27.6	6.65	33.24	120	349	P	H
		2350.32	18.19	-35.81	54	-	-	-	-	-	-	A	H
	*	2402	103.5	-	-	102.53	27.5	6.7	33.23	120	349	P	H
	*	2402	78.74	-	-	-	-	-	-	-	-	A	H
													H
		2369.85	42.46	-31.54	74	41.47	27.56	6.67	33.24	100	3	P	V
		2369.85	17.7	-36.3	54	-	-	-	-	-	-	A	V
	*	2402	99.69	-	-	98.72	27.5	6.7	33.23	100	3	P	V
	*	2402	74.93	-	-	-	-	-	-	-	-	A	V
													V
BT CH 39 2441MHz		2335.62	43.37	-30.63	74	42.35	27.63	6.64	33.25	173	346	P	H
		2335.62	18.61	-35.39	54	-	-	-	-	-	-	A	H
	*	2441	102.76	-	-	101.81	27.42	6.75	33.22	173	346	P	H
	*	2441	78	-	-	-	-	-	-	-	-	A	H
		2486.63	42.72	-31.28	74	41.88	27.25	6.8	33.21	173	346	P	H
		2486.63	17.96	-36.04	54	-	-	-	-	-	-	A	H
		2383.78	43.32	-30.68	74	42.35	27.53	6.68	33.24	106	2	P	V
		2383.78	18.56	-35.44	54	-	-	-	-	-	-	A	V
	*	2441	99.46	-	-	98.51	27.42	6.75	33.22	106	2	P	V
	*	2441	74.7	-	-	-	-	-	-	-	-	A	V
		2492.51	42.33	-31.67	74	41.51	27.23	6.8	33.21	106	2	P	V
		2492.51	17.57	-36.43	54	-	-	-	-	-	-	A	V

BT CH 78 2480MHz	*	2480	99.56	-	-	98.7	27.28	6.79	33.21	113	344	P	H
	*	2480	74.8	-	-	-	-	-	-	-	-	A	H
		2483.56	44.01	-29.99	74	43.16	27.27	6.79	33.21	113	344	P	H
		2483.56	19.25	-34.75	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	96.7	-	-	95.84	27.28	6.79	33.21	100	358	P	V
	*	2480	71.94	-	-	-	-	-	-	-	-	A	V
		2483.76	42.57	-31.43	74	41.73	27.26	6.79	33.21	100	358	P	V
		2483.76	17.81	-36.19	54	-	-	-	-	-	-	A	V
													V
													V

Remark

1. No other spurious found.
2. All results are PASS against Peak and Average limit line.

2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	40.64	-33.36	74	56.99	31	10.93	58.28	100	0	P	H
		4804	15.88	-38.12	54	-	-	-	-	-	-	A	H
													H
													H
		4804	39.42	-34.58	74	55.77	31	10.93	58.28	100	0	P	V
		4804	14.66	-39.34	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	40.89	-33.11	74	57.19	31	10.97	58.27	100	0	P	H
		4882	16.13	-37.87	54	-	-	-	-	-	-	A	H
		7323	44.65	-29.35	74	53.32	36.5	13.35	58.52	100	0	P	H
		7323	19.89	-34.11	54	-	-	-	-	-	-	A	H
		4882	39.14	-34.86	74	55.44	31	10.97	58.27	100	0	P	V
		4882	14.38	-39.62	54	-	-	-	-	-	-	A	V
		7323	43.81	-30.19	74	52.48	36.5	13.35	58.52	100	0	P	V
		7323	19.05	-34.95	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	40.62	-33.38	74	56.73	31.14	11.01	58.26	100	0	P	H
		4960	15.86	-38.14	54	-	-	-	-	-	-	A	H
		7440	44.03	-29.97	74	53.03	36.38	13.21	58.59	100	0	P	H
		7440	19.27	-34.73	54	-	-	-	-	-	-	A	H
		4960	41.4	-32.6	74	57.51	31.14	11.01	58.26	100	0	P	V
		4960	16.64	-37.36	54	-	-	-	-	-	-	A	V
		7440	43.48	-30.52	74	52.48	36.38	13.21	58.59	100	0	P	V
		7440	18.72	-35.28	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission above 18GHz

2.4GHz BT (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT SHF		23495	42.63	-31.37	74	47.73	38.9	9.3	53.3	100	0	P	H
													H
													H
													H
													H
													H
		23411	42.16	-31.84	74	47.28	38.92	9.31	53.35	100	0	P	V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		30	23.81	-16.19	40	31.32	24.15	0.76	32.42	-	-	P	H
		117.3	24.59	-18.91	43.5	38.33	17.15	1.53	32.42	-	-	P	H
		128.94	25.06	-18.44	43.5	38.42	17.46	1.62	32.44	-	-	P	H
		910.76	30.28	-15.72	46	28.68	28.86	4.33	31.59	-	-	P	H
		933.07	30.19	-15.81	46	27.83	29.26	4.39	31.29	-	-	P	H
		947.62	30.67	-15.33	46	27.39	29.95	4.43	31.1	100	0	P	H
													H
													H
													H
													H
													H
													H
		45.52	31.46	-8.54	40	46.55	16.45	0.97	32.51	100	0	P	V
		71.71	23.2	-16.8	40	42.27	12.16	1.24	32.47	-	-	P	V
		117.3	22.49	-21.01	43.5	36.23	17.15	1.53	32.42	-	-	P	V
		885.54	30.17	-15.83	46	28.72	28.97	4.27	31.79	-	-	P	V
		941.8	30.62	-15.38	46	27.75	29.63	4.42	31.18	-	-	P	V
		958.29	30.67	-15.33	46	26.61	30.57	4.45	30.96	-	-	P	V
													V
													V
													V
													V
													V
													V

Remark

1. No other spurious found.
2. All results are PASS against limit line.

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Cookie Ku, Fu Chen and Troye Hsieh	**Temperature :**	19.1~21.6°C
		Relative Humidity :	63.1~68.9%

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	**2.4GHz 2400~2483.5MHz Band Edge @ 3m**	
	BT CH00 2402MHz	
	Horizontal	**Fundamental**
Peak		

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak		

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak		
Peak		Left blank

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak		
Peak		Left blank

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak		

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak		

2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.		

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
Peak Avg.		

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.		

Emission above 18GHz

2.4GHz BT (SHF)

BT	2.4GHz 2400~2483.5MHz	
	BT SHF	
	Horizontal	Vertical
QP / Peak		

Emission below 1GHz

2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
	BT LF	
	Horizontal	Vertical
QP / Peak		

Annex. A Receiver Radiated Emission Measurement

A.1 Limit of Receiver Radiated Emission

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

A.2 Measuring Instruments

See list of measuring equipment of this test report.

A.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

A.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



A.5 Test Result of Receiver Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per NCC LP0002 section 5.13 was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

A.6 Connection Diagram of Test System



A.7 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	Adapter	Samsung	RF1C632EWSD	N/A	N/A	N/A

Remark: Applicant has ensured accessory would not be attached with the product on the market, accessory is provided by lab for testing.

A.8 Test Result of Receiver Radiated Spurious Emission (30MHz ~ 5th Harmonic)

Test Engineer :	Cookie Ku, Fu Chen and Troye Hsieh	**Temperature :**	19.1~26.9°C
		Relative Humidity :	50~68.9%
Frequency	36.790 MHz	**Margin**	Under 6.32 dB
Test Mode	Bluetooth Idle		

	Idle Mode	
	Horizontal	**Vertical**
Peak **Avg.**	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 032014	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 032014

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	37.76	20.93	-19.07	40.00	32.06	20.45	0.86	32.46	---	---	Peak
2	135.73	21.71	-21.79	43.50	35.30	17.19	1.63	32.46	---	---	Peak
3	289.96	33.59	-12.41	46.00	44.76	18.60	2.38	32.25	100	0	Peak
4	760.41	28.70	-17.30	46.00	29.02	27.76	3.80	32.05	---	---	Peak
5	888.45	29.68	-16.32	46.00	28.17	29.02	4.08	31.78	---	---	Peak
6	952.47	30.98	-15.02	46.00	27.38	30.20	4.22	31.04	---	---	Peak
7	2266.00	45.84	-28.16	74.00	44.59	27.70	6.57	33.26	---	---	Peak
8	2842.00	47.36	-26.64	74.00	44.80	28.07	7.26	33.02	---	---	Peak
9	6615.00	44.20	-29.80	74.00	56.67	34.44	12.46	59.76	---	---	Peak
10	8040.00	45.48	-28.52	74.00	53.71	37.10	13.19	58.99	---	---	Peak
11	10380.00	49.91	-24.09	74.00	54.77	39.90	16.98	62.18	100	0	Peak
12	14250.00	49.50	-24.50	74.00	49.71	41.25	19.95	62.15	---	---	Peak

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	36.79	33.68	-6.32	40.00	44.52	20.76	0.85	32.46	100	0	Peak
2	75.59	23.39	-16.61	40.00	42.01	12.56	1.22	32.46	---	---	Peak
3	155.13	26.77	-16.73	43.50	41.02	16.41	1.74	32.50	---	---	Peak
4	773.99	29.11	-16.89	46.00	29.31	27.89	3.82	32.08	---	---	Peak
5	889.42	29.44	-16.56	46.00	27.91	29.03	4.09	31.78	---	---	Peak
6	948.59	30.36	-15.64	46.00	27.02	29.99	4.22	31.09	---	---	Peak
7	2186.00	45.68	-28.32	74.00	44.51	27.72	6.49	33.28	---	---	Peak
8	2968.00	47.70	-26.30	74.00	44.68	28.30	7.44	32.95	---	---	Peak
9	5130.00	41.90	-32.10	74.00	59.20	31.80	10.72	60.33	---	---	Peak
10	7965.00	45.04	-28.96	74.00	53.46	36.89	13.21	59.00	---	---	Peak
11	10755.00	49.74	-24.26	74.00	54.88	39.92	17.00	62.50	100	0	Peak
12	14250.00	49.71	-24.29	74.00	49.92	41.25	19.95	62.15	---	---	Peak

<Receiver Radiated Emission>

LF

HF



Appendix E. Duty Cycle Plots

3DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.89 / 100 = 5.78 %
2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.76 dB
3. 3DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

2.89 ms x 20 channels = 57.8 ms

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100 ms / 57.8 ms] = 2 hops

Thus, the maximum possible ON time:

2.89 ms x 2 = 5.78 ms

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

20 x log(5.78 ms/100 ms) = -24.76 dB

Appendix F. Setup Photographs

<Conducted Emission>

Mode 1

Remote View





Rear View

<Radiated Emission>

Y Plane

LF



HF

SHF



————THE END————