

Test Result Report

Date 2019/07/08

Test Laboratory
Address
Name of corporation
Position
Name of responsible

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen 518057 China
SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch
Manager
Keny Xu



Signature

Type of specified radio equipment	Radio equipment according to Certification Ordinance Article 2 Section 1 No.
Model name	Wine Dispenser with Bluetooth without external adaptor
Manufacturer	Simatelex Manufactory Co., Ltd
Serial Number	N/A
Number of test sample	Model 11
Class of emissions, Assigned frequency and Antenna power	F1D, 2402MHz-2480MHz (2MHz separation, 40CH) 0.00009929W
Name of test person	Darren. yuan
Qualifications or conditions of test person	Test Engineer
Test Date Temperature/Humidity	See attached test report
Measuring Instruments	See attached test report
Test Method	Notification No.88 of MIC, Appendix
Test Result	Pass / Fail See attached test report
Remarks	

Test result and instruments about Type certificate

Bluetooth Low Energy

1. General

Model name	Model 11	Date	2019/6/5
Serial number	N/A	Place	RE 2# chamber
Class of emissions, Assigned frequency and Antenna power	F1D, 2402-2480MHz, (2MHz step 40ch), 0.00009929W	Remarks	

2. Measuring Instruments

Equipment list

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	Calibration body	Classification
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018/9/25	2019/9/24	CEPREI	(c)
Signal Generator (9kHz-40GHz)	KEYSIGHT	N5173B	SEM006-05	2018/9/27	2019/9/26	CEPREI	(c)
Multimeter	FLUKE	Fluke 73III	SEM022-01	2019/4/3	2020/4/2	CEPREI	(c)
Universal Radio Communication Tester	Rohde & Schwarz	CMW 500	SEM010-03	2019/4/2	2020/4/1	CEPREI	(c)
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2018/9/27	2019/9/26	CEPREI	(c)
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2019/4/4	2020/4/3	CEPREI	(c)
EXA Signal Analyzer (10Hz-44GHz)	Agilent Technologies Inc	N9010A	SEM004-12	2019/4/12	2020/4/11	GRGTEST	(c)
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/4/13	2021/4/12	GRGTEST	(c)
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-06	2018/6/8	2021/6/7	GRGTEST	(c)
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2018/11/12	2019/11/11	CEPREI	(c)
MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2018/9/25	2019/9/24	CEPREI	(c)
Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2019/4/1	2020/3/31	CEPREI	(c)
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017/6/27	2020/6/26	NIM	(c)
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-02	2019/5/24	2022/5/23	NIM	(c)

Remark:

- (a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) in Japan (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1) in JRL.
- (b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Act (Act No. 51 of 1992).
- (c) Calibration conducted in countries except Japan, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
- (d) Calibration, etc. conducted by using measuring instruments and other equipment listed in the right column of appended table No. 3, which shall have been given any type of calibration, etc. listed above from (a) to (c).
- From JRL Article 24-2, paragraph 4, Item 2

3. Test Result

Condition	Test Items		Unit	Normal Voltage + 10% (V)			Normal Voltage (3.8 V)			Normal Voltage - 10% (V)			Judgment	Limit	Remarks
				2402MHz	2440MHz	2480MHz	2402MHz	2440MHz	2480MHz	2402MHz	2440MHz	2480MHz			
Normal (23.4° C, 43.2 %)	Frequency		MHz				2401.983	2439.980	2480.021				Pass	50ppm	
			ppm				-7.286	-8.325	-9.073						
	Occupied Bandwidth		MHz				1.0885	1.0862	1.086				Pass	26MHz	
	Spurious Emissions	30MHz-2387MHz	dBm				-54.817	-56.127	-56.216				Pass	-26dBm	
			MHz				2352.15	2123.12	1715.35						
		2387MHz-2400MHz	dBm				-56.644	-55.437	-55.153				Pass	-16dBm	
			MHz				2387.2925	2391.428	2394.9788						
		2483.5MHz-2496.5MHz	dBm				-55.324	-55.275	-55.273				Pass	-16dBm	
			MHz				2493.3914	2492.6699	2493.7621						
		2496.5MHz-12.5GHz	dBm				-52.356	-52.885	-53.347				Pass	-26dBm	
			MHz				5131.6	5127.8	3770.5						
	Antenna Power		W				0.00009929	0.00004502	0.00004307				Pass	0.01W	
			%				0.00	-54.66	-56.62					+20 ~ -80%	
	Secondary Radiated Emissions	30MHz-1GHz	dBm				-61.72	-62.065	-62.329				Pass	-54dBm	
			MHz				31.210	40.550	46.610						
		1GHz-12.5GHz	dBm				-54.18	-54.588	-54.454				Pass	-47dBm	
			MHz				5584.400	4801.400	5754.300						
	Interference Prevention Function	D0:CF:5E:66:23:91											Pass		

Note:


2.1 Details of E.U.T.

Power supply:	Lithium Ion Battery: 3.8V 490mAh rechargeable battery which charged by USB port
Test voltage:	DC 3.8V
Cable:	USB cable: 100cm unshield
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V4.2 LE
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	2.4GHz ceramic antenna
Antenna Gain:	1dBi

2.2 Test Conditions

Power Supply	Lithium Ion Battery: 3.8V 490mAh rechargeable battery which charged by USB port
	The RF unit is supplied DC3.3V. The fluctuation of input voltage to the circuit of RF unit of test equipment is under ±1%, when input voltage from DC3.8V to the test equipment is fluctuated by ±10%. So, all measurement has been conducted by only rated voltage.
	The measurement result of the voltage fluctuation at RF circuit when
DC3.8V +/- 10%.	
DC Input	DC3V30
4.18V	3.32V
3.8V	3.30V
3.42V	3.28V

Temperature:	0~45.0 °C
Humidity:	45~85 % RH
Atmospheric Pressure:	1000~1010 mbar
Note:	
VN:	Normal Voltage
TN:	Normal Temperature
TL:	Low Extreme Test Temperature
TH:	High Extreme Test Temperature



OBW
2402MHz



2442MHz






2480MHz





Tx Spurious



2402MHz











2440MHz













2480MHz











Rx Spurious
2402MHz





2440MHz





2480MHz

