

Test Report No:
2660287R-RFJPV02S-B

TEST REPORT

Japan Rules & Regulations

Product Name	WIRELESS GAMING MOUSE
Brand Name	ASUS
Model No.	P729
Applicant's Name / Address	ASUSTeK COMPUTER INC. 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan
Manufacturer's Name	ASUSTeK COMPUTER INC.
Test Method Requested, Standard	MIC Notice No.88 Appendix No.43 Article 2 Paragraph 1 of Item 19
Verdict Summary	IN COMPLIANCE
Documented By Jinn Chen	<i>Jinn Chen</i>
Approved By Alan Chen	<i>Alan Chen</i>
Date of Receipt	2026/06/08
Date of Issue	2026/07/06
Report Version	V1.0

INDEX

	page
Competences and Guarantees.....	4
General Conditions.....	4
Revision History.....	5
Summary of Test Result.....	6
1. General Information.....	7
1.1. EUT Description.....	7
1.2. EUT Information.....	8
1.3. Testing Location Information.....	8
1.4. Ambient Conditions In The Laboratory.....	9
1.5. Measurement Uncertainty.....	9
1.6. List of Test Equipment.....	10
2. Test Configuration of EUT.....	11
2.1. Test Condition.....	11
2.2. Power Supply Voltage Fluctuation.....	11
2.3. Test Frequency Mode.....	11
2.4. RF and IF Section Must be Tamper Requirement.....	12
2.5. Measurement Configuration.....	13
3. Antenna Power, Antenna Power Tolerance and E.I.R.P.....	14
3.1. Test Setup.....	14
3.2. Test Limit.....	14
3.3. Test Method.....	14
3.4. Test Procedure.....	14
3.5. Test Result of Antenna Power, Antenna Power Tolerance and E.I.R.P.....	14
4. Occupied Bandwidth.....	15
4.1. Test Setup.....	15
4.2. Test Limit.....	15
4.3. Test Method.....	15
4.4. Test Procedure.....	15
4.5. Test Result of Occupied Bandwidth.....	15
5. Frequency Tolerance.....	16
5.1. Test Setup.....	16
5.2. Test Limit.....	16
5.3. Test Method.....	16
5.4. Test Procedure.....	16
5.5. Test Result of Frequency Tolerance.....	16
6. Dwell Time.....	17

6.1.	Test Setup.....	17
6.2.	Test Limit	17
6.3.	Test Method	17
6.4.	Test Procedure	17
6.5.	Test Result of Dwell Time	17
7.	Unwanted Emission Strength	18
7.1.	Test Setup.....	18
7.2.	Test Limit	18
7.3.	Test Method	18
7.4.	Test Procedure	18
7.5.	Test Result of Unwanted Emission Strength	18
8.	Secondary Radiated Emission Strength.....	19
8.1.	Test Setup.....	19
8.2.	Test Limit	19
8.3.	Test Method	19
8.4.	Test Procedure	19
8.5.	Test Result of Secondary Radiated Emission Strength.....	19
9.	Interference Prevention Function	20
9.1.	Test Setup.....	20
9.2.	Test Method	20
9.3.	Test Procedure	20
9.4.	Test Result of Interference Prevention Function	20
Appendix A. Test Result of Antenna Power, Antenna Power Tolerance and E.I.R.P		
Appendix B. Test Result of Occupied Bandwidth		
Appendix C. Test Result of Frequency Tolerance		
Appendix D. Test Result of Dwell Time		
Appendix E. Test Result of Unwanted Emission Strength		
Appendix F. Test Result of Secondary Radiated Emission Strength		
Appendix G. Test Result of Interference Prevention Function		
Appendix H. Test Setup Photograph		

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	2026/07/06

Summary of Test Result

Report Clause	Test Items	Result (PASS/FAIL)	Remark
3	Antenna Power, Antenna Power Tolerance and E.I.R.P	PASS	-
4	Occupied Bandwidth	PASS	-
5	Frequency Tolerance	PASS	-
6	Dwell Time	PASS	-
7	Unwanted Emission Strength	PASS	-
8	Secondary Radiated Emission Strength	PASS	-
9	Interference Prevention Function	PASS	-

Comments and Explanations

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1. General Information

1.1. EUT Description

Frequency Band	2400 ~ 2483.5 MHz		
Operating Frequency	2404 ~ 2478 MHz		
Channel Number	37 Channels		
Type of Modulation	GFSK (2 Mbps)		
Declared Antenna Power	Normal Operation	GFSK (2 Mbps)	0.11 mW/MHz
	AFH Operation	GFSK (2 Mbps)	0.86 mW/MHz

Accessories Information					
No.	Equipment Name	Brand Name	Model No.	Rating	Remark
1	WIRELESS DONGLE	ASUS	MPDONGLE3	DC 5V	N/A
No.	Equipment Name	Description			
2	USB Type C Cable	Shielded, 2m			

Antenna Information				
No.	Brand Name	Part No.	Type	Gain (dBi)
1	JIA DE	WJ.05.0000068	Metal Antenna	3.20

Center Frequency of Each Channel:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
-	-	01	2404	02	2406	03	2408
04	2410	05	2412	06	2414	07	2416
08	2418	09	2420	10	2422	11	2424
-	-	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	-	-

1.2. EUT Information

EUT Power Type	From USB / Battery
----------------	--------------------

1.3. Testing Location Information

Testing Location Information			
Test Laboratory : DEKRA Testing and Certification Co., Ltd.			
V	Address	No. 85, Wenlin St., Linkou Dist., New Taipei City 244017, Taiwan, R.O.C.	
	Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.	
	Phone/Fax Number	TEL: +886-3-275-7255	FAX: +886-3-327-8031
	Site Description	Accredited by TAF Accredited Number: 3023	
	Address/ Performed Location	No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.	
	Phone/Fax Number	TEL: +886-3-582-8001	FAX: +886-3-582-8958
	Site Description	Accredited by TAF Accredited Number: 3024	
	Address/ Performed Location	No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.	
	Phone/Fax Number	TEL: +886-3-582-8001	FAX: +886-3-582-8958
	Site Description	Accredited by TAF Accredited Number: 3024	

1.4. Ambient Conditions In The Laboratory

Performed Item	Items	Required	Actual	Test Date	Tested By
RF Conducted Emission	Temperature (°C)	5~35 °C	22.3~23.2 °C	2026/06/12 ~	Kevin Lai
	Humidity (%RH)	45~85 %	61.5~72.6 %	2026/06/22	

1.5. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty
Antenna Power, Antenna Power Tolerance and E.I.R.P	Spectrum Analyzer: ± 2.13 dB Power Meter: ± 1.06 dB
Occupied Bandwidth	± 1580.61 Hz
Frequency Tolerance	± 1580.61 Hz
Dwell Time	± 0.65 %
Unwanted Emission Strength	± 2.13 dB
Secondary Radiated Emission Strength	± 2.13 dB
Interference Prevention Function	N/A

1.6. List of Test Equipment

For Conducted Measurements / HY-SR02

Equipment	Manufacturer	Model No.	Serial No.	Cal. by	Cal. Method	Cal. Date	Due Date
V DC Power Supply	KEYSIGHT	E36234A	MY59001234	ETC	*(c)	2025/10/27	2026/10/26
V Spectrum Analyzer	R&S	FSV30	103466	ETC	*(c)	2025/12/18	2026/12/17
V Power Meter	Anritsu	ML2496A	1947001	ETC	*(c)	2025/12/22	2026/12/21
V Power Sensor	Anritsu	MA2411B	1911082	ETC	*(c)	2025/12/22	2026/12/21
V Power Sensor	Anritsu	MA2411B	1911083	ETC	*(c)	2025/12/22	2026/12/21

Note:

1. All equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: DTC_RF_Tool_Release V2.0.115.
4. a) Calibration conducted by the National Institute of Information and Communications Technology(NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1).
 b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992).
 c) Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated agency under Article 102-18 paragraph (1).
 d) Calibration conducted by using other equipment that listed above from a) to c).

2. Test Configuration of EUT

2.1. Test Condition

EUT Operational Condition	
Testing Voltage	DC 5V

2.2. Power Supply Voltage Fluctuation

Voltage Test Item	Test Voltage	Voltage Meter Reading Value
Nominal Voltage	DC 5.0V	DC 1.9V
Highest Voltage	DC 5.5V	DC 1.9V
Lowest Voltage	DC 4.5V	DC 1.9V

Note:

1. The Voltage supply for RF Chip U2 Pin C10 is DC 1.9 V.
2. The internal supply gives a fluctuation value less than 1 % (Around 0% from max. to min.)
3. The EUT has component of power supply regulation, therefore only normal condition was evaluated.

When the input voltage from the external power supply to the EUT varied by $\pm 10\%$, the variation of the input voltage to the circuitry of the radio section was confirmed to be $\pm 1\%$ or less.


2.3. Test Frequency Mode

Test Software Version	AB1620_Airoha_Tool_Kit(ATK) / Version 1.1.0.51
-----------------------	--

Modulation	Frequency (MHz)	Power Setting			
		SISO A	SISO B	MIMO A	MIMO B
GFSK (2 Mbps)	2404	57	--	--	--
	2440	57	--	--	--
	2478	58	--	--	--
GFSK (2 Mbps) -AFH	2404	57	--	--	--
	2408	57	--	--	--
	2412	57	--	--	--

2.4. RF and IF Section Must be Tamper Requirement

Requirement	Comments	Result
RF, IF and Modulation section must be tamper	☐ Use Special Screw ☐ Metal Shielding is Soldered ☒ Use Quad Flat Package (QFP) (Please refer to the attachment: EUT Detailed Photographs)	Complete
	☒ RF module/Chip pin >10 ☒ RF module/Chip pins distance <1.5mm (Please refer to the attachment: EUT Detailed Photographs)	Complete



2.5. Measurement Configuration


Tests Item	Antenna Power, Antenna Power Tolerance and E.I.R.P Occupied Bandwidth Frequency Tolerance Dwell Time Unwanted Emission Strength Secondary Radiated Emission Strength Interference Prevention Function
Test Condition	Conducted measurement at transmit chains

Note:

1. Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. After checking the fluctuation of input voltage to the circuit of the radio part (excluding the power supply) of the equipment to be tested, the fluctuation less than $\pm 1\%$ when input voltage from an external supply into the equipment fluctuates $\pm 10\%$, therefore, the test is carried out only at the normal voltage.
3. The EUT is available in two colors: black and white, with white as the primary color for testing purposes. The color does not affect the test results.

3. Antenna Power, Antenna Power Tolerance and E.I.R.P.

3.1. Test Setup



3.2. Test Limit

Antenna Power: $\leq 3\text{mW/MHz}$

Antenna Power Tolerance: $\leq +20\%$

EIRP: $\leq 6.91\text{dBm/MHz}$

3.3. Test Method

According to MIC Notice No. 88 Annex 43.

3.4. Test Procedure


- Connect a high-frequency power meter to the output of the dummy load (attenuator) and measure the output power.
- Output power shall be as follows.
 - Value of a continuous wave.
 - Calculate the output power per 1 MHz by spread bandwidth and duty cycle.

3.5. Test Result of Antenna Power, Antenna Power Tolerance and E.I.R.P.

Refer as Appendix A

4. Occupied Bandwidth

4.1. Test Setup



4.2. Test Limit

≤ 83.5 MHz

4.3. Test Method

According to MIC Notice No. 88 Annex 43.

4.4. Test Procedure

A spectrum analyzer or similar device shall be used to observe a sample of the modulated transmitter's radio frequency power output.


- (a) A positive peak detector function must be used.
- (b) A measurement instrument with an integrated 99% power bandwidth function may be used to automate the test process.
- (c) The measurement instrument bandwidth and span must be set sufficiently with, and, the scan time set sufficiently slowly, to ensure all major modulation products are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.
- (d) 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

4.5. Test Result of Occupied Bandwidth

Refer as Appendix B

5. Frequency Tolerance

5.1. Test Setup



5.2. Test Limit

± 50 ppm

5.3. Test Method

According to MIC Notice No. 88 Annex 43.

5.4. Test Procedure

A spectrum analyzer or similar device shall be used to observe a sample of the unmodulated or modulated transmitter's radio frequency power output.


- (a) A positive peak detector function must be used.
- (b) The measurement instrument bandwidth and span must be set sufficiently wide, and the scan time set sufficiently slowly, to ensure all products of the unmodulated signal are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.
- (c) 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

5.5. Test Result of Frequency Tolerance

Refer as Appendix C

6. Dwell Time

6.1. Test Setup



6.2. Test Limit

≤ 0.4 sec

6.3. Test Method

According to MIC Notice No. 88 Annex 43.

6.4. Test Procedure

A spectrum analyzer or similar device shall be used to observe a sample of the modulated transmitter's radio frequency power output.


- (a) A positive peak detector function must be used.
- (b) The center frequency is set to the test frequency and the span is switched to zero.
- (c) The measurement instrument bandwidth must be set sufficiently with, and, the scan time set sufficiently slowly, to ensure all major modulation products are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.
- (d) "Single sweep" mode may be used to capture a packet over a single scan.

6.5. Test Result of Dwell Time

Refer as Appendix D

7. Unwanted Emission Strength

7.1. Test Setup



7.2. Test Limit

- $\leq 2.5\mu\text{W}/\text{MHz}$ for $30\text{ MHz} < f < 2387\text{ MHz}$
- $\leq 25\mu\text{W}/\text{MHz}$ for $2387\text{ MHz} \leq f < 2400\text{ MHz}$
- $\leq 25\mu\text{W}/\text{MHz}$ for $2483.5\text{ MHz} < f \leq 2496.5\text{ MHz}$
- $\leq 2.5\mu\text{W}/\text{MHz}$ for $2496.5\text{ MHz} < f < 12500\text{ MHz}$

7.3. Test Method

According to MIC Notice No. 88 Annex 43.

7.4. Test Procedure

The EUT is connected to the spectrum analyzer and it is configured at maximum output power in the different test channels.


- (a) A positive peak detector function must be used.
- (b) The measurement instrument bandwidth and span must be set sufficiently with, and, the scan time set sufficiently slow, to ensure all major modulation products are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.
- (c) 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

7.5. Test Result of Unwanted Emission Strength

Refer as Appendix E

8. Secondary Radiated Emission Strength

8.1. Test Setup



8.2. Test Limit

$\leq 4\text{nW}$ for $30\text{ MHz} < f < 1000\text{ MHz}$

$\leq 20\text{nW}$ for $1000\text{ MHz} \leq f < 12500\text{ MHz}$

8.3. Test Method

According to MIC Notice No. 88 Annex 43.

8.4. Test Procedure

The EUT is connected to the spectrum analyzer and it is configured in reception mode in the different test channels.


- A positive peak detector function must be used.
- The measurement instrument bandwidth and span must be set sufficiently with, and, the scan time set sufficiently slowly, to ensure all major modulation products are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.
- 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

8.5. Test Result of Secondary Radiated Emission Strength

Refer as Appendix F

9. Interference Prevention Function

9.1. Test Setup



9.2. Test Method

According to MIC Notice No. 88 Annex 43.

9.3. Test Procedure

Radio equipment used mainly on the same premises and automatically transmits or receives identification code.

9.4. Test Result of Interference Prevention Function

Refer as Appendix G