TESTING LABORATORY
CERTIFICATE #4820.01

FCC PART 15.247

TEST REPORT

For

MPOW TECHNOLOGY CO.,LIMITED

FLAT/RM 605 6/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET
MONGKOK KL HONG KONG

FCC ID: 2AMH2-BH510A-1

Report Type: Original Report	**Product Name:** MPOW MDOTS TRUE WIRELESS EARBUDS

Report Number: RDG201127014-00A

Report Date: 2020-12-30

Reviewed By: Ivan Cao
Assistant Manager

Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road,
Tangxia Town, Dongguan, Guangdong, China
Tel: +86-769-86858888
Fax: +86-769-86858891
www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
DECLARATIONS 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EUT EXERCISE SOFTWARE 6
EQUIPMENT MODIFICATIONS 7
SUPPORT CABLE LIST AND DETAILS 7
SUPPORT EQUIPMENT LIST AND DETAILS 7
BLOCK DIAGRAM OF TEST SETUP 7
SUMMARY OF TEST RESULTS **8**
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE **9**
APPLICABLE STANDARD 9
FCC §15.203 - ANTENNA REQUIREMENT **10**
APPLICABLE STANDARD 10
ANTENNA CONNECTOR CONSTRUCTION 10
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS **11**
APPLICABLE STANDARD 11
EUT SETUP 11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 12
TEST PROCEDURE 12
TEST EQUIPMENT LIST AND DETAILS 12
CORRECTED AMPLITUDE & MARGIN CALCULATION 13
TEST DATA 13
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST **19**
APPLICABLE STANDARD 19
TEST EQUIPMENT LIST AND DETAILS 19
TEST PROCEDURE 19
TEST DATA 19
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING **25**
APPLICABLE STANDARD 25
TEST PROCEDURE 25
TEST EQUIPMENT LIST AND DETAILS 25
TEST DATA 25
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST **31**
APPLICABLE STANDARD 31
TEST PROCEDURE 31
TEST EQUIPMENT LIST AND DETAILS 31
TEST DATA 31

FINAL

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)....34
APPLICABLE STANDARD 34
TEST PROCEDURE 34
TEST EQUIPMENT LIST AND DETAILS....34
TEST DATA 34
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT....40
APPLICABLE STANDARD 40
TEST PROCEDURE 40
TEST EQUIPMENT LIST AND DETAILS....40
TEST DATA 40
FCC §15.247(d) - BAND EDGES TESTING 42
APPLICABLE STANDARD 42
TEST PROCEDURE 42
TEST EQUIPMENT LIST AND DETAILS....42
TEST DATA 43

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	MPOW MDOTS TRUE WIRELESS EARBUDS
EUT Model:	BH510A
Operation Frequency:	2402-2480MHz
Maximum Peak Output Power (Conducted):	1.87 dBm
Antenna Gain▲:	2.2 dBi
Modulation Type:	GFSK, π/4-DQPSK, 8DPSK
Rated Input Voltage:	DC 3.7V from battery or DC 5V from Charger
Serial Number:	RDG201127004-RF-S7
EUT Received Date:	2020.11.30
EUT Received Status:	Good

Objective

This report is prepared on behalf of **MPOW TECHNOLOGY CO.,LIMITED** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

Part of system submittal with FCC ID: 2AMH2-BH510A

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

FINAL

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol "△". Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk "★".

FINAL

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode, which was provided by manufacturer.

EUT Exercise Software

The ' FCCTool ' was used during test, which was provided by manufacturer. The maximum power level was configured by the software as below table:

Test Software Version	FCCTool		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	default	default	default
π/4-DQPSK	default	default	default
8DPSK	default	default	default

FINAL

Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/
/	/	/	/	/	/

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/
/	/	/	/

Block Diagram of Test Setup



FINAL

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
FCC §15.203	Antenna requirement	Compliance
FCC §15.207(a)	AC line conducted emissions	Not applicable
FCC §15.205, §15.209, §15.247(d)	Spurious emissions	Compliance
FCC §15.247(a)(1)	Channel separation	Compliance
FCC §15.247(a)(1)	20 dB bandwidth	Compliance
FCC §15.247(a)(1)(iii)	Quantity of hopping channel test	Compliance
FCC §15.247(a)(1)(iii)	Time of occupancy (dwell time)	Compliance
FCC §15.247(b)(1)	Peak output power measurement	Compliance
FCC §15.247(d)	Band edges	Compliance

Not Applicable: the device was powered by battery when operating.

FINAL

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to§15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 2.0 dBm (1.58 mW).
[(max. power of channel, mW)/(min. test separation distance, mm)][√f(GHz)]
=1.58/5*(√2.480) =0.5< 3.0

So the stand-alone SAR evaluation is not necessary.

FINAL

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
Chip	50	2.2 dBi/2.4~2.5GHz

Result: Compliance.

FINAL

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

According to FCC public notice: DA-00-705, during the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-1	2020-11-10	2023-11-10
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2020-05-06	2021-05-06
HP	Amplifier	8447D	2727A05902	2020-09-05	2021-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiation Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2020-12-05	2023-12-04
Agilent	Spectrum Analyzer	E4440A	SG43360054	2020-07-07	2021-07-07
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2020-06-27	2021-06-27
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2020-09-05	2021-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2020-06-16	2021-06-16
Sinoscite	Bandstop Filters	BSF5150-5850MN-0899-003	0899003	2020-05-06	2021-05-06

**** Statement of Traceability:*** *Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Data

Environmental Conditions

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	22.7°C	22.2°C
Relative Humidity:	40 %	41 %
ATM Pressure:	101.6kPa	101.6kPa
Tester:	Lee Li	Lee Li
Test Date:	2020-12-08	2020-12-08

Test Mode: Transmitting

FINAL

1) 30MHz-1GHz (BDR High channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBµV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.9700	27.49	peak	0.74	28.23	40.00	11.77
74.6200	28.97	peak	-11.24	17.73	40.00	22.27
122.1500	27.55	peak	-4.78	22.77	43.50	20.73
277.3500	27.04	peak	-4.04	23.00	46.00	23.00
638.1900	27.59	peak	1.93	29.52	46.00	16.48
960.2300	34.77	peak	0.16	34.93	54.00	19.07

Vertical:



Frequency (MHz)	Receiver Reading (dBµV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.0000	26.77	peak	1.46	28.23	40.00	11.77
62.0100	31.37	peak	-12.23	19.14	40.00	20.86
118.2700	26.28	peak	-5.01	21.27	43.50	22.23
134.7600	27.04	peak	-5.28	21.76	43.50	21.74
506.2700	28.98	peak	-0.39	28.59	46.00	17.41
968.9600	33.90	peak	0.30	34.20	54.00	19.80

2)1GHz-25GHz:

BDR Mode(GFSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	69.43	PK	H	28.10	1.80	0.00	99.33	N/A	N/A
2402.00	59.26	AV	H	28.10	1.80	0.00	89.16	N/A	N/A
2402.00	64.29	PK	V	28.10	1.80	0.00	94.19	N/A	N/A
2402.00	53.41	AV	V	28.10	1.80	0.00	83.31	N/A	N/A
2390.00	26.95	PK	H	28.08	1.80	0.00	56.83	74.00	17.17
2390.00	15.57	AV	H	28.08	1.80	0.00	45.45	54.00	8.55
4804.00	45.51	PK	H	32.91	3.17	25.60	55.99	74.00	18.01
4804.00	34.38	AV	H	32.91	3.17	25.60	44.86	54.00	9.14
7206.00	41.18	PK	H	35.74	4.82	25.60	56.14	74.00	17.86
7206.00	28.14	AV	H	35.74	4.82	25.60	43.10	54.00	10.90
Middle Channel: 2441 MHz									
2441.00	71.13	PK	H	28.18	1.82	0.00	101.13	N/A	N/A
2441.00	60.15	AV	H	28.18	1.82	0.00	90.15	N/A	N/A
2441.00	62.24	PK	V	28.18	1.82	0.00	92.24	N/A	N/A
2441.00	51.61	AV	V	28.18	1.82	0.00	81.61	N/A	N/A
4882.00	46.05	PK	H	33.06	3.27	25.66	56.72	74.00	17.28
4882.00	33.47	AV	H	33.06	3.27	25.66	44.14	54.00	9.86
7323.00	41.05	PK	H	36.04	4.62	25.73	55.98	74.00	18.02
7323.00	28.74	AV	H	36.04	4.62	25.73	43.67	54.00	10.33
High Channel: 2480 MHz									
2480.00	70.85	PK	H	28.26	1.84	0.00	100.95	N/A	N/A
2480.00	60.84	AV	H	28.26	1.84	0.00	90.94	N/A	N/A
2480.00	63.85	PK	V	28.26	1.84	0.00	93.95	N/A	N/A
2480.00	53.74	AV	V	28.26	1.84	0.00	83.84	N/A	N/A
2483.50	29.04	PK	H	28.27	1.84	0.00	59.15	74.00	14.85
2483.50	18.21	AV	H	28.27	1.84	0.00	48.32	54.00	5.68
4960.00	46.31	PK	H	33.22	3.23	25.63	57.13	74.00	16.87
4960.00	34.45	AV	H	33.22	3.23	25.63	45.27	54.00	8.73
7440.00	40.22	PK	H	36.34	4.41	25.85	55.12	74.00	18.88
7440.00	27.31	AV	H	36.34	4.41	25.85	42.21	54.00	11.79

Worst plots (GFSK Low channel was the worst**)**
Horizontal

Fundamental Test with Band Rejection Filter







Vertical


Fundamental
Test with Band
Rejection Filter
100.0 dBuV/m
Limit1:
Limit2:
50
0.0
1000.000 1500.00 2000.00 2500.00 3000.00 3500.00 4000.00 4500.00 5000.00 6000.00 MHz


100.0 dBuV/m
Limit1:
Limit2:
50
0.0
6000.000 7200.00 8400.00 9600.00 10800.00 12000.00 13200.00 14400.00 15600.00 18000.00 MHz


100.0 dBuV/m
Limit1:
Limit2:
50
0.0
18000.000 18700.00 19400.00 20100.00 20800.00 21500.00 22200.00 22900.00 23600.00 25000.00 MHz

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	21.4 °C
Relative Humidity:	35 %
ATM Pressure:	102.0 kPa
Test by:	Tiger Mo
Test Date:	2020-12-21

Test Result: Compliance. Please refer to following tables and plots

FINAL

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
BDR (GFSK)	Low	2402-2403	1.002	0.63
	Middle	2441-2442	1.002	0.63
	High	2480-2479	1.002	0.63
EDR (π/4-DQPSK)	Low	2402-2403	1.002	0.87
	Middle	2441-2442	1.002	0.88
	High	2480-2479	1.002	0.87
EDR (8DPSK)	Low	2402-2403	1.002	0.85
	Middle	2441-2442	1.002	0.85
	High	2480-2479	1.002	0.85

Note: Limit= (2/3) × 20dB bandwidth

BDR Mode (GFSK):

Low Channel



Date: 21.DEC.2020 13:23:20

Middle Channel



Date: 21.DEC.2020 13:24:15

High Channel



Date: 21.DEC.2020 13:25:01

EDR Mode (π/4-DQPSK):

Low Channel



Date: 21.DEC.2020 13:19:18

Middle Channel



Date: 21.DEC.2020 13:20:41

High Channel



Date: 21.DEC.2020 13:21:27

EDR Mode (8DPSK):

Low Channel



Date: 21.DEC.2020 13:16:17

Middle Channel



Date: 21.DEC.2020 13:17:15

High Channel



Date: 21.DEC.2020 13:18:18

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.4 °C
Relative Humidity:	35 %
ATM Pressure:	102.0 kPa
Test by:	Tiger Mo
Test Date:	2020-12-21

Test Result: Compliance. Please refer to following tables and plots

FINAL

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.948
	Middle	2441	0.948
	High	2480	0.948
EDR Mode (π/4-DQPSK)	Low	2402	1.312
	Middle	2441	1.316
	High	2480	1.312
EDR Mode (8DPSK)	Low	2402	1.268
	Middle	2441	1.272
	High	2480	1.272

BDR Mode (GFSK):

Low Channel



Date: 21.DEC.2020 11:15:40

Middle Channel



Date: 21.DEC.2020 11:16:53

High Channel



Date: 21.DEC.2020 11:17:50

EDR Mode (π/4-DQPSK):

Low Channel



Date: 21.DEC.2020 11:20:37

Middle Channel



Date: 21.DEC.2020 11:21:38

High Channel



Date: 21.DEC.2020 11:22:40

EDR Mode (8DPSK):

Low Channel



Date: 21.DEC.2020 11:26:09

Middle Channel



Date: 21.DEC.2020 11:27:10

High Channel



Date: 21.DEC.2020 11:28:17

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.4~22.6 °C
Relative Humidity:	34~35 %
ATM Pressure:	101.6~102.0 kPa
Test by:	Tiger Mo
Test Date:	2020-12-21~2020-12-22

Test Result: Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Test mode	Frequency Range (MHz)	Number of Hopping Channel	Limit
GFSK	2400-2483.5	79	15
π/4-DQPSK	2400-2483.5	79	
8DPSK	2400-2483.5	79	

BDR Mode (GFSK)



Date: 21.DEC.2020 13:28:47

EDR Mode (π/4-DQPSK)



Date: 22.DEC.2020 14:07:36

EDR Mode (8DPSK)



Date: 22.DEC.2020 14:12:18

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.4~22.6 °C
Relative Humidity:	34~35 %
ATM Pressure:	101.6~102.0 kPa
Test by:	Tiger Mo
Test Date:	2020-12-21~2020-12-22

Test Result: Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Mode	Packet type	Channel	Frequency (MHz)	Puse width (ms)	Result (s)	Limit (s)
GFSK	DH1	Middle	2441	0.392	0.125	0.4
	DH3	Middle	2441	1.677	0.268	
	DH5	Middle	2441	2.957	0.315	
π/4-DQPSK	2DH1	Middle	2441	0.393	0.126	
	2DH3	Middle	2441	1.688	0.270	
	2DH5	Middle	2441	2.968	0.317	
8DPSK	3DH1	Middle	2441	0.421	0.135	
	3DH3	Middle	2441	1.704	0.273	
	3DH5	Middle	2441	2.960	0.316	

Note:
DH1:Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s
DH3:Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s
DH5:Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s

BDR Mode (GFSK):

DH1: Middle Channel



Date: 21.DEC.2020 14:01:39

DH3: Middle Channel



Date: 21.DEC.2020 14:03:29

DH5: Middle Channel



Date: 21.DEC.2020 14:04:38

EDR Mode (π/4-DQPSK):

2DH1: Middle Channel



Date: 21.DEC.2020 14:07:01

2DH3: Middle Channel



Date: 22.DEC.2020 14:32:10

2DH5: Middle Channel



Date: 22.DEC.2020 14:30:55

EDR Mode (8DPSK):

3DH1: Middle Channel



Date: 21.DEC.2020 14:34:47

3DH3: Middle Channel



Date: 21.DEC.2020 14:39:23

3DH5: Middle Channel



Date: 22.DEC.2020 14:34:20

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A
Agilent	USB Wideband Power Sensor	U2021XA	MY5425009	2020-09-12	2021-09-12

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.6 °C
Relative Humidity:	34 %
ATM Pressure:	101.6 kPa
Test by:	Tiger Mo
Test Date:	2020-12-22

Test Result: Compliance.

Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	1.74	21
	2441	1.84	21
	2480	1.87	21
EDR Mode (π/4-DQPSK)	2402	-1.74	21
	2441	-1.77	21
	2480	-1.86	21
EDR Mode (8DPSK)	2402	-1.37	21
	2441	-1.43	21
	2480	-1.46	21

Note: The data above was tested in conducted mode.

FINAL

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

FINAL

Test Data

Environmental Conditions

Temperature:	21.4~22.6 °C
Relative Humidity:	34~35 %
ATM Pressure:	101.6~102.0 kPa
Test by:	Tiger Mo
Test Date:	2020-12-21~2020-12-22

Test Result: Compliance
All emission outside the operation band under more than 20dB below the desired

Single Channel Mode,
BDR Mode (GFSK):

Band Edge, Left Side



Date: 21.DEC.2020 11:37:00

Band Edge, Right Side



Date: 21.DEC.2020 11:38:08

EDR Mode (π/4-DQPSK):

Band Edge, Left Side

Date: 21.DEC.2020 11:33:02

Band Edge, Right Side



Date: 21.DEC.2020 11:33:35

EDR Mode (8DPSK):

Band Edge, Left Side



Date: 21.DEC.2020 11:34:14

Band Edge, Right Side



Date: 21.DEC.2020 11:34:44

Hopping Mode,
BDR Mode (GFSK):

Band Edge, Left Side



Date: 21.DEC.2020 11:43:20

Band Edge, Right Side



Date: 21.DEC.2020 11:47:12

EDR Mode (π/4-DQPSK):

Band Edge, Left Side



Date: 22.DEC.2020 14:50:56

Band Edge, Right Side

Date: 22.DEC.2020 15:10:21

EDR Mode (8DPSK):

Band Edge, Left Side



Date: 22.DEC.2020 14:52:51

Band Edge, Right Side



Date: 22.DEC.2020 14:57:49

******* END OF REPORT *******