



TEST REPORT

Test item description: Network camera

Trademark(s): I-O DATA

Model/Type reference: TS-NS240W

Applicant's name: I-O DATA DEVICE, INC.

Address: 3-10, Sakurada-machi, Kanazawa-shi, Ishikawa, Japan

Manufacturer: I-O DATA DEVICE, INC.

Address: 3-10, Sakurada-machi, Kanazawa-shi, Ishikawa, Japan

Prepared By: Shenzhen CTB Testing Technology Co., Ltd.

Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: Apr. 24, 2026

Sample tested Date: Apr. 24, 2026 to May. 12, 2026

Issue Date: May. 12, 2026

Report No.: CTB26042404601RF01

Test Standards: MIC Public Notice 88:2004, annex 1 and annex 43
Ordinance Article 2 paragraph 1 item (19)
ARIB STD-T66 V3.7

Test Results: PASS

Remark: This is WIFI-2.4GHz band radio test report.

Compiled by:

Reviewed by:

Approved by:

Kai Chen

Martin Feng

Kai ChenMartin FengBin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. The tested sample(s) and the sample information are provided by the applicant. The authenticity, accuracy, and completeness of the provided information are the sole responsibility of the applicant. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The result decision rules of our laboratory are based solely on the direct comparison between the actual measured values of test results and the standard limits, without considering the measurement uncertainty. "★" indicates the testing items were fulfilled by subcontracted lab. "×" indicates the items are not in CNAS accreditation scope.

Table of Contents

Page

1 . TEST SUMMARY	5
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 Carrier Frequency of Channels	9
2.3 Table for Filed Antenna	9
2.4 DESCRIPTION OF TEST MODES	9
2.5 TESTCONDITIONS	10
2.6 DESCRIPTION OF SUPPORT UNITS(CONDUCTEDMODE)	10
2.7 MEASUREMENT INSTRUMENTS LIST	11
3 . RF SHIELDINGMETHOD	13
4 FREQUENCYERROR	14
4.1 LIMIT	14
4.2 MEASURING INSTRUMENTS AND SETTING	14
4.3 TEST PROCEDURE	14
4.4 TEST SETUP LAYOUT	14
4.5 EUT OPERATION DURING TEST	14
4.6 TEST RESULT	15
5ANTENNAPOWER	17
5.1 LIMIT	17
5.2 MEASURING INSTRUMENTS AND SETTING	17
5.3 TEST PROCEDURE	17
5.4 TEST SETUP LAYOUT	18
5.5 TEST RESULT	19
6OCCUPIEDBANDWITH and Spread Factor	26
6.1 LIMIT	26
6.2 MEASURING INSTRUMENTS AND SETTING	26
6.3 TEST PROCEDURE	26
6.4 TEST SETUP LAYOUT	26
6.5 EUT OPERATION DURING TEST	26
6.6 TEST RESULT	27
7UNWANTED EMISSION INTENSITY MEASUREMENT	34
7.1 LIMIT	34
7.2 MEASURING INSTRUMENTS AND SETTING	34

Table of Contents**Page**

7.3 TEST PROCEDURE	34
7.4 TEST SETUP LAYOUT	35
7.5 TEST RESULT	36
8 UNWANTED EMISSION INTENSITY MEASUREMENT	60
8.1 LIMIT	60
8.2 MEASURING INSTRUMENTS AND SETTING	60
8.3 TEST PROCEDURE	60
8.4 TEST RESULT	61
9 TRANSMISSION ANTENNA GAIN (EIRP ANTENNA POWER) MEASUREMENT	67
9.1 LIMIT	67
9.2 MEASURING INSTRUMENTS AND SETTING	67
9.3 TEST PROCEDURE	67
9.4 TEST SETUP LAYOUT	68
9.5 EUT OPERATION DURING TEST	68
9.6 TEST RESULT	68
10 TRANSMISSION RADIATION ANGLE WIDTH (3DB BEAMWIDTH) MEASUREMENT	69
10.1 LIMIT	69
10.2 MEASURING INSTRUMENTS AND SETTING	69
10.3 TEST PROCEDURE	69
10.4 TEST SETUP LAYOUT	70
10.5 EUT OPERATION DURING TEST	70
10.6 TEST RESULT	70
11 RADIO INTERFERENCE PREVENTION CAPABILITY MEASUREMENT	71
11.1 LIMIT	71
11.2 MEASURING ID CODE SOFTWARE	71
11.3 TEST PROCEDURE	71
11.4 TEST SETUP LAYOUT	71
11.5 EUT OPERATION DURING TEST	71
11.6 TEST RESULT	71
12 CARRIER SENSING FUNCTION	72
12.1 TEST REQUIREMENT	72
12.2 BLOCK DIAGRAM OF TEST SETUP	72
12.3 TEST PROCEDURE	72
12.4 TEST RESULT	72

Table of Contents

Page

13 NUMBER OF CARRIERS

73

14 EUT TEST PHOTO

74

1. TEST SUMMARY

1.1 Version

Report No.	Issue Date	Description	Approved
CTB26042404601RF01	May. 12, 2026	Original	Valid

1.2 TEST PROCEDURES AND RESULTS

Part	Rule Section	Description of Test	Result
4.1	3	Frequency Error	Complies
4.3	4	Occupied Bandwidth (99%), Spread-spectrum Bandwidth (90%) and Spread Factor	Complies
4.4	5	Unwanted Emission Intensity	Complies
4.2	6	Antenna Power Error	Complies
4.5	7	Limitation of Collateral Emission of Receiver	Complies
4.6	8	Transmission Antenna Gain (EIRP Antenna Power)	N/A
4.7	9	Transmission Radiation Angle Width (3dB Beamwidth)	N/A
4.8	10	Radio Interference Prevention Capability	Complies
4.9	Note 2	Carrier Sense Capability	Complies
4.10	Note 3	Number of carriers	Complies

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) Note2: MIC Public Notice 88:2004, annex 1 and annex 43

(3) Note3: MIC Ordinance Regulating Radio Equipment Section 4.17 of Article 49.20

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Item	Uncertainty
Occupancy bandwidth	54.3kHz
Conducted output power Above 1G	0.9dB
Conducted output power below 1G	0.9dB
Power Spectral Density , Conduction	0.9dB
Conduction spurious emissions	2.0dB
Out of band emission	2.0dB
3m camber Radiated spurious emission(30MHz-1GHz)	4.6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5.1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB
Frequency Error	54.3Hz
Adjacent channel power below 1G	2.6dB
Adjacent channel power Above 1G	2.8dB
humidity uncertainty	5.5%
Temperature uncertainty	0.63℃
frequency	1×10^{-7}

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Model/Type reference:	TS-NS240W
Model Description:	N/A
Wi-Fi Specification:	IEEE 802.11b/g/n/ax
Hardware Version:	LX500_9269
Software Version:	V1.0.3.7
Operation Frequency:	IEEE 802.11b/g/n20/ax20: 2412-2472MHz IEEE 802.11n40/ax40: 2422-2462MHz
Max. RF output power:	802.11b: 4mW/MHz 802.11g: 4mW/MHz 802.11n20: 3mW/MHz 802.11n40: 2mW/MHz 802.11ax20: 3mW/MHz 802.11ax40: 3mW/MHz
Type of Modulation:	802.11b: DSSS(CCK/DQPSK/DBPSK) 802.11g: OFDM(BPSK/QPSK/16QAM/64QAM) 802.11n/ax (HT20/40): OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmit Data Rate:	802.11b: 1M/2M/5.5M/11M bps 802.11g: 6M/9M/12M/18M/24M/36M/48M/54M bps 802.11n20/ax20: up to 75M bps 802.11n40/ax40: up to 150M bps
Antenna installation:	Internal antenna
Antenna Gain:	2.85dBi
Ratings:	INPUT: AC 100-240V~50/60Hz OUTPUT: 12V=1A

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. This report is for Wi-Fi test report.

2.2 Carrier Frequency of Channels

Channel List for 802.11b/g/n/ax(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452	13	2472
02	2417	06	2437	10	2457	/	/
03	2422	07	2442	11	2462	/	/
04	2427	08	2447	12	2467	/	/

Channel List for 802.11n/ax(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
/	/	05	2432	09	2452	/	/
/	/	06	2437	10	2457	/	/
03	2422	07	2442	11	2462	/	/
04	2427	08	2447	/	/	/	/

Mode	Low channel (MHz)	Middle channel(MHz)	High channel(MHz)
b	2412	2442	2472
g	2412	2442	2472
n20	2412	2442	2472
ax20	2412	2442	2472
n40	2422	2442	2462
ax40	2422	2442	2462

2.3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain(dBi)	NOTE
1	N/A	2.4G antenna	Internal antenna	2.85dBi	N/A

2.4DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX
Mode 2	RX

2.5 TEST CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Supply Voltage				
	PC supply power V	Module input power V	Rated module power V	Tolerance (%)
Normal	100	3.3	3.3	
+10%	110	3.3	3.3	
-10%	90	3.3	3.3	
Others				
Temperature (°C)		20-25		
Relative humidity		54 %.		
ATM Pressure:		1010 mbar		
Note 1: When the input voltage is reduced or increased by 10%, the regulator voltage changes of less than 1%. So the following test items are conducted in the normal voltage.				

BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Mode 1:



2.6 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Test item description	Trademark(s)	Model/Type reference	Note
1	Network camera	I-O DATA	TS-NS240W	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

1. The support equipment was authorized by Declaration of Confirmation.
2. For detachable type I/O cable should be specified the length in cm in 『Length』 column.
3. "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

2.7 MEASUREMENT INSTRUMENTS LIST

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2026/6/27
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2026/6/27
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2026/6/27
4	Communication test set	R&S	CMW500	108058	V3.5.80	2026/6/27
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2026/6/27
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2026/6/27
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2026/6/27
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2026/6/27
9	2.4 GHz Filter	Shenxiang	MSF2400-24 83.5MS-1154	20181015001	/	2026/6/29
10	5 GHz Filter	Shenxiang	MSF5150-58 50MS-1155	20181015001	/	2026/6/29
11	Filter	Xingbo	XBLBQ-DZA 120	190821-1-1	/	2026/6/29
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2026/6/27
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2026/6/27
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	/	2027/6/21
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 (104489/003)	2026/6/27
18	Amplifier	HP	8447E	2945A02747	/	2026/6/27

19	Amplifier	Agilent	8449B	3008A01838	/	2026/6/27
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2026/6/27
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2026/6/27
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2026/6/27
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2026/6/27
26	Amplifier	AEROFLEX	Aeroflex	097	/	2026/6/27
27	Power Meter	KEYSIGHT	N1912AP	N/A	A.05.00	2026/6/27
28	DC power supply	Agilent	E3640A	MY53050046	/	2026/6/27

Remark: Calibration institution "GRG METROLOGY & TEST GROUP Co., LTD."

Remark: Calibration based on Article 24-2, paragraph 4 of the Radio Act method c.

3. RF SHIELDING METHOD

We apply the product for Japan RF certification. The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.

Confirmation method

☐ Sealed with special screws.
☐ Plastic chassis is being welded using ultrasonic waves.
☐ Chassis is glued using a special adhesive.
☐ Metal covers are spot-fused.
☐ Cover is specially interlocked.
☐ RF and Modulation components are covered with shielding case and this shielding case is soldered.
☐ Shield case is welded ant RF and modulations parts, and ID-ROM is welded using BGA Method.
☐ Shield case is welded ant RF and modulations parts, and ID-ROM is glued at its lead with a special adhesive.
☐ Shield case is welded ant RF and modulations parts, and ID-ROM is glued with a non-transparent laminating agent.
☒ Other: All RF and modulation section packet in one IC, and IC is welded using BGA Method, and RF module is welded on the main board, end-User can't open it easily.

The RF chip has a terminal distance to less than 1mm and has 48 terminal.



4 FREQUENCY ERROR

4.1 LIMIT

Item	Limits
Frequency Error	+/-50ppm

4.2 MEASURING INSTRUMENTS AND SETTING

The following table is the setting of Spectrum Analyzer.


Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	10KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.3 TEST PROCEDURE

1. In the case of unmodulated signal (continuous or continuous burst), measure the frequency directly by a frequency meter.
2. In the case of burst waves, the measurement shall be done for enough time in order to obtain the enough measuring accuracy, and the average of the measured values becomes the final value.
3. In the case of a test mode with a specific frequency spectrum, measure the frequency of the specific spectrum by a spectrum analyzer connected a frequency meter.
4. In the cases above, if the frequency equivalent to the test frequency is not directly measured in principle, it shall be obtained by necessary calculation.

In the case of modulated signal, if there is no specific spectrum measurable by a spectrum analyzer but a specific dip is observed, it is allowed to measure the frequency with the signal generator (synthesized). That is, observe a signal of the signal generator concurrently (or alternately) with the tested signal using the spectrum analyzer while setting the frequency of the signal generator to the position of the dip on the screen of the spectrum analyzer, and determine the frequency of the signal generator at the time as a measured value.

4.4 TEST SETUP LAYOUT






4.5 EUT OPERATION DURING TEST

The EUT was placed on the test table and programmed in un-modulation function.

4.6 TEST RESULT

Temperature:	23℃	Relative Humidity:	54%
Test Mode:	TX Mode	Pressure:	101kPa

Test Voltage	Test Frequency (MHz)	Measured Frequency (MHz)	Frequency Error(ppm)	Limit (ppm)	P/F
Normal Voltage	2412	2411.991	-3.731	±50	PASS
	2442	2441.992	-3.276	±50	PASS
	2472	2471.992	-3.236	±50	PASS

Mode	Channel	Test graph
Normal Voltage	Low	
	Middle	
	High	

5ANTENNAPOWER

5.1 LIMIT

Item	Limits
Antenna Power Density	802.11b,g,n(HT20),ax(HE20):10mW/MHz 802.11n(HT40),ax(HE40): 5mW/MHz
Antenna Power Error	+20% (Base on manufacturer declare antenna power density)

5.2 MEASURING INSTRUMENTS AND SETTING

The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.3 TEST PROCEDURE

Attenuation of the attenuator shall be set to provide an optimum input level to the spectrum analyzer.

1. Set the spectrum analyzer as follows for searching the frequency that outputs the maximum antenna power:

Center frequency: Test frequency

Frequency sweep width: Approximately twice of the occupied bandwidth

Resolution bandwidth: 1MHz

Video bandwidth: Approximately three times of the resolution bandwidth

Y-axis scale: 10dB/Div

Sweep time:Minimum time to ensure the measuring accuracy

(In the case of burst wave, one burst shall be included per data point.)

Trigger condition: Free run

Data points: 400 points or more

Sweep mode: Continuous sweep

Detection mode: Positive peak

Display mode: Maximum hold

2. When the trace is complete, find the peak value of the power envelope and record.

In the case of bandwidth above RBW, connect to power meter directly.

3. Calculate antenna power density by the formula below

$PT(mW/MHz) = \text{Total Output Power (mW)} / \text{Burst Ratio} / \text{Spread Bandwidth (MHz)}$ Burst Ratio =ON Time / OFF Time

4. Antenna Power Error is definition that actual measure antenna power tolerance between + 20% to - 80% power range that base on manufacturer declare the conducted power density.

5.4 TEST SETUP LAYOUT




EST DEVIATION

There is no deviation with the original standard.



5.5 TEST RESULT


Temperature:	23℃	Relative Humidity:	54%
Test Mode:	TX Mode		101kPa

Test voltage (V)	Mode	Channel (MHz)	Antenna Power (dBm/MHz)	output power (mW/MHz)	Rated output power (mW/MHz)	Tolerance (%)	Limit
Normal	802.11b	2412	4.289	2.685	4	-32.88	10mW/MHz +20%
		2442	5.166	3.285	4	-17.86	
		2472	3.455	2.216	4	-44.61	
	802.11g	2412	4.96	3.133	4	-21.67	
		2442	4.558	2.856	4	-28.59	
		2472	4.156	2.604	4	-34.91	
	802.11n(HT20)	2412	4.66	2.924	3	-2.53	
		2442	4.234	2.651	3	-11.64	
		2472	3.828	2.414	3	-19.52	
	802.11ax(HT20)	2412	3.115	2.049	3	-31.71	5mW/MHz +20%
		2442	4.174	2.615	3	-12.85	
		2472	3.631	2.307	3	-23.09	
	802.11n(HT40)	2422	2.326	1.708	2	-14.58	
		2442	1.704	1.480	2	-25.98	
		2462	1.358	1.367	2	-31.65	
	802.11ax(HT40)	2422	3.302	2.139	3	-28.70	
		2442	3.364	2.170	3	-27.68	
		2462	2.655	1.843	3	-38.57	


Normal Voltage		
Mode	Channel	Test graph
802.11b	Low	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.411240000 GHz Ref Offset 6.99 dB Ref 26.99 dBm Mkr1 301.0 ms 4.289 dBm Center 2.411240000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 1.000 s (1001 pts)</p>
	Middle	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.441280000 GHz Ref Offset 7.02 dB Ref 27.02 dBm Mkr1 589.0 ms 5.166 dBm Center 2.441280000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 1.000 s (1001 pts)</p>
	High	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.471280000 GHz Ref Offset 7.04 dB Ref 27.04 dBm Mkr1 879.0 ms 3.455 dBm Center 2.471280000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 1.000 s (1001 pts)</p>

Normal Voltage		
Mode	Channel	Test graph
802.11g	Low	<p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.413680000 GHz Res BW 1.0 MHz Span 0 Hz Ref Offset 6.99 dB Ref 26.99 dBm Mkr1 631.0 ms 4.960 dBm</p>
	Middle	<p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.443680000 GHz Res BW 1.0 MHz Span 0 Hz Ref Offset 7.02 dB Ref 27.02 dBm Mkr1 959.0 ms 4.558 dBm</p>
	High	<p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.473680000 GHz Res BW 1.0 MHz Span 0 Hz Ref Offset 7.04 dB Ref 27.04 dBm Mkr1 187.0 ms 4.156 dBm</p>

Normal Voltage		
Mode	Channel	Test graph
802.11n/HT20	Low	
	Middle	
	High	

Normal Voltage		
Mode	Channel	Test graph
802.11ax/HT20	Low	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.414000000 GHz Ref Offset 6.99 dB Ref 26.99 dBm Mkr1 665.0 ms 3.115 dBm Center 2.414000000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 1.000 s (1001 pts)</p>
	Middle	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.444000000 GHz Ref Offset 7.02 dB Ref 27.02 dBm Mkr1 261.0 ms 4.174 dBm Center 2.444000000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 1.000 s (1001 pts)</p>
	High	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.474000000 GHz Ref Offset 7.04 dB Ref 27.04 dBm Mkr1 71.00 ms 3.631 dBm Center 2.474000000 GHz Res BW 1.0 MHz #VBW 1.0 MHz Sweep 1.000 s (1001 pts)</p>

Normal Voltage		
Mode	Channel	Test graph
802.11 n/HT40	Low	
	Middle	
	High	

Normal Voltage		
Mode	Channel	Test graph
802.11 ax/HT40	Low	 <p>Agilent Spectrum Analyzer - Sweep SA Center Freq 2.439360000 GHz Res BW 1.0 MHz Span 0 Hz Mkr1 159.0 ms 3.364 dBm</p>
	Middle	 <p>Agilent Spectrum Analyzer - Sweep SA Center Freq 2.441220000 GHz Res BW 1.0 MHz Span 0 Hz Mkr1 741.0 ms 2.908 dBm</p>
	High	 <p>Agilent Spectrum Analyzer - Sweep SA Center Freq 2.461220000 GHz Res BW 1.0 MHz Span 0 Hz Mkr1 122.0 ms 2.655 dBm</p>

6 OCCUPIED BANDWIDTH and Spread Factor

6.1 LIMIT

Item	Limits
Occupied Band Width	OFDM (802.11n40/ax40): 40MHz Others : 26MHz or less

6.2 MEASURING INSTRUMENTS AND SETTING


The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	300KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3 TEST PROCEDURE

- Setting of SA is following as: RB: 300kHz / VB: 300kHz / SPAN: 40MHz / AT: 30dB Ref: 20dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
- EUT have transmitted the maximum modulation signal and fixed channelize (For DSSS or OFDM Device) or continuous maximum power of hopping mode(For FHSS Device). SA set to 99% of occupied bandwidth to measure occupied bandwidth. The limit is less than 26MHz(For DSSS or OFDM Device) or 83.5MHz(For FHSS Device).
- SA set to 90% of occupied bandwidth to measure Spread Spectrum Bandwidth and must greater than 500kHz.
- Spread Spectrum Factor = Spread Spectrum Bandwidth / modulation rate of EUT.
The modulation rate: MR=1.375 for 802.11b, MR=1.5 for 802.11g/n20, MR=3 for 802.11n40.

6.4 TEST SETUP LAYOUT



EST DEVIATION

There is no deviation with the original standard.

6.5 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULT

Temperature:	23℃	Relative Humidity:	54%
Test Mode:	TX Mode	Pressure:	101kPa


Mode	Test Voltage	Frequency (MHz)	Occupied Bandwidth 99%(MHz)	Spread Bandwidth 90%(MHz)
802.11b	Normal	2412	15.208	10.662
		2442	15.213	10.839
		2472	15.077	10.953
802.11g	Normal	2412	16.432	14.280
		2442	16.429	14.396
		2472	16.353	14.647
802.11n/HT 20	Normal	2412	17.571	15.205
		2442	17.592	15.105
		2472	17.571	15.253
802.11n/HT 40	Normal	2422	36.029	31.065
		2442	36.025	31.533
		2462	36.040	31.405
802.11ax/H T20	Normal	2412	18.894	16.338
		2442	18.921	16.169
		2472	18.755	16.216
802.11ax/H T40	Normal	2422	37.454	32.389
		2442	37.725	32.407
		2462	37.693	31.897

802.11b Normal Voltage


99% Bandwidth



90% Bandwidth



2412MHz




2412 MHz



2442 MHz



2442 MHz




2472 MHz


2472 MHz

802.11g Normal Voltage


99% Bandwidth




90% Bandwidth




2412MHz



2412 MHz



2442 MHz



2442 MHz




2472 MHz


2472 MHz

802.11n/HT20 Normal Voltage

99% Bandwidth



90% Bandwidth



2412MHz




2412 MHz



2442 MHz



2442 MHz



2472 MHz


2472 MHz

802.11n/HT40 Normal Voltage


99% Bandwidth



90% Bandwidth




2422MHz




2412 MHz



2442 MHz



2442 MHz



2462 MHz


2462 MHz

802.11ax/HT20 Normal Voltage

99% Bandwidth



90% Bandwidth




2412MHz




2412 MHz



2442 MHz



2442 MHz




2472 MHz


2472 MHz

802.11ax/HT40 Normal Voltage


99% Bandwidth



90% Bandwidth



2422MHz



2412 MHz



2442 MHz



2442 MHz



2462 MHz

2462 MHz

7 UNWANTED EMISSION INTENSITY MEASUREMENT

7.1 LIMIT

Item	Limits
TX Spurious Emission	$\leq 2.5 \mu\text{W/MHz}$ ($30\text{MHz} \leq f \leq 1000\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($1000\text{MHz} < f \leq 2387\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2387\text{MHz} < f \leq 2400\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2483.5\text{MHz} \leq f < 2496.5\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($2496.5\text{MHz} \leq f < 12500\text{MHz}$)

7.2 MEASURING INSTRUMENTS AND SETTING


The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3 TEST PROCEDURE

- EUT have transmitted the maximum modulation signal and fixed channelize.
- Setting of SA is following as: Below 1GHz RB: 100kHz / VB: 100kHz
Above 1GHz RB: 1MHz / VB: 1MHz / AT: 10dB Ref: 0dBm / Sweep time: Auto
Sweep Mode: Continuous sweep / Detect mode: Positive peak
Trace mode: Max hold
- Setting of SA is following as 30MHz and stop frequency 1000MHz Then to mark peak reading value + cable loss shall be less than 2.5μW.
- Setting of SA is following as 1000MHz and stop frequency 2387MHz Then to mark peak reading value + cable loss shall be less than 2.5μW.
- SA adjusted to start frequency 2387MHz and stop frequency 2400MHz. Then to mark peak reading value + cable loss shall be less than 25μW.
- SA adjusted to start frequency 2483.5MHz and stop frequency 2496.5MHz Then to mark peak reading value + cable loss shall be less than 25μW
- SA adjusted to start frequency 2496.5MHz and stop frequency 12500MHz Then to mark peak reading value + cable loss shall be less than 2.5μW
- Measure side band spurious as follows: For 2.4GHz band: 2374MHz~2400MHz and 2483.5MHz~2509.5MHz RBW = VBW = 30kHz, Result_Value = Measured_Value + 15.2 [dBm]
- If the Result_Value is over the requirement, take total sum of 1MHz band centered at the spur frequency like ACLP measurement as Result_Value.

7.4 TEST SETUP LAYOUT




EST DEVIATION


There is no deviation with the original standard.


7.5 TEST RESULT

Temperature:	23℃	Relative Humidity:	54%
Test Voltage:	Normal Voltage	Pressure:	101kPa


Test mode	Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
802.11b	Low	30MHz≤f≤1000MHz	888.45	-53.28	0.047	2.5	PASS
		1000MHz < f≤2387MHz	2241.36	-42.76	0.053	2.5	PASS
		2387MHz < f≤2400MHz	2396.75	-33.17	0.482	25	PASS
		2483.5MHz≤f < 2496.5MHz	2488.08	-42.6	0.055	25	PASS
		2496.5MHz≤f < 12750MHz	4577.96	-37.59	0.174	2.5	PASS
	Middle	30MHz≤f≤1000MHz	942.77	-51.9	0.006	2.5	PASS
		1000MHz < f≤2387MHz	2041.64	-42.97	0.050	2.5	PASS
		2387MHz < f≤2400MHz	2391.42	-43.02	0.050	25	PASS
		2483.5MHz≤f < 2496.5MHz	2484.64	-42.57	0.055	25	PASS
		2496.5MHz≤f < 12750MHz	4567.71	-35.05	0.313	2.5	PASS
	High	30MHz≤f≤1000MHz	753.62	-53.89	0.004	2.5	PASS
		1000MHz < f≤2387MHz	2285.75	-41.74	0.067	2.5	PASS
		2387MHz < f≤2400MHz	2387.61	-41.79	0.066	25	PASS
		2483.5MHz≤f < 2496.5MHz	2487.01	-34.71	0.338	25	PASS
		2496.5MHz≤f < 12750MHz	4567.71	-31.17	0.764	2.5	PASS










Test mode	Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
802.11g	Low	30MHz≤f≤1000MHz	875.84	-53.13	0.049	2.5	PASS
		1000MHz < f≤2387MHz	2330.13	-43.02	0.050	2.5	PASS
		2387MHz < f≤2400MHz	2399.13	-25.6	2.754	25	PASS
		2483.5MHz≤f < 2496.5MHz	2489.56	-42.88	0.052	25	PASS
		2496.5MHz≤f < 12750MHz	5213.68	-34.72	0.337	2.5	PASS
	Middle	30MHz≤f≤1000MHz	903	-53.5	0.004	2.5	PASS
		1000MHz < f≤2387MHz	2256.62	-42.47	0.057	2.5	PASS
		2387MHz < f≤2400MHz	2391.54	-42.49	0.056	25	PASS
		2483.5MHz≤f < 2496.5MHz	2494.54	-42.57	0.055	25	PASS
		2496.5MHz≤f < 12750MHz	4598.47	-39.78	0.105	2.5	PASS
	High	30MHz≤f≤1000MHz	894.27	-53.76	0.004	2.5	PASS
		1000MHz < f≤2387MHz	2206.69	-42.33	0.058	2.5	PASS
		2387MHz < f≤2400MHz	2397.45	-42.93	0.051	25	PASS
		2483.5MHz≤f < 2496.5MHz	2483.73	-24.18	3.819	25	PASS
		2496.5MHz≤f < 12750MHz	4577.96	-33.97	0.401	2.5	PASS










Test mode	Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
802.11n 20	Low	30MHz≤f≤1000MHz	683.78	-54.14	0.039	2.5	PASS
		1000MHz < f≤2387MHz	2271.88	-42.61	0.055	2.5	PASS
		2387MHz < f≤2400MHz	2397.92	-28.61	1.377	25	PASS
		2483.5MHz≤f < 2496.5MHz	2488.88	-42.93	0.051	25	PASS
		2496.5MHz≤f < 12750MHz	4598.47	-40.22	0.095	2.5	PASS
	Middle	30MHz≤f≤1000MHz	773.02	-53.83	0.004	2.5	PASS
		1000MHz < f≤2387MHz	2339.84	-42.27	0.059	2.5	PASS
		2387MHz < f≤2400MHz	2399.65	-42.71	0.054	25	PASS
		2483.5MHz≤f < 2496.5MHz	2485.63	-42.58	0.055	25	PASS
		2496.5MHz≤f < 12750MHz	5213.68	-33.29	0.469	2.5	PASS
	High	30MHz≤f≤1000MHz	996.12	-53.64	0.004	2.5	PASS
		1000MHz < f≤2387MHz	1990.32	-42.61	0.055	2.5	PASS
		2387MHz < f≤2400MHz	2396.04	-42.88	0.052	25	PASS
		2483.5MHz≤f < 2496.5MHz	2484.85	-32.51	0.561	25	PASS
		2496.5MHz≤f < 12750MHz	12657.72	-40.81	0.083	2.5	PASS









Test mode	Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
802.11n 40	Low	30MHz≤f≤1000MHz	906.88	-53.95	0.040	2.5	PASS
		1000MHz < f≤2387MHz	2384.23	-38.14	0.153	2.5	PASS
		2387MHz < f≤2400MHz	2396.88	-30.98	0.798	25	PASS
		2483.5MHz≤f < 2496.5MHz	2489.88	-42.55	0.056	25	PASS
		2496.5MHz≤f < 12750MHz	4577.96	-35.63	0.274	2.5	PASS
	Middle	30MHz≤f≤1000MHz	775.93	-53.97	0.004	2.5	PASS
		1000MHz < f≤2387MHz	2377.29	-42.26	0.059	2.5	PASS
		2387MHz < f≤2400MHz	2390.56	-39.28	0.118	25	PASS
		2483.5MHz≤f < 2496.5MHz	2485.38	-38.46	0.143	25	PASS
		2496.5MHz≤f < 12750MHz	4577.96	-27.46	1.795	2.5	PASS
	High	30MHz≤f≤1000MHz	159.01	-53.92	0.004	2.5	PASS
		1000MHz < f≤2387MHz	1986.16	-42.68	0.054	2.5	PASS
		2387MHz < f≤2400MHz	2394.32	-42.72	0.053	25	PASS
		2483.5MHz≤f < 2496.5MHz	2486	-36.61	0.218	25	PASS
		2496.5MHz≤f < 12750MHz	5223.93	-34.85	0.327	2.5	PASS










Test mode	Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
802.11a x20	Low	30MHz≤f≤1000MHz	770.11	-53.35	0.046	2.5	PASS
		1000MHz < f≤2387MHz	2373.13	-41.09	0.078	2.5	PASS
		2387MHz < f≤2400MHz	2399.51	-36.23	0.238	25	PASS
		2483.5MHz≤f < 2496.5MHz	2496.34	-42.66	0.054	25	PASS
		2496.5MHz≤f < 12750MHz	5654.58	-40.66	0.086	2.5	PASS
	Middle	30MHz≤f≤1000MHz	925.31	-53.31	0.005	2.5	PASS
		1000MHz < f≤2387MHz	2328.75	-42.54	0.056	2.5	PASS
		2387MHz < f≤2400MHz	2392.64	-42.58	0.055	25	PASS
		2483.5MHz≤f < 2496.5MHz	2485.61	-42.58	0.055	25	PASS
		2496.5MHz≤f < 12750MHz	4588.21	-35.46	0.284	2.5	PASS
	High	30MHz≤f≤1000MHz	745.86	-53.75	0.004	2.5	PASS
		1000MHz < f≤2387MHz	2282.98	-42.39	0.058	2.5	PASS
		2387MHz < f≤2400MHz	2398.05	-42.98	0.050	25	PASS
		2483.5MHz≤f < 2496.5MHz	2483.89	-38.1	0.155	25	PASS
		2496.5MHz≤f < 12750MHz	4598.47	-38.1	0.155	2.5	PASS








Test mode	Test Channel	Test freq. range	Emission Frequency (MHz)	Test result (dBm/MHz)	Test result (uW/MHz)	limits (uW/MHz)	Result
802.11a x40	Low	30MHz≤f≤1000MHz	833.16	-53.82	0.041	2.5	PASS
		1000MHz < f≤2387MHz	2385.61	-36.34	0.232	2.5	PASS
		2387MHz < f≤2400MHz	2399.84	-29.01	1.256	25	PASS
		2483.5MHz≤f < 2496.5MHz	2483.96	-42.77	0.053	25	PASS
		2496.5MHz≤f < 12750MHz	5213.68	-40	0.100	2.5	PASS
	Middle	30MHz≤f≤1000MHz	423.82	-53.3	0.005	2.5	PASS
		1000MHz < f≤2387MHz	2378.68	-40.99	0.080	2.5	PASS
		2387MHz < f≤2400MHz	2399.88	-37.26	0.188	25	PASS
		2483.5MHz≤f < 2496.5MHz	2485.68	-40.05	0.099	25	PASS
		2496.5MHz≤f < 12750MHz	5213.68	-32.35	0.582	2.5	PASS
	High	30MHz≤f≤1000MHz	913.67	-54.1	0.004	2.5	PASS
		1000MHz < f≤2387MHz	2385.61	-42.45	0.057	2.5	PASS
		2387MHz < f≤2400MHz	2399.91	-41.58	0.070	25	PASS
		2483.5MHz≤f < 2496.5MHz	2483.54	-32.04	0.625	25	PASS
		2496.5MHz≤f < 12750MHz	4577.96	-32.15	0.610	2.5	PASS







8 UNWANTED EMISSION INTENSITY MEASUREMENT

8.1 LIMIT

Item	Limits
RX Spurious Emission	$\leq 4\text{nW}$ ($f < 1\text{GHz}$)
	$\leq 20\text{nW}$ ($1\text{GHz} \leq f$)

8.2 MEASURING INSTRUMENTS AND SETTING

The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB	100 kHz (below 1GHz emissions) 1 MHz (above 1GHz emissions)
VB	100 kHz (below 1GHz emissions) 1 MHz (above 1GHz emissions)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


8.3 TEST PROCEDURE

1. EUT have the continuous reception mode and fixed only one channelize.
2. Setting of SA is following as
RB / VB: 100 kHz (below 1GHz emissions) / 1 MHz (above 1GHz emissions) /
AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep /
Detect mode: Positive peak / Trace mode: Max hold
3. SA set RB: 100 kHz and VB: 100kHz. Then adjust to start frequency 30MHz and stop frequency 1000MHz. Search to mark peak reading value + cable loss shall be less than 4nW
4. SA set RB: 1MHz and VB: 1MHz. Then adjust to start frequency 1000MHz and stop frequency 12500MHz. Search to mark peak reading value + cable loss shall be less than 20nW
5. If power level of lower emissions are more than 1/10 of limit (.04nW for $f < 1\text{GHz}$, 2nW for $f \geq 1\text{GHz}$), all those are to be indicated in the 2nd and 3rd lines. If others are 1/10 or less more of the limit, no necessary to be indicated.


8.4 TEST RESULT

Temperature:	23℃	Relative Humidity:	54%
Test Voltage:	Normal Voltage	Pressure:	101kPa


Test mode	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
b mode	30MHz≤f≤1000MHz	901.06	-73.42	0.045	4	PASS
	1000MHz < f≤12750MHz	5230	-55.2	3.020	20	PASS

Test freq.	Test graph
30 MHz ≡ f < 1000 MHz	
1000 MHz ≡ f < 12750 MHz	

Test mode	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
g mode	30MHz≤f≤1000MHz	896.21	-73.97	0.040	4	PASS
	1000MHz < f≤12750MHz	4572	-50.64	8.630	20	PASS




Test mode	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
N20 mode	30MHz≤f≤1000MHz	840.92	-74.16	0.038	4	PASS
	1000MHz < f≤12750MHz	6675.25	-60.74	0.843	20	PASS


Test freq.	Test graph
30 MHz ≤ f < 1000 MHz	
1000 MHz ≤ f < 12750 MHz	

Temperature:	23°C	Relative Humidity:	54%
Test Voltage:	Normal Voltage	Pressure:	101kPa

Test mode	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
N40 mode	30MHz≤f≤1000MHz	904.94	-73.06	0.049	4	PASS
	1000MHz < f≤12750MHz	2680.25	-60.86	0.820	20	PASS


Test freq.	Test graph
30 MHz ≤ f < 1000 MHz	
1000 MHz ≤ f < 12750 MHz	

Test mode	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
ax20 mode	30MHz≤f≤1000MHz	880.69	-74.08	0.039	4	PASS
	1000MHz < f≤12750MHz	12667.75	-60.75	0.841	20	PASS



Temperature:	23°C	Relative Humidity:	54%
Test Voltage:	Normal Voltage	Pressure:	101kPa

Test mode	Test freq. range	Emission Frequency (MHz)	Test result dBm	Test result nW	Limit nW	Result
ax40 mode	30MHz≤f≤1000MHz	842.86	-73.48	0.045	4	PASS
	1000MHz < f≤12750MHz	5241.75	-60.17	0.962	20	PASS

Test freq.	Test graph
30 MHz ≤ f < 1000 MHz	
1000 MHz ≤ f < 12750 MHz	

9 TRANSMISSION ANTENNA GAIN (EIRP ANTENNA POWER) MEASUREMENT

9.1 LIMIT

Item	Limits
EIRP Power Density	$\leq 6.91\text{dBm/MHz}$ (FH form 2427 - 2470.75 MHz) $\leq 12.14\text{dBm/MHz}$ (OFDM,DS from 2400~2483.5MHz) $\leq 12.14\text{dBm}$ (Other from 2400~2483.5MHz)
Note: This test item is not applied for radio equipment with equivalent isotropic radiation power lower than 12.14dBm/MHz, but Antenna Power(Conducted) limit is 10 mW/MHz (10 dBm/MHz), So the test item will be notapplied to the transmission antenna which has a gain of 2.14dBi or less	

9.2 MEASURING INSTRUMENTS AND SETTING

The following table is the setting of Spectrum Analyzer.


Spectrum Parameter	Setting
Attenuation	Auto
RB/VB	1MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

9.3 TEST PROCEDURE


1. Set EUT ad measuring antenna at the same height and roughly facing each other.
2. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of EUT height and swing it to find the maximum output of the measuring antenna. The output level at the spectrum analyzer is read sa "E".
3. Remove the EUT from the turn table and put the replacing antenna facing to measuring antenna at same height. Set the standard signal generator (SSG) at same frequency and transmit on then receive the signal
4. Swing the replacing antenna give a maximum receiving level.
5. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of replacing antenna height and swing it to find the maximum receiving level.
6. Set SSG output power at P_t to give the equivalent output level of "E" or caluate P_t with SSG output which gives the nearest of "E" and difference ($\pm 1\text{dB}$). Record the P_t .
7. Calculate EIRP by the formula below $\text{EIRP} = G_t - L + P_t$. G_t : gain of replacing antenna (dBi)
 L : feeder loss between SSG and replacing antenna P_t : Output power of the SSG
8. If the antenna for the EUT has circular polarization, sum of V-field and H-field will be result if measuring antenna is linear polarization.

9.4 TEST SETUP LAYOUT

For EUT radiation measurement



For standard antenna measurement



TEST DEVIATION

There is no deviation with the original standard.

9.5 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously transmitting mode.

9.6 TEST RESULT

Test voltage	Test modulation	Output power (dBm/MHz)	Gain (dBi)	EIRP (dBm/MHz)	Result
Normal Voltage	802.11b	5.166	2.85	8.016	Pass
Normal Voltage	802.11g	4.96	2.85	7.81	Pass
Normal Voltage	802.11n(HT20)	4.66	2.85	7.51	Pass
Normal Voltage	802.11ax(HT20)	4.174	2.85	7.024	Pass
Normal Voltage	802.11n(HT40)	2.326	2.85	5.176	Pass
Normal Voltage	802.11ax(HT40)	3.655	2.85	6.505	Pass

10 TRANSMISSION RADIATION ANGLE WIDTH (3DB BEAMWIDTH) MEASUREMENT

10.1 LIMIT

Item	Limits
3dB antenna beam width	$360/A$ (If $A < 1$; then $A = 1$) $A = \{\text{EIRP Power [mW]} / 16.36 \text{ for DS, OFDM}\}$ or $A = \{\text{EIRP Power [mW]} / 4.9 \text{ for FH}\}$
Note: This test item is not applied for radio equipment with equivalent isotropic radiation power lower than 12.14dBm/MHz, but Antenna Power(Conducted) limit is 10 mW/MHz (10 dBm/MHz), So the test item will not be applied to the transmission antenna which has a gain of 2.14dBi or less	

10.2 MEASURING INSTRUMENTS AND SETTING


The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	0MHz
RB	1MHz
VB	1KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

10.3 TEST PROCEDURE

1. Set EUT and measuring antenna at the same height and roughly facing each other.
2. Set spectrum analyzer with condition in section 4.7.2 and tune reference level to observe receiving signal position.
3. Rotate directions of the EUT horizontally and vertically to find the maximum receiving power.
4. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of EUT height and swing it to find the maximum output of measuring antenna. The output level at the spectrum analyzer is read as "E"
5. Calculate permitted radiation angle in horizontal and vertical using EIRP measured in another test method.
6. Calculate 3dB antenna beam width by the formula below $360/A$ (If $A < 1$; then $A = 1$). $A = \{\text{EIRP Power [mW]} / 16.36 \text{ for DS, OFDM}\}$ or $A = \{\text{EIRP Power [mW]} / 4.9 \text{ for FH}\}$

10.4 TEST SETUP LAYOUT



TEST DEVIATION

There is no deviation with the original standard.

10.5 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously transmitting mode.

10.6 TEST RESULT

N/A

Note: This test item is not applied for radio equipment with equivalent isotropic radiation power lower than 12.14dBm/MHz

11RADIO INTERFERENCE PREVENTION CAPABILITY MEASUREMENT

11.1 LIMIT

Item	Limits
Identification code	≥ 48 bits


11.2 MEASURING ID CODE SOFTWARE

Item	Limits
MAC IP List	MAC Scan

11.3 TEST PROCEDURE

1. In the case that the EUT has the function of automatically transmitting the identification code:
 - a. Transmit the predetermined identification codes form EUT.
 - b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification ocde:
 - a. Transmit the predetermined identification codes form the counterpart.
 - b . Check if communication is normal.
 - c. Transmit the signals other than predetermined ID codes formthe counterpart.
 - d. check if the EUT stops the transmission, or if it displays that idnetification codes are different from the predetermined ones.

11.4 TEST SETUP LAYOUT



EST DEVIATION

There is no deviation with the original standard.

11.5 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously transmitting mode.

11.6 TEST RESULT

Temperature:	23℃	Relative Humidity:	54%
Pressure:	101kPa		
Test Result:	CONFORM		

MAC: 9CA525BA87F7

12 CARRIER SENSING FUNCTION


12.1 TEST REQUIREMENT

MIC Notice No.88 Appendix No.43

Article 2, Paragraph 1, Item 19 Rules Section 10

12.2 BLOCK DIAGRAM OF TEST SETUP

❖ Measurement System Diagram



❖ Conditions of Application Equipment (EUT)

- The EUT state shall be "normal mode link with wireless router".

12.3 TEST PROCEDURE

1. SG adjusted the frequency as same as the EUT transmitted signal and emitted the absence of modulation from SG and power level is $(on\ 22.79 + G - 20 \cdot \log(f) \text{ dBm})$ (G is the antenna gain, f is the test frequency).
2. Turn off the RF signal of the SG.
3. EUT have transmitted the maximum modulation signal and fixed channelize.
4. Setting of SA: RBW/VBW=1MHz/1MHz, span=50MHz, Sweep time=auto, Sweep mode=continuous, Detect mode=positive peak
5. SG RF signal on.
6. EUT shall be stop the transmitted any signal and SG RF signal off, the EUT will be continuous


12.4 TEST RESULT

Temperature:	23℃	Relative Humidity:	54%
Pressure:	101kPa		
Test Result:	CONFORM for 802.11n/ax(HT40)		
Note: The EUT cannot transmit radio when the field strength at maximal gain direction of receiving antenna power is over 100mV/m; and The Camera can start to transmit after carrier sensing.			

13 NUMBER OF CARRIERS

This device has more than 1 subcarrier in 1MHz, compliance with the requirement.

14EUT TEST PHOTO





***** END OF REPORT *****