Test Report No:
2640204R-RFJPV02S-B

TEST REPORT
Japan Rules & Regulations

Product Name	Bluetooth Headset
Brand Name	Jabra
Model No.	HSC260W
Applicant´s Name / Address	GN Audio Japan Ltd. Shinbashi M-SQUARE7 floor, 1-chome 10th No. 6, Shimbashi, Minato-ku, Tokyo, Japan
Manufacturer's Name	GN Hearing A/S
Test Method Requested, Standard	MIC Notice No.88 Appendix No.43 Article 2 Paragraph 1 of Item 19
Verdict Summary	IN COMPLIANCE
Documented by Jinn Chen	Jinn Chen
Approved by Alan Chen	Alan Chen
Date of Receipt	2026/04/08
Date of Issue	2026/05/18
Report Version	V1.0

INDEX

page

Competences and Guarantees 4
General Conditions 4
Revision History 5
Summary of Test Result 6
1. General Information 7
1.1. EUT Description 7
1.2. EUT Information 8
1.3. Testing Location Information 8
1.4. Measurement Uncertainty 9
1.5. List of Test Equipment 10
2. Test Configuration of EUT 11
2.1. Test Condition 11
2.2. Test Frequency Mode 11
2.3. Test Conditions 12
2.4. RF and IF section must be tamper requirement 12
2.5. Measurement Configuration 12
3. Antenna Power, Antenna Power Tolerance and E.I.R.P. 14
3.1. Test Setup 14
3.2. Test Limit 14
3.3. Test Method 14
3.4. Test Procedure 14
3.5. Test Result of Antenna Power, Antenna Power Tolerance and E.I.R.P. 14
4. Occupied Bandwidth 15
4.1. Test Setup 15
4.2. Test Limit 15
4.3. Test Method 15
4.4. Test Procedure 15
4.5. Test Result of Occupied Bandwidth 15
5. Frequency Tolerance 16
5.1. Test Setup 16
5.2. Test Limit 16
5.3. Test Method 16
5.4. Test Procedure 16
5.5. Test Result of Frequency Tolerance 16
6. Transmitter Spurious Emissions 17
6.1. Test Setup 17

6.2. Test Limit 17
6.3. Test Method 17
6.4. Test Procedure 17
6.5. Test Result of Transmitter Spurious Emissions 17
7. Receiver Spurious Emissions 18
7.1. Test Setup 18
7.2. Test Limit 18
7.3. Test Method 18
7.4. Test Procedure 18
7.5. Test Result of Receiver Spurious Emissions 18
8. Interference Prevention Function 19
8.1. Test Setup 19
8.2. Test Method 19
8.3. Test Procedure 19
8.4. Test Result of Interference Prevention Function 19
Appendix A. Test Result of Antenna Power, Antenna Power Tolerance and E.I.R.P.
Appendix B. Test Result of Occupied Bandwidth
Appendix C. Test Result of Frequency Tolerance
Appendix D. Test Result of Transmitter Spurious Emissions
Appendix E. Test Result of Receiver Spurious Emissions
Appendix F. Test Result of Interference Prevention Function
Appendix G. Test Photograph

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.
In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	2026/05/18

Summary of Test Result

Report Clause	Test Items	Result (PASS/FAIL)	Remark
3	Antenna Power, Antenna Power Tolerance and E.I.R.P	PASS	-
4	Occupied Bandwidth	PASS	-
5	Frequency Tolerance	PASS	-
6	Transmitter Spurious Emissions	PASS	-
7	Receiver Spurious Emissions	PASS	-
8	Interference Prevention Function	PASS	-

Comments and Explanations
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1. General Information

1.1. EUT Description

Frequency Range	2400 ~ 2483.5 MHz	
Operating Frequency / Channel Number	GFSK (1 Mbps): 2402 ~ 2480 MHz / 40 Channels GFSK (2 Mbps): 2404 ~ 2478 MHz / 37 Channels	
Mode	Bluetooth LE	
Type of Modulation	GFSK (1 Mbps, 2 Mbps)	
Declared Antenna Power	GFSK (1 Mbps)	2.56 mW
	GFSK (2 Mbps)	2.55 mW

Note: The Bluetooth LE 2M PHY is not used to transmit packets on the three primary advertising channels.

Accessories Information		
No.	Equipment Name	Description
1	Bluetooth USB Dongle	5V, Type A MIC ID：201-230817
2	Bluetooth USB Dongle	5V, Type C MIC ID：201-230818
3	Wireless Charging Pad (Optional)	Input: 5V/2A；Output：5V/1A
4	USB-C TO USB-C Cable	Shielded, 1.2m

Antenna Information				
Item.	Brand Name	Part No.	Type	Gain (dBi)
1	Jabra	07-11684	Stamping	3.29

1.2. EUT Information

EUT Power Type	From USB / Battery

1.3. Testing Location Information

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
	Linkou Laboratory
Address	No. 85, Wenlin St., Linkou Dist., New Taipei City 244017, Taiwan, R.O.C.
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist.,Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual	Test Date	Tested By
RF Conducted Emission	Temperature (°C)	5~35 °C	25.2 °C	2026/04/15	Neko Chen
	Humidity (%RH)	45~85 %	64.2 %		

1.4. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test Item	Uncertainty
Antenna Power, Antenna Power Tolerance and E.I.R.P.	Spectrum Analyzer: ±2.13 dB Power Meter: ±1.05 dB
Occupied Bandwidth	±1580.61 Hz
Frequency Tolerance	±1580.61 Hz
Transmitter Spurious Emissions	±2.13 dB
Receiver Spurious Emissions	±2.13 dB
Interference Prevention Function	N/A

1.5. List of Test Equipment

For Conducted Measurements / HY-SR02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. by	Cal. Method	Cal. Date	Due Date
V	DC Power Supply	KEYSIGHT	E36234A	MY59001234	ETC	*(c)	2025/10/27	2026/10/26
V	Spectrum Analyzer	R&S	FSV30	103465	ETC	*(c)	2025/06/13	2026/06/12
V	Power Meter	Anritsu	ML2496A	1548003	ETC	*(c)	2025/12/15	2026/12/14
V	Power Sensor	Anritsu	MA2411B	1531024	ETC	*(c)	2025/12/15	2026/12/14
V	Power Sensor	Anritsu	MA2411B	1531025	ETC	*(c)	2025/12/15	2026/12/14

Note:

1.All equipments is calibrated every year.

2.The test instruments marked with “V” are used to measure the final test results.

3.Test Software Version: DEKRA Conduction Test System V9.0.6.

4.a) Calibration conducted by the National Institute of Information and Communications Technology(NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1).

b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992).

c) Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated agency under Article 102-18 paragraph (1).

d) Calibration conducted by using other equipment that listed above from a) to c).

2. Test Configuration of EUT

2.1. Test Condition

EUT Operational Condition	
Testing Voltage	DC 5V by USB

2.2. Test Frequency Mode

Test Software Version	AB1595_Lab Test Tool / Version 5.9.0.3

Modulation	Frequency (MHz)	Power Setting
GFSK (1 Mbps)	2402	39
	2440	39
	2480	39
GFSK (2 Mbps)	2404	39
	2440	39
	2478	39

2.3. Test Conditions

Voltage Test Item	Test Voltage	Voltage meter reading value
Nominal Voltage	DC 5.0 V	DC 1.8 V
Highest Voltage	DC 5.5 V	DC 1.8 V
Lowest Voltage	DC 4.5 V	DC 1.8 V

Note: 1. The Voltage supply for U301 pin C348 is DC 1.8 V.

2. The internal supply gives a fluctuation value less than 1 % (Around 0.00% from max. to min.)

2.4. RF and IF section must be tamper requirement

Requirement	Comments	Result
RF, IF and Modulation section must be tamper	☐Use Special Screw ☐Metal Shielding is Soldered ☒Use Ball Grid Array (BGA) (Please see Attachment: EUT Detailed Photographs)	Complete
	☒RF module/Chip pin >10 ☒RF module/Chip pins distance <1.5mm (Please see Attachment: EUT Detailed Photographs)	Complete



2.5. Measurement Configuration

Test Mode	Mode 1 (Transmit)	GFSK(1 Mbps)
		GFSK(2 Mbps)
	Mode 2 (Receive)	GFSK(1 Mbps)
		GFSK(2 Mbps)

Note:

1. After checking the fluctuation of input voltage to the circuit of the radio part (excluding the power supply) of the equipment to be tested, the fluctuation less than +/- 1 % when input voltage from an external supply into the equipment fluctuates +/- 10%, therefore, the test is carried out only at the normal voltage.
2. Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

3. Antenna Power, Antenna Power Tolerance and E.I.R.P.

3.1. Test Setup



3.2. Test Limit

Antenna Power:

For 20MHz Bandwidth: ≦10 mW/MHz

For 40MHz Bandwidth: ≦5 mW/MHz

For Other Digital Methods: ≦10 mW

Antenna Power Tolerance: ≦+20%

EIRP:

For 20MHz Bandwidth: ≦12.14 dBm/MHz

For 40MHz Bandwidth: ≦9.13 dBm/MHz

For Other Digital Methods: ≦12.14 dBm

3.3. Test Method

According to MIC Notice No. 88 Annex 43.

3.4. Test Procedure

1. Connect a high-frequency power meter to the output of the dummy load (attenuator) and measure the output power.
2. Output power shall be as follows.
   (1) Value of a continuous wave.
   (2) The output power is calculated from the value and the duty factor.

3.5. Test Result of Antenna Power, Antenna Power Tolerance and E.I.R.P.

Refer as Appendix A

4. Occupied Bandwidth

4.1. Test Setup



4.2. Test Limit

≦26 MHz for DSSS , ≦83.5 MHz for FHSS

4.3. Test Method

According to MIC Notice No. 88 Annex 43.

4.4. Test Procedure

A spectrum analyzer or similar device shall be used to observe a sample of the modulated transmitter's radio frequency power output.

(a) A positive peak detector function must be used.

(b) A measurement instrument with an integrated 99% power bandwidth function may be used to automate the test process.

(c) The measurement instrument bandwidth and span must be set sufficiently with, and, the scan time set sufficiently slowly, to ensure all major modulation products are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.

(d) 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

4.5. Test Result of Occupied Bandwidth

Refer as Appendix B

5. Frequency Tolerance

5.1. Test Setup



5.2. Test Limit

± 50 ppm

5.3. Test Method

According to MIC Notice No. 88 Annex 43.

5.4. Test Procedure

A spectrum analyzer or similar device shall be used to observe a sample of the unmodulated transmitter's radio frequency power output.

(a) A positive peak detector function must be used.

(b) The measurement instrument bandwidth and span must be set sufficiently wide, and the scan time set sufficiently slowly, to ensure all products of the unmodulated signal are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.

(c) 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

5.5. Test Result of Frequency Tolerance

Refer as Appendix C

6. Transmitter Spurious Emissions

6.1. Test Setup



6.2. Test Limit

≤ 2.5uW/MHz for 30 MHz < f < 2387 MHz

≤ 25uW/MHz for 2387 MHz ≤ f < 2400 MHz

≤ 25uW/MHz for 2483.5 MHz < f ≤ 2496.5 MHz

≤ 2.5uW/MHz for 2496.5 MHz < f < 12500 MHz

6.3. Test Method

According to MIC Notice No. 88 Annex 43.

6.4. Test Procedure

The EUT is connected to the spectrum analyzer and it is configured at maximum output power in the different test channels.

(a) A positive peak detector function must be used.

(b) The measurement instrument bandwidth and span must be set sufficiently with, and, the scan time set sufficiently slow, to ensure all major modulation products are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.

(c) 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

6.5. Test Result of Transmitter Spurious Emissions

Refer as Appendix D

7. Receiver Spurious Emissions

7.1. Test Setup



7.2. Test Limit

≤ 4nW for 30 MHz < f < 1000MHz

≤ 20nW for 1000 MHz ≤ f < 12500 MHz

7.3. Test Method

According to MIC Notice No. 88 Annex 43.

7.4. Test Procedure

The EUT is connected to the spectrum analyzer and it is configured in reception mode in the different test channels.

(a) A positive peak detector function must be used.

(b) The measurement instrument bandwidth and span must be set sufficiently with, and, the scan time set sufficiently slowly, to ensure all major modulation products are captured. Note that the measurement bandwidth should also be set sufficiently narrow to avoid adding significant error to the test result.

(c) 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided the emission is repetitive in nature.

7.5. Test Result of Receiver Spurious Emissions

Refer as Appendix E

8. Interference Prevention Function

8.1. Test Setup



8.2. Test Method

According to MIC Notice No. 88 Annex 43.

8.3. Test Procedure

Radio equipment used mainly on the same premises and automatically transmits or receives identification code.

8.4. Test Result of Interference Prevention Function

Refer as Appendix F