NCC Test Report

Equipment	:	**藍芽遙控器**
Model No.	:	**RF243A**
Brand Name	:	**C&D**
Applicant	:	**鴻海精密工業股份有限公司**
Address	:	**新北市土城區中山路 66 號**
Standard	:	**LP0002 Section 3.10.1 (2018-01-10)**
Received Date	:	**Jun. 07, 2018**
Tested Date	:	**Nov. 28, 2016(for original test)** **Jun. 21, 2018(for new test)**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: **Approved by:**

Along Chen / Assistant Manager **Gary Chang / Manager**

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 7
1.3 Test Setup Chart 7
1.4 Test Equipment List and Calibration Data 8
1.5 Test Standards 9
1.6 Measurement Uncertainty 9

2 TEST CONFIGURATION 10

2.1 Testing Condition 10
2.2 The Worst Test Modes and Channel Details 10

3 TRANSMITTER TEST RESULTS 11

3.1 6dB and Occupied Bandwidth 11
3.2 RF Output Power 13
3.3 Power Spectral Density 15
3.4 Emissions in Restricted Frequency Bands 17
3.5 Emissions in non-restricted Frequency Bands 27

4 RECEIVER TEST RESULTS 30

4.1 Radiated Emissions 30

5 TEST LABORATORY INFORMATION 36

Release Record

Report No.	Version	Description	Issued Date
TR6N2501-04	Rev. 01	Initial issue	Jul. 12, 2018

Summary of Test Results

NCC Rules	Test Items	Measured	Result
2.3	AC Power Line Conducted Emissions	Note[1]	N/A
3.10.1.5 2.8	Radiated Emissions	[dBuV/m at 3m]: 2483.50MHz 48.59 (Margin -5.41dB) - AV	Pass
3.10.1.2(1)(C)	Maximum Output Power	Power [dBm]: -1.88	Pass
3.10.1.6(2)(A)	6dB Bandwidth	Meet the requirement of limit	Pass
3.10.1.6(2)(B)	Power Spectral Density	Meet the requirement of limit	Pass
3.10.1.4	Antenna Requirement	Meet the requirement of limit	Pass
N/A means Not Applicable. Note[1]: The EUT consumes DC power, so the test is not required.			

1 General Description

1.1 Information

This report is issued as a supplementary report to original ICC report no. TR6N2501-01. The difference is concerned with following item:

✧ PCBA modification of non-RF section for capacitors position changed

In this report, radiated emission test had been re-tested and other test results were kept as same as mentioned on original report.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	**Bluetooth Mode**	**Ch. Freq. (MHz)**	**Channel Number**	**Data Rate**
2400-2483.5	V4.0 LE	2402-2480	0-39 [40]	1 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

1.1.2 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	PCB	N/A	1.5	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3Vdc from battery

1.1.4 Accessories

N/A

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.6 Test Tool and Duty Cycle

Test tool	BeeMPTool, Version: 1.02
Duty cycle of test signal (%)	100.00%
Duty Factor (dB)	0.00


1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	0	0	0

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	---	---	---	---	---

1.3 Test Setup Chart

Test Setup Diagram


1.4 Test Equipment List and Calibration Data

Test Item	Radiated Emission				
Test Site	966 chamber 1 / (03CH01-WS)				
Test Date	Jun. 21, 2018				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101498	Dec. 04, 2017	Dec. 03, 2018
Receiver	R&S	ESR3	101658	Nov. 20, 2017	Nov. 19, 2018
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 25, 2017	Jul. 24, 2018
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 20, 2017	Dec. 19, 2018
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 23, 2017	Nov. 22, 2018
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2017	Nov. 12, 2018
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 07, 2017	Dec. 06, 2018
Preamplifier	EMC	EMC02325	980225	Jul. 28, 2017	Jul. 27, 2018
Preamplifier	Agilent	83017A	MY39501308	Oct. 06, 2017	Oct. 05, 2018
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 07, 2017	Dec. 06, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 07, 2017	Dec. 06, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 07, 2017	Dec. 06, 2018
LF cable 1M	EMC	EMCCFD400-NM-NM-1000	16052	Dec. 07, 2017	Dec. 06, 2018
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 07, 2017	Dec. 06, 2018
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 07, 2017	Dec. 06, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Test Date	Nov. 28, 2016				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2016	Feb. 16, 2017
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 09, 2016	Sep. 08, 2017
Power Meter	Anritsu	ML2495A	1241002	Oct. 06, 2016	Oct. 05, 2017
Power Sensor	Anritsu	MA2411B	1207366	Oct. 06, 2016	Oct. 05, 2017
Signal Generator	R&S	SMB100A	175727	Oct. 19, 2016	Oct. 18, 2017
DC POWER SOURCE	GW INSTEK	GPC-6030D	EM892433	Oct. 20, 2016	Oct. 19, 2017
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

LP0002 Section 3.10.1 (2018-01-10)
ANSI C63.10-2013
ANSI C63.4-2014
FCC KDB 558074 D01 DTS Meas Guidance v04

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	**Uncertainty**
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Radiated emission ≤ 1GHz	±3.66 dB
Radiated emission > 1GHz	±5.63 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH01-WS	24°C / 62%	Vincent Yeh
RF Conducted	TH01-WS	21°C / 64%	Brad Wu

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Mode
Radiated Emissions ≤ 1GHz	BT LE	2440	1Mbps	TX
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	TX
Maximum Output Power	BT LE	2402, 2440, 2480	1Mbps	TX
6dB bandwidth				
Power spectral density				
NOTE: The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.				

Test item	Mode	Test Frequency (MHz)	Data Rate	Mode
Radiated Emissions ≤ 1GHz	BT LE	2440	1Mbps	RX
Radiated Emissions > 1GHz	BT LE	2440	1Mbps	RX
NOTE: The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.				

3 Transmitter Test Results

3.1 6dB and Occupied Bandwidth

3.1.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.1.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth



1. Set resolution bandwidth (RBW) = 20 kHz, Video bandwidth = 100 kHz.
2. Detector = Sample, Trace mode = max hold.
3 Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.1.3 Test Setup



3.1.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.726	1.06	500
BT LE	2440	0.730	1.06	500
BT LE	2480	0.752	1.08	500

Worst Plots	
6dB Bandwidth	99% Occupied Bandwidth
	

3.2 RF Output Power

3.2.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

Antenna gain > 6dBi

Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB

Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.2.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.2.3 Test Setup



3.2.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)
BT LE	2402	0.610	-2.15	30
BT LE	2440	0.640	-1.94	30
BT LE	2480	0.649	**-1.88**	30

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	0.604	-2.19	-
BT LE	2440	0.631	-2.00	-
BT LE	2480	0.640	-1.94	-

Note: Average power is for reference only

3.3 Power Spectral Density


3.3.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.3.2 Test Procedures


1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.3.3 Test Setup



3.3.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-13.81	8
BT LE	2440	-13.24	8
BT LE	2480	-13.99	8

Worst Plot


3.4 Emissions in Restricted Frequency Bands

3.4.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.4.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.4.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.4.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)


Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	54.25	21.65	40.00	-18.35	29.96	-8.31	Peak	---	---
2	163.86	22.45	43.50	-21.05	30.64	-8.19	Peak	---	---
3	308.39	23.58	46.00	-22.42	31.00	-7.42	Peak	---	---
4	406.36	25.72	46.00	-20.28	30.63	-4.91	Peak	---	---
5	514.03	28.80	46.00	-17.20	31.49	-2.69	Peak	---	---
6	640.13	31.87	46.00	-14.13	31.70	0.17	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	24.09	40.00	-15.91	32.23	-8.14	Peak	---	---
2	149.31	22.34	43.50	-21.16	30.48	-8.14	Peak	---	---
3	248.25	22.86	46.00	-23.14	32.06	-9.20	Peak	---	---
4	343.31	24.07	46.00	-21.93	30.63	-6.56	Peak	---	---
5	465.53	27.84	46.00	-18.16	31.39	-3.55	Peak	---	---
6	690.57	31.31	46.00	-14.69	30.41	0.90	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.4.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	40.27	54.00	-13.73	41.48	-1.21	Average	134	334
2	2390.00	53.45	74.00	-20.55	54.66	-1.21	Peak	134	334
3	4804.00	45.21	54.00	-8.79	39.60	5.61	Average	100	329
4	4804.00	52.24	74.00	-21.76	46.63	5.61	Peak	100	329
5	12010.00	44.45	54.00	-9.55	28.70	15.75	Average	100	157
6	12010.00	56.47	74.00	-17.53	40.72	15.75	Peak	100	157

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.22	54.00	-14.78	40.43	-1.21	Average	316	10
2	2390.00	51.29	74.00	-22.71	52.50	-1.21	Peak	316	10
3	4804.00	41.31	54.00	-12.69	35.70	5.61	Average	100	222
4	4804.00	48.47	74.00	-25.53	42.86	5.61	Peak	100	222
5	12010.00	43.67	54.00	-10.33	27.92	15.75	Average	100	62
6	12010.00	56.03	74.00	-17.97	40.28	15.75	Peak	100	62

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	GFSK	**Test Freq. (MHz)**	2440
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.10	54.00	-14.90	40.31	-1.21	Average	113	324
2	2390.00	51.01	74.00	-22.99	52.22	-1.21	Peak	113	324
3	2483.50	39.21	54.00	-14.79	40.07	-0.86	Average	113	324
4	2483.50	50.92	74.00	-23.08	51.78	-0.86	Peak	113	324
5	4880.00	44.32	54.00	-9.68	38.50	5.82	Average	100	335
6	4880.00	51.52	74.00	-22.48	45.70	5.82	Peak	100	335
7	7320.00	39.89	54.00	-14.11	28.90	10.99	Average	100	202
8	7320.00	51.37	74.00	-22.63	40.38	10.99	Peak	100	202

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	GFSK	**Test Freq. (MHz)**	2440
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	39.11	54.00	-14.89	40.32	-1.21	Average	308	12
2	2390.00	50.49	74.00	-23.51	51.70	-1.21	Peak	308	12
3	2483.50	39.32	54.00	-14.68	40.18	-0.86	Average	308	12
4	2483.50	51.39	74.00	-22.61	52.25	-0.86	Peak	308	12
5	4880.00	41.21	54.00	-12.79	35.39	5.82	Average	100	242
6	4880.00	48.54	74.00	-25.46	42.72	5.82	Peak	100	242
7	7320.00	41.04	54.00	-12.96	30.05	10.99	Average	100	163
8	7320.00	51.80	74.00	-22.20	40.81	10.99	Peak	100	163

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	48.59	54.00	-5.41	49.45	-0.86	Average	127	332
2	2483.50	61.04	74.00	-12.96	61.90	-0.86	Peak	127	332
3	4960.00	45.26	54.00	-8.74	39.20	6.06	Average	100	355
4	4960.00	52.27	74.00	-21.73	46.21	6.06	Peak	100	355
5	7440.00	40.21	54.00	-13.79	28.84	11.37	Average	100	168
6	7440.00	51.49	74.00	-22.51	40.12	11.37	Peak	100	168

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	**Test Freq. (MHz)**	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	44.94	54.00	-9.06	45.80	-0.86	Average	333	14
2	2483.50	58.39	74.00	-15.61	59.25	-0.86	Peak	333	14
3	4960.00	42.21	54.00	-11.79	36.15	6.06	Average	100	225
4	4960.00	48.30	74.00	-25.70	42.24	6.06	Peak	100	225
5	7440.00	41.26	54.00	-12.74	29.89	11.37	Average	100	112
6	7440.00	51.72	74.00	-22.28	40.35	11.37	Peak	100	112

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5 Emissions in non-restricted Frequency Bands

3.5.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.5.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level





Emission level measurement



1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.5.3 Test Setup



3.5.4 Test Result of Emissions in non-restricted Frequency Bands

TX Freq 2402MHz / 30MHz~25GHz (down 20dBc)	TX Freq 2440MHz / 30MHz~25GHz (down 20dBc)
	
	

TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)	---
	---
	---

4 Receiver Test Results

4.1 Radiated Emissions

4.1.1 Limit of Radiated Emissions

Radiated emission limits in §2.8			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

4.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=3MHz and RMS detector is for average measured value of radiated emission above 1GHz.

4.1.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



4.1.4 Receiver Emissions (Below 1GHz)


Modulation	GFSK	**Test Freq. (MHz)**	2440
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	55.22	22.11	40.00	-17.89	30.50	-8.39	Peak	---	---
2	152.22	22.42	43.50	-21.08	30.52	-8.10	Peak	---	---
3	299.66	23.04	46.00	-22.96	30.67	-7.63	Peak	---	---
4	383.08	25.81	46.00	-20.19	31.33	-5.52	Peak	---	---
5	486.87	27.67	46.00	-18.33	30.87	-3.20	Peak	---	---
6	603.27	30.45	46.00	-15.55	30.83	-0.38	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	**Test Freq. (MHz)**	2440
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	25.28	40.00	-14.72	33.42	-8.14	Peak	---	---
2	155.13	22.50	43.50	-21.00	30.60	-8.10	Peak	---	---
3	321.00	23.56	46.00	-22.44	30.67	-7.11	Peak	---	---
4	453.89	26.32	46.00	-19.68	30.06	-3.74	Peak	---	---
5	520.82	28.68	46.00	-17.32	31.23	-2.55	Peak	---	---
6	634.31	30.81	46.00	-15.19	30.72	0.09	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

4.1.5 Receiver Emissions (Above 1GHz)


Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1073.00	24.49	54.00	-29.51	32.57	-8.08	Average	100	342
2	1073.00	36.34	74.00	-37.66	44.42	-8.08	Peak	100	342
3	3065.00	29.52	54.00	-24.48	28.46	1.06	Average	100	85
4	3065.00	41.21	74.00	-32.79	40.15	1.06	Peak	100	85
5	9754.00	44.71	54.00	-9.29	29.93	14.78	Average	100	132
6	9754.00	56.00	74.00	-18.00	41.22	14.78	Peak	100	132

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	**Test Freq. (MHz)**	2440
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1075.00	24.29	54.00	-29.71	32.34	-8.05	Average	100	266
2	1075.00	35.91	74.00	-38.09	43.96	-8.05	Peak	100	266
3	3065.00	28.70	54.00	-25.30	27.64	1.06	Average	100	105
4	3065.00	41.44	74.00	-32.56	40.38	1.06	Peak	100	105
5	9754.00	44.50	54.00	-9.50	29.72	14.78	Average	100	293
6	9754.00	56.35	74.00	-17.65	41.57	14.78	Peak	100	293

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

5 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

==END==