待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW	測試項目：操作頻道外的峰值發射
測試頻道：CH 159 (5795MHz)	測試模式：Mode 2: SISO B: 發射器 802.11ax-40BW
6 dB 頻寬：1MHz	視頻頻寬：1MHz
量測距離：3 M	天線極化：Vertical
檢 測 器：峰值	環境溫度：21 ℃
測試日期：108 年 01 月 21 日	環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5809.565	12.691	92.906	105.598	-25.602	131.200	Pass
Vertical	5850.000	12.774	60.488	73.262	-48.938	122.200	Pass
Vertical	5855.000	12.784	58.431	71.215	-39.585	110.800	Pass
Vertical	5875.000	12.825	52.618	65.443	-39.757	105.200	Pass
Vertical	5925.000	12.911	42.563	55.474	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 106 (5530 MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ax-80BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5465.217	11.774	53.567	65.341	-2.879	68.220	Pass
Horizontal	5470.000	11.838	52.546	64.384	-3.836	68.220	Pass
Horizontal	5505.942	12.196	90.925	103.121	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 106 (5530 MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ax-80BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5468.696	13.453	53.120	66.572	-1.648	68.220	Pass
Vertical	5470.000	13.462	51.216	64.678	-3.542	68.220	Pass
Vertical	5505.942	13.639	90.256	103.895	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW	測試項目：操作頻道外的峰值發射
測試頻道：CH 155 (5775 MHz)	測試模式：Mode 2: SISO B: 發射器 802.11ax-80BW
6 dB 頻寬：1MHz	視頻頻寬：1MHz
量測距離：3 M	天線極化：Horizontal
檢 測 器：峰值	環境溫度：21 ℃
測試日期：108 年 01 月 21 日	環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5650.000	11.554	45.789	57.344	-10.876	68.220	Pass
Horizontal	5700.000	11.647	52.207	63.854	-41.346	105.200	Pass
Horizontal	5714.783	11.623	54.066	65.689	-43.650	109.339	Pass
Horizontal	5720.000	11.607	52.556	64.163	-46.637	110.800	Pass
Horizontal	5725.000	11.592	55.644	67.236	-54.964	122.200	Pass
Horizontal	5773.913	11.437	91.863	103.300	-27.900	131.200	Pass
Horizontal	5850.000	11.701	54.198	65.899	-56.301	122.200	Pass
Horizontal	5855.000	11.735	55.057	66.792	-44.008	110.800	Pass
Horizontal	5875.000	11.873	54.003	65.876	-39.324	105.200	Pass
Horizontal	5879.420	11.903	55.552	67.456	-34.473	101.929	Pass
Horizontal	5925.000	12.068	45.565	57.634	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射
測試頻道：CH 155 (5775 MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ax-80BW
6 dB 頻寬：1MHz　　視頻頻寬：1MHz
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5650.000	13.029	44.769	57.798	-10.422	68.220	Pass
Vertical	5700.000	13.003	51.652	64.655	-40.545	105.200	Pass
Vertical	5707.826	12.988	53.835	66.822	-40.569	107.391	Pass
Vertical	5720.000	12.947	52.440	65.387	-45.413	110.800	Pass
Vertical	5725.000	12.930	55.371	68.301	-53.899	122.200	Pass
Vertical	5773.913	12.759	90.778	103.537	-27.663	131.200	Pass
Vertical	5850.000	12.774	52.488	65.262	-56.938	122.200	Pass
Vertical	5855.000	12.784	52.279	65.063	-45.737	110.800	Pass
Vertical	5857.971	12.791	54.932	67.722	-42.246	109.968	Pass
Vertical	5875.000	12.825	51.563	64.388	-40.812	105.200	Pass
Vertical	5879.420	12.834	53.042	65.877	-36.052	101.929	Pass
Vertical	5925.000	12.911	45.028	57.939	--	-	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW	測試項目：操作頻道外的峰值發射
測試頻道：CH 114 (5570 MHz)	測試模式：Mode 2: SISO B: 發射器 802.11ax-160BW
6 dB 頻寬：1MHz	視頻頻寬：1MHz
量測距離：3 M	天線極化：Horizontal
檢 測 器：峰值	環境溫度：21 ℃
測試日期：108 年 01 月 21 日	環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5470.000	11.838	47.627	59.465	-8.755	68.220	Pass
Horizontal	5546.087	11.871	84.420	96.292	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 114 (5570 MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ax-160BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5470.000	13.462	49.121	62.583	-5.637	68.220	Pass
Vertical	5599.130	13.058	85.504	98.562	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 100 (5500 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢測器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 29 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5470.000	11.838	47.610	59.448	-8.772	68.220	Pass
Horizontal	5501.304	12.178	95.504	107.682	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射
測試頻道：CH 100 (5500 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW
6 dB 頻寬：1MHz　　視頻頻寬：1MHz
量測距離：3 M　　天線極化：Vertical
檢 測 器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5470.000	13.462	48.581	62.043	-6.177	68.220	Pass
Vertical	5505.942	13.639	94.775	108.414	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 140 (5700 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5695.290	11.651	93.148	104.798	--	--	--
Horizontal	5725.000	11.592	51.424	63.016	-5.204	68.220	Pass
Horizontal	5726.449	11.588	53.813	65.400	-2.820	68.220	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 140 (5700 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5695.290	13.012	93.984	106.996	--	--	--
Vertical	5725.000	12.930	53.704	66.634	-1.586	68.220	Pass
Vertical	5727.029	12.923	54.351	67.274	-0.946	68.220	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 149 (5745 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5650.000	11.554	41.558	53.113	--	--	--
Horizontal	5700.000	11.647	46.609	58.256	-46.944	105.200	Pass
Horizontal	5720.000	11.607	54.573	66.180	-44.620	110.800	Pass
Horizontal	5723.514	11.596	56.672	68.268	-50.544	118.812	Pass
Horizontal	5725.000	11.592	54.451	66.043	-56.157	122.200	Pass
Horizontal	5740.507	11.543	94.512	106.055	-25.145	131.200	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 149 (5745 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5650.000	13.029	41.661	54.690	--	--	--
Vertical	5700.000	13.003	45.044	58.047	-47.153	105.200	Pass
Vertical	5720.000	12.947	53.547	66.494	-44.306	110.800	Pass
Vertical	5723.007	12.937	58.004	70.941	-46.715	117.656	Pass
Vertical	5725.000	12.930	56.436	69.366	-52.834	122.200	Pass
Vertical	5741.522	12.873	91.861	104.734	-26.466	131.200	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 165 (5825 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5833.696	11.588	92.655	104.243	-26.957	131.200	Pass
Horizontal	5850.000	11.701	50.880	62.581	-59.619	122.200	Pass
Horizontal	5855.000	11.735	51.069	62.804	-47.996	110.800	Pass
Horizontal	5875.000	11.873	44.490	56.363	-48.837	105.200	Pass
Horizontal	5925.000	12.068	42.352	54.421	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 165 (5825 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-20BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5826.522	12.724	92.546	105.270	-25.930	131.200	Pass
Vertical	5850.000	12.774	51.799	64.573	-57.627	122.200	Pass
Vertical	5855.000	12.784	48.279	61.063	-49.737	110.800	Pass
Vertical	5875.000	12.825	43.887	56.712	-48.488	105.200	Pass
Vertical	5925.000	12.911	41.925	54.836	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW	測試項目：操作頻道外的峰值發射
測試頻道：CH 102 (5510MHz)	測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW
6 dB 頻寬：1MHz	視頻頻寬：1MHz
量測距離：3 M	天線極化：Horizontal
檢測器：峰值	環境溫度：21 ℃
測試日期：108 年 01 月 22 日	環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5456.087	11.650	52.651	64.301	-3.919	68.220	Pass
Horizontal	5470.000	11.838	50.560	62.398	-5.822	68.220	Pass
Horizontal	5519.710	12.085	93.142	105.227	--	--	--

待測物型號：AX200NGW
測試頻道：CH 102 (5510MHz)
6 dB 頻寬：1MHz
量測距離：3 M
檢 測 器：峰值
測試日期：108 年 01 月 22 日

測試項目：操作頻道外的峰值發射
測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW
視頻頻寬：1MHz
天線極化：Vertical
環境溫度：21 ℃
環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBµV)	Measure Level (dBµV /m)	Margin (dB)	Limit (dBµV /m)	Result
Vertical	5461.739	13.402	49.853	63.255	-4.965	68.220	Pass
Vertical	5470.000	13.462	48.676	62.138	-6.082	68.220	Pass
Vertical	5508.406	13.622	91.375	104.998	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 134 (5670MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5679.493	11.623	90.706	102.330	--	--	--
Horizontal	5725.000	11.592	45.366	56.958	-11.262	68.220	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 134 (5670MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5679.783	13.022	91.994	105.016	--	--	--
Vertical	5725.000	12.930	47.014	59.944	-8.276	68.220	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW	測試項目：操作頻道外的峰值發射
測試頻道：CH 151 (5755MHz)	測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW
6 dB 頻寬：1MHz	視頻頻寬：1MHz
量測距離：3 M	天線極化：Horizontal
檢 測 器：峰值	環境溫度：21 ℃
測試日期：108 年 01 月 22 日	環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5646.667	11.547	45.413	56.960	--	--	--
Horizontal	5650.000	11.554	42.985	54.540	-13.680	68.220	Pass
Horizontal	5700.000	11.647	51.567	63.214	-41.986	105.200	Pass
Horizontal	5720.000	11.607	58.955	70.562	-40.238	110.800	Pass
Horizontal	5725.000	11.592	59.643	71.235	-50.965	122.200	Pass
Horizontal	5764.601	11.467	93.374	104.841	-26.359	131.200	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 151 (5755MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5650.000	13.029	43.367	56.396	--	--	--
Vertical	5698.913	13.005	54.048	67.053	-37.343	104.396	Pass
Vertical	5700.000	13.003	52.127	65.130	-40.070	105.200	Pass
Vertical	5720.000	12.947	56.787	69.734	-41.066	110.800	Pass
Vertical	5725.000	12.930	57.383	70.313	-51.887	122.200	Pass
Vertical	5757.754	12.815	91.005	103.820	-27.380	131.200	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW	測試項目：操作頻道外的峰值發射
測試頻道：CH 159 (5795MHz)	測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW
6 dB 頻寬：1MHz	視頻頻寬：1MHz
量測距離：3 M	天線極化：Horizontal
檢 測 器：峰值	環境溫度：21 ℃
測試日期：108 年 01 月 22 日	環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5797.500	11.381	90.805	102.186	-29.014	131.200	Pass
Horizontal	5850.000	11.701	46.029	57.730	-64.470	122.200	Pass
Horizontal	5855.000	11.735	47.767	59.502	-51.298	110.800	Pass
Horizontal	5875.000	11.873	44.558	56.431	-48.769	105.200	Pass
Horizontal	5925.000	12.068	41.912	53.981	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 159 (5795MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-40BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5797.174	12.685	91.929	104.614	-26.586	131.200	Pass
Vertical	5850.000	12.774	46.857	59.631	-62.569	122.200	Pass
Vertical	5855.000	12.784	48.383	61.167	-49.633	110.800	Pass
Vertical	5875.000	12.825	44.592	57.417	-47.783	105.200	Pass
Vertical	5925.000	12.911	41.477	54.388	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 106 (5530 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-80BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5467.391	11.804	51.941	63.744	-4.476	68.220	Pass
Horizontal	5470.000	11.838	50.395	62.233	-5.987	68.220	Pass
Horizontal	5505.072	12.204	90.629	102.832	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 106 (5530 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-80BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5470.000	13.462	50.273	63.735	-4.485	68.220	Pass
Vertical	5506.232	13.636	89.158	102.795	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 155 (5775 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-80BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5650.000	11.554	43.384	54.939	-13.281	68.220	Pass
Horizontal	5700.000	11.647	47.871	59.518	-45.682	105.200	Pass
Horizontal	5720.000	11.607	49.673	61.280	-49.520	110.800	Pass
Horizontal	5725.000	11.592	52.588	64.180	-58.020	122.200	Pass
Horizontal	5798.261	11.382	88.336	99.718	-31.482	131.200	Pass
Horizontal	5850.000	11.701	49.012	60.713	-61.487	122.200	Pass
Horizontal	5855.000	11.735	49.653	61.388	-49.412	110.800	Pass
Horizontal	5875.000	11.873	47.862	59.735	-45.465	105.200	Pass
Horizontal	5925.000	12.068	43.284	55.353	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 155 (5775 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-80BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5641.739	13.030	45.320	58.351	--	--	--
Vertical	5650.000	13.029	43.309	56.338	-11.882	68.220	Pass
Vertical	5700.000	13.003	47.404	60.407	-44.793	105.200	Pass
Vertical	5720.000	12.947	49.079	62.026	-48.774	110.800	Pass
Vertical	5725.000	12.930	51.332	64.262	-57.938	122.200	Pass
Vertical	5797.681	12.684	86.862	99.546	-31.654	131.200	
Vertical	5850.000	12.774	48.030	60.804	-61.396	122.200	Pass
Vertical	5855.000	12.784	46.961	59.745	-51.055	110.800	Pass
Vertical	5875.000	12.825	46.343	59.168	-46.032	105.200	Pass
Vertical	5925.000	12.911	42.680	55.591	-12.609	68.200	Pass

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 114 (5570 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-160BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Horizontal

檢 測 器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Horizontal	5467.391	11.804	49.254	61.057	-7.163	68.220	Pass
Horizontal	5470.000	11.838	48.034	59.872	-8.348	68.220	Pass
Horizontal	5545.217	11.879	86.178	98.057	--	--	--

待測物名稱：Intel® Wi-Fi 6 AX200

待測物型號：AX200NGW　　測試項目：操作頻道外的峰值發射

測試頻道：CH 114 (5570 MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ax-160BW

6 dB 頻寬：1MHz　　視頻頻寬：1MHz

量測距離：3 M　　天線極化：Vertical

檢測器：峰值　　環境溫度：21 ℃

測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement:



	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Measure Level (dBμV /m)	Margin (dB)	Limit (dBμV /m)	Result
Vertical	5463.913	13.419	49.123	62.541	-5.679	68.220	Pass
Vertical	5470.000	13.462	46.453	59.915	-8.305	68.220	Pass
Vertical	5527.826	13.498	84.047	97.545	--	--	--

8. 混附發射

8.1. 適用標準

依據國家通訊傳播委員會低功率射頻電機技術規範之第 4.7.4 節：

4.7.4.6 不必要發射頻率屬 2.7 規定頻段者，應符合 2.8 之規定。

依據國家通訊傳播委員會低功率射頻電機技術規範之第 2.7 節:

除本規範另有規定外，任何低功率射頻電機之主波皆不得使用下表所列各頻帶內之頻率;

低功率射頻電機落於下表所列頻帶內之混附發射，其電場強度必須符合第 2.8 節的限制規定。

頻率(兆赫)	頻率(兆赫)	頻率(兆赫)	頻率(兆赫)
0.090 - 0.110	162.01 - 167.17	2200.0 - 2300.0	23600.0 - 24000.0
0.490 - 0.510	167.72 - 173.20	2310.0 - 2390.0	31200.0 - 31800.0
2.172 - 2.198	240.00 - 285.00	2483.5 - 2900.0	36430.0 - 36500.0
3.013 - 3.033	322.00 - 335.40	3260.0 - 3267.0	38600.0 以上
4.115 - 4.198	399.90 - 410.00	3332.0 - 3339.0	
5.670 - 5.690	485.00 - 510.00	3345.8 - 3358.0	
6.200 - 6.300	608.00 - 614.00	3500.0 - 4400.0	
8.230 - 8.400	703.00 - 748.00	4500.0 - 5250.0	
12.265 - 12.600	758.00 - 803.00	5350.0 - 5460.0	
13.340 - 13.430	825.00 - 915.00	7250.0 - 7750.0	
14.965 - 15.020	930.00 - 1240.0	8025.0 - 8500.0	
16.700 - 16.755	1300.0 - 1427.0	9000.0 - 9200.0	
19.965 - 20.020	1435.0 - 1626.5	9300.0 - 9500.0	
25.500 - 25.700	1660.0 - 1785.0	10600.0 - 12700.0	
37.475 - 38.275	1805.0 - 1880.0	13250.0 - 13400.0	
73.500 - 75.400	1885.0 - 1900.0	14470.0 - 14500.0	
108.00 - 138.00	1905.0 - 1985.0	15350.0 - 16200.0	
149.90 - 150.05	2010.0 - 2025.0	17700.0 - 21400.0	
156.70 - 156.90	2110.0 - 2170.0	22010.0 - 23120.0	

發射依據國家通訊傳播委員會低功率射頻電機技術規範之第 2.8 節，低功率射頻電機，除本規範各章節另有放寬規定者外，其電場強度不得超過下表之限值，且其不必要之發射皆不得大於主波發射強度。各頻段重疊處，以較嚴格之限制值為準。

頻　率(兆赫)	電場強度(微伏/公尺)	測距(公尺)
0.009 - 0.490(含)	2,400/頻率(千赫)	300
0.490 (不含) – 1.705 (含)	24,000/頻率(千赫)	30
1.705(不含) – 30 (不含)	30	30
30 (含) – 88 (含)	100	3
88 (不含)- 216 (含)	150	3
216 (不含)- 960 (含)	200	3
960 (不含)以上	500	3

上表規定之電場強度，頻率在 9-90kHz 千赫(kHz)、110-490 千赫(kHz)以及 1000 兆赫(MHz)以上之發射，其量測以平均值檢波器為基準，且須符合第 5.15.2 節之規定；其他發射頻率，應以國際無線電干擾特別委員會(INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE ,CISPR)準峰值 (quasi-peak) 檢波器測量；非以上表所指定之距離測量時，應符合第 5.5 節之規定，輻射發射之量測頻率範圍應符合第 5.14 節之規定。

8.2. 量測方法

RF Conducted Measurement:

待測物之天線埠經由適當之衰減直接連至頻譜分析儀 RF 輸入端，設定頻譜分析儀之解析度頻寬大於 1%頻率掃描範圍寬度，視訊頻寬大於解析度頻寬。

待測物應在正常發射狀態下量測。

RF Radiated Measurement:

待測物置於高 150 公分之非導體桌面（落地型產品置於地上），桌面可 360 度旋轉，接收天線置於距待測物 3m 距離，高度可在 1 至 4 公尺間變動，以量測待測物之最大輻射電場強度。接收天線並應於水平及垂直極化方向各量測一次。

待測物應在正常發射狀態下量測。

備註: 依據低功率射頻電機技術規範(LP0002) 附件三第九項(三)標記差值方法量測。

RBW and VBW Parameter setting:

According to KDB 789033 section II.G.5 Procedure for Unwanted Maximum Emissions Measurements above 1000 MHz.

RBW = 1MHz.

VBW ≥ 3MHz.

According to KDB 789033 section II.G.6 Procedures for Average Unwanted Emissions Measurements above 1000 MHz.

RBW = 1MHz.

VBW = 10Hz, when duty cycle ≥ 98 %

VBW ≥ 1/T, when duty cycle < 98 %

(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)

SISO A

5GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11 a	82.02	0.2116	4726	5000
802.11 n20	82.47	0.2319	4313	5000
802.11 n40	84.00	0.2435	4107	5000
802.11 ac80	83.16	0.2290	4367	5000
802.11 ac160	83.24	0.2304	4340	5000
802.11 ax20	82.47	0.2319	4313	5000
802.11 ax40	83.51	0.2348	4259	5000
802.11 ax80	84.32	0.2493	4012	5000
802.11 ax160	83.59	0.2362	4233	5000

Note: Duty Cycle Refer to Section 12

SISO B

5GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11 a	81.11	0.2116	4726	5000
802.11 n20	83.33	0.2319	4313	5000
802.11 n40	76.24	0.2232	4480	5000
802.11 ac80	82.11	0.2261	4423	5000
802.11 ac160	83.16	0.2290	4367	5000
802.11 ax20	83.50	0.2348	4259	5000
802.11 ax40	82.47	0.2319	4313	5000
802.11 ax80	84.32	0.2493	4012	5000
802.11 ax160	80.41	0.2261	4423	5000

Note: Duty Cycle Refer to Section 12

MIMO

5GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11 n20	84.32	0.2493	4012	5000
802.11 n40	83.34	0.2464	4059	5000
802.11 ac80	83.33	0.2319	4313	5000
802.11 ac160	83.16	0.2290	4367	5000
802.11 ax20	83.16	0.2290	4367	5000
802.11 ax40	83.00	0.2406	4157	5000
802.11 ax80	83.16	0.2290	4367	5000
802.11 ax160	83.16	0.2290	4367	5000

Note: Duty Cycle Refer to Section 12

8.3. 測試架構圖

RF Conducted Measurement:



RF Radiated Measurement:



8.4. 量測不確定度

此項測試之量測不確定度　1GHz 以上為±4.08dB

1GHz 以下為±4.22dB

8.5. 混附發射測試結果

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11a
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	10.470	42.456	52.927	74.00	54.00	Pass
36 (Peak)	5176.667	10.402	92.486	102.888	--	--	--
36 (Average)	5150.000	10.470	26.891	37.362	74.00	54.00	Pass
36 (Average)	5182.609	10.386	84.343	94.730	--	--	--

Figure Channel 36:　　Horizontal (Peak)



Figure Channel 36:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11a
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	12.390	44.016	56.406	74.00	54.00	Pass
36 (Peak)	5186.957	12.528	92.570	105.098	--	--	--
36 (Average)	5150.000	12.390	27.849	40.239	74.00	54.00	Pass
36 (Average)	5182.609	12.510	84.143	96.654	--	--	--

Figure Channel 36:　　Vertical (Peak)



Figure Channel 36:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11a
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5316.812	11.110	93.004	104.113	--	--	--
64 (Peak)	5350.000	11.024	45.307	56.331	74.00	54.00	Pass
64 (Peak)	5352.899	11.017	47.283	58.300	74.00	54.00	Pass
64 (Average)	5323.188	11.093	84.240	95.333	--	--	--
64 (Average)	5350.000	11.024	31.203	42.227	74.00	54.00	Pass

Figure Channel 64:　　Horizontal (Peak)



Figure Channel 64:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11a
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5316.667	13.020	92.612	105.632	--	--	--
64 (Peak)	5350.000	12.999	44.948	57.947	74.00	54.00	Pass
64 (Average)	5314.638	13.021	83.816	96.837	--	--	--
64 (Average)	5350.000	12.999	29.799	42.798	74.00	54.00	Pass

Figure Channel 64:　　Vertical (Peak)



Figure Channel 64:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11a
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	11.703	44.218	55.921	74.00	54.00	Pass
100 (Peak)	5504.783	12.203	89.727	101.929	--	--	--
100 (Average)	5460.000	11.703	29.142	40.845	74.00	54.00	Pass
100 (Average)	5503.333	12.192	81.331	93.523	--	--	--

Figure Channel 100:　　Horizontal (Peak)



Figure Channel 100:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11a
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	13.390	45.422	58.812	74.00	54.00	Pass
100 (Peak)	5496.667	13.620	91.153	104.772	--	--	--
100 (Average)	5460.000	13.390	30.135	43.525	74.00	54.00	Pass
100 (Average)	5498.696	13.625	82.409	96.034	--	--	--

Figure Channel 100:　　Vertical (Peak)



Figure Channel 100:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	10.470	42.355	52.826	74.00	54.00	Pass
36 (Peak)	5184.058	10.383	92.316	102.699	--	--	--
36 (Average)	5150.000	10.470	27.554	38.025	74.00	54.00	Pass
36 (Average)	5183.768	10.384	83.941	94.325	--	--	--

Figure Channel 36:　　Horizontal (Peak)



Figure Channel 36:　　Horizontal (Average)



Note:
1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	12.390	43.585	55.975	74.00	54.00	Pass
36 (Peak)	5184.058	12.516	92.181	104.697	--	--	--
36 (Average)	5150.000	12.390	27.978	40.368	74.00	54.00	Pass
36 (Average)	5186.232	12.525	83.781	96.306	--	--	--

Figure Channel 36: Vertical (Peak)



Figure Channel 36: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5316.377	11.110	92.713	103.823	--	--	--
64 (Peak)	5350.000	11.024	45.095	56.119	74.00	54.00	Pass
64 (Peak)	5351.159	11.022	47.591	58.612	74.00	54.00	Pass
64 (Average)	5321.304	11.098	83.630	94.728	--	--	--
64 (Average)	5350.000	11.024	31.985	43.009	74.00	54.00	Pass

Figure Channel 64:　　Horizontal (Peak)



Figure Channel 64:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5316.522	13.020	92.560	105.580	--	--	--
64 (Peak)	5350.000	12.999	45.922	58.921	74.00	54.00	Pass
64 (Average)	5323.623	13.015	83.539	96.554	--	--	--
64 (Average)	5350.000	12.999	31.117	44.116	74.00	54.00	Pass

Figure Channel 64: Vertical (Peak)



Figure Channel 64: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	11.703	43.068	54.771	74.00	54.00	Pass
100 (Peak)	5496.522	12.144	89.763	101.907	--	--	--
100 (Average)	5460.000	11.703	29.038	40.741	74.00	54.00	Pass
100 (Average)	5498.696	12.160	80.934	93.094	--	--	--

Figure Channel 100:　　Horizontal (Peak)



Figure Channel 100:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	13.390	44.358	57.748	74.00	54.00	Pass
100 (Peak)	5495.217	13.614	90.605	104.219	--	--	--
100 (Average)	5460.000	13.390	29.236	42.626	74.00	54.00	Pass
100 (Average)	5496.957	13.620	81.875	95.495	--	--	--

Figure Channel 100:　　Vertical (Peak)



Figure Channel 100:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	10.470	43.842	54.313	74.00	54.00	Pass
38 (Peak)	5175.507	10.406	88.681	99.087	--	--	--
38 (Average)	5150.000	10.470	27.565	38.036	74.00	54.00	Pass
38 (Average)	5185.797	10.379	80.014	90.393	--	--	--

Figure Channel 38:　　Horizontal (Peak)



Figure Channel 38:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	12.390	44.268	56.658	74.00	54.00	Pass
38 (Peak)	5197.391	12.558	88.799	101.357	--	--	--
38 (Average)	5150.000	12.390	27.738	40.128	74.00	54.00	Pass
38 (Average)	5193.478	12.546	79.875	92.422	--	--	--

Figure Channel 38:　　Vertical (Peak)



Figure Channel 38:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5320.290	11.101	87.968	99.068	--	--	--
62 (Peak)	5350.000	11.024	44.693	55.717	74.00	54.00	Pass
62 (Average)	5318.696	11.104	78.931	90.035	--	--	--
62 (Average)	5350.000	11.024	29.563	40.587	74.00	54.00	Pass

Figure Channel 62:　　Horizontal (Peak)



Figure Channel 62:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5301.159	13.029	88.133	101.162	--	--	--
62 (Peak)	5350.000	12.999	44.423	57.422	74.00	54.00	Pass
62 (Peak)	5351.159	12.999	46.061	59.060	74.00	54.00	Pass
62 (Average)	5304.348	13.028	79.134	92.162	--	--	--
62 (Average)	5350.000	12.999	28.924	41.923	74.00	54.00	Pass

Figure Channel 62:　　Vertical (Peak)



Figure Channel 62:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5460.000	11.703	43.773	55.476	74.00	54.00	Pass
102 (Peak)	5496.232	12.143	86.045	98.187	--	--	--
102 (Average)	5460.000	11.703	28.816	40.519	74.00	54.00	Pass
102 (Average)	5501.594	12.180	77.168	89.348	--	--	--

Figure Channel 102:　　Horizontal (Peak)



Figure Channel 102:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5460.000	13.390	43.579	56.969	74.00	54.00	Pass
102 (Peak)	5495.507	13.615	87.471	101.086	--	--	--
102 (Average)	5460.000	13.390	29.722	43.112	74.00	54.00	Pass
102 (Average)	5507.391	13.630	78.106	91.735	--	--	--

Figure Channel 102:　　Vertical (Peak)



Figure Channel 102:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	10.470	43.675	54.146	74.00	54.00	Pass
42 (Peak)	5191.594	10.361	86.559	96.920	--	--	--
42 (Average)	5150.000	10.470	28.808	39.279	74.00	54.00	Pass
42 (Average)	5186.377	10.377	77.198	87.576	--	--	--

Figure Channel 42:　　Horizontal (Peak)



Figure Channel 42:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	12.390	44.136	56.526	74.00	54.00	Pass
42 (Peak)	5191.594	12.542	87.554	100.095	--	--	--
42 (Average)	5150.000	12.390	29.688	42.078	74.00	54.00	Pass
42 (Average)	5197.536	12.558	78.544	91.102	--	--	--

Figure Channel 42:　　Vertical (Peak)



Figure Channel 42:　　Vertical (Average)



Note:
1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5305.797	11.138	87.503	98.640	--	--	--
58 (Peak)	5350.000	11.024	46.149	57.173	74.00	54.00	Pass
58 (Peak)	5354.348	11.012	50.452	61.465	74.00	54.00	Pass
58 (Average)	5305.362	11.138	77.820	88.959	--	--	--
58 (Average)	5350.000	11.024	31.111	42.135	74.00	54.00	Pass

Figure Channel 58:　　Horizontal (Peak)



Figure Channel 58:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5305.797	13.027	87.607	100.634	--	--	--
58 (Peak)	5350.000	12.999	47.102	60.101	74.00	54.00	Pass
58 (Peak)	5354.348	12.996	50.815	63.811	74.00	54.00	Pass
58 (Average)	5306.957	13.026	77.974	91.000	--	--	--
58 (Average)	5350.000	12.999	31.630	44.629	74.00	54.00	Pass

Figure Channel 58:　　Vertical (Peak)



Figure Channel 58:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5460.000	11.703	45.527	57.230	74.00	54.00	Pass
106 (Peak)	5504.638	12.202	83.560	95.761	--	--	--
106 (Average)	5427.826	11.271	34.488	45.758	74.00	54.00	Pass
106 (Average)	5460.000	11.703	32.468	44.171	74.00	54.00	Pass
106 (Average)	5505.507	12.200	74.338	86.538	--	--	--

Figure Channel 106:　　Horizontal (Peak)



Figure Channel 106:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5460.000	13.390	46.306	59.696	74.00	54.00	Pass
106 (Peak)	5509.130	13.618	84.214	97.832	--	--	--
106 (Average)	5427.246	13.158	35.281	48.440	74.00	54.00	Pass
106 (Average)	5460.000	13.390	33.380	46.770	74.00	54.00	Pass
106 (Average)	5507.391	13.630	75.436	89.065	--	--	--

Figure Channel 106:　　Vertical (Peak)



Figure Channel 106:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5150.000	10.470	41.837	52.308	74.00	54.00	Pass
50 (Peak)	5233.913	10.620	81.227	91.847	--	--	--
50 (Peak)	5350.000	11.024	44.945	55.969	74.00	54.00	Pass
50 (Average)	5150.000	10.470	27.777	38.248	74.00	54.00	Pass
50 (Average)	5234.783	10.626	72.177	82.804	--	--	--
50 (Average)	5350.000	11.024	30.192	41.216	74.00	54.00	Pass
50 (Average)	5398.696	10.934	33.321	44.255	74.00	54.00	Pass

Figure Channel 50:　　Horizontal (Peak)



Figure Channel 50:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5150.000	12.390	42.734	55.124	74.00	54.00	Pass
50 (Peak)	5205.217	12.604	80.698	93.303	--	--	--
50 (Peak)	5350.000	12.999	44.690	57.689	74.00	54.00	Pass
50 (Average)	5147.391	12.381	27.919	40.300	74.00	54.00	Pass
50 (Average)	5150.000	12.390	26.755	39.145	74.00	54.00	Pass
50 (Average)	5226.957	12.700	71.312	84.012	--	--	--
50 (Average)	5350.000	12.999	29.292	42.291	74.00	54.00	Pass
50 (Average)	5398.696	12.984	33.959	46.943	74.00	54.00	Pass

Figure Channel 50:　　Vertical (Peak)



Figure Channel 50:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5413.043	11.071	48.348	59.419	74.00	54.00	Pass
114 (Peak)	5460.000	11.703	44.870	56.573	74.00	54.00	Pass
114 (Peak)	5584.783	11.560	79.948	91.507	--	--	--
114 (Average)	5457.391	11.667	33.743	45.410	74.00	54.00	Pass
114 (Average)	5460.000	11.703	31.665	43.368	74.00	54.00	Pass
114 (Average)	5594.783	11.493	71.129	82.623	--	--	--

Figure Channel 114:　　Horizontal (Peak)



Figure Channel 114:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5453.043	13.340	47.460	60.800	74.00	54.00	Pass
114 (Peak)	5460.000	13.390	45.422	58.812	74.00	54.00	Pass
114 (Peak)	5525.217	13.515	79.484	92.999	--	--	--
114 (Average)	5457.391	13.371	35.542	48.913	74.00	54.00	Pass
114 (Average)	5460.000	13.390	33.159	46.549	74.00	54.00	Pass
114 (Average)	5594.783	13.080	70.318	83.398	--	--	--

Figure Channel 114:　　Vertical (Peak)



Figure Channel 114:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11a
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5149.275	10.473	51.388	61.861	74.00	54.00	Pass
36 (Peak)	5150.000	10.470	50.012	60.483	74.00	54.00	Pass
36 (Peak)	5176.812	10.402	95.446	105.848	--	--	--
36 (Average)	5150.000	10.470	33.539	44.010	74.00	54.00	Pass
36 (Average)	5178.841	10.397	87.031	97.428	--	--	--

Figure Channel 36:　　Horizontal (Peak)



Figure Channel 36:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11a
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	12.390	48.497	60.887	74.00	54.00	Pass
36 (Peak)	5176.812	12.490	95.023	107.513	--	--	--
36 (Average)	5150.000	12.390	31.500	43.890	74.00	54.00	Pass
36 (Average)	5178.696	12.497	86.295	98.791	--	--	--

Figure Channel 36:　　Vertical (Peak)



Figure Channel 36:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11a
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5316.812	11.110	96.496	107.605	--	--	--
64 (Peak)	5350.000	11.024	51.128	62.152	74.00	54.00	Pass
64 (Peak)	5352.464	11.017	53.755	64.773	74.00	54.00	Pass
64 (Average)	5318.696	11.104	88.004	99.108	--	--	--
64 (Average)	5350.000	11.024	37.658	48.682	74.00	54.00	Pass

Figure Channel 64:　　Horizontal (Peak)



Figure Channel 64:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11a
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5326.957	13.014	95.776	108.789	--	--	--
64 (Peak)	5350.000	12.999	52.374	65.373	74.00	54.00	Pass
64 (Average)	5326.087	13.014	87.145	100.158	--	--	--
64 (Average)	5350.000	12.999	37.811	50.810	74.00	54.00	Pass

Figure Channel 64:　　Vertical (Peak)



Figure Channel 64:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11a
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	11.703	45.911	57.614	74.00	54.00	Pass
100 (Peak)	5507.101	12.187	94.517	106.704	--	--	--
100 (Average)	5460.000	11.703	32.507	44.210	74.00	54.00	Pass
100 (Average)	5503.913	12.196	85.883	98.079	--	--	--

Figure Channel 100:　　Horizontal (Peak)



Figure Channel 100:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11a
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	13.390	45.381	58.771	74.00	54.00	Pass
100 (Peak)	5504.638	13.644	93.451	107.095	--	--	--
100 (Average)	5460.000	13.390	31.241	44.631	74.00	54.00	Pass
100 (Average)	5507.391	13.630	85.272	98.901	--	--	--

Figure Channel 100:　　Vertical (Peak)



Figure Channel 100:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5148.986	10.473	51.448	61.921	74.00	54.00	Pass
36 (Peak)	5150.000	10.470	49.359	59.830	74.00	54.00	Pass
36 (Peak)	5177.536	10.400	94.888	105.288	--	--	--
36 (Average)	5150.000	10.470	33.461	43.932	74.00	54.00	Pass
36 (Average)	5178.841	10.397	86.722	97.119	--	--	--

Figure Channel 36:　　Horizontal (Peak)



Figure Channel 36:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5145.362	12.373	50.152	62.525	74.00	54.00	Pass
36 (Peak)	5150.000	12.390	48.419	60.809	74.00	54.00	Pass
36 (Peak)	5177.536	12.492	94.838	107.330	--	--	--
36 (Average)	5150.000	12.390	32.495	44.885	74.00	54.00	Pass
36 (Average)	5178.696	12.497	86.324	98.820	--	--	--

Figure Channel 36:　　Vertical (Peak)



Figure Channel 36:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5315.217	11.113	96.416	107.529	--	--	--
64 (Peak)	5350.000	11.024	52.148	63.172	74.00	54.00	Pass
64 (Peak)	5351.449	11.020	54.493	65.514	74.00	54.00	Pass
64 (Average)	5326.232	11.085	87.600	98.685	--	--	--
64 (Average)	5350.000	11.024	39.451	50.475	74.00	54.00	Pass
64 (Average)	5350.725	11.023	40.453	51.476	74.00	54.00	Pass

Figure Channel 64:　　Horizontal (Peak)



Figure Channel 64:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5324.058	13.015	95.457	108.472	--	--	--
64 (Peak)	5350.000	12.999	52.216	65.215	74.00	54.00	Pass
64 (Peak)	5354.348	12.996	53.308	66.304	74.00	54.00	Pass
64 (Average)	5327.101	13.013	86.893	99.906	--	--	--
64 (Average)	5350.000	12.999	39.291	52.290	74.00	54.00	Pass

Figure Channel 64: Vertical (Peak)



Figure Channel 64: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5454.783	11.633	47.536	59.168	74.00	54.00	Pass
100 (Peak)	5460.000	11.703	46.797	58.500	74.00	54.00	Pass
100 (Peak)	5504.203	12.198	94.457	106.655	--	--	--
100 (Average)	5460.000	11.703	33.417	45.120	74.00	54.00	Pass
100 (Average)	5502.609	12.187	85.859	98.046	--	--	--

Figure Channel 100:　　Horizontal (Peak)



Figure Channel 100:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	13.390	45.842	59.232	74.00	54.00	Pass
100 (Peak)	5506.522	13.635	93.527	107.162	--	--	--
100 (Average)	5460.000	13.390	31.890	45.280	74.00	54.00	Pass
100 (Average)	5507.246	13.631	84.979	98.609	--	--	--

Figure Channel 100:　　Vertical (Peak)



Figure Channel 100:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	10.470	47.442	57.913	74.00	54.00	Pass
38 (Peak)	5175.507	10.406	91.435	101.841	--	--	--
38 (Average)	5150.000	10.470	34.427	44.898	74.00	54.00	Pass
38 (Average)	5178.841	10.397	82.813	93.210	--	--	--

Figure Channel 38:　　Horizontal (Peak)



Figure Channel 38:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	12.390	45.524	57.914	74.00	54.00	Pass
38 (Peak)	5181.449	12.506	91.264	103.770	--	--	--
38 (Average)	5150.000	12.390	33.242	45.632	74.00	54.00	Pass
38 (Average)	5178.696	12.497	82.566	95.062	--	--	--

Figure Channel 38:　　Vertical (Peak)



Figure Channel 38:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5320.290	11.101	91.482	102.582	--	--	--
62 (Peak)	5350.000	11.024	46.501	57.525	74.00	54.00	Pass
62 (Peak)	5351.449	11.020	48.292	59.313	74.00	54.00	Pass
62 (Average)	5302.899	11.144	82.550	93.695	--	--	--
62 (Average)	5350.000	11.024	33.863	44.887	74.00	54.00	Pass

Figure Channel 62:　　Horizontal (Peak)



Figure Channel 62:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5302.609	13.028	90.711	103.739	--	--	--
62 (Peak)	5350.000	12.999	46.959	59.958	74.00	54.00	Pass
62 (Average)	5302.754	13.028	81.787	94.815	--	--	--
62 (Average)	5350.000	12.999	33.489	46.488	74.00	54.00	Pass

Figure Channel 62:　　Vertical (Peak)



Figure Channel 62:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5458.841	11.687	50.614	62.301	74.00	54.00	Pass
102 (Peak)	5460.000	11.703	49.215	60.918	74.00	54.00	Pass
102 (Peak)	5505.652	12.198	91.501	103.699	--	--	--
102 (Average)	5460.000	11.703	36.477	48.180	74.00	54.00	Pass
102 (Average)	5498.986	12.162	82.216	94.378	--	--	--

Figure Channel 102:　　Horizontal (Peak)



Figure Channel 102:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5458.985	13.383	50.110	63.492	74.00	54.00	Pass
102 (Peak)	5460.000	13.390	47.782	61.172	74.00	54.00	Pass
102 (Peak)	5505.797	13.639	90.723	104.363	--	--	--
102 (Average)	5457.536	13.372	36.993	50.365	74.00	54.00	Pass
102 (Average)	5460.000	13.390	35.686	49.076	74.00	54.00	Pass
102 (Average)	5507.246	13.631	81.837	95.467	--	--	--

Figure Channel 102:　　Vertical (Peak)



Figure Channel 102:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	10.470	51.781	62.252	74.00	54.00	Pass
42 (Peak)	5191.304	10.362	89.589	99.951	--	--	--
42 (Average)	5147.246	10.478	40.318	50.796	74.00	54.00	Pass
42 (Average)	5150.000	10.470	39.297	49.768	74.00	54.00	Pass
42 (Average)	5198.406	10.338	80.442	90.779	--	--	--

Figure Channel 42:　　Horizontal (Peak)



Figure Channel 42:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	12.390	51.073	63.463	74.00	54.00	Pass
42 (Peak)	5191.449	12.541	89.669	102.210	--	--	--
42 (Average)	5146.957	12.380	38.977	51.356	74.00	54.00	Pass
42 (Average)	5150.000	12.390	38.355	50.745	74.00	54.00	Pass
42 (Average)	5197.391	12.558	80.717	93.275	--	--	--

Figure Channel 42:　　Vertical (Peak)



Figure Channel 42:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5305.652	11.137	91.615	102.753	--	--	--
58 (Peak)	5350.000	11.024	50.534	61.558	74.00	54.00	Pass
58 (Peak)	5355.652	11.009	56.402	67.411	74.00	54.00	Pass
58 (Average)	5305.217	11.139	82.095	93.234	--	--	--
58 (Average)	5350.000	11.024	36.571	47.595	74.00	54.00	Pass

Figure Channel 58:　　Horizontal (Peak)



Figure Channel 58:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5305.652	13.026	90.888	103.915	--	--	--
58 (Peak)	5350.000	12.999	49.780	62.779	74.00	54.00	Pass
58 (Peak)	5354.058	12.996	56.280	69.276	74.00	54.00	Pass
58 (Average)	5303.043	13.029	81.209	94.237	--	--	--
58 (Average)	5350.000	12.999	37.300	50.299	74.00	54.00	Pass

Figure Channel 58:　　Vertical (Peak)



Figure Channel 58:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5460.000	11.703	51.871	63.574	74.00	54.00	Pass
106 (Peak)	5506.377	12.193	88.918	101.111	--	--	--
106 (Average)	5458.696	11.685	41.382	53.067	74.00	54.00	Pass
106 (Average)	5460.000	11.703	40.174	51.877	74.00	54.00	Pass
106 (Average)	5507.536	12.183	80.456	92.639	--	--	--

Figure Channel 106:　　Horizontal (Peak)



Figure Channel 106:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5460.000	13.390	50.285	63.675	74.00	54.00	Pass
106 (Peak)	5504.638	13.644	88.426	102.070	--	--	--
106 (Average)	5458.261	13.378	39.549	52.926	74.00	54.00	Pass
106 (Average)	5460.000	13.390	38.328	51.718	74.00	54.00	Pass
106 (Average)	5507.391	13.630	79.337	92.966	--	--	--

Figure Channel 106:　　Vertical (Peak)



Figure Channel 106:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5142.609	10.489	49.500	59.989	74.00	54.00	Pass
50 (Peak)	5150.000	10.470	47.053	57.524	74.00	54.00	Pass
50 (Peak)	5301.739	11.147	85.733	96.880	--	--	--
50 (Peak)	5350.000	11.024	48.879	59.903	74.00	54.00	Pass
50 (Peak)	5359.565	10.998	51.888	62.887	74.00	54.00	Pass
50 (Average)	5146.957	10.479	37.784	48.263	74.00	54.00	Pass
50 (Average)	5150.000	10.470	35.445	45.916	74.00	54.00	Pass
50 (Average)	5294.783	11.104	76.873	87.976	--	--	--
50 (Average)	5350.000	11.024	37.440	48.464	74.00	54.00	Pass
50 (Average)	5379.130	10.948	39.026	49.973	74.00	54.00	Pass

Figure Channel 50:　　Horizontal (Peak)



Figure Channel 50:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5146.087	12.376	48.091	60.467	74.00	54.00	Pass
50 (Peak)	5150.000	12.390	46.254	58.644	74.00	54.00	Pass
50 (Peak)	5265.217	12.872	85.826	98.698	--	--	--
50 (Peak)	5350.000	12.999	50.302	63.301	74.00	54.00	Pass
50 (Peak)	5360.000	12.992	53.658	66.650	74.00	54.00	Pass
50 (Average)	5137.391	12.342	36.022	48.364	74.00	54.00	Pass
50 (Average)	5150.000	12.390	34.947	47.337	74.00	54.00	Pass
50 (Average)	5275.217	12.917	76.877	89.795	--	--	--
50 (Average)	5350.000	12.999	39.298	52.297	74.00	54.00	Pass
50 (Average)	5357.826	12.994	40.309	53.303	74.00	54.00	Pass

Figure Channel 50:　　Vertical (Peak)



Figure Channel 50:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5460.000	11.703	47.901	59.604	74.00	54.00	Pass
114 (Peak)	5524.783	12.044	82.935	94.979	--	--	--
114 (Average)	5460.000	11.703	37.486	49.189	74.00	54.00	Pass
114 (Average)	5518.261	12.097	74.990	87.087	--	--	--

Figure Channel 114:　　Horizontal (Peak)



Figure Channel 114:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5438.696	13.240	48.919	62.159	74.00	54.00	Pass
114 (Peak)	5460.000	13.390	47.638	61.028	74.00	54.00	Pass
114 (Peak)	5525.217	13.515	83.935	97.450	--	--	--
114 (Average)	5460.000	13.390	36.828	50.218	74.00	54.00	Pass
114 (Average)	5518.696	13.557	73.996	87.553	--	--	--

Figure Channel 114:　　Vertical (Peak)



Figure Channel 114:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	10.470	44.794	55.265	74.00	54.00	Pass
36 (Peak)	5173.043	10.412	97.149	107.561	--	--	--
36 (Average)	5150.000	10.470	31.291	41.762	74.00	54.00	Pass
36 (Average)	5174.638	10.408	87.707	98.115	--	--	--

Figure Channel 36:　　Horizontal (Peak)



Figure Channel 36:　　Horizontal (Average)



Note:
1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5147.971	12.383	47.062	59.445	74.00	54.00	Pass
36 (Peak)	5150.000	12.390	45.401	57.791	74.00	54.00	Pass
36 (Peak)	5175.217	12.484	96.760	109.244	--	--	--
36 (Average)	5150.000	12.390	31.171	43.561	74.00	54.00	Pass
36 (Average)	5178.551	12.496	87.400	99.896	--	--	--

Figure Channel 36:　　Vertical (Peak)



Figure Channel 36:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5327.391	11.082	97.145	108.227	--	--	--
64 (Peak)	5350.000	11.024	47.635	58.659	74.00	54.00	Pass
64 (Peak)	5357.246	11.005	48.888	59.893	74.00	54.00	Pass
64 (Average)	5314.783	11.115	88.004	99.118	--	--	--
64 (Average)	5350.000	11.024	33.306	44.330	74.00	54.00	Pass

Figure Channel 64:　　Horizontal (Peak)



Figure Channel 64:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5325.072	13.015	95.688	108.702	--	--	--
64 (Peak)	5350.000	12.999	47.574	60.573	74.00	54.00	Pass
64 (Average)	5318.551	13.019	86.654	99.673	--	--	--
64 (Average)	5350.000	12.999	32.963	45.962	74.00	54.00	Pass

Figure Channel 64:　　Vertical (Peak)



Figure Channel 64:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	11.703	45.926	57.629	74.00	54.00	Pass
100 (Peak)	5501.594	12.180	94.076	106.256	--	--	--
100 (Average)	5460.000	11.703	30.526	42.229	74.00	54.00	Pass
100 (Average)	5498.696	12.160	85.284	97.444	--	--	--

Figure Channel 100:　　Horizontal (Peak)



Figure Channel 100:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5459.275	13.384	46.441	59.825	74.00	54.00	Pass
100 (Peak)	5460.000	13.390	44.352	57.742	74.00	54.00	Pass
100 (Peak)	5506.522	13.635	93.358	106.993	--	--	--
100 (Average)	5460.000	13.390	30.432	43.822	74.00	54.00	Pass
100 (Average)	5496.377	13.618	84.374	97.992	--	--	--

Figure Channel 100:　　Vertical (Peak)



Figure Channel 100:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	10.470	47.174	57.645	74.00	54.00	Pass
38 (Peak)	5178.116	10.398	93.590	103.989	--	--	--
38 (Average)	5150.000	10.470	32.192	42.663	74.00	54.00	Pass
38 (Average)	5185.507	10.380	83.543	93.923	--	--	--

Figure Channel 38:　　Horizontal (Peak)



Figure Channel 38:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	12.390	45.885	58.275	74.00	54.00	Pass
38 (Peak)	5178.261	12.495	93.595	106.090	--	--	--
38 (Average)	5150.000	12.390	32.884	45.274	74.00	54.00	Pass
38 (Average)	5198.696	12.561	83.885	96.446	--	--	--

Figure Channel 38:　　Vertical (Peak)



Figure Channel 38:　　Vertical (Average)



Note:
1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5323.333	11.092	92.664	103.756	--	--	--
62 (Peak)	5350.000	11.024	46.658	57.682	74.00	54.00	Pass
62 (Average)	5314.638	11.115	83.267	94.381	--	--	--
62 (Average)	5350.000	11.024	33.286	44.310	74.00	54.00	Pass

Figure Channel 62:　　Horizontal (Peak)



Figure Channel 62:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5315.652	13.020	91.343	104.363	--	--	--
62 (Peak)	5350.000	12.999	46.319	59.318	74.00	54.00	Pass
62 (Average)	5318.841	13.019	81.278	94.297	--	--	--
62 (Average)	5350.000	12.999	33.293	46.292	74.00	54.00	Pass

Figure Channel 62:　　Vertical (Peak)



Figure Channel 62:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5458.841	11.687	49.947	61.634	74.00	54.00	Pass
102 (Peak)	5460.000	11.703	48.875	60.578	74.00	54.00	Pass
102 (Peak)	5502.319	12.185	92.185	104.370	--	--	--
102 (Average)	5457.681	11.672	36.662	48.333	74.00	54.00	Pass
102 (Average)	5460.000	11.703	35.472	47.175	74.00	54.00	Pass
102 (Average)	5498.696	12.160	82.345	94.505	--	--	--

Figure Channel 102:　　Horizontal (Peak)



Figure Channel 102:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11n-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5456.087	13.361	51.036	64.398	74.00	54.00	Pass
102 (Peak)	5460.000	13.390	50.699	64.089	74.00	54.00	Pass
102 (Peak)	5496.957	13.620	90.812	104.432	--	--	--
102 (Average)	5460.000	13.390	35.689	49.079	74.00	54.00	Pass
102 (Average)	5504.638	13.644	81.687	95.331	--	--	--

Figure Channel 102:　　Vertical (Peak)



Figure Channel 102:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	10.470	51.043	61.514	74.00	54.00	Pass
42 (Peak)	5186.232	10.378	91.227	101.605	--	--	--
42 (Average)	5147.391	10.478	39.323	49.800	74.00	54.00	Pass
42 (Average)	5150.000	10.470	37.362	47.833	74.00	54.00	Pass
42 (Average)	5184.638	10.382	82.048	92.430	--	--	--

Figure Channel 42:　　Horizontal (Peak)



Figure Channel 42:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 21 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	12.390	49.710	62.100	74.00	54.00	Pass
42 (Peak)	5198.406	12.561	92.190	104.750	--	--	--
42 (Average)	5147.391	12.381	39.439	51.820	74.00	54.00	Pass
42 (Average)	5150.000	12.390	37.441	49.831	74.00	54.00	Pass
42 (Average)	5194.783	12.551	82.023	94.573	--	--	--

Figure Channel 42:　　Vertical (Peak)



Figure Channel 42:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5304.348	11.141	92.605	103.746	--	--	--
58 (Peak)	5350.000	11.024	46.083	57.107	74.00	54.00	Pass
58 (Average)	5304.493	11.141	81.979	93.120	--	--	--
58 (Average)	5350.000	11.024	34.126	45.150	74.00	54.00	Pass

Figure Channel 58:　　Horizontal (Peak)



Figure Channel 58:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5313.623	13.021	90.885	103.906	--	--	--
58 (Peak)	5350.000	12.999	46.217	59.216	74.00	54.00	Pass
58 (Average)	5302.319	13.028	80.658	93.686	--	--	--
58 (Average)	5350.000	12.999	33.868	46.867	74.00	54.00	Pass

Figure Channel 58: Vertical (Peak)



Figure Channel 58: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5460.000	11.703	50.067	61.770	74.00	54.00	Pass
106 (Peak)	5506.232	12.193	89.664	101.858	--	--	--
106 (Average)	5458.116	11.677	38.254	49.931	74.00	54.00	Pass
106 (Average)	5460.000	11.703	36.894	48.597	74.00	54.00	Pass
106 (Average)	5507.246	12.186	79.970	92.156	--	--	--

Figure Channel 106:　　Horizontal (Peak)



Figure Channel 106:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5460.000	13.390	47.600	60.990	74.00	54.00	Pass
106 (Peak)	5506.087	13.638	88.588	102.226	--	--	--
106 (Average)	5460.000	13.390	34.767	48.157	74.00	54.00	Pass
106 (Average)	5504.783	13.644	78.973	92.617	--	--	--

Figure Channel 106:　　Vertical (Peak)



Figure Channel 106:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5146.087	10.481	47.899	58.380	74.00	54.00	Pass
50 (Peak)	5150.000	10.470	45.476	55.947	74.00	54.00	Pass
50 (Peak)	5301.739	11.147	86.149	97.296	--	--	--
50 (Peak)	5350.000	11.024	47.124	58.148	74.00	54.00	Pass
50 (Peak)	5373.478	10.962	49.921	60.883	74.00	54.00	Pass
50 (Average)	5146.957	10.479	35.822	46.301	74.00	54.00	Pass
50 (Average)	5150.000	10.470	33.041	43.512	74.00	54.00	Pass
50 (Average)	5294.783	11.104	76.728	87.831	--	--	--
50 (Average)	5350.000	11.024	34.869	45.893	74.00	54.00	Pass
50 (Average)	5379.130	10.948	37.568	48.515	74.00	54.00	Pass

Figure Channel 50:　　Horizontal (Peak)



Figure Channel 50:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5142.174	12.361	47.640	60.001	74.00	54.00	Pass
50 (Peak)	5150.000	12.390	45.841	58.231	74.00	54.00	Pass
50 (Peak)	5282.609	12.951	84.975	97.926	--	--	--
50 (Peak)	5350.000	12.999	45.496	58.495	74.00	54.00	Pass
50 (Peak)	5372.609	12.982	48.793	61.775	74.00	54.00	Pass
50 (Average)	5138.261	12.346	35.109	47.455	74.00	54.00	Pass
50 (Average)	5150.000	12.390	32.801	45.191	74.00	54.00	Pass
50 (Average)	5278.696	12.933	75.184	88.117	--	--	--
50 (Average)	5350.000	12.999	33.666	46.665	74.00	54.00	Pass
50 (Average)	5377.826	12.979	36.339	49.318	74.00	54.00	Pass

Figure Channel 50:　　Vertical (Peak)



Figure Channel 50:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5438.261	11.411	48.646	60.057	74.00	54.00	Pass
114 (Peak)	5460.000	11.703	46.930	58.633	74.00	54.00	Pass
114 (Peak)	5527.391	12.023	85.372	97.395	--	--	--
114 (Average)	5456.957	11.662	37.071	48.733	74.00	54.00	Pass
114 (Average)	5460.000	11.703	35.176	46.879	74.00	54.00	Pass
114 (Average)	5547.391	11.861	75.363	87.225	--	--	--

Figure Channel 114:　　Horizontal (Peak)



Figure Channel 114:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 3: MIMO: 發射器 802.11ac-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 22 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5453.913	13.346	48.951	62.297	74.00	54.00	Pass
114 (Peak)	5460.000	13.390	46.819	60.209	74.00	54.00	Pass
114 (Peak)	5562.174	13.281	83.332	96.613	--	--	--
114 (Average)	5458.696	13.380	37.103	50.483	74.00	54.00	Pass
114 (Average)	5460.000	13.390	34.985	48.375	74.00	54.00	Pass
114 (Average)	5534.783	13.454	74.337	87.791	--	--	--

Figure Channel 114:　　Vertical (Peak)



Figure Channel 114:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	10.470	42.315	52.786	74.00	54.00	Pass
36 (Peak)	5185.072	10.381	93.793	104.174	--	--	--
36 (Average)	5150.000	10.470	27.460	37.931	74.00	54.00	Pass
36 (Average)	5186.522	10.378	83.141	93.518	--	--	--

Figure Channel 36:　　Horizontal (Peak)



Figure Channel 36:　　Horizontal (Average)



Note:
1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	12.390	42.806	55.196	74.00	54.00	Pass
36 (Peak)	5185.217	12.521	94.356	106.877	--	--	--
36 (Average)	5150.000	12.390	28.286	40.676	74.00	54.00	Pass
36 (Average)	5188.116	12.532	83.876	96.407	--	--	--

Figure Channel 36:　　Vertical (Peak)



Figure Channel 36:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5317.826	11.107	93.844	104.950	--	--	--
64 (Peak)	5350.000	11.024	45.939	56.963	74.00	54.00	Pass
64 (Average)	5317.391	11.107	83.167	94.275	--	--	--
64 (Average)	5350.000	11.024	31.099	42.123	74.00	54.00	Pass

Figure Channel 64:　　Horizontal (Peak)



Figure Channel 64:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 64 (5320MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
64 (Peak)	5316.377	13.020	93.724	106.744	--	--	--
64 (Peak)	5350.000	12.999	45.076	58.075	74.00	54.00	Pass
64 (Average)	5314.783	13.022	83.100	96.121	--	--	--
64 (Average)	5350.000	12.999	30.403	43.402	74.00	54.00	Pass

Figure Channel 64:　　Vertical (Peak)



Figure Channel 64:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	11.703	43.048	54.751	74.00	54.00	Pass
100 (Peak)	5498.116	12.155	90.652	102.808	--	--	--
100 (Average)	5460.000	11.703	29.032	40.735	74.00	54.00	Pass
100 (Average)	5496.522	12.144	80.150	92.294	--	--	--

Figure Channel 100:　　Horizontal (Peak)



Figure Channel 100:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 100 (5500MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-20BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
100 (Peak)	5460.000	13.390	45.449	58.839	74.00	54.00	Pass
100 (Peak)	5497.826	13.622	91.920	105.542	--	--	--
100 (Average)	5460.000	13.390	29.783	43.173	74.00	54.00	Pass
100 (Average)	5498.696	13.625	81.146	94.771	--	--	--

Figure Channel 100:　　Vertical (Peak)



Figure Channel 100:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	10.470	43.150	53.621	74.00	54.00	Pass
38 (Peak)	5184.638	10.382	91.019	101.401	--	--	--
38 (Average)	5150.000	10.470	28.260	38.731	74.00	54.00	Pass
38 (Average)	5186.377	10.377	79.257	89.635	--	--	--

Figure Channel 38: Horizontal (Peak)



Figure Channel 38: Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 38 (5190MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
38 (Peak)	5150.000	12.390	44.004	56.394	74.00	54.00	Pass
38 (Peak)	5184.638	12.519	91.520	104.038	--	--	--
38 (Average)	5150.000	12.390	29.254	41.644	74.00	54.00	Pass
38 (Average)	5197.391	12.558	79.587	92.145	--	--	--

Figure Channel 38:　　Vertical (Peak)



Figure Channel 38:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5303.478	11.143	89.433	100.576	--	--	--
62 (Peak)	5350.000	11.024	44.319	55.343	74.00	54.00	Pass
62 (Average)	5301.449	11.147	77.715	88.863	--	--	--
62 (Average)	5350.000	11.024	28.406	39.430	74.00	54.00	Pass

Figure Channel 62:　　Horizontal (Peak)



Figure Channel 62:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 62 (5310MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
62 (Peak)	5304.348	13.028	90.122	103.150	--	--	--
62 (Peak)	5350.000	12.999	44.636	57.635	74.00	54.00	Pass
62 (Average)	5302.464	13.028	77.916	90.944	--	--	--
62 (Average)	5350.000	12.999	28.196	41.195	74.00	54.00	Pass

Figure Channel 62:　　Vertical (Peak)



Figure Channel 62:　　Vertical (Average)

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-40BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5460.000	11.703	45.289	56.992	74.00	54.00	Pass
102 (Peak)	5504.638	12.202	88.655	100.856	--	--	--
102 (Average)	5460.000	11.703	29.565	41.268	74.00	54.00	Pass
102 (Average)	5506.812	12.189	76.811	89.000	--	--	--

Figure Channel 102:　　Horizontal (Peak)



Figure Channel 102:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 102 (5510MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-40BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
102 (Peak)	5460.000	13.390	45.025	58.415	74.00	54.00	Pass
102 (Peak)	5504.493	13.642	89.879	103.522	--	--	--
102 (Average)	5460.000	13.390	30.099	43.489	74.00	54.00	Pass
102 (Average)	5503.623	13.640	78.064	91.705	--	--	--

Figure Channel 102:　　Vertical (Peak)



Figure Channel 102:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	10.470	44.203	54.674	74.00	54.00	Pass
42 (Peak)	5185.942	10.379	88.557	98.936	--	--	--
42 (Average)	5150.000	10.470	29.952	40.423	74.00	54.00	Pass
42 (Average)	5194.783	10.351	76.833	87.183	--	--	--

Figure Channel 42:　　Horizontal (Peak)



Figure Channel 42:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 42 (5210MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
42 (Peak)	5150.000	12.390	45.402	57.792	74.00	54.00	Pass
42 (Peak)	5193.768	12.548	89.540	102.088	--	--	--
42 (Average)	5150.000	12.390	30.646	43.036	74.00	54.00	Pass
42 (Average)	5195.072	12.552	77.956	90.507	--	--	--

Figure Channel 42:　　Vertical (Peak)



Figure Channel 42:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5303.623	11.142	89.167	100.310	--	--	--
58 (Peak)	5350.000	11.024	45.569	56.593	74.00	54.00	Pass
58 (Average)	5315.217	11.113	77.357	88.470	--	--	--
58 (Average)	5350.000	11.024	30.116	41.140	74.00	54.00	Pass

Figure Channel 58:　　Horizontal (Peak)



Figure Channel 58:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 58 (5290MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
58 (Peak)	5303.478	13.028	89.341	102.369	--	--	--
58 (Peak)	5350.000	12.999	44.763	57.762	74.00	54.00	Pass
58 (Average)	5302.174	13.029	77.501	90.529	--	--	--
58 (Average)	5350.000	12.999	29.396	42.395	74.00	54.00	Pass

Figure Channel 58: Vertical (Peak)



Figure Channel 58: Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-80BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5438.551	11.415	47.467	58.882	74.00	54.00	Pass
106 (Peak)	5460.000	11.703	45.032	56.735	74.00	54.00	Pass
106 (Peak)	5505.942	12.196	85.783	97.979	--	--	--
106 (Average)	5445.072	11.503	33.847	45.349	74.00	54.00	Pass
106 (Average)	5460.000	11.703	31.213	42.916	74.00	54.00	Pass
106 (Average)	5507.536	12.183	74.045	86.228	--	--	--

Figure Channel 106:　　Horizontal (Peak)



Figure Channel 106:　　Horizontal (Average)

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 106 (5530MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-80BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
106 (Peak)	5426.232	13.152	48.579	61.731	74.00	54.00	Pass
106 (Peak)	5460.000	13.390	44.311	57.701	74.00	54.00	Pass
106 (Peak)	5506.522	13.635	85.789	99.424	--	--	--
106 (Average)	5432.174	13.195	34.247	47.441	74.00	54.00	Pass
106 (Average)	5460.000	13.390	31.510	44.900	74.00	54.00	Pass
106 (Average)	5507.246	13.631	75.014	88.644	--	--	--

Figure Channel 106:　　Vertical (Peak)



Figure Channel 106:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5136.522	10.504	43.910	54.413	74.00	54.00	Pass
50 (Peak)	5150.000	10.470	42.336	52.807	74.00	54.00	Pass
50 (Peak)	5226.957	10.563	83.758	94.321	--	--	--
50 (Peak)	5350.000	11.024	43.694	54.718	74.00	54.00	Pass
50 (Peak)	5354.783	11.012	47.083	58.095	74.00	54.00	Pass
50 (Average)	5150.000	10.470	27.104	37.575	74.00	54.00	Pass
50 (Average)	5235.217	10.630	71.842	82.472	--	--	--
50 (Average)	5350.000	11.024	29.811	40.835	74.00	54.00	Pass

Figure Channel 50:　　Horizontal (Peak)



Figure Channel 50:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 50 (5250MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
50 (Peak)	5108.696	12.241	44.626	56.867	74.00	54.00	Pass
50 (Peak)	5150.000	12.390	42.386	54.776	74.00	54.00	Pass
50 (Peak)	5253.043	12.818	82.468	95.286	--	--	--
50 (Peak)	5350.000	12.999	44.390	57.389	74.00	54.00	Pass
50 (Average)	5150.000	12.390	26.771	39.161	74.00	54.00	Pass
50 (Average)	5234.783	12.735	70.713	83.448	--	--	--
50 (Average)	5350.000	12.999	28.823	41.822	74.00	54.00	Pass
50 (Average)	5395.217	12.981	31.334	44.315	74.00	54.00	Pass

Figure Channel 50:　　Vertical (Peak)



Figure Channel 50:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-160BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5422.174	11.194	47.629	58.823	74.00	54.00	Pass
114 (Peak)	5460.000	11.703	45.461	57.164	74.00	54.00	Pass
114 (Peak)	5599.130	11.472	83.018	94.490	--	--	--
114 (Average)	5457.391	11.667	33.247	44.914	74.00	54.00	Pass
114 (Average)	5460.000	11.703	31.472	43.175	74.00	54.00	Pass
114 (Average)	5594.783	11.493	71.025	82.519	--	--	--

Figure Channel 114:　　Horizontal (Peak)



Figure Channel 114:　　Horizontal (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH 114 (5570MHz)　　測試模式：Mode 1: SISO A: 發射器 802.11ax-160BW
量測距離：3 M　　天線極化：Vertical
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 18 日　　環境濕度：53 %

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Arerage Limit (dBμV/m)	Result
114 (Peak)	5460.000	13.390	45.145	58.535	74.00	54.00	Pass
114 (Peak)	5566.522	13.254	82.226	95.480	--	--	--
114 (Average)	5457.391	13.371	35.430	48.801	74.00	54.00	Pass
114 (Average)	5460.000	13.390	33.030	46.420	74.00	54.00	Pass
114 (Average)	5527.826	13.498	69.900	83.398	--	--	--

Figure Channel 114:　　Vertical (Peak)



Figure Channel 114:　　Vertical (Average)



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

待測物名稱：Intel® Wi-Fi 6 AX200
待測物型號：AX200NGW　　測試項目：混附發射
測試頻道：CH36 (5180MHz)　　測試模式：Mode 2: SISO B: 發射器 802.11ax-20BW
量測距離：3 M　　天線極化：Horizontal
檢測器：峰值　　環境溫度：21 ℃
測試日期：108 年 01 月 19 日　　環境濕度：53 %

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
36 (Peak)	5150.000	10.470	46.318	56.789	74.00	54.00	Pass
36 (Peak)	5178.116	10.398	96.038	106.437	--	--	--
36 (Average)	5150.000	10.470	32.872	43.343	74.00	54.00	Pass
36 (Average)	5178.696	10.397	85.513	95.910	--	--	--

Figure Channel 36:　　Horizontal (Peak)



Figure Channel 36:　　Horizontal (Average)



Note:
1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.