


NCC RADIO TEST REPORT

Product name	TWS EARBUDS TRUE WIRELESS STEREO
Applicant	錦沛科技有限公司
Manufacture	深圳市子然科技有限公司
Rating(s)	DC5V from adapter or DC3.7V from battery
Trademark	Jinpei
Model and/or type reference	JE-01B
Standard	LP0002:2020
Test Result	Pass

Date of receipt : 07-09-2021

Signature :


Date of Issue : 07-27-2021



NCC RADIO TEST REPORT**Report Reference No.** M210728N2

Compiled by (+ signature) Kevin Bothmann

Approved by (+ signature) Jay Gandhi



Date of issue 07-27-2021

Applicant's name 錦沛科技有限公司

Address (221)新北市汐止區文化裡汐碇路 16 之 1 巷 9 號 9 樓

Manufacture's Name 深圳市子然科技有限公司

Address 廣東省深圳市龍華新區油松社區水門新圍村後山工業園 3 棟 4 樓

Test specification:

Standard LP0002: 2020

Test procedure EIA 603、ANSI、FCC/47 CFR/2.1046、2.1047、2.1049、2.1051、2.1053 and 2.1055

Non-standard test method... N/A

Test item description

Product name TWS EARBUDS TRUE WIRELESS STEREO

Trademark Jinpei

Model and/or type reference JE-01B

Rating(s) DC5V from adapter or DC3.7V from battery

Testing Laboratory information

Testing Laboratory Name Electro Magnetic Test, Inc.

Address 1547 Plymouth Street, Mountain View, CA 94043

CAB Identifier Number US0036

Tel. (650) 965-4000

Fax (650) 965-3000

E-mail jgandhi@emtlabs.com

Testing

Date of receipt of test item Jul.09, 2021

Date (s) of performance of tests Jul.09~ Jul.27, 2021

Date of Issue Jul.27, 2021

Test Result **Pass**

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Electro Magnetic Test, Inc., which is an independent testing and consulting firm. The test report is based on testing performed Electro Magnetic Test, Inc. personnel according to the measurement procedure described in the test specification given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Federal Government.

Electro Magnetic Test, Inc. is recognized by the following agencies for performing EMI/EMC testing:

COUNTRY	AGENCY	IDENTIFYING #
USA	Federal Communications Commission (FCC) (EMT's test site is recognized by the FCC)	Registration Number: 90576
USA, Canada, Taiwan, Australia/New Zealand, European Community	National Voluntary Lab Accreditation Program (NVLAP) (EMT is accredited by NVLAP. A copy of the NVLAP Scope Of Accreditation is available upon request.)	Lab Code: 200147-0
Canada	Industry Canada	File No.: IC 2804
Japan	Voluntary Control Council For Interference (VCCI)	See Below
	Open Field Test Site "A"	R-589
	Mains Conducted Emissions Test Site "A"	C-604
	Telecom Conducted Emissions Test Site "A"	T-1655
	3 Meter Semi-Anechoic Chamber Site "E"	R-3227
	3 Meter Semi-Anechoic Chamber Site "E" (1GHz – 6GHz)	G-219
	Mains Conducted Emissions Test Site "E"	C-35793
	Telecom Conducted Emissions Test Site "E"	T-1715
Korea	Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (A copy of the Scope Of Accreditation is available upon request)	US0036
Taiwan	Bureau Of Standards, Metrology and Inspection (BSMI)	Reference Number: SL2-IN-E-1024
Australia / New Zealand	Australian Communications Authority (AUSTEL)	*

***THESE AGENCIES DO NOT ISSUE AN IDENTIFYING NUMBER TO TEST LABS.**

Table of Contents	Page
GENERAL REPORT SUMMARY	3
1 . SUMMARY OF TEST RESULTS	6
1.1 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	14
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	15
3 . EMC EMISSION TEST	17
3.1 CONDUCTED EMISSION MEASUREMENT	17
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	17
3.1.2 TEST PROCEDURE	18
3.1.3 DEVIATION FROM TEST STANDARD	18
3.1.4 TEST SETUP	18
3.1.5 TEST RESULTS	19
3.2 RADIATED EMISSION MEASUREMENT	23
3.2.1 RADIATED EMISSION LIMITS	23
3.2.2 TEST PROCEDURE	24
3.2.3 TEST SETUP	24
3.2.4 EUT OPERATING CONDITIONS	25
3.2.5 TEST RESULTS (BLOW 30 MHZ)	25
3.2.6 TEST RESULTS (BETWEEN30 – 1000 MHZ)	26
3.2.7 TEST RESULTS (FRENQUCY RANGE 1000-25000 MHZ)	38
3.2.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	94
4 . OCCUPIED BANDWIDTH TEST	106
4.1 APPLIED PROCEDURES / LIMIT	106
4.1.1 TEST PROCEDURE	106
4.1.2 TEST SETUP	106
4.1.3 EUT OPERATION CONDITIONS	106
4.1.4 TEST RESULTS	107
5 . NUMBER OF HOPPING CHANNEL	115
5.1 APPLIED PROCEDURES / LIMIT	115
5.1.1 TEST PROCEDURE	115
5.1.2 TEST SETUP	115

Table of Contents	Page
5.1.3 EUT OPERATION CONDITIONS	115
5.1.4 TEST RESULTS	116
6 . AVERAGE TIME OF OCCUPANCY	120
6.1 APPLIED PROCEDURES / LIMIT	120
6.1.1 TEST PROCEDURE	120
6.1.2 TEST SETUP	120
6.1.3 EUT OPERATION CONDITIONS	120
6.1.4 TEST RESULTS	121
7 . HOPPING CHANNEL SEPARATION MEASUREMENT	129
7.1 APPLIED PROCEDURES / LIMIT	129
7.1.1 TEST PROCEDURE	129
7.1.2 TEST SETUP	129
7.1.3 EUT OPERATION CONDITIONS	129
7.1.4 TEST RESULTS	130
8 . PEAK OUTPUT POWER TEST	138
8.1 APPLIED PROCEDURES / LIMIT	138
8.1.1 TEST PROCEDURE	138
8.1.2 DEVIATION FROM STANDARD	138
8.1.3 TEST SETUP	138
8.1.4 EUT OPERATION CONDITIONS	138
8.1.5 TEST RESULTS	139
9 . ANTENNA CONDUCTED SPURIOUS EMISSION	151
9.1 APPLIED PROCEDURES / LIMIT	151
9.1.1 TEST PROCEDURE	151
9.1.2 TEST SETUP	151
9.1.3 EUT OPERATION CONDITIONS	151
9.1.4 TEST RESULTS	152
10. ANTENNA REQUIREMENT	170
10.1 STANDARD REQUIREMENT	170
10.2 EUT ANTENNA	170
11. EUT TEST PHOTO	171

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

LP0002 : 2020			
Standard Section	Test Item	Judgment	Remark
3.3	Conducted Emission	PASS	None
4.10.1.5/3.6	Radiated Spurious Emission	PASS	None
4.10.1.2	Peak Output Power	PASS	None
4.10.1.6	Occupied Bandwidth	PASS	None
4.10.1.6	Hopping Channel Separation	PASS	None
4.10.1.6	Number of Hopping Frequency	PASS	None
4.10.1.6	Dwell Time	PASS	None
4.10.1.5/3.6	Restricted Bands	PASS	None
4.10.1.3	Antenna Requirement	PASS	None

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	1.38dB
2	Radiated Emission Test	3.17dB
3	RF power,conducted	0.16dB
4	Spurious emissions,conducted	0.21dB
5	All emissions,radiated(<1G)	4.68dB
6	All emissions,radiated(>1G)	4.89dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	TWS EARBUDS TRUE WIRELESS STEREO	
Trade Name	Jinpei	
Model Name	JE-01B	
Serial Model Name	N/A	
Model Difference	N/A	
Product Description	The EUT is aTWS EARBUDS TRUE WIRELESS STEREO	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK(1Mbps) π/4 DQPSK(2Mbps) 8QPSKA(3Mbps)
	Number Of Channel	79 CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain(Peak)	5.54dBi
	Output Power:	Left earphone: 1Mbps Mode: -2.156 dBm (Max.) 2Mbps Mode: -2.236 dBm (Max.) 3Mbps Mode: -2.180 dBm (Max.) Right earphone: 1Mbps Mode: -2.246 dBm (Max.) 2Mbps Mode: -2.218dBm (Max.) 3Mbps Mode: -2.132dBm(Max.)
Channel List	Please refer to the Note 2.	
Power Rating	DC5V from adapter or DC3.7V from battery	
Connecting I/O Port(s)	Please refer to the User's Manual	
Products Covered	N/A	
EUT Modification(s)	N/A	
Model difference	N/A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

	Trade Name	Model Name	Antenna Type	Connector	Gain (dBi)
1	GLEAD	LTA312450-P33	Ceramic antenna	N/A	5.54 dBi

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	1Mbps
Mode 2	2Mbps
Mode 3	3Mbps
Mode 4	RX
Mode 5	CHARGE

For Conducted Emission	
Final Test Mode	Description
Mode 3	CH00 /CH39 /CH78
Mode 5	CHARGE

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00 /CH39 /CH78
Mode 3	CH00 /CH39 /CH78
Mode 4	RX
Mode 5	CHARGE

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) For all tests the worst-case was selected as the table above, the data of the worst-case is shown in the report.
- (3) The highest internal source of the EUT is less than 108MHz in charging mode.

2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Power Set	10		
Test software Version	V1.0.2.2	Test program:	FCC_assist
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	Default	Default	Default
Parameters(3Mbps)	Default	Default	Default


1. Connect the EUT to the computer with "USB TO TTL";
2. Open the "FCC_assist" test software after the connection, select the Transport port and Device to connect;

3. After clicking “Open” button, the up left corner changes to green means it is successful to open BT Device , Select the parameters and click Execute.

Note: Test fixture :

Equipment		USB TO TTL	
Model Name	CP2102	Trade Name	K-mate

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED




Block diagram of EUT configuration

RADIATED EMISSION

Test mode: mode 1, 3 ,4

Non-Conductive Table


80 cm above Ground Plane



Test mode: mode 1, 3 ,4

Non-Conductive Table


150 cm above Ground Plane



Test mode: mode 5

Non-Conductive Table

80 cm above Ground Plane



2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	TWS EARBUDS TRUE WIRELESS STEREO	Jinpei	JE-01B	N/A	N/A	EUT
E-2	Adapter	NOKIA	FC0302	N/A	N/A	Test Accessory*
E-3	充電盒	Jinpei	JE-01B	N/A	N/A	EUT

Item	Equipment	Mfr/Brand	Model/Type No.	Note
1	USB Type-C Line	Jinpei	JE-01B	EUT Line length : 30cm
2	Rechargeable Li-ion Battery(耳機電池 L)	Jinpei	FL450909	EUT
3	Rechargeable Li-ion Battery(耳機電池 R)	Jinpei	FL450909	EUT
4	Rechargeable Li-ion Battery(充電盒電池)	Jinpei	PF801438	EUT

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” or “with ferrite core”; “NO” means “unshielded” or “without ferrite core”
- (4) “*”: In this report, the applicant did not provide the accompanying accessories with the equipment. The accessories were provided by the laboratory (or the applicant) and inspected simultaneously.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
Spectrum Analyzer	Keysight	N9020A	MY53300466	April 29, 2021	1 Year
RF Preselector	Hewlett Packard	85685A	3010A01157	April 29, 2021	1 Year
Quasi-Peak Adapter	Hewlett Packard	85650	2521A00584	April 29, 2021	1 Year
Preamplifier	Com Power	PA-102	1482	April 29, 2021	1 Year
RF Attenuator	Mini-Circuits	CAT-10	Asset #1000	December 08, 2020	1 Year
LISN	Com Power	LI-200	12012	September 09, 2020	1 Year
LISN	Com Power	LI-200	12214	September 09, 2020	1 Year
LISN	Com Power	LI-200	1767	September 09, 2020	1 Year
LISN	Com Power	LI-200	1768	September 09, 2020	1 Year
Biconical Antenna	Com Power	AB-100	01557	December 29, 2020	1 Year
Log Periodic Antenna	Com Power	AL-100	16037	December 22, 2020	1 Year
Horn Antenna	Com Power	AHA-118	711054	December 22, 2020	1 Year
Antenna Mast	Com Power	AM-400	N/A	N/A	N/A
Turntable	Com Power	TT-100	N/A	N/A	N/A
Computer	Dell, Inc.	DHS	DNSV641	N/A	N/A

EMI Test Equipment (Continued)

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
EMI Receiver	Rohde & Schwarz	ESU40	100127	June 12, 2021	1 Year
BiConiLog Antenna	ETS-Lindgren	3142D	00102183	August 13, 2020	1 Year
Horn Antenna (1GHz-18GHz)	ETS-Lindgren	3117	00109294	May 6, 2021	1 Year
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	May 6, 2021	1 Year
Preamplifier	Rohde & Schwarz	TS-PR18	100056	June 12, 2021	1 Year
Pre-Amplifier	Agilent	8449B	3008A00409	June 12, 2021	1 Year
Antenna Mast	ETS-Lindgren	2175	00095727	N/A	N/A
Turntable	ETS-Lindgren	2187-3.0	00118231	N/A	N/A
Computer	Acer	Aspire 8930	85100050123	N/A	N/A
Multi-Function Controller	ETS-Lindgren	2090	00102270	N/A	N/A
Loop Antenna	ARA	PLA-1030/B	1029	May 19, 2021	1 Year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5			66 - 56 *	56 - 46 *	LP0002
0.50 -5.0			56.00	46.00	LP0002
5.0 -30.0			60.00	50.00	LP0002

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP




Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 TEST RESULTS

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name. :	JE-01B
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Phase :	L
Test Voltage :	AC 110V/60Hz for Adapter		




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss + Pulse limit.
3. '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2046	5.75	9.75	15.50	53.42	-37.92	AVG	P
2	0.2084	23.98	9.75	33.73	63.27	-29.54	peak	P
3	0.2864	8.05	9.76	17.81	50.63	-32.82	AVG	P
4	0.2924	22.16	9.76	31.92	60.46	-28.54	peak	P
5	0.4190	20.53	9.76	30.29	57.47	-27.18	peak	P
6	0.4190	6.61	9.76	16.37	47.47	-31.10	AVG	P
7	0.6179	11.38	9.78	21.16	46.00	-24.84	AVG	P
8	0.6219	18.16	9.78	27.94	56.00	-28.06	peak	P
9	1.0391	12.07	9.79	21.86	56.00	-34.14	peak	P
10	1.0391	4.64	9.79	14.43	46.00	-31.57	AVG	P
11	11.8568	20.22	22.10	42.32	60.00	-17.68	peak	P
12 *	11.8880	12.41	22.13	34.54	50.00	-15.46	AVG	P

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name. :	JE-01B
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Phase :	N
Test Voltage :	AC 110V/60Hz for Adapter		




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss + Pulse limit.
3. '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1773	27.72	9.77	37.49	64.61	-27.12	peak	P
2	0.1815	7.70	9.76	17.46	54.42	-36.96	AVG	P
3	0.2280	26.58	9.75	36.33	62.52	-26.19	peak	P
4	0.2280	10.95	9.75	20.70	52.52	-31.82	AVG	P
5	0.4386	20.81	9.77	30.58	57.09	-26.51	peak	P
6	0.4386	6.40	9.77	16.17	47.09	-30.92	AVG	P
7	0.5828	20.54	9.77	30.31	56.00	-25.69	peak	P
8	0.6219	10.71	9.78	20.49	46.00	-25.51	AVG	P
9	1.7412	10.10	9.80	19.90	56.00	-36.10	peak	P
10	1.7685	2.63	9.80	12.43	46.00	-33.57	AVG	P
11	11.9465	18.38	22.20	40.58	60.00	-19.42	peak	P
12 *	11.9465	11.77	22.20	33.97	50.00	-16.03	AVG	P

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name. :	JE-01B
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2021-07-22
Test Mode :	Mode 5	Phase :	L
Test Voltage :	AC 110V/60Hz for Adapter		




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss + Pulse limit.
3. '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2061	3.27	9.75	13.02	53.36	-40.34	AVG	P
2	0.2085	23.48	9.75	33.23	63.26	-30.03	peak	P
3	0.2864	22.06	9.76	31.82	60.63	-28.81	peak	P
4	0.2864	8.05	9.76	17.81	50.63	-32.82	AVG	P
5	0.4190	19.53	9.76	29.29	57.47	-28.18	peak	P
6	0.4190	5.61	9.76	15.37	47.47	-32.10	AVG	P
7	0.6180	10.38	9.78	20.16	46.00	-25.84	AVG	P
8	0.6219	17.16	9.78	26.94	56.00	-29.06	peak	P
9	2.3379	9.45	9.81	19.26	56.00	-36.74	peak	P
10	2.3379	1.88	9.81	11.69	46.00	-34.31	AVG	P
11	11.8569	32.58	10.24	42.82	60.00	-17.18	peak	P
12 *	11.8881	24.80	10.24	35.04	50.00	-14.96	AVG	P

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name. :	JE-01B
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2021-07-22
Test Mode :	Mode 5	Phase :	N
Test Voltage :	AC 110V/60Hz for Adapter		



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss + Pulse limit.
3. '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1773	27.22	9.77	36.99	64.61	-27.62	peak	P
2	0.1850	9.43	9.76	19.19	54.26	-35.07	AVG	P
3	0.2046	8.40	9.75	18.15	53.42	-35.27	AVG	P
4	0.2084	26.30	9.75	36.05	63.27	-27.22	peak	P
5	0.2267	9.47	9.75	19.22	52.57	-33.35	AVG	P
6	0.2280	26.08	9.75	35.83	62.52	-26.69	peak	P
7	0.2903	23.95	9.76	33.71	60.52	-26.81	peak	P
8	0.2903	5.28	9.76	15.04	50.52	-35.48	AVG	P
9	0.5828	20.04	9.77	29.81	56.00	-26.19	peak	P
10	0.6219	10.21	9.78	19.99	46.00	-26.01	AVG	P
11	11.9465	17.88	22.20	40.08	60.00	-19.92	peak	P
12 *	11.9465	11.27	22.20	33.47	50.00	-16.53	AVG	P

Test result: The unit does meet the NCC requirements.

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 3.5, then the 3.6 limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	LIMITS (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to LP0002.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Frequency measurement range:

- 1, The spectrum shall be measured from the lowest radio frequency signal generated in the device (without going below 9 kHz), and the upper limit of the measurement range shall be decided according to the maximum operating frequency.
 - 1.1 Maximum operating frequency less than 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
 - 1.2 Maximum operating frequency between 10 GHz~30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
 - 1.3 Maximum operating frequency over 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower.
- 2 Particular attention should be paid to harmonics and subharmonics of the carrier frequency as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.

Spectrum Parameter		Setting	
Attenuation		Auto	
Start Frequency		1000 MHz	
Stop Frequency		10th carrier harmonic	
Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3MHz
AV	$\geq 98\%$	1MHz	10Hz
	$< 98\%$	1MHz	1/T

NOTE: KDB 558074 Zero-Span Spectrum Analyzer Method


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters (For frequencies above 1GHz, table 1.5 meters) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


3.2.5 TEST RESULTS (BLOW 30 MHZ)

There is no detected blow 30MHz

3.2.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)

Left earphone

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	36.303	19.39	-13.57	40.0	-20.61	Peak	Vertical	Pass
2	54.971	19.40	-11.77	40.0	-20.60	Peak	Vertical	Pass
3	77.276	16.06	-17.58	40.0	-23.94	Peak	Vertical	Pass
4	204.556	22.73	-13.55	43.5	-20.77	Peak	Vertical	Pass
5	426.388	24.49	-8.21	46.0	-21.51	Peak	Vertical	Pass
6	454.996	25.28	-8.01	46.0	-20.72	Peak	Vertical	Pass

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	45.031	15.98	-11.41	40.0	-24.02	Peak	Horizontal	Pass
2	101.035	13.84	-13.46	43.5	-29.66	Peak	Horizontal	Pass
3	209.890	23.48	-13.56	43.5	-20.02	Peak	Horizontal	Pass
4	240.195	27.22	-12.33	46.0	-18.78	Peak	Horizontal	Pass
5	364.081	30.82	-9.55	46.0	-15.18	Peak	Horizontal	Pass
6	458.148	29.43	-7.76	46.0	-16.57	Peak	Horizontal	Pass


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX	Polarization :	Vertical
Test Power :	DC3.7V from battery		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	36.788	19.16	-13.31	40.0	-20.84	Peak	Vertical	Pass
2	52.062	19.47	-11.43	40.0	-20.53	Peak	Vertical	Pass
3	201.890	21.41	-13.41	43.5	-22.09	Peak	Vertical	Pass
4	214.496	21.72	-13.58	43.5	-21.78	Peak	Vertical	Pass
5	236.558	21.32	-12.37	46.0	-24.68	Peak	Vertical	Pass
6	452.814	28.93	-7.86	46.0	-17.07	Peak	Vertical	Pass


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX	Polarization :	Horizontal
Test Power :	DC3.7V from battery		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	47.941	22.15	-11.30	40.0	-17.85	Peak	Horizontal	Pass
2	201.890	27.72	-13.41	43.5	-15.78	Peak	Horizontal	Pass
3	216.193	25.46	-13.57	46.0	-20.54	Peak	Horizontal	Pass
4	240.195	31.01	-12.33	46.0	-14.99	Peak	Horizontal	Pass
5	363.839	28.47	-9.57	46.0	-17.53	Peak	Horizontal	Pass
6	456.936	29.12	-7.87	46.0	-16.88	Peak	Horizontal	Pass


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	Mode 5	Polarization :	Vertical
Test Power :	DC5V from adapter		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	37.031	20.55	-13.17	40.0	-19.45	Peak	Vertical	Pass
2	51.820	21.21	-11.42	40.0	-18.79	Peak	Vertical	Pass
3	77.276	16.95	-17.58	40.0	-23.05	Peak	Vertical	Pass
4	136.916	15.19	-17.19	43.5	-28.31	Peak	Vertical	Pass
5	497.423	22.12	-7.12	46.0	-23.88	Peak	Vertical	Pass
6	746.893	25.70	-3.39	46.0	-20.30	Peak	Vertical	Pass

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	Mode 5	Polarization :	Horizontal
Test Power :	DC5V from adapter		




Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	46.243	15.42	-11.41	40.0	-24.58	Peak	Horizontal	Pass
2	104.671	14.11	-13.25	43.5	-29.39	Peak	Horizontal	Pass
3	212.072	13.88	-13.68	43.5	-29.62	Peak	Horizontal	Pass
4	401.902	18.02	-8.60	46.0	-27.98	Peak	Horizontal	Pass
5	601.672	22.36	-5.08	46.0	-23.64	Peak	Horizontal	Pass
6	897.933	24.87	-1.77	46.0	-21.13	Peak	Horizontal	Pass

Test result: The unit does meet the NCC requirements.

Right earphone

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	36.303	19.62	-13.57	40.0	-20.38	Peak	Vertical	Pass
2	55.214	18.67	-11.83	40.0	-21.33	Peak	Vertical	Pass
3	78.730	15.25	-17.47	40.0	-24.75	Peak	Vertical	Pass
4	210.617	21.52	-13.62	43.5	-21.98	Peak	Vertical	Pass
5	225.891	23.85	-12.85	46.0	-22.15	Peak	Vertical	Pass
6	450.390	26.01	-8.00	46.0	-19.99	Peak	Vertical	Pass

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	43.092	21.10	-11.50	40.0	-18.90	Peak	Horizontal	Pass
2	201.405	24.29	-13.42	43.5	-19.21	Peak	Horizontal	Pass
3	239.953	26.47	-12.33	46.0	-19.53	Peak	Horizontal	Pass
4	367.233	30.22	-9.51	46.0	-15.78	Peak	Horizontal	Pass
5	447.481	30.74	-8.07	46.0	-15.26	Peak	Horizontal	Pass
6	946.178	25.78	-1.60	46.0	-20.22	Peak	Horizontal	Pass


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX	Polarization :	Vertical
Test Power :	DC3.7V from battery		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	34.364	21.17	-14.17	40.0	-18.83	Peak	Vertical	Pass
2	54.486	18.32	-11.66	40.0	-21.68	Peak	Vertical	Pass
3	203.587	23.09	-13.48	43.5	-20.41	Peak	Vertical	Pass
4	228.315	22.20	-12.75	46.0	-23.80	Peak	Vertical	Pass
5	368.203	23.45	-9.50	46.0	-22.55	Peak	Vertical	Pass
6	461.057	26.56	-7.84	46.0	-19.44	Peak	Vertical	Pass


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX	Polarization :	Horizontal
Test Power :	DC3.7V from battery		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	204.556	26.63	-13.55	43.5	-16.87	Peak	Horizontal	Pass
2	229.528	25.93	-12.68	46.0	-20.07	Peak	Horizontal	Pass
3	241.165	26.98	-12.35	46.0	-19.02	Peak	Horizontal	Pass
4	366.748	24.62	-9.51	46.0	-21.38	Peak	Horizontal	Pass
5	458.633	31.58	-7.81	46.0	-14.42	Peak	Horizontal	Pass
6	915.631	25.91	-1.75	46.0	-20.09	Peak	Horizontal	Pass


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	Mode 5	Polarization :	Vertical
Test Power :	DC5V from adapter		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	37.273	19.08	-13.06	40.0	-20.92	Peak	Vertical	Pass
2	51.820	20.18	-11.42	40.0	-19.82	Peak	Vertical	Pass
3	78.245	17.18	-17.48	40.0	-22.82	Peak	Vertical	Pass
4	108.793	14.50	-13.50	43.5	-29.00	Peak	Vertical	Pass
5	489.908	21.03	-7.24	46.0	-24.97	Peak	Vertical	Pass
6	761.925	25.45	-3.23	46.0	-20.55	Peak	Vertical	Pass

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	Mode 5	Polarization :	Horizontal
Test Power :	DC5V from adapter		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	ANT	Verdict
1	45.516	15.48	-11.39	40.0	-24.52	Peak	Horizontal	Pass
2	105.156	13.11	-13.23	43.5	-30.39	Peak	Horizontal	Pass
3	138.128	15.90	-17.29	43.5	-27.60	Peak	Horizontal	Pass
4	147.341	15.36	-17.22	43.5	-28.14	Peak	Horizontal	Pass
5	236.073	17.84	-12.42	46.0	-28.16	Peak	Horizontal	Pass
6	790.532	24.80	-3.19	46.0	-21.20	Peak	Horizontal	Pass

Test result: The unit does meet the NCC requirements.

3.2.7 TEST RESULTS (FRENQUENCY RANGE 1000-25000 MHZ)


Left earphone

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.000	47.95	5.06	53.01	74.00	-20.99	peak
4804.000	38.69	5.06	43.75	54.00	-10.25	AVG
7206.000	43.36	7.03	50.39	74.00	-23.61	peak
7206.000	33.92	7.03	40.95	54.00	-13.05	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19655.000	39.13	16.53	55.66	74.00	-18.34	
19655.000	29.25	16.53	45.78	54.00	-8.22	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4804.000	48.91	5.06	53.97	74.00	-20.03	peak
4804.000	36.59	5.06	41.65	54.00	-12.35	AVG
7206.000	43.74	7.03	50.77	74.00	-23.23	peak
7206.000	33.37	7.03	40.40	54.00	-13.60	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19888.000	39.51	16.58	56.09	74.00	-17.91	
19888.000	28.69	16.58	45.27	54.00	-8.73	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	47.14	5.14	52.28	74.00	-21.72	peak
4882.000	38.21	5.14	43.35	54.00	-10.65	AVG
7323.000	42.84	7.54	50.38	74.00	-23.62	peak
7323.000	32.16	7.54	39.70	54.00	-14.30	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20048.000	38.57	16.61	55.18	74.00	-18.82	
20048.000	27.41	16.61	44.02	54.00	-9.98	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	48.43	5.14	53.57	74.00	-20.43	peak
4882.000	38.86	5.14	44	54.00	-10.00	AVG
7323.000	44.67	7.54	52.21	74.00	-21.79	peak
7323.000	32.15	7.54	39.69	54.00	-14.31	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19811.000	39.07	16.57	55.64	74.00	-18.36	
19811.000	28.35	16.57	44.92	54.00	-9.08	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4960.000	47.77	5.22	52.99	74.00	-21.01	peak
4960.000	38.68	5.22	43.90	54.00	-10.10	AVG
7440.000	42.75	8.06	50.81	74.00	-23.19	peak
7440.000	33.61	8.06	41.67	54.00	-12.33	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19059.000	39.77	16.42	56.19	74.00	-17.81	
19059.000	29.46	16.42	45.88	54.00	-8.12	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4960.000	48.54	5.22	53.76	74.00	-20.24	
4960.000	38.62	5.22	43.84	54.00	-10.16	AVG
7440.000	43.41	8.06	51.47	74.00	-22.53	peak
7440.000	32.98	8.06	41.04	54.00	-12.96	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
18788.000	39.01	16.20	55.21	74.00	-18.79	
18788.000	28.47	16.20	44.67	54.00	-9.33	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4804.000	47.91	5.06	52.97	74.00	-21.03	peak
4804.000	38.32	5.06	43.38	54.00	-10.62	AVG
7206.000	43.52	7.03	50.55	74.00	-23.45	peak
7206.000	33.47	7.03	40.50	54.00	-13.50	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20042.000	39.05	16.61	55.66	74.00	-18.34	
20042.000	28.99	16.61	45.60	54.00	-8.40	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4804.000	49.37	5.06	54.43	74.00	-19.57	peak
4804.000	40.74	5.06	45.8	54.00	-8.20	AVG
7206.000	45.08	7.03	52.11	74.00	-21.89	peak
7206.000	35.84	7.03	42.87	54.00	-11.13	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19418.00	39.77	16.49	56.26	74.00	-17.74	
19418.00	29.96	16.49	46.45	54.00	-7.55	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	48.99	5.14	54.13	74.00	-19.87	peak
4882.000	39.92	5.14	45.06	54.00	-8.94	AVG
7323.000	43.77	7.54	51.31	74.00	-22.69	peak
7323.000	34.71	7.54	42.25	54.00	-11.75	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20315.00	39.63	16.67	56.30	74.00	-17.70	
20315.00	28.99	16.67	45.66	54.00	-8.34	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	48.72	5.14	53.86	74.00	-20.14	peak
4882.000	38.32	5.14	43.46	54.00	-10.54	AVG
7323.000	42.66	7.54	50.20	74.00	-23.80	peak
7323.000	32.71	7.54	40.25	54.00	-13.75	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20143.00	39.52	16.63	56.15	74.00	-17.85	
20143.00	30.57	16.63	47.20	54.00	-6.80	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4960.000	49.93	5.22	55.15	74.00	-18.85	peak
4960.000	40.74	5.22	45.96	54.00	-8.04	AVG
7440.000	43.56	8.06	51.62	74.00	-22.38	peak
7440.000	34.57	8.06	42.63	54.00	-11.37	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20017.00	39.74	16.61	56.35	74.00	-17.65	
20017.00	30.72	16.61	47.33	54.00	-6.67	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4960.000	50.35	5.22	55.57	74.00	-18.43	peak
4960.000	39.98	5.22	45.2	54.00	-8.80	AVG
7440.000	43.97	8.06	52.03	74.00	-21.97	peak
7440.000	34.92	8.06	42.98	54.00	-11.02	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20223.00	39.95	16.64	56.59	74.00	-17.41	
20223.00	29.38	16.64	46.02	54.00	-7.98	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.

In frequency ranges 1~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report.


Test result: The unit does meet the NCC requirements.

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1665.514	46.69	-9.73	36.96	74.00	-37.04	peak
2958.826	43.41	-1.97	41.44	74.00	-32.56	peak
4334.023	44.13	4.4	48.53	74.00	-25.47	peak
6850.027	43.71	6.08	49.79	74.00	-24.21	peak
8000.557	42.28	10.38	52.66	74.00	-21.34	peak
17799.587	32.95	24.82	57.77	74.00	-16.23	peak
17799.587	21.84	24.82	46.66	54.00	-7.34	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1702.269	46.22	-9.62	36.60	74.00	-37.40	peak
3017.736	43.34	-1.64	41.70	74.00	-32.30	peak
3845.598	43.69	2.71	46.40	74.00	-27.60	peak
4357.023	45.99	4.45	50.44	74.00	-23.56	peak
6785.555	44.35	6.04	50.39	74.00	-23.61	peak
17960.032	32.77	24.71	57.48	74.00	-16.52	peak
17960.032	22.99	24.71	47.70	54.00	-6.30	AVG

Remark:0

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
20144.000	38.99	16.63	55.62	74.00	-18.38	peak
20144.000	28.41	16.63	45.04	54.00	-8.96	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
19387.00	39.41	16.48	55.89	74.00	-18.11	peak
19387.00	30.82	16.48	47.30	54.00	-6.70	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.

No any other emissions detected which are tested to compliance with the limit. No recording in the test report.

Test result: The unit does meet the NCC requirements.


Right earphone

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4804.000	48.66	5.06	53.72	74.00	-20.28	peak
4804.000	39.41	5.06	44.47	54.00	-9.53	AVG
7206.000	43.83	7.03	50.86	74.00	-23.14	peak
7206.000	35.37	7.03	42.40	54.00	-11.60	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20333.000	38.99	16.67	55.66	74.00	-18.34	
20333.000	30.15	16.67	46.82	54.00	-7.18	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4804.000	48.17	5.06	53.23	74.00	-20.77	peak
4804.000	37.45	5.06	42.51	54.00	-11.49	AVG
7206.000	43.56	7.03	50.59	74.00	-23.41	peak
7206.000	35.53	7.03	42.56	54.00	-11.44	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
18750.000	39.53	16.15	55.68	74.00	-18.32	peak
18750.000	30.67	16.15	46.82	54.00	-7.18	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	49.41	5.14	54.55	74.00	-19.45	peak
4882.000	37.57	5.14	42.71	54.00	-11.29	AVG
7323.000	43.62	7.54	51.16	74.00	-22.84	peak
7323.000	34.09	7.54	41.63	54.00	-12.37	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19644.000	39.31	16.53	55.84	74.00	-18.16	
19644.000	30.45	16.53	46.98	54.00	-7.02	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	47.45	5.14	52.59	74.00	-21.41	peak
4882.000	36.41	5.14	41.55	54.00	-12.45	AVG
7323.000	43.63	7.54	51.17	74.00	-22.83	peak
7323.000	33.80	7.54	41.34	54.00	-12.66	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19653.000	39.77	16.53	56.30	74.00	-17.70	
19653.000	30.61	16.53	47.14	54.00	-6.86	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4960.000	49.23	5.22	54.45	74.00	-19.55	peak
4960.000	39.89	5.22	45.11	54.00	-8.89	AVG
7440.000	45.01	8.06	53.07	74.00	-20.93	peak
7440.000	34.66	8.06	42.72	54.00	-11.28	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
18649.000	39.26	16.05	55.31	74.00	-18.69	
18649.000	30.48	16.05	46.53	54.00	-7.47	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4960.000	48.67	5.22	53.89	74.00	-20.11	peak
4960.000	39.49	5.22	44.71	54.00	-9.29	AVG
7440.000	42.25	8.06	50.31	74.00	-23.69	peak
7440.000	34.91	8.06	42.97	54.00	-11.03	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (1Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20163.000	39.73	16.63	56.36	74.00	-17.64	
20163.000	30.59	16.63	47.22	54.00	-6.78	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4804.000	48.79	5.06	53.85	74.00	-20.15	peak
4804.000	39.05	5.06	44.11	54.00	-9.89	AVG
7206.000	43.51	7.03	50.54	74.00	-23.46	peak
7206.000	35.19	7.03	42.22	54.00	-11.78	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19685.000	38.98	16.53	55.51	74.00	-18.49	
19685.000	30.27	16.53	46.80	54.00	-7.20	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.000	49.74	5.06	54.80	74.00	-19.20	peak
4804.000	40.82	5.06	45.88	54.00	-8.12	AVG
7206.000	45.16	7.03	52.19	74.00	-21.81	peak
7206.000	35.98	7.03	43.01	54.00	-10.99	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2402MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20122.000	39.55	16.63	56.18	74.00	-17.82	
20122.000	30.37	16.63	47.00	54.00	-7.00	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	49.03	5.14	54.17	74.00	-19.83	peak
4882.000	39.92	5.14	45.06	54.00	-8.94	AVG
7323.000	43.69	7.54	51.23	74.00	-22.77	peak
7323.000	34.58	7.54	42.12	54.00	-11.88	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20025.000	38.77	16.61	55.38	74.00	-18.62	
20025.000	29.91	16.61	46.52	54.00	-7.48	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.000	48.47	5.14	53.61	74.00	-20.39	peak
4882.000	38.15	5.14	43.29	54.00	-10.71	AVG
7323.000	42.39	7.54	49.93	74.00	-24.07	peak
7323.000	34.27	7.54	41.81	54.00	-12.19	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2441MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20035.000	39.49	16.61	56.10	74.00	-17.90	
20035.000	29.92	16.61	46.53	54.00	-7.47	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4960.000	47.72	5.22	52.94	74.00	-21.06	peak
4960.000	38.44	5.22	43.66	54.00	-10.34	AVG
7440.000	42.93	8.06	50.99	74.00	-23.01	peak
7440.000	35.19	8.06	43.25	54.00	-10.75	AVG

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Horizontal
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
18898.000	39.33	16.31	55.64	74.00	-18.36	
18898.000	30.19	16.31	46.50	54.00	-7.50	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4960.000	47.27	5.22	52.49	74.00	-21.51	peak
4960.000	38.19	5.22	43.41	54.00	-10.59	AVG
7440.000	42.71	8.06	50.77	74.00	-23.23	peak
7440.000	34.63	8.06	42.69	54.00	-11.31	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	TX 2480MHz (3Mbps-worst case)	Polarization :	Vertical
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
20156.000	39.35	16.63	55.98	74.00	-18.02	
20156.000	30.74	16.63	47.37	54.00	-6.63	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.


In frequency ranges 1~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report.

Test result: The unit does meet the NCC requirements.

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1985.211	46.37	-9.15	37.22	74.00	-36.78	peak
3000.002	43.34	-1.68	41.66	74.00	-32.34	peak
4344.478	44.31	4.42	48.73	74.00	-25.27	peak
6876.514	43.42	6.1	49.52	74.00	-24.48	peak
8010.035	42.45	10.4	52.85	74.00	-21.15	peak
17881.123	33.27	24.76	58.03	74.00	-15.97	peak
17881.123	23.19	24.76	47.95	54.00	-6.05	AVG


Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1777.333	46.42	-9.4	37.02	74.00	-36.98	peak
3016.259	43.59	-1.65	41.94	74.00	-32.06	peak
3900.320	43.61	3.11	46.72	74.00	-27.28	peak
4365.247	46.27	4.46	50.73	74.00	-23.27	peak
6800.147	44.39	6.05	50.44	74.00	-23.56	peak
17884.658	33.17	24.76	57.93	74.00	-16.07	peak
17884.658	23.66	24.76	48.42	54.00	-5.58	AVG


Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC3.7V from battery		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
19425.000	39.42	16.49	55.91	74.00	-18.09	peak
19425.000	28.88	16.49	45.37	54.00	-8.63	AVG


Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2021-07-22
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC3.7V from battery		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19897.000	39.62	16.58	56.20	74.00	-17.80	peak
19897.000	29.91	16.58	46.49	54.00	-7.51	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.

No any other emissions detected which are tested to compliance with the limit. No recording in the test report.

Test result: The unit does meet the NCC requirements.

3.2.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	TX 2402MHz/2480MHz (1Mbps)		
Test Date :	2021-07-22		
Note :	1. The transmitter was setup to transmit at the lowest channel (CH00). Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel (CH78). Then the field strength was measured at 2483.5-2500 MHz. 3. The data of 2390MHz and 2483.5MHz was the worst.		


Left earphone

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant/CF CF(dB)	Act		Limit		Note
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)	
2390.00	H	42.16	--	-5.79	36.37	--	74.00	54.00	CH00
2390.00	V	42.40	--	-5.79	36.61	--	74.00	54.00	CH00
2483.50	H	43.02	--	-4.98	38.04	--	74.00	54.00	CH78
2483.50	V	41.83	--	-4.98	36.85	--	74.00	54.00	CH78


Remark :

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode
- (2) EUT Orthogonal Axis :
 "X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (3) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (4) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.


Horizontal




Vertical



Horizontal



Vertical




Right earphone

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant/CF CF(dB)	Act		Limit		Note
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)	
2390.00	H	41.96	--	-5.79	36.17	--	74.00	54.00	CH00
2390.00	V	41.84	--	-5.79	36.05	--	74.00	54.00	CH00
2483.50	H	41.45	--	-4.98	36.47	--	74.00	54.00	CH78
2483.50	V	41.69	--	-4.98	36.71	--	74.00	54.00	CH78


Remark :

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode
- (2) EUT Orthogonal Axis :
“X” - denotes Laid on Table ; ”Y” - denotes Vertical Stand ; ”Z” - denotes Side Stand
- (3) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (4) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.


Horizontal




Vertical



Horizontal



Vertical



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	24°C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	TX 2402MHz/2480MHz (3Mbps)		
Test Date :	2021-07-22		
Note :	1. The transmitter was setup to transmit at the lowest channel (CH00). Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel (CH78). Then the field strength was measured at 2483.5-2500 MHz. 3. The data of 2390MHz and 2483.5MHz was the worst.		


Left earphone

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant/CF CF(dB)	Act		Limit		Note
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)	
2390.00	H	43.05	--	-5.79	37.26	--	74.00	54.00	CH00
2390.00	V	42.29	--	-5.79	36.50	--	74.00	54.00	CH00
2483.50	H	41.55	--	-4.98	36.57	--	74.00	54.00	CH78
2483.50	V	41.84	--	-4.98	36.86	--	74.00	54.00	CH78


Remark :

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode
- (2) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (3) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (4) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.


Horizontal




Vertical



Horizontal



Vertical




Right earphone

Freq. (MHz)	Ant.Pol. H/V	Reading		Ant/CF CF(dB)	Act		Limit		Note
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)	
2390.00	H	42.45	--	-5.79	36.66	--	74.00	54.00	CH00
2390.00	V	42.16	--	-5.79	36.37	--	74.00	54.00	CH00
2483.50	H	41.35	--	-4.98	36.37	--	74.00	54.00	CH78
2483.50	V	41.06	--	-4.98	36.08	--	74.00	54.00	CH78


Remark :

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode
- (2) EUT Orthogonal Axis :
“X” - denotes Laid on Table ; ”Y” - denotes Vertical Stand ; ”Z” - denotes Side Stand
- (3) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (4) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.


Horizontal




Vertical



Horizontal



Vertical



Test result: The unit does meet the NCC requirements.

4. OCCUPIED BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
4.10.1(6.1.1)	Bandwidth	N/A	2402-2480	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	wide enough to capture the peaks of two adjacent channels.
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep time = Auto, Span=3MHz.

4.1.2 TEST SETUP



4.1.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.4 TEST RESULTS

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		
Test Date :	2021-07-13		

Left earphone:

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	875.2	Pass
2441 MHz	876.4	Pass
2480 MHz	875.0	Pass

Right earphone:

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	874.8	Pass
2441 MHz	879.5	Pass
2480 MHz	871.2	Pass

Left earphone:

CH 00-1Mbps



CH 39-1Mbps




CH 78-1Mbps




Right earphone:

CH00-1Mbps



CH 39-1Mbps



CH 78-1Mbps



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		
Test Date :	2021-07-13		

Left earphone:


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.211	Pass
2441 MHz	1.210	Pass
2480 MHz	1.211	Pass

Right earphone:


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.208	Pass
2441 MHz	1.208	Pass
2480 MHz	1.209	Pass

Left earphone:


CH 00-3Mbps



CH 39-3Mbps




CH 78-3Mbps




Right earphone:


CH 00-3Mbps



CH 39-3Mbps



CH 78-3Mbps



5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

LP0002			
Section	Test Item	Frequency Range (MHz)	Result
4.10.1(6.1.1)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	the frequency band of operation
RB	300kHz
VB	1 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 300kHz, VBW=1 MHz, Sweep time = Auto.

5.1.2 TEST SETUP



5.1.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.4 TEST RESULTS


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	Hopping Mode –1Mbps mode		
Test Date :	2021-07-14		

Number of Hopping Channel	79
---------------------------	----

Left earphone:



Right earphone:




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	Hopping Mode –3Mbps mode		
Test Date :	2021-07-14		

Number of Hopping Channel	79
---------------------------	----

Left earphone:



Right earphone:



6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
4.10.1(6.1.2)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds.
- DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
- DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.

6.1.2 TEST SETUP



6.1.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.4 TEST RESULTS

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00-DH1/DH3/DH5 (1Mbps Mode)		
Test Date :	2021-07-14		

Left earphone:

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2402 MHz	0.369	0.118	0.4000
DH3	2402 MHz	1.610	0.258	0.4000
DH5	2402 MHz	2.865	0.306	0.4000

Data Packet	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	10log(1/x)Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
DH5	2.865	3.750	0.764	76.40%	1.169	0.349


Right earphone:

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2402 MHz	0.370	0.118	0.4000
DH3	2402 MHz	1.605	0.257	0.4000
DH5	2402 MHz	2.865	0.306	0.4000


Data Packet	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	10log(1/x)Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
DH5	2.865	3.750	0.764	76.40%	1.169	0.349

Left earphone:


CH 00- DH1



CH 00- DH3




CH 00- DH5




Right earphone:


CH 00- DH1



CH 00- DH3



CH 00- DH5



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00-DH1/DH3/DH5 (3Mbps Mode)		
Test Date :	2021-07-14		

Left earphone:

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2402 MHz	0.377	0.121	0.4000
DH3	2402 MHz	1.615	0.258	0.4000
DH5	2402 MHz	2.865	0.306	0.4000

Data Packet	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	10log(1/x)Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
DH5	2.865	3.740	0.766	76.60%	1.158	0.349


Right earphone:

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2402 MHz	0.376	0.120	0.4000
DH3	2402 MHz	1.605	0.257	0.4000
DH5	2402 MHz	2.875	0.307	0.4000


Data Packet	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	10log(1/x)Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
DH5	2.875	3.750	0.767	76.67%	1.154	0.348

Left earphone:

CH 00- DH1



CH 00- DH3



Agilent Spectrum Analyzer - Swept SA

Marker 2 Δ 3.74000 ms

PNO: Fast → Trg: Free Run Avg Type: Log-Pwr
IFGain: Low Atten: 24 dB AvgHold: 1/1

Ref Offset 6.5 dB Ref 20.00 dBm

ΔMkr2 3.740 ms
-0.003 dB

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	t		5.745 ms	-4.063 dBm		
2	Δ3	1	t	(Δ)	3.740 ms (Δ)	-0.003 dB		
3	F	1	t		2.880 ms	-2.802 dBm		

Right earphone:

Agilent Spectrum Analyzer - Swept SA

Marker 1 Δ 376.0 μ s

Ref Offset 6.5 dB
Ref 20.00 dBm

10 dB/div
Log


Center 2.402000000 GHz
Res BW 1.0 MHz
#VBW 1.0 MHz

Sweep 1.000 ms (1001 pts)


Span 0 Hz

1 of 2

CH 00- DH3



CH 00- DH5



7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT


Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	300 kHz
VB	1MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 300 kHz and the video bandwidth of 1MHz were utilised for channel separation measurement.

7.1.2 TEST SETUP



7.1.3 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.1.4 TEST RESULTS

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		
Test Date :	2021-07-13/14		

Left earphone:

Frequency	Ch. Separation (KHz)	Limit 2/3(20dB bandwidth) (kHz)	Result
2402 MHz	993.0	583.5	PASS
2441 MHz	993.0	584.3	PASS
2480 MHz	999.0	583.3	PASS


Right earphone:

Frequency	Ch. Separation (KHz)	Limit 2/3(20dB bandwidth) (kHz)	Result
2402 MHz	1002.0	583.2	PASS
2441 MHz	996.0	586.3	PASS
2480 MHz	999.0	580.8	PASS


Ch. Separation >2/3(20dB bandwidth)

Left earphone:


CH 00-1Mbps



CH 39-1Mbps




CH 78-1Mbps




Right earphone:


CH 00-1Mbps



CH 39-1Mbps



CH 78-1Mbps



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		
Test Date :	2021-07-13/14		

Left earphone:

Frequency	Ch. Separation (KHz)	Limit 2/3(20dB bandwidth) (KHz)	Result
2402 MHz	999.0	807.3	PASS
2441 MHz	993.0	806.7	PASS
2480 MHz	1002.0	807.3	PASS


Right earphone:

Frequency	Ch. Separation (KHz)	Limit 2/3(20dB bandwidth) (KHz)	Result
2402 MHz	999.0	805.3	PASS
2441 MHz	999.0	805.3	PASS
2480 MHz	1002.0	806.0	PASS


Ch. Separation >2/3(20dB bandwidth)

Left earphone:


CH 00-3Mbps



CH 39-3Mbps




CH 78-3Mbps




Right earphone:


CH 00-3Mbps



CH 39-3Mbps



CH 78-3Mbps



8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
4.10.1(2)	Peak Output Power	0.125 watt or 21dBm	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW=1.5MHz, VBW= 1.5MHz, Span= Approximately five times the 20 dB bandwidth , Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP




8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


8.1.5 TEST RESULTS

EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00/ CH39 /CH78 (1Mbps Mode)- Left earphone		
Test Date :	2021-07-13		


Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
2402	-2.378	21	0.125
2441	-2.249	21	0.125
2480	-2.156	21	0.125



CH39 -1Mbps




CH78 -1Mbps




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00/ CH39 /CH78 (2Mbps Mode) - Left earphone		
Test Date :	2021-07-13		


Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
2402	-2.454	21	0.125
2441	-2.319	21	0.125
2480	-2.236	21	0.125



CH39 -2Mbps




CH78 -2Mbps




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00/ CH39 /CH78 (3Mbps Mode)- Left earphone		
Test Date :	2021-07-13		


Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
2402	-2.488	21	0.125
2441	-2.323	21	0.125
2480	-2.180	21	0.125



CH39 -3Mbps




CH78 -3Mbps




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00/ CH39 /CH78 (1Mbps Mode)- Right earphone		
Test Date :	2021-07-13		


Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
2402	-2.357	21	0.125
2441	-2.315	21	0.125
2480	-2.246	21	0.125



CH39 -1Mbps




CH78 -1Mbps




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00/ CH39 /CH78 (2Mbps Mode)- Right earphone		
Test Date :	2021-07-13		


Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
2402	-2.493	21	0.125
2441	-2.332	21	0.125
2480	-2.218	21	0.125



CH39 -2Mbps




CH78 -2Mbps




EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00/ CH39 /CH78 (3Mbps Mode)- Right earphone		
Test Date :	2021-07-13		


Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
2402	-2.403	21	0.125
2441	-2.314	21	0.125
2480	-2.132	21	0.125



CH39 -3Mbps



CH78 -3Mbps



9. ANTENNA CONDUCTED SPURIOUS EMISSION

9.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in Section 3.6.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

9.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

9.1.2 TEST SETUP



9.1.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.1.4 TEST RESULTS


EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00 / CH78 (1Mbps)		
Test Date :	2021-07-14		

in any 100kHz bandwidth outside the low frequency band	in any 300 kHz bandwidth outside the high frequency band
Pass	Pass
Result	
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 300kHz bandwidth within the band that contains the highest level of the desired power.	


Remark :

- (1) Hopping enabled and disabled have evaluated, and the worst data was reported


CH00 (Lower) Data rate 1Mbps




CH 78 (Upper) Data rate 1Mbps




CH00 (Lower) Data rate 1Mbps




CH01



CH39




CH78




Right earphone:


CH00 (Lower) Data rate 1Mbps




CH78 (High) Data rate 1Mbps




Data rate 1Mbps




CH01



CH39



CH78



EUT :	TWS EARBUDS TRUE WIRELESS STEREO	Model Name :	JE-01B
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC3.7V from battery
Test Mode :	CH00 / CH78 (3Mbps)		
Test Date :	2021-07-14		


in any 100kHz bandwidth outside the low frequency band	in any 100 kHz bandwidth outside the high frequency band
Pass	Pass
Result	
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.	

Remark :


- (1) Hopping enabled and disabled have evaluated, and the worst data was reported

Left earphone:


CH00 (Lower) Data rate 3Mbps




CH 78 (Upper) Data rate 3Mbps




CH00 (Lower) Data rate 3Mbps




CH01



CH39




CH78




Right earphone:


CH00 (Lower) Data rate 3Mbps




CH 78 (Upper) Data rate 3Mbps




Data rate 3Mbps




CH01



CH39



CH78




10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

4.10.3.1.1 requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

10.2 EUT ANTENNA


The antenna is a Ceramic antenna and no consideration of replacement. Antenna max gain is 5.54dBi from 2.4GHz to 2.5GHz.

11. EUT TEST PHOTO**Radiated Measurement Photos
30MHz-1GHz**

Radiated Measurement Photos Above 1GHz



Conducted Measurement Photos



****End of the report****