



Supplier Assessment



Lcc International Co., Ltd.

Add: Floor 12th, Block A, Oriental Times Square, Huaqiang North Road, Futian District, Shenzhen, Guangdong, China

Tel: 86-755-83241215 / FAX: 86-755-61592869

www.lccetek.com / www.lccinternational.com.cn

MODEL:LT309	Detailed description	SIZE& PACK
	ID card design GPS+GSM+GPRS wireless network GSM 850 / 1900 or 900 / 1800 MHz Dual-band GPS / AGPS / LBS multiple locating mode High sensitive GPS chipset 2.4GHz RFID Attendance function SOS Emergency Alarm Class anti-disturb function Colorful customized name label Built-in 600 mAh battery Voice monitor function Low battery alarm Package content: GPS tracker * 1 USB Cable * 1 Battery * 1 Lanyard * 1 Pin * 1 Screwdriver * 1 Power Adapter * 1 User Manual- English * 1 Certificates: CE FCC ROSH(Optional)	Packing details: Gift Box Size: 120x100x56(mm) Weight: 167.5g 20pcs/CTN CTN measurement: 30x27x22(cm) GW 4kg/ctn

NOTE:

1. EXW.
2. Validity: This quotation sheet is valid for 7days due to the unstable RMB exchange rate.
3. Product warranty for one year.
4. Shipment time: 3-7 days after receiving the 30% deposit.
5. 30% T/T in advance, balance before shipment or 100% Western Union/Paypal.
6. Delivery time : 2-5days to quantity under 500pcs, 10-12days to Quantity 500pcs or more.
7. OEM term: OEM for customer(Logo and Packing) based MOQ 500PCS.



Supplier Assessment



Lcc International Co., Ltd.

Add: Floor 12th, Block A, Oriental Times Square, Huaqiang North Road, Futian District, Shenzhen, Guangdong, China

Tel: 86-755-83241215 / FAX: 86-755-61592869

www.lccetek.com / www.lccinternational.com.cn

LT309 SPECIFICATION	
DIM.	98.0 (L) × 55.0 (W) × 7.8 (H) (mm)
Weight	49g
Network	GSM/GPRS
Band	850/900/1800/1900Mhz
Internal Capacity	128MB
GPS Module	SIRF/MTK MT3336
GPS sensitivity	-159dBm
Acquisition sensitivity	-144dBm
GPS Accuracy	5-10m
GSM Accuracy	300m
GPS Start Time	Cold status 35s Warm status 15s Hot status 2s
GPS Channels	22
Backup battery	Chargeable 3.7V 600mAh Li-ion battery
Standby time	120 hours
Call time	4 hours
Operation Tem.	-20°C to +60°C
Humidity	5%--95% non-condensing
Online system	Web based online tracking platform: 309.gpsyeah.com (demo account: 867597010011440, password: 123456.)