

For BC660K&BC950K Development and Application Process in Power-off and PSM Mode

— 潘先强(Herbert Pan) —



CONTENTS

一、 Foreword	3
二、 Illustration.....	3
三、 Reference for Process of Developing Application.....	4
3.1 BC660K/BC950K	4
3.1.1 Access to CHN Telecom CTWING Platform(AEP)	4
3.1.2 Access to Leshan Platform	14
3.1.3 TCP Application	25
3.1.4 UDP Application.....	36
3.1.5 MQTT-based AWS IoT Application	46
3.1.6 MQTT-based Alibaba Cloud Application	60
3.1.7 HTTP(s) Application	72

一、Foreword

Currently, the NB-IoT modules of Quectel are applied in wide industries, which involve multi-form and multi-style IoT applications. However, due to sensitiveness in power consumption, it is necessary to take life duration of product and battery endurance into consideration in stage of application design. Based on common "power off" and "PSM" and targeted to the NB-IoT terminal application design, relevant design procedure is sorted out and arranged in this document for reference on development design and application.

二、Illustration

1. Related design procedure and utilization illustrated in this document is just for reference on application development. For actual application, please query and refer to corresponding AT document and manual.
2. The document will sort out based on common "Power off" and "PSM" application scenario, which will focus on main procedure design. For some solution on "interrupt", please integrate with actual business. Meanwhile, please note the deployment of PSM shall be merged with power off.
3. The "blue" mark in the document represents the relevant AT commands to be executed. Some important URC and AT response outputs are marked with "red"; At the same time pay attention to check the "notes";
4. The document contains multiple application protocols, which are marked with corresponding rule identifiers. The details are as follows:

Application Protocol	CODE	INDEX	Description
LWM2M	L	L-x-y-z	x- the first digit indicates the corresponding application function y- the second digit indicates the debugging order of the corresponding function z- the third digit represents the implementation methods of different functions of the corresponding application protocol, for example, -1, -2, and -3 respectively represent three different implementation methods. The actual required method should be combined with the program processing and task invocation of mcu
TCP	T	T-x-y-z	
UDP	U	U-x-y-z	
MQTT	Q	Q-x-y-z	
HTTP	H	H-x-y-z	
RAI	R	R-x-y-z	

三、Reference for Process of Developing Application

3.1 BC660K/BC950K

3.1.1 Access to CHN Telecom CTWING Platform(AEP)

3.1.1.1 in Power-off Mode

Application	The terminal is connected to AEP platform of CHN Telecom, the interval of data reported/upload is relatively long, the application logic of mcu or program is relatively simple, and the PSM is not enabled
--------------------	---

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 5-1, skip the command >> OK >> AT+QSCCLK=0 //Disable the deepsleep >> OK	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design

	>> AT+CPSMS=0 //Disable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK	
2-2	// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries	If the application design does not require this step, you can skip the step
2-5	>> AT+CSCON=1 >> OK	If the application design does not require this step, you can skip the step
2-6	>> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK	If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK	

3- Access the AEP platform

— Herbert Pan —

	<pre>>> +QLWADDOBJ: 0 >> AT+QLWREG //Initiate registration >> >> OK >> >> +QLWURC: "registering",102,0 >> >> +QLWREG: 0 >> >> +QLWURC: "observe",7191,0,19,0,0</pre>	
L3-2	<pre>>> AT+QLWOBSRSP=7191,1,19,0,0,2,11,"68656c6c6f20776f726c64",0 //Response observe resource >> >> OK >> >> +QLWOBSRSP: 0</pre>	
L3-3	<pre>>> AT+QLWSTATUS? //Query the status of the current connection >> >> +QLWSTATUS: 2 //registered >> >> OK</pre>	The program or mcu can query the registration status of the platform by AT+QLWSTATUS. After the query returns +QLWSTATUS: 2, then the data can be sent normally
L3-4	<pre>//Report/send data to AEP platform >> AT+QLWNOTIFY=19,0,0,2,11,"68656c6c6f20776f726c64",0,1 //It is recommended to report data of the CON type >> >> OK >> >> +QLWNOTIFY: 0 >> >> +QLWURC: "report",60516 >> >> +QLWURC: "report_ack",0,60516 //the data is successfully reported and the ACK message is received from the platform.</pre>	CON type is recommended for reporting or sending data. When "report_ack" is received, the data is successfully sent
L3-5	<pre>//Set the receiving data mode - Direct Output mode (default) >> >> +QLWURC: "write",40832,19,1,0,2,9,"636f64706c65746564",0 >> AT+QLWWRRSP=40832,2 //After receiving the data, respond platform >> >> OK >> >> +QLWWRRSP: 0</pre>	Currently, the BC660K/BC950K supports only direct output mode
L3-6	<pre>>> AT+QLWDEREG //Initiate de-registration >> >> OK >> >> +QLWDEREG: 0 // de-registered</pre>	If the application design does not require this step, you can skip the step
4- Power off after sending and receiving data		
4-1	<pre>>> AT+CFUN=0 //Set minimum function >> OK</pre>	If the terminal is designed for power-off mode and powered off

	//Wait for the return OK, then mcu control to power off; If not return OK after running AT+CFUN=0 for a long period of time (for example, 20s), you can power off directly.	after data interaction is complete, you need to run AT+CFUN=0, then power off the terminal after return OK to avoid damage to the flash
5- Erase the historical frequency		
5-1	//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 /*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
6- Exception handling or interruption		
6-1	1) The program or mcu needs to add the interrupt method of time-out or failure to register the AEP platform, such as re-registration or reboot. 2) The program or mcu needs to add the interrupt method of timeout or failure for sending or receiving data, such as reboot. 3) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout

3.1.1.2 in PSM Mode

Application	PSM function is enabled, and only the AEP platform of CHN telecom is connected. The data is reported/upload frequently, and the application logic of mcu or program is relatively complex
--------------------	---

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network

	<pre>>> AT+QSClk=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK</pre>	requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	<pre>//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 7-1, skip the command >> OK >> AT+QSClk=0 //Disable the deepsleep >> OK >> AT+CPSMS=1,,,"01000010","00000000" //Enable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK >> AT+QNBIOEVENT=1,1 //Enable the URC of PSM >> OK >> AT+QCFG="dsevent",1 //Enable the URC of Deepsleep >> OK</pre>	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design By AT+CPSMS=1,, "<T3412/TAU>","<T3324> ", you can configure the T3412 and T3324 timers properly which you need.at the same time, after the completion of the registration network, by AT+CEREG=5; +CEREG? You need to query the real value of T3324,T3412/TAU provided by the network
2-2	<pre>// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK</pre>	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	<pre>>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK</pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	<pre>//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK</pre>	If the application design does not require this step, you can skip the step

		//Other queries	
2-5	>> AT+CSCON=1 >> OK		If the application design does not require this step, you can skip the step
2-6	>> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK		If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals		
2-8	>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK	>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK		
2-11	>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain

		RSRP and SNR
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>	Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times
3- Access the AEP platform		
L3-1	<pre>//Set parameters and register AEP >> AT+QLWCFG="auto_reg",0 //Disable the auto_registration function >> >> OK >> AT+QLWCONFIG=0,"221.229.214.202",5683,"868543060025186",86400,3 //Set connection parameters of AEP platform >> >> OK >> AT+QLWADDOBJ=19,0,1,0 //Add object19 and resource for upload channel >> >> OK >> >> +QLWADDOBJ: 0 >> AT+QLWADDOBJ=19,1,1,0 //Add object19 and resource for download channel >> >> OK >> >> +QLWADDOBJ: 0 >> AT+QLWREG //Initiate registration >> >> OK >> >> +QLWURC: "registering",102,0 >> >> +QLWREG: 0 >> >> +QLWURC: "observe",7191,0,19,0,0</pre>	The program or MCU needs to monitor the URC output of the registration status of the platform, and should reboot if the waiting window time of the program is exceeded
L3-2	<pre>>> AT+QLWOBSRSP=7191,1,19,0,0,2,11,"68656c6c6f20776f726c64",0 //Response observe resource >> >> OK >> >> +QLWOBSRSP: 0</pre>	
L3-3	<pre>>> AT+QLWSTATUS? //Query the status of the current connection >> >> +QLWSTATUS: 2 //registered >> >> OK</pre>	The program or mcu can query the registration status of the platform by AT+QLWSTATUS. After the query returns +QLWSTATUS: 2,then the data can be sent normally
L3-4	<pre>//Report/send data to AEP platform >> AT+QLWNOTIFY=19,0,0,2,11,"68656c6c6f20776f726c64",0,1</pre>	CON type is recommended for reporting or sending data.

	<pre>//It is recommended to report data of the CON type >> >> OK >> >> +QLWNOTIFY: 0 >> >> +QLWURC: "report",60516 >> >> +QLWURC: "report_ack",0,60516 //the data is successfully reported and the ACK message is received from the platform.</pre>	When "report_ack" is received, the data is successfully sent
L3-5	<pre>//Set the receiving data mode - Direct Output mode (default) >> >> +QLWURC: "write",40832,19,1,0,2,9,"636f6d706c65746564",0 >> AT+QLWWRRSP=40832,2 //After receiving the data, respond platform >> >> OK >> >> +QLWWRRSP: 0</pre>	Currently, the BC660K/BC950K supports only direct output mode
4- Feature of RAI		
Feature of RAI	1) After the data interaction is completed, you can run AT+QPING=0,"221.229.214.202",4,1,32,1	
R4-1	<pre>>> AT+QPING=0,"221.229.214.202",4,1,32,1 //QPING method with RAI Flag >> OK >> >> +QPING: 0,221.229.214.202,32,342,44 >> >> +QPING: 0,1,1,0,342,342,342 >> >> +CSCON:0 //If +CSCON:0 is returned within 0-2s, RAI is effective >> AT+QSCLK=1 //Enable deepsleep mode >> OK</pre>	RAI implementation method
5- Enter status PSM and Deepsleep		
5-1	<pre>>> >> +QNBIOEVENT: "ENTER PSM" //Enter the PSM state >> >> +QNBIOEVENT: "ENTER DEEPSLEEP" //Enter the deepsleep state</pre>	
6- Exit status of Deepsleep and PSM		
L6-1-1	<pre>//BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QLWRECOVER //Trigger to recovery of the Lwm2m protocol >> >> OK >> >> +QLWURC: "recovered",0,102,0 >> AT+QLWNOTIFY=19,0,0,2,11,"68656c6c6f20776f726c64",0,1 //Send data of the CON type >></pre>	Method to trigger PSM wake-up

	<pre> >> OK >> >> +QLWNOTIFY: 0 >> >> +QNBIOTEVENT: "EXIT PSM" //Exit the PSM state >> >> +QLWURC: "report",26457 >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QLWURC: "report_ack",0,26457 //the data is successfully reported and the ACK message is received from the platform Go to 6-2,or goto L3-3 for sending data,or goto L3-5 for receiving data, and the subsequent process </pre>	
L6-1-2	<pre> //If you want to obtain the accurate signal reference in the current scene immediately after the PSM is woked up, please refer to //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOTEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QPING=0,"221.229.214.202",4,1 //Trigger to exit PSM by PING >> OK >> >> +QNBIOTEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //It is recommended to obtain the signal reference after return the +CSCON:1 >> >> +QPING: 0,221.229.214.202,32,762,44 >> >> +QPING: 0,1,1,0,762,762,762 >> AT+QENG=0 //Query signal reference >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK >> AT+QLWRECOVER //Trigger to recovery of the Lwm2m protocol >> >> OK >> >> +QLWURC: "recovered",0,102,0 >> AT+QLWNOTIFY=19,0,0,2,11,"68656c6c6f20776f726c64",0,1 //Send data of the CON type >> >> OK >> >> +QLWNOTIFY: 0 >> >> +QLWURC: "report",8824 >> >> +QLWURC: "report_ack",0,8824 </pre>	If the program or mcu needs to deal with other tasks, such as collecting the base station cell signal after wake-up; It is recommended to refer to this method to trigger PSM wake-up and obtain the network signal after wake-up. If no such requirement in the program, ignore the process

	//the data is successfully reported and the ACK message is received from the platform Go to 6-2,or goto L3-3 for sending data,or goto L3-5 for receiving data, and the subsequent process	
6-2	//Manual TAU update >> AT+CPSMS=0 >> OK >> AT+CPSMS=1,,,"01000010","00000000" >> OK Go to L3-3 for sending data,or goto L3-5 for receiving data, and the subsequent process	TAU update manually can avoid automatic update of TAU cycle over time, so,non-service power consumption can be reduced; If no requirement in the application, ignore this step
7- Erase the historical frequency		
7-1	//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 //*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
8- Exception handling or interruption		
8-1	1) The program or mcu shall add the interrupt method of timeout or failure of AEP platform registration, such as re-registration or reboot; 2) The program or mcu shall add the interrupt method of sending or receiving data timeout or failure, such as reboot; 3) The program or mcu should add interrupt methods that cannot enter PSM normally or cannot wake up PSM, such as reboot; 4) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout. If unable to enter PSM or wake up from PSM, it is recommended to compare the normal time to enter PSM or exit PSM. If the time exceeds, power off or reboot should can be operated

3.1.2 Access to Leshan Platform

3.1.2.1 in Power-off Mode

Application	The terminal is connected to Leshan platform, the interval of data reported/upload is relatively long, the application logic of mcu or program is relatively simple, and the PSM is not enabled
--------------------	---

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+Qrst=1 //Reboot >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 5-1, skip the command >> OK >> AT+QSCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=0 //Disable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design
2-2	// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	//Query the attribute values of the module	If the application design does not

	<pre> >> AT //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries </pre>		require this step, you can skip the step
2-5	<pre> >> AT+CSCON=1 >> OK </pre>		If the application design does not require this step, you can skip the step
2-6	<pre> >> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK </pre>		If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	<pre> // Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals </pre>		
2-8	<pre> >> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK </pre>		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	<pre> >> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK </pre>	<pre> >> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK </pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre> >> AT+CGPADDR //Query the IP address obtained </pre>		

	<pre>>> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK</pre>	
2-11	<pre>>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK</pre>	CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>	Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times
3- Access the leshan platform		
L3-1	<pre>//Set parameters and register leshan >> AT+QSClk=0 //Disable the deepsleep function >> >> OK >> AT+QIDNSCFG=0,"8.8.8.8","223.6.6.6" //Configure the valid DNS >> OK >> AT+QLWCFG="auto_reg",0 //Disable the auto_registration function >> >> OK >> AT+QLWCONFIG=0,"leshan.eclipseprojects.io",5683,"urn:imei:866207055068526",86400,3 //Set connection parameters of leshan platform >> >> OK >> AT+QLWADDOBJ=3311,0,3,5706,5701,5850 //Add object3311 and resources >> >> OK >> >> +QLWADDOBJ: 0 >> AT+QLWREG //Initiate registration >> >> OK >> >> +QLWURC: "registering",102,0 >> >> +QLWREG: 0</pre>	The program or MCU needs to monitor the URC output of the registration status of the platform, and should reboot if the waiting window time of the program is exceeded
L3-2	<pre>>> AT+QLWSTATUS? //Query the status of the current connection >> >> +QLWSTATUS: 2 //registered >> >> OK</pre>	The program or mcu can query the registration status of the platform by AT+QLWSTATUS. After the query returns +QLWSTATUS: 2,then the data can be sent normally
L3-3	<pre>>> >> +QLWURC: "observe",43605,0,3311,0,5706 >> AT+QLWOBSRSP=43605,1,3311,0,5706,1,5,"white",0</pre>	

	<pre>//Response observe resource >> >> OK >> >> +QLWOBSRSP: 0</pre>	
L3-4	<pre>//Report/send data to leshan platform >> AT+QLWNOTIFY=3311,0,5706,1,6,"orange",0,1 //It is recommended to report data of the CON type >> >> OK >> >> +QLWNOTIFY: 0 >> >> +QLWURC: "report",60516 >> >> +QLWURC: "report_ack",0,60516 //the data is successfully reported and the ACK message is received from the platform.</pre>	CON type is recommended for reporting or sending data. When "report_ack" is received, the data is successfully sent
L3-5	<pre>//Set the receiving data mode - Direct Output mode (default) >> >> +QLWURC: "write",38156,3311,0,5706,2,4,"626c7565",0 >> AT+QLWWRRSP=38156,2 //After receiving the data, respond platform >> >> OK >> >> +QLWWRRSP: 0</pre>	Currently, the BC660K/BC950K supports only direct output mode
L3-6	<pre>>>AT+QLWDELOBJ=3311 //Delete the subscribed object >> >>OK >> >>+QLWDELOBJ: 0 >> >>+QLWURC: "ping",0,102,0 >> AT+QLWDEREG //Initiate de-registration >> >> OK >> >> +QLWDEREG: 0 // de-registered</pre>	If the application design does not require this step, you can skip the step
4- Power off after sending and receiving data		
4-1	<pre>>> AT+CFUN=0 //Set minimum function >> OK //Wait for the return OK, then mcu control to power off; If not return OK after running AT+CFUN=0 for a long period of time (for example, 20s), you can power off directly.</pre>	If the terminal is designed for power-off mode and powered off after data interaction is complete, you need to run AT+CFUN=0, then power off the terminal after return OK to avoid damage to the flash
5- Erase the historical frequency		
5-1	<pre>//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK</pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must

	<pre>>> AT+QCEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 /*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above</pre>	be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
--	--	---

6- Exception handling or interruption

6-1	1) The program or mcu needs to add the interrupt method of time-out or failure to register the leshan platform, such as re-registration or reboot. 2) The program or mcu needs to add the interrupt method of timeout or failure for sending or receiving data, such as reboot. 3) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout
-----	---	--

3.1.2.2 in PSM Mode

Application	PSM function is enabled, and only the Leshan platform is connected. The data is reported/upload frequently, and the application logic of mcu or program is relatively complex
-------------	---

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	<pre>//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY</pre>	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	<pre>//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK</pre>	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		

2-1	<pre> //Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 /*If you did not execute the lock BAND in 7-1, skip the command >> OK >> AT+QSCCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=1,,,"01000010","00000000" //Enable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK >> AT+QNBIOEVENT=1,1 //Enable the URC of PSM >> OK >> AT+QCFG="dsevent",1 //Enable the URC of Deepsleep >> OK </pre>	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design By AT+CPSMS=1,, "<T3412/TAU>","<T3324>", you can configure the T3412 and T3324 timers properly which you need.at the same time, after the completion of the registration network, by AT+CEREG=5; +CEREG? You need to query the real value of T3324,T3412/TAU provided by the network
2-2	<pre> // Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK </pre>	If APN needs to be configured for the SIM card , please perform the command, others can be ignored
2-3	<pre> >> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK </pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	<pre> //Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries </pre>	If the application design does not require this step, you can skip the step
2-5	<pre> >> AT+CSCON=1 >> OK </pre>	If the application design does not require this step, you can skip the step
2-6	<pre> >> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed </pre>	If the application design does not require this step, you can skip the step In the application design of the

	<pre>>> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK</pre>		terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	<pre>// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals</pre>		
2-8	<pre>>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK</pre>		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	<pre>>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK</pre>	<pre>>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK</pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre>>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK</pre>		
2-11	<pre>>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK</pre>		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>		Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times

3- Access the Ieshan platform

L3-1	<pre> //Set parameters and register leshan >> AT+QSCCLK=0 //Disable the deepsleep function >> >> OK >> AT+QIDNSCFG=0,"8.8.8.8","223.6.6.6" //Configure the valid DNS >> OK >> AT+QLWCFG="auto_reg",0 //Disable the auto_registration function >> >> OK >> AT+QLWCONFIG=0,"leshan.eclipseprojects.io",5683,"urn:imei:866207055068526",86400,3 //Set connection parameters of leshan platform >> >> OK >> AT+QLWADDOBJ=3311,0,3,5706,5701,5850 //Add object3311 and resources >> >> OK >> >> +QLWADDOBJ: 0 >> AT+QLWREG //Initiate registration >> >> OK >> >> +QLWURC: "registering",102,0 >> >> +QLWREG: 0 </pre>	The program or MCU needs to monitor the URC output of the registration status of the platform, and should reboot if the waiting window time of the program is exceeded
L3-2	<pre> >> AT+QLWSTATUS? //Query the status of the current connection >> >> +QLWSTATUS: 2 //registered >> >> OK </pre>	The program or mcu can query the registration status of the platform by AT+QLWSTATUS. After the query returns +QLWSTATUS: 2, then the data can be sent normally
L3-3	<pre> >> >> +QLWURC: "observe",43605,0,3311,0,5706 >> AT+QLWOBSRSP=43605,1,3311,0,5706,1,5,"white",0 //Response observe resource >> >> OK >> >> +QLWOBSRSP: 0 </pre>	
L3-4	<pre> //Report/send data to leshan platform >> AT+QLWNOTIFY=3311,0,5706,1,6,"orange",0,1 //It is recommended to report data of the CON type >> >> OK >> >> +QLWNOTIFY: 0 >> >> +QLWURC: "report",60516 </pre>	CON type is recommended for reporting or sending data. When "report_ack" is received, the data is successfully sent

	<pre>>> >> +QLWURC: "report_ack",0,60516 //the data is successfully reported and the ACK message is received from the platform.</pre>	
L3-5	<pre>//Set the receiving data mode - Direct Output mode (default) >> >> +QLWURC: "write",38156,3311,0,5706,2,4,"626c7565",0 >> AT+QLWRRSP=38156,2 //After receiving the data, respond platform >> >> OK >> >> +QLWRRSP: 0</pre>	Currently, the BC660K/BC950K supports only direct output mode
4- Feature of RAI		
Feature of RAI	1) After the data interaction is completed, you can run AT+QPING=0,"8.8.8.8",4,1,32,1	
R4-1	<pre>>> AT+QPING=0,"8.8.8.8",4,1,32,1 //QPING method with RAI Flag >> OK >> >> +QPING: 0,8.8.8.8,32,275,51 >> >> +QPING: 0,1,1,0,275,275,275 >> >> +CSCON:0 //If +CSCON:0 is returned within 0-2s, RAI is effective >> AT+QSCCLK=1 //Enable deepsleep mode >> OK</pre>	RAI implementation method
5- Enter status PSM and Deepsleep		
5-1	<pre>>> >> +QNBIOEVENT: "ENTER PSM" //Enter the PSM state >> >> +QNBIOEVENT: "ENTER DEEPSLEEP" //Enter the deepsleep state</pre>	
6- Exit status of Deepsleep and PSM		
L6-1-1	<pre>//BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QLWRECOVER //Trigger to recovery of the Lwm2m protocol >> >> OK >> >> +QLWURC: "recovered",0,102,0 >> AT+QLWNOTIFY=3311,0,5706,1,3,"red",0,1 //Send data of the CON type >> >> OK >> >> +QLWNOTIFY: 0 >> >> +QNBIOEVENT: "EXIT PSM" //Exit the PSM state >> >> +QLWURC: "report",26457</pre>	Method to trigger PSM wake-up

	<pre> >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QLWURC: "report_ack",0,26457 //the data is successfully reported and the ACK message is received from the platform Go to 6-2,or goto L3-3 for sending data,or goto L3-5 for receiving data, and the subsequent process </pre>	
L6-1-2	<pre> //If you want to obtain the accurate signal reference in the current scene immediately after the PSM is woked up, please refer to //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOTEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QPING=0,"8.8.8.8",4,1 //Trigger to exit PSM by PING >> OK >> >> +QNBIOTEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //It is recommended to obtain the signal reference after return the +CSCON:1 >> >> +QPING: 0,8.8.8.8,32,275,51 >> >> +QPING: 0,1,1,0,275,275,275 >> AT+QENG=0 //Query signal reference >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK >> AT+QLWRECOVER //Trigger to recovery of the Lwm2m protocol >> >> OK >> >> +QLWURC: "recovered",0,102,0 >> AT+QLWNOTIFY=3311,0,5706,1,3,"red",0,1 //Send data of the CON type >> >> OK >> >> +QLWNOTIFY: 0 >> >> +QLWURC: "report",8824 >> >> +QLWURC: "report_ack",0,8824 //the data is successfully reported and the ACK message is received from the platform Go to 6-2,or goto L3-3 for sending data,or goto L3-5 for receiving data, and the subsequent process </pre>	If the program or mcu needs to deal with other tasks, such as collecting the base station cell signal after wake-up; It is recommended to refer to this method to trigger PSM wake-up and obtain the network signal after wake-up. If no such requirement in the program, ignore the process
6-2	<pre> //Manual TAU update >> AT+CPSMS=0 >> OK >> AT+CPSMS=1,,,"01000010","00000000" </pre>	TAU update manually can avoid automatic update of TAU cycle over time, so,non-service power consumption can be

	>> OK Go to L3-3 for sending data, or goto L3-5 for receiving data, and the subsequent process	reduced; If no requirement in the application, ignore this step
7- Erase the historical frequency		
7-1	//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 /*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
8- Exception handling or interruption		
8-1	1) The program or mcu shall add the interrupt method of timeout or failure of leshan platform registration, such as re-registration or reboot; 2) The program or mcu shall add the interrupt method of sending or receiving data timeout or failure, such as reboot; 3) The program or mcu should add interrupt methods that cannot enter PSM normally or cannot wake up PSM, such as reboot; 4) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout. If unable to enter PSM or wake up from PSM, it is recommended to compare the normal time to enter PSM or exit PSM. If the time exceeds, power off or reboot should can be operated

3.1.3 TCP Application

3.1.3.1 in Power-off Mode

Application	The terminal is connected to the TCP server, the interval of data reported/upload is relatively long, the application logic of mcu or program is relatively simple, and the PSM is not enabled
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY	Boot log output, mcu can also determine whether it is normal boot;

	<pre>>> >> +CFUN: 1 >> >> +CPIN: READY</pre>	If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	<pre>//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK</pre>	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	<pre>//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 5-1, skip the command >> OK >> AT+QSCCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=0 //Disable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK</pre>	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design
2-2	<pre>// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK</pre>	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	<pre>>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK</pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	<pre>//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI</pre>	If the application design does not require this step, you can skip the step

	<pre>>> +CGSN:<IMEI> >> >> OK //Other queries</pre>		
2-5	<pre>>> AT+CSCON=1 >> OK</pre>		If the application design does not require this step, you can skip the step
2-6	<pre>>> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK</pre>		If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	<pre>// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals</pre>		
2-8	<pre>>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK</pre>		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	<pre>>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK</pre>	<pre>>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK</pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre>>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK</pre>		
2-11	<pre>>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK</pre>		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to

		run AT+QENG=0 to obtain RSRP and SNR
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>	Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times
3- Connect to TCP server		
T3-1	<pre>//Configure optional parameters >> AT+QICFG="dataformat",0,0 >> >> OK >> AT+QICFG="showlength",1 >> >> OK >> AT+QICFG="showRA",1 >> >> OK</pre>	In the actual development, please configure parameters according to your requirement
T3-2	<pre>//Set the TCP server parameters and initiate the connection >> AT+QIOPEN=0,0,"TCP","220.180.239.212",8058,0,1 //Direct push mode >> >> OK >> >> +QIOPEN: 0,0 >> AT+QISTATE=1,0 //Query TCP connection status >> >> +QISTATE: 0,"TCP","220.180.239.212",8058,0,2,0,1 >> >> OK</pre>	
T3-3-1	<pre>//Send data in non-data mode >> AT+QISEND=0,19,"this is a test text" //Send data >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data</pre>	
T3-3-2	<pre>//Send data in data mode >> AT+QISEND=0 >> >> > this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data</pre>	
T3-4	//Switch receiving mode to Buffer access mode	In actual development, if your

	Or the parameter access_mode of AT+QIOPEN is set to 0 <pre>>> AT+QISWTMD=0,0 //Switch the receive mode to Buffer access mode >> >> OK >> AT+QISEND=0 //Send data in data mode >> >>> this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058 //Receive the URC of data >> AT+QIRD=0,1200 //Read the data in buffer >> >> +QIRD: 12,0,"220.180.239.212",8058,"hello world" >> >> OK</pre>	requirement is buffer access mode, please configure access_mode to 0 in AT+QIOPEN
T3-5	<pre>>> AT+QICLOSE=0 //Close TCP connection >> >> OK >> >> CLOSE OK</pre>	
4- Power off after sending and receiving data		
4-1	<pre>>> AT+CFUN=0 //Set minimum function >> OK //Wait for the return OK, then mcu control to power off; If not return OK after running AT+CFUN=0 for a long period of time (for example, 20s), you can power off directly.</pre>	If the terminal is designed for power-off mode and powered off after data interaction is complete, you need to run AT+CFUN=0, then power off the terminal after return OK to avoid damage to the flash
5- Erase the historical frequency		
5-1	<pre>//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 //*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+Qrst=1 //Reboot, and re-search >> OK Follow 2-7 above</pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
6- Exception handling or interruption		
6-1	1) The program or mcu needs to add the interrupt method of time-out or failure to register the AEP platform, such as re-registration or reboot.	If the terminal has strict requirements on power

	2) The program or mcu needs to add the interrupt method of timeout or failure for sending or receiving data, such as reboot. 3) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	consumption, it is recommended that the program reasonably control timeout
--	--	--

3.1.3.2 in PSM Mode

Application	PSM function is enabled, and only the TCP server is connected. The data is reported/upload frequently, and the application logic of mcu or program is relatively complex
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+Qrst=1 //Reboot >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 7-1, skip the command >> OK >> AT+QSCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=1,,,"01000010","00000000" //Enable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design By AT+CPSMS=1,, " <t3412 ",="" +cereg?="" <="" after="" and="" at+cereg="5;" by="" can="" completion="" configure="" need.at="" network,="" of="" properly="" registration="" same="" t3324="" t3412="" tau>","<t3324>="" td="" the="" time,="" timers="" which="" you=""></t3412>

	<pre>>> OK >> AT+QNBIOEVENT=1,1 //Enable the URC of PSM >> OK >> AT+QCFG="dsevent",1 //Enable the URC of Deepsleep >> OK</pre>	need to query the real value of T3324,T3412/TAU provided by the network
2-2	<pre>// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK</pre>	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	<pre>>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK</pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	<pre>//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries</pre>	If the application design does not require this step, you can skip the step
2-5	<pre>>> AT+CSCON=1 >> OK</pre>	If the application design does not require this step, you can skip the step
2-6	<pre>>> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK</pre>	If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	<pre>// Query the network registration status >> AT+CEREG? //Query the network registration status</pre>	

	<pre>>> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals</pre>		
2-8	<pre>>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK</pre>		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	<pre>>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK</pre>	<pre>>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK</pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre>>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK</pre>		
2-11	<pre>>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK</pre>		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>		Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times
3- Access the TCP server			
T3-1	<pre>//Configure optional parameters >> AT+QICFG="dataformat",0,0 >> >> OK >> AT+QICFG="showlength",1 >> >> OK >> AT+QICFG="showRA",1 >> >> OK</pre>		In the actual development, please configure parameters according to your requirement
T3-2	<pre>//Set the TCP server parameters and initiate the connection >> AT+QIOPEN=0,0,"TCP","220.180.239.212",8058,0,1 //Direct push mode >> >> OK</pre>		

	<pre>>> >> +QIOPEN: 0,0 >> AT+QISTATE=1,0 //Query TCP connection status >> >> +QISTATE: 0,"TCP","220.180.239.212",8058,0,2,0,1 >> >> OK</pre>	
T3-3-1	<pre>//Send data in non-data mode >> AT+QISEND=0,19,"this is a test text" //Send data >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data</pre>	
T3-3-2	<pre>//Send data in data mode >> AT+QISEND=0 >> >> > this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data</pre>	
T3-4	<pre>//Switch receiving mode to Buffer access mode Or the parameter access_mode of AT+QIOPEN is set to 0 >> AT+QISWTMD=0,0 //Switch the receive mode to Buffer access mode >> >> OK >> AT+QISEND=0 //Send data in data mode >> >> > this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058 //Receive the URC of data >> AT+QIRD=0,1200 //Read the data in buffer >> >> +QIRD: 12,0,"220.180.239.212",8058,"hello world" >> >> OK</pre>	In actual development, if your requirement is buffer access mode, please configure access_mode to 0 in AT+QIOPEN

4- Feature of RA1

Feature	1) After the data interaction is completed, you can run AT+QPING=0,"8.8.8.8",4,1,32,1
---------	---

of RAI		
R4-1	<pre> >> AT+QPING=0,"8.8.8.8",4,1,32,1 //QPING method with RAI Flag >> OK >> >> +QPING: 0,8.8.8.8,32,729,51 >> >> +QPING: 0,1,1,0,729,729,729 >> >> +CSCON:0 //If +CSCON:0 is returned within 0-2s, RAI is effective >> AT+QSCCLK=1 //Enable deepsleep mode >> OK </pre>	RAI implementation method
5- Enter status PSM and Deepsleep		
5-1	<pre> >> >> +QNBIOEVENT: "ENTER PSM" //Enter the PSM state >> >> +QNBIOEVENT: "ENTER DEEPSLEEP" //Enter the deepsleep state </pre>	
6- Exit status of Deepsleep and PSM		
T6-1-1	<pre> //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QIOPEN=0,0,"TCP","220.180.239.212",8058,0,1 //Recreate the TCP connection >> >> OK >> >> +QNBIOEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QIOPEN: 0,0 //The TCP connection was established successfully Go to 6-2,or goto T3-3 for sending data,or goto L3-5 for receving data, and the subsequent process </pre>	Method to trigger PSM wake-up
T6-1-2	<pre> //If you want to obtain the accurate signal reference in the current scene immediately after the PSM is woked up, please refer to //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QIOPEN=0,0,"TCP","220.180.239.212",8058,0,1 //Recreate the TCP connection >> >> OK >> >> +QNBIOEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QIOPEN: 0,0 //The TCP connection was established successfully >> AT+QENG=0 //Query signal reference >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 </pre>	If the program or mcu needs to deal with other tasks, such as collecting the base station cell signal after wake-up; It is recommended to refer to this method to trigger PSM wake-up and obtain the network signal after wake-up. If no such requirement in the program, ignore the process

	<pre>>> >> OK >> AT+QISEND=0,51,"rsrp=-75,snr=14,cellid=05C4EF33,earfcn=3686,pci=121" //Send current signal reference data >> >> OK >> >> SEND OK</pre> Go to 6-2, or goto T3-3 for sending data or receiving data, and the subsequent process	
6-2	<pre>//Manual TAU update >> AT+CPSMS=0 >> OK >> AT+CPSMS=1,,,"01000010","00000000" >> OK</pre> Go to T3-3 for sending data or receiving data, and the subsequent process	TAU update manually can avoid automatic update of TAU cycle over time, so, non-service power consumption can be reduced; If no requirement in the application, ignore this step
7- Erase the historical frequency		
7-1	//If 2-8 the registration network is not successful within the set search time(such as 2min), go to <pre>>> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 // *Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above</pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
8- Exception handling or interruption		
8-1	1) The program or mcu shall add the interrupt method of timeout or failure of leshan platform registration, such as re-registration or reboot; 2) The program or mcu shall add the interrupt method of sending or receiving data timeout or failure, such as reboot; 3) The program or mcu should add interrupt methods that cannot enter PSM normally or cannot wake up PSM, such as reboot; 4) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout. If unable to enter PSM or wake up from PSM, it is recommended to compare the normal time to enter PSM or exit PSM. If the time exceeds, power off or reboot should can be operated

3.1.4 UDP Application

3.1.4.1 in Power-off Mode

Application	The terminal is connected to the UDP server, the interval of data reported/upload is relatively long, the application logic of mcu or program is relatively simple, and the PSM is not enabled
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+Qrst=1 //Reboot >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 5-1, skip the command >> OK >> AT+QSCCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=0 //Disable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design
2-2	// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>"	If APN needs to be configured for the SIM card, please perform the

	>> OK	command, others can be ignored
2-3	>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK	If return NO READY, indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries	If the application design does not require this step, you can skip the step
2-5	>> AT+CSCON=1 >> OK	If the application design does not require this step, you can skip the step
2-6	>> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK	If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals	
2-8	>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK	If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1

2-9	>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK	>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK		
2-11	>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK		Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times
3- Connect to UDP server			
U3-1	//Configure optional parameters >> AT+QICFG="dataformat",0,0 >> >> OK >> AT+QICFG="showlength",1 >> >> OK >> AT+QICFG="showRA",1 >> >> OK		In the actual development, please configure parameters according to your requirement
U3-2	//Set the TCP server parameters and initiate the connection >> AT+QIOPEN=0,0,"UDP","220.180.239.212",8058,0,1 //Direct push mode >> >> OK >> >> +QIOPEN: 0,0 >> AT+QISTATE=1,0 //Query TCP connection status >> >> +QISTATE: 0,"UDP","220.180.239.212",8058,0,2,0,1 >> >> OK		
T3-3-1	//Send data in non-data mode >> AT+QISEND=0,19,"this is a test text" //Send data >> >> OK >>		

	<pre>>> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data</pre>	
T3-3-2	<pre>//Send data in data mode >> AT+QISEND=0 >> >> > this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data</pre>	
T3-4	<pre>//Switch receiving mode to Buffer access mode Or the parameter access_mode of AT+QIOPEN is set to 0 >> AT+QISWTMD=0,0 //Switch the receive mode to Buffer access mode >> >> OK >> AT+QISEND=0 //Send data in data mode >> >> > this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058 //Receive the URC of data >> AT+QIRD=0,1200 //Read the data in buffer >> >> +QIRD: 12,0,"220.180.239.212",8058,"hello world" >> >> OK</pre>	In actual development, if your requirement is buffer access mode, please configure access_mode to 0 in AT+QIOPEN
T3-5	<pre>>> AT+QICLOSE=0 //Close UDP connection >> >> OK >> >> CLOSE OK</pre>	
4- Power off after sending and receiving data		
4-1	<pre>>> AT+CFUN=0 //Set minimum function >> OK //Wait for the return OK, then mcu control to power off; If not return OK after running AT+CFUN=0 for a long period of time (for example, 20s), you can power off directly.</pre>	If the terminal is designed for power-off mode and powered off after data interaction is complete, you need to run AT+CFUN=0, then power off the terminal after return OK to avoid damage to the flash
5- Erase the historical frequency		
5-1	<pre>//If 2-8 the registration network is not successful within the set search time(such as 2min), go to</pre>	As described in 2-8, it is suggested that in the program design, after

	<pre>>> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 /*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above</pre>	the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
--	---	---

6- Exception handling or interruption

6-1	1) The program or mcu needs to add the interrupt method of time-out or failure to register the AEP platform, such as re-registration or reboot. 2) The program or mcu needs to add the interrupt method of timeout or failure for sending or receiving data, such as reboot. 3) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout
-----	--	--

3.1.4.2 in PSM Mode

Application	PSM function is enabled, and only the UDP server is connected. The data is reported/upload frequently, and the application logic of mcu or program is relatively complex
-------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	<pre>//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY</pre>	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	<pre>//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK</pre>	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1

2- Search and register network

2-1	<pre>//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 7-1, skip the command >> OK >> AT+QSCCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=1,,,"01000010","00000000" //Enable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK >> AT+QNBIOTEVENT=1,1 //Enable the URC of PSM >> OK >> AT+QCFG="dsevent",1 //Enable the URC of Deepsleep >> OK</pre>	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design By AT+CPSMS=1,, "<T3412/TAU>","<T3324>", you can configure the T3412 and T3324 timers properly which you need.at the same time, after the completion of the registration network, by AT+CEREG=5; +CEREG? You need to query the real value of T3324,T3412/TAU provided by the network
2-2	<pre>// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK</pre>	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	<pre>>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK</pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	<pre>//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries</pre>	If the application design does not require this step, you can skip the step
2-5	<pre>>> AT+CSCON=1 >> OK</pre>	If the application design does not require this step, you can skip the step
2-6	<pre>>> >> +CSCON:1 //Indicates that the RRC connection is complete</pre>	If the application design does not require this step, you can

	//To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK		skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals 		
2-8	>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK	>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK		
2-11	>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK		Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple

		times
3- Access the TCP server		
T3-1	//Configure optional parameters >> AT+QICFG="dataformat",0,0 >> >> OK >> AT+QICFG="showlength",1 >> >> OK >> AT+QICFG="showRA",1 >> >> OK	In the actual development, please configure parameters according to your requirement
T3-2	//Set the TCP server parameters and initiate the connection >> AT+QIOPEN=0,0,"UDP","220.180.239.212",8058,0,1 //Direct push mode >> >> OK >> >> +QIOPEN: 0,0 >> AT+QISTATE=1,0 //Query TCP connection status >> >> +QISTATE: 0,"UDP","220.180.239.212",8058,0,2,0,1 >> >> OK	
T3-3-1	//Send data in non-data mode >> AT+QISEND=0,19,"this is a test text" //Send data >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data	
T3-3-2	//Send data in data mode >> AT+QISEND=0 >> >> > this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data	
T3-4	//Switch receiving mode to Buffer access mode Or the parameter access_mode of AT+QIOPEN is set to 0 >> AT+QISWTMD=0,0 //Switch the receive mode to Buffer access mode >> >> OK >> AT+QISEND=0 //Send data in data mode >>	In actual development, if your requirement is buffer access mode, please configure access_mode to 0 in AT+QIOPEN

	<pre> >> > this is a test text //After ">" is responded, input the data and tap "Ctrl" + "Z" to send it >> >> OK >> >> SEND OK >> >> +QIURC: "recv",0,12,"220.180.239.212",8058 //Receive the URC of data >> AT+QIRD=0,1200 //Read the data in buffer >> >> +QIRD: 12,0,"220.180.239.212",8058,"hello world" >> >> OK </pre>	
4- Feature of RAI		
Feature of RAI	2) After the data interaction is completed, you can run AT+QPING=0,"8.8.8.8",4,1,32,1	
R4-1	<pre> >> AT+QPING=0,"8.8.8.8",4,1,32,1 //QPING method with RAI Flag >> OK >> >> +QPING: 0,8.8.8.8,32,729,51 >> >> +QPING: 0,1,1,0,729,729,729 >> >> +CSCON:0 //If +CSCON:0 is returned within 0-2s, RAI is effective >> AT+QSCCLK=1 //Enable deepsleep mode >> OK </pre>	RAI implementation method
5- Enter status PSM and Deepsleep		
5-1	<pre> >> >> +QNBIOTEVENT: "ENTER PSM" //Enter the PSM state >> >> +QNBIOTEVENT: "ENTER DEEPSLEEP" //Enter the deepsleep state </pre>	
6- Exit status of Deepsleep and PSM		
U6-1-1	<pre> //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOTEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QISEND=0,10,"helloworld" //After exit deepsleep, the program or mcu can directly send UDP data >> >> OK >> >> SEND OK >> >> +QNBIOTEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QIURC: "recv",0,12,"220.180.239.212",8058,"hello world" //Receive data </pre>	Method to trigger PSM wake-up

	Go to 6-2,or goto T3-3 for sending data,or goto L3-5 for receiving data, and the subsequent process	
U6-1-2	//If you want to obtain the accurate signal reference in the current scene immediately after the PSM is woked up, please refer to //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin <pre> >> >> +QNBIOTEVENT: "EXIT DEEPSLEEP" >> AT+QPING=0,"8.8.8.8",4,1 >> >> OK >> >> +QNBIOTEVENT: "EXIT PSM" >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QPING: 0,8.8.8.8,32,699,51 >> >> +QPING: 0,1,1,0,699,699,699 >> AT+QENG=0 //Query signal reference >> >> +QENG: 0,3686,11,121,"05C4EF33",-72,-2,-70,18,8,"4C10",0,0,3 >> >> OK >> AT+QISEND=0,51,"rsrp=-72,snr=18,cellid=05C4EF33,earfcn=3686,pci=121" //Send current signal reference data >> >> OK >> >> SEND OK </pre> Go to 6-2,or goto U3-3 for sending data or receiving data, and the subsequent process	If the program or mcu needs to deal with other tasks, such as collecting the base station cell signal after wake-up; It is recommended to refer to this method to trigger PSM wake-up and obtain the network signal after wake-up. If no such requirement in the program, ignore the process
6-2	//Manual TAU update <pre> >> AT+CPSMS=0 >> OK >> AT+CPSMS=1,,,"01000010","00000000" >> OK </pre> Go to U3-3 for sending data or receiving data, and the subsequent process	TAU update manually can avoid automatic update of TAU cycle over time, so,non-service power consumption can be reduced; If no requirement in the application, ignore this step
7- Erase the historical frequency		
7-1	//If 2-8 the registration network is not successful within the set search time(such as 2min), go to <pre> >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 </pre> //*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out,

	in order to speed up your search for a radio network. >> OK >> AT+Qrst=1 //Reboot, and re-search >> OK Follow 2-7 above	you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
8- Exception handling or interruption		
8-1	1) The program or mcu shall add the interrupt method of timeout or failure of lshan platform registration, such as re-registration or reboot; 2) The program or mcu shall add the interrupt method of sending or receiving data timeout or failure, such as reboot; 3) The program or mcu should add interrupt methods that cannot enter PSM normally or cannot wake up PSM, such as reboot; 4) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout. If unable to enter PSM or wake up from PSM, it is recommended to compare the normal time to enter PSM or exit PSM. If the time exceeds, power off or reboot should can be operated

3.1.5 MQTT-based AWS IoT Application

3.1.5.1 in Power-off Mode

Application	The terminal is connected to the MQTT of AWS IoT platform, the interval of data reported/upload is relatively long, the application logic of mcu or program is relatively simple, and the PSM is not enabled
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSClk=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode.

	<pre>>> AT+QRST=1 //Reboot >> OK</pre>	If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	<pre>//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 5-1, skip the command >> OK >> AT+QSClk=0 //Disable the deepsleep >> OK >> AT+CPSMS=0 //Disable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK</pre>	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design
2-2	<pre>// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK</pre>	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	<pre>>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK</pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	<pre>//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries</pre>	If the application design does not require this step, you can skip the step
2-5	<pre>>> AT+CSCON=1 >> OK</pre>	If the application design does not require this step, you can skip the step
2-6	<pre>>> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed</pre>	If the application design does not require this step, you can skip the step In the application design of the

	<pre>>> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK</pre>	terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.	
2-7	<pre>// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals</pre>		
2-8	<pre>>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK</pre>	If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1	
2-9	<pre>>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK</pre>	<pre>>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK</pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre>>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK</pre>		
2-11	<pre>>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK</pre>	CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR	
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>	Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times	
3- Connect to AWS IoT server			
Q3-1	<pre>//Testing AWS IoT connectivity >> AT+QIDNSCFG=0,"8.8.8.8","8.8.4.4"</pre>	In the actual development, please configure parameters according to	

	<pre> >> >> OK >> AT+QPING=0,"a9ohm2zbim3d5-ats.iot.us-east-1.amazonaws.com",4,1 >> >> OK >> >> +QPING: 0,54.204.191.103,32,356,237 >> >> +QPING: 0,1,1,0,356,356,356 </pre>	your requirement
Q3-2	<pre> //Load the CA certificate and key files >> AT+QSSLCFG=0,0,"cacert" // Upload the RootCA.pem to the FILE system >> >> > >> -----BEGIN CERTIFICATE----- >> MIIDQTCCAimgAwIBAgITBmyfz5m/jAo54vB4ikPmljZbyjANBgkqhkiG9w0BAQsF >> >> rqXRfboQnoZsG4q5WTP468SQvvG5 >> -----END CERTIFICATE----- >> +QSSLCFG: 0,0,"cacert",1187 // The byte size of the indication must correspond to the byte size of the content of AmazonRootCA1.pem >> >> OK >> AT+QSSLCFG=0,0,"clientcert" // Upload the certificate.pem.crt to the FILE system >> >> > >> -----BEGIN CERTIFICATE----- >> MIIDWjCCAKKgAwIBAgIVAKp/znqyrMfoSWNqhC/Ln+qsPPI4MA0GCSqGSIb3DQEB >> >> ++kMnCN/oHJzDI2jzL65XktQm99MojobbN121jZm3v34nqOuYFT6351CaA64DQ== >> -----END CERTIFICATE----- >> >> +QSSLCFG: 0,0,"clientcert",1224 // The byte size of the indication must correspond to the byte size of the content of xxx- certificate.pem.crt >> >> OK >> AT+QSSLCFG=0,0,"clientkey" // Upload the private.pem.key to the FILE system >> >> > >> -----BEGIN RSA PRIVATE KEY----- >> MIIEowIBAAKCAQEA3rCImNdAS6x43he0Zn0hq7BGHrdt3ttlJYmTsCVttkcdGX3+ >> >> cnEBRC2U3DpU1qNrn0D8r8qCJjWbYJwzEbEoFaKi8zHuhLLVuuus >> -----END RSA PRIVATE KEY----- >> >> +QSSLCFG: 0,0,"clientkey",1675 // The byte size of the indication must correspond to the byte size of the content of xxx- </pre>	

	<pre>private.pem.key >> >> OK</pre>	
Q3-3	<pre>//MQTT and SSL configuration >> AT+QSSLCFG=0,0,"seclvel",2 //SSL authorization mode:server authentication >> >> OK >> AT+QMTCFG="ssl",0,1,0,0 //Enable SSL and configure SSL context/connect index >> >> OK >> AT+QMTCFG="version",0,1 //Configure the MQTT version >> >> OK >> AT+QSSLCFG=0,0 //Query and validate the results of the current configuration >> >> +QSSLCFG: 0,0,"seclvel",2 >> +QSSLCFG: 0,0,"sslversion",4 >> +QSSLCFG: 0,0,"dataformat",0,0 >> +QSSLCFG: 0,0,"timeout",90 >> +QSSLCFG: 0,0,"debug",0 >> +QSSLCFG: 0,0,"cacert",1187 >> +QSSLCFG: 0,0,"clientcert",1224 >> +QSSLCFG: 0,0,"clientkey",1675 >> +QSSLCFG: 0,0,"dtls",0 >> +QSSLCFG: 0,0,"dtlsversion",2 >> >> OK</pre>	
Q3-4	<pre>//MQTT of AWS IoT to connect and subscribe >> AT+QMTOPEN=0,"a9ohm2zbim3d5-ats.iot.us-east-1.amazonaws.com",8883 // Open the MQTT SSL connection >> >> OK >> >> +QMTOPEN: 0,0 >> AT+QMTCONN=0,"smartKit001" // Initiate the MQTT server connection >> >> OK >> >> +QMTCONN: 0,0,0 >> AT+QMTSUB=0,1,"toaws/smartKit001/update/message",1 // Subscribe to related topic >> >> OK >> >> +QMTSUB: 0,1,0,1</pre>	
Q3-5-1	<pre>//MQTT publish Publish fixed-length messages in non-data mode >> AT+QMTPUB=0,1,1,0,"aws/meter001/data/report/message",23,"{"temp",22.5,"humi",68}"</pre>	

	<pre>// Publish messages to related topic >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"toaws/smartKit001/update/message",{ "message": "Hello from AWS IoT console"}</pre>	
Q3-5-2	<pre>//MQTT publish Publish fixed-length messages in data mode >> AT+QMTPUB=0,1,1,0,"aws/meter001/data/report/message",23 >> > >> {"temp",22.5,"humi",68} // Publish data >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"toaws/smartKit001/update/message",{ "message": "Hello from AWS IoT console"}</pre>	
Q3-5-3	<pre>//MQTT publish Publish variable-length messages in data mode >> AT+QMTPUB=0,1,1,0,"aws/meter001/data/report/message" >> > >> {"temp",22.5,"humi",68} // Publish data >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"toaws/smartKit001/update/message",{ "message": "Hello from AWS IoT console"}</pre>	
Q3-6	<pre>>> AT+QMTCLOSE=0 // Initiating MQTT connection disconnected >> >> OK >> >> +QMTCLOSE: 0,0</pre>	
4- Power off after sending and receiving data		
4-1	<pre>>> AT+CFUN=0 //Set minimum function >> OK //Wait for the return OK, then mcu control to power off; If not return OK after running AT+CFUN=0 for a long period of time (for example, 20s), you can power off directly.</pre>	If the terminal is designed for power-off mode and powered off after data interaction is complete, you need to run AT+CFUN=0, then power off the terminal after return OK to avoid damage to the flash
5- Erase the historical frequency		
5-1	<pre>//If 2-8 the registration network is not successful within the set search time(such as 2min), go to</pre>	As described in 2-8, it is suggested that in the program design, after

	<pre>>> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 //*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above</pre>	the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
6- Exception handling or interruption		
6-1	1) The program or mcu needs to add the interrupt method of time-out or failure to register the AEP platform, such as re-registration or reboot. 2) The program or mcu needs to add the interrupt method of timeout or failure for sending or receiving data, such as reboot. 3) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout

3.1.5.2 in PSM Mode

Application	PSM function is enabled, and only the MQTT of AWS IoT platform is connected. The data is reported/upload frequently, and the application logic of mcu or program is relatively complex
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	<pre>//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY</pre>	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	<pre>//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSClk=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK</pre>	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip

		this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 7-1, skip the command >> OK >> AT+QSCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=1,,,"01000010","00000000" //Enable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK >> AT+QNBIOEVENT=1,1 //Enable the URC of PSM >> OK >> AT+QCFG="dsevent",1 //Enable the URC of Deepsleep >> OK	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design By AT+CPSMS=1,, "<T3412/TAU>","<T3324>", you can configure the T3412 and T3324 timers properly which you need.at the same time, after the completion of the registration network, by AT+CEREG=5; +CEREG? You need to query the real value of T3324,T3412/TAU provided by the network
2-2	// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries	If the application design does not require this step, you can skip the step
2-5	>> AT+CSCON=1 >> OK	If the application design does not require this step, you can skip the step

2-6	<pre> >> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK </pre>		If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	<pre> // Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals </pre>		
2-8	<pre> >> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK </pre>		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	<pre> >> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK </pre>	<pre> >> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK </pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre> >> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK </pre>		
2-11	<pre> >> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK </pre>		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	<pre> >> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" </pre>		Time conversion: 24/01/16,08:55:19+32/4(h)=

	<pre>>> >> OK</pre>	2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times
3- Access the AWS IoT server		
Q3-1	<pre>//Testing AWS IoT connectivity >> AT+QIDNSCFG=0,"8.8.8.8","8.8.4.4" >> >> OK >> AT+QPING=0,"a9ohm2zbim3d5-ats.iot.us-east-1.amazonaws.com",4,1 >> >> OK >> >> +QPING: 0,54.204.191.103,32,356,237 >> >> +QPING: 0,1,1,0,356,356,356</pre>	In the actual development, please configure parameters according to your requirement
Q3-2	<pre>//Load the CA certificate and key files >> AT+QSSLCFG=0,0,"cacert" // Upload the RootCA.pem to the FILE system >> >> > >> -----BEGIN CERTIFICATE----- >> MIIDQTCCAimgAwIBAgITBmyfz5m/jAo54vB4ikPmljZbyjANBgkqhkiG9w0BAQsF >> >> rqXRfboQnoZsG4q5WTP468SQvvG5 >> -----END CERTIFICATE----- >> +QSSLCFG: 0,0,"cacert",1187 // The byte size of the indication must correspond to the byte size of the content of AmazonRootCA1.pem >> >> OK >> AT+QSSLCFG=0,0,"clientcert" // Upload the certificate.pem.crt to the FILE system >> >> > >> -----BEGIN CERTIFICATE----- >> MIIDWjCCAkKgAwIBAgIVAKp/znqyrMfoSWNqhC/Ln+qsPPI4MA0GCSqGSIb3DQEBA >> >> ++kMnCN/oHJzDI2jzL65XktQm99MojobbN121jZm3v34nqOuYFT6351CaA64DQ== >> -----END CERTIFICATE----- >> >> +QSSLCFG: 0,0,"clientcert",1224 // The byte size of the indication must correspond to the byte size of the content of xxx- certificate.pem.crt >> >> OK >> AT+QSSLCFG=0,0,"clientkey" // Upload the private.pem.key to the FILE system >> >> > >> -----BEGIN RSA PRIVATE KEY-----</pre>	

	<pre> >> MIIEowIBAAKCAQEA3rCImNdAS6x43he0Zn0hq7BGHrdt3ttljYmTsCVttkcdGX3+ >> >> cnEBCR2U3DpU1qNrn0D8r8qCJjWbYJwzEbEoFaKi8zHuhLLVuuus >> -----END RSA PRIVATE KEY----- >> >> +QSSSLCFG: 0,0,"clientkey",1675 // The byte size of the indication must correspond to the byte size of the content of xxx- private.pem.key >> >> OK </pre>	
Q3-3	<pre> //MQTT and SSL configuration >> AT+QSSSLCFG=0,0,"secllevel",2 //SSL authorization mode:server authentication >> >> OK >> AT+QMTCFG="ssl",0,1,0,0 //Enable SSL and configure SSL context/connect index >> >> OK >> AT+QMTCFG="version",0,1 //Configure the MQTT version >> >> OK >> AT+QSSSLCFG=0,0 //Query and validate the results of the current configuration >> >> +QSSSLCFG: 0,0,"secllevel",2 >> +QSSSLCFG: 0,0,"sslversion",4 >> +QSSSLCFG: 0,0,"dataformat",0,0 >> +QSSSLCFG: 0,0,"timeout",90 >> +QSSSLCFG: 0,0,"debug",0 >> +QSSSLCFG: 0,0,"cacert",1187 >> +QSSSLCFG: 0,0,"clientcert",1224 >> +QSSSLCFG: 0,0,"clientkey",1675 >> +QSSSLCFG: 0,0,"dtls",0 >> +QSSSLCFG: 0,0,"dtlsversion",2 >> >> OK </pre>	
Q3-4	<pre> //MQTT of AWS IoT to connect and subscribe >> AT+QMTOPEN=0,"a9ohm2zbim3d5-ats.iot.us-east-1.amazonaws.com",8883 // Open the MQTT SSL connection >> >> OK >> >> +QMTOPEN: 0,0 >> AT+QMTCONN=0,"smartKit001" // Initiate the MQTT server connection >> >> OK >> >> +QMTCONN: 0,0,0 >> AT+QMTSUB=0,1,"toaws/smartKit001/update/message",1 // Subscribe to related topic >> </pre>	

	<pre>>> OK >> >> +QMTSUB: 0,1,0,1</pre>	
Q3-5-1	<pre>//MQTT publish Publish fixed-length messages in non-data mode >> AT+QMTPUB=0,1,1,0,"aws/meter001/data/report/message",23,"{"temp",22.5,"humi",68}" // Publish messages to related topic >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"toaws/smartKit001/update/message","{ "message": "Hello from AWS IoT console"}"</pre>	
Q3-5-2	<pre>//MQTT publish Publish fixed-length messages in data mode >> AT+QMTPUB=0,1,1,0,"aws/meter001/data/report/message",23 >> > >> "{"temp",22.5,"humi",68}" // Publish data >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"toaws/smartKit001/update/message","{ "message": "Hello from AWS IoT console"}"</pre>	
Q3-5-3	<pre>//MQTT publish Publish variable-length messages in data mode >> AT+QMTPUB=0,1,1,0,"aws/meter001/data/report/message" >> > >> "{"temp",22.5,"humi",68}" // Publish data >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"toaws/smartKit001/update/message","{ "message": "Hello from AWS IoT console"}"</pre>	
4- Feature of RAI		
Feature of RAI	3) After the data interaction is completed, you can run AT+QPING=0,"8.8.8.8",4,1,32,1	
R4-1	<pre>>> AT+QPING=0,"8.8.8.8",4,1,32,1 //QPING method with RAI Flag >> OK >> >> +QPING: 0,8.8.8.8,32,729,51 >> >> +QPING: 0,1,1,0,729,729,729</pre>	RAI implementation method

	<pre> >> >> +CSCON:0 //If +CSCON:0 is returned within 0-2s, RAI is effective >> AT+QSCCLK=1 //Enable deepsleep mode >> OK </pre>	
5- Enter status PSM and Deepsleep		
5-1	<pre> >> >> +QNBIOEVENT: "ENTER PSM" //Enter the PSM state >> >> +QNBIOEVENT: "ENTER DEEPSLEEP" //Enter the deepsleep state </pre>	
6- Exit status of Deepsleep and PSM		
T6-1-1	//BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin <pre> >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state //Recreate the MQTT connection >> AT+QSSLCFG=0,0,"seclvel",2 >> >> OK >> AT+QMTCFG="ssl",0,1,0,0 >> >> OK >> AT+QMTCFG="version",0,1 >> >> OK >> AT+QMTOPEN=0,"a9ohm2zbim3d5-ats.iot.us-east-1.amazonaws.com",8883 >> >> OK >> >> +QNBIOEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QMTOPEN: 0,0 >> AT+QMTCNN=0,"meter001" >> >> OK >> >> +QMTCNN: 0,0,0 //The MQTT connection was established successfully Go to 6-2,or goto Q3-5 for sending data or receiving data, and the subsequent process </pre>	Method to trigger PSM wake-up
Q6-1-2	//If you want to obtain the accurate signal reference in the current scene immediately after the PSM is woked up, please refer to //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin <pre> >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" >> AT+QPING=0,"8.8.8.8",4,1 >> >> OK </pre>	If the program or mcu needs to deal with other tasks, such as collecting the base station cell signal after wake-up; It is recommended to refer to this method to trigger PSM wake-up and obtain the network signal after wake-up. If no such requirement in the

	<pre> >> >> +QNBIOEVENT: "EXIT PSM" >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QPING: 0,8.8.8.8,32,699,51 >> >> +QPING: 0,1,1,0,699,699,699 >> AT+QENG=0 //Query signal reference >> >> +QENG: 0,3686,11,121,"05C4EF33",-72,-2,-70,18,8,"4C10",0,0,3 >> >> OK //Recreate the MQTT connection >> AT+QSSLCFG=0,0,"secllevel",2 >> >> OK >> AT+QMTCFG="ssl",0,1,0,0 >> >> OK >> AT+QMTCFG="version",0,1 >> >> OK >> AT+QMTOPEN=0,"a9ohm2zbim3d5-ats.iot.us-east-1.amazonaws.com",8883 >> >> OK >> >> +QMTOPEN: 0,0 >> AT+QMTCNN=0,"meter001" >> >> OK >> >> +QMTCNN: 0,0,0 //The MQTT connection was established successfully Go to 6-2,or goto Q3-5 for sending data or receiving data, and the subsequent process </pre>	program, ignore the process
6-2	<pre> //Manual TAU update >> AT+CPSMS=0 >> OK >> AT+CPSMS=1,,,"01000010","00000000" >> OK Go to Q3-5 for sending data or receiving data, and the subsequent process </pre>	TAU update manually can avoid automatic update of TAU cycle over time, so,non-service power consumption can be reduced; If no requirement in the application, ignore this step
7- Erase the historical frequency		
7-1	<pre> //If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK </pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the

	>> AT+QBAND=1,28 /*Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above	2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
8- Exception handling or interruption		
8-1	1) The program or mcu shall add the interrupt method of timeout or failure of leschan platform registration, such as re-registration or reboot; 2) The program or mcu shall add the interrupt method of sending or receiving data timeout or failure, such as reboot; 3) The program or mcu should add interrupt methods that cannot enter PSM normally or cannot wake up PSM, such as reboot; 4) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout. If unable to enter PSM or wake up from PSM, it is recommended to compare the normal time to enter PSM or exit PSM. If the time exceeds, power off or reboot should can be operated

3.1.6 MQTT-based Alibaba Cloud Application

3.1.6.1 in Power-off Mode

Application	The terminal is connected to the MQTT of Alibaba cloud platform, the interval of data reported/upload is relatively long, the application logic of mcu or program is relatively simple, and the PSM is not enabled
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSClk=1 //The deepsleep is enabled by default >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0

	 //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK	can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 5-1, skip the command >> OK >> AT+QSClk=0 //Disable the deepsleep >> OK >> AT+CPSMS=0 //Disable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design
2-2	// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries	If the application design does not require this step, you can skip the step
2-5	>> AT+CSCON=1 >> OK	If the application design does not require this step, you can skip the step
2-6	>> >> +CSCON:1 //Indicates that the RRC connection is complete	If the application design does not require this step, you can skip the

	//To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK		step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals 		
2-8	>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK		If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1
2-9	>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK	>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK		
2-11	>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK		Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times

3- Connect to Alibaba Cloud server

Q3-1	//Configuring DNS >> AT+QIDNSCFG=0,"223.5.5.5","223.6.6.6" >> >> OK	
Q3-2	//MQTT configuration >> AT+QMTCFG="version",0,1 //Configure the MQTT version >> OK >> AT+QMTCFG="keepalive",0,1200 //Configure the keepalive >> OK >> AT+QMTCFG="aliauth",0,"i2uq00ze3N3","device001","3af2ccf1273f1b8866effc4d64b85d07" //Configure the device certificate for Ali Cloud:ProductKey,DeviceName,DeviceSecret >> >> OK	
Q3-3	//MQTT of Alibaba Cloud to connect >> AT+QMTOPEN=0,"iot-06z00hxss3rggno.mqtt.iothub.aliyuncs.com",1883 // Open the MQTT connection >> >> OK >> >> +QMTOPEN: 0,0 >> AT+QMTCONN=0,"device001" // Initiate the MQTT server connection >> >> OK >> >> +QMTCONN: 0,0,0	
Q3-4-1	//MQTT publish Publish fixed-length messages in non-data mode >> AT+QMTPUB=0,1,1,0,"/sys/i2uq00ze3N3/device001/thing/event /property/post",99,{"id":"null","params":{"temp":23.6, "humi":82},"version":"1.0","method":"thing.event.property.post"}" >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"/sys/i2uq00ze3N3/device001/thing/event/property /post_reply",{"code":200,"data":{"id":"null","message":"success" ,"method":"thing.event.property.post","version":"1.0"}}	
Q3-4-2	//MQTT publish Publish fixed-length messages in data mode >> AT+QMTPUB=0,1,1,0,"/sys/i2uq00ze3N3/device001/thing /event/property/post",99 >> >> > >> {"id":"null","params":{"temp":18.5,"humi":79}, "version":"1.0","method":"thing.event.property.post"} // Publish data >>	

	<pre>>> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"/sys/i2uq00ze3N3/device001/thing/event/property /post_reply","{"code":200,"data":{},"id":"null","message":"success", "method":"thing.event.property.post","version":"1.0"}"</pre>	
Q3-4-3	<pre>//MQTT publish Publish variable-length messages in data mode >> AT+QMTPUB=0,1,1,0,"/sys/i2uq00ze3N3/device001/thing /event/property/post" >> >> > >> {"id":"null","params":{"temp":18.5,"humi":79}, "version":"1.0","method":"thing.event.property.post"} // Publish data >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"/sys/i2uq00ze3N3/device001/thing/event/property /post_reply","{"code":200,"data":{},"id":"null","message":"success", "method":"thing.event.property.post","version":"1.0"}"</pre>	
Q3-5	<pre>//MQTT server push >> >> +QMTRECV: 0,0,"/i2uq00ze3N3/device001/user/reply","LED status:off"</pre>	
Q3-6	<pre>>> AT+QMTCLOSE=0 // Initiating MQTT connection disconnected >> >> OK >> >> +QMTCLOSE: 0,0</pre>	
4- Power off after sending and receiving data		
4-1	<pre>>> AT+CFUN=0 //Set minimum function >> OK //Wait for the return OK, then mcu control to power off; If not return OK after running AT+CFUN=0 for a long period of time (for example, 20s), you can power off directly.</pre>	If the terminal is designed for power-off mode and powered off after data interaction is complete, you need to run AT+CFUN=0, then power off the terminal after return OK to avoid damage to the flash
5- Erase the historical frequency		
5-1	<pre>//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 //*Lock a specific frequency band. Note that it is not recommended for non-specific</pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out,

	situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above	you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
--	--	--

6- Exception handling or interruption

6-1	1) The program or mcu needs to add the interrupt method of time-out or failure to register the AEP platform, such as re-registration or reboot. 2) The program or mcu needs to add the interrupt method of timeout or failure for sending or receiving data, such as reboot. 3) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout
-----	--	--

3.1.6.2 in PSM Mode

Application	PSM function is enabled, and only the MQTT of Alibaba cloud platform is connected. The data is reported/upload frequently, and the application logic of mcu or program is relatively complex
-------------	---

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfund0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to

	<pre> >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 7-1, skip the command >> OK >> AT+QSCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=1,,,"01000010","00000000" //Enable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK >> AT+QNBIOTEVENT=1,1 //Enable the URC of PSM >> OK >> AT+QCFG="dsevent",1 //Enable the URC of Deepsleep >> OK </pre>	check the SIM card itself or the pin connection and hardware design By AT+CPSMS=1,, "<T3412/TAU>","<T3324>", you can configure the T3412 and T3324 timers properly which you need.at the same time, after the completion of the registration network, by AT+CEREG=5; +CEREG? You need to query the real value of T3324,T3412/TAU provided by the network
2-2	// Configure the APN based on the requirement of SIM card <pre> >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK </pre>	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	<pre> >> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK </pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	//Check the attribute values of the module <pre> >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries </pre>	If the application design does not require this step, you can skip the step
2-5	<pre> >> AT+CSCON=1 >> OK </pre>	If the application design does not require this step, you can skip the step
2-6	<pre> >> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 </pre>	If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the

	<pre>>> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:8986112223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK</pre>	relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.	
2-7	<pre>// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals</pre>		
2-8	<pre>>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK</pre>	If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1	
2-9	<pre>>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK</pre>	<pre>>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK</pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre>>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK</pre>		
2-11	<pre>>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK</pre>	CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR	
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>	Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times	
3- Access the Alibaba Cloud server			
Q3-1	//Configuring DNS		

	<pre>>> AT+QIDNSCFG=0,"223.5.5.5","223.6.6.6" >> >> OK</pre>	
Q3-2	<pre>//MQTT configuration >> AT+QMTCFG="version",0,1 //Configure the MQTT version >> OK >> AT+QMTCFG="keepalive",0,1200 //Configure the keepalive >> OK >> AT+QMTCFG="aliauth",0,"i2uq00ze3N3","device001","3af2ccf1273f1b8866effc4d64b85d07" //Configure the device certificate for Ali Cloud:ProductKey,DeviceName,DeviceSecret >> >> OK</pre>	
Q3-3	<pre>//MQTT of Alibaba Cloud to connect >> AT+QMTOPEN=0,"iot-06z00hxss3rggno.mqtt.iothub.aliyuncs.com",1883 // Open the MQTT connection >> >> OK >> >> +QMTOPEN: 0,0 >> AT+QMTCONN=0,"device001" // Initiate the MQTT server connection >> >> OK >> >> +QMTCONN: 0,0,0</pre>	
Q3-4-1	<pre>//MQTT publish Publish fixed-length messages in non-data mode >> AT+QMTPUB=0,1,1,0,"/sys/i2uq00ze3N3/device001/thing/event /property/post",99,{"id":"null","params":{"temp":23.6, "humid":82},"version":"1.0","method":"thing.event.property.post"}" >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"/sys/i2uq00ze3N3/device001/thing/event/property /post_reply","{"code":200,"data":{"id":"null","message":"success" ,"method":"thing.event.property.post","version":"1.0"}"</pre>	
Q3-4-2	<pre>//MQTT publish Publish fixed-length messages in data mode >> AT+QMTPUB=0,1,1,0,"/sys/i2uq00ze3N3/device001/thing /event/property/post",99 >> >> > >> {"id":"null","params":{"temp":18.5,"humid":79}, "version":"1.0","method":"thing.event.property.post"} // Publish data >> >> OK</pre>	

	<pre>>> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"/sys/i2uq00ze3N3/device001/thing/event/property /post_reply","{"code":200,"data":{"id":"null","message":"success", "method":"thing.event.property.post","version":"1.0"}"</pre>	
Q3-4-3	<pre>//MQTT publish Publish variable-length messages in data mode >> AT+QMTPUB=0,1,1,0,"/sys/i2uq00ze3N3/device001/thing /event/property/post" >> >> > >> {"id":"null","params":{"temp":18.5,"humi":79}, "version":"1.0","method":"thing.event.property.post"} // Publish data >> >> OK >> >> +QMTPUB: 0,1,0 >> >> +QMTRECV: 0,0,"/sys/i2uq00ze3N3/device001/thing/event/property /post_reply","{"code":200,"data":{"id":"null","message":"success", "method":"thing.event.property.post","version":"1.0"}"</pre>	
Q3-5	<pre>//MQTT server push >> >> +QMTRECV: 0,0,"/i2uq00ze3N3/device001/user/reply","LED status:off"</pre>	
4- Feature of RAI		
Feature of RAI	1) After the data interaction is completed, you can run AT+QPING=0,"8.8.8.8",4,1,32,1	
R4-1	<pre>>> AT+QPING=0,"8.8.8.8",4,1,32,1 //QPING method with RAI Flag >> OK >> >> +QPING: 0,8.8.8.8,32,729,51 >> >> +QPING: 0,1,1,0,729,729,729 >> >> +CSCON:0 //If +CSCON:0 is returned within 0-2s, RAI is effective >> AT+QSCLK=1 //Enable deepsleep mode >> OK</pre>	RAI implementation method
5- Enter status PSM and Deepsleep		
5-1	<pre>>> >> +QNBIOEVENT: "ENTER PSM" //Enter the PSM state >> >> +QNBIOEVENT: "ENTER DEEPSLEEP" //Enter the deepsleep state</pre>	
6- Exit status of Deepsleep and PSM		
T6-1-1	<pre>//BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state</pre>	Method to trigger PSM wake-up

	<pre>//Recreate the MQTT connection >> AT+QMTCFG="aliauth",0,"i2uq00ze3N3","device001","3af2ccf1273f1b8866effc4d64b85d07" >> OK >> AT+QMTOPEN=0,"iot-06z00hxss3rggno.mqtt.iothub.aliyuncs.com",1883 >> >> OK >> >> +QNBIOTEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QMTOPEN: 0,0 >> AT+QMTCONN=0,"device001" >> >> OK >> >> +QMTCONN: 0,0,0 //The MQTT connection was established successfully Go to 6-2,or goto Q3-4 for sending data or receiving data, and the subsequent process</pre>	
Q6-1-2	<pre>//If you want to obtain the accurate signal reference in the current scene immediately after the PSM is woked up, please refer to //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOTEVENT: "EXIT DEEPSLEEP" >> AT+QPING=0,"8.8.8.8",4,1 >> >> OK >> >> +QNBIOTEVENT: "EXIT PSM" >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QPING: 0,8.8.8.8,32,699,51 >> >> +QPING: 0,1,1,0,699,699,699 >> AT+QENG=0 //Query signal reference >> >> +QENG: 0,3686,11,121,"05C4EF33",-72,-2,-70,18,8,"4C10",0,0,3 >> >> OK //Recreate the MQTT connection >> AT+QMTCFG="aliauth",0,"i2uq00ze3N3","device001","3af2ccf1273f1b8866effc4d64b85d07" >> OK >> AT+QMTOPEN=0,"iot-06z00hxss3rggno.mqtt.iothub.aliyuncs.com",1883 >> >> OK</pre>	If the program or mcu needs to deal with other tasks, such as collecting the base station cell signal after wake-up; It is recommended to refer to this method to trigger PSM wake-up and obtain the network signal after wake-up. If no such requirement in the program, ignore the process

	<pre>>> >> +QMTOPEN: 0,0 >> AT+QMTCONN=0,"device001" >> >> OK >> >> +QMTCONN: 0,0,0 //The MQTT connection was established successfully Go to 6-2,or goto Q3-4 for sending data or receiving data, and the subsequent process</pre>	
6-2	<pre>//Manual TAU update >> AT+CPSMS=0 >> OK >> AT+CPSMS=1,,,"01000010","00000000" >> OK Go to Q3-4 for sending data or receiving data, and the subsequent process</pre>	TAU update manually can avoid automatic update of TAU cycle over time, so,non-service power consumption can be reduced; If no requirement in the application, ignore this step
7- Erase the historical frequency		
7-1	<pre>//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 // *Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above</pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
8- Exception handling or interruption		
8-1	1) The program or mcu shall add the interrupt method of timeout or failure of leshan platform registration, such as re-registration or reboot; 2) The program or mcu shall add the interrupt method of sending or receiving data timeout or failure, such as reboot; 3) The program or mcu should add interrupt methods that cannot enter PSM normally or cannot wake up PSM, such as reboot; 4) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout. If unable to enter PSM or wake up from PSM, it is recommended to compare the normal time to enter PSM or exit PSM. If the time exceeds, power off or reboot should can be operated

3.1.7 HTTP(s) Application

3.1.7.1 in Power-off Mode

Application	The terminal is connected to the HTTP(s) server, the interval of data reported/upload is relatively long, the application logic of mcu or program is relatively simple, and the PSM is not enabled
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QCRST=1 //Reboot >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY >> AT+QBAND=0 //If you did not execute the lock BAND in 5-1, skip the command >> OK >> AT+QSCCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=0 //Disable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware design
2-2	// Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6", "<APN>", "<username>", "<password>"	If APN needs to be configured for the SIM card, please perform the

	>> OK	command, others can be ignored
2-3	>> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK	If return NO READY, indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	//Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries	If the application design does not require this step, you can skip the step
2-5	>> AT+CSCON=1 >> OK	If the application design does not require this step, you can skip the step
2-6	>> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM >> +NCCID:89861122223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK	If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI and upload the data to the server. It will helps for troubleshoot problems.
2-7	// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals	
2-8	>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK	If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1

2-9	>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK	>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK		
2-11	>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK		CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR
2-12	>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK		Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times
3- Connect to HTTP(s) server			
H3-1	//Configure the parameters for HTTP >> AT+QHTTPCFG="contextid",0 >> >> OK >> AT+QHTTPCFG="requestheader",0 >> >> OK >> AT+QHTTPCFG="ssl",0,0 >> >> OK >> AT+QHTTPCFG="contenttype",1 >> >> OK		In the actual development, please configure parameters according to your requirement
H3-2	//Set the SSL parameters for HTTPs >> AT+QSSLCFG=0,0,"sslversion",4 >> >> OK >> AT+QSSLCFG=0,0,"dtls",1 >> >> OK >> AT+QSSLCFG=0,0,"dtlsversion",2 >> >> OK >> AT+QSSLCFG=0,0,"ciphersuite",0xFFFF >> >> OK		In the actual development, please configure parameters according to your requirement

	<pre>>> AT+QSSLCFG=0,0,"sni",1 >> >> OK</pre>	
H3-3	<pre>//Connect to HTTPs and send a GET or POST service >> AT+QIDNSCFG=0,"223.5.5.5","8.8.8.8" //Configure reliable DNS >> >> OK >> AT+QHTTTPURL=57,80 >> >>> >> https://ncu-receiver.fukuku.saico.dev/gas-meter/push/**** >> OK >> AT+QHTTTPGET=80 >> >> OK >> >> +QHTTTPGET: 0,200,99 >> AT+QHTTTPPOST=146 >> >>> >> {"DATETIME":"20240528T143744Z","IMEI":"868020030003890","NCU_FW_VER":100, "GAS_METER":1265035,"CSQ":29,"MCU_TEMP":28,"BAT_VOL":3665,"METER_TYPE":7} >> OK >> >> +QHTTTPPOST: 0,200,139 >> AT+QHTTTPREAD=139 >> >> +QHTTTPREAD: 139,0 >> {"module":{"code":"700.101.1001","name":"GAS_METER_RECEIVER.PUSH_ MEASUREMENT","version":"1.1.3"},"data":{"messageId":"194083404774019072"}} >> >> OK</pre>	In the actual development, please configure parameters according to your application
4- Power off after sending and receiving data		
4-1	<pre>>> AT+CFUN=0 //Set minimum function >> OK //Wait for the return OK, then mcu control to power off; If not return OK after running AT+CFUN=0 for a long period of time (for example, 20s), you can power off directly.</pre>	If the terminal is designed for power-off mode and powered off after data interaction is complete, you need to run AT+CFUN=0, then power off the terminal after return OK to avoid damage to the flash
5- Erase the historical frequency		
5-1	<pre>//If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCSEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 //Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and</pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without

	in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above	clearing the frequency again. Or wait for the next service cycle and try again.
--	---	--

6- Exception handling or interruption

6-1	4) The program or mcu needs to add the interrupt method of time-out or failure to register the AEP platform, such as re-registration or reboot. 5) The program or mcu needs to add the interrupt method of timeout or failure for sending or receiving data, such as reboot. 6) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout
-----	---	--

3.1.7.2 in PSM Mode

Application	PSM function is enabled, and only the HTTP(s) server is connected. The data is reported/upload frequently, and the application logic of mcu or program is relatively complex
--------------------	--

■ Reference for Process of Developing Application:

Index	Process of AT Command	Notes
1- Initial		
1-1	//Power on,initial >> >> RDY >> >> +CFUN: 1 >> >> +CPIN: READY	Boot log output, mcu can also determine whether it is normal boot; If the terminal needs to connect to the network immediately after power on, start from 2-1
1-2	//After powering on, if the terminal (mcu) does not need to connect to the network, or prioritize other tasks, you need to perform >> AT+CFUN=0 //Enter the deepsleep state >> OK >> AT+QSCCLK=1 //The deepsleep is enabled by default >> OK //If the terminal needs to connect to the network later, you can run >> AT+QRST=1 //Reboot >> OK	In the application design, when the module is powered on after the device is powered on, if the terminal has no network requirements temporarily or mcu gives priority to other tasks, cfun0 can be executed to enter the low power mode. If this requirement is not in the application design, skip this step to 2-1
2- Search and register network		
2-1	//Power on,initial >> >> RDY >> >> +CFUN: 1	+CPIN: NOT READY indicates that the module fails to check the sim card.so you need to check the SIM card itself or the pin connection and hardware

	<pre> >> >> +CPIN: READY >> AT+QBAND=0 /*If you did not execute the lock BAND in 7-1, skip the command >> OK >> AT+QSCLK=0 //Disable the deepsleep >> OK >> AT+CPSMS=1,,,"01000010","00000000" //Enable th PSM >> OK >> AT+CEDRXS=0,5 //Disable the eDRX >> OK >> AT+QNBIOTEVENT=1,1 //Enable the URC of PSM >> OK >> AT+QCFG="dsevent",1 //Enable the URC of Deepsleep >> OK </pre>	design By AT+CPSMS=1,, "<T3412/TAU>","<T3324>", you can configure the T3412 and T3324 timers properly which you need.at the same time, after the completion of the registration network, by AT+CEREG=5; +CEREG? You need to query the real value of T3324,T3412/TAU provided by the network
2-2	<pre> // Configure the APN based on the requirement of SIM card >> AT+QCGDEFCONT="IPV4V6","<APN>","<username>","<password>" >> OK </pre>	If APN needs to be configured for the SIM card, please perform the command, others can be ignored
2-3	<pre> >> AT+CPIN? //check the SIM status >> +CPIN: READY >> >> OK </pre>	If return NO READY,indicates the check of SIM card is failed. You need to check the SIM card and hardware. So the program can be directly powered off, or go to the above 1-2, into the low power state
2-4	<pre> //Check the attribute values of the module >> ATI //Query module identification >> Quectel_Ltd >> xxxxxxxx >> Revision: xxxxxxxx >> >> OK >> AT+CGSN=1 //Query the IMEI >> +CGSN:<IMEI> >> >> OK //Other queries </pre>	If the application design does not require this step, you can skip the step
2-5	<pre> >> AT+CSCON=1 >> OK </pre>	If the application design does not require this step, you can skip the step
2-6	<pre> >> >> +CSCON:1 //Indicates that the RRC connection is complete //To query the following parameters, it is recommended to query after return +CSCON:1, or query after the registration network is completed >> AT+CIMI //Query the IMSI >> 460113061353533 >> >> OK >> AT+NCCID //Query the CCID of SIM </pre>	If the application design does not require this step, you can skip the step In the application design of the terminal, you can execute AT+QENG=0 to obtain the relevant network and signal reference, and to encode RSRP, SNR, CELLID, EARFCN and PCI

	<pre>>> +NCCID:8986112223000411769 >> >> OK >> AT+QENG=0 //Query the information about the current camp on the cell >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK</pre>	and upload the data to the server. It will helps for troubleshoot problems.	
2-7	<pre>// Query the network registration status >> AT+CEREG? //Query the network registration status >> +CEREG:0,2 >> >> OK //Periodic queries, such as 500ms intervals</pre>		
2-8	<pre>>> AT+CEREG? >> +CEREG:0,0 //+CEREG:0,2 >> >> OK</pre>	If the query only returns +CEREG:0,0 or +CEREG:0,2 within the search time (no less than 2 minutes); the program goes to 5-1	
2-9	<pre>>> AT+CEREG? >> +CEREG:0,1 //+CEREG:0,5 (roaming) //the registered successfully >> >> OK</pre>	<pre>>> AT+CEREG? >> +CEREG:0,3 //the registration denied >> >> OK</pre>	If the program finally returns +CEREG:0,3 within the search time (e.g. 2 minutes); Restart or try again in the next cycle. If +CEREG:0,3 is still returned after multiple attempts, it is recommended to check the SIM card
2-10	<pre>>> AT+CGPADDR //Query the IP address obtained >> +CGPADDR: 0,"10.21.53.152","2409:8d30:0114:0242:17ab:01f8:98b0:032e" >> >> OK</pre>		
2-11	<pre>>> AT+CSQ //Query the CSQ >> +CSQ:xx,99 >> >> OK</pre>	CSQ=(RSSI+113)/2 CSQ corresponds to signal reference RSSI. In actual applications, it is recommended to run AT+QENG=0 to obtain RSRP and SNR	
2-12	<pre>>> AT+CCLK? //Query the current date and time >> +CCLK: "24/01/16,08:55:19+32" >> >> OK</pre>	Time conversion: 24/01/16,08:55:19+32/4(h)= 2024/01/16,16:55:19 If the default time is returned, pls query the time for multiple times	
3- Access the HTTP(s) server			
H3-1	<pre>//Configure the parameters for HTTP >> AT+QHTTPCFG="contextid",0 >> >> OK >> AT+QHTTPCFG="requestheader",0</pre>	In the actual development, please configure parameters according to your requirement	

	<pre>>> >> OK >> AT+QHTTPCFG="ssl",0,0 >> >> OK >> AT+QHTTPCFG="contenttype",1 >> >> OK</pre>	
H3-2	<pre>//Set the SSL parameters for HTTPs >> AT+QSSLCFG=0,0,"sslversion",4 >> >> OK >> AT+QSSLCFG=0,0,"dtls",1 >> >> OK >> AT+QSSLCFG=0,0,"dtlsversion",2 >> >> OK >> AT+QSSLCFG=0,0,"ciphersuite",0xFFFF >> >> OK >> AT+QSSLCFG=0,0,"sni",1 >> >> OK</pre>	In the actual development, please configure parameters according to your requirement
H3-3	<pre>//Connect to HTTPs and send a GET or POST service >> AT+QIDNSCFG=0,"223.5.5.5","8.8.8.8" //Configure reliable DNS >> >> OK >> AT+QHTTTPURL=57,80 >> >> > >> https://ncu-receiver.fukuku.saico.dev/gas-meter/push/**** >> OK >> AT+QHTTTPGET=80 >> >> OK >> >> +QHTTTPGET: 0,200,99 >> AT+QHTTTPPOST=146 >> >> > >> {"DATETIME":"20240528T143744Z","IMEI":"868020030003890","NCU_FW_VER":100, "GAS_METER":1265035,"CSQ":29,"MCU_TEMP":28,"BAT_VOL":3665,"METER_TYPE":7} >> OK >> >> +QHTTTPPOST: 0,200,139 >> AT+QHTTTPREAD=139 >> >> +QHTTTPREAD: 139,0</pre>	In the actual development, please configure parameters according to your application

	<pre>>> {"module":{"code":"700.101.1001","name":"GAS_METER_RECEIVER.PUSH_MEASUREMENT","version":"1.1.3"},"data":{"messageId":"194083404774019072"}} >> >> OK</pre>	
4- Feature of RAI		
Feature of RAI	1) After the data interaction is completed, you can run AT+QPING=0,"8.8.8.8",4,1,32,1	
R4-1	<pre>>> AT+QPING=0,"8.8.8.8",4,1,32,1 //QPING method with RAI Flag >> OK >> >> +QPING: 0,8.8.8.8,32,729,51 >> >> +QPING: 0,1,1,0,729,729,729 >> >> +CSCON:0 //If +CSCON:0 is returned within 0-2s, RAI is effective >> AT+QSCCLK=1 //Enable deepsleep mode >> OK</pre>	RAI implementation method
5- Enter status PSM and Deepsleep		
5-1	<pre>>> >> +QNBIOEVENT: "ENTER PSM" //Enter the PSM state >> >> +QNBIOEVENT: "ENTER DEEPSLEEP" //Enter the deepsleep state</pre>	
6- Exit status of Deepsleep and PSM		
H6-1-1	<pre>//BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state //Recreate the HTTP connection H3-1,H3-2,H3-3 >> >> +QNBIOEVENT: "EXIT PSM" //Exit the PSM state >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QHHTTPPOST: 0,200,139 //The POST was established successfully Go to 6-2,or goto T3-3 for sending data,or goto L3-5 for receiving data, and the subsequent process</pre>	Method to trigger PSM wake-up
T6-1-2	<pre>//If you want to obtain the accurate signal reference in the current scene immediately after the PSM is woked up, please refer to //BC660K&BC950K support to wake up deepsleep by executing AT command or pulling down PSM_EINT pin >> >> +QNBIOEVENT: "EXIT DEEPSLEEP" //Exit the deepsleep state >> AT+QPING=0,"8.8.8.8",4,1,32 //Trigger PSM wake-up >> >> OK >> >> +QNBIOEVENT: "EXIT PSM"</pre>	If the program or mcu needs to deal with other tasks, such as collecting the base station cell signal after wake-up; It is recommended to refer to this method to trigger PSM wake-up and obtain the network signal after wake-up. If no such requirement in the program, ignore the process

	<pre> >> >> +CSCON: 1 //Indicates that the RRC connection is established after the PSM is wakeup >> >> +QPING: 0,8.8.8.8,32,1284,51 >> >> +QPING: 0,1,1,0,1284,1284,1284 >> AT+QENG=0 //Query signal reference >> +QENG: 0,3686,11,121,"05C4EF33",-75,-8,-65,14,8,"4C10",0,9,3 >> >> OK //Recreate the HTTP connection H3-1,H3-2,H3-3 //It is recommended to report the data of relevant signal reference over HTTP "rsrp=-75,snr=14,cellid=05C4EF33,earfcn=3686,pci=121" Go to 6-2,or goto R4-1 </pre>	
6-2	<pre> //Manual TAU update >> AT+CPSMS=0 >> OK >> AT+CPSMS=1,,,"01000010","00000000" >> OK Go to R4-1 </pre>	TAU update manually can avoid automatic update of TAU cycle over time, so,non-service power consumption can be reduced; If no requirement in the application, ignore this step
7- Erase the historical frequency		
7-1	<pre> //If 2-8 the registration network is not successful within the set search time(such as 2min), go to >> AT+CFUN=0 //Erase the historical frequency based on CFUN0 >> OK >> AT+QCEARFCN //Erase the historical frequency >> OK >> AT+QBAND=1,28 //Lock a specific frequency band. Note that it is not recommended for non-specific situations, Unless you already know the BANDs in the area where the device is located and in order to speed up your search for a radio network. >> OK >> AT+QRST=1 //Reboot, and re-search >> OK Follow 2-7 above </pre>	As described in 2-8, it is suggested that in the program design, after the first search fails to time out, the frequency clearing program must be executed. After run, follow the 2-7 to check the search status again; If the research fails to time out, you are advised to reboot without clearing the frequency again. Or wait for the next service cycle and try again.
8- Exception handling or interruption		
8-1	1) The program or mcu shall add the interrupt method of timeout or failure of lshan platform registration, such as re-registration or reboot; 2) The program or mcu shall add the interrupt method of sending or receiving data timeout or failure, such as reboot; 3) The program or mcu should add interrupt methods that cannot enter PSM normally or cannot wake up PSM, such as reboot; 4) In the case of exceptions, when the program or mcu performs hardware reset or power-off directly, you need to execute AT+CFUN=0 first, and return OK, then control hardware reset or power-off; But software reset or reboot does not run AT+CFUN=0.	If the terminal has strict requirements on power consumption, it is recommended that the program reasonably control timeout. If unable to enter PSM or wake up from PSM, it is recommended to compare the normal time to enter PSM or exit PSM. If the time exceeds,

		power off or reboot should can be operated
--	--	---