




RF TEST REPORT

Report No.	:	TBR-C-202601-0256-8	
Applicant	:	Chengdu ROSESELSA Technology Co., Ltd.	
Equipment Under Test (EUT)			
EUT Name	:	Wireless headphones	
Model No.	:	CERAMICS ULTRA	
Series Model No.	:	CERAMICS ULTRA 2	
Brand Name	:	ROSESELSA	
Receipt Date	:	2025-11-26	
Test Date	:	2025-11-26 to 2025-12-03	
Issue Date	:	2026-02-06	
Rule Part(s)	:	MIC Notice No.88 Annex 43	
Test Standards	:	ARIB STD-T66 Article 2 paragraph 1 item 19	
Conclusions	:	PASS	
		In the configuration tested, the EUT complied with the standards specified above.	
Tested By	:	Lily Zhang	
Reviewed By	:	Henry Huang	
Approved By	:	Ivan Su	
This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.			

Contents

CONTENTS	2
1. GENERAL INFORMATION	4
1.1 Description of Device (EUT)	4
1.2 Channle List	5
2. DESCRIPTION OF TEST	6
2.1 Summary of Test	6
2.2 Assistant Equipment Used for Test	7
2.3 Block Diagram of Test Setup	7
2.4 Test Mode Description	7
2.5 Test Conditions	8
2.6 Measurement Uncertainty (95% confidence levels, k=2)	8
2.7 Test Lab Information	9
2.8 Test Equipment	9
3. TRANSMITTER TEST	10
3.1 Frequency Error	10
3.2 Antenna Power	11
3.3 Occupied Bandwidth	12
3.4 Spread Bandwidth	13
3.5 Dwell Time	14
3.6 Spurious Emission of TX	15
3.7 Interference Prevention Function	16
4. RECEIVER TEST	17
4.1 Secondary Radiated Emissions	17
5. TEST SETUP PHOTOS	18
6. EUT PHOTOS	19
7. LABEL INFORMATION	27
8. CONSTRUCTION PROTECTION CONFIRMATION METHOD	28
8.1 Requirement	28
8.2 Confirmation Method	28
APPENDIX A: FREQUENCY ERROR	29
APPENDIX B: ANTENNA POWER	34
APPENDIX C: OCCUPIED BANDWIDTH	36
APPENDIX D: SPREAD BANDWIDTH	41
APPENDIX E: DWELL TIME	46
APPENDIX F: SPURIOUS EMISSION OF TX	65
APPENDIX G: SPURIOUS EMISSION OF RX	115



Revision History

Report No.	Version	Description	Issued Date
TBR-C-202508-0228-1	Rev.01	Initial issue of report	2025-12-04
TBR-C-202601-0256-8	Rev.02	The second release has updated the names and addresses of the applicants and manufacturers, as well as the model numbers. No changes have been made to the test data.	2026-02-06



1. General Information

1.1 Description of Device (EUT)

EUT	:	Wireless headphones
Model No.	:	CERAMICS ULTRA, CERAMICS ULTRA 2
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name.
Power supply	:	INPUT: DC 5V
Power supply (Charger Box)	:	DC 3.7V 400mAh 1.48Wh Rechargeable Li-ion battery
Power supply (Earphone)	:	DC 3.7V 50mAh 0.185Wh Rechargeable Li-ion battery
Radio Technology	:	Bluetooth V5.0
Operation frequency	:	2402MHz~2480MHz
Modulation	:	GFSK, Pi/4-QPSK, 8-DPSK
Data Rate	:	1Mbps, 2Mbps, 3Mbps
Antenna Type	:	FPC antenna, Maximum Gain: -1.48dBi
Declared Output Power	:	Normal Operation (79 Channels): 0.1mW/MHz
Applicant	:	Chengdu ROSELSA Technology Co., Ltd.
Address	:	Room 302, 3rd Floor, Building 4, Yingcaijiayuan, No.569 East Jinfu Road, Zitong Community, Tianfu Block, Wenjiang District, Chengdu, Sichuan, China
Manufacturer	:	Chengdu ROSELSA Technology Co., Ltd.
Address	:	Room 302, 3rd Floor, Building 4, Yingcaijiayuan, No.569 East Jinfu Road, Zitong Community, Tianfu Block, Wenjiang District, Chengdu, Sichuan, China
Software Version	:	BTW25041-ROSE-20250812-V0.0.10
Hardware Version	:	v1.2
Remark: (1)The antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab. (2)The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.		



1.2 Channle List

Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		



2. Description of Test

2.1 Summary of Test

CLAUSE (ARIB STD-T66)	TEST PARAMETER	RESULTS
Transmitter Parameters		
3.2 (2)	Antenna Power	PASS
3.2 (3)	Tolerances for Antenna Power	PASS
3.2 (4)	Frequency Tolerance	PASS
3.2 (5)	Transmission Rate	PASS
3.2 (7)	Occupied Frequency Bandwidth	PASS
3.2 (8)	Spread Bandwidth	PASS
3.2 (9)	Process Gain	PASS
3.2 (10)	Number of Carriers	N/A
3.2 (11)	Dwell Time	PASS
3.2 (6)	Spurious Emissions	PASS
/	Interference prevention function	PASS
/	Carrier Sensing function	N/A
Receiver Parameters		
3.3 (1)	Secondary Radiated Emissions	PASS

Note: N/A is an abbreviation for Not Applicable.



2.2 Assistant Equipment Used for Test

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	Trade Name
Notebook	inspiron 5509	----	DELL

2.3 Block Diagram of Test Setup



Test PC run test software provided by client to control EUT work in test mode as described in clause 2.4

2.4 Test Mode Description

The test software (**WQ7033_BQB_TEST_V1.13**) was used to control EUT work in Continuous TX mode, and select test channel, wireless mode:

Tested Mode, Channel and Data Rate Information		
Mode	Channel	Frequency (MHz)
Carrier Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
Pi/4-QPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
8DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
GFSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
Pi/4-QPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
8DPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK Rx Mode	CH0	2402
	CH39	2441
	CH78	2480
8DPSK Rx Mode	CH0	2402
	CH39	2441
	CH78	2480
Parameters	1	



Test Voltage Information

Voltage Fluctuation Test	Power supply voltage DC (Normal)	Power supply voltage DC (+10%)	Power supply voltage DC (-10%)
Input To EUT	DC 3.7V	DC 4.07V	DC 3.33V
Output To RF Module	DC 3.3V	DC 3.334V	DC 3.232V
Voltage Variation (%)	----	+1%	-2%

During the input supply voltage to the EUT from the external power source is varied by $\pm 10\%$, the fluctuation of input voltage to the circuit of RF unit of test equipment is exceed $\pm 1\%$. So, all measurement has been conducted by normal and limit voltage.

2.5 Test Conditions

Temperature range	24°C
Humidity range	48%
Pressure range	102kPa

2.6 Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Bandwidth	0.2KHz	/
Antenna Power	0.33dB	/
Frequency Tolerance	2.8×10^{-4} MHz	/
Conducted spurious emission	0.13dB	/



2.7 Test Lab Information

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.

2.8 Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Rohde&Schwarz	FSV40-N	102197	Jun. 16, 2025	Jun. 15, 2026
RF Control Unit	Tonsced	JS0806-2	21F8060439	Aug. 27, 2025	Aug. 26, 2026
Digital Oscilloscope	Tektronix	TDS3014B	C011238	Jun. 16, 2025	Jun. 15, 2026
DC power supply	WTKS POWER	WSD-6020	W210916060 20P01	Aug. 27, 2025	Aug. 26, 2026
Calibration agencies:			Guangzhou LiSai Metrology & Test Co., Ltd. CCIC (Shenzhen) Metrology & Testing Service Co.,Ltd		
Note: Calibration by the calibration agencies listed in the table correspond to paragraph 4 (ii) (c) of Article 24-2 in the Radio Law.					
☐ (a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) or a designated calibration agency under Article 102-18-1 of the Radio Act.					
☐ (b) Calibration conducted based on the regulations of Article 135 or 144 of the Measurement Act.					
☒ (c) Calibration conducted in foreign countries, which is equivalent to calibration conducted by the NICT or a designated calibration agency under Article 102-18-1 of the Radio Act.					
☐ (d) Calibration, etc. conducted by using measuring instruments and other facilities listed at the bottom of appended table 3 of the Radio Act, which is to have been calibrated as described in (a) through (c) above.					




3. Transmitter Test

3.1 Frequency Error

3.1.1 Test Limit

+/- 50×10^{-6} or less (50ppm)

3.1.2 Block Diagram of Test Setup



3.1.3 Test Procedure

- (1) Configure EUT and assistant system
- (2) Set EUT work in carrier Tx mode as described in clause 2.4
- (3) Connected the EUT's antenna port to the Spectrum Analyzer by suitable

attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 10 KHz.

Video BW: 10 KHz.

Span: 1MHz.

Detector: Peak.

Trace Mode: Max Hold.

- (4) When the trace is complete, find the peak value of the power envelope and record the frequency.

3.1.4 Deviation From Test Standard

No deviation

3.1.5 Test Result

Please refer to the Appendix A.




3.2 Antenna Power

3.2.1 Test Limit

Antenna Power Limit	3mW/MHz
EIRP Limit	6.91dBm/MHz
Tolerance	+20%

3.2.2 Block Diagram of Test Setup



3.2.3 Test Procedure

Connect the UUT to the spectrum analyzer and use the following settings:

Centre Frequency: The centre frequency of the channel under test.

RBW: 1 MHz/VBW: 3 MHz/ Span: Wide enough to cover the complete power envelope of the signal of the EUT. / Detector: Peak. / Trace Mode: Max Hold.

When the trace is complete, find the peak value of the power envelope and record the frequency. Then turn to the spectrum settings as following:

RBW: 1 MHz/VBW: 1 MHz/ Span: 0Hz, find the maximum value.

Calculated the Maximum deviation and recorded the results.

3.2.4 Deviation From Test Standard

No deviation

3.2.5 Test Result

Please refer to the Appendix B.




3.3 Occupied Bandwidth

3.3.1 Test Limit

Permissible value for occupied bandwidth using the FH system, a hybrid system combining DS and FH systems, or a hybrid system combining FH and OFDM systems shall be 83.5 MHz or less, while necessary bandwidth (minimum occupied bandwidth sufficient to ensure information transmission of required quality at a required transmission rate for the system used under specified conditions for a given emission type) using a system other than any of the above shall be 26 MHz or less.

3.3.2 Block Diagram of Test Setup



3.3.3 Test Procedure

Setting of SA is following as: RBW:300 kHz / VBW: 300 kHz / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold

EUT have transmitted the maximum modulation signal and fixed channelize (For DSSS or OFDM Device) or continuous maximum power of hopping mode (For FHSS Device). SA set to 99% of occupied bandwidth to measure occupied bandwidth. The limit is less than 26 MHz (For DSSS or OFDM Device) or 83.5 MHz (For FHSS Device).

3.3.4 Deviation From Test Standard

No deviation

3.3.5 Test Result

Please refer to the Appendix C.




3.4 Spread Bandwidth

3.4.1 Test Limit

Spread Bandwidth $\geq$ 500 kHz, Process Gain $\geq$ 5

3.4.2 Block Diagram of Test Setup



3.4.3 Test Procedure

Setting of SA is following as: RBW:300 kHz / VBW: 300 kHz / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold

EUT have transmitted the maximum modulation signal and fixed channelize (For DSSS or OFDM Device) or continuous maximum power of hopping mode (For FHSS Device). SA set to 90% of occupied bandwidth to measure Spread Spectrum Bandwidth and must greater than 500 kHz.

3.4.4 Deviation From Test Standard

No deviation

3.4.5 Test Result

Please refer to the Appendix D.




3.5 Dwell Time

3.5.1 Test Limit

Frequency dwell time (time during which radio waves continue to be emitted at a specified frequency) of a transmitting equipment using the FH system shall be 0.4 seconds or less.

3.5.2 Block Diagram of Test Setup



3.5.3 Test Procedure

- (1) Configure EUT and assistant system
- (2) Set EUT work in test mode as described in clause 2.4
- (3) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 1MHz.

Video BW: 1MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Max Hold.

Sweep: Video Trigger

- (4) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

3.5.4 Deviation From Test Standard

No deviation

3.5.5 Test Result

Please refer to the Appendix E.




3.6 Spurious Emission of TX

3.6.1 Test Limit

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows:

FREQUENCIES (MHz)	LIMIT
30.0MHz to 1000MHz	$\leq 2.5\mu\text{W}/\text{MHz}$
1000MHz to 2387MHz	$\leq 2.5\mu\text{W}/\text{MHz}$
2387.0MHz to 2400.0MHz	$\leq 25\mu\text{W}/\text{MHz}$
2483.5MHz to 2496.5MHz	$\leq 25\mu\text{W}/\text{MHz}$
2496.5MHz to 13000.0MHz	$\leq 2.5\mu\text{W}/\text{MHz}$

3.6.2 Block Diagram of Test Setup



3.6.3 Test Procedure

- (1) Configure EUT and assistant system
- (2) Set EUT work in test mode as described in clause 2.4
- (3) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:
Below 1G: BW: 100kHz. Video BW: 100kHz.
Above 1G: BW: 1MHz. Video BW: 1MHz.
Detector: Peak. Trace Mode: Max Hold.
- (4) All the emissions from 30MHz to 13.0GHz were measured and record.

3.6.4 Deviation From Test Standard

No deviation

3.6.5 Test Result

Please refer to the Appendix F.



3.7 Interference Prevention Function

3.7.1 Test Limit

Item	Limits
Identification	≥48 bits
MAC IP List	MAC Scan

3.7.2 Block Diagram of Test Setup



3.7.3 Test Procedure

1. In the case that the EUT has the function of automatically transmitting the identification code: a. Transmit the predetermined identification codes form EUT. b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification ocde: a. Transmit the predetermined identification codes form the counterpart. b . Check if communication is normal. c. Transmit the signals other than predetermined ID codes form the counterpart. d. check if the EUT stops the transmission, or if it displays that idnetification codes are different from the predetermined ones.

3.7.4 Deviation From Test Standard

No deviation

3.7.5 Test Result

Temperature:	24℃	Humidity:	48%RH
Mac:	84:9D:4B:00:EB:07		
Test result:	CONFORM		
Tested by:	Lily.zhang		




4. Receiver Test

4.1 Secondary Radiated Emissions

4.1.1 Test Limit

The limit on secondary emissions radiated from the receiving equipment within which the function of other radio equipment will not be impaired shall be, in terms of the power of a dummy antenna circuit that has the same electrical constant as the receiving antenna, 4 nW or less at a frequency below 1 GHz and 20 nW or less at a frequency of 1 GHz or higher as measured using the circuit.

4.1.2 Block Diagram of Test Setup



4.1.3 Test Procedure

- (1) Configure EUT and assistant system
- (2) Set EUT work in test mode as described in clause 2.4
- (3) Connected the EUT's antenna port to the Spectrum Analyzer by suitable

attenuator, set the Spectrum Analyzer as below:

Below 1G: BW: 100kHz. Video BW: 100kHz.

Above 1G: BW: 1MHz. Video BW: 1MHz.

Detector: Peak. Trace Mode: Max Hold.

- (4) All the emissions from 30MHz to 13.0GHz were measured and record.

4.1.4 Deviation From Test Standard


No deviation

4.1.5 Test Result

Please refer to the Appendix G.



5. Test Setup Photos



6. EUT Photos

Photo 1 Appearance of EUT




Photo 2 Appearance of EUT




Photo 3 Appearance of EUT




Photo 4 Appearance of EUT




Photo 5 Appearance of EUT




Photo 6 Appearance of EUT




Photo 7 Appearance of EUT



Photo 8 Internal of EUT




Photo 9 Internal of EUT




Photo 10 Internal of EUT




Photo 11 Appearance of PCB




Photo 12 Appearance of PCB




Photo 13 Appearance of PCB




Photo 14 Appearance of PCB




Photo 15 Appearance of PCB






Photo 16 Appearance of PCB




7. Label Information

Label

Unit: mm



Label Location




8. Construction Protection Confirmation Method

8.1 Requirement

The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.

8.2 Confirmation Method

RF module is welded directly to PCB board. So the end user can not to modify or change the RF Parts easily.



Appendix A: Frequency Error

Test Result


Test Condition	Test Mode	Antenna	Freq(MHz)	Result[ppm]	Limit[ppm]	Verdict
NTNV	Single carrier	Ant1	2402	-7.91008	±50	PASS
			2441	-7.78370	±50	PASS
			2480	-7.66129	±50	PASS
NTLV	Single carrier	Ant1	2402	-7.91008	±50	PASS
			2441	-7.78370	±50	PASS
			2480	-7.66129	±50	PASS
NTHV	Single carrier	Ant1	2402	-7.91008	±50	PASS
			2441	-7.78370	±50	PASS
			2480	-7.66129	±50	PASS


Remark: Only show the test data of worst condition.

Both headphones were tested, and only the worst mode was recorded.(Left Earphone)




Test Graphs






NTLV_Ant1_2402



NTLV_Ant1_2441




NTLV_Ant1_2480






NTHV_Ant1_2402




NTHV_Ant1_2441



NTHV_Ant1_2480





Appendix B: Antenna Power

Test Result

Antenna Power(Left Earphone)									
Test Condition	Test Mode	Antenna	Freq(MHz)	Result (dBm)	Result (mW)	90%BW (MHz)	Result (mW/MHz)	Limit (mW/MHz)	Verdict
NTNV	DH5	Ant1	Hop	6.15	4.1210	70.729	0.0583	≤3	PASS
	2DH5	Ant1	Hop	1.90	1.5488	70.929	0.0218	≤3	PASS
	3DH5	Ant1	Hop	3.40	2.1878	72.328	0.0302	≤3	PASS
LTVN	DH5	Ant1	Hop	6.16	4.1305	70.929	0.0582	≤3	PASS
	2DH5	Ant1	Hop	1.88	1.5417	70.929	0.0217	≤3	PASS
	3DH5	Ant1	Hop	3.36	2.1677	70.729	0.0306	≤3	PASS
HTNV	DH5	Ant1	Hop	6.11	4.0832	69.730	0.0586	≤3	PASS
	2DH5	Ant1	Hop	1.86	1.5346	70.929	0.0216	≤3	PASS
	3DH5	Ant1	Hop	3.24	2.1086	75.125	0.0281	≤3	PASS

Remark: Only show the test data of worst condition.

Tolerance(Left Earphone)								
Test Condition	Test Mode	Antenna	Freq(MHz)	Power (mW/MHz)	RatedPower (mW/MHz)	Result (%)	Limit (%)	Verdict
NTNV	DH5	Ant1	Hop	0.0583	0.1	-41.7	+20	PASS
	2DH5	Ant1	Hop	0.0218	0.1	-78.2	+20	PASS
	3DH5	Ant1	Hop	0.0302	0.1	-69.8	+20	PASS
LTVN	DH5	Ant1	Hop	0.0582	0.1	-41.8	+20	PASS
	2DH5	Ant1	Hop	0.0217	0.1	-78.3	+20	PASS
	3DH5	Ant1	Hop	0.0306	0.1	-69.4	+20	PASS
HTNV	DH5	Ant1	Hop	0.0586	0.1	-41.4	+20	PASS
	2DH5	Ant1	Hop	0.0216	0.1	-78.4	+20	PASS
	3DH5	Ant1	Hop	0.0281	0.1	-71.9	+20	PASS

Remark: Only show the test data of worst condition.



Antenna Power(Right Earphone)									
Test Condition	Test Mode	Antenna	Freq(MHz)	Result (dBm)	Result (mW)	90%BW (MHz)	Result (mW/MHz)	Limit (mW/MHz)	Verdict
NTNV	DH5	Ant1	Hop	5.98	3.9628	70.727	0.0560	≤3	PASS
	2DH5	Ant1	Hop	1.83	1.5241	70.918	0.0215	≤3	PASS
	3DH5	Ant1	Hop	3.28	2.1281	72.320	0.0294	≤3	PASS
LTVN	DH5	Ant1	Hop	5.97	3.9537	70.893	0.0558	≤3	PASS
	2DH5	Ant1	Hop	1.81	1.5171	70.893	0.0214	≤3	PASS
	3DH5	Ant1	Hop	3.26	2.1184	70.714	0.0300	≤3	PASS
HTNV	DH5	Ant1	Hop	6.01	3.9902	69.724	0.0572	≤3	PASS
	2DH5	Ant1	Hop	1.83	1.5241	70.911	0.0215	≤3	PASS
	3DH5	Ant1	Hop	3.16	2.0701	75.117	0.0276	≤3	PASS

Remark: Only show the test data of worst condition.

Tolerance(Right Earphone)								
Test Condition	Test Mode	Antenna	Freq(MHz)	Power (mW/MHz)	RatedPower (mW/MHz)	Result (%)	Limit (%)	Verdict
NTNV	DH5	Ant1	Hop	0.0560	0.1	-44	+20	PASS
	2DH5	Ant1	Hop	0.0215	0.1	-78.5	+20	PASS
	3DH5	Ant1	Hop	0.0294	0.1	-70.6	+20	PASS
LTVN	DH5	Ant1	Hop	0.0558	0.1	-44.2	+20	PASS
	2DH5	Ant1	Hop	0.0214	0.1	-78.6	+20	PASS
	3DH5	Ant1	Hop	0.0300	0.1	-70	+20	PASS
HTNV	DH5	Ant1	Hop	0.0572	0.1	-42.8	+20	PASS
	2DH5	Ant1	Hop	0.0215	0.1	-78.5	+20	PASS
	3DH5	Ant1	Hop	0.0276	0.1	-72.4	+20	PASS

Remark: Only show the test data of worst condition.



Appendix C: Occupied Bandwidth

Test Result


Test Condition	Test Mode	Antenna	Freq(MHz)	Result [MHz]	Limit [MHz]	Verdict
NTNV	DH5	Ant1	Hop	78.122	≤83.5	PASS
	2DH5	Ant1	Hop	78.322	≤83.5	PASS
	3DH5	Ant1	Hop	78.122	≤83.5	PASS
NTLV	DH5	Ant1	Hop	78.322	≤83.5	PASS
	2DH5	Ant1	Hop	77.922	≤83.5	PASS
	3DH5	Ant1	Hop	78.322	≤83.5	PASS
NTHV	DH5	Ant1	Hop	78.122	≤83.5	PASS
	2DH5	Ant1	Hop	77.722	≤83.5	PASS
	3DH5	Ant1	Hop	78.122	≤83.5	PASS


Remark: Only show the test data of worst condition.

Both headphones were tested, and only the worst mode was recorded.(Left Earphone)




Test Graphs






NTLV_DH5_Ant1_Hop




NTLV_2DH5_Ant1_Hop



NTLV_3DH5_Ant1_Hop






NTHV_DH5_Ant1_Hop




NTHV_2DH5_Ant1_Hop



NTHV_3DH5_Ant1_Hop





Appendix D: Spread Bandwidth

Test Result


Test Condition	Test Mode	Antenna	Freq(MHz)	Result [MHz]	Limit [MHz]	SpreadFactor	Limit	Verdict
NTNV	DH5	Ant1	Hop	70.729	≥ 0.5	70.729	>5	PASS
	2DH5	Ant1	Hop	70.929	≥ 0.5	35.465	>5	PASS
	3DH5	Ant1	Hop	72.328	≥ 0.5	24.109	>5	PASS
NTLV	DH5	Ant1	Hop	70.929	≥ 0.5	70.929	>5	PASS
	2DH5	Ant1	Hop	70.929	≥ 0.5	35.465	>5	PASS
	3DH5	Ant1	Hop	70.729	≥ 0.5	23.576	>5	PASS
NTHV	DH5	Ant1	Hop	69.730	≥ 0.5	69.730	>5	PASS
	2DH5	Ant1	Hop	70.929	≥ 0.5	35.465	>5	PASS
	3DH5	Ant1	Hop	75.125	≥ 0.5	25.042	>5	PASS


Remark: Only show the test data of worst condition.

Both headphones were tested, and only the worst mode was recorded.(Left Earphone)




Test Graphs






NTLV_DH5_Ant1_Hop




NTLV_2DH5_Ant1_Hop




NTLV_3DH5_Ant1_Hop






NTHV_DH5_Ant1_Hop



NTHV_2DH5_Ant1_Hop



NTHV_3DH5_Ant1_Hop



Appendix E: Dwell Time

Test Result


Test Condition	Test Mode	Antenna	Freq(MHz)	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit [s]	Verdict
NTNV	DH1	Ant1	Hop	0.41	110	0.045	≤0.4	PASS
	DH3	Ant1	Hop	1.66	110	0.183	≤0.4	PASS
	DH5	Ant1	Hop	2.87	60	0.172	≤0.4	PASS
	2DH1	Ant1	Hop	0.38	100	0.038	≤0.4	PASS
	2DH3	Ant1	Hop	1.62	70	0.113	≤0.4	PASS
	2DH5	Ant1	Hop	2.87	40	0.115	≤0.4	PASS
	3DH1	Ant1	Hop	0.38	110	0.042	≤0.4	PASS
	3DH3	Ant1	Hop	1.62	70	0.113	≤0.4	PASS
	3DH5	Ant1	Hop	2.87	30	0.086	≤0.4	PASS
NTLV	DH1	Ant1	Hop	0.41	150	0.062	≤0.4	PASS
	DH3	Ant1	Hop	1.66	70	0.116	≤0.4	PASS
	DH5	Ant1	Hop	2.87	90	0.258	≤0.4	PASS
	2DH1	Ant1	Hop	0.38	90	0.034	≤0.4	PASS
	2DH3	Ant1	Hop	1.62	90	0.146	≤0.4	PASS
	2DH5	Ant1	Hop	2.87	90	0.258	≤0.4	PASS
	3DH1	Ant1	Hop	0.38	110	0.042	≤0.4	PASS
	3DH3	Ant1	Hop	1.62	100	0.162	≤0.4	PASS
	3DH5	Ant1	Hop	2.87	80	0.23	≤0.4	PASS
NTHV	DH1	Ant1	Hop	0.41	110	0.045	≤0.4	PASS
	DH3	Ant1	Hop	1.66	90	0.149	≤0.4	PASS
	DH5	Ant1	Hop	2.87	30	0.086	≤0.4	PASS
	2DH1	Ant1	Hop	0.38	110	0.042	≤0.4	PASS
	2DH3	Ant1	Hop	1.62	30	0.049	≤0.4	PASS
	2DH5	Ant1	Hop	2.87	20	0.057	≤0.4	PASS
	3DH1	Ant1	Hop	0.38	110	0.042	≤0.4	PASS
	3DH3	Ant1	Hop	1.62	30	0.049	≤0.4	PASS
	3DH5	Ant1	Hop	2.87	50	0.144	≤0.4	PASS


Remark: Only show the test data of worst condition.

Both headphones were tested, and only the worst mode was recorded.(Left Earphone)





Test Graphs







NTNV_DH5_Ant1_Hop





NTNV_2DH1_Ant1_Hop







NTNV_2DH3_Ant1_Hop






NTNV_2DH5_Ant1_Hop




NTNV_3DH1_Ant1_Hop






Date: 3.DEC.2025 15:09:13




Date: 3.DEC.2025 15:09:24

NTNV_3DH3_Ant1_Hop





Date: 3.DEC.2025 15:10:50






NTNV_3DH5_Ant1_Hop




NTLV_DH1_Ant1_Hop






Date: 3.DEC.2025 14:49:05




Date: 3.DEC.2025 14:49:15

NTLV_DH3_Ant1_Hop





Date: 3.DEC.2025 15:06:24







NTLV_DH5_Ant1_Hop





NTLV_2DH1_Ant1_Hop







NTLV_2DH3_Ant1_Hop






NTLV_2DH5_Ant1_Hop




NTLV_3DH1_Ant1_Hop






Date: 3.DEC.2025 15:09:42




Date: 3.DEC.2025 15:09:53

NTLV_3DH3_Ant1_Hop





Date: 3.DEC.2025 15:11:19






NTLV_3DH5_Ant1_Hop




NTHV_DH1_Ant1_Hop






Date: 3.DEC.2025 14:49:33




Date: 3.DEC.2025 14:49:44

NTHV_DH3_Ant1_Hop





Date: 3.DEC.2025 15:06:54






NTHV_DH5_Ant1_Hop




NTHV_2DH1_Ant1_Hop






Date: 3.DEC.2025 14:59:17




Date: 3.DEC.2025 14:59:28

NTHV_2DH3_Ant1_Hop





Date: 3.DEC.2025 15:08:33






NTHV_2DH5_Ant1_Hop




NTHV_3DH1_Ant1_Hop






Date: 3.DEC.2025 15:10:12




Date: 3.DEC.2025 15:10:23

NTHV_3DH3_Ant1_Hop



Date: 3.DEC.2025 15:11:48





Appendix F: Spurious Emission of TX

Test Result

Test Condition	Test Mode	Antenna	Freq (MHz)	Freq.Range [MHz]	Result [dBm]	Limit [dBm]	Result [μW]	Limit [μW]	Verdict
NTNV	DH5	Ant1	2402	30~1000	-58.69	≤-26	0.00135	≤2.5	PASS
				1000~2387	-60.08	≤-26	0.00098	≤2.5	PASS
				2387~2400	-34.93	≤-16	0.32137	≤25	PASS
				2483.5~2496.5	-52.43	≤-16	0.00571	≤25	PASS
				2496.5~13000	-49.37	≤-26	0.01156	≤2.5	PASS
			2441	30~1000	-58.98	≤-26	0.00126	≤2.5	PASS
				1000~2387	-59.14	≤-26	0.00122	≤2.5	PASS
				2387~2400	-52.61	≤-16	0.00548	≤25	PASS
				2483.5~2496.5	-52.13	≤-16	0.00612	≤25	PASS
				2496.5~13000	-48.09	≤-26	0.01552	≤2.5	PASS
			2480	30~1000	-58.94	≤-26	0.00128	≤2.5	PASS
				1000~2387	-62.24	≤-26	0.00060	≤2.5	PASS
				2387~2400	-52.57	≤-16	0.00553	≤25	PASS
				2483.5~2496.5	-51.13	≤-16	0.00771	≤25	PASS
				2496.5~13000	-49.76	≤-26	0.01057	≤2.5	PASS
	2DH5	Ant1	2402	30~1000	-55.28	≤-26	0.00296	≤2.5	PASS
				1000~2387	-59.32	≤-26	0.00117	≤2.5	PASS
				2387~2400	-31.11	≤-16	0.77446	≤25	PASS
				2483.5~2496.5	-52.28	≤-16	0.00592	≤25	PASS
				2496.5~13000	-49.55	≤-26	0.01109	≤2.5	PASS
			2441	30~1000	-56.30	≤-26	0.00234	≤2.5	PASS
				1000~2387	-61.27	≤-26	0.00075	≤2.5	PASS
				2387~2400	-52.42	≤-16	0.00573	≤25	PASS
				2483.5~2496.5	-52.58	≤-16	0.00552	≤25	PASS
				2496.5~13000	-49.79	≤-26	0.01050	≤2.5	PASS
			2480	30~1000	-55.61	≤-26	0.00275	≤2.5	PASS
				1000~2387	-62.12	≤-26	0.00061	≤2.5	PASS
				2387~2400	-52.22	≤-16	0.00600	≤25	PASS
				2483.5~2496.5	-51.11	≤-16	0.00774	≤25	PASS
				2496.5~13000	-49.03	≤-26	0.01250	≤2.5	PASS
	3DH5	Ant1	2402	30~1000	-57.05	≤-26	0.00197	≤2.5	PASS
				1000~2387	-59.22	≤-26	0.00120	≤2.5	PASS
				2387~2400	-34.88	≤-16	0.32509	≤25	PASS
				2483.5~2496.5	-52.55	≤-16	0.00556	≤25	PASS
				2496.5~13000	-49.61	≤-26	0.01094	≤2.5	PASS
			2441	30~1000	-55.53	≤-26	0.00280	≤2.5	PASS
				1000~2387	-61.50	≤-26	0.00071	≤2.5	PASS
				2387~2400	-52.57	≤-16	0.00553	≤25	PASS
				2483.5~2496.5	-52.23	≤-16	0.00598	≤25	PASS
				2496.5~13000	-49.29	≤-26	0.01178	≤2.5	PASS



			2480	30~1000	-55.41	≤-26	0.00288	≤2.5	PASS
				1000~2387	-61.50	≤-26	0.00071	≤2.5	PASS
				2387~2400	-52.73	≤-16	0.00533	≤25	PASS
				2483.5~2496.5	-51.42	≤-16	0.00721	≤25	PASS
				2496.5~13000	-48.55	≤-26	0.01396	≤2.5	PASS
NTLV	DH5	Ant1	2402	30~1000	-58.86	≤-26	0.00130	≤2.5	PASS
				1000~2387	-59.95	≤-26	0.00101	≤2.5	PASS
				2387~2400	-34.23	≤-16	0.37757	≤25	PASS
				2483.5~2496.5	-52.58	≤-16	0.00552	≤25	PASS
				2496.5~13000	-49.24	≤-26	0.01191	≤2.5	PASS
			2441	30~1000	-57.98	≤-26	0.00159	≤2.5	PASS
				1000~2387	-61.98	≤-26	0.00063	≤2.5	PASS
				2387~2400	-52.47	≤-16	0.00566	≤25	PASS
				2483.5~2496.5	-52.50	≤-16	0.00562	≤25	PASS
				2496.5~13000	-49.44	≤-26	0.01138	≤2.5	PASS
	2DH5	Ant1	2480	30~1000	-58.80	≤-26	0.00132	≤2.5	PASS
				1000~2387	-61.89	≤-26	0.00065	≤2.5	PASS
				2387~2400	-52.57	≤-16	0.00553	≤25	PASS
				2483.5~2496.5	-51.01	≤-16	0.00793	≤25	PASS
				2496.5~13000	-46.54	≤-26	0.02218	≤2.5	PASS
			2402	30~1000	-56.61	≤-26	0.00218	≤2.5	PASS
				1000~2387	-59.69	≤-26	0.00107	≤2.5	PASS
				2387~2400	-30.81	≤-16	0.82985	≤25	PASS
				2483.5~2496.5	-52.50	≤-16	0.00562	≤25	PASS
				2496.5~13000	-49.61	≤-26	0.01094	≤2.5	PASS
	3DH5	Ant1	2441	30~1000	-57.47	≤-26	0.00179	≤2.5	PASS
				1000~2387	-60.89	≤-26	0.00081	≤2.5	PASS
				2387~2400	-52.39	≤-16	0.00577	≤25	PASS
				2483.5~2496.5	-52.46	≤-16	0.00568	≤25	PASS
				2496.5~13000	-49.80	≤-26	0.01047	≤2.5	PASS
			2480	30~1000	-56.69	≤-26	0.00214	≤2.5	PASS
				1000~2387	-62.15	≤-26	0.00061	≤2.5	PASS
				2387~2400	-52.45	≤-16	0.00569	≤25	PASS
				2483.5~2496.5	-51.49	≤-16	0.00710	≤25	PASS
				2496.5~13000	-49.89	≤-26	0.01026	≤2.5	PASS
			2402	30~1000	-55.92	≤-26	0.00256	≤2.5	PASS
				1000~2387	-59.43	≤-26	0.00114	≤2.5	PASS
				2387~2400	-32.20	≤-16	0.60256	≤25	PASS
				2483.5~2496.5	-52.31	≤-16	0.00587	≤25	PASS
				2496.5~13000	-49.46	≤-26	0.01132	≤2.5	PASS
			2441	30~1000	-56.68	≤-26	0.00215	≤2.5	PASS
				1000~2387	-61.36	≤-26	0.00073	≤2.5	PASS
				2387~2400	-52.75	≤-16	0.00531	≤25	PASS
				2483.5~2496.5	-52.47	≤-16	0.00566	≤25	PASS
				2496.5~13000	-49.55	≤-26	0.01109	≤2.5	PASS



			2480	30~1000	-55.45	≤-26	0.00285	≤2.5	PASS
				1000~2387	-61.83	≤-26	0.00066	≤2.5	PASS
				2387~2400	-52.60	≤-16	0.00550	≤25	PASS
				2483.5~2496.5	-50.96	≤-16	0.00802	≤25	PASS
				2496.5~13000	-49.30	≤-26	0.01175	≤2.5	PASS
NTHV	DH5	Ant1	2402	30~1000	-58.89	≤-26	0.00129	≤2.5	PASS
				1000~2387	-59.59	≤-26	0.00110	≤2.5	PASS
				2387~2400	-35.08	≤-16	0.31046	≤25	PASS
				2483.5~2496.5	-52.48	≤-16	0.00565	≤25	PASS
				2496.5~13000	-49.32	≤-26	0.01169	≤2.5	PASS
			2441	30~1000	-59.14	≤-26	0.00122	≤2.5	PASS
				1000~2387	-62.08	≤-26	0.00062	≤2.5	PASS
				2387~2400	-52.48	≤-16	0.00565	≤25	PASS
				2483.5~2496.5	-52.39	≤-16	0.00577	≤25	PASS
				2496.5~13000	-49.83	≤-26	0.01040	≤2.5	PASS
	2DH5	Ant1	2480	30~1000	-58.64	≤-26	0.00137	≤2.5	PASS
				1000~2387	-61.96	≤-26	0.00064	≤2.5	PASS
				2387~2400	-52.51	≤-16	0.00561	≤25	PASS
				2483.5~2496.5	-51.26	≤-16	0.00748	≤25	PASS
				2496.5~13000	-48.50	≤-26	0.01413	≤2.5	PASS
			2402	30~1000	-56.25	≤-26	0.00237	≤2.5	PASS
				1000~2387	-58.76	≤-26	0.00133	≤2.5	PASS
				2387~2400	-31.39	≤-16	0.72611	≤25	PASS
				2483.5~2496.5	-52.31	≤-16	0.00587	≤25	PASS
				2496.5~13000	-49.92	≤-26	0.01019	≤2.5	PASS
	3DH5	Ant1	2441	30~1000	-58.14	≤-26	0.00153	≤2.5	PASS
				1000~2387	-59.93	≤-26	0.00102	≤2.5	PASS
				2387~2400	-52.13	≤-16	0.00612	≤25	PASS
				2483.5~2496.5	-52.35	≤-16	0.00582	≤25	PASS
				2496.5~13000	-48.99	≤-26	0.01262	≤2.5	PASS
			2480	30~1000	-54.44	≤-26	0.00360	≤2.5	PASS
				1000~2387	-61.86	≤-26	0.00065	≤2.5	PASS
				2387~2400	-52.43	≤-16	0.00571	≤25	PASS
				2483.5~2496.5	-51.15	≤-16	0.00767	≤25	PASS
				2496.5~13000	-50.14	≤-26	0.00968	≤2.5	PASS
			2402	30~1000	-56.33	≤-26	0.00233	≤2.5	PASS
				1000~2387	-59.53	≤-26	0.00111	≤2.5	PASS
				2387~2400	-31.79	≤-16	0.66222	≤25	PASS
				2483.5~2496.5	-52.47	≤-16	0.00566	≤25	PASS
				2496.5~13000	-49.55	≤-26	0.01109	≤2.5	PASS
			2441	30~1000	-55.66	≤-26	0.00272	≤2.5	PASS
				1000~2387	-61.64	≤-26	0.00069	≤2.5	PASS
				2387~2400	-51.85	≤-16	0.00653	≤25	PASS
				2483.5~2496.5	-52.47	≤-16	0.00566	≤25	PASS
				2496.5~13000	-50.03	≤-26	0.00993	≤2.5	PASS





			2480	30~1000	-57.72	≤-26	0.00169	≤2.5	PASS
				1000~2387	-61.76	≤-26	0.00067	≤2.5	PASS
				2387~2400	-52.62	≤-16	0.00547	≤25	PASS
				2483.5~2496.5	-50.96	≤-16	0.00802	≤25	PASS
				2496.5~13000	-49.47	≤-26	0.01130	≤2.5	PASS

Remark: Only show the test data of worst condition.
Both headphones were tested, and only the worst mode was recorded.(Left Earphone)




Test Graphs






NTNV_DH5_Ant1_2402_2483.5~2496.5




NTNV_DH5_Ant1_2402_2496.5~13000




NTNV_DH5_Ant1_2441_30~1000






NTNV_DH5_Ant1_2441_1000~2387




NTNV_DH5_Ant1_2441_2387~2400




NTNV_DH5_Ant1_2441_2483.5~2496.5






NTNV_DH5_Ant1_2441_2496.5~13000




NTNV_DH5_Ant1_2480_30~1000




NTNV_DH5_Ant1_2480_1000~2387






NTNV_DH5_Ant1_2480_2387~2400




NTNV_DH5_Ant1_2480_2483.5~2496.5




NTNV_DH5_Ant1_2480_2496.5~13000






NTNV_2DH5_Ant1_2402_30~1000




NTNV_2DH5_Ant1_2402_1000~2387




NTNV_2DH5_Ant1_2402_2387~2400






NTVN_2DH5_Ant1_2402_2483.5~2496.5




NTVN_2DH5_Ant1_2402_2496.5~13000




NTVN_2DH5_Ant1_2441_30~1000






NTNV_2DH5_Ant1_2441_1000~2387




NTNV_2DH5_Ant1_2441_2387~2400




NTNV_2DH5_Ant1_2441_2483.5~2496.5






NTNV_2DH5_Ant1_2441_2496.5~13000




NTNV_2DH5_Ant1_2480_30~1000




NTNV_2DH5_Ant1_2480_1000~2387






NTNV_2DH5_Ant1_2480_2387~2400




NTNV_2DH5_Ant1_2480_2483.5~2496.5




NTNV_2DH5_Ant1_2480_2496.5~13000






NTNV_3DH5_Ant1_2402_30~1000




NTNV_3DH5_Ant1_2402_1000~2387




NTNV_3DH5_Ant1_2402_2387~2400






NTVN_3DH5_Ant1_2402_2483.5~2496.5




NTVN_3DH5_Ant1_2402_2496.5~13000




NTVN_3DH5_Ant1_2441_30~1000






NTNV_3DH5_Ant1_2441_1000~2387




NTNV_3DH5_Ant1_2441_2387~2400




NTNV_3DH5_Ant1_2441_2483.5~2496.5






NTNV_3DH5_Ant1_2441_2496.5~13000




NTNV_3DH5_Ant1_2480_30~1000




NTNV_3DH5_Ant1_2480_1000~2387






NTNV_3DH5_Ant1_2480_2387~2400




NTNV_3DH5_Ant1_2480_2483.5~2496.5




NTNV_3DH5_Ant1_2480_2496.5~13000






NTLV_DH5_Ant1_2402_30~1000




NTLV_DH5_Ant1_2402_1000~2387




NTLV_DH5_Ant1_2402_2387~2400






NTLV_DH5_Ant1_2402_2483.5~2496.5




NTLV_DH5_Ant1_2402_2496.5~13000




NTLV_DH5_Ant1_2441_30~1000






NTLV_DH5_Ant1_2441_1000~2387




NTLV_DH5_Ant1_2441_2387~2400




NTLV_DH5_Ant1_2441_2483.5~2496.5






NTLV_DH5_Ant1_2441_2496.5~13000




NTLV_DH5_Ant1_2480_30~1000




NTLV_DH5_Ant1_2480_1000~2387






NTLV_DH5_Ant1_2480_2387~2400




NTLV_DH5_Ant1_2480_2483.5~2496.5




NTLV_DH5_Ant1_2480_2496.5~13000






NTLV_2DH5_Ant1_2402_30~1000




NTLV_2DH5_Ant1_2402_1000~2387




NTLV_2DH5_Ant1_2402_2387~2400






NTLV_2DH5_Ant1_2402_2483.5~2496.5




NTLV_2DH5_Ant1_2402_2496.5~13000




NTLV_2DH5_Ant1_2441_30~1000






NTLV_2DH5_Ant1_2441_1000~2387




NTLV_2DH5_Ant1_2441_2387~2400




NTLV_2DH5_Ant1_2441_2483.5~2496.5






NTLV_2DH5_Ant1_2441_2496.5~13000




NTLV_2DH5_Ant1_2480_30~1000




NTLV_2DH5_Ant1_2480_1000~2387






NTLV_2DH5_Ant1_2480_2387~2400




NTLV_2DH5_Ant1_2480_2483.5~2496.5




NTLV_2DH5_Ant1_2480_2496.5~13000






NTLV_3DH5_Ant1_2402_30~1000




NTLV_3DH5_Ant1_2402_1000~2387




NTLV_3DH5_Ant1_2402_2387~2400






NTLV_3DH5_Ant1_2402_2483.5~2496.5




NTLV_3DH5_Ant1_2402_2496.5~13000




NTLV_3DH5_Ant1_2441_30~1000






NTLV_3DH5_Ant1_2441_1000~2387




NTLV_3DH5_Ant1_2441_2387~2400




NTLV_3DH5_Ant1_2441_2483.5~2496.5






NTLV_3DH5_Ant1_2441_2496.5~13000




NTLV_3DH5_Ant1_2480_30~1000




NTLV_3DH5_Ant1_2480_1000~2387






NTLV_3DH5_Ant1_2480_2387~2400





NTLV_3DH5_Ant1_2480_2483.5~2496.5




NTLV_3DH5_Ant1_2480_2496.5~13000








NTHV_DH5_Ant1_2402_2483.5~2496.5




NTHV_DH5_Ant1_2402_2496.5~13000




NTHV_DH5_Ant1_2441_30~1000






NTHV_DH5_Ant1_2441_1000~2387




NTHV_DH5_Ant1_2441_2387~2400




NTHV_DH5_Ant1_2441_2483.5~2496.5






NTHV_DH5_Ant1_2441_2496.5~13000




NTHV_DH5_Ant1_2480_30~1000




NTHV_DH5_Ant1_2480_1000~2387






NTHV_DH5_Ant1_2480_2387~2400




NTHV_DH5_Ant1_2480_2483.5~2496.5




NTHV_DH5_Ant1_2480_2496.5~13000






NTHV_2DH5_Ant1_2402_30~1000




NTHV_2DH5_Ant1_2402_1000~2387




NTHV_2DH5_Ant1_2402_2387~2400






NTHV_2DH5_Ant1_2402_2483.5~2496.5




NTHV_2DH5_Ant1_2402_2496.5~13000




NTHV_2DH5_Ant1_2441_30~1000






NTHV_2DH5_Ant1_2441_1000~2387




NTHV_2DH5_Ant1_2441_2387~2400




NTHV_2DH5_Ant1_2441_2483.5~2496.5






NTHV_2DH5_Ant1_2441_2496.5~13000




NTHV_2DH5_Ant1_2480_30~1000




NTHV_2DH5_Ant1_2480_1000~2387






NTHV_2DH5_Ant1_2480_2387~2400




NTHV_2DH5_Ant1_2480_2483.5~2496.5




NTHV_2DH5_Ant1_2480_2496.5~13000






NTHV_3DH5_Ant1_2402_30~1000




NTHV_3DH5_Ant1_2402_1000~2387




NTHV_3DH5_Ant1_2402_2387~2400






NTHV_3DH5_Ant1_2402_2483.5~2496.5




NTHV_3DH5_Ant1_2402_2496.5~13000




NTHV_3DH5_Ant1_2441_30~1000






NTHV_3DH5_Ant1_2441_1000~2387




NTHV_3DH5_Ant1_2441_2387~2400




NTHV_3DH5_Ant1_2441_2483.5~2496.5






NTHV_3DH5_Ant1_2441_2496.5~13000




NTHV_3DH5_Ant1_2480_30~1000




NTHV_3DH5_Ant1_2480_1000~2387






NTHV_3DH5_Ant1_2480_2387~2400




NTHV_3DH5_Ant1_2480_2483.5~2496.5



NTHV_3DH5_Ant1_2480_2496.5~13000





Appendix G: Spurious Emission of RX

Test Result


Test Condition	Test Mode	Antenna	Freq (MHz)	Freq.Range [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	DH5	Ant1	2402	30~1000	-89.94	≤-54	0.00101	≤4	PASS
				1000~13000	-68.09	≤-47	0.15524	≤20	PASS
			2441	30~1000	-90.64	≤-54	0.00086	≤4	PASS
				1000~13000	-69.64	≤-47	0.10864	≤20	PASS
			2480	30~1000	-90.52	≤-54	0.00089	≤4	PASS
				1000~13000	-69.48	≤-47	0.11272	≤20	PASS
NTLV	DH5	Ant1	2402	30~1000	-89.9	≤-54	0.00102	≤4	PASS
				1000~13000	-69	≤-47	0.12589	≤20	PASS
			2441	30~1000	-90.57	≤-54	0.00088	≤4	PASS
				1000~13000	-69.61	≤-47	0.10940	≤20	PASS
			2480	30~1000	-90.07	≤-54	0.00098	≤4	PASS
				1000~13000	-69.78	≤-47	0.10520	≤20	PASS
NTHV	DH5	Ant1	2402	30~1000	-89.9	≤-54	0.00102	≤4	PASS
				1000~13000	-69.29	≤-47	0.11776	≤20	PASS
			2441	30~1000	-90.38	≤-54	0.00092	≤4	PASS
				1000~13000	-69.73	≤-47	0.10641	≤20	PASS
			2480	30~1000	-90.58	≤-54	0.00087	≤4	PASS
				1000~13000	-69.52	≤-47	0.11169	≤20	PASS


Remark: Only show the test data of worst condition.

Both headphones were tested, and only the worst mode was recorded.(Left Earphone)




Test Graphs






NTVN_DH5_Ant1_2441_1000~13000




NTVN_DH5_Ant1_2480_30~1000




NTVN_DH5_Ant1_2480_1000~13000






NTLV_DH5_Ant1_2402_30~1000




NTLV_DH5_Ant1_2402_1000~13000




NTLV_DH5_Ant1_2441_30~1000






NTLV_DH5_Ant1_2441_1000~13000




NTLV_DH5_Ant1_2480_30~1000




NTLV_DH5_Ant1_2480_1000~13000






NTHV_DH5_Ant1_2402_30~1000




NTHV_DH5_Ant1_2402_1000~13000




NTHV_DH5_Ant1_2441_30~1000






NTHV_DH5_Ant1_2441_1000~13000




NTHV_DH5_Ant1_2480_30~1000



NTHV_DH5_Ant1_2480_1000~13000





-----END OF THE REPORT-----

