

SAR Report

Applicant : 全虹企業股份有限公司
Product Type : Mobile Phone
Trade Name : POCO
Model Number : M2102J20SG
Applicable Standard : CNS 14959 / CNS 14958-1
Received Date : Dec. 23, 2020
Test Period : Dec. 31. 2020 ~ Jan. 05, 2021
Issued Date : Feb. 05, 2021

Issued by

Tested By : Kris Pan
(Kris Pan)

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note:

- 1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2.This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
- 3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.



Revision History

Rev.	Issue Date	Revisions	Revised By
00	Jan. 11, 2021	Initial Issue	Nicole Chu
01	Feb. 05, 2021	Revised report information (P1) Revised chapter 3 (P6)	Snow Wang

Contents

1.	General Information	4
1.1	Reference Applicable Standard.....	4
1.2	Test Site Environment	4
1.3	Laboratory Information	4
2.	Summary of Maximum Reported SAR Value.....	5
3.	Description of Equipment under Test (EUT)	6
4.	Introduction	9
5.	SAR Definition.....	9
6.	SAR Measurement Setup	10
7.	System Components.....	11
7.1	DASY E-Field Probe System	11
7.1.1	E-Field Probe Specification	11
7.2	Data Acquisition Electronic (DAE) System.....	12
7.3	Robot.....	12
7.4	Measurement Server.....	12
7.5	Device Holder.....	13
7.6	Phantom - SAM v4.0	13
8.	Test Equipment List.....	14
9.	Tissue Simulating Liquids	15
10.	Measurement Process	16
10.1	Device and Test Conditions.....	16
10.2	System Performance Check	17
10.2.1	Symmetric Dipoles for System Validation	17
10.2.2	Validation.....	18
10.3	Dosimetric Assessment Setup	19
10.3.1	Handset Test Position - Head Position.....	19
10.3.2	Measurement Procedures.....	21
10.4	Spatial Peak SAR Evaluation	22
11.	Measurement Uncertainty	23
12.	SAR Test Results Summary.....	26
12.1	Test Results.....	26
12.2	European Council Recommendation 1999 519 EC	33
13.	Conclusion	34
14.	References.....	34
	Appendix A - System Performance Check.....	35
	Appendix B - SAR Measurement Data	40
	Appendix C - Calibration	50

1. General Information

1.1 Reference Applicable Standard

Standard	Description	Version
ANSI/IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	2005
IEEE 1528	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head From Wireless Communications Devices: Measurement Techniques.	2013
IEC 62209-1	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)	2016
CNS 14959	Limit for exposing to time-varying electric, magnetic and electromagnetic fields (up to 300 GHz)	2005-12
CNS 14958-1	Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)	2005-12

1.2 Test Site Environment

Items	Required (IEEE 1528-2013)	Actual
Temperature (°C)	18-25	21-23

1.3 Laboratory Information

Issue Location

Site Name: A Test Lab Techno Corp.

<http://www.atl-lab.com.tw/e-index.htm>

Site Address: No. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C.)

Tel : +886-3-2710188

Fax : +886-3-2710190



2. Summary of Maximum Reported SAR Value

Equipment Class	Mode	Highest Reported 10g SAR (W/Kg)
		Head standalone SAR _{10g} (W/kg)
Licensed	GSM900	0.491
	WCDMA Band I	0.463
	WCDMA Band VIII	0.533
	LTE Band 1	0.311
	LTE Band 3	0.350
	LTE Band 7	0.176
	LTE Band 8	0.397
	LTE Band 28	0.537
	LTE Band 38	0.221
	LTE Band 41	0.258

3. Description of Equipment under Test (EUT)

Applicant	全虹企業股份有限公司 臺北市大安區敦化南路 2 段 207 號 36 樓				
Manufacturer	小米通訊技術有限公司 中國北京市海淀區西二旗中路 33 號院 6 號樓 9 層 019 號				
Product Type	Mobile Phone				
Trade Name	POCO				
Model Number	M2102J20SG				
IMEI No.	IMEI 1: 864460050023705, IMEI 2: 864460050023713				
Test Device	Production Unit				
TX Frequency	890.2 - 914.8 MHz (PGSM 900) 1920 - 1980 MHz (WCDMA Band 1) 885 - 915 MHz (WCDMA Band 8) 1920 - 1980 MHz LTE Band 1 (BW 5, 10, 15, 20 MHz) 1710 - 1785 MHz LTE Band 3 (BW 1.4, 3, 5, 10, 15, 20 MHz) 2500 - 2570 MHz LTE Band 7 (BW 5, 10, 15, 20 MHz) 885 - 915 MHz LTE Band 8 (BW 1.4, 3, 5, 10 MHz) 703 - 748 MHz LTE Band 28 (BW 3, 5, 10, 15, 20 MHz) 2570 - 2620 MHz LTE Band 38 (BW 5, 10, 15, 20 MHz) 2535 - 2655 MHz LTE Band 41 (BW 5, 10, 15, 20 MHz)				
Max. Avg. Conducted Power	2.070	W /	33.16	dBm	PGSM 900
	0.261	W /	24.16	dBm	WCDMA Band 1
	0.259	W /	24.13	dBm	WCDMA Band 8
	0.272	W /	24.35	dBm	LTE Band 1
	0.274	W /	24.38	dBm	LTE Band 3
	0.250	W /	23.98	dBm	LTE Band 7
	0.276	W /	24.41	dBm	LTE Band 8
	0.262	W /	24.18	dBm	LTE Band 28
	0.244	W /	23.88	dBm	LTE Band 38
	0.255	W /	24.06	dBm	LTE Band 41
Max. SAR Measurement	0.537 W/kg Head SAR				
Device Category	Portable				
RF Exposure Environment	General Population / Uncontrolled				
Battery Option	Standard				
Application Type	Certification				

Note:

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment / general population exposure limits specified in Std. C95.1-2005 & CNS14959 & PLMN ALL and had been tested in accordance with the measurement procedures specified in IEEE Std. 1528-2013 and IEC 62209-1.



Antenna list:

Antenna	Brand	Model Number	Type	Frequency	Max. Gain (dBi)
上天線	瑞聲科技	J20S 天線	PIFA Antenna	GSM900	-3.85
				WCDMA (Band I)	-0.8
				WCDMA (Band 8)	-3.85
				LTE2100 (Band 1)	-0.8
				LTE1800 (Band 3)	-3.1
				LTE2600 (Band 7)	-1.6
				LTE900 (Band 8)	-3.85
				LTE700 (Band 28)	-3.17
				LTE2600 (Band 38)	-2.3
				LTE2500 (Band 41)	-2.3
下天線	瑞聲科技	J20S 天線	PIFA Antenna	GSM900	-5.6
				WCDMA (Band I)	0.9
				WCDMA (Band 8)	-5.6
				LTE2100 (Band 1)	0.9
				LTE1800 (Band 3)	-0.5
				LTE2600 (Band 7)	0.5
				LTE900 (Band 8)	-5.6
				LTE700 (Band 28)	-5.44
				LTE2600 (Band 38)	0.3
				LTE2500 (Band 41)	0.5
Ant-0	瑞聲科技	J20S WiFi 天線	PIFA Antenna	Bluetooth	-2.7
				2412 – 2462 MHz	-2.7
				5150 – 5250 MHz	-2.25
				5250 – 5350 MHz	-2.25
				5470 – 5725 MHz	-2.92
				5725 – 5850 MHz	-2.92
Ant-1	瑞聲科技	J20S WiFi 天線	PIFA Antenna	2412 – 2462 MHz	-2.86
Ant-1	瑞聲科技	J20S WiFi 天線	PIFA Antenna	5150 – 5250 MHz	1.44
				5250 – 5350 MHz	1.77
				5470 – 5725 MHz	1.59
				5725 – 5850 MHz	-0.07
Antenna	Brand	Model Number	Type	Frequency	Modulation
NFC	睿翔訊通	J20S NFC 天線	線圈	13.56 MHz	ASK



附屬裝置表:

裝置名稱	廠牌	型號	備註
內建固定式電池	MI	BN57	3.87 VDC, 5060 mAh 製造商(1): 寧德新能源科技有限公司 製造商(2): 欣旺達電子股份有限公司 *僅製造商不同
電源供應器	MI	MDY-12-EB	INPUT : AC 100-240 V, 50/60 Hz, 0.7 A OUTPUT : 正常輸出:DC 5 V, 3 A 快速輸出:DC 3.6-20 V, 3-1.35 A
USB 線(1)	MI	H23220	STD-A → Type-C Shielded, 1.0 m
USB 線(2)	MI	L23220	STD-A → Type-C Shielded, 1.0 m

4. Introduction

The A Test Lab Techno Corp. has performed measurements of the maximum potential exposure to the user. The test procedures, as described in IEC 62209-1 / CNS14959 / PLMN ALL were employed and they specify the maximum exposure limit of 2.0W/kg as averaged over any 10 gram of tissue. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the equipment are included within this test report.

5. SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dw) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below :

$$SAR = \frac{d}{dt} \left(\frac{dw}{dm} \right) = \frac{d}{dt} \left(\frac{dw}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$


Where :

σ = conductivity of the tissue (S/m)

ρ = mass density of the tissue (kg/m³)

E = RMS electric field strength (V/m)

6. SAR Measurement Setup



The DASY52 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli TX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
5. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
6. A computer operating Windows 7 or Windows 8.
7. DASY52 software.
8. Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
9. The SAM twin phantom enabling testing left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. Validation dipole kits allowing validating the proper functioning of the system.

7. System Components

7.1 DASY E-Field Probe System

The SAR measurements were conducted with the dosimetric probe (manufactured by SPEAG), designed in the classical triangular configuration [3] and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped when reaching the maximum.

7.1.1 E-Field Probe Specification

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in brain tissue (rotation around probe axis) ± 0.5 dB in brain tissue (rotation normal probe axis)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Calibration	ISO/IEC 17025 calibration service available
 	
EX3DV4 E-Field Probe Probe setup on robot	

7.2 Data Acquisition Electronic (DAE) System

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4 mV, 400 mV)	
Input Offset Voltage	< 5 μ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

7.3 Robot


Positioner	Stäubli Unimation Corp.	
Robot Model	TX90XL	
Number of Axes	6	
Norminal Load	5 kg	
Reach	1450 mm	
Repeatability	$\pm$ 0.035 mm	

7.4 Measurement Server

Processor	Stäubli Unimation Corp.	
I/O-board	TX90XL	
Number of Axes	Link to DAE4 16-bit A/D converter for surface detection system Digital I/O interface Serial link to robot Direct emergency stop output for robot	

7.5 Device Holder

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



7.6 Phantom - SAM v4.0

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness	2 ±0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	1000×500 mm (L×W)
Table 1. Specification of SAM v4.0	





8. Test Equipment List

Testing Engineer: Jason Tsao

Brand	Name of Equipment	Type/Model	Serial Number	Calibration	
				Cal. Date	Cal.Period
SPEAG	750MHz System Validation Kit	D750V3	1004	2020/09/17	1 year
SPEAG	900MHz System Validation Kit	D900V2	073	2020/05/08	1 year
SPEAG	1800MHz System Validation Kit	D1800V2	265	2020/04/28	1 year
SPEAG	1900MHz System Validation Kit	D1900V2	5d111	2020/09/18	1 year
SPEAG	2600MHz System Validation Kit	D2600V2	1007	2020/09/29	1 year
SPEAG	Dosimetric E-Field Probe	EX3DV4	3847	2020/05/20	1 year
SPEAG	Data Acquisition Electronics	DAE4	541	2020/03/18	1 year
SPEAG	Measurement Server	SE UMS 011 AA	1025	NCR	
SPEAG	Device Holder	N/A	N/A	NCR	
SPEAG	Phantom	SAM V4.0	TP-1009	NCR	
SPEAG	Robot	Staubli TX90XL	F16/54FTA1/A/01	NCR	
SPEAG	Software	DASY52 V52.10 (3)	N/A	NCR	
SPEAG	Software	SEMCAD X V14.6.10(7331)	N/A	NCR	
R&S	Wireless Communication Test Set	CMU200	112387	2020/05/15	1 year
Anritsu	Radio Communication Analyzer	MT8820C	6201342039	2020/12/03	1 year
R&S	Wideband Radio Communication Tester	CMW500	103168	2020/11/20	1 year
SPEAG	Network Analyzer	DAKS_VNA R140	0010318	2020/05/26	1 year
SPEAG	Dielectric Probe Kit	DAKS-3.5	1101	2020/05/26	1 year
HILA	Digital Thermometer	TM-906A	1500033	2020/10/28	1 year
Agilent	Power Sensor	8481H	3318A20779	2020/06/09	1 year
Agilent	Power Meter	EDM Series E4418B	GB40206143	2020/06/09	1 year
Agilent	Signal Generator	E8257D	MY44320425	2020/03/04	1 year
Agilent	Dual Directional Coupler	778D	50334	NCR	
Woken	Dual Directional Coupler	0100AZ20200801O	11012409517	NCR	
Mini-Circuits	Power Amplifier	EMC014225P	980292	NCR	
Mini-Circuits	Power Amplifier	EMC2830P	980293	NCR	
Aisi	Attenuator	IEAT 3dB	N/A	NCR	

Table 2. Test Equipment List

9. Tissue Simulating Liquids

The Head and Muscle mixtures consist of a viscous gel using hydroxethylcellulouse (HEC) gelling agent and saline solution. Preservation with a bacteriacide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an E5071B Network Analyzer.

Ingredient	Frequency					
	HSL750 - Head	HSL900 - Head	HSL1800 - Head	HSL1950 - Head	HSL2600 - Head	HSL3500 - Head
Water	49.23 %	51.07 %	54.88 %	55.27 %	55.67 %	71.8 %
HEC	0.27 %	0.23 %	0 %	0 %	0 %	0 %
Sugar	48.93 %	47.31 %	0 %	0 %	0 %	0 %
Preventol	0.29 %	0.24 %	0 %	0 %	0 %	0 %
Salt	1.28 %	1.15 %	0.21 %	0.26 %	0.29 %	0 %
Glycol monobutyl	0 %	0 %	44.91 %	44.47 %	44.04 %	44.04 %
Triton X-100	0 %	0 %	0 %	0 %	0 %	20.0 %
DGBE	0 %	0 %	44.50 %	44.50 %	45.10 %	8.0 %

Table 3. Recipes for Head Tissue Simulating Liquids

Target Frequency	Head	
(MHz)	ϵ_r	σ (S/m)
150	52.3	0.76
300	45.3	0.87
450	43.5	0.87
835	41.5	0.90
900	41.5	0.97
915	41.5	0.98
1450	40.5	1.20
1610	40.3	1.29
1800 - 2000	40.0	1.40
2450	39.2	1.80
3000	38.5	2.40
5800	35.3	5.27
(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)		
Table 4. Tissue dielectric parameters for head phantoms		

10. Measurement Process

10.1 Device and Test Conditions

The device was put in operation using the **R&S CMU200 or Agilent E5515C (8960) wireless Communication Test Set**. Communication between device and tester was established by air-link in order to simulate the actual usage as close as possible. The spatial peak SAR values were assessed for the lowest, middle and highest channels defined by **PGSM 900** (#01=890.2 MHz, #62=902.4 MHz, #124=914.8 MHz) and **WCDMA BAND 1** (#9612=1922.4 MHz, #9750=1950.0 MHz, #9888=1977.6 MHz) and **WCDMA BAND 8** (#2737= 887.4 MHz, #2800= 900.0 MHz, #2863= 912.6 MHz) systems. Power level was set to its maximum, i.e., **PGSM 900** nominal maximum output power class 4 (PCL 5, 33 dBm) and **WCDMA BAND 1** nominal maximum output power class 3 and **WCDMA BAND 8** nominal maximum output power class 3. These parameters will need to be replaced for the individual phone tested. All SAR measurements for LTE were performed using the **Anritsu MT8820C**. A closed loop power control setting allowed the UE to transmit at the maximum output power during the SAR measurements. Configure the base station to support LTE tests, and set channel, RB allocation number, RB allocation offset, and send continuously up power control commands to the device. MPR was enabled for this device. A-MPR was disabled for all SAR test measurements.

10.2 System Performance Check

10.2.1 Symmetric Dipoles for System Validation

Construction	Symmetrical dipole with 1/4 balun enables measurement of feed point impedance with NWA matched for use near flat phantoms filled with head simulating solutions Includes distance holder and tripod adaptor Calibration Calibrated SAR value for specified position and input power at the flat phantom in head simulating solutions.
Return Loss	> 20 dB at specified verification position
Options	Dipoles for other frequencies or solutions and other calibration conditions are available upon request




Figure 1. System Verification Setup Diagram

Figure 2. Validation Kit

10.2.2 Validation


Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$.


Mixture Type	Frequency (MHz)	Power	Probe	Dipole	SAR _{1g} (W/Kg)	Normalize to 1 Watt 1 g (W/Kg)	1 W Target SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	Normalize to 1 Watt 10 g (W/Kg)	1 W Target SAR _{10g} (W/Kg)	Difference percentage 1 g	Difference percentage 10 g	Date
			Model / Serial No.	Model / Serial No.									
Head	750	250 mW	EX3DV4-S N3847	D750V3 – SN1004	2.16	8.64	8.37	1.43	5.72	5.48	3.2%	4.4%	Jan. 05, 2021
Head	900	250 mW	EX3DV4-S N3847	D900V2 – SN073	2.65	10.6	11.20	1.69	6.76	7.33	-5.4%	-7.8%	Jan. 05, 2021
Head	1800	250 mW	EX3DV4-S N3847	D1800V2 – SN265	9.39	37.56	38.80	4.94	19.76	20.20	-3.2%	-2.2%	Jan. 04, 2021
Head	1950	250 mW	EX3DV4-S N3847	D1950V3 – SN1117	9.84	39	40.00	5.1	20.4	20.30	-1.6%	0.5%	Jan. 04, 2021
Head	2600	250 mW	EX3DV4-S N3847	D2600V2 – SN1007	14.9	59.6	57.30	6.55	26.2	25.90	4.0%	1.2%	Dec. 31, 2020

10.3 Dosimetric Assessment Setup

10.3.1 Handset Test Position - Head Position


1. Specifies two handset test positions against the head phantom – the "Cheek" position and the "Tilt" position. The DUT shall be tested in both of these positions on the left and right sides of the SAM phantom. In some cases (e.g. asymmetric handsets) the DUT positioning procedures representing intended use conditions cannot be used.
2. The cheek position is established as follows:
 - (a) Configure the DUT for talk operation, if necessary. For example, for a DUT with a flip, swivel or slide cover piece, open the cover if this is consistent with talk operation. If the DUT can also be used with the cover closed, both configurations shall be tested.
 - (b) Define two imaginary lines on the DUT, the vertical centreline and the horizontal line, for the DUT in vertical orientation as shown in figure as below. The vertical centreline passes through two points on the front side of the DUT: the midpoint of the width w_t of the handset at the level of the acoustic output (Point A), and the midpoint of the width w_b at the bottom of the handset (Point B). The horizontal line is perpendicular to the vertical centreline and passes through the centre of the acoustic output. The two lines intersect at Point A.
 - (c) Position the DUT close to the surface of the phantom such that Point A is on the (virtual) extension of the line passing through Points RE (right ear) and LE (left ear) on the phantom. The plane defined by the vertical centreline and the horizontal line of the DUT shall be parallel to the sagittal plane of the phantom.
 - (d) Translate the DUT towards the phantom along the line passing through RE and LE until the handset touches the ear.
 - (e) Rotate the DUT around its vertical centreline until the plane defined by the DUT vertical centreline and horizontal line is parallel to the N-F line, and then translate the DUT towards the phantom along the LE-RE line until DUT Point A touches the ear at the ERP (ear reference point).
 - (f) While keeping Point A on the line passing through RE and LE and maintaining the DUT in contact with the pinna, rotate the handset about the line N-F until any point on the DUT is in contact with a phantom point below the pinna (cheek). The physical angles of rotation shall be documented.
 - (g) While keeping DUT Point A in contact with the ERP, rotate the handset around a line perpendicular to the plane defined by the DUT vertical centreline and horizontal line and passing through DUT Point A, until the DUT vertical centreline is in the reference plane.





3. The Tilt position is established as follows:

- Repeat Steps (a) to (g) of cheek procedure to place the DUT in the cheek position.
- While maintaining the orientation of the DUT, move the DUT away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15° .
- Rotate the DUT around the horizontal line by 15° .
- While maintaining the orientation of the DUT, move the DUT towards the phantom on a line passing through RE and LE until any part of the DUT touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g. extended antenna on the back of the phantom head, the angle of the DUT shall be reduced. In this case, the tilt position is obtained if any part of the DUT is in contact with the pinna and a second part of the DUT is in contact with the phantom, e.g. the antenna with the back of the head.



10.3.2 Measurement Procedures

The evaluation was performed with the following procedures :

Surface Check :

A surface checks job gathers data used with optical surface detection. It determines the distance from the phantom surface where the reflection from the optical detector has its peak. Any following measurement jobs using optical surface detection will then rely on this value. The surface check performs its search a specified number of times, so that the repeatability can be verified.

Reference :

The reference job measures the field at a specified reference position, at 2 mm from the selected section's grid reference point.

Area Scan :

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines can find the maximum locations even in relatively coarse grids. When an area scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. Any following zoom scan within the same procedure will then perform fine scans around these maxima. The area covered the entire dimension of the EUT and the horizontal grid spacing was 15 mm × 15 mm.

Zoom Scan :

Zoom scans are used to assess the highest averaged SAR for cubic averaging volumes with 1 g and 10 g of simulated tissue. The zoom scan measures 5 x 5 x 7 points in a 32 x 32 x 30 mm cube whose base faces are centered around the maxima returned from a preceding area scan within the same procedure.

Drift :

The drift job measures the field at the same location as the most recent reference job within the same procedure, with the same settings. The drift measurement gives the field difference in dB from the last reference measurement. Several drift measurements are possible for each reference measurement. This allows monitoring of the power drift of the device in the batch process. If the value changed by more than 5 %, the evaluation was repeated.

10.4 Spatial Peak SAR Evaluation

The DASY52 software includes all numerical procedures necessary to evaluate the spatial peak SAR values. Based on the Draft: SCC-34, SC-2, WG-2 - Computational Dosimetry, IEEE P1529/D0.0 (Draft Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) Associated with the Use of Wireless Handsets - Computational Techniques), a new algorithm has been implemented. The spatial-peak SAR can be computed over any required mass.

The base for the evaluation is a "cube" measurement in a volume of (32x32x30) mm³ (5x5x7 points). The measured volume must include the 1 g and 10 g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan. If the 10 g cube or both cubes are not entirely inside the measured volumes, the system issues a warning regarding the evaluated spatial peak values within the Postprocessing engine (SEMCAD). This means that if the measured volume is shifted, higher values might be possible. To get the correct values you can use a finer measurement grid for the area scan. In complicated field distributions, a large grid spacing for the area scan might miss some details and give an incorrectly interpolated peak location.

The entire evaluation of the spatial peak values is performed within the Postprocessing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into three stages:

Interpolation and Extrapolation

The probe is calibrated at the center of the dipole sensors which is located 1 to 2.7 mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated.

In DASY52, the choice of the coordinate system defining the location of the measurement points has no influence on the uncertainty of the interpolation, Maxima Search and SAR extrapolation routines. The interpolation, Maxima Search and extrapolation routines are all based on the modified Quadratic Shepard's method [7].

11. *Measurement Uncertainty*

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, we estimate the measurement uncertainties in SAR to be less than $\pm 30\%$ [8] .

According to Std. C95.3 [9] , the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of ± 1 to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least ± 2 dB can be expected.

According to CENELEC [10] , typical worst-case uncertainty of field measurements is ± 5 dB. For well-defined modulation characteristics the uncertainty can be reduced to ± 3 dB.

Decision Rule

- ☒ Uncertainty is not included.
- ☐ Uncertainty is included.

IEEE 1528-2013 & IEC 62209-1 Measurement uncertainty evaluation template for handset SAR test (300 MHz~3 GHz)								
Uncertainty component	Tol.	Prob. Dist.	Div.	C _i - 1g	C _i - 10g	u _i - 1g (± %)	u _i - 10g (± %)	v _i
Measurement system								
Probe calibration	6.1	N	1	1	1	6.1	6.1	∞
Axial isotropy	4.7	R	1.732	0.7	0.7	1.9	1.9	∞
Hemispherical isotropy	9.6	R	1.732	0.7	0.7	3.9	3.9	∞
Boundary effect	1.0	R	1.732	1	1	0.6	0.6	∞
Linearity	4.7	R	1.732	1	1	2.7	2.7	∞
System detection limits	0.25	R	1.732	1	1	0.1	0.1	∞
Readout electronics	0.3	N	1	1	1	0.3	0.3	∞
Response time	0.0	R	1.732	1	1	0.0	0.0	∞
Integration time	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Noise	3.0	R	1.732	1	1	1.7	1.7	∞
RF Ambient Reflections	3.0	R	1.732	1	1	1.7	1.7	∞
Probe Positioner	0.02	R	1.732	1	1	0.01	0.01	∞
Probe Positioning	0.4	R	1.732	1	1	0.2	0.2	∞
Max. SAR evaluation	2.0	R	1.732	1	1	1.2	1.2	∞
Test sample related								
Test sample positioning	2.9	N	1	1	1	2.9	2.9	145
Device holder uncertainty	3.6	N	1	1	1	3.6	3.6	7
SAR drift measurement	5.0	R	1.732	1	1	2.9	2.9	∞
Phantom and tissue parameters								
Phantom shell uncertainty	6.1	R	1.732	1	1	3.5	3.5	∞
Liquid Conductivity (target)	5.0	R	1.732	0.78	0.71	2.3	2.0	∞
Liquid Conductivity (measurement)	4.8	R	1.732	0.78	0.71	2.2	2.0	∞
Liquid Permittivity (target)	5.0	R	1.732	0.23	0.26	0.7	0.8	∞
Liquid Permittivity (measurement)	4.8	R	1.732	0.23	0.26	0.6	0.7	∞
Combined standard uncertainty								
-	-	RSS	-	-	-	11.2	11.2	642
Expanded uncertainty (95% confidence interval)								
-	-	k =2	-	-	-	22.4	22.3	-

IEEE 1528-2013 & IEC 62209-1 Measurement uncertainty evaluation template for SAR test (3 GHz~6 GHz)								
Uncertainty component	Tol.	Prob. Dist.	Div.	C _i - 1g	C _i - 10g	u _i - 1g (± %)	u _i - 10g (± %)	v _i
Measurement system								
Probe calibration	6.7	N	1	1	1	6.7	6.7	∞
Axial isotropy	4.7	R	1.732	0.7	0.7	1.9	1.9	∞
Hemispherical isotropy	9.6	R	1.732	0.7	0.7	3.9	3.9	∞
Boundary effect	2.0	R	1.732	1	1	1.2	1.2	∞
Linearity	4.7	R	1.732	1	1	2.7	2.7	∞
System detection limits	0.25	R	1.732	1	1	0.1	0.1	∞
Readout electronics	0.3	N	1	1	1	0.3	0.3	∞
Response time	0.0	R	1.732	1	1	0.0	0.0	∞
Integration time	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Noise	3.0	R	1.732	1	1	1.7	1.7	∞
RF Ambient Reflections	3.0	R	1.732	1	1	1.7	1.7	∞
Probe Positioner	0.04	R	1.732	1	1	0.02	0.02	∞
Probe Positioning	0.8	R	1.732	1	1	0.5	0.5	∞
Max. SAR evaluation	4.0	R	1.732	1	1	2.3	2.3	∞
Test sample related								
Test sample positioning	2.9	N	1	1	1	2.9	2.9	145
Device holder uncertainty	3.6	N	1	1	1	3.6	3.6	7
SAR drift measurement	5.0	R	1.732	1	1	2.9	2.9	∞
Phantom and tissue parameters								
Phantom shell uncertainty	6.6	R	1.732	1	1	3.8	3.8	∞
Liquid Conductivity (target)	5.0	R	1.732	0.78	0.71	2.3	2.0	∞
Liquid Conductivity (measurement)	4.8	R	1.732	0.78	0.71	2.2	2.0	∞
Liquid Permittivity (target)	5.0	R	1.732	0.23	0.26	0.7	0.8	∞
Liquid Permittivity (measurement)	4.8	R	1.732	0.23	0.26	0.6	0.7	∞
Combined standard uncertainty								
-	-	RSS	-	-	-	11.9	11.8	804
Expanded uncertainty (95% confidence interval)								
-	-	k =2	-	-	-	23.7	23.6	-

12. SAR Test Results Summary

12.1 Test Results

PGSM 900 MHz SAR Test Results - Head							
Frequency		Test Mode	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz						
62	902.4	Voice	Right-Cheek	0	0.32	0.455	Ant Upper
62	902.4	Voice	Right-Tilted	0	0.343	0.488	Ant Upper
1	890.2	Voice	Right-Tilted	0	0.316	0.440	Ant Upper
124	914.8	Voice	Right-Tilted	0	0.354	0.491	Ant Upper
62	902.4	Voice	Left-Cheek	0	0.287	0.408	Ant Upper
62	902.4	Voice	Left-Tilted	0	0.303	0.431	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959					Head 2.0 W/kg Averaged over 10 gram		

PGSM 900 MHz SAR Test Results - Head							
Frequency		Test Mode	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz						
62	902.4	Voice	Right-Cheek	0	0.063	0.071	Ant Lower
62	902.4	Voice	Right-Tilted	0	0.064	0.074	Ant Lower
1	890.2	Voice	Right-Tilted	0	0.105	0.123	Ant Lower
124	914.8	Voice	Right-Tilted	0	0.025	0.028	Ant Lower
62	902.4	Voice	Left-Cheek	0	0.052	0.058	Ant Lower
62	902.4	Voice	Left-Tilted	0	0.03	0.034	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959					Head 2.0 W/kg Averaged over 10 gram		

WCDMA Band 1 SAR Test Results - Head							
Frequency		Modulation or Sub-Test	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz						
9750	1950	RMC12.2K	Right-Cheek	0	0.267	0.393	Ant Upper
9750	1950	RMC12.2K	Right-Tilted	0	0.304	0.448	Ant Upper
9612	1922.4	RMC12.2K	Right-Tilted	0	0.319	0.463	Ant Upper
9888	1977.6	RMC12.2K	Right-Tilted	0	0.307	0.447	Ant Upper
9750	1950	RMC12.2K	Left-Cheek	0	0.166	0.244	Ant Upper
9750	1950	RMC12.2K	Left-Tilted	0	0.204	0.300	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959					Head 2.0 W/kg Averaged over 10 gram		

WCDMA Band 1 SAR Test Results - Head							
Frequency		Modulation or Sub-Test	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz						
9750	1950	RMC12.2K	Right-Cheek	0	0.049	0.054	Ant Lower
9750	1950	RMC12.2K	Right-Tilted	0	0.043	0.048	Ant Lower
9750	1950	RMC12.2K	Left-Cheek	0	0.052	0.058	Ant Lower
9612	1922.4	RMC12.2K	Left-Cheek	0	0.065	0.072	Ant Lower
9888	1977.6	RMC12.2K	Left-Cheek	0	0.046	0.052	Ant Lower
9750	1950	RMC12.2K	Left-Tilted	0	0.041	0.046	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959					Head 2.0 W/kg Averaged over 10 gram		

WCDMA Band 8 SAR Test Results - Head							
Frequency		Modulation or Sub-Test	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz						
2800	900	RMC12.2K	Right-Cheek	0	0.379	0.500	Ant Upper
2737	887.4	RMC12.2K	Right-Cheek	0	0.387	0.507	Ant Upper
2863	912.6	RMC12.2K	Right-Cheek	0	0.404	0.533	Ant Upper
2800	900	RMC12.2K	Right-Tilted	0	0.395	0.521	Ant Upper
2800	900	RMC12.2K	Left-Cheek	0	0.343	0.452	Ant Upper
2800	900	RMC12.2K	Left-Tilted	0	0.316	0.417	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959					Head 2.0 W/kg Averaged over 10 gram		

WCDMA Band 8 SAR Test Results - Head							
Frequency		Modulation or Sub-Test	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz						
2800	900	RMC12.2K	Right-Cheek	0	0.087	0.099	Ant Lower
2737	887.4	RMC12.2K	Right-Cheek	0	0.076	0.085	Ant Lower
2863	912.6	RMC12.2K	Right-Cheek	0	0.11	0.126	Ant Lower
2800	900	RMC12.2K	Right-Tilted	0	0.029	0.033	Ant Lower
2800	900	RMC12.2K	Left-Cheek	0	0.061	0.069	Ant Lower
2800	900	RMC12.2K	Left-Tilted	0	0.029	0.033	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959					Head 2.0 W/kg Averaged over 10 gram		

LTE Band 1 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
18300	1950	20M	QPSK	18	0	Right-Cheek	0	0.294	0.298	Ant Upper
18300	1950	20M	QPSK	18	0	Right-Tilted	0	0.289	0.293	Ant Upper
18100	1930	20M	QPSK	18	0	Right-Tilted	0	0.31	0.311	Ant Upper
18500	1970	20M	QPSK	18	0	Right-Tilted	0	0.276	0.285	Ant Upper
18300	1950	20M	QPSK	18	0	Left-Cheek	0	0.149	0.151	Ant Upper
18300	1950	20M	QPSK	18	0	Left-Tilted	0	0.189	0.192	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 1 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
18300	1950	20M	QPSK	1	0	Right-Cheek	0	0.051	0.067	Ant Lower
18300	1950	20M	QPSK	1	0	Right-Tilted	0	0.036	0.047	Ant Lower
18300	1950	20M	QPSK	1	0	Left-Cheek	0	0.067	0.088	Ant Lower
18100	1930	20M	QPSK	1	0	Left-Cheek	0	0.06	0.077	Ant Lower
18500	1970	20M	QPSK	1	0	Left-Cheek	0	0.054	0.072	Ant Lower
18300	1950	20M	QPSK	1	0	Left-Tilted	0	0.038	0.050	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 3 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
19575	1747.5	20M	QPSK	18	0	Right-Cheek	0	0.264	0.266	Ant Upper
19575	1747.5	20M	QPSK	18	0	Right-Tilted	0	0.347	0.350	Ant Upper
19300	1720	20M	QPSK	18	0	Right-Tilted	0	0.291	0.292	Ant Upper
19850	1775	20M	QPSK	18	0	Right-Tilted	0	0.338	0.342	Ant Upper
19575	1747.5	20M	QPSK	18	0	Left-Cheek	0	0.182	0.184	Ant Upper
19575	1747.5	20M	QPSK	18	0	Left-Tilted	0	0.233	0.235	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 3 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
19575	1747.5	20M	QPSK	18	0	Right-Cheek	0	0.042	0.053	Ant Lower
19300	1720	20M	QPSK	18	0	Right-Cheek	0	0.042	0.054	Ant Lower
19850	1775	20M	QPSK	18	0	Right-Cheek	0	0.05	0.065	Ant Lower
19575	1747.5	20M	QPSK	18	0	Right-Tilted	0	0.032	0.041	Ant Lower
19575	1747.5	20M	QPSK	18	0	Left-Cheek	0	0.038	0.048	Ant Lower
19575	1747.5	20M	QPSK	18	0	Left-Tilted	0	0.028	0.036	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 7 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
21100	2535	20M	QPSK	18	82	Right-Cheek	0	0.155	0.159	Ant Upper
20850	2510	20M	QPSK	18	82	Right-Cheek	0	0.159	0.169	Ant Upper
21350	2560	20M	QPSK	18	82	Right-Cheek	0	0.164	0.176	Ant Upper
21100	2535	20M	QPSK	18	82	Right-Tilted	0	0.124	0.127	Ant Upper
21100	2535	20M	QPSK	18	82	Left-Cheek	0	0.049	0.050	Ant Upper
21100	2535	20M	QPSK	18	82	Left-Tilted	0	0.05	0.051	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 7 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
21100	2535	20M	QPSK	18	82	Right-Cheek	0	0.056	0.076	Ant Lower
20850	2510	20M	QPSK	18	82	Right-Cheek	0	0.057	0.079	Ant Lower
21350	2560	20M	QPSK	18	82	Right-Cheek	0	0.058	0.081	Ant Lower
21100	2535	20M	QPSK	18	82	Right-Tilted	0	0.044	0.059	Ant Lower
21100	2535	20M	QPSK	18	82	Left-Cheek	0	0.029	0.039	Ant Lower
21100	2535	20M	QPSK	18	82	Left-Tilted	0	0.027	0.037	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 8 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
21650	900	10M	QPSK	1	0	Right-Cheek	0	0.362	0.396	Ant Upper
21550	890	10M	QPSK	1	0	Right-Cheek	0	0.341	0.377	Ant Upper
21750	910	10M	QPSK	1	0	Right-Cheek	0	0.395	0.397	Ant Upper
21650	900	10M	QPSK	1	0	Right-Tilted	0	0.321	0.351	Ant Upper
21650	900	10M	QPSK	1	0	Left-Cheek	0	0.327	0.358	Ant Upper
21650	900	10M	QPSK	1	0	Left-Tilted	0	0.284	0.311	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 8 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
21650	900	10M	QPSK	1	0	Right-Cheek	0	0.088	0.119	Ant Lower
21550	890	10M	QPSK	1	0	Right-Cheek	0	0.081	0.109	Ant Lower
21750	910	10M	QPSK	1	0	Right-Cheek	0	0.111	0.136	Ant Lower
21650	900	10M	QPSK	1	0	Right-Tilted	0	0.033	0.045	Ant Lower
21650	900	10M	QPSK	1	0	Left-Cheek	0	0.067	0.090	Ant Lower
21650	900	10M	QPSK	1	0	Left-Tilted	0	0.034	0.046	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 28 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
27435	725.5	20M	QPSK	1	99	Right-Cheek	0	0.284	0.316	Ant Upper
27310	713	20M	QPSK	1	99	Right-Cheek	0	0.362	0.407	Ant Upper
27560	738	20M	QPSK	1	99	Right-Cheek	0	0.397	0.537	Ant Upper
27435	725.5	20M	QPSK	1	99	Right-Tilted	0	0.214	0.238	Ant Upper
27435	725.5	20M	QPSK	1	99	Left-Cheek	0	0.194	0.216	Ant Upper
27435	725.5	20M	QPSK	1	99	Left-Tilted	0	0.154	0.171	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 28 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
27435	725.5	20M	QPSK	1	99	Right-Cheek	0	0.047	0.064	Ant Lower
27310	713	20M	QPSK	1	99	Right-Cheek	0	0.032	0.042	Ant Lower
27560	738	20M	QPSK	1	99	Right-Cheek	0	0.053	0.078	Ant Lower
27435	725.5	20M	QPSK	1	99	Right-Tilted	0	0.016	0.022	Ant Lower
27435	725.5	20M	QPSK	1	99	Left-Cheek	0	0.029	0.040	Ant Lower
27435	725.5	20M	QPSK	1	99	Left-Tilted	0	0.015	0.020	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 38 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
38000	2595	20M	QPSK	18	0	Right-Cheek	0	0.203	0.221	Ant Upper
37850	2580	20M	QPSK	18	0	Right-Cheek	0	0.199	0.211	Ant Upper
38150	2610	20M	QPSK	18	0	Right-Cheek	0	0.202	0.219	Ant Upper
38000	2595	20M	QPSK	18	0	Right-Tilted	0	0.161	0.176	Ant Upper
38000	2595	20M	QPSK	18	0	Left-Cheek	0	0.066	0.072	Ant Upper
38000	2595	20M	QPSK	18	0	Left-Tilted	0	0.08	0.087	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 38 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
38000	2595	20M	QPSK	1	0	Right-Cheek	0	0.036	0.051	Ant Lower
37850	2580	20M	QPSK	1	0	Right-Cheek	0	0.035	0.049	Ant Lower
38150	2610	20M	QPSK	1	0	Right-Cheek	0	0.031	0.044	Ant Lower
38000	2595	20M	QPSK	1	0	Right-Tilted	0	0.034	0.048	Ant Lower
38000	2595	20M	QPSK	1	0	Left-Cheek	0	0.024	0.034	Ant Lower
38000	2595	20M	QPSK	1	0	Left-Tilted	0	0.018	0.026	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 41 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
40640	2595	20M	QPSK	18	0	Right-Cheek	0	0.228	0.246	Ant Upper
40140	2545	20M	QPSK	18	0	Right-Cheek	0	0.238	0.256	Ant Upper
41140	2645	20M	QPSK	18	0	Right-Cheek	0	0.254	0.258	Ant Upper
40640	2595	20M	QPSK	18	0	Right-Tilted	0	0.198	0.213	Ant Upper
40640	2595	20M	QPSK	18	0	Left-Cheek	0	0.081	0.087	Ant Upper
40640	2595	20M	QPSK	18	0	Left-Tilted	0	0.106	0.114	Ant Upper
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

LTE Band 41 SAR Test Results - Head										
Frequency		Bandwidth (MHz)	Modulation	RB Size	RB Offset	Test Position	Spacing (mm)	SAR _{10 g} (W/kg)	Reported SAR _{10 g}	Note
Ch.	MHz									
40640	2595	20M	QPSK	18	0	Right-Cheek	0	0.038	0.054	Ant Lower
40140	2545	20M	QPSK	18	0	Right-Cheek	0	0.042	0.059	Ant Lower
41140	2645	20M	QPSK	18	0	Right-Cheek	0	0.034	0.048	Ant Lower
40640	2595	20M	QPSK	18	0	Right-Tilted	0	0.034	0.048	Ant Lower
40640	2595	20M	QPSK	18	0	Left-Cheek	0	0.025	0.035	Ant Lower
40640	2595	20M	QPSK	18	0	Left-Tilted	0	0.018	0.025	Ant Lower
Safety Limit / Spatial Peak European Council Recommendation 1999 519 EC NCC CNS14959						Head 2.0 W/kg Averaged over 10 gram				

12.2 European Council Recommendation 1999 519 EC

Depending on frequency, the following physical quantities (dosimetric / exposimetric quantities) are used to specify the basic restrictions on electromagnetic fields :

- * between 0 and 1 Hz basic restrictions are provided for magnetic flux density for static magnetic fields (0 Hz) and current density for time-varying fields up to 1 Hz, in order to prevent effects on the cardiovascular and central nervous system,
- * between 1Hz and 10 MHz basic restrictions are provided for current density to prevent effects on nervous system functions,
- * Between 100 kHz and 10 GHz basic restrictions on SAR are provided to prevent whole-body heat stress and excessive localized heating of tissues. In the range 100 kHz to 10 MHz, restrictions on both current density and SAR are provided,
- * Between 10 GHz and 300 GHz basic restrictions on power density are provided to prevent heating in tissue at or near the body surface.

Frequency Range	Magnetic flux density (mT)	Current density (mA/m ²) (rms)	Whole body average SAR (W/kg)	Localized SAR (head and trunk) (W/kg)	Localized SAR (limbs) (W/kg)	Power density, S (W/m ²)
0	40	-----	-----	-----	-----	-----
> 0 - 1 Hz	-----	8	-----	-----	-----	-----
1 - 4 Hz	-----	8/f	-----	-----	-----	-----
4 - 1000 Hz	-----	2	-----	-----	-----	-----
1000 Hz - 100 kHz	-----	f/500	-----	-----	-----	-----
100 kHz - 10 MHz	-----	f/500	0.08	2	4	-----
10 MHz - 10 GHz	-----	-----	0.08	2	4	-----
10 - 300 GHz	-----	-----	-----	-----	-----	10
Table 5. Reference levels for electric, magnetic and electromagnetic fields (0Hz to 300GHz, unperturbed RMS values)						

13. Conclusion

The SAR test values found for the portable mobile phone are below the maximum recommended level of 2.0 W/kg (W/kg).

14. References

- [1] Std. C95.1-2005, "American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300KHz to 100GHz", New York: IEEE, Aug. 1992.
- [2] NCRP, National Council on Radiation Protection and Measurements, "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields", NCRP report NO. 86, 1986.
- [3] T. Schmid, O. Egger, and N. Kuster, "Automatic E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105-113, Jan. 1996.
- [4] K. Poković, T. Schmid, and N. Kuster, "Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequency", in ICECOM'97, Dubrovnik, October 15-17, 1997, pp.120-124.
- [5] K. Poković, T. Schmid, and N. Kuster, "E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23-25 June, 1996, pp.172-175.
- [6] N. Kuster, and Q. Balzano, "Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz", IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [7] Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988 , pp. 139-148.
- [8] N. Kuster, R. Kastle, T. Schmid, "Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [9] Std. C95.3-1991, "IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave, New York: IEEE, Aug. 1992.
- [10] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10 KHz-300GHz, Jan. 1995.

Appendix A - System Performance Check

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/5

System Performance Check at 750MHz_Head

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1004

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.896$ S/m; $\epsilon_r = 42.539$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(9.54, 9.54, 9.54) @ 750 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

System Performance Check at 750MHz/Area Scan (61x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.91 W/kg

System Performance Check at 750MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 58.46 V/m; Power Drift = -0.03 dB


Peak SAR (extrapolated) = 3.31 W/kg

SAR(1 g) = 2.16 W/kg; SAR(10 g) = 1.43 W/kg

Smallest distance from peaks to all points 3 dB below = 17.2 mm

Ratio of SAR at M2 to SAR at M1 = 65.3%

Maximum value of SAR (measured) = 2.90 W/kg



0 dB = 2.90 W/kg = 4.62 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/5

System Performance Check at 900MHz_Head

DUT: Dipole 900 MHz; Type: D900V2; Serial: D900V2 - SN:073

Communication System: UID 0, CW (0); Frequency: 900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 900$ MHz; $\sigma = 0.969$ S/m; $\epsilon_r = 41.574$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(9.3, 9.3, 9.3) @ 900 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

System Performance Check at 900MHz/Area Scan (61x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.63 W/kg

System Performance Check at 900MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 62.08 V/m; Power Drift = 0.12 dB


Peak SAR (extrapolated) = 4.21 W/kg

SAR(1 g) = 2.65 W/kg; SAR(10 g) = 1.69 W/kg

Smallest distance from peaks to all points 3 dB below = 17.6 mm

Ratio of SAR at M2 to SAR at M1 = 62.7%

Maximum value of SAR (measured) = 3.65 W/kg



0 dB = 3.65 W/kg = 5.62 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/4

System Performance Check at 1800MHz_Head

DUT: Dipole 1800 MHz; Type: D1800V2; Serial: D1800V2 - SN:265

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1800$ MHz; $\sigma = 1.416$ S/m; $\epsilon_r = 40.342$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(8.14, 8.14, 8.14) @ 1800 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

System Performance Check at 1800MHz/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.6 W/kg

System Performance Check at 1800MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 103.8 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 17.4 W/kg

SAR(1 g) = 9.39 W/kg; SAR(10 g) = 4.94 W/kg

Smallest distance from peaks to all points 3 dB below = 10.7 mm

Ratio of SAR at M2 to SAR at M1 = 54%

Maximum value of SAR (measured) = 14.6 W/kg



0 dB = 14.6 W/kg = 11.64 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/4

System Performance Check at 1950MHz_Head

DUT: Dipole 1950 MHz; Type: D1950V3; Serial: D1950V3 - SN:1117

Communication System: UID 0, CW (0); Frequency: 1950 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1950$ MHz; $\sigma = 1.387$ S/m; $\epsilon_r = 40.145$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(7.78, 7.78, 7.78) @ 1950 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

System Performance Check at 1950MHz/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.3 W/kg

System Performance Check at 1950MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 106.2 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 18.4 W/kg

SAR(1 g) = 9.84 W/kg; SAR(10 g) = 5.1 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 53.6%

Maximum value of SAR (measured) = 15.3 W/kg



0 dB = 15.3 W/kg = 11.85 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2020/12/31

System Performance Check at 2600MHz_Head

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN:1007

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.993$ S/m; $\epsilon_r = 39.397$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(7.2, 7.2, 7.2) @ 2600 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

System Performance Check at 2600MHz/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 25.2 W/kg

System Performance Check at 2600MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 113.6 V/m; Power Drift = 0.04 dB


Peak SAR (extrapolated) = 32.6 W/kg

SAR(1 g) = 14.9 W/kg; SAR(10 g) = 6.55 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 45.2%

Maximum value of SAR (measured) = 26.0 W/kg



0 dB = 26.0 W/kg = 14.15 dBW/kg

Appendix B - SAR Measurement Data

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/5

82_GSM900 CH 124_Right-Tilted_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, GSM900 (0); Frequency: 914.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 915$ MHz; $\sigma = 0.984$ S/m; $\epsilon_r = 41.401$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(9.3, 9.3, 9.3) @ 914.8 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.861 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.93 V/m; Power Drift = -0.11 dB


Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.590 W/kg; SAR(10 g) = 0.354 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 41.9%

Maximum value of SAR (measured) = 1.01 W/kg



0 dB = 1.01 W/kg = 0.04 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/4

54_WCDMA Band I CH 9612_Right-Tilted_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, WCDMA Band I (0); Frequency: 1922.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1922.4$ MHz; $\sigma = 1.364$ S/m; $\epsilon_r = 40.295$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(7.78, 7.78, 7.78) @ 1922.4 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.958 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 16.01 V/m; Power Drift = 0.14 dB


Peak SAR (extrapolated) = 1.40 W/kg

SAR(1 g) = 0.667 W/kg; SAR(10 g) = 0.319 W/kg

Smallest distance from peaks to all points 3 dB below = 8.6 mm

Ratio of SAR at M2 to SAR at M1 = 47.1%

Maximum value of SAR (measured) = 1.15 W/kg



0 dB = 1.15 W/kg = 0.61 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/5

69_WCDMA Band VIII CH 2863_Right-Cheek_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, WCDMA Band VIII (0); Frequency: 912.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 913$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 41.422$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(9.3, 9.3, 9.3) @ 912.6 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.992 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 30.15 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.655 W/kg; SAR(10 g) = 0.404 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 44.4%

Maximum value of SAR (measured) = 0.977 W/kg



0 dB = 0.977 W/kg = -0.10 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/4

27_LTE Band 1 CH 18100_QPSK_BW 20M_18RB Size 0RB Offset_Right-Tilted_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, Generic LTE (0); Frequency: 1930 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1930$ MHz; $\sigma = 1.37$ S/m; $\epsilon_r = 40.255$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(7.78, 7.78, 7.78) @ 1930 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.974 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 15.62 V/m; Power Drift = 0.12 dB


Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.645 W/kg; SAR(10 g) = 0.310 W/kg

Smallest distance from peaks to all points 3 dB below = 9.3 mm

Ratio of SAR at M2 to SAR at M1 = 47.3%

Maximum value of SAR (measured) = 1.11 W/kg



0 dB = 1.11 W/kg = 0.45 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/4

38_LTE Band 3 CH 19575_QPSK_BW 20M_18RB Size 0RB Offset_Right-Tilted_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, Generic LTE (0); Frequency: 1747.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1747.5$ MHz; $\sigma = 1.368$ S/m; $\epsilon_r = 40.476$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(8.14, 8.14, 8.14) @ 1747.5 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 1.09 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 16.83 V/m; Power Drift = -0.15 dB


Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.754 W/kg; SAR(10 g) = 0.347 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 49.6%

Maximum value of SAR (measured) = 1.31 W/kg



0 dB = 1.31 W/kg = 1.17 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2020/12/31

19_LTE Band 7 CH 21350_QPSK_BW 20M_18RB Size 82RB Offset_Right-Cheek_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, Generic LTE (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.935$ S/m; $\epsilon_r = 39.556$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(7.2, 7.2, 7.2) @ 2560 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.575 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.46 V/m; Power Drift = 0.04 dB


Peak SAR (extrapolated) = 0.821 W/kg

SAR(1 g) = 0.341 W/kg; SAR(10 g) = 0.164 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 39.2%

Maximum value of SAR (measured) = 0.581 W/kg



0 dB = 0.581 W/kg = -2.36 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/5

112_LTE Band 8 CH 21750_QPSK_BW 10M_1RB Size 0RB Offset_Right-Cheek_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, Generic LTE (0); Frequency: 910 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 910$ MHz; $\sigma = 0.979$ S/m; $\epsilon_r = 41.458$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(9.3, 9.3, 9.3) @ 910 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 1.06 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 29.88 V/m; Power Drift = -0.06 dB


Peak SAR (extrapolated) = 1.37 W/kg

SAR(1 g) = 0.638 W/kg; SAR(10 g) = 0.395 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 43.6%

Maximum value of SAR (measured) = 0.957 W/kg



0 dB = 0.957 W/kg = -0.19 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2021/1/5

126_LTE Band 28 CH 27560_QPSK_BW 20M_1RB Size 99RB Offset_Right-Cheek_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, Generic LTE (0); Frequency: 738 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 738$ MHz; $\sigma = 0.895$ S/m; $\epsilon_r = 42.715$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(9.54, 9.54, 9.54) @ 738 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.958 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.91 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 1.47 W/kg

SAR(1 g) = 0.633 W/kg; SAR(10 g) = 0.397 W/kg

Smallest distance from peaks to all points 3 dB below = 9.1 mm

Ratio of SAR at M2 to SAR at M1 = 41.1%

Maximum value of SAR (measured) = 1.06 W/kg



0 dB = 1.06 W/kg = 0.25 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2020/12/31

1_LTE Band 38 CH 38000_QPSK_BW 20M_18RB Size 0RB Offset_Right-Cheek_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, Generic LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1.59

Medium parameters used (interpolated): $f = 2595$ MHz; $\sigma = 1.985$ S/m; $\epsilon_r = 39.412$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(7.2, 7.2, 7.2) @ 2595 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.708 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 13.64 V/m; Power Drift = 0.04 dB


Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.423 W/kg; SAR(10 g) = 0.203 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 41.4%

Maximum value of SAR (measured) = 0.687 W/kg



0 dB = 0.687 W/kg = -1.63 dBW/kg

Test Laboratory: A Test Lab Techno Corp.

Date: 2020/12/31

13_LTE Band 41 CH 41140_QPSK_BW 20M_18RB Size 0RB Offset_Right-Cheek_Ant Upper

DUT: M2102J20SG; Type: Mobile Phone

Communication System: UID 0, Generic LTE (0); Frequency: 2645 MHz; Duty Cycle: 1:1.59

Medium parameters used (interpolated): $f = 2645$ MHz; $\sigma = 2.048$ S/m; $\epsilon_r = 39.255$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5.2 Configuration:

- Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV4 - SN3847; ConvF(7.2, 7.2, 7.2) @ 2645 MHz; Calibrated: 2020/5/20
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn541; Calibrated: 2020/3/18
- Phantom: Twin-SAM V4.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: TP-1009
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x131x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.923 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 15.25 V/m; Power Drift = -0.00 dB


Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.523 W/kg; SAR(10 g) = 0.254 W/kg

Smallest distance from peaks to all points 3 dB below = 9.3 mm

Ratio of SAR at M2 to SAR at M1 = 37.3%

Maximum value of SAR (measured) = 0.907 W/kg



0 dB = 0.907 W/kg = -0.42 dBW/kg



Appendix C - Calibration

All of the instruments Calibration information are listed below.

- Dipole _ D750V3 SN:1004
- Dipole _ D900V2 SN:073
- Dipole _ D1800V2 SN:265
- Dipole _ D1900V3 SN:5d111
- Dipole _ D2600V2 SN:1007
- Probe _ EX3DV4 SN:3847
- DAE _ DAE4 SN:541



ST-044_20-185

Client: ATL Certificate No: Z20-60365

CALIBRATION CERTIFICATE

Object: D750V3 - SN: 1004

Calibration Procedure(s): FF-Z11-003-01
Calibration Procedures for dipole validation kits

Calibration date: September 17, 2020

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106276	12-May-20 (CTTL, No.J20X02965)	May-21
Power sensor NRP6A	101369	12-May-20 (CTTL, No.J20X02965)	May-21
ReferenceProbe EX3DV4	SN 3617	30-Jan-20(SPEAG,No.EX3-3617_Jan20)	Jan-21
DAE4	SN 771	10-Feb-20(CTTL-SPEAG,No.Z20-60017)	Feb-21

Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	25-Feb-20 (CTTL, No.J20X00516)	Feb-21
NetworkAnalyzer E5071C	MY46110673	10-Feb-20 (CTTL, No.J20X00515)	Feb-21

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	[Signature]
Reviewed by:	Lin Hao	SAR Test Engineer	[Signature]
Approved by:	Qi Dianyuan	SAR Project Leader	[Signature]

Issued: September 22, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Client ATL

Certificate No: Z20-60158

CALIBRATION CERTIFICATE

Object D900V2 - SN:073

Calibration Procedure(s) FF-Z11-003-01
Calibration Procedures for dipole validation kits

Calibration date: May 8, 2020

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106277	04-Sep-19 (CTTL, No.J19X07825)	Sep-20
Power sensor NRP8S	104291	04-Sep-19 (CTTL, No.J19X07825)	Sep-20
Reference Probe EX3DV4	SN 7307	24-May-19(SPEAG,No.EX3-7307_May19)	May-20
DAE4	SN 1555	22-Aug-19(CTTL-SPEAG,No.Z19-60295)	Aug-20
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	25-Feb-20 (CTTL, No.J20X00516)	Feb-21
NetworkAnalyzer E5071C	MY46110673	10-Feb-20 (CTTL, No.J20X00515)	Feb-21

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: May 10, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z20-60158

Page 1 of 6



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: ctll@chinattl.com http://www.chinattl.cn

Client **ATL**

Certificate No: **Z20-60159**

CALIBRATION CERTIFICATE

Object **D1800V2 - SN: 265**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **April 28, 2020**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106277	04-Sep-19 (CTTL, No.J19X07825)	Sep-20
Power sensor NRP8S	104291	04-Sep-19 (CTTL, No.J19X07825)	Sep-20
Reference Probe EX3DV4	SN 7307	24-May-19(SPEAG,No.EX3-7307_May19)	May-20
DAE4	SN 1555	22-Aug-19(CTTL-SPEAG,No.Z19-60295)	Aug-20
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	25-Feb-20 (CTTL, No.J20X00516)	Feb-21
NetworkAnalyzer E5071C	MY46110673	10-Feb-20 (CTTL, No.J20X00515)	Feb-21

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: May 5, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z20-60159

Page 1 of 6



Client ATL

Certificate No: Z20-60367

CALIBRATION CERTIFICATE

Object D1900V2 - SN: 5d111

Calibration Procedure(s) FF-Z11-003-01
Calibration Procedures for dipole validation kits

Calibration date: September 18, 2020

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106276	12-May-20 (CTTL, No.J20X02965)	May-21
Power sensor NRP6A	101369	12-May-20 (CTTL, No.J20X02965)	May-21
ReferenceProbe EX3DV4	SN 3617	30-Jan-20(SPEAG,No.EX3-3617_Jan20)	Jan-21
DAE4	SN 771	10-Feb-20(CTTL-SPEAG,No.Z20-60017)	Feb-21
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	25-Feb-20 (CTTL, No.J20X00516)	Feb-21
NetworkAnalyzer E5071C	MY46110673	10-Feb-20 (CTTL, No.J20X00515)	Feb-21

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: September 22, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z20-60367

Page 1 of 6



Client **ATL**

Certificate No: **Z20-60374**

CALIBRATION CERTIFICATE

Object **D2600V2 - SN: 1007**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **September 29, 2020**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106276	12-May-20 (CTTL, No.J20X02965)	May-21
Power sensor NRP6A	101369	12-May-20 (CTTL, No.J20X02965)	May-21
Reference Probe EX3DV4	SN 3617	30-Jan-20(SPEAG,No.EX3-3617_Jan20)	Jan-21
DAE4	SN 771	10-Feb-20(CTTL-SPEAG,No.Z20-60017)	Feb-21
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	25-Feb-20 (CTTL, No.J20X00516)	Feb-21
Network Analyzer E5071C	MY46110673	10-Feb-20 (CTTL, No.J20X00515)	Feb-21

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: October 4, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z20-60374

Page 1 of 6



In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

EX-042-20-107

Client **ATL**

Certificate No: **Z20-60165**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN : 3847**

Calibration Procedure(s) **FF-Z11-004-01**
Calibration Procedures for Dosimetric E-field Probes

Calibration date: **May 20, 2020**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	18-Jun-19(CTTL, No.J19X05125)	Jun-20
Power sensor NRP-Z91	101547	18-Jun-19(CTTL, No.J19X05125)	Jun-20
Power sensor NRP-Z91	101548	18-Jun-19(CTTL, No.J19X05125)	Jun-20
Reference 10dBAttenuator	18N50W-10dB	10-Feb-20(CTTL, No.J20X00525)	Feb-22
Reference 20dBAttenuator	18N50W-20dB	10-Feb-20(CTTL, No.J20X00526)	Feb-22
Reference Probe EX3DV4	SN 3617	30-Jan-20(SPEAG, No.EX3-3617_Jan20/2)	Jan-21
DAE4	SN 1556	4-Feb-20(SPEAG, No.DAE4-1556_Feb20)	Feb-21
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGenerator MG3700A	6201052605	18-Jun-19(CTTL, No.J19X05127)	Jun-20
Network Analyzer E5071C	MY46110673	10-Feb-20(CTTL, No.J20X00515)	Feb-21

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: May 22, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Client : ATL

Certificate No: Z20-60115

CALIBRATION CERTIFICATE

Object DAE4 - SN: 541

Calibration Procedure(s) FF-Z11-002-01
Calibration Procedure for the Data Acquisition Electronics (DAEx)

Calibration date: March 18, 2020

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Process Calibrator 753	1971018	24-Jun-19 (CTTL, No.J19X05126)	Jun-20

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: March 20, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.