

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: Certification Ordinance Article 2-1-19
Report No.: RJBDKG-WTW-P21070276F-1
Product: Wireless Keyboard
Brand: logicool G
Model No.: Y-R0069
Received Date: 2023/12/21
Test Date: 2024/1/4 ~ 2024/3/29
Issued Date: 2024/4/10
Applicant: Logitech Far East Ltd.
Address: #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan, R.O.C.
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory
Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan
Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

Approved by: _____

May Chen / Manager

, Date: _____

2024/4/10

This test report consists of 61 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Phoenix Huang / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Supplementary Information	5
3 General Information	6
3.1 General Description	6
3.2 Output Power Description of EUT	7
3.3 Antenna Description of EUT	8
3.4 Channel List	9
3.5 Power Setting	10
3.6 Test Mode Applicability and Tested Channel Detail	11
4 Test Instruments	12
4.1 Frequency Tolerance	12
4.2 Occupied Bandwidth	12
4.3 Spurious Emissions	12
4.4 Spurious Emissions of Receiver	12
4.5 Antenna Power	13
4.6 Interference Prevention Function	13
5 Limits of Test Items	14
5.1 Frequency Tolerance	14
5.2 Occupied Bandwidth	14
5.3 Spurious Emissions	14
5.4 Spurious Emissions of Receiver	14
5.5 Antenna Power	14
5.6 Interference Prevention Function	15
6 Test Arrangements	16
6.1 Frequency Tolerance	16
6.2 Occupied Bandwidth	16
6.3 Spurious Emissions	16
6.4 Spurious Emissions of Receiver	16
6.5 Antenna Power	16
6.6 Interference Prevention Function	17
7 Test Results of Test Item	18
7.1 Frequency Tolerance	18
7.2 Occupied Bandwidth	19
7.3 Spurious Emissions	27
7.4 Spurious Emissions of Receiver	49
7.5 Antenna Power	57
7.6 Interference Prevention Function	59
8 Pictures of Test Arrangements	60
9 Information of the Testing Laboratories	61



Release Control Record

Issue No.	Description	Date Issued
RJBDBG-WTW-P21070276F-1	Original release.	2024/4/10

1 Certificate

Product: Wireless Keyboard

Brand: logicool G

Test Model: Y-R0069

Sample Status: Engineering sample

Applicant: Logitech Far East Ltd.

Test Date: 2024/1/4 ~ 2024/3/29

Standard: Certification Ordinance Article 2-1-19

Measurement procedure: MIC notice 88 Appendix 43

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

Certification Ordinance Article 2-1-19		
Clause	Test Item	Result
OR: Article 5 OR: Annex 1 table 7-8	Frequency Tolerance	Pass
OR: Article 6 Annex 2.30	Occupied Bandwidth	Pass
OR: Article 7. Annex 3.26	Spurious Emissions	Pass
OR: Article 49-20	Antenna Specifications	Pass
OR: Article 24.2	Spurious Emissions of Receiver	Pass
OR: Article 49-20	Housing Requirements	Pass (Refer to Note 1)
OR: Article 49-20	Antenna Power	Pass
OR: Article 49-20	Absolute Gain of Transmitting Antenna	Pass
OR: Article 49-20	Angular Width of Principal Radiation (AWPR)	N/A
OR: Article 49-20	Number of Carriers within 1 MHz Bandwidth in OFDM	N/A
OR: Article 49-20	Dwell Time (FH employed)	N/A
OR: Article 9-4.5 RE: Article 6-2.3 RE: Article 6-2.5	Interference Prevention Function	Pass
OR: Article 49-20	Carrier Sense Capability	N/A

Notes:

1. The relative information refer section 3.1 of this report.
2. OR: Ordinance Regulating Radio Equipment
3. RE: Regulations for Enforcement of the radio law
4. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in ETSI TR 100 028-1 and ETSI TR 100 028-2:

Parameter	Uncertainty (±)
Occupied Bandwidth	1050.00 Hz
Spurious Emissions	2.5 dB
Output Power Density	1.2 dB
Frequency Tolerance	960 Hz

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Wireless Keyboard
Brand	logicool G
Test Model	Y-R0069
Test Software Version	RF Sample with Receiver [Number Lock]
Status of EUT	Engineering sample
Power Supply Rating	3.7Vdc from battery or 5Vdc from USB interface
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	Up to 2 Mbps (*Note 1)
Operating Frequency	2.402 ~ 2.480 GHz (*Note 1)
Number of Channel	40 (*Note 1)
Accessory	1. USB-A to USB-C cable x 1 (shielded, 1.8 m with one core)(Color: black, white) 2. USB Extender x 1 (Color: black, white)
Assembly	The EUT is constructed as a Wireless Keyboard. The housing consists of two plastic parts, the plastic enclosure was fixed together by screws with pad to hold screwing hole under table. The pad is small so the screw can't be observed directly. Also it won't be easy to be opened.

Note:

1. BT-LE technique supports 1Mbps and 2Mbps data rates, both have been evaluated in this test report. Refer to "section 3.4 Channel List" for more detail specification.
2. The EUT may have a lot of colors for marketing requirement.
3. The device of GFSK and Bluetooth technology can't transmit simultaneously.
4. The EUT could be supplied with rechargeable battery as the following table:

No.	Manufacturer	Model	Specification
1	SYNERGY SCIEN TECH CORP.	AHB355085PCT-03 or 533-000210	Power Rating : 3.7 Vdc, 1500 mAh, 5.6 Wh
2	SYNERGY SCIENTECH CORP.	AHB355085PCT-02 or 533-000152	Power Rating : 3.7 Vdc, 1500 mAh, 5.6 Wh
3	Springpower Technology (Shenzhen) Co., Ltd.	325085 or 533-000204	Power Rating : 3.7 Vdc, 1500 mAh, 5.55 Wh

5. The EUT could be supplied configurations A and B as the following table:

Configuration	Remark
A	Configuration A and B are different suppliers of PCB/Power IC/Charger IC/Power Connector.
B	

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Output Power Description of EUT

Operation Mode	Channel Number	Rated Output Power (mW)	Conducted RF Output Power (mW)	Radiated RF Output Power (mW)
BT-LE 1M	0	3	1.738	6.84
	19	3	1.977	7.295
	39	3	2.223	6.456
BT-LE 2M	1	3	1.667	6.56
	19	3	1.901	7.014
	37	3	2.234	6.488

3.3 Antenna Description of EUT

1. The antenna information is listed as below.

Frequency (MHz)	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
2403	logitech G	Y-R0069	5.95	2.4~2.4835	PIFA	none
2442			5.67			
2479			4.63			

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. Antenna Pattern:

Please refer to the attached file (Antenna pattern).

3.4 Channel List

BT-LE channels:

RF Channel	RF Center Frequency	Channel Index	Channels Type for BT 5.x		Channels Type for BT 4.x
			Maximum Data Rate 2Mbps	Maximum Data Rate 1Mbps	Maximum Data Rate 1Mbps
0	2402 MHz	37		●	●
1	2404 MHz	0	●		●
2	2406 MHz	1	●		●
3	2408 MHz	2	●		●
4	2410 MHz	3	●		●
5	2412 MHz	4	●		●
6	2414 MHz	5	●		●
7	2416 MHz	6	●		●
8	2418 MHz	7	●		●
9	2420 MHz	8	●		●
10	2422 MHz	9	●		●
11	2424 MHz	10	●		●
12	2426 MHz	38		●	●
13	2428 MHz	11	●		●
14	2430 MHz	12	●		●
15	2432 MHz	13	●		●
16	2434 MHz	14	●		●
17	2436 MHz	15	●		●
18	2438 MHz	16	●		●
19	2440 MHz	17	●		●
20	2442 MHz	18	●		●
21	2444 MHz	19	●		●
22	2446 MHz	20	●		●
23	2448 MHz	21	●		●
24	2450 MHz	22	●		●
25	2452 MHz	23	●		●
26	2454 MHz	24	●		●
27	2456 MHz	25	●		●
28	2458 MHz	26	●		●
29	2460 MHz	27	●		●
30	2462 MHz	28	●		●
31	2464 MHz	29	●		●
32	2466 MHz	30	●		●
33	2468 MHz	31	●		●
34	2470 MHz	32	●		●
35	2472 MHz	33	●		●
36	2474 MHz	34	●		●
37	2476 MHz	35	●		●
38	2478 MHz	36	●		●
39	2480 MHz	39		●	●

3.5 Power Setting

Power Setting			
Channel	BT-LE 1M	Channel	BT-LE 2M
0	Default	1	Default
19	Default	19	Default
39	Default	38	Default

3.6 Test Mode Applicability and Tested Channel Detail

Test Conditions	Voltage (Vdc)
V_{normal}	3.7
$V_{max. (+10\%)}$	4.07
$V_{min. (-10\%)}$	3.33

Pre-Scan:	1. For EUT input voltage has 5 Vdc/ 3.7 Vdc conditions. Pre-scan these ways and find the worst case as a representative test condition. 2. The EUT has the following config of different suppliers: configuration A/ B. Pre-scan these configs of EUT and find the worst case as a representative test condition. 3. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
Worst Case:	1. The EUT input voltage worst condition: 3.7 Vdc 2. EUT Worst configuration: A

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
Frequency Tolerance	BT-LE 1M	0, 19, 39	unmodulated	-
	BT-LE 2M	1, 19, 38	unmodulated	-
Occupied Bandwidth	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	1, 19, 38	GFSK	2Mb/s
Spurious Emissions	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	1, 19, 38	GFSK	2Mb/s
Spurious Emissions of Receiver	BT-LE 1M	0, 19, 39	-	-
	BT-LE 2M	1, 19, 38	-	-
Antenna Power	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	1, 19, 38	GFSK	2Mb/s
Interference Prevention Function	Normal Operation			

Test Item	Operation Description
Frequency Tolerance	BLE1M TX Unmodulated 2402MHz BLE1M TX Unmodulated 2440MHz BLE1M TX Unmodulated 2480MHz BLE2M TX Unmodulated 2404MHz BLE2M TX Unmodulated 2440MHz BLE2M TX Unmodulated 2478MHz
Occupied Bandwidth	BLE1M TX Modulated 2402MHz BLE1M TX Modulated 2440MHz BLE1M TX Modulated 2480MHz BLE2M TX Modulated 2404MHz BLE2M TX Modulated 2440MHz BLE2M TX Modulated 2478MHz
Spurious Emissions	
Antenna Power	
Spurious Emissions of Receiver	BLE1M RX 2402MHz BLE1M RX 2440MHz BLE1M RX 2480MHz BLE2M RX 2404MHz BLE2M RX 2440MHz BLE2M RX 2478MHz
Interference Prevention Function	Normal mode

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 Frequency Tolerance

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until	Calibration Authority	Calibration Method
DC Power Supply Topward	6603D	795558	Note 2	Note 2	BV CPS E&E	(d)
MXA Signal Analyzer Keysight	N9020B	MY60112409	2024/2/20	2025/2/19	ETC	(c)
Software	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A	N/A	N/A
True RMS Clamp Meter FLUKE	325	31130711WS	2023/6/8	2024/6/7	ETC	(c)

Notes:

- Calibration method:
 - Calibration conducted by the National Institute of Information and Communications Technology (NICT) or a designated calibration agency under Article 102-18 paragraph (1).
 - Calibration conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992) Japan Calibration Service System.
 - Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
 - Calibration conducted by using other equipment that listed above from a) to c).
- The power supply no evaluation calibrated, which used the RMS clamp meter to verify before each testing.
- The test was performed in Oven room 2.
- Tested Date: 2024/3/28

4.2 Occupied Bandwidth

Refer to section 4.1 to get the tested date and information of the instruments.

4.3 Spurious Emissions

Refer to section 4.1 to get the tested date and information of the instruments.

4.4 Spurious Emissions of Receiver

Refer to section 4.1 to get the tested date and information of the instruments.

4.5 Antenna Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until	Calibration Authority	Calibration Method
DC Power Supply Topward	6603D	795558	Note 2	Note 2	BV CPS E&E	(d)
Pulse Power Sensor Anritsu	MA2411B	1726434	2023/6/19	2024/6/18	ETC	(c)
RF Power Meter Anritsu	ML2495A	1529002	2023/6/17	2024/6/16	ETC	(c)
True RMS Clamp Meter FLUKE	325	31130711WS	2023/6/8	2024/6/7	ETC	(c)

Notes:

- Calibration method:
 - Calibration conducted by the National Institute of Information and Communications Technology (NICT) or a designated calibration agency under Article 102-18 paragraph (1).
 - Calibration conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992) Japan Calibration Service System.
 - Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
 - Calibration conducted by using other equipment that listed above from a) to c).
- The power supply no evaluation calibrated, which used the RMS clamp meter to verify before each testing.
- The test was performed in Oven room 2.
- Tested Date: 2024/3/29

4.6 Interference Prevention Function

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until	Calibration Authority	Calibration Method
Bluetooth Simulator Anritsu	MT8852B	1218002	2023/5/21	2024/5/20	ETC	(c)
DC Power Supply Topward	6603D	795558	Note 2	Note 2	BV CPS E&E	(d)
Fixed Attenuator Woken	MDCS18N-10	MDCS18N-10-01	2023/3/27	2024/3/26	BV CPS E&E	(d)
True RMS Clamp Meter FLUKE	325	31130711WS	2023/6/8	2024/6/7	ETC	(c)

Notes:

- Calibration method:
 - Calibration conducted by the National Institute of Information and Communications Technology (NICT) or a designated calibration agency under Article 102-18 paragraph (1).
 - Calibration conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992) Japan Calibration Service System.
 - Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
 - Calibration conducted by using other equipment that listed above from a) to c).
- The power supply no evaluation calibrated, which used the RMS clamp meter to verify before each testing.
- The test was performed in Oven room 2.
- Tested Date: 2024/1/4

5 Limits of Test Items

5.1 Frequency Tolerance

Tolerance of frequency shall be +/- 50ppm.

5.2 Occupied Bandwidth

Modulation Method	Limit	Remark
DSSS	<26 MHz	
OFDM	<26 MHz	Antenna power limitation is 10 mW/MHz
	26 – 40 MHz	Antenna power limitation is 5 mW/MHz
FHSS	<83.5 MHz	
Other Digital	<26 MHz	

5.3 Spurious Emissions

Frequencies	Limit
Operating frequency 2400 to 2483.5 MHz	
30.0 MHz to 1000.0 MHz	$\leq 0.25 \text{ uW/100 kHz}$
1000.0 MHz to 2387 MHz	$\leq 2.5 \text{ uW/MHz}$
2387.0 MHz to 2400.0 MHz	$\leq 25 \text{ uW/MHz}$
2483.5 MHz to 2496.5 MHz	$\leq 25 \text{ uW/MHz}$
2496.5 MHz to 12500.0 MHz	$\leq 2.5 \text{ uW/MHz}$

5.4 Spurious Emissions of Receiver

Frequencies	Limit
Below 1 GHz	$\leq 4 \text{ nW}$
Above 1 GHz	$\leq 20 \text{ nW}$

5.5 Antenna Power

Modulation System	Frequency Band Used	Antenna Power (Max.)	E.I.R.P. Limit (Note 3)
DSSS	2400 – 2483.5 MHz	10 mW/MHz	12.14 dBm/MHz ~ 22.14 dBm/MHz (16.368 mW/MHz ~ 163.68 mW/MHz)
OFDM (Note 1)	2400 – 2483.5 MHz	10 mW/MHz	12.14 dBm/MHz ~ 22.14 dBm/MHz (16.368 mW/MHz ~ 163.68 mW/MHz)
OFDM (Note 2)	2400 – 2483.5 MHz	5 mW/MHz	9.13 dBm/MHz ~ 19.13 dBm/MHz (8.184 mW/MHz ~ 81.84 mW/MHz)
FHSS	2400 – 2483.5 MHz	3 mW/MHz	6.91 dBm/MHz ~ 16.91 dBm/MHz (4.91 mW/MHz ~ 49.10 mW/MHz)
Other Digital	2400 – 2483.5 MHz	10 mW	12.14 dBm ~ 22.14 dBm (16.368 mW ~ 163.68 mW)

Notes:

- Occupied bandwidth is less than 26 MHz.
- Occupied bandwidth is more than 26 MHz and less than 40 MHz.
- E.I.R.P. limit is variable by the HPBA, the HPBA (half-power beam width) of the antenna shall be 360 / A degrees or less, where $A = \text{E.I.R.P.} / (2.14 \text{ dBi} + \text{"Antenna Power (limit)"})$.
- Tolerance of antenna power shall be +20% (upper value).

5. When an E.I.R.P. is less than 2.14 dBi + antenna power limit. The shortage can be compensated for by the antenna power. (Application to transmitting devices using "Other method" is Limited to "GFSK")


5.6 Interference Prevention Function

When conducting wireless communications that transmit data or other information: A function that automatically sends or receives an identification code.


When performing radiolocation work: A function that allows you to distinguish between reflected waves of radio waves transmitted by your own station and radio waves transmitted by other radio stations by identifying the modulation method and other characteristics of received radio waves. (However, if it also has the function of transmitting signals for data transmission, both functions shall be included.)

6 Test Arrangements

6.1 Frequency Tolerance




6.2 Occupied Bandwidth




6.3 Spurious Emissions




6.4 Spurious Emissions of Receiver



6.5 Antenna Power



6.6 Interference Prevention Function



7 Test Results of Test Item

7.1 Frequency Tolerance

Environmental Conditions:	22°C, 64% RH	Tested By:	Katina Lu
---------------------------	--------------	------------	-----------

BT-LE 1M

Channel	Frequency (MHz)	V_{normal}		$V_{max.}$		$V_{min.}$	
		Carrier frequency (MHz)	Frequency tolerance (ppm)	Carrier frequency (MHz)	Frequency tolerance (ppm)	Carrier frequency (MHz)	Frequency tolerance (ppm)
0	2402	2402.005400	2.248	2402.005240	2.181	2402.005240	2.181
19	2440	2440.005420	2.221	2440.005420	2.221	2440.005400	2.213
39	2480	2480.005460	2.201	2480.005420	2.185	2480.005520	2.225

BT-LE 2M

Channel	Frequency (MHz)	V_{normal}		$V_{max.}$		$V_{min.}$	
		Carrier frequency (MHz)	Frequency tolerance (ppm)	Carrier frequency (MHz)	Frequency tolerance (ppm)	Carrier frequency (MHz)	Frequency tolerance (ppm)
1	2404	2404.005300	2.204	2404.005260	2.188	2404.005240	2.179
19	2440	2440.005400	2.213	2440.005300	2.172	2440.005320	2.180
38	2478	2478.005420	2.187	2478.005360	2.163	2478.005420	2.187

7.2 Occupied Bandwidth

Environmental Conditions:	22°C, 64% RH	Tested By:	Katina Lu
---------------------------	--------------	------------	-----------


BT-LE 1M


Channel	Frequency (MHz)	V_{normal}	$V_{max.}$	$V_{min.}$
		Occupied Bandwidth (MHz)	Occupied Bandwidth (MHz)	Occupied Bandwidth (MHz)
0	2402	1.28	1.28	1.27
19	2440	1.28	1.28	1.28
39	2480	1.29	1.29	1.28

NOTE: For the test plots please refer to the below pages.




BUREAU
VERITAS







BUREAU
VERITAS




BT-LE 2M

Channel	Frequency (MHz)	V_{normal}	$V_{max.}$	$V_{min.}$
		Occupied Bandwidth (MHz)	Occupied Bandwidth (MHz)	Occupied Bandwidth (MHz)
1	2404	2.18	2.18	2.17
19	2440	2.19	2.18	2.19
38	2478	2.19	2.19	2.19

NOTE: For the test plots please refer to the below pages.




BUREAU
VERITAS






BUREAU
VERITAS





BUREAU
VERITAS



7.3 Spurious Emissions


Environmental Conditions:	22°C, 64% RH	Tested By:	Katina Lu
---------------------------	--------------	------------	-----------


BT-LE 1M

TEST CHANNEL		CH 0 (2402 MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASUREMENT VALUE	LIMIT	RESULT
V_{normal}	30.0 to 1000.0	567.501	0.000865 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2373.997	0.187068 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2399.994	1.475707 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2488.846	0.189234 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	10739.384	0.327341 uW/MHz	2.5 uW/MHz	PASS
V_{max.}	30.0 to 1000.0	892.694	0.000828 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2364.808	0.140929 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2400.000	1.227439 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2486.152	0.176604 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3819.463	0.391742 uW/MHz	2.5 uW/MHz	PASS
V_{min.}	30.0 to 1000.0	857.046	0.000773 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2350.591	0.144544 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2399.997	1.717908 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2494.691	0.150314 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3674.412	0.42658 uW/MHz	2.5 uW/MHz	PASS
TEST CHANNEL		CH 19 (2440 MHz)			
V_{normal}	30.0 to 1000.0	912.579	0.000946 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2387.000	0.17378 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2388.331	0.147231 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2492.688	0.172187 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3905.743	0.338844 uW/MHz	2.5 uW/MHz	PASS
V_{max.}	30.0 to 1000.0	538.038	0.000771 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2373.823	0.166341 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2397.194	0.146893 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2488.606	0.158125 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3913.246	0.360579 uW/MHz	2.5 uW/MHz	PASS
V_{min.}	30.0 to 1000.0	912.094	0.0008 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2241.192	0.149624 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2388.498	0.137404 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2491.606	0.178649 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3686.916	0.348337 uW/MHz	2.5 uW/MHz	PASS







TEST CHANNEL		CH 39 (2480 MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASUREMENT VALUE	LIMIT	RESULT
V_{normal}	30.0 to 1000.0	886.995	0.000881 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2366.022	0.166341 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2398.619	0.159221 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2494.027	0.228034 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3825.715	0.304789 uW/MHz	2.5 uW/MHz	PASS
V_{max.}	30.0 to 1000.0	896.695	0.000736 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2352.498	0.155955 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2387.702	0.158855 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2495.974	0.177011 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3785.701	0.402717 uW/MHz	2.5 uW/MHz	PASS
V_{min.}	30.0 to 1000.0	891.724	0.000769 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2285.749	0.142561 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2397.408	0.153815 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2483.799	0.177011 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3859.477	0.314051 uW/MHz	2.5 uW/MHz	PASS

NOTE: 1. The spectrum plots are attached on the following pages.












V min.



CH 0 (2402 MHz)









V max.




CH 19 (2440 MHz)







V min.



CH 19 (2440 MHz)









Vmax.



CH 39 (2480 MHz)

V min.



CH 39 (2480 MHz)


BT-LE 2M

TEST CHANNEL		CH 1 (2404 MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASUREMENT VALUE	LIMIT	RESULT
V_{normal}	30.0 to 1000.0	867.837	0.000774 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2306.207	0.149624 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2399.564	0.138357 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2489.825	0.167109 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3769.445	0.345939 uW/MHz	2.5 uW/MHz	PASS
V_{max.}	30.0 to 1000.0	916.944	0.000859 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2330.133	0.132739 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2392.046	0.153462 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2489.768	0.157036 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3770.696	0.331894 uW/MHz	2.5 uW/MHz	PASS
V_{min.}	30.0 to 1000.0	970.658	0.000879 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2336.548	0.156315 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2398.006	0.148252 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2483.934	0.163305 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	4921.098	0.335738 uW/MHz	2.5 uW/MHz	PASS
TEST CHANNEL		CH 19 (2440 MHz)			
V_{normal}	30.0 to 1000.0	868.201	0.000824 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2361.167	0.161065 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2388.191	0.174985 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2488.078	0.163682 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3718.177	0.34914 uW/MHz	2.5 uW/MHz	PASS
V_{max.}	30.0 to 1000.0	847.952	0.000861 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2347.644	0.154882 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2387.533	0.150661 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2487.077	0.214783 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3760.692	0.333426 uW/MHz	2.5 uW/MHz	PASS
V_{min.}	30.0 to 1000.0	918.641	0.000752 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2386.653	0.145546 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2391.248	0.157761 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2488.898	0.162555 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3896.990	0.389045 uW/MHz	2.5 uW/MHz	PASS

TEST CHANNEL		CH 38 (2478 MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASUREMENT VALUE	LIMIT	RESULT
V_{normal}	30.0 to 1000.0	729.612	0.000828 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2282.975	0.147911 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2397.142	0.146555 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2488.663	0.161808 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3686.916	0.302691 uW/MHz	2.5 uW/MHz	PASS
V_{max.}	30.0 to 1000.0	854.985	0.000897 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2156.585	0.146218 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2390.328	0.141906 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2487.283	0.161065 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	8379.808	0.325837 uW/MHz	2.5 uW/MHz	PASS
V_{min.}	30.0 to 1000.0	890.511	0.000957 uW/100kHz	0.25 uW/100kHz	PASS
	1000.0 to 2387.0	2330.306	0.146555 uW/MHz	2.5 uW/MHz	PASS
	2387.0 to 2400.0	2390.567	0.161436 uW/MHz	25 uW/MHz	PASS
	2483.5 to 2496.5	2494.622	0.159221 uW/MHz	25 uW/MHz	PASS
	2496.5 to 12500.0	3728.181	0.341193 uW/MHz	2.5 uW/MHz	PASS







NOTE: 1. The spectrum plots are attached on the following pages.

Vnormal









CH 1 (2404 MHz)

V max.




CH 1 (2404 MHz)







V min.



CH 1 (2404 MHz)




V max.




CH 19 (2440 MHz)

V min.









CH 19 (2440 MHz)

Vnormal









CH 38 (2478 MHz)

Vmax.



CH 38 (2478 MHz)

V min.



CH 38 (2478 MHz)


7.4 Spurious Emissions of Receiver


Environmental Conditions:	22°C, 64% RH	Tested By:	Katina Lu
---------------------------	--------------	------------	-----------


BT-LE 1M

TEST CHANNEL		CH 0 (2402 MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASUREMENT VALUE(nW)	LIMIT (nW)	RESULT
V_{normal}	30.0 to 1000.0	175.985	0.048084	4	PASS
	1000.0 to 12500.0	4802.187	0.619441	20	PASS
$V_{max.}$	30.0 to 1000.0	183.988	0.052966	4	PASS
	1000.0 to 12500.0	4802.187	0.592925	20	PASS
$V_{min.}$	30.0 to 1000.0	175.985	0.049545	4	PASS
	1000.0 to 12500.0	4802.187	0.647143	20	PASS
TEST CHANNEL		CH 19 (2440 MHz)			
V_{normal}	30.0 to 1000.0	175.985	0.050003	4	PASS
	1000.0 to 12500.0	4878.375	0.345939	20	PASS
$V_{max.}$	30.0 to 1000.0	175.985	0.048417	4	PASS
	1000.0 to 12500.0	4878.375	0.356451	20	PASS
$V_{min.}$	30.0 to 1000.0	175.985	0.054576	4	PASS
	1000.0 to 12500.0	4878.375	0.346737	20	PASS
TEST CHANNEL		CH 39 (2480 MHz)			
V_{normal}	30.0 to 1000.0	183.988	0.050816	4	PASS
	1000.0 to 12500.0	4957.437	0.49545	20	PASS
$V_{max.}$	30.0 to 1000.0	183.988	0.048084	4	PASS
	1000.0 to 12500.0	4957.437	0.496592	20	PASS
$V_{min.}$	30.0 to 1000.0	175.985	0.047973	4	PASS
	1000.0 to 12500.0	4957.437	0.462381	20	PASS

NOTE: 1. The spectrum plots are attached on the following pages.











BT-LE 2M


TEST CHANNEL		CH 0 (2402 MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASUREMENT VALUE(nW)	LIMIT (nW)	RESULT
V_{normal}	30.0 to 1000.0	175.985	0.048084	4	PASS
	1000.0 to 12500.0	4802.187	0.619441	20	PASS
V_{max.}	30.0 to 1000.0	183.988	0.052966	4	PASS
	1000.0 to 12500.0	4802.187	0.592925	20	PASS
V_{min.}	30.0 to 1000.0	175.985	0.049545	4	PASS
	1000.0 to 12500.0	4802.187	0.647143	20	PASS
TEST CHANNEL		CH 19 (2440 MHz)			
V_{normal}	30.0 to 1000.0	175.985	0.050003	4	PASS
	1000.0 to 12500.0	4878.375	0.345939	20	PASS
V_{max.}	30.0 to 1000.0	175.985	0.048417	4	PASS
	1000.0 to 12500.0	4878.375	0.356451	20	PASS
V_{min.}	30.0 to 1000.0	175.985	0.054576	4	PASS
	1000.0 to 12500.0	4878.375	0.346737	20	PASS
TEST CHANNEL		CH 39 (2480 MHz)			
V_{normal}	30.0 to 1000.0	183.988	0.050816	4	PASS
	1000.0 to 12500.0	4957.437	0.49545	20	PASS
V_{max.}	30.0 to 1000.0	183.988	0.048084	4	PASS
	1000.0 to 12500.0	4957.437	0.496592	20	PASS
V_{min.}	30.0 to 1000.0	175.985	0.047973	4	PASS
	1000.0 to 12500.0	4957.437	0.462381	20	PASS

NOTE: 1. The spectrum plots are attached on the following pages.

V_{normal}V_{max}V_{min}

CH 0 (2402 MHz)





7.5 Antenna Power

Environmental Conditions:	25°C, 60% RH	Tested By:	Kevin Ko
---------------------------	--------------	------------	----------

For BT-LE 1M

Voltage (Vdc)	Channel Number	Frequency (MHz)	Conducted RF Output Power (mW)	Radiated RF Output Power (mW)
3.7	0	2402	1.663	6.545
	19	2440	1.901	7.014
	39	2480	2.168	6.296
4.07	0	2402	1.596	6.281
	19	2440	1.977	7.295
	39	2480	2.223	6.456
3.33	0	2402	1.738	6.84
	19	2440	1.858	6.856
	39	2480	2.08	6.04
Maximum Limit (mW):			10	-
Rated Power (mW):			3	-
Tolerance of Antenna Power (mW):			3.6	-
Maximum EIRP Limit (mW):			-	16.368

Notes:

1. Antenna gain of 2402 MHz is 5.95 dBi.
2. Antenna gain of 2440 MHz is 5.67 dBi.
3. Antenna gain of 2480 MHz is 4.63 dBi.
4. The radiated RF output power is a "calculated" value derived from the conducted value.
5. Formula: Radiated RF output power = Conducted RF output power + Antenna gain

For BT-LE 2M

Voltage (Vdc)	Channel Number	Frequency (MHz)	Conducted RF Output Power (mW)	Radiated RF Output Power (mW)
3.7	1	2404	1.667	6.56
	19	2440	1.901	7.014
	38	2478	2.148	6.238
4.07	1	2404	1.644	6.47
	19	2440	1.897	7
	38	2478	2.168	6.296
3.33	1	2404	1.641	6.458
	19	2440	1.837	6.778
	38	2478	2.234	6.488
Maximum Limit (mW):			10	-
Rated Power (mW):			3	-
Tolerance of Antenna Power (mW):			3.6	-
Maximum EIRP Limit (mW):			-	16.368

Notes:

1. Antenna gain of 2404 MHz is 5.95 dBi.
2. Antenna gain of 2440 MHz is 5.67 dBi.
3. Antenna gain of 2478 MHz is 4.63 dBi.
4. The radiated RF output power is a "calculated" value derived from the conducted value.
5. Formula: Radiated RF output power = Conducted RF output power + Antenna gain

7.6 Interference Prevention Function

Environmental Conditions:	22°C, 55% RH	Tested By:	Kevin Ko
Link Mode		Test Result	
BT-LE		Pass	

8 Pictures of Test Arrangements



9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---