

NCC

低功率射頻電機型式試驗報告

產品名稱 : 藍牙耳機
型號 : T2
廠牌 : Klipsch
商標 : 
申請者 : 鈺環數位音響有限公司
申請者地址 : 臺中市霧峰區五福里中投西路二段 442 號
測試標準 : LP0002 (107 年版)
參考法規 : ANSI C63.10-2013
測試結果 : 符合
接收日期 : 2020/8/5
測試日期 : 2020/8/7~2020/8/27

測試工程師

: 
(陳駿豪)

報告審核人

: 
(陳柏均)

報告簽屬人

: 
(柯承志)



修訂紀錄

報告編號	版本	描述	發行日期
2010TW3701-T3	1.0	Original Report	2020-10-29

備註: 原始報告為 2008TW3701-T3,證號為 CCAH20LP0720E0, 此次為複製報告, 因市場銷售需求僅變更產品型號, 依工程判定不須重新檢測比對新器材設備之主波輸出功率/電場強度與原取得審驗案件器材設備於 $\pm 2\text{dB}$ 範圍內之要求, 並沿用原報告之數據內容。

CONTENTS

Description	Page
1. 一般資訊.....	5
2. 產品描述.....	6
2.1 產品資訊.....	6
2.2 產品規格.....	7
2.3 測試模式.....	8
2.4 測試配置.....	9
2.5 測試周邊.....	11
2.6 操作程序.....	11
3. 測試設備明細.....	12
4. 量測不確定度.....	13
5. 測試結果.....	14
5.1 電源傳導測試.....	15
5.1.1 量測方法.....	15
5.1.2 限制要求.....	15
5.1.3 測試架構圖.....	15
5.1.4 電源傳導測試結果.....	16
5.2 峰值傳導輸出功率.....	22
5.2.1 量測方法.....	22
5.2.2 限制要求.....	22
5.2.3 測試架構圖.....	22
5.2.4 峰值傳導輸出功率測試結果.....	23
5.3 天線之要求.....	26
5.3.1 限制要求.....	26
5.3.2 天線樣式.....	26
5.4 帶外發射限制.....	27
5.4.1 量測方法.....	27
5.4.2 限制要求.....	27
5.4.3 測試架構圖.....	27
5.4.4 帶外輻射測試結果.....	28
5.5 輻射電場強度.....	32
5.5.1 量測方法.....	32
5.5.2 限制要求.....	32
5.5.3 測試架構圖.....	33
5.5.4 輻射電場強度測試結果.....	35

5.6 頻帶邊緣	61
5.6.1 量測方法	61
5.6.2 限制要求	61
5.6.3 測試架構圖	62
5.6.4 頻帶邊緣測試結果	63
5.7 間隔頻寬	72
5.7.1 量測方法	72
5.7.2 限制要求	72
5.7.3 測試架構圖	72
5.7.4 間隔頻寬測試結果	73
5.8 跳頻頻道數	76
5.8.1 量測方法	76
5.8.2 限制要求	76
5.8.3 測試架構圖	76
5.8.4 跳頻頻道數測試結果	77
5.9 占用時間	78
5.9.1 量測方法	78
5.9.2 限制要求	78
5.9.3 測試架構圖	78
5.9.4 占用時間測試結果	79

1. 一般資訊

申請者	鈺環數位音響有限公司
申請者地址	臺中市霧峰區五福里中投西路二段 442 號
製造商	XIAMEN ACOUSYCOM ELECTRONIC CO.,LTD
實驗室	台灣曼瑞檢測科技有限公司
實驗室地址	33377 台灣桃園市龜山區復興二路 38 號
實驗室資訊	1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm. 2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada. 3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.
實驗室測試環境條件	溫度 (°C) : 20-35 / 濕度 (%RH) : 30-65

2. 產品描述

2.1 產品資訊

產品名稱	藍牙耳機
產品型號	T2
廠牌	Klipsch
商標	
頻率範圍	2402~2480MHz
規格	Bluetooth Dual Mode: V5.0
調變模式	FHSS (GFSK, $\pi/4$ DQPSK, 8DPSK)
待測物電壓	By Battery (DC 3.7V)
最大輸出功率	8.702dBm
USB Type C Cable	Brand: Klipsch M/N: T2 USB Length: 50cm
無線充電盒 #1	Brand: Klipsch Product Name: Charging Case (Wireless charging) M/N: T2
充電盒 #2	Brand: Klipsch Product Name: Charging Case M/N: T2

2.2 產品規格

Type of modulation	FHSS (GFSK, $\pi/4$ DQPSK, 8DPSK)
Data Rate	1Mbps(GFSK), 2Mbps($\pi/4$ DQPSK), 3Mbps(8DPSK)

V5.0

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz
03	2405 MHz	04	2406 MHz	05	2407 MHz
06	2408 MHz	07	2409 MHz	08	2410 MHz
09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz
15	2417 MHz	16	2418 MHz	17	2419 MHz
18	2420 MHz	19	2421 MHz	20	2422 MHz
21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz
27	2429 MHz	28	2430 MHz	29	2431 MHz
30	2432 MHz	31	2433 MHz	32	2434 MHz
33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz
39	2441 MHz	40	2442 MHz	41	2443 MHz
42	2444 MHz	43	2445 MHz	44	2446 MHz
45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz
51	2453 MHz	52	2454 MHz	53	2455 MHz
54	2456 MHz	55	2457 MHz	56	2458 MHz
57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz
63	2465 MHz	64	2466 MHz	65	2467 MHz
66	2468 MHz	67	2469 MHz	68	2470 MHz
69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz
75	2477 MHz	76	2478 MHz	77	2479 MHz
78	2480 MHz	N/A	N/A	N/A	N/A

2.3 測試模式


Test Mode	Mode 1: 發射器- 1Mbps(GFSK)
	Mode 2: 發射器- 3Mbps(8DPSK)
	Mode 3: 接收機- 1Mbps(GFSK)
	Mode 4: Normal Mode(Charge with Charging Case (Wireless charging))
	Mode 5: Normal Mode(Charge with Charging Case)

Note:

1. 經初測驗證過，1GHz 以下的 Mode 1 & Mode 2 並無明顯差異，故僅檢附最差狀況之 Mode1。
2. 2Mbps 速率測試數據類似於 3Mbps，因此僅檢附 1Mbps 和 3Mbps 之測試數據。
3. 此右耳產品與 2008TW3701-T1 & 2008TW3701-T5 為成套販售且互相搭配測試，所以 Mode4 /Mode5 的測試數據皆與 2008TW3701-T1 的 Mode4/Mode5 測試數據一致。


2.4 測試配置

待測物測試配置圖 (Mode1~Mode3)



Signal Cable Type		Signal Cable Description
A	USB Cable	Shielded, 1.0m
B	USB Mouse Cable	Shielded, 1.6m

待測物測試配置圖 (Mode4~Mode5)



Signal Cable Type		Signal Cable Description
A	Type C USB Cable	Shielded, 0.5m

2.5 測試周邊

待測裝置測試時，其搭配系統測試時之週邊裝置包括如下：

(Mode1~Mode3)

No.	周邊名稱	廠牌	型號	序號	電源線
1	Notebook PC	Lenovo	T450	PC0BH4FR	Non-shielded, 0.8m
2	USB Mouse	Lenovo	M-U0025-O	HS427HA10UV	N/A

(Mode4~Mode5)

No.	周邊名稱	廠牌	型號	序號	電源線
1	Adapter	meitu	MA-1611	170605	N/A

2.6 操作程序

1.	Turn on the power of all equipment.
2.	Execute "Actions V2.20" program
3.	Configure the test channel and the data rate.
4.	Start test.

3. 測試設備明細

電源傳導 – SR2

儀器名稱	製造商	型號	財產編號	校正年限	校正有效日期
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2021/3/26
Cable	Rosnol	N1C50-RG400- B1C50-500CM	MRTTWE00013	1 year	2021/6/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/3/25

輻射干擾 – AC1

儀器名稱	製造商	型號	財產編號	校正年限	校正有效日期
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2020/9/4
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2021/3/25
Active Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2021/4/27
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2021/4/24
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2021/4/24
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2021/4/24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2021/4/24
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2021/6/16

傳導量測設備 –SR2

儀器名稱	製造商	型號	財產編號	校正年限	校正有效日期
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2020/10/2
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2021/7/14
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2021/3/26

EMI 測試軟體

軟體名稱	製造商	版本
e3	Audix	9.160520a
EMI	Quietek	V3

4. 量測不確定度

電源傳導量測-電源線 (Conducted Emission- Power Line)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.15MHz~30MHz: $\pm 2.53\text{dB}$
輻射干擾量測 (Radiated Spurious Emission)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz~30MHz: $\pm 3.92\text{dB}$ 30MHz~1GHz: $\pm 4.25\text{dB}$ 1GHz~18GHz: $\pm 4.40\text{dB}$ 18GHz~40GHz: $\pm 4.45\text{dB}$
頻率誤差量測 (Frequency Error)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 78.4\text{Hz}$
傳導功率量測 (Conducted Power)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.84\text{dB}$
傳導干擾量測 (Conducted Spurious Emission)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 2.65\text{ dB}$
佔用頻寬量測 (Occupied Bandwidth)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 3.3%
溫度 / 濕度 (Temp. / Humidity)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.82^\circ\text{C}/ \pm 3\%$
直流電源 (DC Voltage)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.3\%$

5. 測試結果

產品名稱 藍牙耳機


型號 T2

法規章節	量測項目	限制值	測試結果	測試數據
2.3	電源傳導	低功率射頻電機技術規範 2.3 節	符合	第 5.1 章節
3.10.1.2	峰值傳導輸出功率	$\leq 21.00\text{dBm}$	符合	第 5.2 章節
3.10.1.3	天線之要求	低功率射頻電機技術規範 3.10.1.3 節	符合	第 5.3 章節
3.10.1.5	帶外發射限制	$\leq 20\text{dBc(Peak)}$	符合	第 5.4 章節
2.8	輻射電場強度	低功率射頻電機技術規範 2.8 節	符合	第 5.5 章節
2.7	頻帶邊緣	$\leq 74\text{dBuV/m(Peak)}$ $\leq 54\text{dBuV/m(Average)}$	符合	第 5.6 章節
3.10.1.6(1)(A)	間隔頻寬	不得小於25 kHz 或跳頻頻道20 dB 頻寬之三分之二，兩者取較寬者。	符合	第 5.7 章節
3.10.1.6(1)(A)(a)	跳頻頻道數	至少15個無重疊的頻道	符合	第 5.8 章節
3.10.1.6(1)(A)(a)	占用時間	$\leq 0.4\text{s}$	符合	第 5.9 章節

備註：符合性的判定是基於測試結果符合規範的限制值或客戶的宣告要求，測試結果的判定是不考慮測量不確定度的值。

5.1.4 電源傳導測試結果

EUT	藍牙耳機	Date of Test	2020-08-21
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	27°C / 46%
Polarity	Line1	Site / Test Engineer	SR2 / Tim
Test Mode	BT_TX_DH5_CH39	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	*	0.168	41.19	9.61	50.80	-14.25	65.06	QP
2	*	0.168	24.51	9.61	34.12	-20.93	55.06	Average
3		0.433	24.58	9.63	34.21	-22.97	57.19	QP
4		0.433	13.69	9.63	23.31	-23.87	47.19	Average
5		1.702	22.29	9.68	31.97	-24.03	56.00	QP
6		1.702	12.87	9.68	22.55	-23.45	46.00	Average
7		5.761	19.20	9.76	28.96	-31.04	60.00	QP
8		5.761	14.24	9.76	24.00	-26.00	50.00	Average
9		8.645	16.96	9.84	26.80	-33.20	60.00	QP
10		8.645	12.53	9.84	22.38	-27.62	50.00	Average
11		21.581	17.83	10.01	27.83	-32.17	60.00	QP
12		21.581	12.67	10.01	22.68	-27.32	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	藍牙耳機	Date of Test	2020-08-21
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	27°C /46%
Polarity	Neutral	Site / Test Engineer	SR2 / Tim
Test Mode	BT_TX_DH5_CH39	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	*	0.159	40.07	9.62	49.69	-15.83	65.52	QP
2		0.159	24.23	9.62	33.85	-21.66	55.52	Average
3		0.226	32.00	9.62	41.62	-20.96	62.58	QP
4		0.226	16.74	9.62	26.36	-26.21	52.58	Average
5		0.451	27.59	9.64	37.23	-19.62	56.85	QP
6	*	0.451	19.19	9.64	28.83	-18.02	46.85	Average
7		3.120	24.53	9.71	34.25	-21.75	56.00	QP
8		3.120	17.07	9.71	26.78	-19.22	46.00	Average
9		6.809	19.81	9.80	29.61	-30.39	60.00	QP
10		6.809	13.98	9.80	23.78	-26.22	50.00	Average
11		20.587	17.80	10.08	27.88	-32.12	60.00	QP
12		20.587	12.77	10.08	22.84	-27.16	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	藍牙耳機	Date of Test	2020-08-07
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	27°C /52%
Polarity	Line1	Site / Test Engineer	SR2 / Kaunaz
Test Mode	Mode4	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.159	20.83	9.61	30.44	-35.08	65.52	QP
2	0.159	5.16	9.61	14.77	-40.74	55.52	Average
3	0.204	17.05	9.61	26.66	-36.78	63.45	QP
4	0.204	2.54	9.61	12.16	-41.29	53.45	Average
5	*	0.676	22.88	32.52	-23.48	56.00	QP
6	*	0.676	11.07	20.71	-25.29	46.00	Average
7	1.131	16.71	9.66	26.37	-29.63	56.00	QP
8	1.131	6.42	9.66	16.08	-29.92	46.00	Average
9	5.617	4.24	9.76	14.00	-46.00	60.00	QP
10	5.617	-1.82	9.76	7.94	-42.06	50.00	Average
11	13.442	9.08	9.91	19.00	-41.00	60.00	QP
12	13.442	1.18	9.91	11.09	-38.91	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	藍牙耳機	Date of Test	2020-08-07
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	27°C /52%
Polarity	Neutral	Site / Test Engineer	SR2 / Kaunaz
Test Mode	Mode4	Test Voltage	AC 110V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1		0.154	20.74	9.62	30.36	-35.39	65.75	QP
2		0.154	9.33	9.62	18.95	-36.81	55.75	Average
3		0.253	15.62	9.63	25.25	-36.40	61.64	QP
4		0.253	7.76	9.63	17.39	-34.25	51.64	Average
5	*	0.672	27.67	9.65	37.32	-18.68	56.00	QP
6	*	0.672	22.27	9.65	31.92	-14.08	46.00	Average
7		1.099	19.36	9.67	29.03	-26.97	56.00	QP
8		1.099	13.81	9.67	23.48	-22.52	46.00	Average
9		7.304	15.16	9.81	24.97	-35.03	60.00	QP
10		7.304	9.71	9.81	19.52	-30.48	50.00	Average
11		11.277	12.13	9.91	22.04	-37.96	60.00	QP
12		11.277	8.04	9.91	17.95	-32.05	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	藍牙耳機	Date of Test	2020-08-07
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	27°C /52%
Polarity	Line1	Site / Test Engineer	SR2 / Kaunaz
Test Mode	Mode5	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.154	28.02	9.61	37.63	-28.13	65.75	QP
2	0.154	10.90	9.61	20.51	-35.25	55.75	Average
3	0.213	21.43	9.61	31.04	-32.04	63.09	QP
4	0.213	3.71	9.61	13.32	-39.76	53.09	Average
5	* 0.690	26.83	9.64	36.47	-19.53	56.00	QP
6	* 0.690	16.75	9.64	26.39	-19.61	46.00	Average
7	1.455	14.37	9.67	24.04	-31.96	56.00	QP
8	1.455	2.72	9.67	12.40	-33.60	46.00	Average
9	7.754	11.19	9.82	21.01	-38.99	60.00	QP
10	7.754	2.86	9.82	12.68	-37.32	50.00	Average
11	14.495	10.00	9.92	19.93	-40.07	60.00	QP
12	14.495	2.00	9.92	11.92	-38.08	50.00	Average

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	藍牙耳機	Date of Test	2020-08-07
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	27°C /52%
Polarity	Neutral	Site / Test Engineer	SR2 / Kaunaz
Test Mode	Mode5	Test Voltage	AC 110V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.177	24.63	9.62	34.25	-30.38	64.63	QP
2	0.177	13.17	9.62	22.79	-31.84	54.63	Average
3	0.217	22.85	9.62	32.48	-30.44	62.91	QP
4	0.217	11.54	9.62	21.16	-31.75	52.91	Average
5	* 0.672	33.19	9.65	42.84	-13.16	56.00	QP
6	* 0.672	27.23	9.65	36.88	-9.12	46.00	Average
7	1.572	17.92	9.68	27.61	-28.39	56.00	QP
8	1.572	9.12	9.68	18.80	-27.20	46.00	Average
9	5.554	19.07	9.77	28.83	-31.17	60.00	QP
10	5.554	7.58	9.77	17.35	-32.65	50.00	Average
11	9.338	17.59	9.87	27.46	-32.54	60.00	QP
12	9.338	9.85	9.87	19.72	-30.28	50.00	Average

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

5.2 峰值傳導輸出功率

5.2.1 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀RF輸入端，設定頻譜分析儀之解析度頻寬大於6dB發射頻寬或使用峰值功率表。除使用上述測量方式外，並得使用以最大傳導輸出功率作為測量方式。

5.2.2 限制要求


操作於2400-2483.5 MHz之跳頻或數位調變的發射器材與5725-5850 MHz之跳頻發射器材：1W(含)以下，當跳頻系統符合國家通訊傳播委員會低功率射頻電機技術規範之第3.10.1.6(1)(A)(a)節，其限制值為0.125 W(含)以下。

若用於非固定式點對點操作時，若其發射天線之方向性增益超過6dBi，應依所超過之dB數等量降低峰值輸出功率。如用於固定式點對點(註)操作時，應符合下列情形之一：

(1)操作於2400-2483.5兆赫(MHz)者，其發射天線之方向性增益超過6dBi，應於每超過3dB降低1dB之峰值輸出功率。

(2) 操作於5725-5850兆赫(MHz)者，其發射天線之方向性增益超過6dBi，不需降低峰值輸出功率。

5.2.3 測試架構圖



5.2.4 峰值傳導輸出功率測試結果


待測物名稱	藍牙耳機	測試日期	2020/8/19
待測物型號	T2	溫度 / 濕度	23°C / 55%
測試場地 / 測試工程師	SR2 / Eric		

Test Mode	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)
DH5(1Mbps)	00	2402	5.977	< 21
DH5(1Mbps)	39	2441	6.075	< 21
DH5(1Mbps)	78	2480	5.665	< 21
2-DH5(2Mbps)	00	2402	8.264	< 21
2-DH5(2Mbps)	39	2441	8.471	< 21
2-DH5(2Mbps)	78	2480	8.702	< 21
3-DH5(3Mbps)	00	2402	6.774	< 21
3-DH5(3Mbps)	39	2441	6.828	< 21
3-DH5(3Mbps)	78	2480	7.064	< 21


備 註： 1. 此量測值已含線材損耗(Cable Loss=1dB)。

2. 封包型式共分為 DH1,DH3,DH5 經過初測並無明顯差異,故僅列最差之模式呈現在報告中。


CH00 (2402MHz) DH5(1Mbps)



CH39 (2441MHz) DH5(1Mbps)




CH78 (2480MHz) DH5(1Mbps)




CH00 (2402MHz) 2-DH5(2Mbps)




CH39 (2441MHz) 2-DH5(2Mbps)



CH78 (2480MHz) 2-DH5(2Mbps)





5.3 天線之要求

5.3.1 限制要求

依據國家通訊傳播委員會低功率射頻電機技術規範之第3.10.1.4節規定，天線之規格可不受下述規定之限制。

低功率射頻電機之發射機或收發信機所使用之天線，應為全固定、半固定式或以獨特之耦合(unique coupling)方式連接機體。製造者可設計供使用者因損壞而替換之天線，但不得設計或使用原認證以外之天線或可供引接各類電纜之標準天線插座或電氣連接頭，如：BNC、F type、N type、M type、UG type、RCA、SMA、SMB...等及其他各類工業或通訊標準接頭。

5.3.2 天線樣式

此藍牙耳機其天線為 PCB Antenna Type，(檢附天線規格書)

Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	深圳市大山通訊有限公司	PLT-TWS SPORT-R	-0.70dBi

5.4 帶外發射限制

5.4.1 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀 RF 輸入端：

- (1) 頻率掃描範圍足以檢測頻帶內的發射波峰位準以及由受測物產生之最低頻率到第 10 次諧波的所有混附發射，通常需要分幾段以涵蓋全部頻率範圍。
- (2) 解析頻寬為 100 kHz，視訊頻寬不小於解析頻寬。
- (3) 掃描時間為自動，檢波功能為峰值，訊號軌跡為最大保留(Max Hold)。
- (4) 將標記設定於任何欲紀錄之波峰上，所顯示之位準值必須符合指定之限制值。


備 註: DH1,DH3,DH5僅為封包傳輸率的差異,其針對此章節無顯著之影響，因此僅檢附DH5為測試數據。

5.4.2 限制要求


使用頻帶範圍外之任意 100 千赫 (kHz)內，發射器所產生的射頻功率相較於使用頻帶範圍中包含最高所需功率之 100 千赫 (kHz)內的射頻功率，衰減值限制如下：

- (1) 輸出功率以低功率射頻電機技術規範附件二之峰值輸出功率方式量測者，至少須衰減 20 dB，可使用射頻傳導或輻射方式測量。
- (2) 輸出功率以數位調變技術系統之最大傳導輸出功率量測方式者，至少須衰減 30 dB。
- (3) 若落於禁用頻段之輻射發射，應符合低功率射頻電機技術規範第 2.8 節之規定。


5.4.3 測試架構圖




5.4.4 帶外輻射測試結果




CH39 (2441MHz) DH5(1Mbps)




CH39 (2441MHz) DH5(1Mbps)




CH78 (2480MHz) DH5(1Mbps)




CH78 (2480MHz) DH5(1Mbps)




CH78 (2480MHz) DH5(1Mbps)




CH78 (2480MHz) DH5(1Mbps)




CH00 (2402MHz) 3-DH5(3Mbps)




CH00 (2402MHz) 3-DH5(3Mbps)




CH00 (2402MHz) 3-DH5(3Mbps)




CH00 (2402MHz) 3-DH5(3Mbps)




CH39 (2441MHz) 3-DH5(3Mbps)




CH39 (2441MHz) 3-DH5(3Mbps)




CH39 (2441MHz) 3-DH5(3Mbps)




CH39 (2441MHz) 3-DH5(3Mbps)




CH78 (2480MHz) 3-DH5(3Mbps)




CH78 (2480MHz) 3-DH5(3Mbps)



CH78 (2480MHz) 3-DH5(3Mbps)



CH78 (2480MHz) 3-DH5(3Mbps)



5.5 輻射電場強度

5.5.1 量測方法

待測物置於非導體桌面（落地型產品置於地上），受測物使用交流電源時，將其與任何配件設備之電源線連接至位於旋轉桌的交流電源。受測物使用電池時，測試時應裝置新電池或充電完全的電池。受測物與配件設備之電源線無須束綁，桌面上受測設備的所有電源線由桌子的後緣垂下沿旋轉桌表面接至交流插座。落地型設備的交流電源線可以方便的型態走線。桌面可 360 度旋轉，接收天線置於距待測物 3m 距離，高度可在 1 至 4 公尺間變動，以量測待測物之最大輻射電場強度，接收天線並應於水平及垂直極化方向各量測一次。（待測物擺設方式根據 ANSI C63.10-2013 版本，待測物放置桌中心，1G 以下擺設高度為 80cm/1G 以上擺設高度為 150cm）

- (1) 任一頻率小於或等於 1000 MHz 之訊號,使用 CISPR 準峰值檢波器
- (2) 任一頻率大於 1000 MHz 之訊號，使用平均值檢波器測量，當規定之發射限制值為平均值時(含 1000 MHz 以下)，受測訊號藉由峰值檢波器(RBW:1MHz,VBW:3MHz)所測量之峰值，亦須符合峰值發射限制值，其峰值發射限制值為最大容許平均值加 20 dB。

備 註:

1. DH1,DH3,DH5僅為封包傳輸率的差異,其針對此章節無顯著之影響，因此僅檢附DH5為測試數據。
2. 若為手持式或穿戴式之裝置，需對其三個正交軸的方位評估測試，並記錄最差的數值。

5.5.2 限制要求


其電場強度不得超過下表之限值，且其不必要之發射皆不得大於主波發射強度。各頻段重疊處，以較嚴格之限制值為準。

頻 率 (MHz)	電場強度(uV/m)	測距(m)
0.009 - 0.490(含)	2,400/f(KHz)	300
0.490 (不含) – 1.705 (含)	24,000/f(KHz)	30
1.705(不含) – 30 (不含)	30	30
30 (含) – 88 (含)	100	3
88 (不含)- 216 (含)	150	3
216 (不含)- 960 (含)	200	3
960 (不含)以上	500	3


上表規定之電場強度，頻率在 9-90kHz 千赫(kHz)、110-490 千赫(kHz)以及 1000 兆赫(MHz)以上之發射，其量測以平均值檢波器為基準，且須符合低功率射頻電機技術規範第 5.14 節之規定；其他頻率之發射，應以 CISPR 準峰值(quasi-peak) 檢波器測量；非以上表所指定之距離測量時須符合低功率射頻電機技術規範第 5.5 節之規定，而輻射發射之量測頻率範圍須符合低功率射頻電機技術規範第 5.12 節之規定。

5.5.3 測試架構圖


Under 30MHz Test Setup




Under 1GHz Test Setup



1GHz ~ 18GHz Test Setup:




18GHz ~25GHz Test Setup:



5.5.4 輻射電場強度測試結果

EUT	藍牙耳機	Date of Test	2020-08-24
Factor	VULB 9162	Temp. / Humidity	24°C / 52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	59.100	4.68	20.25	24.93	-15.07	40.00	100	100	QP
2	71.710	12.77	16.06	28.82	-11.18	40.00	100	320	QP
3	220.120	16.89	19.04	35.93	-10.07	46.00	100	220	QP
4	* 316.150	18.92	22.06	40.97	-5.03	46.00	100	285	QP
5	359.800	14.42	23.57	37.99	-8.01	46.00	100	10	QP
6	480.080	12.44	25.45	37.89	-8.11	46.00	100	-40	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-24
Factor	VULB 9162	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 39	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	62.010	12.81	19.38	32.19	-7.81	40.00	100	20	QP
2		71.710	11.94	16.06	27.99	-12.01	40.00	100	330	QP
3		225.940	10.15	19.52	29.68	-16.32	46.00	100	220	QP
4		320.030	9.73	22.21	31.95	-14.05	46.00	100	65	QP
5		375.320	6.73	23.80	30.53	-15.47	46.00	100	150	QP
6		480.080	5.88	25.45	31.33	-14.67	46.00	100	155	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-24
Factor	VULB 9162	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_RX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	72.680	8.31	15.82	24.13	-15.87	40.00	100	180	QP
2	156.100	14.24	15.99	30.23	-13.27	43.50	100	95	QP
3	218.180	16.07	18.95	35.01	-10.99	46.00	100	45	QP
4	* 312.270	17.50	21.90	39.40	-6.60	46.00	100	180	QP
5	361.740	11.95	23.60	35.55	-10.45	46.00	100	65	QP
6	480.080	6.68	25.45	32.13	-13.87	46.00	100	45	QP

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-24
Factor	VULB 9162	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_RX_DH5_CH 39	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	62.010	14.73	19.38	34.11	-5.89	40.00	100	0	QP
2		71.590	15.81	16.09	31.90	-8.10	40.00	100	165	QP
3		225.940	9.32	19.52	28.85	-17.15	46.00	100	30	QP
4		314.950	11.96	22.01	33.97	-12.03	46.00	100	150	QP
5		436.430	6.09	24.69	30.78	-15.22	46.00	100	225	QP
6		562.530	6.21	26.83	33.05	-12.95	46.00	100	400	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	VULB 9162	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	Mode4	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	39.700	1.10	20.56	21.66	-18.34	40.00	100	100	QP
2	102.750	-0.87	19.41	18.54	-24.96	43.50	100	320	QP
3	173.560	4.41	16.68	21.10	-22.40	43.50	100	220	QP
4	356.890	-0.20	23.53	23.33	-22.67	46.00	100	0	QP
5	580.960	1.11	27.16	28.27	-17.73	46.00	100	350	QP
6	* 858.380	0.45	31.32	31.77	-14.23	46.00	100	20	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	VULB 9162	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	Mode4	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	39.700	1.10	20.56	21.66	-18.34	40.00	100	200	QP
2	100.810	-1.42	19.60	18.18	-25.32	43.50	100	250	QP
3	172.590	3.14	16.59	19.73	-23.77	43.50	100	330	QP
4	325.850	-0.24	22.45	22.21	-23.79	46.00	100	0	QP
5	489.780	-0.36	25.63	25.27	-20.73	46.00	100	45	QP
6	* 622.670	0.51	27.87	28.37	-17.63	46.00	100	80	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	VULB 9162	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	Mode5	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	49.400	-1.24	21.62	20.38	-19.62	40.00	100	330	QP
2	136.700	5.98	15.61	21.59	-21.91	43.50	100	200	QP
3	172.590	5.62	16.59	22.21	-21.29	43.50	100	115	QP
4	209.450	3.67	18.61	22.28	-21.22	43.50	100	10	QP
5	334.580	1.21	22.80	24.01	-21.99	46.00	100	185	QP
6	* 606.180	1.07	27.60	28.67	-17.33	46.00	100	110	QP

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	VULB 9162	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	Mode5	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	35.820	2.49	19.29	21.78	-18.22	40.00	100	100	QP
2	99.840	-1.51	19.64	18.12	-25.38	43.50	100	105	QP
3	172.590	5.56	16.59	22.15	-21.35	43.50	100	400	QP
4	358.830	-0.60	23.56	22.96	-23.04	46.00	100	0	QP
5	512.090	0.36	26.01	26.37	-19.63	46.00	100	50	QP
6	* 732.280	1.50	29.60	31.11	-14.89	46.00	100	-15	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4804.000	53.53	3.28	56.81	-17.19	74.00	100	125	Peak
2	*	4804.000	46.35	3.28	49.63	-4.37	54.00	100	125	Average
3		7206.000	48.42	10.88	59.30	-14.70	74.00	100	400	Peak
4		9608.000	33.51	14.62	48.13	-25.87	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. No3 is not in restricted band, its limit is 20dBc/30dBc of the fundamental emission level(already evaluated in Section 5.4) or LP0002 Section 2.8 which is higher.(Here, we are using stringent limits:74dBuV/m.)
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4804.000	52.00	3.28	55.28	-18.72	74.00	100	-20	Peak
2	*	4804.000	44.27	3.28	47.55	-6.45	54.00	100	-20	Average
3		7206.000	51.11	10.88	62.00	-12.00	74.00	100	400	Peak
4		9608.000	34.72	14.62	49.35	-24.65	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. No3 is not in restricted band, its limit is 20dBc/30dBc of the fundamental emission level(already evaluated in Section 5.4) or LP0002 Section 2.8 which is higher.(Here, we are using stringent limits:74dBuV/m.)
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4882.000	49.43	3.47	52.90	-21.10	74.00	100	400	Peak
2	* 7323.000	45.94	11.21	57.15	-16.85	74.00	100	110	Peak
3	* 7323.000	36.05	11.21	47.26	-6.74	54.00	100	110	Average
4	9764.000	32.35	14.92	47.27	-26.73	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4882.000	48.55	3.47	52.01	-21.99	74.00	100	400	Peak
2	* 7323.000	47.84	11.21	59.05	-14.95	74.00	100	-40	Peak
3	* 7323.000	39.08	11.21	50.29	-3.71	54.00	100	-40	Average
4	9764.000	31.59	14.92	46.51	-27.49	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	43.77	3.65	47.42	-26.58	74.00	100	400	Peak
2	* 7440.000	43.42	11.55	54.97	-19.03	74.00	100	95	Peak
3	* 7440.000	35.38	11.55	46.93	-7.07	54.00	100	95	Average
4	9920.000	33.98	15.21	49.19	-24.81	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	43.32	3.65	46.97	-27.03	74.00	100	400	Peak
2	* 7440.000	46.15	11.55	57.69	-16.31	74.00	100	-40	Peak
3	* 7440.000	38.12	11.55	49.67	-4.33	54.00	100	-40	Average
4	9920.000	34.00	15.21	49.21	-24.79	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4804.000	57.13	3.28	60.41	-13.59	74.00	100	130	Peak
2	*	4804.000	48.58	3.28	51.86	-2.14	54.00	100	130	Average
3		7206.000	49.85	10.88	60.74	-13.26	74.00	100	400	Peak
4		9608.000	33.85	14.62	48.47	-25.53	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. No3 is not in restricted band, its limit is 20dBc/30dBc of the fundamental emission level(already evaluated in Section 5.4) or LP0002 Section 2.8 which is higher.(Here, we are using stringent limits:74dBuV/m.)
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4804.000	54.58	3.28	57.86	-16.14	74.00	100	-20	Peak
2	*	4804.000	47.16	3.28	50.44	-3.56	54.00	100	-20	Average
3		7206.000	51.67	10.88	62.55	-11.45	74.00	100	400	Peak
4		9608.000	35.60	14.62	50.23	-23.77	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. No3 is not in restricted band, its limit is 20dBc/30dBc of the fundamental emission level(already evaluated in Section 5.4) or LP0002 Section 2.8 which is higher.(Here, we are using stringent limits:74dBuV/m.)
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4882.000	50.32	3.47	53.79	-20.21	74.00	100	400	Peak
2	* 7323.000	46.12	11.21	57.34	-16.66	74.00	100	100	Peak
3	* 7323.000	38.98	11.21	50.19	-3.81	54.00	100	100	Average
4	9764.000	32.52	14.92	47.44	-26.56	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4882.000	51.04	3.47	54.51	-19.49	74.00	100	25	Peak
2	4882.000	43.63	3.47	47.10	-6.90	54.00	100	25	Average
3	* 7323.000	49.50	11.21	60.72	-13.28	74.00	100	-40	Peak
4	* 7323.000	41.65	11.21	52.86	-1.14	54.00	100	-40	Average
5	9764.000	32.34	14.92	47.25	-26.75	74.00	100	400	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	44.16	3.65	47.82	-26.18	74.00	100	400	Peak
2	* 7440.000	43.35	11.55	54.89	-19.11	74.00	100	10	Peak
3	* 7440.000	35.26	11.55	46.81	-7.19	54.00	100	10	Average
4	9920.000	33.47	15.21	48.67	-25.33	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4960.000	44.80	3.65	48.45	-25.55	74.00	100	400	Peak
2	* 7440.000	47.72	11.55	59.27	-14.73	74.00	100	-40	Peak
3	* 7440.000	40.00	11.55	51.55	-2.45	54.00	100	-40	Average
4	9920.000	32.40	15.21	47.61	-26.39	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_RX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1000.000	48.23	-7.95	40.28	-33.72	74.00	100	400	Peak
2	* 1187.000	52.50	-7.12	45.38	-28.62	74.00	100	400	Peak
3	1782.000	42.42	-4.99	37.43	-36.57	74.00	100	400	Peak
4	2071.000	42.57	-4.11	38.46	-35.54	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_RX_DH5_CH 39	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1187.320	50.17	-7.12	43.05	-30.95	74.00	100	400	Peak
2	* 1782.150	52.13	-4.99	47.14	-26.86	74.00	100	400	Peak
3	1986.115	48.21	-4.46	43.75	-30.25	74.00	100	400	Peak
4	2224.000	44.35	-3.43	40.92	-33.08	74.00	100	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	25°C /46%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	Mode4	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1088.719	42.66	-7.56	35.11	-38.89	74.00	150	400	Peak
2	1419.156	41.26	-6.09	35.18	-38.82	74.00	150	400	Peak
3	* 1799.531	40.37	-4.95	35.42	-38.58	74.00	150	400	Peak
4	2009.375	39.61	-4.38	35.23	-38.77	74.00	150	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	25°C /46%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	Mode4	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1174.781	42.60	-7.17	35.42	-38.58	74.00	150	400	Peak
2	* 1536.563	41.94	-5.63	36.30	-37.70	74.00	150	400	Peak
3	1772.969	40.69	-5.01	35.68	-38.32	74.00	150	400	Peak
4	2307.406	39.20	-3.07	36.14	-37.86	74.00	150	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	25°C /46%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	Mode5	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1072.250	43.29	-7.63	35.67	-38.33	74.00	150	400	Peak
2	1515.844	41.18	-5.69	35.49	-38.51	74.00	150	400	Peak
3	* 1888.250	41.40	-4.71	36.69	-37.31	74.00	150	400	Peak
4	2342.469	38.90	-2.91	35.99	-38.01	74.00	150	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-15
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	25°C /46%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	Mode5	Test Voltage	AC 110V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1222.594	42.20	-6.96	35.24	-38.76	74.00	150	400	Peak
2	1636.969	40.86	-5.37	35.49	-38.51	74.00	150	400	Peak
3	2119.344	39.29	-3.89	35.40	-38.60	74.00	150	400	Peak
4	* 2594.281	38.52	-2.28	36.24	-37.76	74.00	150	400	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

5.6 頻帶邊緣

5.6.1 量測方法

待測物置於非導體桌面（落地型產品置於地上），受測物使用交流電源時，將其與任何配件設備之電源線連接至位於旋轉桌的交流電源。受測物使用電池時，測試時應裝置新電池或充電完全的電池。受測物與配件設備之電源線無須束綁，桌面上受測設備的所有電源線由桌子的後緣垂下沿旋轉桌表面接至交流插座。落地型設備的交流電源線可以方便的型態走線。桌面可360度旋轉，接收天線置於距待測物3m距離，高度可在1至4公尺間變動，以量測待測物之最大輻射電場強度，接收天線並應於水平及垂直極化方向各量測一次。（待測物擺設方式根據 ANSI C63.10-2013版，待測物放置桌中心，1G以下擺設高度為80cm/1G以上擺設高度為150cm）

- (1) 任一頻率小於或等於1000 MHz 之訊號,使用CISPR準峰值檢波器
- (2) 任一頻率大於1000 MHz 之訊號，使用平均值檢波器測量，當規定之發射限制值為平均值時(含1000 MHz 以下)，受測訊號藉由峰值檢波器(RBW:1MHz,VBW:3MHz)所測量之峰值，亦須符合峰值發射限制值，其峰值發射限制值為最大容許平均值加20 dB。

備 註:

1. DH1,DH3,DH5僅為封包傳輸率的差異,其針對此章節無顯著之影響，因此僅檢附DH5為測試數據。
2. 若為手持式或穿戴式之裝置，需對其三個正交軸的方位評估測試，並記錄最差的數值。


5.6.2 限制要求

除低功率射頻電機技術規範另有規定外，任何低功率射頻電機之主波皆不得使用下表所列各頻段之頻率低功率射頻電機落於下表所列頻帶內之混附發射，其電場強度必須符合低功率射頻電機技術規範之第2.8節限制規定


頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)
0.090~0.110	25.500~25.700	703.00~748.00	2310.0~2390.0	13250~13400
0.490~0.510	37.475~38.275	758.00~803.00	2483.5~2900.0	14470~14500
2.172~2.198	73.500~75.400	825.00~915.00	3260.0~3267.0	15350~16200
3.013~3.033	108.00~138.00	930.00~1240.0	3332.0~3339.0	17700~21400
4.115~4.198	149.90~150.05	1300.0~1427.0	3345.8~3358.0	22010~23120
5.670~5.690	156.70~156.90	1435.0~1626.5	3500.0~4400.0	23600~24000
6.200~6.300	162.01~167.17	1660.0~1785.0	4500.0~5250.0	31200~31800
8.230~8.400	167.72~173.20	1805.0~1880.0	5350.0~5460.0	36430~36500
12.265~12.600	240.00~285.00	1885.0~1900.0	7250.0~7750.0	38600 以上
13.340~13.430	322.00~335.40	1905.0~1985.0	8025.0~8500.0	
14.965~15.020	399.90~410.00	2010.0~2025.0	9000.0~9200.0	
16.700~16.755	485.00~510.00	2110.0~2170.0	9300.0~9500.0	
19.965~20.020	608.00~614.00	2200.0~2300.0	10600~12700	

5.6.3 測試架構圖

1GHz ~ 18GHz Test Setup:




18GHz ~ 25GHz Test Setup:



5.6.4 頻帶邊緣測試結果

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C / 52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2389.300	50.71	-2.71	48.00	-26.00	74.00	165	40	Peak
2	2390.000	48.75	-2.70	46.05	-27.95	74.00	165	40	Peak
3	2401.900	99.31	-2.65	96.66	N/A	N/A	165	40	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2389.200	52.22	-2.71	49.52	-24.48	74.00	175	275	Peak
2		2390.000	51.42	-2.70	48.71	-25.29	74.00	175	275	Peak
3		2401.900	97.41	-2.65	94.75	N/A	N/A	175	275	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2480.150	100.45	-2.31	98.15	N/A	N/A	185	230	Peak
2	2483.500	51.61	-2.29	49.31	-24.69	74.00	185	230	Peak
3	* 2483.875	52.36	-2.29	50.06	-23.94	74.00	185	230	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2479.800	97.78	-2.31	95.47	N/A	N/A	150	280	Peak
2	2483.500	48.66	-2.29	46.37	-27.63	74.00	150	280	Peak
3	* 2485.150	50.92	-2.29	48.63	-25.37	74.00	150	280	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2370.000	49.77	-2.79	46.97	-27.03	74.00	165	40	Peak
2		2390.000	47.24	-2.70	44.54	-29.46	74.00	165	40	Peak
3		2401.800	99.48	-2.65	96.83	N/A	N/A	165	40	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2389.300	51.98	-2.71	49.27	-24.73	74.00	175	275	Peak
2		2390.000	48.21	-2.70	45.51	-28.49	74.00	175	275	Peak
3		2402.200	98.05	-2.65	95.40	N/A	N/A	175	275	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2480.150	102.09	-2.31	99.79	N/A	N/A	185	230	Peak
2	* 2483.500	57.96	-2.29	55.67	-18.33	74.00	185	230	Peak
3	2483.850	57.93	-2.29	55.64	-18.36	74.00	185	230	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C / 52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 78	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2480.000	100.92	-2.31	98.61	N/A	N/A	185	230	Average
2	* 2483.500	40.35	-2.29	38.06	-15.94	54.00	185	230	Average
3	2487.875	39.62	-2.27	37.34	-16.66	54.00	185	230	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	藍牙耳機	Date of Test	2020-08-26
Factor	BBHA 9120D	Temp. / Humidity	24°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	BT_TX_3-DH5_CH 78	Test Voltage	By Notebook PC



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2480.125	99.23	-2.31	96.93	N/A	N/A	150	280	Peak
2	2483.500	54.35	-2.29	52.06	-21.94	74.00	150	280	Peak
3	* 2483.675	55.39	-2.29	53.10	-20.90	74.00	150	280	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

5.7 間隔頻寬

5.7.1 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀RF輸入端，頻譜分析儀之設定,參考如下:


- (1) 頻率掃描範圍約為20 dB頻寬之2 到3 倍，中心頻率為跳頻頻道。
- (2) 解析頻寬不小於20 dB 頻寬的1%，視訊頻寬不小於解析頻寬。
- (3) 掃描時間為自動，檢波功能為峰值，訊號軌跡為最大保留(Max Hold)
- (4) 受測物必須以最大資料傳輸率發射，利用記號至波峰(Mark to Peak)功能以標記波峰。
- (5) 利用差值記號功能以測量發射之20 dB頻寬。若該值會因不同操作模式而異，對不同模式重複此測試。

備 註: DH1,DH3,DH5僅為封包傳輸率的差異,其針對此章節無顯著之影響，因此僅檢附DH5為測試數據。

5.7.2 限制要求

應大於或等於25 kHz 或跳頻頻道之20 dB頻寬，兩者取較寬者。但操作頻率為2400 MHz~2483.5 MHz 頻段且輸出功率應小於或等於125 mW 跳頻系統，其載波頻率頻道間隔不得小於25 kHz 或跳頻頻道20 dB頻寬之三分之二，兩者取較寬者。系統之跳頻頻道應依虛擬亂數排列，在各頻率之跳頻頻道上跳躍。每一發射機必須均等的使用每一頻率。系統接收機應具有與發射機跳躍頻道頻寬相匹配之輸入頻寬，且應隨所發射之訊號同步偏移接收頻率。

5.7.3 測試架構圖




5.7.4 間隔頻寬測試結果


Test Mode	Channel No.	Frequency (MHz)	Channel Separation (MHz)	Limit (kHz)	Limit of 2/3*20dB Bandwidth (kHz)	Result
DH5(1Mbps)	00	2402	1.00	25	643.667	Pass
DH5(1Mbps)	39	2441	1.00	25	643.467	Pass
DH5(1Mbps)	78	2480	1.00	25	641.733	Pass
3-DH5(3Mbps)	00	2402	1.00	25	457.067	Pass
3-DH5(3Mbps)	39	2441	1.00	25	463.133	Pass
3-DH5(3Mbps)	78	2480	1.00	25	463.333	Pass

備註：Limit 為 25 kHz 或跳頻頻道 20 dB 頻寬之三分之二，兩者取較寬者。


CH00 (2402MHz) DH5(1Mbps)- Channel Separation




CH00 (2402MHz) DH5(1Mbps)- 20dB Bandwidth




CH39 (2441MHz) DH5(1Mbps)- Channel Separation




CH39 (2441MHz) DH5(1Mbps)- 20dB Bandwidth




CH78 (2480MHz) DH5(1Mbps)- Channel Separation




CH78 (2480MHz) DH5(1Mbps)- 20dB Bandwidth




CH00 (2402MHz) 3-DH5(3Mbps)- Channel Separation




CH00 (2402MHz) 3-DH5(3Mbps)- 20dB Bandwidth




CH39 (2441MHz) 3-DH5(3Mbps)- Channel Separation




CH39 (2441MHz) 3-DH5(3Mbps)- 20dB Bandwidth



CH78 (2480MHz) 3-DH5(3Mbps)-Channel Separation



CH78 (2480MHz) 3-DH5(3Mbps)- 20dB Bandwidth



5.8. 跳頻頻道數

5.8.1 量測方法

(一) 啟動受測物之跳頻功能。

(二) 頻譜分析儀設定如下：

1. 頻率掃描範圍為受測物之操作頻帶。
2. 解析頻寬不小於1%的頻率掃描範圍，視訊頻寬不小於解析頻寬。
3. 掃描時間為自動，檢波功能為峰值，訊號軌跡為最大保留(Max Hold)


備 註: DH1,DH3,DH5為封包傳輸率的差異,其針對此章節無顯著之影響，因此僅檢附DH5為測試數據。

5.8.2 限制要求

(一) 操作於2400 MHz~2483.5 MHz之展頻跳頻系統，須使用至少15 個無重疊的頻道。應使用智慧型跳頻技術，以避免占用於特定跳頻頻道。


(二) 操作於5725 MHz~5850 MHz 之展頻跳頻系統，至少須使用75 個以上跳頻頻道(hopping channel)，每一跳頻頻道之20 dB頻寬應小於或等於1 MHz。

5.8.3 測試架構圖



5.8.4 跳頻頻道數測試結果

Test Mode (Hopping)	Channel Numbers	Frequency (MHz)	Limit (Hopping Channels)	Result
DH5(1Mbps)	79	2402~2480	≥ 15	Pass
3-DH5(3Mbps)	79	2402~2480	≥ 15	Pass



5.9. 占用時間

5.9.1 量測方法

(一) 啟動受測物之跳頻功能。

(二) 頻譜分析儀設定如下：


1. 頻率掃描範圍為零，中心頻率為跳頻頻道，解析頻寬為1 MHz，視訊頻寬不小於解析頻寬。
2. 掃描時間為足以測得每一個跳頻頻道之所有停留時間。
3. 檢波功能為峰值，訊號軌跡為最大保留(Max Hold)
4. 利用差值記號功能以決定停留時間。若該值會因不同操作模式而異，對不同模式重複此測試。

5.9.2 限制要求

(一) 操作於2400 MHz~2483.5 MHz之展頻跳頻系統在0.4 秒乘以跳頻頻道數之週期內，任一頻率占用之平均時間應小於或等於0.4 秒。應使用智慧型跳頻技術，以避免占用於特定跳頻頻道。

(二) 操作於5725 MHz~5850 MHz 之展頻跳頻系統在30秒週期內，任一頻率占用之平均時間應小於或等於0.4 秒。應使用智慧型跳頻技術，以避免占用於特定跳頻頻道。

5.9.3 測試架構圖



5.9.4 占用時間測試結果

Test Mode	Frequency (MHz)	Time of Occupancy (ms)	Hopping of Numbers	Sweep time (ms)	Duty cycle	Dwell Time (Sec)	Limit (Sec)	Result
DH5(1Mbps)	2402	2.88	13	50	0.75	0.30	0.4	Pass
	2441	2.88	13	50	0.75	0.30	0.4	Pass
	2480	2.88	13	50	0.75	0.30	0.4	Pass
3-DH5(3Mbps)	2402	2.88	13	50	0.75	0.30	0.4	Pass
	2441	2.88	13	50	0.75	0.30	0.4	Pass
	2480	2.88	13	50	0.75	0.30	0.4	Pass


備註：(1) $\text{Duty cycle} = ((\text{Time slot length (ms)} * \text{Hopping of Number}) / \text{Sweep time (ms)})$ 。

$\text{Dwell time} = ((\text{Duty cycle} * (\text{Time Period} < 0.4 * 79 >)) / (\text{Total Hopping of Number} < 79 >))$


(2) 經初測驗證過，Dwell Time 針對測試頻道數並無明顯差異，故僅檢附最差狀況之測試頻道。

(3) 封包型式共分為 DH1,DH3,DH5 ,僅列最差之模式呈現在報告中。


CH00 (2402MHz) DH5(1 Mbps)- Duty Cycle




CH00 (2402MHz) DH5(1 Mbps)- Dwell time




CH39 (2441MHz) DH5(1 Mbps)- Duty Cycle




CH39 (2441MHz) DH5(1 Mbps)- Dwell time




CH78 (2480MHz) DH5(1 Mbps)- Duty Cycle




CH78 (2480MHz) DH5(1 Mbps)- Dwell time




CH00 (2402MHz) 3-DH5(3 Mbps)- Duty Cycle




CH00 (2402MHz) 3-DH5(3 Mbps)- Dwell time




CH39 (2441MHz) 3-DH5(3 Mbps)- Duty Cycle




CH39 (2441MHz) 3-DH5(3 Mbps)- Dwell time



CH78 (2480MHz) 3-DH5(3 Mbps)- Duty Cycle



CH78 (2480MHz) 3-DH5(3 Mbps)- Dwell time



The End