

NCC RADIO TEST REPORT

Product name	Dongle
Applicant	Ubudu SAS
Manufacture	Ubudu SAS
Rating(s)	4.5 - 5.5 VDC
Trademark	Ubudu
Model and/or type reference	type V1
Standard	LP0002:2018
Test Result	Pass

Date of receipt : 01-17-2019

Signature :

Date of Issue : 02-15-2019



NCC RADIO TEST REPORT

Report Reference No...... M80620J716

Compiled by (+ signature) Kevin Bothmann

Approved by (+ signature) Jay Gandhi

Date of issue..... 02-15-2019

Applicant's name Ubudu SAS

Address 22 rue Tourlaque 75018 Paris, France

Manufacture's Name Ubudu SAS

Address 22 rue Tourlaque 75018 Paris, France

Test specification:

Standard LP0002: 2018

Test procedure EIA 603、ANSI、FCC/47 CFR/2.1046、2.1047、2.1049、2.1051、2.1053 and 2.1055

Non-standard test method..... N/A

Test item description

Product name : Dongle

Brand name : Ubudu

Model and/or type reference : type V1

Rating(s) : 4.5 - 5.5 VDC

Testing Laboratory information

Testing Laboratory Name : Electro Magnetic Test, Inc.

Address : 1547 Plymouth Street, Mountain View, CA 94043

CAB Identifier Number : US0036

Tel : (650) 965-4000

Fax : (650) 965-3000

E-mail : jgandhi@emtlabs.com

Testing

Date of receipt of test item..... Jan. 17 , 2019

Date (s) of performance of tests..... Jan. 17~ Feb. 12, 2019

Date of Issue Feb. 15, 2019

Test Result **Pass**

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Electro Magnetic Test, Inc., which is an independent testing and consulting firm. The test report is based on testing performed Electro Magnetic Test, Inc. personnel according to the measurement procedure described in the test specification given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Federal Government.

Electro Magnetic Test, Inc. is recognized by the following agencies for performing EMI/EMC testing:

COUNTRY	AGENCY	IDENTIFYING #
USA	Federal Communications Commission (FCC) (EMT's test site is recognized by the FCC)	Registration Number: 90576
USA, Canada, TUBUDUN, Australia/New Zealand, European Community	National Voluntary Lab Accreditation Program (NVLAP) (EMT is accredited by NVLAP. A copy of the NVLAP Scope Of Accreditation is available upon request.)	Lab Code: 200147-0
Canada	Industry Canada	File No.: IC 2804
Japan	Voluntary Control Council For Interference (VCCI)	A-0118
	Open Field Test Site "A"	-
	Mains Conducted Emissions Test Site "A"	-
	Telecom Conducted Emissions Test Site "A"	-
	3 Meter Semi-Anechoic Chamber Site "E"	-
	3 Meter Semi-Anechoic Chamber Site "E" (1GHz – 6GHz)	-
	Mains Conducted Emissions Test Site "E"	-
	Telecom Conducted Emissions Test Site "E"	-
Korea	Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (A copy of the Scope Of Accreditation is available upon request)	US0036
TUBUDUN	Bureau Of Standards, Metrology and Inspection (BSMI)	Reference Number: SL2-IN-E-1024
Australia / New Zealand	Australian Communications Authority (AUSTEL)	*

***THESE AGENCIES DO NOT ISSUE AN IDENTIFYING NUMBER TO TEST LABS.**

Table of Contents	Page
GENERAL REPORT SUMMARY	3
1 . SUMMARY OF TEST RESULTS	6
1.1 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	12
3 . TRANSMITTER EMISSION TEST	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
3.1.2 TEST PROCEDURE	16
3.1.3 DEVIATION FROM TEST STANDARD	16
3.1.4 TEST SETUP	16
3.1.5 TEST RESULTS	17
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 TEST SETUP	20
3.2.4 EUT OPERATING CONDITIONS	20
3.2.5 TEST RESULTS (BLOW 30MHZ)	21
3.2.6 TEST RESULTS (BETWEEN30 – 1000 MHZ)	21
3.2.7 TEST RESULTS (ABOVE 1000 MHZ)	25
3.2.8 TEST RESULTS (BETWEEN30 – 1000 MHZ)	41
3.2.9 TEST RESULTS (ABOVE 1000 MHZ)	45
3.2.10 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	61
4 . OCCUPIED BANDWIDTH TEST	63
4.1 APPLIED PROCEDURES / LIMIT	63
4.1.1 TEST PROCEDURE	63
4.1.2 TEST SETUP	63
4.1.3 EUT OPERATION CONDITIONS	63
4.1.4 TEST RESULTS	64
5 . POWER DENSITY	66
5.1 APPLIED PROCEDURES / LIMIT	66
5.1.1 TEST PROCEDURE	66

Table of Contents	Page
5.1.2 TEST SETUP	66
5.1.3 EUT OPERATION CONDITIONS	66
5.1.4 TEST RESULTS	67
6 . PEAK OUTPUT POWER TEST	69
6.1 APPLIED PROCEDURES / LIMIT	69
6.1.1 TEST PROCEDURE	69
6.1.2 DEVIATION FROM STANDARD	69
6.1.3 TEST SETUP	69
6.1.4 EUT OPERATION CONDITIONS	69
6.1.5 TEST RESULTS	70
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	72
7.1 APPLIED PROCEDURES / LIMIT	72
7.1.1 TEST PROCEDURE	72
7.1.2 TEST SETUP	72
7.1.3 EUT OPERATION CONDITIONS	72
7.1.4 TEST RESULTS	73
8. ANTENNA REQUIREMENT	75
8.1 STANDARD REQUIREMENT	75
8.2 EUT ANTENNA	75
9. EUT TEST PHOTO	76
10. APPENDIX-Photographs of EUT Constructional Details	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

LP0002 : 2018			
Standard Section	Test Item	Judgment	Remark
2.3	Conducted Emission	N/A	None
3.10.1(5)/2.8	Radiated Spurious Emission	PASS	None
3.10.1(2)	Peak Output Power	PASS	None
3.10.1(6.2.1)	6dB Occupied Bandwidth	PASS	None
3.10.1(6.2.2)	Power Density	PASS	None
3.10.1(5)/2.8	Restricted Bands	PASS	None
3.10.1(3)	Antenna Requirement	PASS	None

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	1.38dB
2	Radiated Emission Test	3.17dB
3	RF power,conducted	0.16dB
4	Spurious emissions,conducted	0.21dB
5	All emissions,radiated(<1G)	4.68dB
6	All emissions,radiated(>1G)	4.89dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Dongle	
Brand Name	Ubudu	
Model Name	type V1	
Derivative Model	N/A	
OEM Brand/Model Name	N/A	
Product Description	The EUT is a Dongle.	
	Operation Frequency:	2402~2480 MHz
	BT Version:	Bluetooth 4.2
	Modulation Type:	GFSK
	Bit Rate of Transmitter	1Mbps
	Number Of Channel	40
	Antenna Designation:	Please see Note 3.
	Antenna Gain(Peak)	External antenna:3 dBi Directional antenna:12 dBi
	Output Power:	-1.35dBm
Channel List	Please refer to the Note 2.	
Power Rating	4.5 - 5.5 VDC	
Connecting I/O Port(s)	Please refer to the User's Manual	
Products Covered	N/A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.

Description of Channel:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	21	2442
02	2404	22	2444
03	2406	23	2446
04	2408	24	2448
05	2410	25	2450
06	2412	26	2452
07	2414	27	2454
08	2416	28	2456
09	2418	29	2458
10	2420	30	2460
11	2422	31	2462
12	2424	32	2464
13	2426	33	2466
14	2428	34	2468
15	2430	35	2470
16	2432	36	2472
17	2434	37	2474
18	2436	38	2476
19	2438	39	2478
20	2440	40	2480

- 3.

Table for Filed Antenna

	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	Maritex	BLU-ANT02TF F3SR	External antenna	RP-SMA	3 dBi	Antenna
2	YAGI.PL	hermetic mobile 12HV	DIRECTIONAL ANTENNA	RP-SMA	12 dBi	Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	GFSK

For Conducted Emission	
Final Test Mode	Description
Mode 1	GFSK

For Radiated Emission	
Final Test Mode	Description
Mode 1	GFSK

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) For all tests the worst-case was selected as the table above, the data of the worst-case is shown in the report.

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.


Test software Version	Test program: nRFgo		
Frequency	2402 MHz	2440 MHz	2480 MHz
Parameters(1Mbps)	Default	Default	Default

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Block diagram of EUT configuration

Non-Conductive Table

80 cm above Ground Plane



2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Dongle	Ubudu SAS	type V1	N/A	N/A	EUT
E-2	Notebook	ASUS	X401A	N/A	N/A	Provide by lab.

Item	Shielded Type	Ferrite Core	Length	Note
1#	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” means “shielded” or “with ferrite core”; “NO” means “unshielded” or “without ferrite core”

2.5.1 EQUIPMENTS LIST FOR ALL TEST ITEMS

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
Spectrum Analyzer	Hewlett Packard	8566B	3013A07296	April 29, 2018	1 Year
RF Preselector	Hewlett Packard	85685A	3010A01157	April 29, 2018	1 Year
Quasi-Peak Adapter	Hewlett Packard	85650	2521A00584	April 29, 2018	1 Year
Preamplifier	Com Power	PA-102	1482	April 29, 2018	1 Year
RF Attenuator	Mini-Circuits	CAT-10	Asset #1000	December 8, 2018	1 Year
LISN	Com Power	LI-200	12012	September 10, 2018	1 Year
LISN	Com Power	LI-200	12214	September 10, 2018	1 Year
LISN	Com Power	LI-200	1767	September 10, 2018	1 Year
LISN	Com Power	LI-200	1768	September 10, 2018	1 Year
Biconical Antenna	Com Power	AB-100	01557	December 29, 2018	1 Year
Log Periodic Antenna	Com Power	AL-100	16037	December 22, 2018	1 Year
Horn Antenna	Com Power	AHA-118	711054	December 22, 2018	1 Year
Antenna Mast	Com Power	AM-400	N/A	N/A	N/A
Turntable	Com Power	TT-100	N/A	N/A	N/A
Computer	Dell, Inc.	DHS	DNSV641	N/A	N/A
Printer	Hewlett Packard	C8124A	CN39B2234T	N/A	N/A
Plotter	Hewlett Packard	7470A	2308A96499	N/A	N/A

EMI Test Equipment (Continued)

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
EMI Receiver	Rohde & Schwarz	ESU40	100127	June 12, 2018	1 Year
BiConiLog Antenna	ETS-Lindgren	3142D	00102183	August 14, 2018	1 Year
Horn Antenna	ETS-Lindgren	3117	00109294	May 6, 2018	1 Year
Preamplifier	Rohde & Schwarz	TS-PR18	100056	June 12, 2018	1 Year
Antenna Mast	ETS-Lindgren	2175	00095727	N/A	N/A
Turntable	ETS-Lindgren	2187-3.0	00118231	N/A	N/A
Computer	Acer	Aspire 8930	85100050123	N/A	N/A
Multi-Function Controller	ETS-Lindgren	2090	00102270	N/A	N/A
Loop Antenna	ARA	PLA-1030/B	1029	May 19, 2018	1 Year

3. TRANSMITTER EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5			66 - 56 *	56 - 46 *	LP0002
0.50 -5.0			56.00	46.00	LP0002
5.0 -30.0			60.00	50.00	LP0002

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 TEST RESULTS

Not applicable. The EUT uses DC power.

Test result: The unit does meet the NCC requirements.

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 2.7, then the 2.8 limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to LP0002.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters (For frequencies above 1GHz, table 1.5 meters) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.3 TEST SETUP

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


3.2.5 TEST RESULTS (BLOW 30MHZ)

There is not detected blow 30MHz.

3.2.6 TEST RESULTS (BETWEEN30 – 1000 MHZ)

External antenna:

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX	Polarization :	Horizontal
Test Power :	DC 5V		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		36.8952	38.23	-16.72	21.51	40.00	-18.49	QP
2		71.8319	40.52	-19.07	21.45	40.00	-18.55	QP
3		137.9028	38.06	-14.83	23.23	43.50	-20.27	QP
4		216.0240	38.81	-16.38	22.43	46.00	-23.57	QP
5		299.3158	36.28	-9.69	26.59	46.00	-19.41	QP
6	*	798.9796	30.91	3.44	34.35	46.00	-11.65	QP

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX	Polarization :	Vertical
Test Power :	DC 5V		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	37.2854	48.65	-14.59	34.06	40.00	-5.94	QP
2		73.3593	40.27	-18.93	21.34	40.00	-18.66	QP
3		178.7581	38.21	-12.47	25.74	43.50	-17.76	QP
4		297.2241	35.38	-9.98	25.40	46.00	-20.60	QP
5		462.3455	35.03	-6.75	28.28	46.00	-17.72	QP
6		726.8052	32.96	-0.51	32.45	46.00	-13.55	QP

Test result: The unit does meet the NCC requirements.


EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX	Polarization :	Horizontal
Test Power :	DC 5V		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		36.6375	38.58	-14.74	23.84	40.00	-16.16	QP
2		63.9827	37.52	-17.66	19.86	40.00	-20.14	QP
3		146.8874	38.55	-15.42	23.13	43.50	-20.37	QP
4		241.6760	39.04	-14.04	25.00	46.00	-21.00	QP
5		399.0300	34.91	-6.94	27.97	46.00	-18.03	QP
6	*	701.7607	31.53	0.32	31.85	46.00	-14.15	QP

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX	Polarization :	Vertical
Test Power :	DC 5V		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	35.8746	47.76	-16.76	31.00	40.00	-9.00	QP
2		56.7916	43.97	-19.88	24.09	40.00	-15.91	QP
3		125.4457	36.42	-15.12	21.30	43.50	-22.20	QP
4		219.0750	41.89	-16.09	25.80	46.00	-20.20	QP
5		356.6757	33.73	-7.73	26.00	46.00	-20.00	QP
6		787.8513	31.52	1.51	33.03	46.00	-12.97	QP

3.2.7 TEST RESULTS (ABOVE 1000 MHZ)


External antenna:

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Model1(2402MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400.000	46.32	-5.70	40.62	74.00	-33.38	peak
2400.000	35.67	-5.70	29.97	54.00	-24.03	AVG
4804.000	48.13	5.06	53.19	74.00	-20.81	peak
4804.000	38.49	5.06	43.55	54.00	-10.45	AVG
7206.000	45.11	7.03	52.14	74.00	-21.86	peak
7206.000	33.67	7.03	40.70	54.00	-13.30	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2402MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
18789.00	38.79	16.20	54.99	74.00	-19.01	peak
18789.00	28.66	16.20	44.86	54.00	-9.14	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2402MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2400.000	46.95	-5.70	41.25	74.00	-32.75	peak
2400.000	35.63	-5.70	29.93	54.00	-24.07	AVG
4804.000	48.52	5.06	53.58	74.00	-20.42	peak
4804.000	36.44	5.06	41.50	54.00	-12.50	AVG
7206.000	43.60	7.03	50.63	74.00	-23.37	peak
7206.000	33.58	7.03	40.61	54.00	-13.39	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX TX Mode1(2402MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
19632.00 0	38.67	16.53	55.20	74.00	-18.80	peak
19632.00	28.25	16.53	44.78	54.00	-9.22	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4880.000	48.33	5.14	53.47	74.00	-20.53	peak
4880.000	38.57	5.14	43.71	54.00	-10.29	AVG
7320.000	43.31	7.52	50.83	74.00	-23.17	peak
7320.000	33.74	7.52	41.26	54.00	-12.74	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
18569.00	39.06	15.97	55.03	74.00	-18.97	peak
18569.00	28.72	15.97	44.69	54.00	-9.31	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4880.000	48.62	5.14	53.76	74.00	-20.24	peak
4880.000	38.64	5.14	43.78	54.00	-10.22	AVG
7320.000	42.59	7.52	50.11	74.00	-23.89	peak
7320.000	33.27	7.52	40.79	54.00	-13.21	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
19064.00 0	38.11	16.42	54.53	74.00	-19.47	peak
19064.00	27.65	16.42	44.07	54.00	-9.93	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2480MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	46.51	-4.98	41.53	74.00	-32.47	peak
2483.500	35.84	-4.98	30.86	54.00	-23.14	AVG
4960.000	48.67	5.22	53.89	74.00	-20.11	peak
4960.000	38.26	5.22	43.48	54.00	-10.52	AVG
7440.000	42.58	8.06	50.64	74.00	-23.36	peak
7440.000	32.49	8.06	40.55	54.00	-13.45	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2480MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
20015.00 0	39.03	16.61	55.64	74.00	-18.36	peak
20015.00	28.44	16.61	45.05	54.00	-8.95	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2480MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	46.14	-4.98	41.16	74.00	-32.84	peak
2483.500	35.83	-4.98	30.85	54.00	-23.15	AVG
4960.000	48.52	5.22	53.74	74.00	-20.26	peak
4960.000	38.55	5.22	43.77	54.00	-10.23	AVG
7440.000	42.34	8.06	50.40	74.00	-23.60	peak
7440.000	32.70	8.06	40.76	54.00	-13.24	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2480MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
18342.00	38.49	15.73	54.22	74.00	-19.78	peak
18342.00	28.22	15.73	43.95	54.00	-10.05	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.

No any other emissions detected which are tested to compliance with the limit. No recording in the test report.


Test result: The unit does meet the NCC requirements.

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1766.520	46.14	-9.44	36.70	74.00	-37.30	peak
3001.025	43.52	-1.68	41.84	74.00	-32.16	peak
3879.650	43.81	2.95	46.76	74.00	-27.24	peak
4369.367	46.15	4.47	50.62	74.00	-23.38	peak
6801.402	44.39	6.05	50.44	74.00	-23.56	peak
17959.654	33.05	24.71	57.76	74.00	-16.24	peak
17959.654	23.56	24.71	48.27	54.00	-5.73	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1843.489	46.27	-9.43	36.84	74.00	-37.16	peak
2966.674	43.56	-1.91	41.65	74.00	-32.35	peak
4357.591	44.28	4.45	48.73	74.00	-25.27	peak
6866.541	43.32	6.09	49.41	74.00	-24.59	peak
8009.627	42.26	10.40	52.66	74.00	-21.34	peak
17884.592	33.14	24.76	57.90	74.00	-16.10	peak
17884.592	23.03	24.76	47.79	54.00	-6.21	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
18421.000	39.51	15.81	55.32	74.00	-18.68	peak
18421.000	29.05	15.81	44.86	54.00	-9.14	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
19329.000	38.44	16.46	54.90	74.00	-19.10	peak
19329.000	28.86	16.46	45.32	54.00	-8.68	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.


No any other emissions detected which are tested to compliance with the limit. No recording in the test report.

Test result: The unit does meet the NCC requirements.

3.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHZ)

Direction antenna:

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX	Polarization :	Horizontal
Test Power :	DC 5V		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		37.0248	38.99	-14.66	24.33	40.00	-15.67	QP
2		145.8608	38.82	-15.33	23.49	43.50	-20.01	QP
3		178.1323	38.52	-12.60	25.92	43.50	-17.58	QP
4		259.2336	36.78	-12.88	23.90	46.00	-22.10	QP
5		420.5803	31.77	-6.63	25.14	46.00	-20.86	QP
6	*	699.3046	32.32	0.44	32.76	46.00	-13.24	QP

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX	Polarization :	Vertical
Test Power :	DC 5V		




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	36.3813	48.88	-16.74	32.14	40.00	-7.86	QP
2		56.3947	41.49	-19.94	21.55	40.00	-18.45	QP
3		106.3850	32.95	-13.50	19.45	43.50	-24.05	QP
4		193.7726	38.02	-16.22	21.80	43.50	-21.70	QP
5		289.0020	33.32	-10.32	23.00	46.00	-23.00	QP
6		721.7259	32.41	-0.41	32.00	46.00	-14.00	QP

Test result: The unit does meet the NCC requirements.


EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX	Polarization :	Horizontal
Test Power :	DC 5V		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		37.6798	34.20	-14.51	19.69	40.00	-20.31	QP
2		63.0915	36.57	-17.90	18.67	40.00	-21.33	QP
3		118.1860	37.71	-15.00	22.71	43.50	-20.79	QP
4		183.8437	33.17	-11.72	21.45	43.50	-22.05	QP
5		349.2500	31.80	-8.05	23.75	46.00	-22.25	QP
6	*	699.3046	32.04	0.44	32.48	46.00	-13.52	QP

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX	Polarization :	Vertical
Test Power :	DC 5V		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		40.2757	43.53	-16.67	26.86	40.00	-13.14	QP
2		118.6012	37.29	-14.69	22.60	43.50	-20.90	QP
3		185.7880	37.37	-15.67	21.70	43.50	-21.80	QP
4		272.2776	35.77	-12.27	23.50	46.00	-22.50	QP
5		407.5144	32.21	-6.45	25.76	46.00	-20.24	QP
6	*	798.9796	30.29	3.44	33.73	46.00	-12.27	QP

Test result: The unit does meet the NCC requirements.

3.2.9 TEST RESULTS (ABOVE 1000 MHZ)


Direction antenna:

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Model1(2402MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2400.000	46.37	-5.70	40.67	74.00	-33.33	peak
2400.000	35.59	-5.70	29.89	54.00	-24.11	AVG
4804.000	48.24	5.06	53.30	74.00	-20.70	peak
4804.000	38.55	5.06	43.61	54.00	-10.39	AVG
7206.000	45.29	7.03	52.32	74.00	-21.68	peak
7206.000	33.57	7.03	40.60	54.00	-13.40	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2402MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
18654.00 0	38.78	16.05	54.83	74.00	-19.17	peak
18654.00	28.66	16.05	44.71	54.00	-9.29	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2402MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2400.000	46.87	-5.70	41.17	74.00	-32.83	peak
2400.000	35.88	-5.70	30.18	54.00	-23.82	AVG
4804.000	48.47	5.06	53.53	74.00	-20.47	peak
4804.000	36.26	5.06	41.32	54.00	-12.68	AVG
7206.000	43.85	7.03	50.88	74.00	-23.12	peak
7206.000	33.74	7.03	40.77	54.00	-13.23	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX TX Mode1(2402MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
20163.00 0	38.57	16.63	55.20	74.00	-18.80	peak
20163.00	28.15	16.63	44.78	54.00	-9.22	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4880.000	48.56	5.14	53.70	74.00	-20.30	peak
4880.000	38.67	5.14	43.81	54.00	-10.19	AVG
7320.000	43.24	7.52	50.76	74.00	-23.24	peak
7320.000	33.69	7.52	41.21	54.00	-12.79	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
19032.00	38.74	16.42	55.16	74.00	-18.84	peak
19032.00	28.32	16.42	44.74	54.00	-9.26	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4880.000	48.90	5.14	54.04	74.00	-19.96	peak
4880.000	38.72	5.14	43.86	54.00	-10.14	AVG
7320.000	42.58	7.52	50.10	74.00	-23.90	peak
7320.000	33.36	7.52	40.88	54.00	-13.12	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2440MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
20024.00	38.03	16.61	54.64	74.00	-19.36	peak
20024.00	27.56	16.61	44.17	54.00	-9.83	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2480MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	46.59	-4.98	41.61	74.00	-32.39	peak
2483.500	36.18	-4.98	31.20	54.00	-22.80	AVG
4960.000	48.67	5.22	53.89	74.00	-20.11	peak
4960.000	38.22	5.22	43.44	54.00	-10.56	AVG
7440.000	42.67	8.06	50.73	74.00	-23.27	peak
7440.000	32.51	8.06	40.57	54.00	-13.43	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2480MHz)	Polarization :	Horizontal
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
18976.00	38.54	16.39	54.93	74.00	-19.07	peak
18976.00	28.43	16.39	44.82	54.00	-9.18	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Mode1(2480MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	46.44	-4.98	41.46	74.00	-32.54	peak
2483.500	35.78	-4.98	30.80	54.00	-23.20	AVG
4960.000	48.65	5.22	53.87	74.00	-20.13	peak
4960.000	38.61	5.22	43.83	54.00	-10.17	AVG
7440.000	42.57	8.06	50.63	74.00	-23.37	peak
7440.000	32.76	8.06	40.82	54.00	-13.18	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	TX Model1(2480MHz)	Polarization :	Vertical
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
19650.00 0	38.36	16.53	54.89	74.00	-19.11	peak
19650.00	27.99	16.53	44.52	54.00	-9.48	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.

No any other emissions detected which are tested to compliance with the limit. No recording in the test report.


Test result: The unit does meet the NCC requirements.

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1776.184	46.32	-9.40	36.92	74.00	-37.08	peak
3015.352	43.55	-1.65	41.90	74.00	-32.10	peak
3899.653	43.57	3.11	46.68	74.00	-27.32	peak
4365.182	46.24	4.46	50.70	74.00	-23.30	peak
6800.332	44.33	6.05	50.38	74.00	-23.62	peak
17884.59 2	33.10	24.76	57.86	74.00	-16.14	peak
17884.59	23.62	24.76	48.38	54.00	-5.62	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	1GHz to 18GHz
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
1984.000	46.32	-9.15	37.17	74.00	-36.83	peak
3001.369	43.28	-1.68	41.60	74.00	-32.40	peak
4343.569	44.26	4.42	48.68	74.00	-25.32	peak
6877.659	43.33	6.10	49.43	74.00	-24.57	peak
8011.347	42.36	10.40	52.76	74.00	-21.24	peak
17880.32 5	33.20	24.76	57.96	74.00	-16.04	peak
17884.59	23.16	24.76	47.92	54.00	-6.08	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Horizontal
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC 5V		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
19667.00	38.85	16.53	55.38	74.00	-18.62	peak
19667.00	28.64	16.53	45.17	54.00	-8.83	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2019-01-25
Test Mode :	RX (worst case)	Polarization :	Vertical
Measurement Distance	3 m	Frenqucy Range	18GHz to 25GHz
Test Power :	DC 5V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
18023.00	38.63	15.40	54.03	74.00	-19.97	peak
18023.00	28.04	15.40	43.44	54.00	-10.56	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Remark:

All the modes had been tested, but only the worst data recorded in the report.

No any other emissions detected which are tested to compliance with the limit. No recording in the test report.

Test result: The unit does meet the NCC requirements.

3.2.10 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)


EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Test Data	2019-01-25
Pressure :	1010 hPa	Relative Humidity :	54%
Test Mode :	Mode 1	Test Voltage :	DC 5V
Note :	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz. 3. The data of 2390MHz and 2483.5MHz was the worst.		

Test Mode	Ant.Pol. H/V	Freq. (MHz)	Reading		Ant/CF CF(dB)	Act		Limit	
			Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)
Mode 1	V	2390.00	46.24	--	-5.79	40.45	--	74.00	54.00
	H	2390.00	48.19	--	-5.79	42.4	--	74.00	54.00
	V	2483.50	50.41	--	-4.98	45.43	--	74.00	54.00
	H	2483.50	52.52	--	-4.98	47.54	--	74.00	54.00


Remark :

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode
- (2) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (3) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (4) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Horizontal



Vertical



Test result: The unit does meet the NCC requirements.

4. OCCUPIED BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
3.10.1(6.2.1)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	$>$ Measurement Bandwidth or Channel Separation
RB	100 kHz (6dB Bandwidth) / 100 kHz (Channel Separation)
VB	300 kHz (6dB Bandwidth) / 300 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

4.1.2 TEST SETUP




4.1.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.4 TEST RESULTS

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Power :	DC 5V
Test Mode :	Mode 1		

Test Mode	Test Channel	Frequency (MHz)	6 dB Bandwidth (KHz)	Limit (kHz)
Mode 1	CH01	2402	637	≧ 500
	CH20	2440	641	≧ 500
	CH40	2480	654	≧ 500





5. POWER DENSITY

5.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
3.10.1(6.2.2)	Power density	8dBm	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	3 kHz
VB	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 3KHz, VBW=10KHz.

5.1.2 TEST SETUP



5.1.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


5.1.4 TEST RESULTS

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	Mode 1		

Test Channel	Frequency(MHz)	Power Density(dBm)	LIMIT(dBm)
CH01	2402 MHz	-17.01	2.00
CH20	2440 MHz	-16.30	2.00
CH40	2480 MHz	-16.37	2.00

Note: Directional antenna: 12 dBi, Limit reduced 6 dBm.





6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

LP0002				
Section	Test Item	Limit	Frequency Range (MHz)	Result
3.10.1(2)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS


6.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 1 MHz, VBW= 3 MHz, Sweep time = Auto.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.5 TEST RESULTS

EUT :	Dongle	Model Name :	type V1
Temperature :	24 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	Mode 1		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit(dBm)	Result
CH01	2402 MHz	-1.49	24	PASS
CH20	2440MHz	-1.35	24	PASS
CH40	2480 MHz	-1.48	24	PASS

Note: Directional antenna: 12 dBi, Limit reduced 6 dBm.





7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in Section 2.8.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100 KHz /300 KHz for Peak

7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

7.1.2 TEST SETUP



7.1.3 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.4 TEST RESULTS


EUT :	Dongle	Model Name :	type V1
Temperature :	25 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode:	Mode 1		

in any 100kHz bandwidth outside the low frequency band	in any 100 kHz bandwidth outside the high frequency band
Pass	Pass
Result	
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.	

CH01 (Lower)



CH40 (Upper)



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

3.10.3.1.1 requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

8.2 EUT ANTENNA

The antenna is an external antenna or DIRECTIONAL ANTENNA with RP-SMA connector and no consideration of replacement. Antenna max gain is 3 dBi (external antenna) or 12 dBi (DIRECTIONAL ANTENNA) from 2.4GHz to 2.5GHz.

9. EUT TEST PHOTO

**Radiated Measurement Photos
30MHz-1GHz**




**Radiated Measurement Photos
Above 1GHz**



**Radiated Measurement Photos
30MHz-1GHz**



**Radiated Measurement Photos
Above 1GHz**



10. APPENDIX-Photographs of EUT Constructional Details

Please refer to **APPENDIX**.