


Test report No:
2570857R.701

MIC TEST REPORT

Product Name	Rechargeable Li-ion Battery Pack
Model and /or type reference	BP 18 Li 4,0 HPC-ASI
Trademark	FESTOOL
Applicant's name / address	Nanjing Chervon Industry Co., Ltd. No.529 Jiangjun Road, Jiangning Economic & Technical Development Zone, 211106 Nanjing Jiangsu China
Test method requested, standard	Notification No. 88 Annex 43 Article 2 paragraph 1 item 19
Verdict Summary	IN COMPLIANCE
Documented by (name / position & signature)	Tim Cao / Project Manager 
Approved by (name / position & signature)	Frank He / Manager 
Date of issue	2025-09-15
Report Version	V1.0
Report template No	Template_MIC-2.4G-RF-V1.0

INDEX

	page
Competences and Guarantees	4
General conditions	4
Environmental conditions	4
Possible test case verdicts	5
Abbreviations	5
Document History	6
Remarks and Comments	6
Used Equipment	7
Uncertainty	8
1 General Information	9
2 Description of Test Setup	10
2.1 Test Voltage	10
3 Verdict summary section	11
3.1 Standards	11
3.2 Deviation(s) from the Standard(s) / Test Specification(s)	11
3.3 Overview of results	12
4 Test Results	13
4.1 Antenna Power Antenna Power Tolerance and E.I.R.P.	13
4.1.1 Limit	13
4.1.2 Test Set up	13
4.1.3 Test Procedure	13
4.2 Occupied Bandwidth	14
4.2.1 Limit	14
4.2.2 Test Setup	14
4.2.3 Test Procedure	14
4.3 Frequency Tolerance	15
4.3.1 Limit	15
4.3.2 Test Setup	15
4.3.3 Test Procedure	15
4.4 Transmitter Spurious Emission	17
4.4.1 Limit	17
4.4.2 Test Setup	17
4.4.3 Test Procedure	17
4.5 Receiver Spurious Emission	19

4.5.1	Limit	19
4.5.2	Test Setup	19
4.5.3	Test Procedure	19
4.6	Interference Prevention Function Measurement	21
4.6.1	Limit	21
4.6.2	Test Setup	21
4.6.3	Test Procedure	21
5	Conforming the structure that is difficult to open	22
6	Setup photo and EUT photo	23
7	Test Result	24
Appendix A: Antenna Power Tolerance and E.I.R.P		24
Appendix B: Occupied Bandwidth		25
Appendix C: Frequency Tolerance		27
Appendix D: Transmitter Spurious Emissions		29
Appendix E: Receiver Spurious Emissions		37
Appendix F: Interference Prevention Function		41

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Jul. 31, 2025
Date (start test)	Jul. 31, 2025
Date (finish test)	Aug. 08, 2025

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	24°C
Relative Humidity air	60%

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2570857R.701	V1.0	Initial issue of report.	2025-09-15

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with Article 2 paragraph 1 item 19.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1 General Information

USED EQUIPMENT

Conducted Test/ TR8

Instrument	Manufacturer	Model No.	Serial No.	Next Cal. Date
Wireless Connectivity Tester	R&S	CMW 270	102593	2026.05.09
Coaxial Cable	N/A	N/A	2477	2026.06.09
Coaxial Cable	N/A	N/A	2478	2026.06.09
Temperature/Humidity Meter	RTS	RTS-8S	RF08	2026.07.10
MAX Signal Analyzer	Keysight	N9010A	MY48030494	2025.10.18
RF Control Unit	Tonscend	JS0806-2	22G8060594	2026.01.25
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	2026.03.22
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	2026.03.22
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	2026.07.05
Test Software	Tonscend	TS1120	JS1120-3	N/A

Instrument	Manufacturer	Model No.	Serial No.	Firmware Version	Software version	Calibration Body	Calibration Method
Wireless Connectivity Tester	R&S	CMW 270	102593	V 4.0.60	N/A	CEPREI	c
Coaxial Cable	N/A	N/A	2477	N/A	N/A	CEPREI	c
Coaxial Cable	N/A	N/A	2478	N/A	N/A	CEPREI	c
Temperature/Humidity Meter	RTS	RTS-8S	RF08	N/A	N/A	CEPREI	c
MAX Signal Analyzer	Keysight	N9010A	MY48030494	A.14.03	N/A	CEPREI	c
RF Control Unit	Tonscend	JS0806-2	22G8060594	N/A	N/A	CEPREI	c
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	B.01.96	N/A	CEPREI	c
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	N/A	N/A	CEPREI	c
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	B.01.95	N/A	GRGTEST	c
Test Software	Tonscend	TS1120	JS1120-3	N/A	V3.0.22	CEPREI	c

Calibration Method:

- a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1)
- b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992)
- c) Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1)
- d) Calibration conducted by using measuring instruments and other equipment listed in the right column of Table No. 3 attached hereto, which shall have been given any of calibration, etc. listed above from a) to c)
- CEPREI : China ceprei laboratory calibration & testing centre.
- DEKRA : DEKRA Testing and Certification (Suzhou) Co., Ltd.
- GRGTEST: Grg Metrology&Test (WuXi) Co.,Ltd.

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test item	Uncertainty
Antenna Power Antenna Power Tolerance and E.I.R.P	± 1.3 dB
Occupied Bandwidth	± 0.15 kHz
Frequency Tolerance	± 0.15 kHz
Transmitter Spurious Emissions	± 1.3 dB
Receiver Spurious Emissions	± 1.3 dB

1 GENERAL INFORMATION

Product Name..... :	Rechargeable Li-ion Battery Pack					
Model No. :	BP 18 Li 4,0 HPC-ASI					
Trademark	FESTOOL					
Operation Temperature	-10~50℃					
Manufacturer..... :	Festool GmbH					
Manufacturer address	Wertstraße 20, 73240 Wendlingen, Germany					
Power Supply..... :	DC: 18 Vdc					
SN / IMEI	43802296					
Wireless specification..... :	Bluetooth					
Operating frequency range(s)	2402~2480MHz					
Type of Modulation..... :	GFSK					
PHYs	☒	LE 1M	☐	LE 2M	☐	LE Coded S=2/8
Data Rate	☒	1Mbit/s	☐	2Mbit/s	☐	500/125 Kbit/s
Number of channels	40					
Antenna Type	PCB					
Antenna Gain..... :	-7.3 dBi					
Declared Power	1 mW					

Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

2 DESCRIPTION OF TEST SETUP

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) N/A	N/A	N/A	N/A
(2) N/A	N/A	N/A	N/A
(3) N/A	N/A	N/A	N/A
software	Type / Version	Manufacturer	Supplied by
nRF	2.4.2	N/A	N/A

2.1 Test Voltage

Power supply voltage fluctuation test

Voltage Fluctuation Test	Normal Voltage	High Voltage Normal Voltage +10% of	Low Voltage Normal Voltage -10% of
Input To EUT	DC 18 V	DC 19.8 V	DC 16.2 V
Test Result	3.3 V	3.3 V	3.3 V
Voltage Variation	Reference	0%	0%

Note:

Changing the supply voltage of the EUT will not change the voltage of the RF module.

During the input supply voltage to the EUT from the external power source is varied by +/- 10%, if output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/-1%. Exempt extremely high and low supply voltage condition test, EUT only operated in normal voltage to test all regulations.

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
Article 2 paragraph 1 item (19)	2023	2.4GHz Band Advanced Low Power Data Communication System
Notification No. 88 Annex 43.	2004	Test methods for radio equipment listed in Article 2, Paragraph 1, Item 19 and Item 19-2-2 of Certification Ordinance
--	--	--

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

No deviation

3.3 Overview of results

Test Item - MIC notification 88 Annex 43				
Performed Test Item	Normative References	Test Performed	Verdict	Remark
Antenna Power Tolerance and E.I.R.P	MIC notification 88 Annex 43 section 6	Yes	PASS	Test data please refer to Appendix A
Occupied Bandwidth	MIC Notification 88 Annex 43 section 4	Yes	PASS	Test data please refer to Appendix B
Frequency Tolerance	MIC Notification 88 Annex 43 section 3	Yes	PASS	Test data please refer to Appendix C
Transmitter Spurious Emissions	MIC Notification 88 Annex 43 section 7	Yes	PASS	Test data please refer to Appendix D
Receiver Spurious Emissions	MIC Notification 88 Annex 43 section 7	Yes	PASS	Test data please refer to Appendix E
Interference Prevention Function	MIC Notification 88 Annex 43 section 12	Yes	PASS	Test data please refer to Appendix F

4 TEST RESULTS

4.1 Antenna Power Antenna Power Tolerance and E.I.R.P

VERDICT: PASS

4.1.1 Limit

Standard Article 2 paragraph 1 item 19


Output Power

- | | |
|-------------------------------------|--|
| ☒ | Max EIRP $\leq 12.14\text{dBm}$ |
| ☒ | Antenna power $\leq 10\text{mW}$ |
| ☐ | Max antenna gain = Max EIRP - declared power Max declared conductive power |
| ☐ | Antenna power = Max EIRP - Antenna gain |

Output Power Tolerance

- | | |
|-------------------------------------|------------------------------|
| ☒ | Output Power Tolerance: +20% |
|-------------------------------------|------------------------------|

4.1.2 Test Set up



4.1.3 Test Procedure

References Rule

- | | |
|-------------------------------------|-------------------------------------|
| ☒ | Method 1: MIC Notice 88 Appendix 43 |
|-------------------------------------|-------------------------------------|


Step 1

- Connect a high-frequency power meter to the output of the dummy load (attenuator) and measure the total power.
- Antenna power shall be as follows.
 - Value of a for continuous wave
 - Burst wave The average power in the burst is calculated from the value of (a) and the transmission time rate.

4.2 Occupied Bandwidth**VERDICT: PASS****4.2.1 Limit****Standard**

Article 2 paragraph 1 item 19

- | | |
|-------------------------------------|--|
| ☐ | Channel Power of DSSS, the limit should $\leq 26\text{MHz}$ |
| ☐ | Channel Power of FHSS, the limit should $\leq 83.5\text{MHz}$ |
| ☐ | Channel Power of OFDM |
| ☐ | Nominal Bandwidth=20MHz, the limit should $\leq 26\text{MHz}$ |
| ☐ | Nominal Bandwidth=40MHz, the limit should $\leq 38\text{MHz}$ |
| ☒ | Channel Power of other situation, the limit should $\leq 26\text{MHz}$ |

4.2.2 Test Setup**4.2.3 Test Procedure**

References Rule

- | | |
|-------------------------------------|-------------------------------|
| ☒ | Notification No. 88 Annex 43. |
|-------------------------------------|-------------------------------|

Step 1


1. Set spectrum analyzer to following setting:

- Center frequency: Equal to center frequency of test signal
- Span: Between 2 times and 3.5 times the limited bandwidth.
- RBW: Less than 3% of the limited bandwidth
- VBW: Equal to RBW
- Sweep mode: Continuous sweep
- Detect mode: Positive peak
- Trace mode: Max hold

2. The integrated 99% power bandwidth function may be used to measure the spread bandwidth.

4.3 Frequency Tolerance**VERDICT: PASS****4.3.1 Limit****Standard**

Article 2 paragraph 1 item 19

 $\leq \pm 50$ ppm**4.3.2 Test Setup****4.3.3 Test Procedure**

References Rule

- ☒
- Notification No. 88 Annex 43.

Step 1

- ☒
- Unmodulation Wave (CW signal)

1. Set spectrum analyzer as following setting:

Center frequency: Equal to center frequency of signal under test

Span: Widest enough to see the entire waveform

RBW: 10kHz

VBW: 10kHz

Detect mode: Positive Peak

Trace mode: Max hold

Sweep time: Auto

2. Use the peak search function to find the highest level frequency and record data.

- ☐
- Modulation Wave

1. Set spectrum analyzer to following setting:

Center frequency: Equal to center frequency of signal under test

Span: Widest enough to see the entire waveform

RBW: 100kHz

VBW: 100kHz

Detect mode: Positive Peak


Trace mode: Max hold

Sweep time: Auto

2. Use the peak search function to find the highest level frequency, record maximum level.
3. Setting display line to 10dB lower than the maximum level.
4. Mark the lowest and highest frequency where the test signal intersect the display line, record the frequency F_L , F_H .
5. The Center frequency of test $F_C = (F_L + F_H)/2$

4.4 Transmitter Spurious Emission**VERDICT: PASS****4.4.1 Limit****Standard**

Article 2 paragraph 1 item 19

Frequency between 30 - 2387 MHz, $\leq 2.5\mu\text{W}/\text{MHz}$ Frequency between 2387 - 2400 MHz, $\leq 25\mu\text{W}/\text{MHz}$ Frequency between 2483.5 - 2496.5 MHz, $\leq 25\mu\text{W}/\text{MHz}$ Frequency between 2496.5 - 12500, $\leq 2.5\mu\text{W}/\text{MHz}$ **4.4.2 Test Setup****4.4.3 Test Procedure**

References Rule



Notification No. 88 Annex 43.

Step 1

1. Set the spectrum analyzer as follows when searching.

Sweep frequency width	30MHz to 5 times the carrier frequency
Resolution bandwidth	100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz
Video bandwidth	Same as resolution bandwidth
Sweep time	Minimum time for guaranteed measurement accuracy
Sweep mode	Single sweep
Detection mode	positive peak

2. Set the spectrum analyzer for secondary emission measurement as follows.


Center frequency	Secondary emission frequency
Sweep frequency width	0Hz
Resolution bandwidth	100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz
Video bandwidth	Same as resolution bandwidth
Sweep time	Minimum time for guaranteed measurement accuracy
Sweep mode	Single sweep
Detection mode	sample

4.5 Receiver Spurious Emission**VERDICT: PASS****4.5.1 Limit****Standard**

Article 2 paragraph 1 item 19

<= 4nW for 30 - 1000 MHz

<= 20nW for 1000 - 12500 MHz

4.5.2 Test Setup**4.5.3 Test Procedure**

References Rule

☒ Notification No. 88 Annex 43.

Step 1

1. Set the spectrum analyzer as follows when searching.

Sweep frequency width 30MHz to 5 times the carrier frequency

Resolution bandwidth 100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz

Video bandwidth Same as resolution bandwidth

Sweep time Minimum time for guaranteed measurement accuracy

Sweep mode Single sweep

Detection mode positive peak

2. Set the spectrum analyzer for secondary emission measurement as follows.

Center frequency Secondary emission frequency

Sweep frequency width	0Hz
Resolution bandwidth	100 kHz for frequencies below 1 GHz, 1 MHz for frequencies above 1 GHz
Video bandwidth	Same as resolution bandwidth
Sweep time	Minimum time for guaranteed measurement accuracy
Sweep mode	Single sweep
Detection mode	sample

4.6 Interference Prevention Function Measurement

VERDICT: PASS


4.6.1 Limit

Standard

Article 2 Paragraph 1 of item 19

The one automatically to transmit and to receive identification code with the wireless equipment of the wireless station used in the same premises.

4.6.2 Test Setup



4.6.3 Test Procedure

References Rule
☒ Notification No. 88 Annex 43.

Step 1

1. Establish communication between EUT and auxiliary equipment, auxiliary must have an ability to parse and display the identifier code.
2. When the test equipment has the function of automatically transmitting the identification code.
 - A. The test equipment sends the identification code specified in the equipment rules.
 - B. Check the identification code sent by the demodulator.
3. When the test equipment has the function of automatically receiving the identification code.
 - A. The opposite device transmits the identification code specified in the device rules.
 - B. Verify that a dedicated fixture is used to communicate with the test equipment.
 - C. Send a code from the counter that differs from the identification code specified in the equipment rules.
 - D. Verify that the test equipment stops transmitting or displays a different ID.
4. If the encoding specified in the device rules is the same as the demodulated encoding, recoded as "Good", otherwise record as "No".

5 CONFORMING THE STRUCTURE THAT IS DIFFICULT TO OPEN

The Radio Equipment:	
☐	Use Special Screw
☐	Metal Shielding is Soldered
☐	Use Ball Grid Array (BGA)
☒	RF module/Chip Pins > 20
☐	RF module/Chip Pins distance < 1.5 mm

The high-frequency section and modulation section (except for the antenna system) are not capable of being opened easily.

6 SETUP PHOTO AND EUT PHOTO

Remark: The test setup photo and EUT Photo please see appendix.

7 TEST RESULT

APPENDIX A: ANTENNA POWER TOLERANCE AND E.I.R.P

Model	Frequency (MHz)	Real Value (dBm)	EIRP (dBm)	RealValue (mW)	Tolerance (%)	Declared Output (mW)	Tolerance Limit (%)	Conducted Limit (mW)	EIRP Limit (dBm)
LE_1M	2402	-2.32	-9.62	0.59	-41.39	1	+20	10	12.14
	2440	-1.45	-8.75	0.72	-28.39	1	+20	10	12.14
	2480	-0.23	-7.53	0.95	-5.16	1	+20	10	12.14

Note1: EIRP = Real Value + Antenna Gain.

Note2: Antenna Gain Refer to Clause 1.


Note3: Deviation = (Total Reading Value - Declared Output Power) / Declared Output Power * 100%

APPENDIX B: OCCUPIED BANDWIDTH

TestCondition	TestMode	Freq(MHz)	Result [MHz]	Limit [MHz]	Verdict
NTNV	BLE_1M	2402	1.271	≤26	PASS
NTNV	BLE_1M	2440	1.271	≤26	PASS
NTNV	BLE_1M	2480	1.271	≤26	PASS

Test Graphs





APPENDIX C: FREQUENCY TOLERANCE


TestCondition	TestMode	Freq(MHz)	CenterFreq [MHz]	Result[ppm]	Limit[ppm]	Verdict
NTNV	BLE_1M	2402	2402.015	6.24480	±50	PASS
NTNV	BLE_1M	2440	2440.015	6.14754	±50	PASS
NTNV	BLE_1M	2480	2480.012	4.83871	±50	PASS


Test Graphs

NTNV-BLE_1M-Ant1-2402-PASS



NTNV-BLE_1M-Ant1-2440-PASS








APPENDIX D: TRANSMITTER SPURIOUS EMISSIONS


TestCondition	TestMode	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [μW]	Limit [μW]	Verdict
NTNV	BLE_1M	2402	30~1000	923.37	-47.22	≤-26	0.01897	≤2.5	PASS
NTNV	BLE_1M	2402	1000~2387	2376.60	-45.73	≤-26	0.02673	≤2.5	PASS
NTNV	BLE_1M	2402	2387~2400	2400.00	-35.30	≤-16	0.29512	≤25	PASS
NTNV	BLE_1M	2402	2483.5~2496.5	2485.79	-45.63	≤-16	0.02735	≤25	PASS
NTNV	BLE_1M	2402	2496.5~13000	7206.79	-41.96	≤-26	0.06368	≤2.5	PASS
NTNV	BLE_1M	2440	30~1000	913.67	-47.63	≤-26	0.01726	≤2.5	PASS
NTNV	BLE_1M	2440	1000~2387	2063.48	-45.64	≤-26	0.02729	≤2.5	PASS
NTNV	BLE_1M	2440	2387~2400	2397.91	-46.48	≤-16	0.02249	≤25	PASS
NTNV	BLE_1M	2440	2483.5~2496.5	2495.14	-45.67	≤-16	0.02710	≤25	PASS
NTNV	BLE_1M	2440	2496.5~13000	7319.71	-42.62	≤-26	0.05470	≤2.5	PASS
NTNV	BLE_1M	2480	30~1000	771.08	-47.11	≤-26	0.01945	≤2.5	PASS
NTNV	BLE_1M	2480	1000~2387	2340.19	-46.07	≤-26	0.02472	≤2.5	PASS
NTNV	BLE_1M	2480	2387~2400	2388.51	-46.08	≤-16	0.02466	≤25	PASS
NTNV	BLE_1M	2480	2483.5~2496.5	2483.55	-36.83	≤-16	0.20749	≤25	PASS
NTNV	BLE_1M	2480	2496.5~13000	7441.02	-42.64	≤-26	0.05445	≤2.5	PASS


Test Graphs























APPENDIX E: RECEIVER SPURIOUS EMISSIONS


TestCondition	TestMode	Antenna	Freq(MHz)	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	BLE_1M	Ant1	2402	30~1000	191.99	-84.69	≤-54	0.00340	≤4	PASS
NTNV	BLE_1M	Ant1	2402	1000~12500	4801.90	-73.66	≤-47	0.04305	≤20	PASS
NTNV	BLE_1M	Ant1	2440	30~1000	191.99	-84.07	≤-54	0.00392	≤4	PASS
NTNV	BLE_1M	Ant1	2440	1000~12500	4878.38	-70.83	≤-47	0.08260	≤20	PASS
NTNV	BLE_1M	Ant1	2480	30~1000	722.10	-77.97	≤-54	0.01596	≤4	PASS
NTNV	BLE_1M	Ant1	2480	1000~12500	4957.73	-69.86	≤-47	0.10328	≤20	PASS

Test Graphs









APPENDIX F: INTERFERENCE PREVENTION FUNCTION

Test Item	:	Interference Prevention Function Measurement
Test Site	:	TR8
Test Mode	:	Normal Mode
EUT MAC Address	:	F3:6A:E6:48:6D:15
<div><div></div><div><div>BP18 4,0 ASI</div><div>F3:6A:E6:48:6D:15</div><div>NOT BONDED</div></div><div><div><div>CONNECT</div><div>⋮</div></div></div><div><div>▲ -51 dBm</div><div>↔ 55 ms</div></div></div>		

The End