

Report on the FCC and ISED Testing of the

Invue Security Products, Inc
IR3 Ecosystem:
IR3Key

In accordance with:
LP0002, Updated July 2020

Prepared for: Invue Security Products Inc
9201 Baybrook Lane
Charlotte, North Carolina 28277 USA



America

**Add value.
Inspire trust.**

COMMERCIAL-IN-CONFIDENCE

Document Number: NC72170834.7 | Issue: 2

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Brad A Reasoner	EMC Technical Lead	Authorized Signatory	03 December 2021

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD America, Inc. document control rules.

FCC Accreditation	Innovation, Science, and Economic Development Canada
Designation Number US1148 New Brighton, MN Test	Accreditation
Laboratory	Site Number 4512A New Brighton, MN Test Laboratory

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with the standard(s) listed above.



A2LA Cert. No. 2955.11

DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD America with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD America. No part of this document may be reproduced without the prior written approval of TÜV SÜD America. © TÜV SÜD.

ACCREDITATION

Our A2LA Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our A2LA Accreditation.

TÜV SÜD America Inc
141 14th Street NW
New Brighton, MN 55112

Phone: 651-631-2487
www.tuv-sud-america.com



Contents

1	Report Summary	3
1.1	Report Modification Record.....	3
1.2	Introduction.....	3
1.3	Summary of Results	4
1.4	Product Information	5
1.5	Deviations from the Standard.....	10
1.6	EUT Modification Record	10
1.7	Test Location	10
2	Test Details	11
2.1	Radiated Emissions.....	11
3	Diagram of Test Set-ups	21
4	Accreditation, Disclaimers and Copyright.....	22



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Table 1.1-1 – Modification Record

Issue	Description of Change	Date of Issue
1	First Issue	31 August 2021
2	Added Pictures; Added Antenna Information	03 December 2021

1.2 Introduction

Applicant	Dan Hepka
Manufacturer	Invue Security Products, Inc
Applicant's Email Address	DanHepka@invue.com
Model Number(s)	IR3Key
Serial Number(s)	n/a
Number of Samples Tested	1
Test Specification/Issue/Date	LP0002, Updated July 2020
Order Number	72170636
SABS UIN	002554
Date of Receipt of EUT	02 July 2021
Start of Test	10 AUG 2021
Finish of Test	26 AUG 2021
Related Document(s)	n/a



1.3 Summary of Results

A summary of the tests carried out in accordance with the specifications shown below.

Table 1.3-1 – Summary of Results

Section	LP0002 Clause	Test Description	Accreditation	Base Standard
2.1	3.6	Radiated Disturbance	A2LA	ANSI C63.10-2013

Table 1.3-2 – Test Accreditation

Test Name	Name of Tester(s)	Results / Comments
Radiated Emissions	Franklin Rose	Pass



1.4 Product Information

1.4.1 Technical Description

The Equipment Under Test (EUT) was a IR Key for the IR3 System. A full description and detailed product specification details are available from the manufacturer.

Test Arrangement (Client & Source, Client w/ artificial Source, Source w/ Load)	Client & Source
WPT Frequency (kHz)	127 kHz
WPT Intended Distance (cm)	0 cm
EUT Utilizes RF Data Communication in addition to WPT	No
EUT Utilizes Modulation Communication within WPT function	No
EUT Incorporates another Wireless Device	No
Additional Wireless Device is located in Source or Client	n/a

WPT Source-Specific

WPT Number of Inductive areas	1
WPT Number of Clients	1
WPT Client(s) Position (Fixed or Variable)	Fixed

LP0002-Specific

Frequency Classification	Section 3 "Test Item and Criteria -General requirements"
WPT Role	WPT Source
EUT is subject to another LP0002 Clause	No

Antenna Information

Antenna Brand	InVue
Antenna Model	IR3 Coil
Antenna Type	Coil
Antenna Gain	0.0 dBi

Top View




Photo 1.4-1 – Top View of the PCB

Bottom View




Photo 1.4-2 – Bottom View of the PCB

Side View




Photo 1.4-3 – Right Side View of the PCB

Side View




Photo 1.4-4 – Left Side View of the PCB

Top View



Photo 1.4-5 – Top View of the EUT

Bottom View




Photo 1.4-6 – Bottom View of the EUT

Side View



Photo 1.4-7 – Left Side View of the EUT

Side View



Photo 1.4-8 – Right Side View of the EUT

**Table 1.4-1 – Cable Descriptions**

Cable/Port	Description
DC leads	10 cm DC leads installed for testing

Table 1.4-2 – Support Equipment Descriptions

Make/Model	Description
WPT Client / Representative Load	Security Key Lock (for loading EUT during WPT)

1.4.2 Modes of Operation

The tested mode of operation was continuous operation.

1.5 Deviations from the Standard

No deviations from the applicable test standard were made during testing.

1.6 EUT Modification Record

The table below details modifications made to the EUT during the test program. The modifications incorporated during each test are recorded on the appropriate test pages.

Table 1.6-1 – Modification Record

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
0	Initial State		

1.7 Test Location

TÜV SÜD conducted the following tests at our New Brighton, MN Test Laboratory.

Office address:

TÜV SÜD America
141 14th Street NW
New Brighton, MN 55112 USA



2 Test Details

2.1 Radiated Emissions

2.1.1 Specification Reference

LP0002 3.6

2.1.2 Equipment Under Test and Modification State

As shown in §1.4 with modification state “0”, as noted in §1.6.

2.1.3 Test Voltage / Frequency

3.9 V DC, < 1 A

2.1.4 Date of Test

26 August 2021

2.1.5 Test Method

The EUT was set up in a semi-anechoic chamber on a remotely controlled turntable and placed on a non-conductive support 0.8 m above a reference ground plane using a measurement distance of 3m.

A pre-scan of the EUT emissions profile was made while varying the antennae-to-EUT azimuth and antennae-to-EUT polarization using a peak detector. Using the pre-scan list of the highest emissions detected, their bearing and associated antenna polarization, the EUT was then formally measured using an Average detector. The readings were maximized by adjusting the antenna height, polarization and turntable azimuth, in accordance with the specification.

Measurements were extrapolated to their respective limit distance(s) using the formulae found in LP0002.

2.1.6 Environmental Conditions

The EUT was evaluated within the climatic range of the EUT as specified by the manufacturer. When the manufacturer does not specify climatic parameters for the EUT, all tests are performed within the ambient climatic conditions of the laboratory.



2.1.7 Additional Observations

The frequency range investigated was determined in accordance with LP0002. Emissions > 20 dB were not recorded.

Measurements were done using BAT-EMC (v3.18) automated software. Reported level is the actual level with all the correction factors factored in. Correction Factor column is for informational purposes only.

2.1.8 Sample Computation (Radiated Emissions)

Measuring equipment raw measurement (dB μ V) @ 30 MHz			20.0
Correction Factor (dB/m)	Cable 2	0.24	18.94
	TEM00011 (antenna)	18.70	
Reported Quasi-peak Final Measurement (dB μ V/m) @ 30 MHz			38.94

2.1.9 Test Results

Test Summary: EUT operated as intended before, during, and after testing.

Test Result: Pass

NOTE: In accordance with other methods of measurement used for this test, testing was carried out at 3m with extrapolation factor added to the entire measurement range (9 kHz – 30 MHz) to 300m. Because measurements were extrapolated to 300m, the limits of LP0002 were also extrapolated to 300m in the range where they are specified at 30m. Therefore, both the measurement and the limit have been extrapolated to the same distance of 300 m.


See data below for detailed results.



Spurious 9kHz - 30M, EUT X-Axis

Frequency Range	Polarity	Antenna Distance	RBW	Step Size	Sweep Time
9kHz- 150kHz	Vertical	3m	200Hz	18001Pts	Auto
150kHz- 30MHz	Vertical	3m	9kHz	18001Pts	Auto

— Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Average/3.0m/
 — Taiwan LP0002 General Field Strength Limits, @ 300m 300m - QPeak/3.0m/
 — Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Peak/3.0m/
 — Meas.Peak (Vertical)
 ◆ Average (Average) (Vertical)



08/26/2021 11:46

Limit:
FCC 18 misc non-ISM <500 W

Test Results:
Pass


Test Notes: No emissions within 20 dB of the limit.

Figure 2.1-1 – Graphical Results – 9 kHz to 30 MHz – Vertical Polarity



Spurious 9kHz - 30M, EUT X-Axis

— Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Average/3.0m/
— Taiwan LP0002 General Field Strength Limits, @ 300m 300m - QPeak/3.0m/
— Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Peak/3.0m/
— Meas.Peak (Vertical)



Limit:
FCC 18 misc non-ISM <500 W

Test Results:
Pass

Test Notes: No emissions within 20 dB of the limit.


Figure 2.1-2 – Graphical Results – 9 kHz to 30 MHz – Horizontal Polarity



Spurious 9kHz - 30M, EUT Y-Axis

Frequency Range	Polarity	Antenna Distance	RBW	Step Size	Sweep Time
9kHz- 150kHz	Vertical	3m	200Hz	18001Pts	Auto
150kHz- 30MHz	Vertical	3m	9kHz	18001Pts	Auto

— Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Average/3.0m/
 — Taiwan LP0002 General Field Strength Limits, @ 300m 300m - QPeak/3.0m/
 — Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Peak/3.0m/
 — Meas.Peak (Vertical)
 ◆ Average (Average) (Vertical)



Limit:
FCC 18 misc non-ISM <500 W


Test Results:
Pass

Test Notes: No emissions within 20 dB of the limit.

Figure 2.1-3 – Graphical Results – 9 kHz to 30 MHz – Vertical Polarity



Spurious 9kHz - 30M, EUT Y-Axis



Limit:
FCC 18 misc non-ISM <500 W

Test Results:
Pass

Test Notes: No emissions within 20 dB of the limit.


Figure 2.1-4 – Graphical Results – 9 kHz to 30 MHz – Horizontal Polarity



Spurious 9kHz - 30M, EUT Z-Axis

Frequency Range	Polarity	Antenna Distance	RBW	Step Size	Sweep Time
9kHz- 150kHz	Vertical	3m	200Hz	18001Pts	Auto
150kHz- 30MHz	Vertical	3m	9kHz	18001Pts	Auto

— Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Average/3.0m/
 — Taiwan LP0002 General Field Strength Limits, @ 300m 300m - QPeak/3.0m/
 — Taiwan LP0002 General Field Strength Limits, @ 300m 300m - Peak/3.0m/
 — Meas.Peak (Vertical)
 ◆ Average (Average) (Vertical)



08/26/2021 13:01

Limit:
FCC 18 misc non-ISM <500 W


Test Results:
Pass

Test Notes: No emissions within 20 dB of the limit.

Figure 2.1-5 – Graphical Results – 9 kHz to 30 MHz – Vertical Polarity



Spurious 9kHz - 30M, EUT Z-Axis



Limit:
FCC 18 misc non-ISM <500 W

Test Results:
Pass

Test Notes: No emissions within 20 dB of the limit.

Figure 2.1-6 – Graphical Results – 9 kHz to 30 MHz – Horizontal Polarity

2.1.10 Radiated Emissions Test Set-up Photos




Photo 2.1-1 – Front View of the Test Setup up to 1 GHz




Photo 2.1-2 – Rear View of the Test Setup up to 1 GHz



2.1.11 Test Location and Test Equipment Used

The tests were carried out in New Brighton, MN.

Test Area: 3mSAC

Table 2.1-1 – Radiated Emissions Equipment List

Device #	Manufacturer	Description	Model	Serial #	Cal Code	Cal Date	Cal Due
WRLE02418	EMCO/EMC Test	Antenna, Loop	6502	2215	G	11/10/2020	11/10/2022
NBLE11555	Rohde & Schwarz	Receiver, 2 Hz-44 GHz	ESW44	101537	G	12/31/2020	12/31/2021

Cal Code G = Calibration performed by an accredited outside source.

Cal Code B = Calibration verification performed internally.

Cal Code Y = Passive Device, or Calibration not required when used with other calibrated equipment.

3 Diagram of Test Set-ups




Figure 3-1 – Radiated Emissions Test Setup up to 1 GHz – Tabletop



4 Accreditation, Disclaimers and Copyright

TÜV SÜD America Inc.'s reports apply only to the specific sample tested under stated test conditions. It is the manufacturer's responsibility to assure the continued compliance of production units of this model. TÜV SÜD America, Inc. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD America, Inc.'s issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and TÜV SÜD America, Inc., extracts from the test report shall not be reproduced, except in full without TÜV SÜD America, Inc.'s written approval.

This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the federal government.

STATEMENT OF MEASUREMENT UNCERTAINTY – Emissions

The test system for conducted emissions is defined as the LISN, tuned receiver or spectrum analyzer, and coaxial cable. This test system has a measurement uncertainty of ± 3.30 dB. The test system for radiated emissions is defined as the antenna, the pre-amplifier, the spectrum analyzer and the coaxial cable. This test system for 30 MHz-1000 MHz has a measurement uncertainty of ± 5.88 dB and above 1 GHz a measurement uncertainty of ± 4.47 dB. The measurement uncertainty values for conducted and radiated emissions meet the requirements as expressed in CISPR 16-4-2. The equipment comprising the test systems is calibrated on an annual basis.

TEST EQUIPMENT

All measurement instrumentation is traceable to the National Institute of Standards and Technology and is calibrated to meet test method standard requirements and/or manufacturer's specifications.