



JAPAN RADIO TEST REPORT

Client Information:

Applicant: Lazuli LLC
Applicant add.: Shibuya Dogenzaka Tokyu Building 2F-C1-10-8 Dogenzaka, Shibuya-ku
Tokyo Japan 150-0043

Product Information:

Product Name: Wireless Speaker
Model No.: ZNY20
Derivative model No.: N/A
Brand Name: ZEENY
Report No.: CTT2026071002R21T-01

Standards: Item 19 of Article 2 Paragraph 1

Prepared By:

Shenzhen C-link Testing & Technology Co., Ltd.

Add.: No.709, Enhai Building, No.1 Hangkong Road, Sanwei Community, Hangcheng Street,
Bao'an District, Shenzhen, Guangdong, China

Date of Receipt: Jul. 10, 2026

Date of Test: Jul. 10, 2026~ Jul. 24, 2026

Date of Issue: Jul. 24, 2026

Test Result: Pass

This device has been tested and found to comply with the stated standard(s) above, which is (are) applicable only to the tested sample identified in the report.

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen C-link Testing & Technology Co., Ltd. this document may be altered or revised by Shenzhen C-link Testing & Technology Co., Ltd. personal only, and shall be noted in the revision of the document. This test report must not be used by the client to claim product endorsement.

Reviewed by:

Mary Ye



Approved by:

Brown Lu



1 Contents

1	CONTENTS	2
2	TEST SUMMARY.....	3
2.1	Measurement Uncertainty	3
3	GENERAL INFORMATION.....	5
3.1	Test Location	6
3.2	EUT Peripheral List	6
3.3	Test Peripheral List.....	6
4	EQUIPMENT USED DURING TEST.....	6
5	TEST RESULTS.....	7
5.1	Radio Technical Requirements Specification.....	7
5.2	E.U.T. Test Conditions	8
5.3	Antenna Requirement.....	10
5.4	Interference Prevention Function	11
5.5	Frequency Error	12
5.6	Occupied Bandwidth (99%)	16
5.7	Spread Spectrum Bandwidth (90%).....	20
5.8	Antenna Power	24
5.9	Spurious Emissions of Tx.....	26
5.10	Dwell Time.....	52
5.11	Pseudorandom Frequency Hopping Sequence	59
5.12	RF Accessibility	60
5.13	Spurious Emissions of Rx	61
6	PHOTOGRAPHS	66
6.1	EUT TEST PHOTO	66



2 Test Summary

TEST	TEST REQUIREMENT	LIMIT/SEVERITY	RESULT
Antenna Requirement	Item 19 of Article 2-1	Notice 88 Appendix 43,B-1 (1)&(2)	PASS
Test frequency	Item 19 of Article 2-1	Notice 88 Appendix 43, A-3	PASS
Frequency Error	Item 19 of Article 2-1	±50 PPM or less	PASS
Occupied Bandwidth	Item 19 of Article 2-1	83.5 MHz or less	PASS
Spread-spectrum Bandwidth	Item 19 of Article 2-1	Only for reported	PASS
Antenna Power	Item 19 of Article 2-1	3 mW /MHz or less Error + 20%; 10mW Error + 20%	PASS
Spurious Emission of Tx	Item 19 of Article 2-1	(1) Below 2387 MHz : -26dBm/MHz (2) 2387 to 2400 MHz : -16dBm/MHz (3) 2483.5 through 2496.5 MHz : -16dBm/MHz (4) Over 2496.5 MHz : -26dBm/MHz	PASS
Dwell Time	Item 19 of Article 2-1	less than 0.4sec	PASS
Interference prevention capability	Item 19 of Article 2-1	Notice 88 Appendix 43	PASS
RF accessibility	Item 19 of Article 2-1	Notice 88 Appendix 43	PASS
Spurious Emission of Rx	Item 19 of Article 2-1	(1) Below 1 GHz: -54dBm (2) 1GHz or higher: -47dBm	PASS
Carrier sense function	Item 19 of Article 2-1	/	N/A, Note2

Remark:

Note 1:EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

Note 2: Not apply to this device of FHSS

2.1 Measurement Uncertainty

The report uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

No.	Item	Uncertainty
1	Frequency Error / 99% & 90% Bandwidth	$\pm 0.85 \times 10^{-7}$
2	Antenna Power	± 0.70 dB



3	Spurious Emissions	± 0.80 dB
4	DC / AC Power Source	$\pm 1.4\%$



3 General Information

Manufacturer:	Lazuli LLC
Manufacturer Address:	Shibuya Dogenzaka Tokyu Building 2F-C1-10-8 Dogenzaka, Shibuya-ku Tokyo Japan 150-0043
Product Name:	Wireless Speaker
Model No.:	ZNY20
Brand Name:	ZEENY
Derivative model No.:	N/A
Sample ID:	260710002-01
Sample(s) Quantity:	1
Operating Frequency	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, ($\pi/4$)DQPSK, 8DPSK
Number of Channels	79 Channels (for FHSS)
Channel Separation:	1 MHz (for FHSS)
Dwell time	Per channel is less than 0.4s.
Antenna Type	PCB Antenna
Antenna gain:	0dBi
Normal antenna power:	FHSS: F1D:0.5mW/MHz, G1D: 0.5mW/MHz
Bluetooth version:	Bluetooth 5.3
Power Supply Range:	INPUT: DC5V DC 7.4V from battery
Normal Test Voltage:	The same as above
Hard Ware Version:	V1.0
Soft Ware Version:	V1.0
Model difference:	N/A



3.1 Test Location

Shenzhen C-link Testing & Technology Co., Ltd.

No.709, Enhai Building, No.1 Hangkong Road, Sanwei Community, Hangcheng Street, Bao 'an District, Shenzhen, Guangdong, China

3.2 EUT Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	Signal cord
1	N/A	N/A	N/A	N/A	N/A	N/A

3.3 Test Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	Signal cord
1	Computer	Lenovo	N/A	TP00076A	N/A	N/A	N/A
2	USB Line	UGREEN	N/A	USB3.0	N/A	N/A	N/A

4 Equipment Used during Test

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date	Cal. Lab
1	SIGNAL Analyzer	Keysight	N9020A	MY533004 66	2026.01.16	2027.01.15	Guangzhou Lisai Metrology & Test Co. Ltd.
2	RF Automatic Test System	MWRFTest	MV1 00-RFCB	/	2026.01.16	2027.01.15	

Remark:

(a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) in Japan (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1) in JRL.

(b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Act (Act No. 51 of 1992).

(c) Calibration conducted in countries except Japan, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).

(d) Calibration, etc. conducted by using measuring instruments and other equipment listed in the right column of appended table No. 3, which shall have been given any type of calibration, etc. listed above from (a) to (C)

From JRL Article 24-2, paragraph 4, Item 2

Note: The testing equipment is calibrated using the C method.

5 Test Results

5.1 Radio Technical Requirements Specification


Table 1: Radio Technical Requirements Specification for 2.4 GHz band wide-band low-power data communication system (Item 19 of Article 2-1)

Items	Technical standard
Assigned frequency or designated frequency	2,400-2,483.5MHz
Communication method	One-way communication, simplex, semi-duplex, or duplex operation of digital signal transmission including spread spectrum
Tolerance of frequency ($\times 10^{-6}$)	± 50
Tolerance of occupied bandwidth	FH : 83.5MHz or less FH + DS : 83.5MHz or less FH + OFDM : 83.5MHz or less OFDM : 40MHz or less Others : 26MHz or less
Antenna power	Designated value (1) FH, FH+DS , FH+OFDM: 3mW/MHz (used in the range of 2400 – 2483.5 MHz) (2) OFDM , DS other than (1) 10mW/MHz (3) Other than (1) & (2) 10mW (4) OFDM OBW 26 - 40MHz: 5mW/MHz Tolerance:+20%
Antenna gain	1) 12.14 dBi or less in principle 2) In case of directional antenna (1) FH, FH+DS or FH+OFDM using 2400 – 2483.5 MHz EIRP $\leq$ 16.91 dBm/MHz (2) OFDM or DS other than (1) EIRP $\leq$ 22.14 dBm/MHz (3) Other than (1) and (2): 22.14 dBm or less (4) OFDM OBW 26 - 40MHz: 19.14dBm/MHz (5) Half-power angle of directional antenna (e) in case of the item 2): $e \leq 360/A$ (The A is 10 in maximum.)
Tolerance of spurious emission intensity	(1) Below 2387 MHz : 2.5 μ W/MHz (2) 2387 to 2400 MHz : 25 μ W/MHz (3) 2483.5 through 2496.5 MHz : 25 μ W/MHz (4) Over 2496.5 MHz : 2.5 μ W/MHz
Spreading bandwidth	Only for reported
Limit of secondary radiated emissions	(1) Below 1 GHz : 4 nW (2) 1 GHz or higher : 20 nW
Interference prevention function	Shall have the function of automatic transmission and reception of identification sign.
Structure	Shall be of the structure that the RF and modulator sections excluding antenna cannot easily be opened.
Note	DS: Direct spread FH: Frequency hopping OFDM: Orthogonal frequency division multiplexing

5.2 E.U.T. Test Conditions

Power supply:

The EUT has the input voltage to the circuit of RF unit complies with output voltage limitation ($\pm 1\%$) against input voltage fluctuation ($\pm 10\%$). So, all measurements were conducted at only rated voltage DC 7.4V.



Test below:

1: The fluctuation of C point is under $\pm 1\%$, when input voltage from A point to the test equipment is fluctuated by $\pm 10\%$.

The measurement result of the voltage fluctuation at RF circuit when DC 7.4V $\pm 10\%$

DC 7.4V	DC3V3
7.4V	3V3
8.14V	3V3
6.66V	3V3

Pre-test the EUT in all voltage mode at the DC 8.14V, DC 7.4V and DC 6.66V and conducted to determine the worst-case mode, only the worst-case results (DC 7.4V) are recorded in this report.

The EUT has the input voltage to the circuit of RF unit complies with output voltage limitation ($\pm 1\%$) against input voltage fluctuation ($\pm 10\%$). So, all measurements were conducted at only rated voltage DC 7.4V.

Temperature:

5.0 -35.0 °C

Humidity:

45-85 % RH

Atmospheric Pressure:

1000 -1020 mbar

Test frequencies:

If the EUT can be set to 3 or more different (carrier) frequencies in 1 allocated band, testing shall be performed using the Lowest, Middle and the Highest frequency (L, M and H). If there are 2 or fewer frequencies, testing shall be performed with the available frequencies.

**EUT channels and frequencies list:****For FHSS:**

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454	/	/
26	2428	53	2455	/	/

Test frequencies are the lowest channel: 0 channel(2402 MHz), middle channel: 39 channel(2441 MHz) and highest channel: 78 channel(2480 MHz)


5.3 Antenna Requirement

Standard requirement

Applicable for equipment with an antenna terminal, including testing terminals) If an antenna connector is available, all relevant tests will be carried out conducted. If not, tests will be carried out in an anechoic room or with a suitable test-fixture.

EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi



Antenna

Result: All relevant tests will be carried out conducted.

5.4 Interference Prevention Function

LIMIT

Item	Limits
Identification code	≥ 48 bits


MEASURING ID CODE SOFTWARE

Item	Limits
MAC IP List	MAC Scan

TEST PROCEDURES

- In the case that the EUT has the function of automatically transmitting the identification code:
 - Transmit the predetermined identification codes form EUT.
 - Check the transmitted identification codes with the demodulator.
- In the case of receiving the identification ocde:
 - Transmit thepredetermined identification codes form the counterpart.
 - . Check if communicationis normal.
 - Transmit the signals other than predetermined ID codes form the counterpart.
 - check if the EUT stops the transmission, or if it displays that idnetification codes are different from the predetermined ones.

TEST SETUP LAYOUT



TEST DEVIATION

There is no deviation with the original standard.

EUT OPERATION DURING TEST

The EUT was programmed to be in normal transmitting mode.


TEST RESULT OF RADIO INTERFERENCE PREVENTION CAPABILIT

EUT:	Bluetooth wireless earphones	Test Date:	2026/07/16
Temperature:	25 ⁰ C	Tested by:	Renny
Humidity:	55 % RH	Test result:	CONFORM
Atmospheric Pressure:	1013 mbar		

MAC Address: 44: A3: C5: DE:1B: 00

5.5 Frequency Error

Test Requirement:	Item 19 of Article 2-1
	Tolerance of frequency: $\pm 50 \times 10^{-6}$
Temperature:	23.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1013 mbar
Test Status:	Test the EUT in transmitting mode without modulation.
Test Configuration:	



Test Procedure:

1. Test Conditions:

Frequency Counter or Spectrum Analyzer is used for measurement.

2. EUT conditions:

Modulation/Spread/Hopping OFF, CW Tx

3. Spectrum Analyzer conditions:

Frequency: Test Frequency

Span 1MHz

RBW 10 kHz (Modulation OFF for FHSS; Modulation ON for DSSS),

VBW 30 kHz (Modulation OFF for FHSS; Modulation ON for DSSS),

Sweep Time Auto

Detector mode Positive peak

Indication mode Max hold



Test result:
For FHSS:


Test channel	Test Frequency (MHz)	Test Result			Unit	Limit
		Normal Voltage	High Voltage	Low Voltage		
		7.4V DC	8.14V DC	6.66V DC		
Lowest	2402.0	2402.022	N/A	N/A	MHz	±50 PPM or less
		+9.16	N/A	N/A	PPM	
Middle	2441.0	2441.022	N/A	N/A	MHz	
		+9.01	N/A	N/A	PPM	
Highest	2480.0	2480.024	N/A	N/A	MHz	
		+9.68	N/A	N/A	PPM	

Note: The nominal frequency shall be confirmed by the applicant and test lab.


Result plot as follows:

For FHSS:


Channel 0: 2.402 GHz:



Channel 39: 2.441 GHz:



Channel 78: 2.480 GHz




Test result: The unit does meet the requirements.

5.6 Occupied Bandwidth (99%)

Test Requirement:	Item 19 of Article 2-1 83.5MHz or less(FHSS)
Temperature:	23.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1013 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Test Conditions:
Spectrum Analyzer is used for measurement.
2. EUT conditions:
Modulation/Spread/Hopping ON, PC Modulation Tx
For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.
3. Spectrum Analyzer conditions:
Frequency: Test Frequency
Span: 83.5 MHz(FHSS), 5MHz(DSSS)
RBW: 1 MHz(FHSS), 300 kHz(DSSS)
VBW: 1 MHz(FHSS), 300 kHz(DSSS)
Sweep Time Auto
detector mode Positive peak
Indication mode Max hold
OBW 99%

Test result:
For FHSS:

BR mode (GFSK):

Test channels	Test Result			Unit	Limit
	Normal Voltage	High Voltage	Low Voltage		
	7.4V DC	8.14V DC	6.66V DC		
79 channels (2402~2480 MHz)	78.697	N/A	N/A	MHz	83.5 MHz or less

EDR mode ($\pi/4$)DQPSK


Test channels	Test Result			Unit	Limit
	Normal Voltage	High Voltage	Low Voltage		
	7.4V DC	8.14V DC	6.66V DC		
79 channels (2402~2480 MHz)	78.703	N/A	N/A	MHz	83.5 MHz or less

EDR mode (8DPSK):


Test channels	Test Result			Unit	Limit
	Normal Voltage	High Voltage	Low Voltage		
	7.4V DC	8.14V DC	6.66V DC		
79 channels (2402~2480 MHz)	78.686	N/A	N/A	MHz	83.5 MHz or less

Result plot as follows:


For FHSS:BDR mode (GFSK):



EDR mode ($\pi/4$)DQPSK:



EDR mode (8DPSK):



Test result: The unit does meet the requirements.

5.7 Spread Spectrum Bandwidth (90%)

Test Requirement:	Item 19 of Article 2-1
Temperature:	23.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1013 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Test Conditions:
Spectrum Analyzer is used for measurement.
2. EUT conditions:
Modulation/Spread/Hopping ON, PC Modulation Tx
For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.
3. Spectrum Analyzer conditions:
Frequency: Test Frequency
Span: 83.5 MHz(FHSS), 5MHz(DSSS)
RBW: 1 MHz(FHSS), 300 kHz(DSSS)
VBW: 1 MHz(FHSS), 300 kHz(DSSS)
Sweep Time Auto
detector mode Positive peak
Indication mode Max hold
OBW 90%

**Test result:****For FHSS:**

BDR mode (GFSK):

Test channels	Test Result (MHz)
	Normal Voltage
	7.4V DC
79 channels (2402~2480 MHz)	71.494

EDR mode ($\pi/4$)DQPSK:


Test channels	Test Result (MHz)
	Normal Voltage
	7.4V DC
79 channels (2402~2480 MHz)	71.653

EDR mode (8DPSK):


Test channels	Test Result (MHz)
	Normal Voltage
	7.4V DC
79 channels (2402~2480 MHz)	71.507

Result plot as follows:


For FHSS:BDR mode (GFSK):



For FHSS: EDR mode ($\pi/4$)DQPSK:



For FHSS: EDR mode (8DPSK):



Test result: The unit does meet the requirements.

5.8 Antenna Power

Test Requirement:	Item 19 of Article 2-1 3 mW/MHz or less(FHSS)
Temperature:	23.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1013 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

The EUT was directly connected to the RF Automatic Test System and antenna output port as show in the block diagram above.

**Test result:****For FHSS:**

Frequency MHz	Total power (dBm)	Total Power (mW)	SBW MHz	Antenna Power (mW/MHz)	Rated output Power (mW/MHz)	Antenna Power (mW/MHz)	Antenna Power Tolerance(%)	
						Limit	Result	Limit
GFSK(1Mbps)								
2402-2480 DH5	15.256	33.543	71.494	0.469	0.5	3	-6.2%	+20%
π/4/DQPSK(2Mbps)								
2402-2480 2DH5	14.338	27.152	71.653	0.379	0.5	3	-24.2%	+20%
8DPSK (3Mbps)								
2402-2480 3DH5	14.894	30.860	71.507	0.432	0.5	3	-13.6%	+20%

Antenna Power= Total power /spread bandwidth

Normal antenna power: BR&EDR: F1D:0.5mW/MHz, G1D:0.5 mW/MHz

5.9 Spurious Emissions of Tx

Test Requirement:	Item 19 of Article 2-1
	(1) 30 to 1000 MHz : 2.5μW/MHz(-36dBm/100kHz)
	(2) 1000 to 2387 MHz : 2.5μW/MHz(-26dBm/MHz)
	(3) 2387 to 2400 MHz : 25μW/MHz(-16dBm/MHz)
	(4) 2483.5 through 2496.5 MHz : 25μW/MHz(-16dBm/MHz)
	(5) Over 2496.5 MHz : 2.5μW/MHz(-26dBm/MHz)
Temperature:	23.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1013 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

- Test Conditions:
Spectrum Analyzer is used for measurement.
- EUT conditions:
Modulation/Spread/Hopping ON, , PC Modulation Tx
For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.
- Spectrum Analyzer conditions:
Step 1
All spurious are measured from 30 MHz to 13 GHz by peak mode.
Step 2
IF the value measured by Step1 is 2 dB or less, measure in average mode.
Test setup for Step 1:
Frequency: 30 MHz – 1000 MHz,
RBW 100 kHz (Below 1000 MHz), VBW 100 kHz (Below 1000 MHz)
1000 MHz – 2400 MHz, 2483.5 MHz –13 GHz
RBW 1 MHz (above 1000 MHz), VBW 1 MHz (above 1000 MHz)
Sweep Time Auto
detector mode Positive peak, Indication mode Max hold
Test setup for Step 2:
Frequency: Spurious Frequency
RBW 100 kHz (Below 1000 MHz), VBW 100 kHz (Below 1000 MHz)
RBW 1 MHz (above 1000 MHz), VBW 1 MHz (above 1000 MHz)
Sweep Time Auto,
Detector mode Sample, Indication mode Max hold



Test result:


Condition	Mode	Frequen cy (MHz)	Range (MHz)	Emission Frequenc y (MHz)	Max Value (dBm/MHz)	Max Value (uW/MHz)	Limit Start(u W/MHz)	Limit Stop (uW/MHz)	Verdict
NVNT	1-DH1	2402	30-1000	121.18	-51.89	0.0065	2.5	2.5	Pass
NVNT	1-DH1	2402	1000-2387	2355.1	-57.15	0.0019	2.5	2.5	Pass
NVNT	1-DH1	2402	2387-2400	2400	-40.84	0.0824	25	25	Pass
NVNT	1-DH1	2402	2483.5-249 6.5	2488.32	-58.05	0.0016	25	25	Pass
NVNT	1-DH1	2402	2496.5-130 00	4807.27	-44.14	0.0385	2.5	2.5	Pass
NVNT	1-DH1	2441	30-1000	121.18	-56.7	0.0021	2.5	2.5	Pass
NVNT	1-DH1	2441	1000-2387	2122.08	-58.03	0.0016	2.5	2.5	Pass
NVNT	1-DH1	2441	2387-2400	2393.32	-57.62	0.0017	25	25	Pass
NVNT	1-DH1	2441	2483.5-249 6.5	2489.03	-57.69	0.0017	25	25	Pass
NVNT	1-DH1	2441	2496.5-130 00	4880.79	-45.31	0.0294	2.5	2.5	Pass
NVNT	1-DH1	2480	30-1000	121.18	-51.48	0.0071	2.5	2.5	Pass
NVNT	1-DH1	2480	1000-2387	2123.47	-56.96	0.002	2.5	2.5	Pass
NVNT	1-DH1	2480	2387-2400	2387.03	-57.64	0.0017	25	25	Pass
NVNT	1-DH1	2480	2483.5-249 6.5	2483.59	-50.79	0.0083	25	25	Pass
NVNT	1-DH1	2480	2496.5-130 00	4964.82	-46.1	0.0245	2.5	2.5	Pass
NVNT	2-DH1	2402	30-1000	121.18	-52.19	0.006	2.5	2.5	Pass
NVNT	2-DH1	2402	1000-2387	2134.57	-57.22	0.0019	2.5	2.5	Pass
NVNT	2-DH1	2402	2387-2400	2399.99	-35.41	0.2877	25	25	Pass
NVNT	2-DH1	2402	2483.5-249 6.5	2495.99	-58.02	0.0016	25	25	Pass
NVNT	2-DH1	2402	2496.5-130 00	4807.27	-45.25	0.0299	2.5	2.5	Pass
NVNT	2-DH1	2441	30-1000	48.43	-57.94	0.0016	2.5	2.5	Pass
NVNT	2-DH1	2441	1000-2387	2120.7	-56.8	0.0021	2.5	2.5	Pass
NVNT	2-DH1	2441	2387-2400	2393.3	-57.79	0.0017	25	25	Pass
NVNT	2-DH1	2441	2483.5-249 6.5	2487.86	-58.04	0.0016	25	25	Pass
NVNT	2-DH1	2441	2496.5-130 00	4880.79	-45.09	0.031	2.5	2.5	Pass
NVNT	2-DH1	2480	30-1000	121.18	-57.56	0.0018	2.5	2.5	Pass
NVNT	2-DH1	2480	1000-2387	2133.18	-57.35	0.0018	2.5	2.5	Pass
NVNT	2-DH1	2480	2387-2400	2387.7	-58.29	0.0015	25	25	Pass
NVNT	2-DH1	2480	2483.5-249 6.5	2483.63	-48.99	0.0126	25	25	Pass
NVNT	2-DH1	2480	2496.5-130	4964.82	-46.08	0.0247	2.5	2.5	Pass




			00						
NVNT	3-DH1	2402	30-1000	120.21	-52.99	0.005	2.5	2.5	Pass
NVNT	3-DH1	2402	1000-2387	2112.37	-57.17	0.0019	2.5	2.5	Pass
NVNT	3-DH1	2402	2387-2400	2399.95	-36.22	0.2388	25	25	Pass
NVNT	3-DH1	2402	2483.5-249 6.5	2485.5	-58.22	0.0015	25	25	Pass
NVNT	3-DH1	2402	2496.5-130 00	4807.27	-44.07	0.0392	2.5	2.5	Pass
NVNT	3-DH1	2441	30-1000	121.18	-52.26	0.0059	2.5	2.5	Pass
NVNT	3-DH1	2441	1000-2387	2123.47	-57.78	0.0017	2.5	2.5	Pass
NVNT	3-DH1	2441	2387-2400	2392.64	-58.19	0.0015	25	25	Pass
NVNT	3-DH1	2441	2483.5-249 6.5	2488.95	-57.76	0.0017	25	25	Pass
NVNT	3-DH1	2441	2496.5-130 00	4880.79	-44.81	0.033	2.5	2.5	Pass
NVNT	3-DH1	2480	30-1000	121.18	-51.62	0.0069	2.5	2.5	Pass
NVNT	3-DH1	2480	1000-2387	2126.24	-57.47	0.0018	2.5	2.5	Pass
NVNT	3-DH1	2480	2387-2400	2394.18	-57.77	0.0017	25	25	Pass
NVNT	3-DH1	2480	2483.5-249 6.5	2483.63	-48.12	0.0154	25	25	Pass
NVNT	3-DH1	2480	2496.5-130 00	4964.82	-46.31	0.0234	2.5	2.5	Pass

Test Graphs


Tx. Spurious NVNT 1-DH1 2402MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 1-DH1 2402MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 1-DH1 2402MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 1-DH1 2402MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 1-DH1 2402MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 1-DH1 2441MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 1-DH1 2480MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 2-DH1 2402MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 2-DH1 2480MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 3-DH1 2402MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 @ 2387MHz-2400MHz




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 @ 2483.5MHz-2496.5MHz




Tx. Spurious NVNT 3-DH1 2441MHz Ant1 @ 2496.5MHz-13000MHz




Tx. Spurious NVNT 3-DH1 2480MHz Ant1 @ 30MHz-1000MHz




Tx. Spurious NVNT 3-DH1 2480MHz Ant1 @ 1000MHz-2387MHz




Tx. Spurious NVNT 3-DH1 2480MHz Ant1 @ 2387MHz-2400MHz



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 @ 2483.5MHz-2496.5MHz






5.10 Dwell Time

Test Requirement:	Item 19 of Article 2-1 less than 0.4sec
Temperature:	23.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1013 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below. Modulation/Spread/Hopping ON, Hopping frequency is fixed, Bluetooth equipment is setting DH5 mode

Test Configuration:



Test Procedure:

1. Test Conditions:
Spectrum Analyzer is used for measurement.
2. EUT conditions:
Modulation/Spread/Hopping ON, Hopping frequency is fixed, Bluetooth equipment is setting DH5 mode
For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.
3. Spectrum Analyzer conditions:
Frequency: Test Frequency (fixed hopping frequency)
Span 0 Hz
RBW 1 MHz
VBW 1 MHz
Sweep Time EUT condition
Trigger Video Trigger
Measures the Transmission time of 1 burst (sec)
Measures the Burst cycle (sec)
4. Calculation procedure :
$$\text{Dwell time} = (0.4(\text{s}) \times [\text{spreading rate}] \times [\text{Transmission time of 1 burst(s)}]) / ([\text{burst cycle(s)}] \times [\text{No. of hopping channel}])$$

Note:
* Spreading rate = $[\text{Spread bandwidth (actual measurement value)}] / [\text{Transmission rate}]$

Test result:

For FHSS: BDR mode (GFSK):

Test channel	Test Frequency (MHz)	Test Result			Unit	Limit
		Normal Voltage	High Voltage	Low Voltage		
		7.4V DC	N/A	N/A		
Lowest	2402.0	0.278	N/A	N/A	Sec	less than 0.4 sec
Middle	2441.0	0.277	N/A	N/A	Sec	
Highest	2480.0	0.277	N/A	N/A	Sec	

For FHSS: EDR mode ($\pi/4$)DQPSK:

Test channel	Test Frequency (MHz)	Test Result			Unit	Limit
		Normal Voltage	High Voltage	Low Voltage		
		7.4V DC	N/A	N/A		
Lowest	2402.0	0.278	N/A	N/A	Sec	less than 0.4 sec
Middle	2441.0	0.278	N/A	N/A	Sec	
Highest	2480.0	0.277	N/A	N/A	Sec	

For FHSS: EDR mode (8DPSK):

Test channel	Test Frequency (MHz)	Test Result			Unit	Limit
		Normal Voltage	High Voltage	Low Voltage		
		7.4V DC	N/A	N/A		
Lowest	2402.0	0.276	N/A	N/A	Sec	less than 0.4 sec
Middle	2441.0	0.277	N/A	N/A	Sec	
Highest	2480.0	0.276	N/A	N/A	Sec	

Remark: Calculated method: Dwell time=(0.4(s) x [spreading rate] x [Transmission time of 1 burst(s)])/([burst cycle(s)] x [No. of hopping channel])

Note: Spreading rate=[Spread bandwidth (actual measurement value)]/[Transmission rate]

Transmission rate is 1.0 Mbps for Normal mode;

Transmission rate is 1.0 Mbps for EDR mode;


Transmission rate is 1.0 Mbps for EDR mode;

All the modes (DH1/DH3/DH5/2DH1/2DH3/2DH5/3DH1/3DH3/3DH5) have tested and recorded the worst mode(DH5/2DH5/3DH5) in the report


Result plot as follows:

BDR mode (GFSK):


Channel 0: 2.402 GHz:




Channel 39: 2.441 GHz:




Channel 78: 2.480 GHz


EDR mode ($\pi/4$)DQPSK:


Channel 0: 2.402 GHz:



Channel 39: 2.441 GHz:




Channel 78: 2.480 GHz




EDR mode (8DPSK):


Channel 0: 2.402 GHz:



Channel 39: 2.441 GHz:



Channel 78: 2.480 GHz



Test result: The unit does meet the requirements.

5.11 Pseudorandom Frequency Hopping Sequence

Standard requirement


Article 2, Item (19) Notice 88 Appendix 43, 44, 45 requirement:

The EUT shall have the capability to transmit or to receive the MAC identification automatically, so that sender and receiver shall exclude other equipment.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.


5.12 RF Accessibility

Standard requirement

Article 2, Item (19) Notice 88 Appendix 43

The EUT shall be constructed in such a way that sensitive RF parts, (like modulation and oscillator parts) cannot be reached easily by the user. These parts shall be covered by soldered metal caps or glue or by other mechanical covers. If the covers are fixed with screws, these shall be not the common type(s) like a Phillips, but special versions like Torx, so that the user cannot open the device with common tools.

The chip's pin spacing is 0.4mm and is not easy to modify, The number of pins on the chip is 32.



5.13 Spurious Emissions of Rx

Test Requirement:	Item 19 of Article 2-1 (1) Below 1 GHz : 4 nW or less(-54dBm) (2) 1 GHz and over : 20 nW or less(-47dBm)
Temperature:	23.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1013 mbar
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Test Conditions: Spectrum Analyzer is used for measurement.
2. EUT conditions:
Modulation/Spread/Hopping ON
For equipment using diffusion code, set to the test diffusion code and modulate with standard coding test signal.
3. Spectrum Analyzer conditions:
Step 1
All spurious are measured from 30 MHz to 13 GHz by peak mode.
Step 2
IF the value measured by Step1 is 2 dB or less, measure in average mode.
Test setup for Step 1:
Frequency: 30 MHz – 2400 MHz , 2483.5 MHz –13 GHz
RBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz)
VBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz)
Sweep Time Auto
detector mode Positive peak
Indication mode Max hold
Test setup for Step 2:
Frequency: Spurious Frequency
Span 0 Hz
RBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz)
VBW 100 kHz (30 – 1GHz) , 1 MHz (over 1GHz)
Sweep Time Auto
detector mode Sample
Indication mode Max hold

**Test result:**


Condition	Frequency (MHz)	Range (MHz)	Emission Frequency (MHz)	Max Value (dBm)	Max Value (nW)	Limit (nW)	Verdict
NVNT	2402	30-1000	869.05	-88.89	0.0013	4	Pass
NVNT	2402	1000-13000	11728	-75.11	0.0308	20	Pass
NVNT	2441	30-1000	775.93	-89.25	0.0012	4	Pass
NVNT	2441	1000-13000	2452	-67.6	0.1738	20	Pass
NVNT	2480	30-1000	940.83	-88.81	0.0013	4	Pass
NVNT	2480	1000-13000	2452	-70.75	0.0841	20	Pass

Note:


All the Modulation mode (GFSK, ($\pi/4$)DQPSK, 8DPSK) have tested and recorded the worst case GFSK in the report

Test Graphs


Rx. Spurious NVNT 1-DH1 2402MHz Ant1 @ 30MHz-1000MHz




Rx. Spurious NVNT 1-DH1 2402MHz Ant1 @ 1000MHz-13000MHz




Rx. Spurious NVNT 1-DH1 2441MHz Ant1 @ 30MHz-1000MHz




Rx. Spurious NVNT 1-DH1 2441MHz Ant1 @ 1000MHz-13000MHz



Rx. Spurious NVNT 1-DH1 2480MHz Ant1 @ 30MHz-1000MHz




Rx. Spurious NVNT 1-DH1 2480MHz Ant1 @ 1000MHz-13000MHz



6 Photographs

6.1 EUT TEST PHOTO



****End of report****