

Test Report

Applicant: FUZHOU XINLIN INTELLIGENT TECHNOLOGY CO., LTD.

Address: 3/F 14-3 No.756 Qi'an Road, Gaishan Town, Cangshan District,
Fuzhou, Fujian, China

Manufacturer: FUZHOU XINLIN INTELLIGENT TECHNOLOGY CO., LTD.

Address: 3/F 14-3 No.756 Qi'an Road, Gaishan Town, Cangshan District,
Fuzhou, Fujian, China

Product(s): Braille Display

Brand(s): XIN LIN ZHI NENG KE JI

Test Model(s): XL20A01KY

Series Model(s): N/A

Test Date: Jun. 11, 2026 ~ Jul. 06, 2026

Issued Date: Jul. 10, 2026

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park,
HuangJiang Town, Dongguan City, People's Republic of China

Standards: Article 2 Paragraph 1, item 19, MIC notice 88 Appendix 43

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

Nature Lee

Nature Lee

Reviewed by :



Approved by :

Scott He

Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Table of Contents

Release Control Record	4
1 Summary of Test Results.....	5
1.1 Test Instruments.....	6
1.2 Measurement Uncertainty.....	7
1.3 Modification Record	7
2 General Information.....	8
2.1 General Description of EUT.....	8
2.2 Description of test modes	9
2.2.1 Channel list of this EUT:	9
2.2.2 Test mode applicability and tested channel detail	10
2.2.3 Assembly	11
2.2.4 Applicable Standard	11
2.2.5 Antenna Specifications	11
2.3 Description of Support Units	12
2.3.1 Configuration of System under Test	12
3 Test types and results.....	13
3.1 Frequency tolerance measurement.....	13
3.1.1 Limits of frequency tolerance measurement	13
3.1.2 Test Setup.....	13
3.1.3 Deviation from Test Standard	13
3.1.4 Test Procedure	13
3.1.5 Test Results	14
3.2 Occupied bandwidth measurement (99% power bandwidth).....	19
3.2.1 Limits of occupied bandwidth measurement	19
3.2.2 Test Setup.....	19
3.2.3 Deviation of Test Standard	19
3.2.4 Test Procedure	19
3.2.5 Test Results	20
3.3 Spreading bandwidth measurement (90% power bandwidth).....	30
3.3.1 Limits of spreading bandwidth and spreading factor	30
3.3.2 Test Procedure	30
3.3.3 Deviation from Test Standard	30
3.3.4 Test Procedure	30
3.3.5 Test Results	30
3.4 Spurious emissions for transmitter measurement	40
3.4.1 Limit of Spurious emissions for transmitter measurement	40
3.4.2 Test Setup.....	40
3.4.3 Deviation from Test Standard	40
3.4.4 Test Procedure	40
3.4.5 Test Results	41
3.5 Antenna power measurement.....	79
3.5.1 Limits of antenna power	79
3.5.2 Test Setup.....	79
3.5.3 Test Procedure	79
3.5.4 Test result of conducted output power.....	80
3.6 Spurious emissions for receiver.....	81
3.6.1 Limits of spurious emissions for receiver	81
3.6.2 Test Setup.....	81
3.6.3 Deviation from Test Standard	81
3.6.4 Test Procedure	81
3.6.5 Test Results	82

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](#)

Web: [www.lyns-tci.com](#)

E-Mail: [service-hs@lyns-tci.com](#)

Release

[Ver. 1.5](#)

3.7 Interference prevention function	120
3.7.1 Limits of interference prevention function.....	120
3.7.2 Test Procedure	120
3.7.3 Test Setup.....	120
3.7.4 Test results.....	121
4 Photographs of the test configuration.....	122
Appendix – Information on the Testing Laboratories.....	123

Release Control Record

Issue No.	Description	Date Issued
26040801-RF-JP-01	Original Release	Jul. 10, 2026

1 Summary of Test Results

The EUT has been tested according to the following specifications:

Article 2 Paragraph 1, item 19	ARIB STD-T66	Report reference	Parameter	Test Results (Note)
General provisions				
C	3.2(4)	4.1	Frequency tolerance	C
D	3.2(7)	4.2	Occupied bandwidth	C
E	3.2(6)	4.4	Spurious emissions	C
Transmitting equipment				
F	3.2(1)	4.5	Antenna power	C
---	--	--	SAR	NA
Transmitting antenna				
--	--	2.25	Type, configuration, etc. of transmitting antenna	C
--	--	2.25	Direction pattern of transmitting antenna	C
Receiving equipment				
G	3.3(1)	4.6	Spurious emissions of receiver	C
--	--	2.25	Refer to all articles for transmitting antenna	C
Operating frequency 2400 to 2483.5MHz				
--	3.7(1)	3.23	High Frequency /modulation section cannot be opened easily	C
--	3.1(1)	2.1	Communication method	C
--	3.2(1)a	2.1	Modulation method	C
--	3.2(1)a	2.1	Spread spectrum method	C
--	3.2(2)	4.5	Antenna power	C
--	3.6(2)	4.5	Absolute gain of transmitting antenna	C
--	3.6(2)	4.5	Angular width of principal radiation (AWPR)	C
--	3.2(10)	4.2	Number of carriers within 1MHz band within OFDM	C
--	3.2(8)	4.3	Diffusion bandwidth	C
--	3.2(9)	4.3	Spreading factor	C
--	3.4.1(1)	4.7	Interference Prevention Function	C
--	3.4.1(3)	4.7	Carrier Sense Capability	C
Note: C = Conform; NC = Not Conform; NT = Not Tested; NA = Not Applicable;				

1.1 Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.Date	Calibration Method
Spectrum	Keysight	N9020A	MY51240612	2026-07-23	C
Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101783	2026-07-23	C
Power Meter 10Hz~18GHz	Tonscend	JS0806-2	188060126	2026-07-23	C
Signal generator	Agilent	E4421B	GB40051020	2027-05-22	C
Horn Antenna	Schwarzbeck	BBHA 9120 D	1959	2027-07-26*	C
Attenuator	Weinschael	54A-10	N/A	2026-07-23	C
Universal Switch Control Unit	Rohde&Schwarz	CMW500	12010002k50	2026-07-23	C
Test Software	Tonscend	JS0806-2	NA	NA	C
Humidity tester	Jingchuang	GSP-8A	CMA22B000592	2026-07-28	C

Note:

1. The test was witness in 966 Chamber and RF Oven room.
2. The calibration interval of the above test instruments is 12/24* months and the calibrations are traceable to LISAI/CHINA.
3. Calibration body's name: GUANGZHOU LISAI CALIBRATION AND TESTING CO., LTD.
Address: No.8 South Street Shi Ji Institute Guangzhou. Guangdong. China.

Calibration Method:

- a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1)
- b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992)
- c) Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1)
- d) Calibration conducted by using measuring instruments and other equipment listed in the right column of Table No. 3 attached hereto, which shall have been given any of calibration, etc. listed above from a) to c)

1.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameter	Uncertainty
Occupied Bandwidth	206.50 Hz
Spurious emissions	$\pm 3.84\text{dB}$
Output power density	1.37dB
Out of band radiated power	2.52 dB
Frequency Tolerance	0.104 ppm
Temperature	$\pm 0.23^{\circ}\text{C}$
Humidity	$\pm 0.3\%$
DC and low frequency voltages	$\pm 0.3\%$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.3 Modification Record

There were no modifications required for compliance.

2 General Information

2.1 General Description of EUT

Product Name	Braille Display
Test Model Name	XL20A01KY
Series Models Name	N/A
Power Supply Rating	DC 3.85V/3.2A/0Hz/12.32W
Temperature Operating Range	0 ~ 60℃
Modulation Type	BT-LE(GFSK)
Modulation Technology	DTS
Transfer Rate	1 Mbps; 2Mbps
Operating Frequency	2402 ~ 2480MHz
Rated RF output power density	Please see Note 1
Conducted power density	Please see Note 1
EIRP power density	Please see Note 1
Antenna Type	FPC Antenna
Antenna Gain	3.89dBi
Accessory Device	N/A
Radio FW	20C_V1.0
Radio HW	20C_V1.0

Note:

1. The power table as below table:

Test condition for Modulation Technology	Rated output power density (mW)	Conducted power density (mW)	EIRP power density (mW)
GFSK (1 Mbps)	0.4	0.366	0.896
GFSK (2 Mbps)	0.3	0.294	0.720

- The above EUT information was declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or user's manual.
- Hwa-Hsing (Dongguan) Testing Co., Ltd. is not responsible for the accuracy of the information provided by the manufacturer.
- Please refer to the EUT photo document (Reference No.: 26040801) for detailed product photo.
- For the test results, the EUT had been tested with all conditions, and only the worst case was shown in the test report.

2.2 Description of test modes**2.2.1 Channel list of this EUT:**

40 channels are provided to BT-LE (1Mbps, 2Mbps):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note:

- 1.The channels which were indicated in bold type of the above channel list were selected as presentative test channel. There fore, only the data of the test channels were recorded in this report.
- 2.By means of test software for BT LE provided by manufacture, the power levels during the tests were set according to the following codes:

2.2.2 Test mode applicability and tested channel detail

Test items		Test Conditions for voltage supply	Environmental Conditions
1	Frequency tolerance measurement	V_{normal} V_{high} V_{low}	21.2deg. C, 52%RH
2	Occupied bandwidth measurement (99% power bandwidth)		
3	Spreading bandwidth measurement (90% power bandwidth)		
4	Spurious emissions for transmitter measurement		
5	Antenna power measurement		
6	Spurious emissions for receiver		

EUT Configure mode No.	Test conditions for modulation technology
Mode A	GFSK 1Mbps
Mode B	GFSK 2Mbps
RF power setting value	
Channel	Power setting
Low	0
Middle	0
High	0

Note:

- For the test results, the EUT had been tested with all conditions, and the worst-case mode of data will record in the report.
- By means of test software which provided by manufacture, the power levels during the tests were set according to the above table.

2.2.3 Assembly

The RF circuit was located inside of the EUT.

2.2.4 Applicable Standard

When there is a fluctuation of +/-10% input voltage from external power to the test equipment. If the fluctuation of input voltage to the circuit of the radio part (excl. power) in the test equipment is confirmed below +/-1%, Measurement shall be tested with the rated voltage.

2.2.5 Antenna Specifications

Ant. Type	Highest Peak Gain (dBi) 2.4GHz ~ 2.5GHz
FPC Antenna	3.89dBi

Note: The Antenna pattern Please refer to the attached file (Antenna report).

2.3 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	Notebook	HUAWEI	NbD-WFH9	EUEPM21725002655	N/A
2	Notebook	DELL	Inspiron 14R Aluminum Edition	6WPG9-63PV4-RBPF2-T6RHW-W9GBP	N/A

No.	Signal Cable Description of The Above Support Units
1	USB Cable: Unshielded, Detachable 1.2m;

2.3.1 Configuration of System under Test

Bluetooth TX/RX:




3 Test types and results

3.1 Frequency tolerance measurement

3.1.1 Limits of frequency tolerance measurement

Condition	Tolerance of frequency Limit (e.i.r.p)
Under all test conditions	Within +/- 50ppm

3.1.2 Test Setup



3.1.3 Deviation from Test Standard

No deviation.

3.1.4 Test Procedure

If the fluctuation of input voltage to the circuit of the radio part (excl. power) in the test equipment is confirmed below +/-1%, Measurement shall be tested with the rated voltage.

When there is a fluctuation of +/-10% input voltage from external power to the test equipment. In case the test equipment is designed to function only within the specified fluctuation range of +/-10% for the voltage source tests shall be conducted applying the rated voltage and a respective specified maximum/minimum value of fluctuation range.


Test method according to Clause 5 of Annex No.43 of MIC Notification No.88.


- The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- The EUT was transmitted non-modulated frequencies.
- In case of a test mode generating specific frequency spectrum, the spectrum frequency is measured with the spectrum analyzer.


3.1.5 Test Results


Test Condition	Test Mode	Antenna	Channel	Result[ppm]	Limit[ppm]	Verdict
NTNV	BLE_1M	Ant1	2402	-17.48543	±50	PASS
			2440	-17.62295	±50	PASS
			2480	-17.74194	±50	PASS
NTLV	BLE_1M	Ant1	2402	-17.48543	±50	PASS
			2440	-17.62295	±50	PASS
			2480	-17.74194	±50	PASS
NTHV	BLE_1M	Ant1	2402	-17.48543	±50	PASS
			2440	-17.62295	±50	PASS
			2480	-17.74194	±50	PASS


- The test plots listing in the below pages.











Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](#)

Web: [www.lyns-tci.com](#)

E-Mail: [service-hs@lyns-tci.com](#)

Release

[Ver. 1.5](#)

3.2 Occupied bandwidth measurement (99% power bandwidth)**3.2.1 Limits of occupied bandwidth measurement**

Condition	Occupied bandwidth Limit	Remark
Occupied bandwidth	<26MHz	For 802.11b, g & 802.11n (HT20)
Occupied bandwidth	<26MHz	For BT-LE (GFSK)

3.2.2 Test Setup**3.2.3 Deviation of Test Standard**

No deviation.

3.2.4 Test Procedure


Test method according to Clause 5 of Annex No.43 of MIC Notification No.88.


The EUT was placed inside the environmental test chamber and powered by nominal DC voltage. The bandwidth of the fundamental frequency was measured by spectrum analyzer. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.


3.2.5 Test Results


Test Condition	Test Mode	Antenna	Channel	Result [MHz]	Limit [MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	1.393	≤26	PASS
			2440	1.250	≤26	PASS
			2480	1.217	≤26	PASS
	BLE_2M	Ant1	2402	2.162	≤26	PASS
			2440	2.157	≤26	PASS
			2480	2.151	≤26	PASS
NTLV	BLE_1M	Ant1	2402	1.370	≤26	PASS
			2440	1.252	≤26	PASS
			2480	1.216	≤26	PASS
	BLE_2M	Ant1	2402	2.164	≤26	PASS
			2440	2.156	≤26	PASS
			2480	2.152	≤26	PASS
NTHV	BLE_1M	Ant1	2402	1.369	≤26	PASS
			2440	1.250	≤26	PASS
			2480	1.218	≤26	PASS
	BLE_2M	Ant1	2402	2.163	≤26	PASS
			2440	2.157	≤26	PASS
			2480	2.150	≤26	PASS

Note: For the test plots please refer to the below.


























3.3 Spreading bandwidth measurement (90% power bandwidth)

3.3.1 Limits of spreading bandwidth and spreading factor

Condition	Limit	Remark
Spreading Bandwidth	$\geq 500\text{kHz}$	N/A

3.3.2 Test Procedure



3.3.3 Deviation from Test Standard

No deviation.

3.3.4 Test Procedure

Test method according to Clause 5 of Annex No.43 of MIC Notification No.88.
The EUT was placed inside the environmental test chamber and powered by nominal DC voltage. The bandwidth of the fundamental frequency was measured by spectrum analyzer. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 5 %of the total mean power of a given emission.

3.3.5 Test Results

Test Condition	Test Mode	Antenna	Channel	Result [MHz]	Limit [MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	0.831	≥ 0.5	PASS
			2440	0.827	≥ 0.5	PASS
			2480	0.827	≥ 0.5	PASS
	BLE_2M	Ant1	2402	1.371	≥ 0.5	PASS
			2440	1.372	≥ 0.5	PASS
			2480	1.366	≥ 0.5	PASS
NTLV	BLE_1M	Ant1	2402	0.832	≥ 0.5	PASS
			2440	0.827	≥ 0.5	PASS
			2480	0.826	≥ 0.5	PASS
	BLE_2M	Ant1	2402	1.371	≥ 0.5	PASS
			2440	1.370	≥ 0.5	PASS
			2480	1.365	≥ 0.5	PASS
NTHV	BLE_1M	Ant1	2402	0.833	≥ 0.5	PASS
			2440	0.828	≥ 0.5	PASS
			2480	0.826	≥ 0.5	PASS
	BLE_2M	Ant1	2402	1.370	≥ 0.5	PASS
			2440	1.369	≥ 0.5	PASS
			2480	1.365	≥ 0.5	PASS

Note: For the test plots please refer to the below.

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)


Tel: [0769-85598986](#)


Web: [www.lyns-tci.com](#)


E-Mail: [service-hs@lyns-tci.com](#)


Release


[Ver. 1.5](#)
























3.4 Spurious emissions for transmitter measurement

3.4.1 Limit of Spurious emissions for transmitter measurement

Frequencies (MHz)	Limit
Operating frequency 2400 to 2483.5MHz	
30.0MHz to 2387MHz	$\leq 2.5\mu\text{W}(-26\text{dBm})/\text{MHz}$
2387.0MHz to 2400.0MHz	$\leq 25\mu\text{W}(-16\text{dBm})/\text{MHz}$
2483.5MHz to 2496.5MHz	$\leq 25\mu\text{W}(-16\text{dBm})/\text{MHz}$
2496.5MHz to 12500.0MHz	$\leq 2.5\mu\text{W}(-26\text{dBm})/\text{MHz}$

3.4.2 Test Setup



3.4.3 Deviation from Test Standard

No deviation.

3.4.4 Test Procedure

Test method according to Clause 5 of Annex No.43 of MIC Notification No.88.

The EUT was placed inside the environmental test chamber and powered by nominal DC voltage. The spurious emissions for transmitter was measured by spectrum analyzer.

The settings of the spectrum analyzer during spurious searches are as follows:

- Sweep Bandwidth Starts spurious searches from the smallest possible frequencies to more than 5 times the carrier frequencies (for example from 30 MHz up to 12.5 GHz for a 2.4 GHz system).
- Resolution Bandwidth 1 MHz
- Video Bandwidth 1 MHz
- Y-Axis Scale 10 dB/Div
- Input Level: Maximum dynamic range value
- Sweep Time: Minimum amount of time to ensure measurement accuracy.
- Sweep Points: Over 400 points
- Detection Mode: Positive peak
- Display mode: Maximum hold

3.4.5 Test Results

Test Condition	Test Mode	Antenna	Channel	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [uW/MHz]	Limit [uW/MHz]	Verdict
NTNV	BLE_1M	Ant1	2402	30~2387	80.68	-56.29	≤-26	0.002460368	≤2.5	PASS
				2387~2400	2399.99	-39.90	≤-16	0.10964782	≤25	PASS
				2483.5~2497	2484.00	-60.06	≤-16	0.000680769	≤25	PASS
				2497~13000	4803.60	-32.24	≤-26	0.763835784	≤2.5	PASS
			2440	30~2387	232.70	-52.48	≤-26	0.002612161	≤2.5	PASS
				2387~2400	2387.44	-61.59	≤-16	0.000760326	≤25	PASS
				2483.5~2497	2495.13	-61.76	≤-16	0.000785236	≤25	PASS
				2497~13000	4879.70	-34.56	≤-26	0.553350109	≤2.5	PASS
			2480	30~2387	198.23	-51.09	≤-26	0.002249055	≤2.5	PASS
				2387~2400	2392.51	-61.69	≤-16	0.000749894	≤25	PASS
				2483.5~2497	2484.72	-53.59	≤-16	0.005407543	≤25	PASS
				2497~13000	4960.10	-36.24	≤-26	0.39536662	≤2.5	PASS
	BLE_2M	Ant1	2402	30~2387	233.29	-56.94	≤-26	0.002754229	≤2.5	PASS
				2387~2400	2399.99	-25.66	≤-16	2.890679882	≤25	PASS
				2483.5~2497	2493.07	-61.06	≤-16	0.000756833	≤25	PASS
				2497~13000	4804.10	-32.34	≤-26	0.756832895	≤2.5	PASS
			2440	30~2387	269.24	-52.42	≤-26	0.002612161	≤2.5	PASS
				2387~2400	2393.28	-61.30	≤-16	0.000772681	≤25	PASS
				2483.5~2497	2488.72	-61.47	≤-16	0.000855067	≤25	PASS
				2497~13000	4879.20	-34.57	≤-26	0.545757861	≤2.5	PASS
			2480	30~2387	195.58	-53.57	≤-26	0.002697739	≤2.5	PASS
				2387~2400	2394.99	-61.27	≤-16	0.000685488	≤25	PASS
				2483.5~2497	2483.60	-51.39	≤-16	0.005081594	≤25	PASS
				2497~13000	4959.00	-36.42	≤-26	0.387257645	≤2.5	PASS
NTLV	BLE_1M	Ant1	2402	30~2387	64.18	-52.13	≤-26	0.002328091	≤2.5	PASS
				2387~2400	2399.99	-39.23	≤-16	0.142560759	≤25	PASS
				2483.5~2497	2496.48	-61.08	≤-16	0.000760326	≤25	PASS
				2497~13000	4804.60	-32.17	≤-26	0.749894209	≤2.5	PASS
			2440	30~2387	54.45	-49.85	≤-26	0.009036495	≤2.5	PASS
				2387~2400	2389.10	-61.54	≤-16	0.000814704	≤25	PASS
				2483.5~2497	2494.30	-61.50	≤-16	0.000816582	≤25	PASS
				2497~13000	4880.20	-34.58	≤-26	0.564936975	≤2.5	PASS
			2480	30~2387	45.32	-54.62	≤-26	0.007379042	≤2.5	PASS
				2387~2400	2399.67	-61.60	≤-16	0.000762079	≤25	PASS
				2483.5~2497	2486.02	-51.77	≤-16	0.003126079	≤25	PASS
				2497~13000	4960.60	-36.17	≤-26	0.389045145	≤2.5	PASS
	BLE_2M	Ant1	2402	30~2387	60.05	-55.14	≤-26	0.00724436	≤2.5	PASS
				2387~2400	2399.99	-25.27	≤-16	2.630267992	≤25	PASS
				2483.5~2497	2485.88	-61.75	≤-16	0.000787046	≤25	PASS
				2497~13000	4803.00	-32.73	≤-26	0.744731974	≤2.5	PASS
			2440	30~2387	70.95	-54.62	≤-26	0.004487454	≤2.5	PASS
				2387~2400	2398.55	-60.79	≤-16	0.000609537	≤25	PASS
				2483.5~2497	2493.35	-61.21	≤-16	0.00083946	≤25	PASS
				2497~13000	4879.20	-34.67	≤-26	0.570164272	≤2.5	PASS
			2480	30~2387	268.94	-55.59	≤-26	0.002409905	≤2.5	PASS
				2387~2400	2392.58	-61.52	≤-16	0.000711214	≤25	PASS
				2483.5~2497	2484.63	-51.26	≤-16	0.004285485	≤25	PASS
				2497~13000	4960.10	-37.40	≤-26	0.376703799	≤2.5	PASS
NTHV	BLE_1M	Ant1	2402	30~2387	54.16	-49.47	≤-26	0.007227698	≤2.5	PASS
				2387~2400	2399.87	-39.90	≤-16	0.154525444	≤25	PASS

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](#)


Web: [www.lyns-tci.com](#)


E-Mail: [service-hs@lyns-tci.com](#)


Release


[Ver. 1.5](#)

BLE_2M	Ant1	2440	2483.5~2497	2491.13	-60.00	≤-16	0.000851138	≤25	PASS
			2497~13000	4804.10	-32.39	≤-26	0.741310241	≤2.5	PASS
		2480	30~2387	64.18	-51.88	≤-26	0.001778279	≤2.5	PASS
			2387~2400	2390.93	-60.87	≤-16	0.000696627	≤25	PASS
			2483.5~2497	2493.92	-61.42	≤-16	0.000719449	≤25	PASS
			2497~13000	4879.70	-34.55	≤-26	0.558470195	≤2.5	PASS
		2402	30~2387	205.60	-54.00	≤-26	0.002338837	≤2.5	PASS
			2387~2400	2387.82	-61.18	≤-16	0.000818465	≤25	PASS
			2483.5~2497	2483.93	-53.32	≤-16	0.007943282	≤25	PASS
			2497~13000	4960.10	-36.28	≤-26	0.389941987	≤2.5	PASS
		2440	30~2387	51.21	-49.24	≤-26	0.010069317	≤2.5	PASS
			2387~2400	2400.00	-25.37	≤-16	2.779713268	≤25	PASS
			2483.5~2497	2484.30	-60.67	≤-16	0.000729458	≤25	PASS
			2497~13000	4805.10	-32.32	≤-26	0.749894209	≤2.5	PASS
		2480	30~2387	53.28	-52.02	≤-26	0.009015711	≤2.5	PASS
			2387~2400	2395.57	-61.41	≤-16	0.000743019	≤25	PASS
			2483.5~2497	2492.67	-61.71	≤-16	0.00074817	≤25	PASS
			2497~13000	4879.20	-34.66	≤-26	0.533334895	≤2.5	PASS
		2402	30~2387	48.56	-53.79	≤-26	0.005420009	≤2.5	PASS
			2387~2400	2387.40	-61.84	≤-16	0.000698232	≤25	PASS
			2483.5~2497	2483.67	-54.51	≤-16	0.005457579	≤25	PASS
			2497~13000	4961.10	-36.62	≤-26	0.376703799	≤2.5	PASS










Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)Tel: [0769-85598986](#)Web: [www.lyns-tci.com](#)E-Mail: [service-hs@lyns-tci.com](#)


Release


Ver. 1.5













































Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)Tel: [0769-85598986](#)Web: [www.lyns-tci.com](#)E-Mail: [service-hs@lyns-tci.com](#)


Release


Ver. 1.5















































3.5 Antenna power measurement


3.5.1 Limits of antenna power

Modulation system	Frequency band used	Antenna power (max.)	EIRP (max)	
			Omni-directional case	Directional case
DS. OFDM(Narrow-Band)	2,400–2,4835MHz	10mW/MHz	12.14dBm/MHz (16.367mW/MHz)	22.14dBm/MHz (163.682mW/MHz)
OFDM(Wide-Band)	2,400–2,4835MHz	5mW/MHz	9.13dBm/MHz (8.185mW/MHz)	19.13dBm/MHz (81.846mW/MHz)
DTS	2,400–2,4835MHz	10mW	12.14dBm (16.367mW)	22.14dBm (163.682mW)

Tolerance of antenna power shall be +20% (upper value).

According article 49.20 f (2), the angular width of the principal radiation in the horizontal and vertical planes of the transmitting antenna shall not exceed the value obtained by the following expression. $360/A$ degree. A represents the value determined by dividing an equivalent power by the value obtained by applying an antenna power with the mean power to the transmitting antenna with its absolute gain being 2.14 dB, and shall be 1 when it is lower than 1.

3.5.2 Test Setup



3.5.3 Test Procedure

Test method according to Clause 6 of Annex No.43 of MIC Notification No.88.

The EUT was placed inside the environmental test chamber and powered by nominal DC voltage. The Antenna power was measured by power meter.

- Connect the high frequency power meter to the IF output of the spectrum analysers.
- Recording the power level.

3.5.4 Test result of conducted output power

BT-LE (GFSK-1 Mbps)

Test condition	Conducted output power (mW)						
	CH 0 2402MHz		CH 19 2440MHz		CH 39 2480MHz		Max.Limit (mW)
	Power	Tolerance(%)	Power	Tolerance(%)	Power	Tolerance(%)	
Voltage normal	0.363	-15.00	0.340	-21.40	0.365	-19.20	10
Voltage high	0.365	-15.20	0.340	-21.00	0.366	-19.20	10
Voltage low	0.365	-15.20	0.341	-20.60	0.366	-19.40	10
Rated Power	0.4mW						
Test condition	EIRP output power (mW)						
	CH 0 2402MHz		CH 19 2440MHz		CH 39 2480MHz		Max.Limit (mW)
	Power	Tolerance(%)	Power	Tolerance(%)	Power	Tolerance(%)	
Voltage normal	0.889		0.833		0.894		16.367
Voltage high	0.894		0.833		0.896		16.367
Voltage low	0.894		0.835		0.896		16.367

BT-LE (GFSK-2 Mbps)

Test condition	Conducted output power (mW)						Max.Limit (mW)
	CH 0 2402MHz		CH 19 2440MHz		CH 39 2480MHz		
	Power	Tolerance(%)	Power	Tolerance(%)	Power	Tolerance(%)	
Voltage normal	0.290	-15.60	0.273	-21.60	0.292	-19.00	10
Voltage high	0.292	-16.20	0.274	-21.20	0.293	-19.20	10
Voltage low	0.292	-16.00	0.273	-21.40	0.294	-19.00	10
Rated Power	0.3mW						
Test condition	EIRP output power (mW)						Max.Limit (mW)
	CH 0 2402MHz		CH 19 2440MHz		CH 39 2480MHz		
	Power	Tolerance(%)	Power	Tolerance(%)	Power	Tolerance(%)	
Voltage normal	0.710		0.669		0.715		16.367
Voltage high	0.715		0.671		0.718		16.367
Voltage low	0.715		0.669		0.720		16.367

Note:


1. The value of EIRP densities are "calculated" values.
2. Formula: EIRP output power = Conducted RF output power + Antenna Gain.

3.6 Spurious emissions for receiver

3.6.1 Limits of spurious emissions for receiver

Frequencies(MHz)	Limit
Below 1GHz	$\leq 4\text{nW}$ (-54dBm)
Above 1GHz	$\leq 20\text{nW}$ (-47dBm)

3.6.2 Test Setup



3.6.3 Deviation from Test Standard

No deviation.

3.6.4 Test Procedure

Test method according to Clause 7 of Annex No.43 of MIC Notification No.88.


The EUT was placed inside the environmental test chamber and powered by nominal DC voltage. The spurious emissions for receiver was measured by spectrum analyzer.


The settings of the spectrum analyzer during spurious searches are as follows:


- Sweep Bandwidth Starts spurious searches from the smallest possible frequencies to more than 5 times the carrier frequencies (for example from 30 MHz up to 12.5 GHz for a 2.4 GHz system).
- Resolution Bandwidth 1 MHz
- Video Bandwidth 1 MHz
- Y-Axis Scale 10 dB/Div
- Input Level: Maximum dynamic range value
- Sweep Time: Minimum amount of time to ensure measurement accuracy.
- Sweep Points: Over 400 points
- Detection Mode: Positive peak
- Display mode: Maximum hold


3.6.5 Test Results


Test Condition	Test Mode	Antenna	Channel	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	BLE_1M	Ant1	2402	30~1000	63.95	-59	≤-54	1.25893	≤4	PASS
				1000~13000	12592.00	-58.83	≤-47	1.30918	≤20	PASS
			2440	30~1000	63.95	-59	≤-54	1.25893	≤4	PASS
				1000~13000	12815.80	-58.77	≤-47	1.32739	≤20	PASS
	BLE_2M	Ant1	2480	30~1000	63.95	-58.97	≤-54	1.26765	≤4	PASS
				1000~13000	12548.80	-58.83	≤-47	1.30918	≤20	PASS
			2402	30~1000	64.07	-58.92	≤-54	1.28233	≤4	PASS
				1000~13000	6.0673	-57.53	≤-47	1.76604	≤20	PASS
			2440	30~1000	64.07	-59.17	≤-54	1.21060	≤4	PASS
				1000~13000	12712.60	-58.74	≤-47	1.33660	≤20	PASS
			2480	30~1000	63.95	-59.05	≤-54	1.24451	≤4	PASS
				1000~13000	12769.60	-58.82	≤-47	1.31220	≤20	PASS
NTLV	BLE_1M	Ant1	2402	30~1000	63.95	-58.79	≤-54	1.32130	≤4	PASS
				1000~13000	11631.90	-58.65	≤-47	1.36458	≤20	PASS
			2440	30~1000	63.95	-59.26	≤-54	1.18577	≤4	PASS
				1000~13000	12851.80	-58.97	≤-47	1.26765	≤20	PASS
	BLE_2M	Ant1	2480	30~1000	63.95	-59.02	≤-54	1.25314	≤4	PASS
				1000~13000	6540.70	-58.65	≤-47	1.36458	≤20	PASS
			2402	30~1000	63.95	-58.52	≤-54	1.40605	≤4	PASS
				1000~13000	5.460	-57.07	≤-47	1.96336	≤20	PASS
			2440	30~1000	63.95	-58.93	≤-54	1.27938	≤4	PASS
				1000~13000	12596.20	-58.99	≤-47	1.26183	≤20	PASS
			2480	30~1000	63.95	-59.33	≤-54	1.16681	≤4	PASS
				1000~13000	6150.10	-58.27	≤-47	1.48936	≤20	PASS
NTHV	BLE_1M	Ant1	2402	30~1000	63.95	-59.02	≤-54	1.25314	≤4	PASS
				1000~13000	7411.30	-58.61	≤-47	1.37721	≤20	PASS
			2440	30~1000	63.95	-59.21	≤-54	1.19950	≤4	PASS
				1000~13000	6021.10	-58.64	≤-47	1.36773	≤20	PASS
	BLE_2M	Ant1	2480	30~1000	63.95	-58.67	≤-54	1.35831	≤4	PASS
				1000~13000	12608.20	-58.77	≤-47	1.32739	≤20	PASS
			2402	30~1000	63.95	-58.22	≤-54	1.50661	≤4	PASS
				1000~13000	5.8464	-58.45	≤-47	1.42889	≤20	PASS
			2440	30~1000	63.95	-58.66	≤-54	1.36144	≤4	PASS
				1000~13000	5469.00	-58.47	≤-47	1.42233	≤20	PASS
			2480	30~1000	63.95	-58.94	≤-54	1.27644	≤4	PASS
				1000~13000	12929.00	-58.83	≤-47	1.30918	≤20	PASS















































Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)


Tel: [0769-85598986](#)

Web: [www.lyns-tci.com](#)

E-Mail: [service-hs@lyns-tci.com](#)


Release


[Ver. 1.5](#)





Note: Some values exceed 1/10 of the limit, and these values have been retested using an average detector.
The results are as follows:

Test Condition	Test Mode	Antenna	Channel	Freq.Range [MHz]	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [nW]	Limit [nW]	Verdict
NTNV	BLE_1M	Ant1	2402	30~1000	63.95	-61.138	≤-54	0.76948	≤4	PASS
			2440	30~1000	64.00	-58.576	≤-54	1.38803	≤4	PASS
			2480	30~1000	63.95	-60.914	≤-54	0.81021	≤4	PASS
	BLE_2M	Ant1	2402	30~1000	64.00	-59.274	≤-54	1.18195	≤4	PASS
			2440	30~1000	64.00	-59.686	≤-54	1.07498	≤4	PASS
			2480	30~1000	63.95	-61.381	≤-54	0.72761	≤4	PASS
NTLV	BLE_1M	Ant1	2402	30~1000	64.01	-59.229	≤-54	1.19426	≤4	PASS
			2440	30~1000	63.95	-61.105	≤-54	0.77535	≤4	PASS
			2480	30~1000	63.99	-58.554	≤-54	1.39508	≤4	PASS
	BLE_2M	Ant1	2402	30~1000	63.99	-59.219	≤-54	1.19702	≤4	PASS
			2440	30~1000	63.95	-60.908	≤-54	0.81133	≤4	PASS
			2480	30~1000	63.98	-59.538	≤-54	1.11224	≤4	PASS
NTHV	BLE_1M	Ant1	2402	30~1000	63.95	-61.082	≤-54	0.77947	≤4	PASS
			2440	30~1000	64.07	-62.821	≤-54	0.52228	≤4	PASS
			2480	30~1000	64.07	-63.058	≤-54	0.49454	≤4	PASS
	BLE_2M	Ant1	2402	30~1000	64.00	-59.017	≤-54	1.25401	≤4	PASS
			2440	30~1000	64.00	-59.517	≤-54	1.11764	≤4	PASS
			2480	30~1000	64.01	-59.256	≤-54	1.18686	≤4	PASS


























Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Tel: [0769-85598986](#)


Web: [www.lyns-tci.com](#)


E-Mail: [service-hs@lyns-tci.com](#)

Release

[Ver. 1.5](#)







Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)


Tel: [0769-85598986](#)


Web: [www.lyns-tci.com](#)


E-Mail: [service-hs@lyns-tci.com](#)

Release

[Ver. 1.5](#)







Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)


Tel: [0769-85598986](#)

Web: [www.lyns-tci.com](#)

E-Mail: [service-hs@lyns-tci.com](#)

Release

[Ver. 1.5](#)



Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)


Tel: [0769-85598986](#)

Web: [www.lyns-tci.com](#)

E-Mail: [service-hs@lyns-tci.com](#)

Release

[Ver. 1.5](#)



3.7 Interference prevention function

3.7.1 Limits of interference prevention function

No limit for use.

3.7.2 Test Procedure

The interference prevention requirement is a requirement that client devices should send an identification code to the master device in order to identify itself as a valid/authorized client.

An acceptable result is to take a screenshot to demonstrate that the MAC address is 48 bits,


The intent of this requirement is that client devices which do not have a valid identification code cannot connect to the master device (such unauthorized client devices therefore cannot "interfere" with authorized client devices because unauthorized client devices will not be allowed to connect to the master).

This requirement applies to all 2.4 GHz devices (in fact, this requirement applies to most transmitters/transceivers when they are intended to be used in Japan). For 2.4 GHz devices, the identification code must consist of 48 bits.

The majority of 2.4 GHz devices are still WLAN, Bluetooth or ZigBee devices. In such cases, one of the IEEE 802.xx protocols will be used. As it happens (and this is probably not a coincidence) the MAC address which is assigned to such devices consists of 48 bits.

As a result of said changes in the Japanese Radio Law, the test laboratory (now) needs to verify the operation/existence of the interference prevention function and needs to report the result(s) of this test in the test report.


3.7.3 Test Setup



3.7.4 Test results

Link mode	Test result
BT	Good
The MAC Address	00:80:E1:26:CE:B4
服务: 0x400000 < BLE > XINLIN TECH: 地址: 00:80:E1:26:CE:B4 RSSI: -74 服务: 0x400000 < BLE >	

4 Photographs of the test configuration



Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-85598986](#)

Email: service-hs@lyns-tci.com

Web Site: www.lyns-tci.com

The address and road map of all our labs can be found in our web site also.

--- END ---