

Japan Test Report


Equipment : TV Adapter
Model No. : TVA3.1
Applicant : SBO Hearing A/S
Address : Kongebakken 9 DK-2765 Smørum, Denmark
Standard : Article 2 Paragraph 1 Item 19
Received Date : Apr. 27, 2026
Tested Date : May 28, 2026

Measurement was conducted by the following test method:
the test method of Ordinance Concerning Technical Regulations Conformity Certification
etc. of Specified Radio Equipment in Annex 1, the Ministry of Internal Affairs and
Communications notification in Annex "43" of Article 88, Paragraph 1.

We, International Certification Corporation, would like to declare that the tested sample has
been evaluated and in compliance with the requirement of the above standards. The test
results contained in this report refer exclusively to the product. It shall not be reproduced
except in full without the written approval of our laboratory.

Reviewed by:

Approved by:


Alex Huang / Supervisor



Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Test Equipment and Calibration Data	7
1.3	Testing Applied Standards	7
1.4	Deviation from Test Standard and Measurement Procedure.....	7
1.5	Measurement Uncertainty	7
2	TEST CONFIGURATION.....	8
2.1	Testing Location and Conditions.....	8
2.2	Testing Facility	8
2.3	Supporting Units.....	8
2.4	The Worst Test Modes and Channel Details	8
3	TRANSMITTER TEST RESULTS	9
3.1	Antenna Power	9
3.2	Frequency Tolerance	10
3.3	Occupied Bandwidth	11
3.4	Transmitter Spurious Emissions.....	12
3.5	Interference Prevention Function	13
4	TEST LABORATORY INFORMATION	14

Appendix A. Antenna Power

Appendix B. Frequency Tolerance

Appendix C. Occupied Bandwidth

Appendix D. Transmitter Spurious Emissions

Appendix E. Interference Prevention Function

Release Record

Report No.	Version	Description	Issued Date
JR642701	Rev. 01	Initial issue	Jun. 29, 2026

Summary of Test Results

Ref. Std. Clause	Description	Result
3.2(2)(3)	Antenna Power	Pass
3.2(4)	Frequency Tolerance	Pass
3.2(6)	Transmitter Spurious Emission	Pass
3.2(7)	Occupied Bandwidth	Pass
3.3(1)	Receiver Emission	N/A
3.4.1	Interference prevention function	Pass

Note: The 2GFSK FHSS supports TX only.

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Power Type	5Vdc from adapter
Type(s) of Modulation / Technology	2GFSK-FHSS = 2Mbps
Frequency Range (MHz)	2404 ~ 2476 MHz
Total Channel Number	36
HW Version	3.1
SW Version	2.3.1

1.1.2 Accessories

Accessories		
No.	Equipment	Description
1	AC adapter	Brand Name: PHIHONG Model Name: A M05A-050A-R I/P: 100-240V~ 50-60Hz, 0.2A O/P: 5V=1A Power Line: 1.82m non-shielded without core

1.1.3 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	monopole antenna	No	1.9	---

Note: Please refer to antenna report for more details about antenna pattern and other information.

1.1.4 Antenna Power

Modulation Mode	Rated Power (mW/MHz)	Measured Conducted Power (mW/MHz)	Radiated Power (mW/MHz)
2GFSK-FHSS	0.3	0.25351	0.39264

1.1.5 Channel List

Frequency band (MHz)				2404 ~ 2476			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2404	9	2422	18	2442	27	2460
1	2406	10	2424	19	2444	28	2462
2	2408	11	2428	20	2446	29	2464
3	2410	12	2430	21	2448	30	2466
4	2412	13	2432	22	2450	31	2468
5	2414	14	2434	23	2452	32	2470
6	2416	15	2436	24	2454	33	2472
7	2418	16	2438	25	2456	34	2474
8	2420	17	2440	26	2458	35	2476

1.1.6 Test Tool and Power Index

Test Tool
Hardware, Version: 0.9.3

Power Index			
Modulation Mode	Test Frequency (MHz)		
	2404	2440	2476
2GFSK-FHSS	Default	Default	Default

1.1.7 Test Voltage

Test Voltage	☒ Vnom (5 Vdc)	☒ Vmax (5.5 Vdc)	☒ Vmin (4.5 Vdc)
--------------	--	--	--

1.1.8 Protection Method for High Frequency and Modulation Section

Protected Method	Description
Special Screw	RF and Modulation components are covered within case of EUT and this case used special screw to protect anybody to open this case

1.2 Test Equipment and Calibration Data

Test Item	RF Conducted						
Test Site	(TH01-WS)						
Tested Date	May 28, 2026						
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until	Calibration Authority	Calibration Method
Spectrum Analyzer	R&S	FSV40	101486	Mar. 10, 2026	Mar. 09, 2027	ETC	(C)
DC POWER SOURCE	GW INSTEK	GPE-6030	GEZ824073	Oct. 27, 2025	Oct. 26, 2026	ETC	(C)
Power Sensor	Anritsu	MA2411B	1207367	Feb. 04, 2026	Feb. 03, 2027	ETC	(C)
Power Meter	Anritsu	ML2495A	1218007	Feb. 04, 2026	Feb. 03, 2027	ETC	(C)
Measurement Software	Sporton	SENSE	5.11.9	NA	NA	N/A	N/A
Note 1: Calibration Interval of instruments listed above is one year.							
Note 2: Calibration Method							
a. Calibration conducted by the National Institute of Information and Communications Technology(NICT) or a designated calibration agency under Article 102-18 paragraph (1) of the Radio Law.							
b. Calibration conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992) Japan Calibration Service System.							
c. Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).							
d. Calibration conducted by using other equipment that listed above from a) to c).							

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Article 2 Paragraph 1 Item 19

1.4 Deviation from Test Standard and Measurement Procedure

None

1.5 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.139 Hz
Conducted power	± 0.808 dB
Frequency error	$\pm 1 \times 10^{-9}$
TX Conducted emission	± 2.680 dB
RX Conducted emission	± 3.034 dB

2 Test Configuration

2.1 Testing Location and Conditions

Test Site	Site Category	Ambient Condition	Tested By
TH01-WS	OVEN Room	20.9℃ / 61%	Alan Tang

2.2 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

2.3 Supporting Units

Support Unit	Brand	Model	FCC ID
Laptop	DELL	Latitude 4400	DoC

2.4 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test channel
Antenna Power	2GFSK-FHSS	Hopping
Frequency Tolerance	2GFSK-FHSS	2404 / 2440 / 2476
Occupied Bandwidth	2GFSK-FHSS	Hopping
Transmitter Spurious Emission	2GFSK-FHSS	Hopping
Interference prevention function	2GFSK-FHSS	Hopping

3 Transmitter Test Results

3.1 Antenna Power

3.1.1 Limit of Antenna Power

Spread Spectrum Method	Frequency Range	Limit	Tolerance
1) FHSS (compound method with DSSS or OFDM)	2427 ~ 2470.75 MHz	3 mW / MHz	+20 %
	2400 ~ 2483.5 MHz (except 2427 ~2470.75MHz)	10 mW / MHz	
2) DSSS	2400 ~ 2483.5 MHz	10 mW / MHz	
3) OFDM (OBW with 26 MHz)	2400 ~ 2483.5 MHz	10 mW / MHz	
4) OFDM (OWB with 26 ~ 40MHz)	2400 ~ 2483.5 MHz	5 mW / MHz	
5) Other method (Except SS & OFDM)	2400 ~ 2483.5 MHz	10mW	

3.1.2 Test Procedures

Measure the total power by Power Meter

3.1.3 Test Setup



3.1.4 Test Result

Refer to Appendix A.

3.2 Frequency Tolerance


3.2.1 Limit of Frequency Tolerance

Frequency tolerance shall be +/- 50ppm.

3.2.2 Test Procedures

1. Set Span = 5 MHz, RBW = 100 kHz, VBW = 300 kHz, Sweep time = Auto, detector = Peak.
2. The peak value of the power envelope shall be measured and noted.
3. The span shall be reduced and the marker moved in a positive frequency increment until the upper, (relative to the centre frequency), -10 dBc point is reached. This value shall be noted as f1.
The marker shall then be moved in a negative frequency increment until the lower, (relative to the centre frequency), -10 dBc point is reached. This value shall be noted as f2.
The Measurement Frequency is calculated as $(f1 + f2) / 2$.
4. $FT(ppm) = \{ (MF - CF) / CF \} \times 1000000$
(FT: Frequency Tolerance, MF: Measurement Frequency, CF: Centre Frequency.)

3.2.3 Test Setup



3.2.4 Test Result

Refer to Appendix B.

3.3 Occupied Bandwidth

3.3.1 Limit of Occupied Bandwidth

Spread Spectrum Method	Limit (MHz)
FHSS (compound method with DSSS or OFDM)	83.5
DSSS	26
OFDM(Narrow bandwidth)	26
OFDM(Wide bandwidth)	26 ~ 40
Other method (Except SS & OFDM)	26

3.3.2 Test Procedures

1. Set Span = 40MHz, RBW = VBW = 300kHz, detector = Peak, Sweep time = Auto.
2. Enable OBW function of spectrum analyzer to measure OBW and capture test plot.

3.3.3 Test Setup



3.3.4 Test Result

Refer to Appendix C.

3.4 Transmitter Spurious Emissions


3.4.1 Limit of Transmitter Spurious Emissions

Item	Limits
Tx Spurious Emission	$\leq 2.5 \mu\text{W} / \text{MHz}$ ($2387\text{MHz} > f$; $2496.5\text{MHz} < f$).
	$\leq 25 \mu\text{W} / \text{MHz}$ ($2387\text{MHz} \leq f < 2400\text{MHz}$) and ($2483.5\text{MHz} < f \leq 2496.5\text{MHz}$).

3.4.2 Test Procedures

1. Set EUT to transmit at rated power and channel to perform test.
2. Set RBW = VBW = 1MHz, Detector type = Peak, Sweep time = Auto.
3. Following above setting of spectrum analyzer to measure spurious emission of 30~12500 MHz.

3.4.3 Test Setup



3.4.4 Test Result

Refer to Appendix D.

3.5 Interference Prevention Function


3.5.1 Limit of Interference Prevention Function

Limits
The identification code shall be 48 bits long

3.5.2 Test Procedures

1. Set EUT under operating mode and link up with companion equipment
2. Check communication status between EUT and companion equipment is normal

3.5.3 Test Setup



3.5.4 Test Result

Refer to Appendix E.

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <https://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==

**Summary**

Mode	Result	Antenna Power (dBm/MHz)	Antenna Power (mW/MHz)	Declare (mW/MHz)	Tolerance (%)	Limit+ (%)	Limit- (%)
2.4-2.4835GHz	-	-	-	-	-	-	-
GFSK(2Mbps) FHSS	Pass	-5.96	0.25351	0.3	-15.50	20	-Inf

Inf = There's no restriction for the limit.

Result

Mode	Result	Antenna Power (dBm/MHz)	Antenna Power (mW/MHz)	Declare (mW/MHz)	Tolerance (%)	Limit+ (%)	Limit- (%)
GFSK(2Mbps) FHSS	-	-	-	-	-	-	-
Hopping Mode_TnomVnom	Pass	-5.97	0.25293	0.3	-15.69	20	-Inf
Hopping Mode_TnomVmin	Pass	-5.96	0.25351	0.3	-15.50	20	-Inf
Hopping Mode_TnomVmax	Pass	-5.97	0.25293	0.3	-15.69	20	-Inf

Inf = There's no restriction for the limit.



Summary

Mode	Antenna Power (dBm/MHz)	Antenna Power (mW/MHz)	EIRP Antenna Power (dBm/MHz)	EIRP Antenna Power (mW/MHz)
2.4-2.4835GHz	-	-	-	-
GFSK(2Mbps) FHSS	-5.96	0.25351	-4.06	0.39264

Result

Mode	Result	Gain (dBi)	Antenna Power (dBm/MHz)	Antenna Power (mW/MHz)	Antenna Power Lim. (mW/MHz)	EIRP Antenna Power (dBm/MHz)	EIRP Antenna Power (mW/MHz)	EIRP Antenna Power Lim. (mW/MHz)
GFSK(2Mbps) FHSS	-	-	-	-	-	-	-	-
Hopping Mode_TnomVnom	Pass	1.90	-5.97	0.25293	3	-4.07	0.39174	4.91
Hopping Mode_TnomVmin	Pass	1.90	-5.96	0.25351	3	-4.06	0.39264	4.91
Hopping Mode_TnomVmax	Pass	1.90	-5.97	0.25293	3	-4.07	0.39174	4.91



Summary

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
2.4-2.4835GHz	-	-	-	-	-	-	-
GFSK(2Mbps) FHSS	Pass	2.476G	2.475987812G	-4.9223	±50	1	-

Result

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
GFSK(2Mbps) FHSS	-	-	-	-	-	-	-
2404MHz_TnomVnom	Pass	2.404G	2.4040025G	1.0399	±50	1	-
2404MHz_TnomVmin	Pass	2.404G	2.4040025G	1.0399	±50	1	-
2404MHz_TnomVmax	Pass	2.404G	2.404000938G	0.39	±50	1	-
2440MHz_TnomVnom	Pass	2.44G	2.43999G	-4.0984	±50	1	-
2440MHz_TnomVmin	Pass	2.44G	2.439989688G	-4.2264	±50	1	-
2440MHz_TnomVmax	Pass	2.44G	2.439989375G	-4.3545	±50	1	-
2476MHz_TnomVnom	Pass	2.476G	2.475987812G	-4.9223	±50	1	-
2476MHz_TnomVmin	Pass	2.476G	2.475987812G	-4.9223	±50	1	-
2476MHz_TnomVmax	Pass	2.476G	2.475987812G	-4.9223	±50	1	-




2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2404MHz_TnomVnom

28/05/2026




Ch(Hz)	Center(Hz)	Fl(Hz)	Fh(Hz)	ppm	Limit(ppm)	Port	Remark
2.404G	2.4040025G	2.403284375G	2.404720625G	1.0399	±50	1	-

2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2404MHz_TnomVmin

28/05/2026



Ch(Hz)	Center(Hz)	Fl(Hz)	Fh(Hz)	ppm	Limit(ppm)	Port	Remark
2.404G	2.4040025G	2.403285625G	2.404719375G	1.0399	±50	1	-




2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2404MHz_TnomVmax

28/05/2026




2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2440MHz_TnomVnom

28/05/2026






2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2440MHz_TnomVmin

28/05/2026

CF (Hz)
2.44G
Span (Hz)
5M
RBW (Hz)
100k
VBW (Hz)
300k
Sweep Time (s)
8.01m
Detector Type
Peak



Ch(Hz)	Center(Hz)	F(Hz)	Fh(Hz)	ppm	Limit(ppm)	Port	Remark
2.44G	2.43989688G	2.439273125G	2.44070625G	-4.2264	±50	1	-


2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2440MHz_TnomVmax

28/05/2026

CF (Hz)
2.44G
Span (Hz)
5M
RBW (Hz)
100k
VBW (Hz)
300k
Sweep Time (s)
8.01m
Detector Type
Peak



Ch(Hz)	Center(Hz)	F(Hz)	Fh(Hz)	ppm	Limit(ppm)	Port	Remark
2.44G	2.43989375G	2.4392725G	2.44070625G	-4.3545	±50	1	-




2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2476MHz_TnomVnom

28/05/2026

CF (Hz)
2.476G
Span (Hz)
5M
RBW (Hz)
100k
VBW (Hz)
300k
Sweep Time (s)
8.01m
Detector Type
Peak



Ch(Hz)	Center(Hz)	F(Hz)	Fh(Hz)	ppm	Limit(ppm)	Port	Remark
2.476G	2.475987812G	2.475271875G	2.47670375G	-4.9223	±50	1	-


2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2476MHz_TnomVmin

28/05/2026

CF (Hz)
2.476G
Span (Hz)
5M
RBW (Hz)
100k
VBW (Hz)
300k
Sweep Time (s)
8.01m
Detector Type
Peak



Ch(Hz)	Center(Hz)	F(Hz)	Fh(Hz)	ppm	Limit(ppm)	Port	Remark
2.476G	2.475987812G	2.4752725G	2.476703125G	-4.9223	±50	1	-




2.4-2.4835GHz_GFSK(2Mbps) FHSS

Freq. Stability-FS

2476MHz_TnomVmax

28/05/2026

CF (Hz)
2.476G
Span (Hz)
5M
RBW (Hz)
100k
VBW (Hz)
300k
Sweep Time (s)
8.01m
Detector Type
Peak



Ch(Hz)	Center(Hz)	F(Hz)	Fh(Hz)	ppm	Limit(ppm)	Port	Remark
2.476G	2.475987812G	2.475271875G	2.47670375G	-4.9223	±50	1	-



Occupied Bandwidth

Appendix C

Summary

Mode	Max-OBW (Hz)	ITU-Code	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-
GFSK(2Mbps) FHSS	73.763M	73M8F1D	73.763M

Max-OBW = Maximum 99% occupied bandwidth; Min-OBW = Minimum 99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	P1-OBW (Hz)
GFSK(2Mbps) FHSS	-	-	-
Hopping Mode_TnomVnom	Pass	83.5M	73.763M
Hopping Mode_TnomVmin	Pass	83.5M	73.763M
Hopping Mode_TnomVmax	Pass	83.5M	73.763M

P1-OBW = Port 1 99% occupied bandwidth




2.4-2.4835GHz_GFSK(2Mbps) FHSS

OBW-FS

Hopping Mode_TnomVnom

28/05/2026





2.4-2.4835GHz_GFSK(2Mbps) FHSS

OBW-FS

Hopping Mode_TnomVmin

28/05/2026







Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Freq (Hz)	Psum (dBm/MHz)	Psum (uW/MHz)	Limit (dBm/MHz)	Limit (uW/MHz)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-
GFSK(2Mbps) FHSS	Pass	2.387G	2.4G	1M	2.39999G	-32.69	0.53827	-16.02	25

Result

Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Freq (Hz)	Psum (dBm/MHz)	Psum (uW/MHz)	Limit (dBm/MHz)	Limit (uW/MHz)
GFSK(2Mbps) FHSS	-	-	-	-	-	-	-	-	-
Hopping Mode_TnomVnom	Pass	30M	2.387G	1M	2.38582G	-46.85	0.02065	-26.02	2.5
Hopping Mode_TnomVnom	Pass	2.387G	2.4G	1M	2.39999G	-32.69	0.53827	-16.02	25
Hopping Mode_TnomVnom	Pass	2.4835G	2.4965G	1M	2.48356G	-40.72	0.08472	-16.02	25
Hopping Mode_TnomVnom	Pass	2.4965G	12.5G	1M	11.22237G	-46.38	0.02301	-26.02	2.5
Hopping Mode_TnomVmin	Pass	30M	2.387G	1M	2.38663G	-46.21	0.02393	-26.02	2.5
Hopping Mode_TnomVmin	Pass	2.387G	2.4G	1M	2.39997G	-33.00	0.50119	-16.02	25
Hopping Mode_TnomVmin	Pass	2.4835G	2.4965G	1M	2.48362G	-41.56	0.06982	-16.02	25
Hopping Mode_TnomVmin	Pass	2.4965G	12.5G	1M	12.48781G	-46.64	0.02168	-26.02	2.5
Hopping Mode_TnomVmax	Pass	30M	2.387G	1M	2.38685G	-46.86	0.02061	-26.02	2.5
Hopping Mode_TnomVmax	Pass	2.387G	2.4G	1M	2.4G	-33.42	0.45499	-16.02	25
Hopping Mode_TnomVmax	Pass	2.4835G	2.4965G	1M	2.48362G	-41.52	0.07047	-16.02	25
Hopping Mode_TnomVmax	Pass	2.4965G	12.5G	1M	11.20548G	-46.61	0.02183	-26.02	2.5




2.4-2.4835GHz_GFSK(2Mbps) FHSS

CSE-TX-FS

Hopping Mode_TnomVnom

28/05/2026




F-Start(Hz)	F-Stop(Hz)	Freq(Hz)	Psum(dBm)	Limit(dBm)	Margin(dB)	P1(dBm)
30M	2.387G	2.38582G	-46.85	-26.02	-20.83	-46.85
2.387G	2.4G	2.39999G	-32.69	-16.02	-16.67	-32.69
2.4835G	2.4965G	2.48356G	-40.72	-16.02	-24.70	-40.72
2.4965G	12.5G	11.22237G	-46.38	-26.02	-20.36	-46.38

2.4-2.4835GHz_GFSK(2Mbps) FHSS


CSE-TX-FS

Hopping Mode_TnomVmin

28/05/2026



F-Start(Hz)	F-Stop(Hz)	Freq(Hz)	Psum(dBm)	Limit(dBm)	Margin(dB)	P1(dBm)
30M	2.387G	2.38663G	-46.21	-26.02	-20.19	-46.21
2.387G	2.4G	2.39997G	-33.00	-16.02	-16.98	-33.00
2.4835G	2.4965G	2.48360G	-41.56	-16.02	-25.54	-41.56
2.4965G	12.5G	12.46781G	-46.64	-26.02	-20.62	-46.64





Interference Prevention Function

Appendix E

Summary

Mode	Result	MAC (ID Length)	ID Limit	Function
2.4-2.4835GHz	-	-	-	-
GFSK(2Mbps) FHSS	Pass	98:D9:3D:7F:09:5C	48 bits	Good

Result

Mode	Result	MAC (ID Length)	ID Limit	Function
GFSK(2Mbps) FHSS	-	-	-	-
Hopping Mode_TnomVnom	Pass	98:D9:3D:7F:09:5C	48 bits	Good
Hopping Mode_TnomVmin	Pass	98:D9:3D:7F:09:5C	48 bits	Good
Hopping Mode_TnomVmax	Pass	98:D9:3D:7F:09:5C	48 bits	Good