

Prüfbericht-Nr.: <i>Test Report No.:</i>	50152537 001	Auftrags-Nr.: <i>Order No.:</i>	114076968	Seite 1 von 19 Page 1 of 19
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	27-Apr-2018	
Auftraggeber: <i>Client:</i>	香港商亞薩合萊有限公司台灣分公司 10365 台北市大同區承德路三段 217 號 2 樓			
Prüfgegenstand: <i>Test item:</i>	Digital door locks			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	YDM7216			
Auftrags-Inhalt: <i>Order content:</i>	LP0002 Test Report (RFID)			
Prüfgrundlage: <i>Test specification:</i>	NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2018) Section 3.2			
Wareneingangsdatum: <i>Date of receipt:</i>	09-May-2018			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000737838-001			
Prüfzeitraum: <i>Testing period:</i>	30-May-2018 ~ 06-Jun-2018			
Ort der Prüfung: <i>Place of testing:</i>	EMC/RF Laboratory Taipei			
Prüflaboratorium: <i>Testing laboratory:</i>	TUV Rheinland Taiwan Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
2018-06-08 Mars Y.J. Lin / Project Engineer		2018-06-08 Rene Chanton/Expert, Electrical		
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet				
Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.: 50152537 001
Test Report No.

Seite 2 von 19
Page 2 of 19

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Passed

5.1.2 FIELD STRENGTH OF FUNDAMENTAL

RESULT: Passed

5.1.3 FREQUENCY STABILITY

RESULT: Passed

5.1.4 SPURIOUS EMISSION

RESULT: Passed

Contents

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS.....	4
2.	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY	7
3.	GENERAL PRODUCT INFORMATION.....	8
3.1	PRODUCT FUNCTION AND INTENDED USE	8
3.2	RATINGS AND SYSTEM DETAILS.....	8
3.3	INDEPENDENT OPERATION MODES	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	9
3.5	SUBMITTED DOCUMENTS.....	9
4.	TEST SET-UP AND OPERATION MODES.....	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE.....	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	11
4.5	TEST SETUP DIAGRAM	11
5.	TEST RESULTS	12
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	12
5.1.1	<i>Antenna Requirement</i>	<i>12</i>
5.1.2	<i>Field strength of fundamental.....</i>	<i>13</i>
5.1.3	<i>Frequency Stability.....</i>	<i>14</i>
5.1.4	<i>Spurious Emission</i>	<i>15</i>
5.2	PHOTOGRAPHS OF THE TEST SET-UP.....	16
6.	LIST OF TABLES	19
7.	LIST OF PHOTOGRAPHS.....	19

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix P: Photo Documentation

(File Name: 50152537APPENDIX P)

Appendix D: Test Result of Radiated Emissions

(File Name: 50152537APPENDIX D)

Test Specifications

The following standards were applied

Table 1: Applied Standard and Test Levels

Radio
NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2018)(107 年 1 月 10 日)

2. Test Sites

2.1 Test Facilities

TUV Rheinland Taiwan Ltd.

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

FCC Registration No.: 340738
IC Canada Registration No.: 9465A-1
TAF Accredited NCC Test Lab. No.:0759
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th



Testing Laboratory
0759

2.2 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMG	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESR 7	101549	2017/11/10	2018/11/10
Spectrum Analyzer	R&S	FSV 40	100921	2018/05/02	2019/05/02
EXA Signal Analyzer	KEYSIGHT	N9010A	MY52221334	2018/02/05	2019/02/04
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	2017/08/14	2018/08/14
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2018/01/18	2019/01/18
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	60558	2017/11/21	2018/11/21
Bilog Antenna	TESEQ	CBL6111D	29804	2017/08/18	2018/08/18
Horn Antenna	ETS-Lindgren	3117	201918	2017/08/18	2018/08/18
Horn Antenna (18GHz~40GHz)	COM-POWER	AH-840	101029	2017/11/28	2018/11/28
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	2018/06/14	2019/06/14
EMI Test Receiver	R&S	ESR 7	101549	2017/11/10	2018/11/10
Spectrum Analyzer	R&S	FSL3	101943	2015/09/07	2018/09/07
Temp. & Humid. Chamber	Giant Force	GCT-099-40-S	MAF0103-007	2017/03/09	2019/03/09

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are $\pm 3\text{dB}$.

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF power, conducted	$\pm 1.5 \text{ dB}$
Radiated emission of transmitter, valid up to 26 GHz	$\pm 6 \text{ dB}$
Radiated emission of receiver, valid up to 26 GHz	$\pm 6 \text{ dB}$
Temperature	$\pm 2 \text{ }^{\circ}\text{C}$
Humidity	$\pm 10 \text{ } \%$

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Digital door locks, working at 13.56 MHz with RFID function.
For details refer to the User Guide, Data Sheet and Block Diagram.

3.2 Ratings and System Details

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Digital door locks
Type Identification	YDM7216
Brand Name	Yale

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequency	13.56 MHz
Operation Voltage	4 ~ 6.5Vdc
Modulation	ASK
Antenna Type	Loop Antenna

3.3 Independent Operation Modes

Basic operation modes are:

- A. Transmitting

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Block Diagram.

3.5 Submitted Documents

- Block Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum emission level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a test mode firmware which makes it possible to transmit signal when switched on the power

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:


N/A

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Passed**

Standard : LP0002(2018): 2.2

Requirement : use of approved antennas only

The antenna is Loop Antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

5.1.2 Field strength of fundamental

RESULT:
Passed

Test standard : LP0002(2018) : 3.2

Basic standard : LP0002(2018)

Test setup

Test Frequency : 13.56 MHz
 Operation Mode : A

Ambient temperature : 25.3°C
 Relative humidity : 49%
 Atmospheric pressure : 100-103 kPa

Table 6: Test result of Field strength of fundamental and modulation sidebands

Frequency (MHz)	Meas. Result	Detector	Test Result	Limits (QP)		Pass/Fail
	dBµV/m @3m		dBµV/m @30m	dBµV/m @3m	dBµV/m@ 30m	
13.560	46.12	QP	26.12	123.99	103.99	Pass

For details refer to Appendix D.

5.1.3 Frequency Stability

RESULT:
Passed

Test standard : LP0002(2018) : 3.2.1.3 , 5.18

Basic standard : LP0002(2018)

Kind of test site : Shielded room

Test setup

Test Frequency : 13.56 MHz

Operation Mode : A

Ambient temperature : 25.3°C

Relative humidity : 49%

Atmospheric pressure : 100-103 kPa

Table 7: Test result of Frequency Stability

Frequency Stability Measurement					
Fundamental frequency (MHz)	Temperature (°C)	Voltage	Measurement frequency (MHz)	Frequency Error (ppm)	Limit ±0.01%
13.56000	-20	Normal	13.560250	18.44	±100ppm
	-10	Normal	13.560250	18.44	
	0	Normal	13.560200	14.75	
	10	Normal	13.560150	11.06	
	20	Normal	13.560000	0.00	
	30	Normal	13.559900	-7.37	
	40	Normal	13.559900	-7.37	
	50	Normal	13.559850	-11.06	

5.1.4 Spurious Emission

RESULT:**Passed**

Test standard	:	LP0002(2018) 3.2.1.2
Basic standard	:	LP0002(2018)
Limits	:	Radiated emissions which fall in the restricted bands, as defined in LP0002(2018) 2.8 must comply with the radiated emission limits specified in LP0002(2018) 2.8
		Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2018) 2.8
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Operation mode	:	A
Ambient temperature	:	25.3°C
Relative humidity	:	49%
Atmospheric pressure	:	100-103 kPa

Remark: Testing was carried out within frequency range 9kHz to the tenth harmonic.


For details refer to Appendix D.

5.2 Photographs of the Test Set-Up


Photograph 1: Set-up for Radiated Emissions (Front View)




Photograph 2: Set-up for Radiated Emissions (Back View 1)



Photograph 3: Set-up for Radiated Emissions (Back View 2)



Photograph 4: Set-up for Conducted Test (View 1)



Photograph 5: Set-up for Conducted Test (View 2)



6. List of Tables

Table 1: Applied Standard and Test Levels	4
Table 2: List of Test and Measurement Equipment	6
Table 3: Emission Measurement Uncertainty.....	7
Table 4: Basic Information of EUT	8
Table 5: Technical Specification of EUT	8
Table 6: Test result of Field strength of fundamental and modulation sidebands.....	13
Table 7: Test result of Frequency Stability	14

7. List of Photographs

Photograph 1: Set-up for Radiated Emissions (Front View)	16
Photograph 2: Set-up for Radiated Emissions (Back View 1)	16
Photograph 3: Set-up for Radiated Emissions (Back View 2)	17
Photograph 4: Set-up for Conducted Test (View 1)	17
Photograph 5: Set-up for Conducted Test (View 2)	18