TEST REPORT

Product Name	:	Cute meet 300
Brand Mark	:	eppfun
Model No.	:	LS003
FCC ID	:	2AY3ILS003
Report Number	:	BLA-EMC-202104-A8201
Date of Sample Receipt	:	2021/4/22
Date of Test	:	2021/4/22 to 2021/5/21
Date of Issue	:	2021/6/2
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

Shenzhen Changsheng Technology Co.,Ltd.
4#405 XinggangTongchuanghui, No. 6099 Baoan Avenue, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China 518103

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Jozu

Review by: Sweet. Liang

Approved by: Kmen Li

Date: 2021/6/2

BlueAsia of Technical Services(Shenzhen) Co., Ltd. BLA

REPORT REVISE RECORD

Version No.	Date	Description
00	2021/6/2	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY 5
2 GENERAL INFORMATION 6
3 GENERAL DESCRIPTION OF E.U.T. 6
4 TEST ENVIRONMENT 7
5 TEST MODE 7
6 MEASUREMENT UNCERTAINTY 7
7 DESCRIPTION OF SUPPORT UNIT 8
8 LABORATORY LOCATION 8
9 TEST INSTRUMENTS LIST 9
1 ANTENNA REQUIREMENT 13
1.1 CONCLUSION 13
2 CONDUCTED SPURIOUS EMISSIONS 14
2.1 LIMITS 14
2.2 BLOCK DIAGRAM OF TEST SETUP 14
2.3 TEST DATA 14
3 HOPPING CHANNEL NUMBER 15
3.1 LIMITS 15
3.2 BLOCK DIAGRAM OF TEST SETUP 15
3.3 TEST DATA 15
4 CARRIER FREQUENCIES SEPARATION 16
4.1 LIMITS 16
4.2 BLOCK DIAGRAM OF TEST SETUP 16
4.3 TEST DATA 16
5 20DB BANDWIDTH 17
5.1 BLOCK DIAGRAM OF TEST SETUP 17
5.2 TEST DATA 17
6 CONDUCTED PEAK OUTPUT POWER 18
6.1 LIMITS 18
6.2 BLOCK DIAGRAM OF TEST SETUP 18

BlueAsia

6.3 EST DATA 18

7 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 19

7.1 LIMITS 19
7.2 BLOCK DIAGRAM OF TEST SETUP 19
7.3 PROCEDURE 19
7.4 TEST DATA 21

8 RADIATED SPURIOUS EMISSIONS 23

8.1 LIMITS 23
8.2 BLOCK DIAGRAM OF TEST SETUP 24
8.3 PROCEDURE 24
8.4 TEST DATA 26

9 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 34

9.1 LIMITS 34
9.2 BLOCK DIAGRAM OF TEST SETUP 35
9.3 PROCEDURE 35
9.4 TEST DATA 37

10 CONDUCTED BAND EDGES MEASUREMENT 41

10.1 LIMITS 41
10.2 BLOCK DIAGRAM OF TEST SETUP 41
10.3 TEST DATA 41

11 DWELL TIME 42

11.1 LIMITS 42
11.2 BLOCK DIAGRAM OF TEST SETUP 42
11.3 EST DATA 42

12 APPENDIX 43

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 91

APPENDIX B: PHOTOGRAPHS OF EUT 93

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass

BlueAsia

2 GENERAL INFORMATION

Applicant	Shenzhen Changsheng Technology Co.,Ltd.
Address	4#405 XinggangTongchuanghui, No. 6099 Baoan Avenue, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China 518103
Manufacturer	Shenzhen Changsheng Technology Co.,Ltd.
Address	4#405 XinggangTongchuanghui, No. 6099 Baoan Avenue, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China 518103
Factory	Shenzhen Changsheng Technology Co.,Ltd.
Address	4#405 XinggangTongchuanghui, No. 6099 Baoan Avenue, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China 518103
Product Name	Cute meet 300
Test Model No.	LS003

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	N/A
Software Version	N/A

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	-2dBi(Provided by customer)

BlueAsia

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	3.7Vdc

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
Remark: *Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned Only the GFSK, of the worst mode would be recorded in this report.*	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

BlueAsia

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	HASEE	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Hopping Channel Number					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Carrier Frequencies Separation					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of 20dB Bandwidth					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**

BlueAsia

Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Peak Output Power					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of Radiated Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11

BlueAsia

Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Radiated Emissions which fall in the restricted bands					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A

BlueAsia

Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Dwell Time					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

BlueAsia

1 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

1.1 CONCLUSION

Standard Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -2dBi.



2 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

2.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

2.2 BLOCK DIAGRAM OF TEST SETUP



2.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

3 HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

3.1 LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

3.2 BLOCK DIAGRAM OF TEST SETUP



3.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

4 CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

4.1 LIMITS

Limit:	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

4.2 BLOCK DIAGRAM OF TEST SETUP



4.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

5 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

5.1 BLOCK DIAGRAM OF TEST SETUP



5.2 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

6 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

6.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

6.2 BLOCK DIAGRAM OF TEST SETUP



6.3 EST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

7 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX mode
Test Mode (Final Test)	TX mode
Tester	Jozu
Temperature	25℃
Humidity	60%

7.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

7.2 BLOCK DIAGRAM OF TEST SETUP



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

7.3 PROCEDURE

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

7.4 TEST DATA

[TestMode: TX mode]; [Line: Line][Power:AC120V/60Hz]

Conducted Emission Measurement

File :CE Data :#3 Date: 2021/5/8 Time: 14:57:10



Site Phase: *L1* Temperature:
Limit: FCC Class B Conduction(QP) Power: Humidity: %
EUT: Cute meet 300
M/N: LS003
Mode: BT mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1900	20.89	9.83	30.72	64.04	-33.32	QP	
2		0.1900	15.75	9.83	25.58	54.04	-28.46	AVG	
3		0.5380	26.42	9.87	36.29	56.00	-19.71	QP	
4	*	0.5380	19.87	9.87	29.74	46.00	-16.26	AVG	
5		1.1940	19.07	9.92	28.99	56.00	-27.01	QP	
6		1.1940	13.64	9.92	23.56	46.00	-22.44	AVG	
7		2.7860	14.08	9.97	24.05	56.00	-31.95	QP	
8		2.7860	7.45	9.97	17.42	46.00	-28.58	AVG	
9		6.0340	11.02	10.06	21.08	60.00	-38.92	QP	
10		6.0340	3.88	10.06	13.94	50.00	-36.06	AVG	
11		13.1700	3.74	10.28	14.02	60.00	-45.98	QP	
12		13.1700	-1.63	10.28	8.65	50.00	-41.35	AVG	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX mode]; [Line: Neutral] [Power:AC120V/60Hz]

Conducted Emission Measurement

File :CE Data :#4 Date: 2021/5/8 Time: 15:03:47



Site
Phase: N
Temperature:
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %
EUT: Cute meet 300
M/N: LS003
Mode: BT mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2300	19.97	9.76	29.73	62.45	-32.72	QP	
2		0.2300	14.89	9.76	24.65	52.45	-27.80	AVG	
3		0.4780	21.05	9.79	30.84	56.37	-25.53	QP	
4	*	0.4780	15.40	9.79	25.19	46.37	-21.18	AVG	
5		1.2260	18.27	9.84	28.11	56.00	-27.89	QP	
6		1.2260	12.89	9.84	22.73	46.00	-23.27	AVG	
7		2.0380	13.65	9.86	23.51	56.00	-32.49	QP	
8		2.0380	7.98	9.86	17.84	46.00	-28.16	AVG	
9		4.4580	9.29	9.92	19.21	56.00	-36.79	QP	
10		4.4580	3.59	9.92	13.51	46.00	-32.49	AVG	
11		13.3580	4.55	10.24	14.79	60.00	-45.21	QP	
12		13.3580	-0.54	10.24	9.70	50.00	-40.30	AVG	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

8 RADIATED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

8.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3
Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

BlueAsia

8.2 BLOCK DIAGRAM OF TEST SETUP







8.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.

Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

8.4 TEST DATA

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.

[TestMode: TX lowest channel]; [Polarity: Horizontal]



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	39.98	3.71	43.69	74.00	-30.31	peak			
2		7206.000	39.88	5.96	45.84	74.00	-28.16	peak			
3	*	9608.000	38.96	9.29	48.25	74.00	-25.75	peak			

Test Result: Pass

[TestMode: TX lowest channel]; [Polarity: Vertical]



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	39.27	3.71	42.98	74.00	-31.02	peak			
2		7206.000	38.56	5.96	44.52	74.00	-29.48	peak			
3	*	9608.000	37.81	9.29	47.10	74.00	-26.90	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]

Radiated Emission Measurement

File :RE Data :#3 Date: 2021/5/7 星期 Time: 上午 9:52:01



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4882.000	40.97	3.36	44.33	74.00	-29.67	peak			
2		7323.000	38.55	6.43	44.98	74.00	-29.02	peak			
3	*	9764.000	37.15	9.63	46.78	74.00	-27.22	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]

Radiated Emission Measurement

File :RE Data :#4 Date: 2021/5/7 星期 Time: 上午 9:54:57



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4882.000	40.30	3.36	43.66	74.00	-30.34	peak			
2		7323.000	39.04	6.43	45.47	74.00	-28.53	peak			
3	*	9764.000	37.04	9.63	46.67	74.00	-27.33	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Horizontal]

Radiated Emission Measurement

File :RE Data :#5 Date: 2021/5/7 星期 Time: 上午 9:57:13



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4960.000	40.23	3.75	43.98	74.00	-30.02	peak			
2		7440.000	39.69	6.86	46.55	74.00	-27.45	peak			
3	*	9920.000	36.85	10.16	47.01	74.00	-26.99	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Vertical]

Radiated Emission Measurement

File :RE Data :#6 Date: 2021/5/7 星期 Time: 上午 9:59:09



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4960.000	38.78	3.75	42.53	74.00	-31.47	peak			
2		7440.000	38.53	6.86	45.39	74.00	-28.61	peak			
3	*	9920.000	37.39	10.16	47.55	74.00	-26.45	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

Below 1GHz:

[TestMode: TX]; [Polarity: Vertical]

Radiated Emission Measurement

File :RE Data :#20 Date: 2021/5/7 星期 Time: 下午 12:08:45



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 Class B	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-TX-mode		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	47.3255	3.84	24.42	28.26	40.00	-11.74	QP			
2		55.8047	2.89	23.82	26.71	40.00	-13.29	QP			
3		93.7685	3.45	19.87	23.32	43.50	-20.18	QP			
4		128.1130	1.55	22.80	24.35	43.50	-19.15	QP			
5		197.2001	1.98	20.11	22.09	43.50	-21.41	QP			
6		230.9068	3.92	22.35	26.27	46.00	-19.73	QP			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX]; [Polarity: Horizontal]

Radiated Emission Measurement

File :RE Data :#21 Date: 2021/5/7 星期 Time: 下午 12:10:14



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 Class B	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-TX-mode		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		39.0245	-1.14	23.99	22.85	40.00	-17.15	QP			
2	*	63.3132	2.06	22.61	24.67	40.00	-15.33	QP			
3		141.3298	-1.00	23.18	22.18	43.50	-21.32	QP			
4		196.5098	1.73	20.15	21.88	43.50	-21.62	QP			
5		230.9068	2.11	22.35	24.46	46.00	-21.54	QP			
6		460.7271	-1.07	28.45	27.38	46.00	-18.62	QP			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

9 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

9.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3
Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

BlueAsia

9.2 BLOCK DIAGRAM OF TEST SETUP







9.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

9.4 TEST DATA

[TestMode: *GFSK*]

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.

[TestMode: TX]; [Polarity: Horizontal]



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	52.70	-4.61	48.09	74.00	-25.91	peak			
2		2390.000	52.28	-4.27	48.01	74.00	-25.99	peak			

Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]

Radiated Emission Measurement

File :RE Data :#8 Date: 2021/5/7 星期 Time: 上午 10:07:21



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	52.82	-4.61	48.21	74.00	-25.79	peak			
2		2390.000	51.29	-4.27	47.02	74.00	-26.98	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX]; [Polarity: Horizontal]

Radiated Emission Measurement

File :RE Data :#9 Date: 2021/5/7 星期 Time: 上午 10:11:07



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	60.57	-3.84	56.73	74.00	-17.27	peak			
2	*	2483.500	49.95	-3.84	46.11	54.00	-7.89	AVG			
3		2500.000	51.38	-3.78	47.60	74.00	-26.40	peak			
4		2500.000	37.69	-3.78	33.91	54.00	-20.09	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]

Radiated Emission Measurement

File :RE Data :#11 Date: 2021/5/7 星期 Time: 上午 10:17:16



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Cute meet300	Distance: 3m	
M/N: LS003		
Mode: BT-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	57.27	-3.84	53.43	74.00	-20.57	peak			
2	*	2483.500	55.68	-3.84	51.84	54.00	-2.16	AVG			
3		2500.000	50.20	-3.78	46.42	74.00	-27.58	peak			
4		2500.000	36.37	-3.78	32.59	54.00	-21.41	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

10 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

10.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

11 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

11.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 EST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

12 APPENDIX

12.1 Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	6.374	6.374	21	Pass
NVNT	1-DH1	2441	Ant1	5.763	5.763	21	Pass
NVNT	1-DH1	2480	Ant1	4.785	4.785	21	Pass
NVNT	2-DH1	2402	Ant1	4.03	4.03	21	Pass
NVNT	2-DH1	2441	Ant1	3.452	3.452	21	Pass
NVNT	2-DH1	2480	Ant1	3.353	3.353	21	Pass
NVNT	3-DH1	2402	Ant1	4.654	4.654	21	Pass
NVNT	3-DH1	2441	Ant1	4.064	4.064	21	Pass
NVNT	3-DH1	2480	Ant1	3.348	3.348	21	Pass

Power NVNT 1-DH1 2402MHz Ant1



Power NVNT 1-DH1 2441MHz Ant1



Power NVNT 1-DH1 2480MHz Ant1



Power NVNT 2-DH1 2402MHz Ant1



Power NVNT 2-DH1 2441MHz Ant1



Power NVNT 2-DH1 2480MHz Ant1



Power NVNT 3-DH1 2402MHz Ant1



Power NVNT 3-DH1 2441MHz Ant1



Power NVNT 3-DH1 2480MHz Ant1



12.2 -20dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.948	0	Pass
NVNT	1-DH1	2441	Ant1	0.941	0	Pass
NVNT	1-DH1	2480	Ant1	0.938	0	Pass
NVNT	2-DH1	2402	Ant1	1.332	0	Pass
NVNT	2-DH1	2441	Ant1	1.33	0	Pass
NVNT	2-DH1	2480	Ant1	1.303	0	Pass
NVNT	3-DH1	2402	Ant1	1.282	0	Pass
NVNT	3-DH1	2441	Ant1	1.295	0	Pass
NVNT	3-DH1	2480	Ant1	1.299	0	Pass

-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1



12.3 Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.8324336616
NVNT	1-DH1	2441	Ant1	0.8281797405
NVNT	1-DH1	2480	Ant1	0.8663975176
NVNT	2-DH1	2402	Ant1	1.186044025
NVNT	2-DH1	2441	Ant1	1.186791976
NVNT	2-DH1	2480	Ant1	1.166429347
NVNT	3-DH1	2402	Ant1	1.168177255
NVNT	3-DH1	2441	Ant1	1.16483555
NVNT	3-DH1	2480	Ant1	1.168310249

OBW NVNT 1-DH1 2402MHz Ant1



OBW NVNT 1-DH1 2441MHz Ant1



OBW NVNT 1-DH1 2480MHz Ant1



OBW NVNT 2-DH1 2402MHz Ant1



OBW NVNT 2-DH1 2441MHz Ant1



OBW NVNT 2-DH1 2480MHz Ant1



OBW NVNT 3-DH1 2402MHz Ant1



OBW NVNT 3-DH1 2441MHz Ant1



OBW NVNT 3-DH1 2480MHz Ant1



12.4 Carrier Frequencies Separation

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2441.071	2442.058	0.987	0.941	Pass
NVNT	2-DH1	Ant1	2440.891	2441.89	0.999	0.025	Pass
NVNT	3-DH1	Ant1	2440.891	2441.89	0.999	0.863	Pass

CFS NVNT 1-DH1 2441MHz Ant1



CFS NVNT 2-DH1 2441MHz Ant1



CFS NVNT 3-DH1 2441MHz Ant1



12.5 Number of Hopping Channel

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH1	Ant1	79	15	Pass
NVNT	2-DH1	Ant1	79	15	Pass
NVNT	3-DH1	Ant1	79	15	Pass

Hopping No. NVNT 1-DH1 2402MHz Ant1



Hopping No. NVNT 1-DH1 2441MHz Ant1



Hopping No. NVNT 2-DH1 2441MHz Ant1



Hopping No. NVNT 3-DH1 2441MHz Ant1


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441750000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
05:01:19 PM Apr 27, 2021
Ref Offset 2.03 dB
10 dB/div
Ref 20.00 dBm
Mkr1 2.401 920 5 GHz
1.153 dBm
Start 2.40000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.48350 GHz
Sweep 8.000 ms (1001 pts)
1 N 1 f 2.401 920 5 GHz 1.153 dBm
2 N 1 f 2.480 160 0 GHz -2.511 dBm

12.6 Dwell Time

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.383	121.794	318	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.638	250.614	153	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.884	285.516	99	31600	400	Pass

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst

Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH3 2441MHz Ant1 One Burst



Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
05:04:01 PM Apr 27, 2021
Ref Offset 2.03 dB
10 dB/div
Ref 20.00 dBm
Log
10.0
0.00
-10.0
-20.0
-30.0
-40.0
-50.0
-60.0
-70.0
Center 2.441000000 GHz
Span 0 Hz
Res BW 1.0 MHz
#VBW 3.0 MHz
Sweep 31.60 s (10001 pts)

12.7 Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	No-Hopping	-61.87	-20	Pass
NVNT	1-DH1	2480	Ant1	No-Hopping	-58.83	-20	Pass
NVNT	2-DH1	2402	Ant1	No-Hopping	-57.15	-20	Pass
NVNT	2-DH1	2480	Ant1	No-Hopping	-55.52	-20	Pass
NVNT	3-DH1	2402	Ant1	No-Hopping	-56.74	-20	Pass
NVNT	3-DH1	2480	Ant1	No-Hopping	-53.93	-20	Pass

Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.526000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
04:57:16 PM Apr 27, 2021
Ref Offset 2.08 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.479 9 GHz
0.031 dBm
-21.20 dBm
Start 2.47600 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.57600 GHz
Sweep 9.600 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.479 9 GHz 0.031 dBm
2 N 1 f 2.483 5 GHz -58.540 dBm
3 N 1 f 2.500 0 GHz -57.413 dBm
4 N 1 f 2.487 4 GHz -55.140 dBm
MSG
STATUS

12.8 Band Edge(Hopping)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	Hopping	-60.84	-20	Pass
NVNT	1-DH1	2480	Ant1	Hopping	-58.88	-20	Pass
NVNT	2-DH1	2402	Ant1	Hopping	-56.81	-20	Pass
NVNT	2-DH1	2480	Ant1	Hopping	-55.32	-20	Pass
NVNT	3-DH1	2402	Ant1	Hopping	-55.69	-20	Pass
NVNT	3-DH1	2480	Ant1	Hopping	-55.44	-20	Pass

Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.526000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 2000/2000
05:02:10 PM Apr 27, 2021
Ref Offset 2.08 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.479 1 GHz
-0.240 dBm
-19.62 dBm
Start 2.47600 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.57600 GHz
Sweep 9.600 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.479 1 GHz -0.240 dBm
2 N 1 f 2.483 5 GHz -56.729 dBm
3 N 1 f 2.500 0 GHz -56.128 dBm
4 N 1 f 2.492 1 GHz -55.067 dBm
MSG
STATUS

12.9 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	-45.1	-20	Pass
NVNT	1-DH1	2441	Ant1	-48.7	-20	Pass
NVNT	1-DH1	2480	Ant1	-47.85	-20	Pass
NVNT	2-DH1	2402	Ant1	-50.46	-20	Pass
NVNT	2-DH1	2441	Ant1	-42.3	-20	Pass
NVNT	2-DH1	2480	Ant1	-41.87	-20	Pass
NVNT	3-DH1	2402	Ant1	-42.94	-20	Pass
NVNT	3-DH1	2441	Ant1	-42.05	-20	Pass
NVNT	3-DH1	2480	Ant1	-41.8	-20	Pass

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref



Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref



Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref



Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref



Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref



Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref



Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Ref



Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Ref



Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 13.265000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 10/10
04:57:53 PM Apr 27, 2021
Ref Offset 2.08 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.479 4 GHz
-2.046 dBm
-19.64 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 26.50 GHz
Sweep 2.530 s (30001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.479 4 GHz -2.046 dBm
2 N 1 f 200.3 MHz -41.443 dBm
3 N 1 f 4.994 9 GHz -55.200 dBm
4 N 1 f 7.440 7 GHz -50.196 dBm
5 N 1 f 9.919 2 GHz -51.356 dBm
MSG
STATUS

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Conducted Emissions at AC Power Line (150kHz-30MHz)



Radiated Spurious Emissions





BlueAsia

APPENDIX B: PHOTOGRAPHS OF EUT

Reference to the test report No. BLA-EMC-202104-A8202

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia