

NCC RF Test Report

Report No.: NCC_RF_SL20092201-CRE-023_BT

Test Models: M201923002, M201923003, M201923005, M201923006

Series Model: See section 3.1

Received Date: 01/12/2021

Test Date: 01/13/2021 - 03/12/2021

Issued Date: 03/15/2021

Applicant: Crestron Electronics, Inc.

Address: 15 Volvo Dr Rockleigh, NJ 07647, USA

Manufacturer: Crestron Electronics, Inc.

Address: 15 Volvo Dr Rockleigh, NJ 07647, USA

Issued By: Bureau Veritas Consumer Products Services, Inc.

Lab Address: 775 Montague Expressway, Milpitas, CA 95035

**FCC Registration /
Designation Number:** 540430 / 4842D



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record.....	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty.....	6
2.2 Modification Record.....	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Description of Support Units	12
3.3.1 Configuration of System under Test.....	Error! Bookmark not defined.
3.4 General Description of Applied Standards.....	12
4 Test Types and Results	13
4.1 Radiated Emission and Bandedge Measurement.....	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement.....	13
4.1.2 Test Instruments.....	14
4.1.3 Deviation from Test Standard.....	16
4.1.4 Test Setup.....	16
4.1.5 EUT Operating Conditions.....	17
4.1.6 Test Results	18
4.2 Conducted Emission Measurement	27
4.2.1 Limits of Conducted Emission Measurement	27
4.2.2 Test Instruments.....	27
4.2.3 Test Procedures	28
4.2.4 Deviation From Test Standard	28
4.2.5 Test Setup.....	28
4.2.6 EUT Operating Condition	28
4.2.7 Test Results	29
4.3 Number of Hopping Frequency Used	31
4.3.1 Limits of Hopping Frequency Used Measurement.....	31
4.3.2 Test Setup.....	31
4.3.3 Test Instruments.....	31
4.3.4 Test Procedure	31
4.3.5 Deviation from Test Standard.....	31
4.3.6 Test Results	31
4.4 Dwell Time on Each Channel.....	33
4.4.1 Limits of Dwell Time on Each Channel Measurement.....	33
4.4.2 Test Setup.....	33
4.4.3 Test Instruments.....	33
4.4.4 Test Procedures	33
4.4.5 Deviation from Test Standard.....	33
4.4.6 Test Results	34
4.5 Channel Bandwidth	37
4.5.1 Limits of Channel Bandwidth Measurement.....	37
4.5.2 Test Setup.....	37
4.5.3 Test Instruments.....	37
4.5.4 Test Procedure	37
4.5.5 Deviation from Test Standard.....	37

4.5.6 EUT Operating Condition	37
4.5.7 Test Results	38
4.6 Hopping Channel Separation	39
4.6.1 Limits of Hopping Channel Separation Measurement.....	39
4.6.2 Test Setup.....	39
4.6.3 Test Instruments.....	39
4.6.4 Test Procedure.....	39
4.6.5 Deviation from Test Standard.....	39
4.6.6 Test Results	40
4.7 Maximum Output Power	41
4.7.1 Limits of Maximum Output Power Measurement.....	41
4.7.2 Test Setup.....	41
4.7.3 Test Instruments.....	41
4.7.4 Test Procedure.....	41
4.7.5 Deviation from Test Standard.....	41
4.7.6 EUT Operating Condition	41
4.7.7 Test Results	42
4.8 Conducted Out of Band Emission Measurement.....	43
4.8.1 Limits of Conducted Out of Band Emission Measurement.....	43
4.8.2 Test Instruments.....	43
4.8.3 Test Procedure.....	43
4.8.4 Deviation from Test Standard.....	43
4.8.5 EUT Operating Condition	43
4.8.6 Test Results	43
5 Pictures of Test Arrangements	46
Appendix – Information on the Testing Laboratories.....	47

Release Control Record

Issue No.	Description	Date Issued
NCC_RF_SL20092201-CRE-023_BT	Original Report	03/15/2021

1 Certificate of Conformity

Product: 10.1 & 7 inch Touch Screen Surface/Wall Mount

Brand: Crestron

Test Models: M201923002, M201923003, M201923005, M201923006

Sample Status: Engineering Sample

Applicant: Crestron Electronics, Inc.

Test Date: 01/13/2021 - 03/12/2021

Standards: LP0002: 2020
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services, Inc., Milpitas Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :




Ellen Chu / Test Engineer

Date:

03/15/2021

Approved by :



Gary Chou / Engineer Reviewer

Date:

03/15/2021

2 Summary of Test Results

LP0002			
NCC Clause	Test Item	Result	Remarks
4.10.1.5	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit.
3.3	AC Power Conducted Emission	N/A	Power supplied by POE.
4.10.1.6	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
4.10.1.6	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
4.10.1.6	Channel Bandwidth	PASS	Meet the requirement of limit.
4.10.1.6	Hopping Channel Separation	PASS	Meet the requirement of limit.
4.10.1.2	Maximum Peak Output Power	PASS	Meet the requirement of limit.
4.10.1.5	Conducted Out of Band Emission	PASS	Meet the requirement of limit.
3.2	Antenna Requirement	PASS	The EUT has an internal antenna which is not user accessible

1. If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	3.856 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.638 dB
Radiated Emissions above 1 GHz	Above 1GHz	4.580dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	10.1 & 7 inch Touch Screen Surface/Wall Mount	
Brand	Crestron	
Test Model	M201923002, M201923003, M201923005, M201923006	
Series Model	M201923002	TSW-770-B-S
		TSW-770-W-S
		TSW-770P-B-S
		TSW-770P-W-S
		TSW-770-GV-B-S
		TSW-770-GV-W-S
		TSS-770-B-S
		TSS-770-W-S
		TSW-770R-W
		TSW-770R-B
		TSS-770-T-B-S
		TSS-770-T-W-S
	M201923003	TSW-1070-B-S
		TSW-1070-W-S
		TSW-1070P-B-S
		TSW-1070P-W-S
		TSW-1070-GV-B-S
		TSW-1070-GV-W-S
		TSS-1070-B-S
		TSS-1070-W-S
		TSW-1070R-W
		TSW-1070R-B
		TSS-1070-T-B-S
		TSS-1070-T-W-S
		TSW-1070-B-S-T-V
	M201923005	TS-770-B-S
		TS-770-W-S
		TS-770-GV-B-S
		TS-770-GV-W-S
		TS-770R-W
		TS-770R-B
	M201923006	TS-1070-B-S
		TS-1070-W-S
		TS-1070-GV-B-S
		TS-1070-GV-W-S
		TS-1070R-W
		TS-1070R-B

		TS-1070-B-S-T-V
Model Difference	All models are identical to each other except by their color.	
Status of EUT	Engineering Sample	
Power Supply Rating	Vdc supplied from POE, 48 Vdc, 350mA (802.3af POE Injector)	
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK	
Modulation Technology	FHSS	
Transfer Rate	BDR/EDR: up to 3MB/s	
Operating Frequency	2402~2480MHz	
Number of Channel	79	
Output Power	3.77mW (5.76 dBm)	
Antenna Type	PCB Antenna, -3.92dBi Gain	
Antenna Connector	IPEX	
Accerries	No accerries sold with device	

3.2 Description of Test Modes

79 channels are provided for BT-BDR/EDR mode:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE:

1. The EUT had been pre-tested on the positions of each 3 axis. The worst case was found when positioned on **X-plane**.
2. "-" means no effect.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	GFSK	DH5
-	0 to 78	39	FHSS	8DPSK	3DH5

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	25deg. C, 65%RH	Vdc supplied from POE	Ellen Chu
RE<1G	25deg. C, 65%RH	Vdc supplied from POE	Ellen Chu
APCM	21deg. C, 60%RH	Vdc supplied from POE	Ellen Chu


3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	Dell	Precision 7510	FRYPPC2	N/A	Provided by Customer
B.	POE	I.T.E	PW180KB4800F03	N/A	N/A	Connect from Laptop to EUT

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Cat5E Lan	1	10m	No	0	Connect from EUT to POE

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

LP0002
KDB 558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
EMI Test Receiver Keysight	ESW 44	1328.4100K- 101662-MH	08/30/2020	08/30/2021
Spectrum Analyzer Keysight	N9030B	0240376	06/15/2020	06/15/2021
Hybrid Antenna Sunol	JB1	A030702	09/04/2020	09/04/2021
Horn Antenna ETS-Lindgren	3117	218554	11/22/2020	11/22/2021
Preamplifier RF-Lambda	RAMP00M50GA	17032300048	06/18/2020	06/18/2021
Preamplifier RF Bay, Inc.	LPA-6-30	11170601	04/27/2020	04/27/2021

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

TEST PROCEDURES

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.3 Deviation from Test Standard


No deviation.

4.1.4 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.5 EUT Operating Conditions

- a. Connected the EUT with the Notebook Computer which is placed on remote site.
- b. Controlling software has been activated to set the EUT on specific status.

4.1.6 Test Results

Below 1GHz Data:


BT_GFSK

CHANNEL	TX MODE 2441 MHz	DETECTOR FUNCTION	Quasi Peak
FREQUENCY RANGE	30MHz – 1GHz		

ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m												
No	Freq. [MHz]	Raw (dBuV)	Factor (dB1/m)	Level (dBuV/m)	Measurement Type	Pol	Hgt (cm)	Azt Deg	Limit (dBuV/m)	Margin (dB)	Pass /Fail	
1	29.79	-23.5	0.7	-22.8	Quasi Max	V	233	101.9	40	-68.8	Pass	
2	32.08	-10.4	25.5	15.1	Quasi Max	H	195	313	40	-24.9	Pass	
3	105.712	2.6	17.5	20.1	Quasi Max	H	152	244.5	43.5	-23.4	Pass	
4	548.985	-9.4	25.6	16.2	Quasi Max	H	279	79.6	46	-29.8	Pass	
5	780.248	-8.7	28.7	20	Quasi Max	V	177	0	46	-26	Pass	
6	842.071	-8.9	29.5	20.6	Quasi Max	V	275	165.2	46	-25.4	Pass	

REMARKS:

1. Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
2. Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) –Preamplifier Gain (dB)
3. Margin = Level (dBuV/m) - Limit value (dBuV/m)



BT_8DPSK


CHANNEL	TX MODE 2441 MHz	DETECTOR FUNCTION	Quasi Peak
FREQUENCY RANGE	30MHz – 1GHz		

ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m

No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)	
1	30.68	12.4	25	37.4	Quasi Max	V	100	125.7	40	-2.6	Pass
2	105.66	15.4	17.9	33.3	Quasi Max	V	106	173.1	43.5	-10.2	Pass
3	239.54	12.8	18.3	31.1	Quasi Max	H	134	163.2	46	-14.9	Pass
4	500.009	-2.2	24.8	22.6	Quasi Max	H	106	163.9	46	-23.4	Pass
5	750.005	1.6	28.6	30.2	Quasi Max	V	143	248.8	46	-15.8	Pass
6	875.012	9.3	30.1	39.4	Quasi Max	H	106	118.8	46	-6.6	Pass

REMARKS:

1. Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
2. Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) –Preamplifier Gain (dB)
3. Margin = Level (dBuV/m) - Limit value (dBuV/m)



Above 1GHz Data:

BT_GFSK

CHANNEL	TX MODE 2402 MHz	DETECTOR FUNCTION	Peak Average
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m												
No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail	
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)		
1	11601.09	41.3	3.3	44.6	Peak Max	H	400	101.9	74	-29.4	Pass	
2	3185.147	53.8	-8.9	44.9	Peak Max	V	206.6	279.6	74	-29.1	Pass	
3	2402.047	56.7	-10.1	46.6	Peak Max	V	163.1	356.2	74	-27.4	Pass	
4	11601.09	30.3	3.3	33.6	Average Max	H	400	101.9	54	-20.4	Pass	
5	3185.147	39.7	-8.9	30.8	Average Max	V	206.6	279.6	54	-23.2	Pass	
6	2402.047	51.9	-10.1	41.8	Average Max	V	163.1	356.2	54	-12.2	Pass	

CHANNEL	TX MODE 2441 MHz	DETECTOR FUNCTION	Peak Average
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m											
No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)	
1	3192.387	55.1	-8.9	46.2	Peak Max	V	215.8	302.4	74	-27.8	Pass
2	2123.792	54.7	-10.9	43.8	Peak Max	V	184.3	68.6	74	-30.2	Pass
3	1411.69	57.6	-14.6	43	Peak Max	V	305.7	88.6	74	-31	Pass
4	3192.387	41.6	-8.9	32.7	Average Max	V	215.8	302.4	54	-21.3	Pass
5	2123.792	43	-10.9	32.1	Average Max	V	184.3	68.6	54	-21.9	Pass
6	1411.69	44.3	-14.6	29.7	Average Max	V	305.7	88.6	54	-24.3	Pass

CHANNEL	TX MODE 2480 MHz	DETECTOR FUNCTION	Peak Average
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m											
No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)	
1	4254.109	51.2	-8.4	42.8	Peak Max	H	283	60.5	74	-31.2	Pass
2	3195.305	54.8	-8.9	45.9	Peak Max	H	147	358.9	74	-28.1	Pass
3	1239.164	60.2	-14.2	46	Peak Max	H	238	240.4	74	-28	Pass
4	4254.109	38.9	-8.4	30.5	Average Max	H	283	60.5	54	-23.5	Pass
5	3195.305	40.8	-8.9	31.9	Average Max	H	147	358.9	54	-22.1	Pass
6	1239.164	44.6	-14.2	30.4	Average Max	H	238	240.4	54	-23.6	Pass

REMARKS:

1. Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
2. Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) –Preamplifier Gain (dB)
3. Margin = Level (dBuV/m) - Limit value (dBuV/m)

BT_8DPSK

CHANNEL	TX MODE 2402 MHz	DETECTOR FUNCTION	Peak Average
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m											
No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)	
1	1064.307	61.3	-15.5	45.8	Peak Max	H	100	325.3	74	-28.2	Pass
2	2402.082	57.7	-10.1	47.6	Peak Max	H	193	0.5	74	-26.4	Pass
3	4258.839	51.8	-8.4	43.4	Peak Max	H	100	349	74	-30.6	Pass
4	1064.307	43.2	-15.5	27.7	Average Max	H	100	325.3	54	-26.3	Pass
5	2402.082	53.1	-10.1	43	Average Max	H	193	0.5	54	-11	Pass
6	4258.839	39	-8.4	30.6	Average Max	H	100	349	54	-23.4	Pass

CHANNEL	TX MODE 2441 MHz	DETECTOR FUNCTION	Peak
FREQUENCY RANGE	1GHz ~ 25GHz		Average

ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m											
No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)	
1	4256.731	50.1	-8.4	41.7	Peak Max	H	132	6.9	74	-32.3	Pass
2	1062.149	61.7	-15.5	46.2	Peak Max	H	117	303.1	74	-27.8	Pass
3	3194.868	55.1	-8.9	46.2	Peak Max	H	208	358.8	74	-27.8	Pass
4	4256.731	38.5	-8.4	30.1	Average Max	H	132	6.9	54	-23.9	Pass
5	1062.149	45.8	-15.5	30.3	Average Max	H	117	303.1	54	-23.7	Pass
6	3194.868	40.6	-8.9	31.7	Average Max	H	208	358.8	54	-22.3	Pass

CHANNEL	TX MODE 2480 MHz	DETECTOR FUNCTION	Peak
FREQUENCY RANGE	1GHz ~ 25GHz		Average


ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m											
No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)	
1	1413.618	55.8	-14.6	41.1	Peak Max	H	374	242.2	74	-32.9	Pass
2	4247.972	50.4	-8.5	41.9	Peak Max	H	208	83.4	74	-32.1	Pass
3	1062.537	57.1	-15.5	41.6	Peak Max	H	208	35.9	74	-32.4	Pass
4	1413.618	43.2	-14.6	28.6	Average Max	H	374	242.2	54	-25.4	Pass
5	4247.972	37.6	-8.5	29.1	Average Max	H	208	83.4	54	-24.9	Pass
6	1062.537	44.6	-15.5	29.1	Average Max	H	208	35.9	54	-24.9	Pass

REMARKS:

1. Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
2. Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) –Preamplifier Gain (dB)
3. Margin = Level (dBuV/m) - Limit value (dBuV/m)

RESTRICTED BAND (LOW CHANNEL)

BT_GFSK




ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m

No	Freq. [MHz]	Raw (dBuV)	Factor (dB(1/m))	Level (dBuV/m)	Measurement Type	Pol	Hgt (cm)	Azt Deg	Limit (dBuV/m)	Margin (dB)	Pass /Fail
1	2389.354	20.9	39.1	60	Peak Max	V	247	173.3	74	-14	Pass
4	2389.354	7.3	39.1	46.4	Average Max	V	247	173.3	54	-7.6	Pass

REMARKS:

1. Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
2. Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) -Preamplifier Gain (dB)
3. Margin = Level (dBuV/m) - Limit value(dBuV/m)

RESTRICTED BAND (HIGH CHANNEL)



ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m


No	Freq.	Raw	Factor	Level	Measurement Type	Pol	Hgt	Azt	Limit	Margin	Pass /Fail
	[MHz]	(dBuV)	(dB1/m)	(dBuV/m)			(cm)	Deg	(dBuV/m)	(dB)	
1	2483.985	21	39.6	60.6	Peak Max	V	266	4.2	74	-13.4	Pass
4	2483.985	7.5	39.6	47.1	Average Max	V	266	4.2	54	-6.9	Pass

REMARKS:

- Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
- Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) -Preamplifier Gain (dB)
- Margin = Level (dBuV/m) - Limit value(dBuV/m)

RESTRICTED BAND (LOW CHANNEL)

BT_8PSK




ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m

No	Freq. [MHz]	Raw (dBuV)	Factor (dB(1/m))	Level (dBuV/m)	Measurement Type	Pol	Hgt (cm)	Azt Deg	Limit (dBuV/m)	Margin (dB)	Pass /Fail
1	2310.154	20.5	38.7	59.2	Peak Max	V	294	328.4	74	-14.8	Pass
4	2310.154	7.1	38.7	45.8	Average Max	V	294	328.4	54	-8.2	Pass

REMARKS:

1. Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
2. Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) -Preamplifier Gain (dB)
3. Margin = Level (dBuV/m) - Limit value(dBuV/m)

RESTRICTED BAND (HIGH CHANNEL)



ANTENNA POLARITY & test distance: HORIZONTAL & VERTICAL at 3 m

No	Freq. [MHz]	Raw (dBuV)	Factor (dB1/m)	Level (dBuV/m)	Measurement Type	Pol	Hgt (cm)	Azt Deg	Limit (dBuV/m)	Margin (dB)	Pass /Fail
1	2483.742	21.3	39.6	60.9	Peak Max	H	153	274	74	-13.1	Pass
4	2483.742	7.5	39.6	47.1	Average Max	H	153	274	54	-6.9	Pass

REMARKS:

- Level (dBuV) = Reading (dBuV) + Factor (dB(1/m)).
- Factor (dB(1/m)) = Antenna Factor(AF) (dB(1/m)) + Cable Loss (dB) -Preamplifier Gain (dB)
- Margin = Level (dBuV/m) - Limit value(dBuV/m)

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
EMI Test Receiver, Rohde & Schwarz	ESIB 40	100179	1/29/2021	1/29/2022
Transient Limiter, Electro-Metrics	EM-7600-5	106	12/31/2020	12/31/2021
LISN, ETS-Lindgren	3816/2NM	214372	1/29/2021	1/29/2022

NOTE: N/A

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation From Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition


Same as 4.1.6.

4.2.7 Test Results

Phase	Line (L)	Detector Function					Quasi-Peak / Average			
No	Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line/Neutral	Limit dBuV	Margin dB	Pass /Fail
1	26.62991	39.52	9.89	0.57	49.97	Quasi Peak	Line	60	-10.03	Pass
2	25.75304	38.69	9.86	0.53	49.08	Quasi Peak	Line	60	-10.92	Pass
3	26.91649	38.72	9.9	0.58	49.19	Quasi Peak	Line	60	-10.81	Pass
4	27.49484	38.3	9.9	0.6	48.8	Quasi Peak	Line	60	-11.2	Pass
5	26.3342	38.26	9.88	0.55	48.7	Quasi Peak	Line	60	-11.3	Pass
6	27.78573	38.02	9.91	0.61	48.54	Quasi Peak	Line	60	-11.46	Pass
7	26.62991	37.28	9.89	0.57	47.73	Average	Line	50	-2.27	Pass
8	25.75304	36.56	9.86	0.53	46.95	Average	Line	50	-3.05	Pass
9	26.91649	36.67	9.9	0.58	47.15	Average	Line	50	-2.85	Pass
10	25.75492	36.56	9.86	0.53	46.95	Average	Line	50	-3.05	Pass
11	25.46844	36.79	9.84	0.52	47.16	Average	Line	50	-2.84	Pass
12	28.36784	35.73	9.92	0.63	46.27	Average	Line	50	-3.73	Pass

REMARKS:

1. The emission levels of other frequencies were very low against the limit.
2. Margin value = Emission level - Limit value
3. Emission Level = Correction Factor + Raw Value + Factors Value.




Phase	Neutral(N)	Detector Function	Quasi-Peak / Average
-------	------------	-------------------	----------------------

No	Frequency MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line/Neutral	Limit dBuV	Margin dB	Pass /Fail
1	25.76498	39.06	9.86	0.7	49.62	Quasi Peak	Neutral	60	-10.38	Pass
2	26.63296	39.45	9.89	0.72	50.06	Quasi Peak	Neutral	60	-9.94	Pass
3	26.9149	38.69	9.9	0.73	49.32	Quasi Peak	Neutral	60	-10.68	Pass
4	26.33579	38.35	9.88	0.71	48.95	Quasi Peak	Neutral	60	-11.05	Pass
5	27.79012	38.32	9.91	0.75	48.98	Quasi Peak	Neutral	60	-11.02	Pass
6	27.50249	38.04	9.91	0.74	48.68	Quasi Peak	Neutral	60	-11.32	Pass
7	25.76498	34.61	9.86	0.7	45.17	Average	Neutral	50	-4.83	Pass
8	26.63296	37.42	9.89	0.72	48.03	Average	Neutral	50	-1.97	Pass
9	26.9149	36.25	9.9	0.73	46.88	Average	Neutral	50	-3.12	Pass
10	26.33579	36.42	9.88	0.71	47.01	Average	Neutral	50	-2.99	Pass
11	27.79012	35.8	9.91	0.75	46.45	Average	Neutral	50	-3.55	Pass
12	27.50249	36.07	9.91	0.74	46.72	Average	Neutral	50	-3.28	Pass

REMARKS:

1. The emission levels of other frequencies were very low against the limit.
2. Margin value = Emission level - Limit value
3. Emission Level = Correction Factor + Raw Value + Factors Value.




4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure



- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.




4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 Test Results

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number * 0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS /FAIL
		Period (sec)	Sweep time (sec)	Times in a sweep	Times in a period				
DH1	79	31.6	3.16	32	320	0.413	132.16	400	PASS
DH3	79	31.6	3.16	15	150	1.68	252	400	PASS
DH5	79	31.6	3.16	10	100	2.96	296	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.


8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number * 0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS /FAIL
		Period (sec)	Sweep time (sec)	Times in a sweep	Times in a period				
3DH1	79	31.6	3.16	32	320	0.424	135.68	400	PASS
3DH3	79	31.6	3.16	16	160	1.68	268.8	400	PASS
3DH5	79	31.6	3.16	8	80	2.93	234.4	400	PASS


NOTE: Test plots of the transmitting time slot are shown on next page

GFSK


DH1



DH3




DH5




8DPSK


3DH1



3DH3



3DH5




4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard


No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to Test mode and transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.9954	1.373
39	2441	0.9742	1.359
78	2480	0.9995	1.379




4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.


4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)		20dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.004	1.005	0.9954	1.373	0.66	0.92	Pass
39	2441	1.020	1.005	0.9742	1.359	0.65	0.91	Pass
78	2480	1.008	1.005	0.9995	1.379	0.67	0.92	Pass

NOTE: The minimum limit is two-third 20dB bandwidth.




4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 1W.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation from Test Standard


No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

Channel	Frequency (MHZ)	Output Power (mW)		Output Power (dBm)		Power Limit (W)	Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	3.71	3.77	5.69	5.76	1	Pass
39	2441	3.20	3.22	5.05	5.08	1	Pass
78	2480	2.65	2.69	4.24	4.30	1	Pass



4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits of Conducted Out of Band Emission Measurement

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.



4.8.5 EUT Operating Condition

The software provided by client enabled the EUT to test mode and transmit and receive data at lowest, middle and highest channel frequencies individually.


4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, Mark 2 indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK



8DPSK



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

Bureau Veritas is a global leader in testing, inspection and certification (TIC) services. We help businesses improve safety, sustainability and productivity; and our clients include the majority of leading brands in retail, manufacturing and other industries. With a presence in every major country around the world, our quality assurance and compliance solutions are vital in helping our customers enhance product quality and concept-to-consumer journeys. We also assist with increasing speed to market, profitability and brand equity throughout the supply chain. Bureau Veritas is a leading wireless/IoT testing, inspection, audit and certification provider, with a global network of test laboratories to support the IoT industry in areas of connectivity, security, interoperability as well as quality, health & safety, and environmental/chemical requirements.

If you have any comments, please feel free to contact us at the following:

Milpitas EMC/RF/Safety/Telecom Lab

775 Montague Expressway, Milpitas, CA 95035
Tel: +1 408 526 1188

Sunnyvale OTA/Bluetooth Lab

1293 Anvilwood Avenue, Sunnyvale, CA 94089
Tel: +1 669 600 5293

Littleton EMC/RF/Safety/Environmental Lab

1 Distribution Center Cir #1, Littleton, MA 01460
Tel: +1 978 486 8880

Email: sales.eaw@us.bureauveritas.com

Web Site: www.cpsusa-bureauveritas.com

The address and road map of all our labs can be found in our web site also.

--- END ---