



RF TEST REPORT

Product Name: Wireless Mechanical Keyboard

Model Number: Node75-LP-JIS

Issued For : Shenzhen NuPhy Technology Co., LTD

3820 Baoshan Times Building, Minqiang Community, Minzhi
Street, Longhua District, Shenzhen, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT25L396RF02

Sample Received Date: Mar. 05, 2026

Date of Test: Mar. 06, 2026 ~ Mar. 16, 2026

Date of Issue: Mar. 16, 2026

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.

Shenzhen LGT Test Service Co., Ltd. Tel: 0755-89668180 E-mail: lgt@lgt-cert.com Web: www.lgt-cert.com
Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District,
Shenzhen, Guangdong, China



TEST REPORT CERTIFICATION

Applicant: Shenzhen NuPhy Technology Co., LTD
Address: 3820 Baoshan Times Building, Minqiang Community, Minzhi Street,
Longhua District, Shenzhen, China
Manufacturer: SHENZHEN ARBITER TECHNOLOGY CO., LTD
Address: Floor 2, 3 and 4, Bldg. A, Meisheng Industrial Park, Chongqing Rd.,
Fuhai St., Baoan Dist., Shenzhen, Guangdong
Product Name: Wireless Mechanical Keyboard
Trademark: NuPhy
Model Number: Node75-LP-JIS
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
Article 2 Paragraph 1 of Item 19, annex 43 and annex 1, MIC Notice No.88 Appendix No.43	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Manager





Table of Contents

1. SUMMARY OF TEST RESULTS	6
1.1 TEST LABORATORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TABLE FOR PARAMETERS OF THE TEST SOFTWARE SETTING	10
2.4 TEST CONDITIONS	10
2.5 TEST ENVIRONMENTAL	10
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3. FREQUENCY ERROR	13
3.1 LIMIT	13
3.2 TEST PROCEDURES	13
3.3 TEST SETUP	13
3.4 TEST RESULT	13
4. ANTENNA POWER	14
4.1 LIMIT	14
4.2 TEST PROCEDURE	14
4.3 TEST SETUP	14
4.4 TEST DEVIATION	14
4.5 TEST RESULT	14
5. RADIATION POWER	15
5.1 LIMIT	15
5.2 TEST RESULT	15
6. OCCUPIED BANDWIDTH (99%) & SPREAD BANDWIDTH (90%)	16
6.1 LIMIT	16
6.2 TEST PROCEDURE	16
6.3 TEST SETUP	16
6.4 TEST DEVIATION	16
6.5 TEST RESULT	16
7. UNWANTED EMISSION INTENSITY MEASUREMENT	17
7.1 LIMIT	17
7.2 TEST PROCEDURE	17
7.3 TEST SETUP	18
7.4 TEST DEVIATION	18
7.5 TEST RESULT	18



8. DWELL TIME	19
8.1 LIMIT	19
8.2 TEST PROCEDURES	19
8.3 TEST SETUP	19
8.4 TEST RESULT	19
9. IMITATION OF COLLATERAL EMISSION OF RECEIVER MEASUREMENT	20
9.1 LIMIT	20
9.2 TEST PROCEDURES	20
9.3 TEST RESULT	20
10. TRANSMISSION RADIATION ANGLE WIDTH (3DB BEAMWIDTH) MEASUREMENT	21
10.1 LIMIT	21
10.2 TEST PROCEDURES	21
10.3 TEST SETUP	21
10.4 TEST DEVIATION	21
10.5 TEST RESULT	21
11. RADIO INTERFERENCE PREVENTION CAPABILITY MEASUREMENT	22
11.1 LIMIT	22
11.2 MEASURING ID CODE SOFTWARE	22
11.3 TEST PROCEDURES	22
11.4 TEST SETUP	22
11.5 TEST DEVIATION	22
11.6 EUT OPERATION DURING TEST	22
11.7 TEST RESULT OF RADIO INTERFERENCE PREVENTION CAPABILITY	22
APPENDIX I - TEST RESULTS	23
FREQUENCY ERROR	23
ANTENNA POWER	25
EIRP POWER	26
OCCUPIED CHANNEL BANDWIDTH	27
SPREADING BANDWIDTH	29
TX SPURIOUS EMISSION	31
RX SPURIOUS EMISSION	37
APPENDIX II - TEST SETUP PHOTOS	41
APPENDIX III - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	42



Revision History

Rev.	Issue Date	Contents
00	Mar. 16, 2026	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards: STD-T66 V3.7 and MIC Notice No.88 Appendix No.43.

Rule Section	Description of Test	Judgement
3.2(4)	Frequency Error	PASS
3.2(7)&(8)	Occupied Bandwidth(99%)&Spread-spectrum Bandwidth(90%)	PASS
3.2(6)	Unwanted Emission Intensity	PASS
3.2(3)	Power Error	PASS
3.3	Limitation of Collateral Emission of Receiver	PASS
3.6	Transmission Radiation Power	PASS
3.6	Transmission Radiation Angle Width (3dB Beamwidth)	N/A
3.4	Radio Interference Prevention Capability	PASS
3.2(9)	Spreading Factor	PASS
3.2(11)	Dwell Time	N/A
Note(2)	Carrier Sense Capability	N/A
3.7 Note(3)	Construction Protection Confirmation	PASS

Note:

- (1) "N/A" means test is not applicable in this Test Report.
- (2) Article 2 Paragraph 1 of Item 19, annex 43 and annex 1.
- (3) Please refer to Japan Radio Protection Declaration.



1.1 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

No.	Item	Uncertainty
1	RF Output Power, Conducted	$\pm 0.71\text{dB}$
2	Conducted emission	$\pm 2.80\text{dB}$
3	Temperature	$\pm 0.5^{\circ}\text{C}$

Note: The measurement uncertainty is not included in the test result.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Wireless Mechanical Keyboard	
Test Model Number:	Node75-LP-JIS	
Series Number:	N/A	
Model Difference:	N/A	
Product Description:	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Number Of Channel:	40CH
	Antenna Designation:	Chip Antenna
	Antenna Gain(dBi):	1.62dBi
	Based on the application, features, or specification exhibited in User Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User Manual.	
Channel List:	Please refer to the Note 5.	
Rating:	Input: DC 5V	
Battery:	Capacity: 3000mAh Rated Voltage: 3.7V	
Hardware Version:	VER1.2	
Software Version:	V1.0.7.6	
Connecting I/O Port(s):	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



5.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	--	--
13	2428	27	2456	--	--

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Lowest frequency		Middle frequency		Highest frequency	
00	2402	19	2440	39	2480



2.2 DESCRIPTION OF THE TEST MODES

Pretest Mode	Description
Mode 1	GFSK (CH00 CH19 CH39)

2.3 TABLE FOR PARAMETERS OF THE TEST SOFTWARE SETTING

Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
2.4G	GFSK	1.62	0	RFTTest_0901_boxed V1.0.7.6

2.4 TEST CONDITIONS

Power Supply Voltage Fluctuation Test

Voltage Fluctuation Test	Normal Voltage	High Voltage	Low Voltage
Input DC Power(V)	3.7	4.07	3.33
RF Chip Input DC Power(V)	3.300	3.331	3.281
Voltage Variation (%)	/	0.94	-0.58

Note: 1. Voltage Variation (%)

= (RF chip Input high or Low Voltage - RF chip Input Normal Voltage)/ RF chip Input Normal Voltage* 100

2. RF chip Input DC power fluctuation is verified at the power input PIN of the RF chip.

When the input supply voltage to the EUT from the external power source is varied by +/- 10%, the output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/-1%, and the DC power fluctuation at the power input PIN of the RF chip is equal to or less than +/-1%.Exempt extremely high and low supply voltage condition tests, EUT only operated in normal voltage to test all regulations.

2.5 TEST ENVIRONMENTAL

During the measurement the environmental conditions

Normal Temperature: 24.5°C

Relative Humidity: 53 %

Air Pressure: 101.78 kPa



2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating

Auxiliary Equipment for RF

Description	Manufacturer	Model	S/N	Rating
N/A	N/A	N/A	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until	Classification
Signal Analyzer	Keysight	N9010B	MY60242508	2026-03-03	2027-03-02	(c)
Signal Analyzer	Keysight	N9020A	MY50530994	2026-03-02	2027-03-01	(c)
RF Automatic Test system	MW	MW100-R FCB	MW220324LG-33	2026-03-03	2027-03-02	(c)
MXG Vector Signal Generator	Keysight	N5182B	MY59100717	2026-03-03	2027-03-02	(c)
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2025-07-30	2026-07-29	(c)
Attenuator	eastsheep	90db	N.A	2026-03-02	2027-03-01	(c)
Temperature & Humidity	JINGCHUAN G	BT-3	N.A	2026-03-05	2027-03-04	(c)
Digital multimeter	MASTECH	MS8261	MBGBC83053	2025-07-30	2026-07-29	(c)
DC source	Keysight	E3634A	MY58036468	2026-03-05	2027-03-04	(c)

Remark:

Notice: Calibration duration for above equipments is 1 year.

Test Equipment Calibration

All of the test equipment is effective use and calibration certification institution, LISAI, the address is No.8.South Street Shi li institute Guangzhou.Guangdong.China



3. FREQUENCY ERROR

3.1 LIMIT

Item	Limits
Frequency Error	$\pm 50\text{ppm}$

3.2 TEST PROCEDURES


The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	10KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

- (1) In the case of unmodulated signal (continuous or continuous burst), measure the frequency directly by a frequency meter.
- (2) In the case of burst waves, the measurement shall be done for enough time in order to obtain the enough measuring accuracy, and the average of the measured values becomes the final value.
- (3) In the case of a test mode with a specific frequency spectrum, measure the frequency of the specific spectrum by a spectrum analyzer.
- (4) In the cases above, if the frequency equivalent to the test frequency is not directly measured in principle, it shall be obtained by necessary calculation.

In the case of modulated signal, if there is no specific spectrum measurable by a spectrum analyzer but a specific dip is observed, it is allowed to measure the frequency with the signal generator (synthesized). That is, observe a signal of the signal generator concurrently (or alternately) with the tested signal using the spectrum analyzer while setting the frequency of the signal generator to the position of the dip on the screen of the spectrum analyzer, and determine the frequency of the signal generator at the time as a measured value.

3.3 TEST SETUP



3.4 TEST RESULT

For the measurement records, refer to the appendix I.



4. ANTENNA POWER


4.1 LIMIT

Item	Limits
Antenna Power Density	$\leq 3\text{mW/MHz}$ (FH,FH+DS,FH+OFDM form 2400 – 2483.5 MHz) $\leq 10\text{mW/MHz}$ (OFDM,DS from 2400~2483.5MHz, 26MHz) $\leq 5\text{mW/MHz}$ (OFDM,DS from 2400~2483.5MHz, 40MHz) $\leq 10\text{mW}$ (Other from 2400~2483.5MHz)
Power Error	+20%, -80% (Base on manufacturer declare power)

4.2 TEST PROCEDURE

1. EUT turn to test frequency channel and keep continuous transmitting.
2. Reading the output power from the Power meter as P_{EUT} .
3. Turn the Signal generator to frequency channel the same as the EUT.
4. Turn the level of Signal generator, scan with the power meter until the power equal to P_{EUT} , the level of Signal generator recorded as "P".
5. The antenna power of EUT is "P".
6. EIRP power = "P"+antenna gain.

4.3 TEST SETUP



4.4 TEST DEVIATION

There is no deviation with the original standard.

4.5 TEST RESULT

For the measurement records, refer to the appendix I.



5. RADIATION POWER

5.1 LIMIT

Item	Limits
Radiation power EIRP	FH or FH+DS or FH+OFDM from 2400 – 2483.5 MHz ,EIRP $\leq$ 6.91dBm/MHz CCK/OFDM/DBPSK (2400~2483.5MHz) OFDM or DS other than (20MHz) EIRP $\leq$ 12.14 dBm/MHz OFDM or DS other than (40MHz) EIRP $\leq$ 9.13dBm/MHz Other from 2400~2483.5MHz: 12.14 dBm or less

5.2 TEST RESULT

For the measurement records, refer to the appendix I.



6. OCCUPIED BANDWIDTH (99%) & SPREAD BANDWIDTH (90%)


6.1 LIMIT

Item	Limits
Occupied Band Width:	≤83.5MHz (FH,FH+DS,FH+OFDM) ≤26MHz (Others)
Spreading Bandwidth:	≥500 kHz (DS,FH,FH+DS,FH+OFDM)

6.2 TEST PROCEDURE

1. Setting of SA is following as: GFSK RB: 1MHz / VB: 1MHz / SPAN: 83.5MHz / AT: 25dB Ref: 10dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold.
2. EUT have transmitted the maximum modulation signal and fixed channelize (For DSSS or OFDM Device) or continuous maximum power of hopping mode (For FHSS Device). SA set to 99% of occupied bandwidth to measure occupied bandwidth. The limit is less than 26MHz (For FH or OFDM Device) or 83.5MHz (For FHSS Device).
3. SA set to 90% of occupied bandwidth to measure Spread Spectrum Bandwidth and must greater than 500kHz.
4. Spread Spectrum Factor = Spread Spectrum Bandwidth / modulation rate of EUT.
5. Spread Spectrum Factor limit is greater than 5.

6.3 TEST SETUP



6.4 TEST DEVIATION

There is no deviation with the original standard.

6.5 TEST RESULT

For the measurement records, refer to the appendix I.



7. UNWANTED EMISSION INTENSITY MEASUREMENT

7.1 LIMIT

Item	Limits
TX Spurious Emission	$\leq 2.5 \mu\text{W/MHz}$ ($30\text{MHz} \leq f \leq 1000\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($1000\text{MHz} < f \leq 2387\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2387\text{MHz} < f \leq 2400\text{MHz}$)
	$\leq 25 \mu\text{W/MHz}$ ($2483.5\text{MHz} \leq f < 2496.5\text{MHz}$)
	$\leq 2.5 \mu\text{W/MHz}$ ($2496.5\text{MHz} \leq f < 12500\text{MHz}$)

7.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	30-1000MHz: 100KHz/100KHz
	Above 1GHz: 1 MHz/1 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

1. Set EUT to transmitted the maximum modulation signal and hopping frequency continuous transmission mode.
2. Setting of SA is following as: Below 1GHz RB: 100KHz / VB: 100KHz, Above 1GHz RB: 1MHz / VB: 1MHz / AT: 10dB Ref: 0dBm / Sweep time: Auto/ Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. Setting of SA is following as 30MHz and stop frequency 1000MHz. Then to mark peak reading value + cable loss shall be less than 2.5 μ W.
4. Setting of SA is following as 1000MHz and stop frequency 2387MHz. Then to mark peak reading value + cable loss shall be less than 2.5 μ W.
5. SA adjusted to start frequency 2387MHz and stop frequency 2400MHz. Then to mark peak reading value + cable loss shall be less than 25 μ W.
6. SA adjusted to start frequency 2483.5MHz and stop frequency 2496.5MHz. Then to mark peak reading value + cable loss shall be less than 25 μ W.
7. SA adjusted to start frequency 2496.5MHz and stop frequency 12750MHz. Then to mark peak reading value + cable loss shall be less than 2.5 μ W.
8. When we tested 30MHz-1GHz, we used the RB 100KHz setting for the test. The limit on the test chart was converted. The conversion formula: $-26\text{dBm} + 10 \cdot \log(100\text{K}/1\text{M}) = -36\text{dBm}$.
9. If the Result_Value is over the requirement, take total sum of 1MHz band centered at the spur frequency like ACLP measurement as Result_Value.

Test frequency for reading points:

1. Set the test frequency point to the center frequency, RB: 1MHz / VB: 1MHz, SPAN: 0MHz, Sweep time: Minimum time in which measurement accuracy is guaranteed, Detect mode: RMS / Trace mode: Single
2. Set the spectrometer to Band Power, integrate the average power of the frequency point, and obtain the final result value.



7.3 TEST SETUP



7.4 TEST DEVIATION

There is no deviation with the original standard.

7.5 TEST RESULT

For the measurement records, refer to the appendix I.



8. DWELL TIME

8.1 LIMIT


Item	Limits
Hopping Freq. Dwell Time	$\leq 0.4 \text{ sec (In } 0.4 \text{ sec} \times \text{ spreading rate)}$ $\leq 0.05 \text{ sec (one pulse)}$

8.2 TEST PROCEDURES

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	0 MHz
RB	1 MHz
VB	1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Continuous

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for GFSK packet transmitting.
- Measure the maximum time duration of one single pulse.
- Dwell time = [spreading rate/16] x duty-cycle x 0.4 seconds.

8.3 TEST SETUP



8.4 TEST RESULT

N/A.

The prototype adopts FHSS+DSSS hybrid technology and does not require testing.



9. IMITATION OF COLLATERAL EMISSION OF RECEIVER MEASUREMENT

9.1 LIMIT

Item	Limits
RX Spurious Emission:	$\leq 4\text{nW}$ ($f < 1\text{GHz}$)
	$\leq 20\text{nW}$ ($1\text{GHz} \leq f$)

9.2 TEST PROCEDURES

Spectrum Parameter	Setting
Attenuation	Auto
RB	100 kHz (below 1GHz emissions) 1 MHz (above 1GHz emissions)
VB	100 kHz (below 1GHz emissions) 1 MHz (above 1GHz emissions)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

1. Set EUT to hopping frequency continuous reception mode.
2. Setting of SA is following as RB / VB: 100 kHz (below 1GHz emissions) / 1 MHz (above 1GHz emissions) / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. SA set RB: 100kHz and VB: 100kHz. Then adjust to start frequency 30MHz and stop frequency 1000MHz. Search to mark peak reading value + cable loss shall be less than 4nW
4. SA set RB: 1MHz and VB: 1MHz. Then adjust to start frequency 1000MHz and stop frequency 12500MHz. Search to mark peak reading value + cable loss shall be less than 20nW
5. If power level of lower emissions are more than 1/10 of limit (.0.4nW for $f < 1\text{GHz}$, 2nW for $f \geq 1\text{GHz}$), all those are to be indicated in the 2nd and 3rd lines. If others are 1/10 or less more of the limit, no necessary to be indicated.

9.3 TEST RESULT

For the measurement records, refer to the appendix I.



10. TRANSMISSION RADIATION ANGLE WIDTH (3DB BEAMWIDTH) MEASUREMENT

10.1 LIMIT


Item	Limits
3dB antenna beam width	$e \leq 360/A$ (The A is 10 in maximum) $A = \{EIRP \text{ Power [mW/MHz]} / \{2.14dBi + \text{output power (10mW /MHz, 3mW/MHz)}\}\}$ Shall be 1 when A is lower than 1

10.2 TEST PROCEDURES

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	0 MHz
RB	1 MHz
VB	1 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

1. Set EUT and measuring antenna at the same height and roughly facing each other.
2. Set spectrum analyzer with condition in section 11.2 and tune reference level to observe receiving signal position.
3. Rotate directions of the EUT horizontally and vertically to find the maximum receiving power.
4. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of EUT height and swing it to find the maximum output of measuring antenna. "E" is the half-power beam width (angle between two points at which radiated power becomes 1/2)
5. Calculate permitted radiation angle in horizontal and vertical using EIRP measured in another test method.
6. Calculate 3dB antenna beam width by the formula below $360/A$ (If $A < 1$; then $A = 1$).
 $A = \{EIRP \text{ Power [mW/MHz]} / \{2.14dBi + \text{output power (10mW /MHz, 3mW/MHz)}\}\}$
Shall be 1 when A is lower than 1

10.3 TEST SETUP



10.4 TEST DEVIATION

There is no deviation with the original standard.

10.5 TEST RESULT

As the EUT max EIRP is less than 6.91dBm/MHz, so the test is not applicable and skipped.



11. RADIO INTERFERENCE PREVENTION CAPABILITY MEASUREMENT

11.1 LIMIT

Item	Limits
Identification code	≥ 48 bits


11.2 MEASURING ID CODE SOFTWARE

Item	Limits
MAC IP List	MAC Scan

11.3 TEST PROCEDURES

- In the case that the EUT has the function of automatically transmitting the identification code:
 - Transmit the predetermined identification codes from EUT.
 - Check the transmitted identification codes with the demodulator.
- In the case of receiving the identification code:
 - Transmit the predetermined identification codes from the counterpart.
 - Check if communication is normal.
 - Transmit the signals other than predetermined ID codes from the counterpart.
 - check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

11.4 TEST SETUP



11.5 TEST DEVIATION

There is no deviation with the original standard.

11.6 EUT OPERATION DURING TEST

The EUT was programmed to be in normal transmitting mode.




11.7 TEST RESULT OF RADIO INTERFERENCE PREVENTION CAPABILITY

The MAC address is A3:E3:C2:72:2B:3B.



APPENDIX I - TEST RESULTS

Frequency Error							
Condition	Mode	Frequency (MHz)	Measured Frequency (MHz)	Frequency Error (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
NVNT	2.4G	2402	2401.98	-20000	-8.33	±50	Pass
NVNT	2.4G	2440	2439.98	-20000	-8.2	±50	Pass
NVNT	2.4G	2480	2479.98	-20000	-8.06	±50	Pass





Antenna Power

Condition	Mode	Frequency (MHz)	Power (dBm)	Antenna Power (mW)	Limit (mW)	Declared Power (mW)	Tolerance (%)	Upper Limit (%)	Verdict
NVNT	2.4G	2402	0.81	1.205	10	2	-39.75	20	Pass
NVNT	2.4G	2440	0.91	1.233	10	2	-38.35	20	Pass
NVNT	2.4G	2480	0.6	1.148	10	2	-42.6	20	Pass






EIRP Power

Condition	Mode	Frequency (MHz)	Antenna Power (dBm)	Gain (dBi)	EIRP Power (dBm)	Limit (dBm)	Verdict
NVNT	2.4G	2402	0.81	1.62	2.43	12.14	Pass
NVNT	2.4G	2440	0.91	1.62	2.53	12.14	Pass
NVNT	2.4G	2480	0.6	1.62	2.22	12.14	Pass



Occupied Channel Bandwidth




Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	2.4G	2402	1.486
NVNT	2.4G	2440	1.339
NVNT	2.4G	2480	1.292





Spreading Bandwidth


Condition	Mode	Frequency (MHz)	90% OBW (MHz)	Limit (MHz)	Verdict
NVNT	2.4G	2402	0.876	0.5	Pass
NVNT	2.4G	2440	0.876	0.5	Pass
NVNT	2.4G	2480	0.844	0.5	Pass














Tx Spurious Emission




Condition	Mode	Frequency (MHz)	Range (MHz)	Emission Frequency (MHz)	Max Peak Value (dBm)	Max RMS Value (dBm)	Max Peak Value (uW)	Max RMS Value (uW)	Limit Start(uW)	Limit Stop (uW)	Verdict
NVNT	2.4G	2402	30-1000	157.07	-51.48	NA	0.0071	NA	2.5	2.5	Pass
NVNT	2.4G	2402	1000-2387	2385.61	-34.53	NA	0.3524	NA	2.5	2.5	Pass
NVNT	2.4G	2402	2387-2400	2399.94	-23.04	NA	4.9659	NA	25	25	Pass
NVNT	2.4G	2402	2483.5-2496.5	2496.49	-56.12	NA	0.0024	NA	25	25	Pass
NVNT	2.4G	2402	2496.5-13000	7202.07	-30.11	NA	0.975	NA	2.5	2.5	Pass
NVNT	2.4G	2440	30-1000	157.07	-52.78	NA	0.0053	NA	2.5	2.5	Pass
NVNT	2.4G	2440	1000-2387	2374.52	-50.85	NA	0.0082	NA	2.5	2.5	Pass
NVNT	2.4G	2440	2387-2400	2392.06	-44.31	NA	0.0371	NA	25	25	Pass
NVNT	2.4G	2440	2483.5-2496.5	2487.80	-49.07	NA	0.0124	NA	25	25	Pass
NVNT	2.4G	2440	2496.5-13000	7317.61	-31.11	NA	0.7745	NA	2.5	2.5	Pass
NVNT	2.4G	2480	30-1000	157.07	-51.97	NA	0.0064	NA	2.5	2.5	Pass
NVNT	2.4G	2480	1000-2387	2352.32	-55.18	NA	0.003	NA	2.5	2.5	Pass
NVNT	2.4G	2480	2387-2400	2399.94	-48.74	NA	0.0134	NA	25	25	Pass
NVNT	2.4G	2480	2483.5-2496.5	2483.57	-34.39	NA	0.3639	NA	25	25	Pass
NVNT	2.4G	2480	2496.5-13000	7443.65	-32.54	NA	0.5572	NA	2.5	2.5	Pass





















Rx Spurious Emission

Condition	Mode	Frequency (MHz)	Range (MHz)	Emission Frequency (MHz)	Max Peak Value (dBm)	Max RMS Value (dBm)	Max Peak Value (nW)	Max RMS Value (nW)	Limit (nW)	Verdict
NVNT	2.4G	2402	30-1000	235.64	-73.61	NA	0.0436	NA	4	Pass
NVNT	2.4G	2402	1000-13000	2440.00	-53.08	-56.77	4.9204	2.1038	20	Pass
NVNT	2.4G	2440	30-1000	156.10	-72.07	NA	0.0621	NA	4	Pass
NVNT	2.4G	2440	1000-13000	2416.00	-60.82	NA	0.8279	NA	20	Pass
NVNT	2.4G	2480	30-1000	31.94	-74.56	NA	0.035	NA	4	Pass
NVNT	2.4G	2480	1000-13000	2440.00	-50.15	-55.53	9.6605	2.799	20	Pass










APPENDIX II - TEST SETUP PHOTOS





APPENDIX III - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Note: Please see the attached Node75-LP-JIS_EUT Photos.

※※※※END OF THE REPORT※※※※