

TEST REPORT

Reference No..... : WTX25X10277554W001
Applicant : ShenZhen Rapoo Technology Co., Ltd.
Address : 22, Jinxiu Road East, Pingshan District, Shenzhen, China
Manufacturer : ShenZhen Rapoo Technology Co., Ltd.
Address : 22, Jinxiu Road East, Pingshan District, Shenzhen, China
Product Name : Multi-mode Wireless Keyboard
Model No..... : 0212N-01
Standards : Item 19 of Article 2 Paragraph 1
Date of Receipt sample : 2025-10-22
Date of Test..... : 2025-10-24 to 2025-11-18
Date of Issue : 2025-11-21
Test Report Form No. : WTX_Item 19_2_1W
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Gala Wang/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TEST FACILITY	6
1.5 EUT SETUP AND TEST MODE	7
1.6 TEST CONDITIONS	8
1.7 MEASUREMENT UNCERTAINTY	9
1.8 TEST EQUIPMENT LIST AND DETAILS	10
1.9 CALIBRATION INFORMATION	10
2. SUMMARY OF TEST RESULTS	11
3. RF OUTPUT POWER	12
3.1 STANDARD APPLICABLE	12
3.2 TEST SETUP BLOCK DIAGRAM	12
3.3 TEST PROCEDURE	12
3.4 SUMMARY OF TEST RESULTS/PLOTS	12
4. FREQUENCY TOLERANCE	13
4.1 STANDARD APPLICABLE	13
4.2 TEST SETUP BLOCK DIAGRAM	13
4.3 TEST PROCEDURE	13
4.4 SUMMARY OF TEST RESULTS/PLOTS	13
5. OCCUPIED BANDWIDTH	14
5.1 STANDARD APPLICABLE	14
5.2 TEST SETUP BLOCK DIAGRAM	14
5.3 TEST PROCEDURE	14
5.4 SUMMARY OF TEST RESULTS/PLOTS	15
6. TRANSMITTER SPURIOUS EMISSIONS	16
6.1 STANDARD APPLICABLE	16
6.2 TEST SETUP BLOCK DIAGRAM	16
6.3 TEST PROCEDURE	16
6.4 SUMMARY OF TEST RESULTS/PLOTS	16
7. RECEIVER SPURIOUS EMISSIONS	17
7.1 STANDARD APPLICABLE	17
7.2 TEST SETUP BLOCK DIAGRAM	17
7.3 TEST PROCEDURE	17
7.4 SUMMARY OF TEST RESULTS/PLOTS	17
8. INTERFERENCE PREVENTION FUNCTION	18
8.1 STANDARD APPLICABLE	18
8.2 TEST SETUP BLOCK DIAGRAM	18
8.3 TEST PROCEDURE	18
8.4 SUMMARY OF TEST RESULTS/PLOTS	18
APPENDIX SUMMARY	19
APPENDIX A	20
APPENDIX B	21
APPENDIX C	24
APPENDIX D	27
APPENDIX E	38
APPENDIX F	43
APPENDIX PHOTOGRAPHS	44

Reference No.: WTX25X10277554W001

Version No.	Date of issue	Description
Rev.00	2025-11-21	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Multi-mode Wireless Keyboard
Trade Name:	RAPOO
Model No.:	0212N-01
Adding Model(s):	E9050L, E9350L, E9710M, 0212R-01, E9610M, E9550L, E9810M, 0212T-01
Rated Voltage:	Battery DC 3.7V
Battery Capacity:	500mAh
Power Adapter:	/
Hardware version:	V1.1
Software version:	V2.4.8
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model 0212N-01, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth	
Bluetooth Version:	V5.0(LE mode)
Frequency Range:	2402-2480MHz
Max.RF Rated Output	1Mbps:0.8mW 2Mbps:0.8mW
Type of Modulation:	GFSK
Data Rate:	1Mbps, 2Mbps
Quantity of Channels	40
Channel Separation:	2MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	-5.68dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

Reference No.: WTX25X10277554W001

➤ Center Frequency of Each of Channel:

LE	
Channel	Frequency (MHz)
00	2402
01	2404
⋮	⋮
19	2440
⋮	⋮
38	2478
39	2480

1.2 Test Standards

The tests were performed according to following standards:

Article 2 paragraph 1 item 19: Low power data communications system in the 2.4GHz band.

MIC Notice No.88 Appendix No.43: Test Method for Radio Equipment specified in Article 2 paragraph 1 item 19 of Regulations for Certification

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with test method for radio equipment specified in MIC public notice 88:2004, annex 43 for certification.

1.4 Test Facility

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx/Rx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2480MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Test Conditions

Supply Voltage				
	EUT supply power V	module input power V	Rated module power V	Tolerance (%)
Normal	3.70	3.3	3.3	
+10%	4.07	3.3	3.3	
-10%	3.33	3.3	3.3	
Others				
Temperature (°C)		20-25		
Relative humidity		51 %.		
ATM Pressure:		1019 mbar		
Note 1: When the input voltage is reduced or increased by 10%, the regulator voltage changes of less than 1%. So the following test items are conducted in the normal voltage.				

1.7 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	9kHz-6GHz	0.57dB
Frequency Tolerance	9kHz-6GHz	1×10 ⁻⁷
Occupied Bandwidth	9kHz-6GHz	0.015MHz
Transmitter Spurious Emissions	9kHz-25GHz	2.76dB
Receiver Spurious Emissions	9kHz-25GHz	2.76dB

1.8 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Signal Generator	Agilent	83752A	3610A01453	2025-02-23	2026-02-22
Vector Signal Generator	Agilent	N5182A	MY47070202	2025-02-23	2026-02-22
Power Sensor	Agilent	U2021XA	MY55160007	2025-02-23	2026-02-22
Power Sensor	Agilent	U2021XA	MY54240001	2025-02-23	2026-02-22
Spectrum Analyzer	Agilent	N9020A	US47140102	2025-02-23	2026-02-22
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2025-02-23	2026-02-22
Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2025-02-23	2026-02-22
Universal Radio Communication Tester	Rohde & Schwarz	CMW500	148650	2025-02-23	2026-02-22
Attenuator	Pasternack	PE4007-4	/	2025-02-23	2026-02-22

Remark:

(a) Calibration conducted by the National institute of information and communications Technology (NICT) in Japan (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph in JRL.

(b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Act (Act No. 51 of 1992).

(c) Calibration conducted in countries except Japan, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).

(d) Calibration, etc. conducted by using measuring instruments and other equipment listed in the right column of appended table No. 3, which shall have been given any type of calibration, etc. listed above from (a) to (c).

The calibration corresponds to c described above.

From JRL Article 24-2, paragraph 4, Item 2

Notice: calibration duration for above equipments is 1 year

1.9 Calibration Information

CCIC (Shenzhen) Metrology & Testing Service Co., Ltd
Shenghui Hongxing Chuangzhi Square, Tongren Road, Tianliao Community,
Yutang Subdistrict, Guangming District, Shenzhen, Guangdong, China.

Waltek Testing Group (Shenzhen) Co., Ltd.

[Http://www.waltek.com.cn](http://www.waltek.com.cn)

Page 10 of 44

2. SUMMARY OF TEST RESULTS

MIC RULES	DESCRIPTION OF TEST	RESULT
Item 19	RF Output Power	Compliant
Item 19	Frequency Tolerance	Compliant
Item 19	Occupied Bandwidth	Compliant
Item 19	Transmitter Spurious Emissions	Compliant
Item 19	Receiver Spurious Emissions	Compliant
Item 19	Interference Prevention Function	Compliant
Item 19	Carrier Sending Function	N/A

N/A: not applicable.


3. RF OUTPUT POWER

3.1 Standard Applicable

According to Item 19 of Article 2 Paragraph 1, the antenna power of the transmitter shall be one of the items below.

- (1) The antenna power of the transmitting equipment which uses the frequency hopping method (including a combination of the frequency hopping method and direct spread method or a combination of the frequency hopping method and OFDM), and that uses emissions of a frequency from 2,427 MHz to 2,470.75 MHz shall provide a mean power within a bandwidth of 1 MHz of 3mW or less in the case of modulation using a standard coding test signal with the same transmission rate as that of the modulation signal.
- (2) The antenna power of the transmitting equipment which uses OFDM or the spread spectrum method and does not conform to (1) above shall provide the mean power within a bandwidth of 1 MHz of 10 mW or less for the 20MHz system and 5 mW for the 40MHz system in the case of modulation using a standard coding test signal with the same transmission rate as that of the modulation signal.
- (3) The antenna power of the transmitting equipment other than that stated in (1) and (2) above shall be 10 mW or less. and the maximum permit tolerance is +20%, no lower limit.

3.2 Test Setup Block Diagram



3.3 Test Procedure

Refer to Schedule 43: Wireless Equipment Test Methods published in Certification Regulations, Article 2-1(19)

3.4 Summary of Test Results/Plots


Please refer to Appendix A

4. FREQUENCY TOLERANCE

4.1 Standard Applicable

According to Item 19 of Article 2 Paragraph 1, the maximum permit tolerance of frequency is 50ppm.

4.2 Test Setup Block Diagram



4.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW, VBW=10KHz, Span = 1MHz.
- 4 'Maximum Hold' mode may be used to accumulate the measurement result over several scans provided emission is repetitive in nature.
5. Repeat above procedures until all frequency measured was complete.

4.4 Summary of Test Results/Plots

Please refer to Appendix B


5. OCCUPIED BANDWIDTH

5.1 Standard Applicable

According to Item 19 of Article 2 Paragraph 1. For FHSS the occupied bandwidth shall not exceed 83.5MHz, the spreading bandwidth no less than 500kHz, and the operating frequency range lies within the band 2400MHz to 2483.5 MHz.

For BLE The limit of 99% occupied bandwidth should be within 26MHz, and the spreading bandwidth no less than 500kHz

5.2 Test Setup Block Diagram



5.3 Test Procedure

(1) Set up the spectrum analyzer as the follows:

Center frequency: Test frequency

Sweep bandwidth: 2 to 3.5 times of allowance

Resoluble bandwidth: less than 3% of allowance

Video bandwidth: Equivalent to resolvable bandwidth

Sweep time: Minimum time by which measuring accuracy is assured (In case of burst wave, 1 burst shall be contained per 1 sample)

Sampling points: More than 400 points

Sweep mode : Continuous sweeping

Detection mode: Positive peak

Display mode: Maximum holding

(2) Repeat the sweeping till no change was observed on the display and enter all values of data point to the computer as array variable.

(3) About all data, convert dB value to antilogarithm of electric power dimension.

(4) Add up the electric power of all data and record it as "Sum total of electric power".

(5) Adding up data in order from the lowest frequency to upper frequencies, look for a limit point where the

Waltek Testing Group (Shenzhen) Co., Ltd.

[Http://www.waltek.com.cn](http://www.waltek.com.cn)

Reference No.: WTX25X10277554W001

value reaches to 0.5% (5% in case of diffusion bandwidth) of "Sum total of electric power". Convert the limit point to frequency and record as "Lowest limit frequency".

(6) Adding up data in order from the highest frequency to lower frequencies, look for a limit point where the value reaches to 0.5% (5% in case of diffusion bandwidth) of "Sum total of electric power". Convert the limit point to frequency and record as "Highest limit frequency".

(7) Repeat above procedures until all frequency measured was complete.

5.4 Summary of Test Results/Plots

Please refer to Appendix C


6. TRANSMITTER SPURIOUS EMISSIONS

6.1 Standard Applicable

According to Item 19 of Article 2 Paragraph 1. The transmitter spurious emissions shall not exceed the following limit:

- (1) Below 2387MHz : 2.5 μ W/MHz
- (2) 2387 to 2400MHz : 25 μ W/MHz
- (3) 2483.5 through 2496.5MHz : 25 μ W/MHz
- (4) Over 2496.5MHz : 2.5 μ W/MHz

6.2 Test Setup Block Diagram



6.3 Test Procedure

- (1) A spectrum in case of conducted measurements, the radio device shall be connected to the measuring equipment via a suitable attenuator.
- (2) The measurement equipment shall be set for peak hold mode of operation.
- (3) The transmitter shall be operated at the highest output power, or, in the case of equipment able to operate at more than one power level, at the lowest and highest output powers;
- (4) The resolution bandwidth shall be set to 100kHz from 10MHz to 1GHz, the resolution bandwidth shall be set to 1MHz above 1GHz, and the sweep time shall be set to auto mode, to ensure all major modulation products are captured.
- (5) When the searched result is less than the specified limit, the maximum one shall be recorded, when the result is more than the specified limit, all measured values shall be recorded.
- (6) This measurement shall be repeated with the transmitter in standby mode where applicable.
- (7) Repeat above procedures until all frequency measured was complete.

6.4 Summary of Test Results/Plots

Please refer to Appendix D


7. RECEIVER SPURIOUS EMISSIONS

7.1 Standard Applicable

According to Item 19 of Article 2 Paragraph 1. The receiver spurious emissions shall not exceeded the following limit:

- (1) Below 1GHz : 4nW
- (2) 1GHz or higher : 20nW

7.2 Test Setup Block Diagram



7.3 Test Procedure

- (1) A spectrum In case of conducted measurements, the radio device shall be connected to the measuring equipment via a suitable attenuator.
- (2) The measurement equipment shall be set for peak hold mode of operation.
- (3) the transmitter shall be operated at the receiving mode.
- (4) The resolution bandwidth shall be set to 100kHz from 10MHz to 1GHz, the resolution bandwidth shall be set to 1MHz above 1GHz , and the sweep time shall be set to auto mode, to ensure all major modulation products are captured.
- (5) When the searched result is less than the specified limit, the maximum one shall be recorded, when the result is more than the specified limit, all measured values shall be recorded.
- (6) This measurement shall be repeated with the transmitter in standby mode where applicable.
- (7) Repeat above procedures until all frequency measured was complete.

7.4 Summary of Test Results/Plots


Please refer to Appendix E

8. INTERFERENCE PREVENTION FUNCTION

8.1 Standard Applicable

According to Item 19 of Article 2 Paragraph 1. The device shall have the function of automatic transmission or reception of identification code.

8.2 Test Setup Block Diagram



8.3 Test Procedure

1. Set the EUT in the usual operation condition
2. The radio equipment with automatic transmitting function of identification code
 - A. Transmit the assigned identification code from the radio equipment.
 - B. Confirm the identification code received by the demodulator.
3. The radio equipment with automatic receiving function of identification code
 - A. Transmit the assigned identification code from the opposite equipment.
 - B. Confirm that the usual communication is available.
 - C. Transmit the identification code distinct from the assigned one from the opposite equipment.
 - D. Confirm that the radio equipment is stopped or an indication is displayed as the identification code is different.
4. The identification function shall be recorded.

8.4 Summary of Test Results/Plots

Please refer to Appendix F

APPENDIX SUMMARY

Project No.	WTX25X10277554W001	Test Engineer	Timi Huang
Start date	2025/10/28	Finish date	2025/10/28
Temperature	23.3℃	Humidity	51%
RF specifications	Bluetooth-LE		

APPENDIX	Description of Test Item	Result
A	RF OUTPUT POWER	Compliant
B	FREQUENCY TOLERANCE	Compliant
C	OCCUPIED BANDWIDTH	Compliant
D	TRANSMITTER SPURIOUS EMISSIONS	Compliant
E	RECEIVER SPURIOUS EMISSIONS	Compliant
F	INTERFERENCE PREVENTION FUNCTION	Compliant

APPENDIX A

RF OUTPUT POWER

➤ RF Output Power:

Mode	Test Channel	Measure Value (dBm)	Limit (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	Result
LE-GFSK-1M bps	Low	-1.69	10	-5.68	-7.37	12.14	Pass
	Middle	-1.41	10	-5.68	-7.09	12.14	Pass
	High	-0.96	10	-5.68	-6.64	12.14	Pass
LE-GFSK-2M bps	Low	-1.68	10	-5.68	-7.36	12.14	Pass
	Middle	-1.42	10	-5.68	-7.10	12.14	Pass
	High	-0.94	10	-5.68	-6.62	12.14	Pass

*The LE EIRP is less than 12.14dBm, so the half-power beam width is not necessary.


➤ RF Output Power Tolerance

Mode	Test Channel	Output Power (mW)	Rated Output Power (mW)	Tolerance (%)	Limit (%)	Result
LE-GFSK-1M bps	Low	0.678	0.8	-15.295	≤+20%	Pass
	Middle	0.723	0.8	-9.654	≤+20%	Pass
	High	0.802	0.8	0.210	≤+20%	Pass
LE-GFSK-2M bps	Low	0.679	0.8	-15.100	≤+20%	Pass
	Middle	0.721	0.8	-9.862	≤+20%	Pass
	High	0.805	0.8	0.672	≤+20%	Pass


Note: Tolerance = (Output Power – Rated Output Power) / Rated Output Power * 100%

APPENDIX B**FREQUENCY TOLERANCE**


Mode	Test Frequency (MHz)	Reading Value (MHz)	Tolerance (ppm)	Limit (ppm)	Result
LE-GFSK-1M bps	2402	2401.992	-3.33	± 50	Pass
	2440	2439.992	-3.28	± 50	Pass
	2480	2479.992	-3.23	± 50	Pass
LE-GFSK-2M bps	2402	2401.992	-3.33	± 50	Pass
	2440	2439.992	-3.28	± 50	Pass
	2480	2479.992	-3.23	± 50	Pass




Low-2Mbps



Middle-2Mbps




High-2Mbps




APPENDIX C**OCCUPIED BANDWIDTH**

Mode	Channel	99% Emission bandwidth		Result
		Reading Value (MHz)	Limit (MHz)	
LE-GFSK- 1Mbps	Low	1.440	<26	Pass
	Middle	1.320	<26	Pass
	High	1.440	<26	Pass
LE-GFSK- 2Mbps	Low	2.280	<26	Pass
	Middle	2.280	<26	Pass
	High	2.280	<26	Pass


99% Emission bandwidth




Low-2Mbps



Middle-2Mbps



High-2Mbps





APPENDIX D


TRANSMITTER SPURIOUS EMISSIONS


➤ For LE

Mode	Channel	Frequency Range (MHz)	Freq. (MHz)	Reading Value	Result (μW/MHz)	Limit (μW/MHz)	Result
LE-GFSK -1Mbps	Low	30-1000	990.300	-48.40dBm/100kHz	0.14450	2.5	Pass
		1000-2387	2356.486	-50.65dBm/MHz	0.00861	2.5	Pass
		2387-2400	2400.000	-23.78dBm/MHz	4.18794	25	Pass
		2483.5-2496.5	2492.236	-52.17dBm/MHz	0.00607	25	Pass
		2496.5-127500	7213.110	-41.02dBm/MHz	0.07907	2.5	Pass
	Middle	30-1000	621.700	-49.41dBm/100kHz	0.11460	2.5	Pass
		1000-2387	2289.910	-51.80dBm/MHz	0.00661	2.5	Pass
		2387-2400	2392.044	-49.96dBm/MHz	0.01009	25	Pass
		2483.5-2496.5	2488.102	-49.68dBm/MHz	0.01076	25	Pass
		2496.5-127500	7315.645	-42.99dBm/MHz	0.05023	2.5	Pass
	High	30-1000	827.340	-48.78dBm/100kHz	0.13240	2.5	Pass
		1000-2387	2223.334	-51.74dBm/MHz	0.00670	2.5	Pass
		2387-2400	2399.948	-51.52dBm/MHz	0.00705	25	Pass
		2483.5-2496.5	2483.500	-39.20dBm/MHz	0.12023	25	Pass
		2496.5-127500	9325.331	-43.45dBm/MHz	0.04519	2.5	Pass
LE-GFSK -2Mbps	Low	30-1000	386.960	-47.89dBm/100kHz	0.16260	2.5	Pass
		1000-2387	2356.486	-51.12dBm/MHz	0.00773	2.5	Pass
		2387-2400	2400.000	-18.96dBm/MHz	12.7057	25	Pass
		2483.5-2496.5	2484.150	-51.90dBm/MHz	0.00646	25	Pass
		2496.5-127500	7213.110	-41.17dBm/MHz	0.07638	2.5	Pass
	Middle	30-1000	258.920	-48.59dBm/100kHz	0.13840	2.5	Pass
		1000-2387	1285.722	-51.96dBm/MHz	0.00637	2.5	Pass
		2387-2400	2391.914	-50.04dBm/MHz	0.00991	25	Pass
		2483.5-2496.5	2488.206	-49.60dBm/MHz	0.01096	25	Pass
		2496.5-127500	7315.645	-42.72dBm/MHz	0.05346	2.5	Pass
	High	30-1000	584.840	-48.61dBm/100kHz	0.13770	2.5	Pass
		1000-2387	2220.560	-52.07dBm/MHz	0.00621	2.5	Pass
		2387-2400	2388.170	-50.80dBm/MHz	0.00832	25	Pass
		2483.5-2496.5	2483.500	-36.76dBm/MHz	0.21086	25	Pass
		2496.5-127500	11991.241	-43.23dBm/MHz	0.04750	2.5	Pass














LE-High-1Mbps












LE-High-2Mbps





APPENDIX E

RECEIVER SPURIOUS EMISSIONS


➤ For LE


➤ Mode	Channel	Frequency Range (MHz)	Freq. (MHz)	Reading Value	Result (nW)	Limit (nW)	Result
LE-GFSK-1Mbps	Low	30-1000	480.080	-73.33dBm/100kHz	0.05	4	Pass
		1000-12750	11504.500	-63.64dBm/MHz	0.43	20	Pass
	Middle	30-1000	829.280	-73.78dBm/100kHz	0.04	4	Pass
		1000-12750	10071.000	-63.61dBm/MHz	0.44	20	Pass
	High	30-1000	328.760	-73.27dBm/100kHz	0.05	4	Pass
		1000-12750	11833.500	-63.64dBm/MHz	0.43	20	Pass
LE-GFSK-2Mbps	Low	30-1000	425.760	-73.28dBm/100kHz	0.05	4	Pass
		1000-12750	12068.500	-63.94dBm/MHz	0.40	20	Pass
	Middle	30-1000	427.700	-73.26dBm/100kHz	0.05	4	Pass
		1000-12750	12068.500	-63.09dBm/MHz	0.49	20	Pass
	High	30-1000	953.440	-73.15dBm/100kHz	0.05	4	Pass
		1000-12750	10188.500	-63.49dBm/MHz	0.45	20	Pass

LE-Low-1Mbps




LE-Middle-1Mbps







LE-High-1Mbps

LE-Low-2Mbps



LE-Middle-2Mbps





LE-High-2Mbps

APPENDIX F

INTERFERENCE PREVENTION FUNCTION

Test Item	Test Result
Transmitting Function of Identification Code	Good
Receiving Function of Identification Code	Good

Identification Code	d1:00:80:80:43:32
---------------------	-------------------

Reference No.: WTX25X10277554W001

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****