

# NCC

## 低功率射頻電機型式試驗報告

產品名稱: 無線基地台  
英文名稱: OmniAccess Stellar  
型號: OAW-AP1301  
廠牌: Alcatel-Lucent Enterprise  
申請者: 皇輝科技股份有限公司  
申請者地址: 台北市內湖區民權東路六段 11 巷 43 之 1 號 3 樓  
測試標準: LP0002 (109 年版) 4.10 章節  
參考法規: ANSI C63.10-2013  
測試結果: 符合  
接收日期: 2020.08.25  
測試日期: 2020.09.22 ~2020.12.01  
發行日期: 2020.12.07

測試工程師:



( 陳駿豪 )

報告審核人:



( 陳柏均 )

報告簽屬人:



(柯承志)



本測試報告僅對實驗室所受測之樣品負責

本測試報告非經本公司同意不可局部複製使用

### 修訂紀錄

| 報告編號          | 版本  | 描述              | 發行日期       |
|---------------|-----|-----------------|------------|
| 2010TW0002-T6 | 1.0 | Original Report | 2020-12-07 |

## CONTENTS

| Description                    | Page      |
|--------------------------------|-----------|
| <b>1. 一般資訊 .....</b>           | <b>5</b>  |
| <b>2. 產品資訊 .....</b>           | <b>6</b>  |
| 2.1. 待測物裝置資料 .....             | 6         |
| 2.2. 通道清單 .....                | 7         |
| 2.3. 測試模式 .....                | 7         |
| 2.4. 測試系統組合圖 .....             | 8         |
| 2.5. 測試周邊 .....                | 9         |
| 2.6. 待測裝置測試時之典型操作程式 .....      | 10        |
| <b>3. 量測不確定度 .....</b>         | <b>11</b> |
| <b>4. 測試設備明細 .....</b>         | <b>12</b> |
| <b>5. 測試結果 .....</b>           | <b>14</b> |
| 5.1. 電源端點干擾測試 .....            | 15        |
| 5.1.1. 適用標準 .....              | 15        |
| 5.1.2. 量測方法 .....              | 15        |
| 5.1.3. 測試架構圖 .....             | 15        |
| 5.1.4. 電源端點測試結果 .....          | 16        |
| 5.2. 峰值傳導輸出功率 .....            | 20        |
| 5.2.1. 適用標準 .....              | 20        |
| 5.2.2. 量測方法 .....              | 20        |
| 5.2.3. 測試架構圖 .....             | 20        |
| 5.2.4. 峰值傳導輸出功率測試結果 .....      | 21        |
| 5.3. 天線之要求 .....               | 23        |
| 5.3.1. 適用標準 .....              | 23        |
| 5.3.2. 天線樣式 .....              | 23        |
| 5.4. 輻射干擾測試 .....              | 24        |
| 5.4.1. 適用標準 .....              | 24        |
| 5.4.2. 量測方法 .....              | 24        |
| 5.4.3. 測試架構圖 .....             | 25        |
| 5.4.4. 輻射干擾測試結果 .....          | 26        |
| 5.5. 混附發射之 RF 傳導發射 .....       | 80        |
| 5.5.1. 適用標準 .....              | 80        |
| 5.5.2. 量測方法 .....              | 80        |
| 5.5.3. 測試架構圖 .....             | 80        |
| 5.5.4. 混附發射之 RF 傳導發射測試結果 ..... | 81        |

---

|        |                     |     |
|--------|---------------------|-----|
| 5.6.   | 開放頻帶邊緣之不必要幅射要求..... | 114 |
| 5.6.1. | 適用標準 .....          | 114 |
| 5.6.2. | 量測方法 .....          | 114 |
| 5.6.3. | 測試架構圖 .....         | 115 |
| 5.6.4. | 測試結果 .....          | 116 |
| 5.7.   | 佔用頻道寬度.....         | 212 |
| 5.7.1. | 適用標準 .....          | 212 |
| 5.7.2. | 量測方法 .....          | 212 |
| 5.7.3. | 測試架構圖 .....         | 212 |
| 5.7.4. | 佔用頻帶寬度測試結果.....     | 213 |
| 5.8.   | 發射電功率密度 .....       | 222 |
| 5.8.1. | 適用標準 .....          | 222 |
| 5.8.2. | 量測方法 .....          | 222 |
| 5.8.3. | 測試架構圖 .....         | 222 |
| 5.8.4. | 功率密度量測結果.....       | 223 |

## 1. 一般資訊

|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 申請者       | 皇輝科技股份有限公司                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 申請者地址     | 台北市內湖區民權東路六段 11 巷 43 之 1 號 3 樓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 製造商       | ALE International                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| 製造商地址     | 26801 West Agoura Road, Calabasas, CA 91301, United States                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 實驗室       | 台灣曼瑞檢測科技有限公司                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 實驗室地址     | 33377 台灣桃園市龜山區復興二路 38 號                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 實驗室資訊     | <ol style="list-style-type: none"> <li>1. MRT facility is an FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.</li> <li>2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.</li> <li>3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC, Industry Taiwan, EU and TELEC Rules.</li> </ol> |
| 實驗室測試環境條件 | 溫度 (°C) : 20-35 / 濕度 (%RH) : 30-65                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

## 2. 產品資訊

### 2.1. 待測物裝置資料

|         |                                                                                                                                                  |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| 產品名稱    | 無線基地台                                                                                                                                            |
| 產品型號    | OAW-AP1301                                                                                                                                       |
| 產品廠牌    | Alcatel-Lucent Enterprise                                                                                                                        |
| 無線規格    | 802.11a/b/g/n/ac/ax                                                                                                                              |
| 工作溫度    | 0 ~ 50 °C                                                                                                                                        |
| 待測物額定電壓 | PoE input or AC adapter input                                                                                                                    |
| 工作環境    | Indoor Use                                                                                                                                       |
| 頻率範圍    | 802.11b/g/n-HT20/VHT20/ax-HE20: 2412 ~ 2462 MHz<br>802.11n-HT40/VHT40/ax-HE40: 2422 ~ 2452 MHz                                                   |
| 信道數量    | 802.11b/g/n-HT20/VHT20/ax-HE20: 11<br>802.11n-HT40/VHT40/ax-HE40: 7                                                                              |
| 調變模式    | 802.11b: DSSS; 802.11g/n/VHT: OFDM; 802.11ax: OFDMA                                                                                              |
| 傳輸速率    | 802.11b: 1/2/5.5/11Mbps<br>802.11g: 6/9/12/18/24/36/48/54Mbps<br>802.11n: up to 300Mbps<br>802.11VHT: up to 400Mbps<br>802.11ax: up to 573.5Mbps |

## 2.2. 通道清單

802.11b/g/n-HT20/VHT20/ax-HE20

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 01      | 2412 MHz  | 02      | 2417 MHz  | 03      | 2422 MHz  |
| 04      | 2427 MHz  | 05      | 2432 MHz  | 06      | 2437 MHz  |
| 07      | 2442 MHz  | 08      | 2447 MHz  | 09      | 2452 MHz  |
| 10      | 2457 MHz  | 11      | 2462 MHz  | --      | --        |

802.11n-HT40/VHT40/ax-HE40


| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 03      | 2422 MHz  | 04      | 2427 MHz  | 05      | 2432 MHz  |
| 06      | 2437 MHz  | 07      | 2442 MHz  | 08      | 2447 MHz  |
| 09      | 2452 MHz  | --      | --        | --      | --        |

## 2.3. 測試模式


Mode 1: 發射器 802.11b (1Mbps)  
Mode 2: 發射器 802.11g (6Mbps)  
Mode 3: 發射器 802.11n-HT20 (MCS0)  
Mode 4: 發射器 802.11n-HT40 (MCS0)  
Mode 5: 發射器 802.11VHT20 (MCS0)  
Mode 6: 發射器 802.11VHT40 (MCS0)  
Mode 7: 發射器 802.11ax-HE20 (MCS0)  
Mode 8: 發射器 802.11ax-HE40 (MCS0)  
Mode 9: Normal Mode

## 2.4. 測試系統組合圖

Connection Diagram (Mode 1~8)



Connection Diagram (Mode 9)



| Cable Type |             | Cable Description    |
|------------|-------------|----------------------|
| A          | Power Cable | Non-Shielding, 1.5m  |
| B          | Power Cable | Non-Shielding, 1.5m  |
| C          | LAN Cable   | Non-Shielding, > 10m |
| D          | LAN Cable   | Non-Shielding, > 10m |

## 2.5. 測試周邊

|   | Product    | Manufacturer | Model No.    | Serial No.     | Power Cord         |
|---|------------|--------------|--------------|----------------|--------------------|
| 1 | Notebook   | Lenovo       | E430c        | MP-4CFX213/10  | Non-Shielded, 1.8m |
| 2 | iPhone     | Apple        | ML7E2CH/A    | C6KR9BR2GRY    | N/A                |
| 3 | Notebook   | ASUS         | PRO45V       | N/A            | Non-Shielded, 1.8m |
| 4 | USB Dongle | SanDisk      | BL161025264V | N/A            | N/A                |
| 5 | Adapter    | DELTA        | ADP-30HR B   | 1WMD05S00T5    | Non-Shielded, 1.8m |
| 6 | Notebook   | Lenovo       | E431         | PF-10ZRN 13/12 | Non-Shielded, 1.8m |

## 2. 6. 待測裝置測試時之典型操作程式

|    |                                               |
|----|-----------------------------------------------|
| 1. | Setup the EUT and simulators as shown on 2.4  |
| 2. | Turn on the power of all equipment.           |
| 3. | Execute "QSPR v50-00186.exe" program.         |
| 4. | Configure the test channel and the data rate. |
| 5. | Start test.                                   |

### 3. 量測不確定度

|                                                                                                            |
|------------------------------------------------------------------------------------------------------------|
| 電源傳導量測-電源線 (Conducted Emission- Power Line)                                                                |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 2.53dB                             |
| 電源傳導量測-通訊埠 (Conducted Emission- Impedance Stabilization Network Measurement )                              |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 3.96dB                             |
| 輻射干擾量測 (Radiated Spurious Emission)                                                                        |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 3.92dB (Below 30M)                 |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 4.25dB (30M~1G)                    |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 4.40dB (1G~18G)                    |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 4.45dB (18G~40G)                   |
| 頻率誤差量測 (Frequency Error)                                                                                   |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): $\pm 78.4\text{Hz}$                |
| 傳導功率量測 (Conducted Power)                                                                                   |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): $\pm 0.84\text{dB}$                |
| 傳導干擾量測 (Conducted Spurious Emission)                                                                       |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): $\pm 2.65\text{ dB}$               |
| 佔用頻寬量測 (Occupied Bandwidth)                                                                                |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 3.3%                               |
| 溫度 / 濕度 (Temp. / Humidity)                                                                                 |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): $\pm 0.82^\circ\text{C} / \pm 3\%$ |
| 直流電源 (DC Voltage)                                                                                          |
| Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): $\pm 0.3\%$                        |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

#### 4. 測試設備明細

##### Radiated Disturbance-AC1:

| Instrument                 | Manufacturer | Type No.                  | Asset No.   | Cali. Interval | Cali. Due Date |
|----------------------------|--------------|---------------------------|-------------|----------------|----------------|
| Broadband TRILOG Antenna   | SCHWARZBECK  | VULB 9162                 | MRTTWA00001 | 1 year         | 2021/10/5      |
| Active Loop Antenna        | SCHWARZBECK  | FMZB 1519B                | MRTTWA00002 | 1 year         | 2021/4/27      |
| Broadband Hornantenna      | SCHWARZBECK  | BBHA 9120D                | MRTTWA00003 | 1 year         | 2021/4/24      |
| Breitband Hornantenna      | SCHWARZBECK  | BBHA 9170                 | MRTTWA00004 | 1 year         | 2021/4/24      |
| Broadband Preamplifier     | SCHWARZBECK  | BBV 9718                  | MRTTWA00005 | 1 year         | 2021/4/24      |
| Broadband Amplifier        | SCHWARZBECK  | BBV 9721                  | MRTTWA00006 | 1 year         | 2021/4/24      |
| Signal Analyzer            | R&S          | FSV40                     | MRTTWA00007 | 1 year         | 2021/3/24      |
| EMI Test Receiver          | R&S          | ESR3                      | MRTTWA00009 | 1 year         | 2021/3/25      |
| EXA Signal Analyzer        | KEYSIGHT     | N9010A                    | MRTTWA00012 | 1 year         | 2021/10/14     |
| EXA Signal Analyzer        | KEYSIGHT     | N9010B                    | MRTTWA00074 | 1 year         | 2021/7/14      |
| Antenna Cable              | HUBERSUHNER  | SF106                     | MRTTWE00010 | 1 year         | 2021/6/16      |
| Temperature/Humidity Meter | TFA          | 35.1078.10.IT             | MRTTWA00032 | 1 year         | 2021/5/29      |
| Cable                      | Rosnol       | K1K50-UP0264-K1<br>K50-4M | MRTTWE00012 | 1 year         | 2021/6/21      |

##### Conducted Emissions-SR2 :

| Instrument                 | Manufacturer | Type No.                    | Asset No.   | Cali. Interval | Cali. Due Date |
|----------------------------|--------------|-----------------------------|-------------|----------------|----------------|
| Two-Line V-Network         | R&S          | ENV216                      | MRTTWA00019 | 1 year         | 2021/3/26      |
| Two-Line V-Network         | R&S          | ENV216                      | MRTTWA00020 | 1 year         | 2021/4/24      |
| 8-Wire ISN (T8-Cat6)       | R&S          | ENY81 CA6                   | MRTTWA00017 | 1 year         | 2021/5/25      |
| 8-Wire ISN (T8)            | R&S          | ENY81                       | MRTTWA00018 | 1 year         | 2021/5/25      |
| 8-Wire ISN                 | TESEQ        | CDN ST08AS                  | MRTTWA00083 | 1 year         | 2021/9/2       |
| EMI Test Receiver          | R&S          | ESR3                        | MRTTWA00045 | 1 year         | 2021/5/26      |
| Conducted Cable            | Rosnol       | N1C50-RG400-B1C<br>50-500CM | MRTTWE00013 | 1 year         | 2021/6/21      |
| Temperature/Humidity Meter | TFA          | 35.1078.10.IT               | MRTTWA00033 | 1 year         | 2021/5/28      |

## Conducted Test Equipment-SR2:

| Instrument                                 | Manufacturer | Type No.      | Asset No.   | Cali. Interval | Cali. Due Date |
|--------------------------------------------|--------------|---------------|-------------|----------------|----------------|
| X-Series USB Peak and Average Power Sensor | KEYSIGHT     | U2021XA       | MRTTWA00014 | 1 year         | 2021/4/24      |
| X-Series USB Peak and Average Power Sensor | KEYSIGHT     | U2021XA       | MRTTWA00015 | 1 year         | 2021/3/26      |
| Wideband Radio Communication Taster        | R&S          | CMW 500       | MRTTWA00041 | 1 year         | 2021/1/7       |
| EXA Signal Analyzer                        | KEYSIGHT     | N9010A        | MRTTWA00012 | 1 year         | 2021/10/14     |
| EXA Signal Analyzer                        | KEYSIGHT     | N9010B        | MRTTWA00074 | 1 year         | 2021/7/14      |
| Attenuator                                 | MVE          | 20dB          | MRTSUE06547 | N/A            | N/A            |
| Signal Analyzer                            | R&S          | FSV40         | MRTTWA00007 | 1 year         | 2021/3/24      |
| Temperature & Humidity Chamber             | TEN BILLION  | TTH-B3UP      | MRTTWA00036 | 1 year         | 2021/6/9       |
| Temperature/Humidity Meter                 | TFA          | 35.1078.10.IT | MRTTWA00033 | 1 year         | 2021/5/28      |

| Software | Version   | Function          |
|----------|-----------|-------------------|
| e3       | 9.160520a | EMI Test Software |

## 5. 測試結果

產品名稱 無線基地台  
型號 OAW-AP1301

| 章節             | 量測項目     | 限制值                                                             | 測試結果 | 測試數據     |
|----------------|----------|-----------------------------------------------------------------|------|----------|
| 3.3            | 電源傳導     | 低功率射頻電機技術規範 3.3 節                                               | 符合   | 第 5.1 章節 |
| 4.10.1.2       | 峰值傳導輸出功率 | $\leq 30.00\text{dBm}$                                          | 符合   | 第 5.2 章節 |
| 4.10.1.3       | 天線之要求    | 低功率射頻電機技術規範 4.10.1.3 節                                          | 符合   | 第 5.3 章節 |
| 4.10.1.5       | 帶外發射限制   | $\leq 30\text{dBc(Average)}$                                    | 符合   | 第 5.4 章節 |
| 3.6            | 輻射電場強度   | 低功率射頻電機技術規範 3.6 節                                               | 符合   | 第 5.5 章節 |
| 3.5            | 頻帶邊緣     | $\leq 74\text{dBuV/m(Peak)}$<br>$\leq 54\text{dBuV/m(Average)}$ | 符合   | 第 5.6 章節 |
| 4.10.1.6(2)(A) | 佔用頻寬     | $\geq 500\text{kHz}$                                            | 符合   | 第 5.7 章節 |
| 4.10.1.6(2)(B) | 功率頻譜密度   | $\leq 8\text{dBm}$                                              | 符合   | 第 5.8 章節 |

### Notes:

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) Output power test was verified over all data rates of each mode, and then choose the maximum power output (low data rate) for final test of each channel.
- 3) The test results shown in the following sections represent the worst case emissions.
- 4) The power setting of CDD & Beamforming mode is same. For 802.11n/VHT/ax uses worst case beamforming mode in the test report.
- 5) For 2417MHz and 2457MHz Radiated bandedge testing, we choose Low and high channel worst Polarity Vertical in this report.

## 5.1. 電源端點干擾測試

### 5.1.1. 適用標準

依據國家通訊傳播委員會低功率射頻電機技術規範之第 3.3 節，以市電為電源之低功率射頻電機，其傳導回電源線上頻率自 150kHz 至 30MHz 之射頻電壓(在電源端子每一電源線對接地點)應小於或等於下表所列之限值。測量時應經過 50 微亨利( $\mu\text{H}$ )及 50 歐姆( $\Omega$ )之電源線阻抗模擬網路(LISN)。頻率重疊處，以較低限值為準。

| Frequency 頻率範圍<br>MHz | 傳導限制值(dBuV)          |                      |
|-----------------------|----------------------|----------------------|
|                       | 準尖峰值                 | 平均值                  |
| 0.15 - 0.50           | 66-56 <sup>(註)</sup> | 56-46 <sup>(註)</sup> |
| 0.50 - 5.0            | 56                   | 46                   |
| 5.0 - 30              | 60                   | 50                   |


註:隨頻率之對數遞減

### 5.1.2. 量測方法

待測物置於高 80 公分之非導體桌面（落地型產品置於地上），將待測物之電源線接至電源阻抗網路器(LISN)，同時保持待測物至 LISN 距 80 公分，並將電源線多餘部份以 30 至 40 公分之八字形捆綁於電源線中央並離地 40cm，於在正常工作狀態下，執行待測物之火線(Line)及地線(neutral)各一次量測。電源端點場強之測量範圍由 0.15MHz -30MHz，所量測之讀值皆為準尖峰值(Quasi-Peak Value)及平均值(Average Value)。場強接收機之解析頻寬為 9kHz。


備 註: 經初測驗證過，電源端點干擾測試對測試頻道數並無差異，因此檢附其中一個測試頻道之測試數。

### 5.1.3. 測試架構圖



#### 5.1.4. 電源端點測試結果

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-11-30     |
| Factor    | CE_ENV216-L1 (Filter ON)               | Temp. / Humidity     | 23.2°C /51.6%  |
| Polarity  | Line1                                  | Site / Test Engineer | SR2 / Eric Lin |
| Test Mode | Transmit by 802.11b at channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | * | 0.150           | 35.05          | 9.61     | 44.66                | -21.34      | 66.00          | QP                |
| 2  |   | 0.150           | 22.95          | 9.61     | 32.56                | -23.44      | 56.00          | AV                |
| 3  |   | 0.373           | 35.92          | 9.62     | 45.54                | -12.90      | 58.43          | QP                |
| 4  |   | 0.373           | 28.32          | 9.62     | 37.94                | -10.50      | 48.43          | AV                |
| 5  |   | 0.678           | 26.76          | 9.64     | 36.40                | -19.60      | 56.00          | QP                |
| 6  |   | 0.678           | 21.16          | 9.64     | 30.80                | -15.20      | 46.00          | AV                |
| 7  |   | 3.850           | 24.61          | 9.72     | 34.33                | -21.67      | 56.00          | QP                |
| 8  |   | 3.850           | 17.11          | 9.72     | 26.83                | -19.17      | 46.00          | AV                |
| 9  |   | 9.050           | 26.63          | 9.85     | 36.49                | -23.51      | 60.00          | QP                |
| 10 |   | 9.050           | 21.03          | 9.85     | 30.89                | -19.11      | 50.00          | AV                |
| 11 |   | 12.460          | 22.41          | 9.90     | 32.32                | -27.68      | 60.00          | QP                |
| 12 |   | 12.460          | 14.11          | 9.90     | 24.02                | -25.98      | 50.00          | AV                |

Note:

1. " \*", means this data is the worst emission level.
- 2.C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-11-30     |
| Factor    | CE_ENV216-N (Filter ON)                | Temp. / Humidity     | 23.2°C /51.6%  |
| Polarity  | Neutral                                | Site / Test Engineer | SR2 / Eric Lin |
| Test Mode | Transmit by 802.11b at channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No |   | Frequency<br>(MHz) | Reading<br>(dBuV) | C.F<br>(dB) | Measurement<br>(dBuV/m) | Margin<br>(dB) | Limit<br>(dBuV/m) | Remark<br>(QP/PK/AV) |
|----|---|--------------------|-------------------|-------------|-------------------------|----------------|-------------------|----------------------|
| 1  |   | 0.170              | 35.81             | 9.62        | 45.43                   | -19.53         | 64.96             | QP                   |
| 2  |   | 0.170              | 27.81             | 9.62        | 37.43                   | -17.53         | 54.96             | AV                   |
| 3  |   | 0.370              | 36.82             | 9.63        | 46.46                   | -12.04         | 58.50             | QP                   |
| 4  | * | 0.370              | 27.52             | 9.63        | 37.16                   | -11.34         | 48.50             | AV                   |
| 5  |   | 0.640              | 26.92             | 9.65        | 36.57                   | -19.43         | 56.00             | QP                   |
| 6  |   | 0.640              | 20.67             | 9.65        | 30.32                   | -15.68         | 46.00             | AV                   |
| 7  |   | 1.530              | 25.27             | 9.68        | 34.95                   | -21.05         | 56.00             | QP                   |
| 8  |   | 1.530              | 19.77             | 9.68        | 29.45                   | -16.55         | 46.00             | AV                   |
| 9  |   | 3.860              | 26.23             | 9.73        | 35.96                   | -20.04         | 56.00             | QP                   |
| 10 |   | 3.860              | 17.63             | 9.73        | 27.36                   | -18.64         | 46.00             | AV                   |
| 11 |   | 12.410             | 22.46             | 9.93        | 32.39                   | -27.61         | 60.00             | QP                   |
| 12 |   | 12.410             | 14.96             | 9.93        | 24.89                   | -25.11         | 50.00             | AV                   |

Note:

1. " \*", means this data is the worst emission level.
- 2.C.F (Correction Factor) = LISN (dB)+ Cable Loss (dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

|           |                          |                      |                 |
|-----------|--------------------------|----------------------|-----------------|
| EUT       | OAW-AP1301               | Date of Test         | 2020-09-22      |
| Factor    | CE_ENV216-L1 (Filter ON) | Temp. / Humidity     | 23.2°C /51.6%   |
| Polarity  | Line1                    | Site / Test Engineer | SR2 / Kevin Ker |
| Test Mode | Normal Operation         | Test Voltage         | 110V/60Hz       |




| No | Frequency (MHz) | Reading (dBUV) | C.F (dB) | Measurement (dBUV/m) | Margin (dB) | Limit (dBUV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 0.151           | 41.75          | 9.61     | 51.36                | -14.58      | 65.94          | QP                |
| 2  | 0.151           | 26.35          | 9.61     | 35.96                | -19.98      | 55.94          | AV                |
| 3  | 0.182           | 38.87          | 9.61     | 48.48                | -15.91      | 64.39          | QP                |
| 4  | *               | 0.182          | 31.67    | 41.28                | -13.11      | 54.39          | AV                |
| 5  | 0.401           | 36.62          | 9.62     | 46.24                | -11.59      | 57.83          | QP                |
| 6  | 0.401           | 28.02          | 9.62     | 37.64                | -10.19      | 47.83          | AV                |
| 7  | 0.650           | 31.05          | 9.64     | 40.69                | -15.31      | 56.00          | QP                |
| 8  | 0.650           | 14.75          | 9.64     | 24.39                | -21.61      | 46.00          | AV                |
| 9  | 2.260           | 29.85          | 9.69     | 39.54                | -16.46      | 56.00          | QP                |
| 10 | 2.260           | 17.75          | 9.69     | 27.44                | -18.56      | 46.00          | AV                |
| 11 | 12.140          | 26.64          | 9.90     | 36.54                | -23.46      | 60.00          | QP                |
| 12 | 12.140          | 20.24          | 9.90     | 30.14                | -19.86      | 50.00          | AV                |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement(dBUV/m) = Reading(dBUV) + C.F (Correction Factor).

|           |                         |                      |                 |
|-----------|-------------------------|----------------------|-----------------|
| EUT       | OAW-AP1301              | Date of Test         | 2020-09-22      |
| Factor    | CE_ENV216-N (Filter ON) | Temp. / Humidity     | 23.2°C /51.6%   |
| Polarity  | Neutral                 | Site / Test Engineer | SR2 / Kevin Ker |
| Test Mode | Normal Operation        | Test Voltage         | 110V/60Hz       |



| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 0.150           | 40.41          | 9.62     | 50.03                | -15.97      | 66.00          | QP                |
| 2  | 0.150           | 26.11          | 9.62     | 35.73                | -20.27      | 56.00          | AV                |
| 3  | 0.400           | 37.03          | 9.63     | 46.66                | -11.19      | 57.85          | QP                |
| 4  | *               | 0.400          | 26.63    | 36.26                | -11.59      | 47.85          | AV                |
| 5  | 0.646           | 32.12          | 9.65     | 41.77                | -14.23      | 56.00          | QP                |
| 6  | 0.646           | 22.12          | 9.65     | 31.77                | -14.23      | 46.00          | AV                |
| 7  | 1.130           | 31.87          | 9.67     | 41.54                | -14.46      | 56.00          | QP                |
| 8  | 1.130           | 20.77          | 9.67     | 30.44                | -15.56      | 46.00          | AV                |
| 9  | 3.330           | 30.75          | 9.72     | 40.47                | -15.53      | 56.00          | QP                |
| 10 | 3.330           | 20.85          | 9.72     | 30.57                | -15.43      | 46.00          | AV                |
| 11 | 8.570           | 29.33          | 9.85     | 39.18                | -20.82      | 60.00          | QP                |
| 12 | 8.570           | 22.33          | 9.85     | 32.18                | -17.82      | 50.00          | AV                |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

## 5.2. 峰值傳導輸出功率

### 5.2.1. 適用標準

依據國家通訊傳播委員會低功率射頻電機技術規範之第 4.10.1.2(1)(C)節，操作於 2400-2483.5 MHz 之數位調變的發射器材：1 瓦(W)(含)以下。

依據國家通訊傳播委員會低功率射頻電機技術規範之第 4.10.1.3 節，天線增益限制如下：

(1) 操作於 2400 MHz~2483.5 MHz 頻段：

(A) 進行固定式點對點操作時，其發射天線之方向性增益超過6 dBi，每超過3 dBi，最大傳導輸出功率限制值應降低1 dB。

(B) 除第(A)節外，如其發射天線之方向性增益超過6dBi，應依所超過之dB數等量降低最大傳導輸出功率。

(C) 天線以多向波束發射方式(含同時發射或循序發射)將訊號導向多個接收機或接收機群組時，應符合下列規定：

(a) 非同時發射多向波束者，所有載波或頻道傳輸至所有天線陣列或陣列群之總和傳導輸出功率應符合 4.10.1.2 之功率限制值。如天線/天線陣列群之方向性增益超過 6 dBi，每超過 3 dBi，總和傳導輸出功率限制值應降低 1 dB。方向性增益值應計算如下：

(i) 方向性增益值=  $10\log(\text{天線陣列之單元數目}) + \text{各單元中最高之方向性增益值}$ 。

(ii) 天線陣列間之遮蔽效應或波束干涉損失能充分佐證時，方向性增益得低於(i)計算數值。


同時發射多向波束於相同或不同頻道者，其每一波束功率應符合(a)之功率限制值。如發射波束有重疊現象，功率應降低，以確保總和傳導輸出功率符合(a)之限制值。同時發射的所有波束總和傳導輸出功率不大於(a) 總和傳導輸出功率限制值加 8 dB。方向性增益值計算同(a)。

(c) 發射機之天線具備單向波束功能者，應符合(1)(A)及(3)後段之規定。

### 5.2.2. 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀 RF 輸入端，設定頻譜分析儀之解析度頻寬大於 6dB 發射頻寬或使用峰值功率表。

### 5.2.3. 測試架構圖



#### 5.2.4. 峰值傳導輸出功率測試結果

|               |                                |                   |            |
|---------------|--------------------------------|-------------------|------------|
| Product       | OmniAccess Stellar, OAW-AP1301 | Temperature       | 23 ~ 25°C  |
| Test Engineer | Eric Lin                       | Relative Humidity | 44 ~ 52%   |
| Test Site     | SR2                            | Test Date         | 2020/11/18 |
| Model No.     | OAW-AP1301                     |                   |            |

| Test Mode | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Total Average Power (dBm) | Limit (dBm) | Result |
|-----------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|-------------|--------|
| 11b       | 1Mbps             | 01          | 2412        | 21.03                     | 20.89                     | 23.97                     | ≤ 30.00     | Pass   |
| 11b       | 1Mbps             | 06          | 2437        | 22.53                     | 21.57                     | 25.09                     | ≤ 30.00     | Pass   |
| 11b       | 1Mbps             | 11          | 2462        | 20.47                     | 20.98                     | 23.74                     | ≤ 30.00     | Pass   |
| 11g       | 6Mbps             | 01          | 2412        | 19.43                     | 18.97                     | 22.22                     | ≤ 30.00     | Pass   |
| 11g       | 6Mbps             | 06          | 2437        | 20.97                     | 19.81                     | 23.44                     | ≤ 30.00     | Pass   |
| 11g       | 6Mbps             | 11          | 2462        | 18.88                     | 18.36                     | 21.64                     | ≤ 30.00     | Pass   |
| 11n-HT20  | MCS0              | 01          | 2412        | 17.03                     | 16.83                     | 19.94                     | ≤ 29.69     | Pass   |
| 11n-HT20  | MCS0              | 02          | 2417        | 19.27                     | 19.03                     | 22.16                     | ≤ 29.69     | Pass   |
| 11n-HT20  | MCS0              | 06          | 2437        | 21.15                     | 21.75                     | 24.47                     | ≤ 29.69     | Pass   |
| 11n-HT20  | MCS0              | 11          | 2462        | 19.91                     | 18.61                     | 22.32                     | ≤ 29.69     | Pass   |
| 11n-HT40  | MCS0              | 03          | 2422        | 14.07                     | 14.01                     | 17.05                     | ≤ 29.69     | Pass   |
| 11n-HT40  | MCS0              | 06          | 2437        | 16.06                     | 16.19                     | 19.14                     | ≤ 29.69     | Pass   |
| 11n-HT40  | MCS0              | 09          | 2452        | 15.15                     | 15.24                     | 18.21                     | ≤ 29.69     | Pass   |
| VHT20     | MCS0              | 01          | 2412        | 18.08                     | 16.73                     | 20.47                     | ≤ 29.69     | Pass   |
| VHT20     | MCS0              | 02          | 2417        | 19.45                     | 19.26                     | 22.37                     | ≤ 29.69     | Pass   |
| VHT20     | MCS0              | 06          | 2437        | 21.63                     | 20.37                     | 24.06                     | ≤ 29.69     | Pass   |
| VHT20     | MCS0              | 10          | 2457        | 20.14                     | 20.00                     | 23.08                     | ≤ 29.69     | Pass   |
| VHT20     | MCS0              | 11          | 2462        | 17.76                     | 16.98                     | 20.40                     | ≤ 29.69     | Pass   |
| VHT40     | MCS0              | 03          | 2422        | 14.33                     | 13.81                     | 17.09                     | ≤ 29.69     | Pass   |
| VHT40     | MCS0              | 06          | 2437        | 16.49                     | 16.23                     | 19.37                     | ≤ 29.69     | Pass   |
| VHT40     | MCS0              | 09          | 2452        | 15.23                     | 15.10                     | 18.18                     | ≤ 29.69     | Pass   |

| Test Mode | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Total Average Power (dBm) | Limit (dBm) | Result |
|-----------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|-------------|--------|
| 11ax-HE20 | MCS0              | 01          | 2412        | 17.55                     | 17.96                     | 20.77                     | ≤ 29.69     | Pass   |
| 11ax-HE20 | MCS0              | 06          | 2437        | 20.10                     | 20.91                     | 23.53                     | ≤ 29.69     | Pass   |
| 11ax-HE20 | MCS0              | 10          | 2457        | 19.14                     | 19.03                     | 22.10                     | ≤ 29.69     | Pass   |
| 11ax-HE20 | MCS0              | 11          | 2462        | 17.70                     | 16.87                     | 20.32                     | ≤ 29.69     | Pass   |
| 11ax-HE40 | MCS0              | 03          | 2422        | 14.74                     | 14.31                     | 17.54                     | ≤ 29.69     | Pass   |
| 11ax-HE40 | MCS0              | 06          | 2437        | 16.23                     | 15.65                     | 18.96                     | ≤ 29.69     | Pass   |
| 11ax-HE40 | MCS0              | 09          | 2452        | 15.43                     | 15.73                     | 18.59                     | ≤ 29.69     | Pass   |

Note 1: Total Average Power (dBm) =  $10 \cdot \log [10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)}]$  (dBm).

2. Limit= 30dBm-(6.31dBi-6) = 29.69dBm

### 5.3. 天線之要求

#### 5.3.1. 適用標準

低功率射頻電機之發射機或收發信機所使用之天線，應為全固定、半固定式或以獨特之耦合(unique coupling)方式連接機體。製造者可設計供使用者因損壞而替換之天線，但不得設計或使用原認證以外之天線或可供引接各類電纜之標準天線插座或電氣連接頭，如：BNC、F type、N type、M type、UG type、RCA、SMA、SMB...等及其他各類工業或通訊標準接頭。

#### 5.3.2. 天線樣式

| Antenna Type                                                 | Frequency Band (GHz) | T <sub>x</sub> Paths | Bandwidth (MHz) | Max Peak Gain (dBi) |       | CDD Directional Gain (dBi) |      | Beamforming Directional Gain (dBi) |
|--------------------------------------------------------------|----------------------|----------------------|-----------------|---------------------|-------|----------------------------|------|------------------------------------|
|                                                              |                      |                      |                 | Ant 0               | Ant 1 | Power                      | PSD  |                                    |
| Wi-Fi Internal Antenna List (2.4GHz 2*2 MIMO, 5GHz 2*2 MIMO) |                      |                      |                 |                     |       |                            |      |                                    |
| PIFA                                                         | 2412 ~ 2462          | 2                    | 20, 40          | 3.20                | 3.30  | 3.30                       | 6.31 | 6.31                               |
| Antenna                                                      | 5150 ~ 5850          | 2                    | 20, 40, 80      | 3.10                | 3.30  | 3.30                       | 6.31 | 6.31                               |

Note 1: The EUT supports Cyclic Delay Diversity (CDD) technology for 802.11a/b/g/n/ac/ax and it is correlated.

If all antennas have the same gain,  $G_{ANT}$ , Directional gain =  $G_{ANT} + \text{Array Gain}$ , where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,  
Array Gain =  $10 \log (N_{ANT} / N_{SS})$  dB = 3.01;
- For power measurements on IEEE 802.11 devices,  
Array Gain = 0 dB for  $N_{ANT} \leq 4$ ;

If antenna gains are not equal, Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{ANT}$  set equal to the gain of the antenna having the highest gain.

Note 2: The EUT also supports Beamforming mode, and the Beamforming support 802.11n/ac/ax, not include 802.11a/b/g. The directional gain =  $G_{ANT} + \text{Array Gain}$  (3.01dBi).

Note 3: Antenna type and antenna gain are provided by the manufacturer.

Note 4: Antenna Kit: MFR: SERCOM; M/N: ALE\_OAW-AP1301.

## 5.4. 輻射干擾測試

### 5.4.1. 適用標準

依據國家通訊傳播委員會低功率射頻電機技術規範之第 4.10.1.5 節，使用頻帶範圍外之任意 100 千赫 (kHz) 內，發射器所產生的射頻功率相較於使用頻帶範圍中包含最高所需功率之 100 千赫 (kHz) 內的射頻功率，衰減值限制如下：

(1) 輸出功率以低功率射頻電機技術規範附件二之峰值輸出功率方式量測者，至少須衰減 20 dB，可使用射頻傳導或輻射方式測量。

(2) 輸出功率以低功率射頻電機技術規範 4.10.1(2)(2.3) 之最大傳導輸出功率量測方式者，至少須衰減 30 dB。

此外，落於第 3.5 節禁用頻段之輻射發射，應符合第 3.6 節之規定。

依據國家通訊傳播委員會低功率射頻電機技術規範之第 3.6 節，低功率射頻電機，除本規範各章節另有放寬規定者外，其電場強度不得超過下表之限值，且其不必要之發射皆不得大於主波發射強度。各頻段重疊處，以較嚴格之限制值為準。

| 頻率(f)<br>(MHz)            | 電場強度<br>(微伏特/公尺, $\mu\text{V/m}$ ) | 測距<br>(公尺) |
|---------------------------|------------------------------------|------------|
| $0.009 \leq f \leq 0.490$ | $2400/f(\text{kHz})$               | 300        |
| $0.490 < f \leq 1.705$    | $24000/f(\text{kHz})$              | 30         |
| $1.705 < f < 30$          | 30                                 | 30         |
| $30 \leq f \leq 88$       | 100                                | 3          |
| $88 < f \leq 216$         | 150                                | 3          |
| $216 < f \leq 960$        | 200                                | 3          |
| $960 < f$                 | 500                                | 3          |


上表規定之電場強度，發射頻率在 9 kHz~90 kHz、110 kHz~490 kHz 及 1000MHz 以上者，其量測應以平均值檢波器為基準，且須符合低功率射頻電機技術規範第 6.14.節之規定；其他發射頻率，應以 CISPR 準峰值(quasi-peak) 檢波器測量；非以上表所指定之距離測量時，應符合第 6.5 節之規定，而輻射發射之量測頻率範圍須符合低功率射頻電機技術規範第 6.12 節之規定。

### 5.4.2. 量測方法


低頻待測物置於高 80 公分之非導體桌面（落地型產品置於地上），高頻待測物置於高 150 公分之非導體桌面，受測物與配件設備之電源線無須束綁，桌面上受測設備的所有電源線由桌子的後緣垂下沿旋轉桌表面接至交流插座。落地型設備的交流電源線可以方便的型態走線。桌面可 360 度旋轉，接收天線置於距待測物 3m 距離，高度可在 1 至 4 公尺間變動，以量測待測物之最大輻射電場強度。接收天線並應於水準及垂直極化方向各量測一次。

### 5.4.3. 測試架構圖

#### Below 1GHz Test Setup:




#### Above 1GHz Test Setup:



#### 5.4.4. 輻射干擾測試結果

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBUV) | C.F (dB) | Measurement (dBUV/m) | Margin (dB) | Limit (dBUV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4128.000        | 38.80          | 1.31     | 40.11                | -33.89      | 74.00          | Peak              |
| 2  | 4825.000        | 38.71          | 3.33     | 42.04                | -31.96      | 74.00          | Peak              |
| 3  | 5760.000        | 36.03          | 5.11     | 41.14                | -32.86      | 74.00          | Peak              |
| 4  | * 7919.000      | 34.82          | 12.40    | 47.22                | -26.78      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                               | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No |      | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|------|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 0.00 | 3669.000        | 40.17          | -0.26    | 39.91                | -34.09      | 74.00          | Peak              |
| 2  | 0.00 | 4825.000        | 39.61          | 3.33     | 42.94                | -31.06      | 74.00          | Peak              |
| 3  | 0.00 | 6372.000        | 36.45          | 7.53     | 43.98                | -30.02      | 74.00          | Peak              |
| 4  | *    | 7987.000        | 33.99          | 12.51    | 46.50                | -27.50      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4026.000        | 37.25          | 0.97     | 38.22                | -35.78      | 74.00          | Peak              |
| 2  | 4876.000        | 39.58          | 3.45     | 43.03                | -30.97      | 74.00          | Peak              |
| 3  | 6253.000        | 37.70          | 7.01     | 44.70                | -29.30      | 74.00          | Peak              |
| 4  | * 7987.000      | 34.16          | 12.51    | 46.67                | -27.33      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                               | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4060.000        | 37.34          | 1.08     | 38.42                | -35.58      | 74.00          | Peak              |
| 2  | 4876.000        | 40.07          | 3.45     | 43.52                | -30.48      | 74.00          | Peak              |
| 3  | 6610.000        | 34.72          | 8.58     | 43.30                | -30.70      | 74.00          | Peak              |
| 4  | * 7919.000      | 34.15          | 12.40    | 46.55                | -27.45      | 74.00          | Peak              |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
- Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4043.000        | 38.11          | 1.02     | 39.14                | -34.86      | 74.00          | Peak              |
| 2  | 4927.000        | 42.66          | 3.57     | 46.24                | -27.76      | 74.00          | Peak              |
| 3  | 6253.000        | 37.88          | 7.01     | 44.89                | -29.11      | 74.00          | Peak              |
| 4  | * 7817.000      | 34.55          | 12.23    | 46.78                | -27.22      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                               | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 3873.000        | 37.58          | 0.44     | 38.03                | -35.97      | 74.00          | Peak              |
| 2  | * 4927.000      | 45.94          | 3.57     | 49.51                | -24.49      | 74.00          | Peak              |
| 3  | 6882.000        | 35.08          | 9.78     | 44.86                | -29.14      | 74.00          | Peak              |
| 4  | 7902.000        | 34.34          | 12.37    | 46.71                | -27.29      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11g at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4145.000        | 36.95          | 1.36     | 38.32                | -35.68      | 74.00          | Peak              |
| 2  | 4825.000        | 38.14          | 3.33     | 41.47                | -32.53      | 74.00          | Peak              |
| 3  | 6253.000        | 35.93          | 7.01     | 42.94                | -31.06      | 74.00          | Peak              |
| 4  | * 7936.000      | 34.97          | 12.43    | 47.40                | -26.60      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                               | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11g at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4128.000        | 37.42          | 1.31     | 38.73                | -35.27      | 74.00          | Peak              |
| 2  | 4825.000        | 40.54          | 3.33     | 43.87                | -30.13      | 74.00          | Peak              |
| 3  | 7171.000        | 34.94          | 10.78    | 45.73                | -28.27      | 74.00          | Peak              |
| 4  | * 7970.000      | 34.18          | 12.48    | 46.66                | -27.34      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11g at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4026.000        | 37.86          | 0.97     | 38.82                | -35.18      | 74.00          | Peak              |
| 2  | 4876.000        | 39.27          | 3.45     | 42.72                | -31.28      | 74.00          | Peak              |
| 3  | 6253.000        | 36.54          | 7.01     | 43.54                | -30.46      | 74.00          | Peak              |
| 4  | * 7902.000      | 34.56          | 12.37    | 46.93                | -27.07      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                               | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11g at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 3941.000        | 37.07          | 0.68     | 37.75                | -36.25      | 74.00          | Peak              |
| 2  | 4876.000        | 40.64          | 3.45     | 44.09                | -29.91      | 74.00          | Peak              |
| 3  | 6338.000        | 35.84          | 7.38     | 43.22                | -30.78      | 74.00          | Peak              |
| 4  | * 7783.000      | 33.84          | 12.18    | 46.02                | -27.98      | 74.00          | Peak              |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
- Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11g at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 3771.000        | 37.91          | 0.09     | 38.00                | -36.00      | 74.00          | Peak              |
| 2  | 4927.000        | 42.08          | 3.57     | 45.65                | -28.35      | 74.00          | Peak              |
| 3  | 6253.000        | 37.95          | 7.01     | 44.96                | -29.04      | 74.00          | Peak              |
| 4  | * 7919.000      | 34.35          | 12.40    | 46.75                | -27.25      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                             | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                               | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11g at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 3958.000        | 37.80          | 0.74     | 38.54                | -35.46      | 74.00          | Peak              |
| 2  | * 4927.000      | 45.85          | 3.57     | 49.43                | -24.57      | 74.00          | Peak              |
| 3  | 6508.000        | 35.53          | 8.13     | 43.66                | -30.34      | 74.00          | Peak              |
| 4  | 7868.000        | 34.03          | 12.31    | 46.35                | -27.65      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                  | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT20 at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4298.000        | 38.08          | 1.88     | 39.96                | -34.04      | 74.00          | Peak              |
| 2  | 4825.000        | 38.21          | 3.33     | 41.54                | -32.46      | 74.00          | Peak              |
| 3  | 6253.000        | 36.56          | 7.01     | 43.57                | -30.43      | 74.00          | Peak              |
| 4  | * 7902.000      | 33.98          | 12.37    | 46.35                | -27.65      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                    | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT20 at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4128.000        | 38.03          | 1.31     | 39.34                | -34.66      | 74.00          | Peak              |
| 2  | 4825.000        | 39.50          | 3.33     | 42.83                | -31.17      | 74.00          | Peak              |
| 3  | 6610.000        | 34.88          | 8.58     | 43.46                | -30.54      | 74.00          | Peak              |
| 4  | * 7953.000      | 34.77          | 12.45    | 47.22                | -26.78      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                  | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT20 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4162.000        | 37.48          | 1.42     | 38.90                | -35.10      | 74.00          | Peak              |
| 2  | 4995.000        | 36.20          | 3.74     | 39.94                | -34.06      | 74.00          | Peak              |
| 3  | 6253.000        | 36.79          | 7.01     | 43.80                | -30.20      | 74.00          | Peak              |
| 4  | * 7936.000      | 34.22          | 12.43    | 46.65                | -27.35      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                    | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT20 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4281.000        | 36.63          | 1.82     | 38.44                | -35.56      | 74.00          | Peak              |
| 2  | 4893.000        | 36.74          | 3.49     | 40.24                | -33.76      | 74.00          | Peak              |
| 3  | 6508.000        | 36.03          | 8.13     | 44.16                | -29.84      | 74.00          | Peak              |
| 4  | * 7868.000      | 34.58          | 12.31    | 46.89                | -27.11      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                  | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT20 at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4213.000        | 36.87          | 1.59     | 38.46                | -35.54      | 74.00          | Peak              |
| 2  | 4927.000        | 42.21          | 3.57     | 45.79                | -28.21      | 74.00          | Peak              |
| 3  | 6253.000        | 37.59          | 7.01     | 44.60                | -29.40      | 74.00          | Peak              |
| 4  | * 7987.000      | 33.89          | 12.51    | 46.40                | -27.60      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                    | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT20 at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4230.000        | 37.88          | 1.65     | 39.53                | -34.47      | 74.00          | Peak              |
| 2  | * 4927.000      | 44.39          | 3.57     | 47.97                | -26.03      | 74.00          | Peak              |
| 3  | 6151.000        | 36.23          | 6.56     | 42.79                | -31.21      | 74.00          | Peak              |
| 4  | 7868.000        | 34.10          | 12.31    | 46.41                | -27.59      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                  | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT40 at Channel 2422MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4349.000        | 36.86          | 2.05     | 38.90                | -35.10      | 74.00          | Peak              |
| 2  | 4825.000        | 36.21          | 3.33     | 39.54                | -34.46      | 74.00          | Peak              |
| 3  | 6253.000        | 36.94          | 7.01     | 43.95                | -30.05      | 74.00          | Peak              |
| 4  | * 7868.000      | 34.38          | 12.31    | 46.69                | -27.31      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                    | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT40 at Channel 2422MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4128.000        | 36.64          | 1.31     | 37.95                | -36.05      | 74.00          | Peak              |
| 2  | 4995.000        | 36.31          | 3.74     | 40.05                | -33.95      | 74.00          | Peak              |
| 3  | 5998.000        | 36.06          | 5.88     | 41.95                | -32.05      | 74.00          | Peak              |
| 4  | * 7834.000      | 33.98          | 12.26    | 46.24                | -27.76      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                  | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT40 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4281.000        | 35.94          | 1.82     | 37.76                | -36.25      | 74.00          | Peak              |
| 2  | 4893.000        | 36.24          | 3.49     | 39.73                | -34.27      | 74.00          | Peak              |
| 3  | 6253.000        | 35.99          | 7.01     | 42.99                | -31.01      | 74.00          | Peak              |
| 4  | * 7936.000      | 33.35          | 12.43    | 45.78                | -28.22      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                    | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT40 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 3992.000        | 37.06          | 0.85     | 37.91                | -36.09      | 74.00          | Peak              |
| 2  | 4876.000        | 36.38          | 3.45     | 39.83                | -34.17      | 74.00          | Peak              |
| 3  | 6559.000        | 34.87          | 8.36     | 43.23                | -30.77      | 74.00          | Peak              |
| 4  | * 7970.000      | 34.16          | 12.48    | 46.64                | -27.36      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                  | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT40 at Channel 2452MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4315.000        | 37.53          | 1.93     | 39.46                | -34.54      | 74.00          | Peak              |
| 2  | 4927.000        | 37.61          | 3.57     | 41.19                | -32.81      | 74.00          | Peak              |
| 3  | 6253.000        | 36.41          | 7.01     | 43.42                | -30.58      | 74.00          | Peak              |
| 4  | * 7834.000      | 35.37          | 12.26    | 47.63                | -26.37      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                             |                      |                |
|-----------|---------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                  | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                  | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                    | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11n-HT40 at Channel 2452MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4094.000        | 37.11          | 1.19     | 38.31                | -35.69      | 74.00          | Peak              |
| 2  | 4927.000        | 37.86          | 3.57     | 41.43                | -32.57      | 74.00          | Peak              |
| 3  | 6525.000        | 35.38          | 8.21     | 43.58                | -30.42      | 74.00          | Peak              |
| 4  | * 7783.000      | 34.43          | 12.18    | 46.61                | -27.39      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                           | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT20 at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4145.000        | 36.63          | 1.36     | 37.99                | -36.01      | 74.00          | Peak              |
| 2  | 4825.000        | 37.96          | 3.33     | 41.29                | -32.71      | 74.00          | Peak              |
| 3  | * 7035.000      | 35.83          | 10.40    | 46.23                | -27.77      | 74.00          | Peak              |
| 4  | 7902.000        | 33.66          | 12.37    | 46.03                | -27.97      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT20 at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4230.000        | 37.44          | 1.65     | 39.09                | -34.91      | 74.00          | Peak              |
| 2  | 4825.000        | 37.17          | 3.33     | 40.50                | -33.50      | 74.00          | Peak              |
| 3  | 6066.000        | 36.18          | 6.18     | 42.36                | -31.64      | 74.00          | Peak              |
| 4  | * 7970.000      | 33.63          | 12.48    | 46.11                | -27.89      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                           | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT20 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4298.000        | 36.66          | 1.88     | 38.53                | -35.47      | 74.00          | Peak              |
| 2  | 4740.000        | 36.94          | 3.13     | 40.06                | -33.94      | 74.00          | Peak              |
| 3  | 6253.000        | 37.14          | 7.01     | 44.15                | -29.85      | 74.00          | Peak              |
| 4  | * 7936.000      | 34.32          | 12.43    | 46.74                | -27.26      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT20 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 3652.000        | 39.78          | -0.32    | 39.46                | -34.54      | 74.00          | Peak              |
| 2  | 4910.000        | 36.38          | 3.53     | 39.91                | -34.09      | 74.00          | Peak              |
| 3  | 7018.000        | 34.32          | 10.35    | 44.67                | -29.33      | 74.00          | Peak              |
| 4  | * 7987.000      | 34.10          | 12.51    | 46.61                | -27.39      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                           | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT20 at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 3873.000        | 37.94          | 0.44     | 38.39                | -35.61      | 74.00          | Peak              |
| 2  | 4927.000        | 38.20          | 3.57     | 41.78                | -32.22      | 74.00          | Peak              |
| 3  | 6253.000        | 37.59          | 7.01     | 44.60                | -29.40      | 74.00          | Peak              |
| 4  | * 7919.000      | 34.37          | 12.40    | 46.77                | -27.23      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT20 at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4128.000        | 36.91          | 1.31     | 38.22                | -35.78      | 74.00          | Peak              |
| 2  | 4927.000        | 39.70          | 3.57     | 43.27                | -30.73      | 74.00          | Peak              |
| 3  | 6542.000        | 35.33          | 8.28     | 43.61                | -30.39      | 74.00          | Peak              |
| 4  | * 8650.000      | 36.06          | 12.82    | 48.88                | -25.12      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                           | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT40 at Channel 2422MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4230.000        | 37.97          | 1.65     | 39.62                | -34.38      | 74.00          | Peak              |
| 2  | 4842.000        | 36.68          | 3.37     | 40.05                | -33.95      | 74.00          | Peak              |
| 3  | 6253.000        | 36.73          | 7.01     | 43.73                | -30.27      | 74.00          | Peak              |
| 4  | * 7936.000      | 34.18          | 12.43    | 46.60                | -27.40      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT40 at Channel 2422MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4366.000        | 37.99          | 2.10     | 40.09                | -33.91      | 74.00          | Peak              |
| 2  | 4893.000        | 37.63          | 3.49     | 41.12                | -32.88      | 74.00          | Peak              |
| 3  | * 7188.000      | 36.00          | 10.83    | 46.84                | -27.16      | 74.00          | Peak              |
| 4  | 7970.000        | 33.71          | 12.48    | 46.19                | -27.81      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                           | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT40 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4026.000        | 37.77          | 0.97     | 38.73                | -35.27      | 74.00          | Peak              |
| 2  | 4638.000        | 37.78          | 2.88     | 40.66                | -33.34      | 74.00          | Peak              |
| 3  | 6253.000        | 37.69          | 7.01     | 44.69                | -29.31      | 74.00          | Peak              |
| 4  | * 7919.000      | 34.23          | 12.40    | 46.62                | -27.38      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT40 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4213.000        | 36.12          | 1.59     | 37.71                | -36.29      | 74.00          | Peak              |
| 2  | 4876.000        | 37.79          | 3.45     | 41.24                | -32.76      | 74.00          | Peak              |
| 3  | 6100.000        | 36.29          | 6.33     | 42.62                | -31.38      | 74.00          | Peak              |
| 4  | * 8021.000      | 34.30          | 12.53    | 46.82                | -27.18      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                           | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT40 at Channel 2452MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4060.000        | 36.82          | 1.08     | 37.90                | -36.10      | 74.00          | Peak              |
| 2  | 4876.000        | 37.07          | 3.45     | 40.52                | -33.48      | 74.00          | Peak              |
| 3  | 6372.000        | 37.13          | 7.53     | 44.66                | -29.34      | 74.00          | Peak              |
| 4  | * 7868.000      | 34.56          | 12.31    | 46.87                | -27.13      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                      |                      |                |
|-----------|--------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                           | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                           | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by VHT40 at Channel 2452MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4332.000        | 37.46          | 1.99     | 39.45                | -34.55      | 74.00          | Peak              |
| 2  | 4910.000        | 37.79          | 3.53     | 41.32                | -32.68      | 74.00          | Peak              |
| 3  | 6525.000        | 35.45          | 8.21     | 43.65                | -30.35      | 74.00          | Peak              |
| 4  | * 7936.000      | 34.65          | 12.43    | 47.08                | -26.92      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                   | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE20 at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4060.000        | 37.08          | 1.08     | 38.16                | -35.84      | 74.00          | Peak              |
| 2  | 4808.000        | 37.78          | 3.29     | 41.07                | -32.93      | 74.00          | Peak              |
| 3  | 6253.000        | 36.89          | 7.01     | 43.90                | -30.10      | 74.00          | Peak              |
| 4  | * 7902.000      | 34.49          | 12.37    | 46.86                | -27.14      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                     | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE20 at Channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4298.000        | 37.29          | 1.88     | 39.17                | -34.83      | 74.00          | Peak              |
| 2  | 4825.000        | 36.98          | 3.33     | 40.31                | -33.69      | 74.00          | Peak              |
| 3  | 6576.000        | 34.96          | 8.43     | 43.39                | -30.61      | 74.00          | Peak              |
| 4  | * 7868.000      | 34.21          | 12.31    | 46.53                | -27.47      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                   | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE20 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4162.000        | 37.15          | 1.42     | 38.57                | -35.43      | 74.00          | Peak              |
| 2  | 5012.000        | 36.30          | 3.76     | 40.06                | -33.94      | 74.00          | Peak              |
| 3  | 6253.000        | 37.47          | 7.01     | 44.47                | -29.53      | 74.00          | Peak              |
| 4  | * 7902.000      | 33.65          | 12.37    | 46.02                | -27.98      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                     | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE20 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4128.000        | 37.26          | 1.31     | 38.57                | -35.43      | 74.00          | Peak              |
| 2  | 4536.000        | 37.95          | 2.64     | 40.59                | -33.41      | 74.00          | Peak              |
| 3  | 6355.000        | 35.91          | 7.46     | 43.37                | -30.63      | 74.00          | Peak              |
| 4  | * 7851.000      | 34.90          | 12.29    | 47.19                | -26.81      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                   | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE20 at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4196.000        | 36.78          | 1.53     | 38.32                | -35.68      | 74.00          | Peak              |
| 2  | 4927.000        | 36.86          | 3.57     | 40.44                | -33.56      | 74.00          | Peak              |
| 3  | 6253.000        | 36.98          | 7.01     | 43.99                | -30.01      | 74.00          | Peak              |
| 4  | * 7919.000      | 34.13          | 12.40    | 46.53                | -27.47      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                     | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE20 at Channel 2462MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4077.000        | 37.93          | 1.14     | 39.07                | -34.93      | 74.00          | Peak              |
| 2  | 4927.000        | 39.59          | 3.57     | 43.16                | -30.84      | 74.00          | Peak              |
| 3  | 6338.000        | 36.07          | 7.38     | 43.45                | -30.55      | 74.00          | Peak              |
| 4  | * 7936.000      | 34.02          | 12.43    | 46.45                | -27.55      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                   | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE40 at Channel 2422MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4162.000        | 37.79          | 1.42     | 39.21                | -34.79      | 74.00          | Peak              |
| 2  | 4927.000        | 36.60          | 3.57     | 40.18                | -33.82      | 74.00          | Peak              |
| 3  | 6474.000        | 35.56          | 7.98     | 43.54                | -30.46      | 74.00          | Peak              |
| 4  | * 7902.000      | 33.81          | 12.37    | 46.18                | -27.82      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                     | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE40 at Channel 2422MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4162.000        | 37.02          | 1.42     | 38.44                | -35.56      | 74.00          | Peak              |
| 2  | 4740.000        | 37.74          | 3.13     | 40.87                | -33.13      | 74.00          | Peak              |
| 3  | 6525.000        | 35.24          | 8.21     | 43.45                | -30.55      | 74.00          | Peak              |
| 4  | * 7970.000      | 33.95          | 12.48    | 46.43                | -27.57      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                   | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE40 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4026.000        | 37.24          | 0.97     | 38.21                | -35.79      | 74.00          | Peak              |
| 2  | 4808.000        | 38.02          | 3.29     | 41.31                | -32.69      | 74.00          | Peak              |
| 3  | 6253.000        | 37.18          | 7.01     | 44.19                | -29.81      | 74.00          | Peak              |
| 4  | * 7868.000      | 34.05          | 12.31    | 46.36                | -27.64      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                     | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE40 at Channel 2437MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4026.000        | 37.21          | 0.97     | 38.18                | -35.82      | 74.00          | Peak              |
| 2  | 4876.000        | 37.40          | 3.45     | 40.85                | -33.15      | 74.00          | Peak              |
| 3  | 6559.000        | 34.85          | 8.36     | 43.21                | -30.79      | 74.00          | Peak              |
| 4  | * 7936.000      | 34.06          | 12.43    | 46.49                | -27.51      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Horizontal                                   | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE40 at Channel 2452MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4128.000        | 37.55          | 1.31     | 38.86                | -35.14      | 74.00          | Peak              |
| 2  | 4910.000        | 38.13          | 3.53     | 41.66                | -32.34      | 74.00          | Peak              |
| 3  | 6253.000        | 36.54          | 7.01     | 43.54                | -30.46      | 74.00          | Peak              |
| 4  | * 7885.000      | 35.22          | 12.34    | 47.56                | -26.44      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                                              |                      |                |
|-----------|----------------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                                   | Date of Test         | 2020-10-17     |
| Factor    | BBHA 9120D                                   | Temp. / Humidity     | 25.4°C/48.4%   |
| Polarity  | Vertical                                     | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11ax-HE40 at Channel 2452MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 4060.000        | 37.81          | 1.08     | 38.89                | -35.11      | 74.00          | Peak              |
| 2  | 4910.000        | 37.43          | 3.53     | 40.96                | -33.04      | 74.00          | Peak              |
| 3  | 6253.000        | 36.29          | 7.01     | 43.30                | -30.70      | 74.00          | Peak              |
| 4  | * 7970.000      | 33.82          | 12.48    | 46.30                | -27.70      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

### The worst case of Radiated Emission below 1GHz:

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-11-29     |
| Factor    | VULB 9162                              | Temp. / Humidity     | 25°C /54%      |
| Polarity  | Horizontal                             | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 49.400          | -6.29          | 22.02    | 15.73                | -24.27      | 40.00          | QP                |
| 2  | 104.205         | -4.17          | 18.98    | 14.81                | -28.69      | 43.50          | QP                |
| 3  | 281.715         | -3.30          | 21.08    | 17.78                | -28.22      | 46.00          | QP                |
| 4  | 519.850         | -4.38          | 26.45    | 22.07                | -23.93      | 46.00          | QP                |
| 5  | 727.430         | -4.48          | 29.75    | 25.27                | -20.73      | 46.00          | QP                |
| 6  | * 898.150       | -4.47          | 31.76    | 27.29                | -18.71      | 46.00          | QP                |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- The amplitude of Radiated emissions (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

|           |                                        |                      |                |
|-----------|----------------------------------------|----------------------|----------------|
| EUT       | OAW-AP1301                             | Date of Test         | 2020-11-29     |
| Factor    | VULB 9162                              | Temp. / Humidity     | 25°C /54%      |
| Polarity  | Vertical                               | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | Transmit by 802.11b at channel 2412MHz | Test Voltage         | 110V/60Hz      |




| No | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 33.880          | -1.74          | 19.11    | 17.37                | -22.63      | 40.00          | QP                |
| 2  | 50.855          | -3.12          | 21.89    | 18.77                | -21.23      | 40.00          | QP                |
| 3  | 447.100         | -4.78          | 24.84    | 20.06                | -25.94      | 46.00          | QP                |
| 4  | 533.915         | -5.22          | 26.62    | 21.40                | -24.60      | 46.00          | QP                |
| 5  | 695.420         | -5.04          | 29.25    | 24.21                | -21.79      | 46.00          | QP                |
| 6  | * 859.350       | -3.11          | 31.54    | 28.43                | -17.57      | 46.00          | QP                |

Note:

- "\*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- The amplitude of Radiated emissions (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

**Co-location Mode:**

|           |                              |                      |                |
|-----------|------------------------------|----------------------|----------------|
| EUT       | OAW-AP1311                   | Date of Test         | 2020-10-12     |
| Factor    | BBHA 9120D                   | Temp. / Humidity     | 25.8°C/48.0%   |
| Polarity  | Horizontal                   | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | 2.4G Wi-Fi+5G Wi-Fi Transmit | Test Voltage         | 110V/60Hz      |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  |   | 3745.500        | 43.04          | 0.00     | 43.05                | -30.95      | 74.00          | Peak              |
| 2  | * | 4808.000        | 48.97          | 3.29     | 52.26                | -21.74      | 74.00          | Peak              |
| 3  |   | 6941.500        | 36.30          | 10.04    | 46.35                | -27.65      | 74.00          | Peak              |
| 4  |   | 7953.000        | 36.55          | 12.45    | 49.00                | -25.00      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                              |                      |                |
|-----------|------------------------------|----------------------|----------------|
| EUT       | OAW-AP1311                   | Date of Test         | 2020-10-12     |
| Factor    | BBHA 9120D                   | Temp. / Humidity     | 25.8°C/48.0%   |
| Polarity  | Vertical                     | Site / Test Engineer | AC1 / Jay Chiu |
| Test Mode | 2.4G Wi-Fi+5G Wi-Fi Transmit | Test Voltage         | 110V/60Hz      |




| No |   | Frequency (MHz) | Reading (dBuV) | C.F (dB) | Measurement (dBuV/m) | Margin (dB) | Limit (dBuV/m) | Remark (QP/PK/AV) |
|----|---|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  |   | 4000.500        | 39.57          | 0.88     | 40.45                | -33.55      | 74.00          | Peak              |
| 2  | * | 4808.000        | 51.16          | 3.29     | 54.45                | -19.55      | 74.00          | Peak              |
| 3  |   | 4804.000        | 47.93          | 3.29     | 51.22                | -2.78       | 54.00          | Average           |
| 4  |   | 6703.500        | 36.91          | 8.99     | 45.90                | -28.10      | 74.00          | Peak              |
| 5  |   | 7876.500        | 38.47          | 12.33    | 50.79                | -23.21      | 74.00          | Peak              |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB)– Preamplifier(dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                  |                      |                 |
|-----------|------------------|----------------------|-----------------|
| EUT       | OAW-AP1301       | Date of Test         | 2020-10-13      |
| Factor    | VULB 9162        | Temp. / Humidity     | 25°C /54%       |
| Polarity  | Horizontal       | Site / Test Engineer | AC1 / Kevin Ker |
| Test Mode | Normal operation | Test Voltage         | 110V/60Hz       |




| No | Frequency (MHz) | Reading (dBUV) | C.F (dB) | Measurement (dBUV/m) | Margin (dB) | Limit (dBUV/m) | Remark (QP/PK/AV) |
|----|-----------------|----------------|----------|----------------------|-------------|----------------|-------------------|
| 1  | 99.840          | 0.20           | 19.64    | 19.84                | -23.66      | 43.50          | QP                |
| 2  | 228.365         | 0.21           | 19.73    | 19.94                | -26.06      | 46.00          | QP                |
| 3  | 303.260         | 2.15           | 21.53    | 23.68                | -22.32      | 46.00          | QP                |
| 4  | 566.320         | 0.86           | 26.90    | 27.76                | -18.24      | 46.00          | QP                |
| 5  | 667.210         | 0.66           | 28.62    | 29.28                | -16.72      | 46.00          | QP                |
| 6  | * 854.320       | 0.54           | 31.30    | 31.84                | -14.16      | 46.00          | QP                |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement(dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

|           |                  |                      |                 |
|-----------|------------------|----------------------|-----------------|
| EUT       | OAW-AP1301       | Date of Test         | 2020-10-13      |
| Factor    | VULB 9162        | Temp. / Humidity     | 25°C /54%       |
| Polarity  | Vertical         | Site / Test Engineer | AC1 / Kevin Ker |
| Test Mode | Normal operation | Test Voltage         | 110V/60Hz       |



| No |   | Frequency<br>(MHz) | Reading<br>(dBuV) | C.F<br>(dB) | Measurement<br>(dBuV/m) | Margin<br>(dB) | Limit<br>(dBuV/m) | Remark<br>(QP/PK/AV) |
|----|---|--------------------|-------------------|-------------|-------------------------|----------------|-------------------|----------------------|
| 1  | * | 64.210             | 3.21              | 18.58       | 21.79                   | -18.21         | 40.00             | QP                   |
| 2  |   | 107.210            | 1.21              | 18.98       | 20.19                   | -23.31         | 43.50             | QP                   |
| 3  |   | 229.360            | 1.02              | 19.81       | 20.83                   | -25.17         | 46.00             | QP                   |
| 4  |   | 387.650            | 1.14              | 23.98       | 25.12                   | -20.88         | 46.00             | QP                   |
| 5  |   | 532.600            | 0.96              | 26.34       | 27.30                   | -18.70         | 46.00             | QP                   |
| 6  |   | 752.300            | 1.25              | 29.83       | 31.08                   | -14.92         | 46.00             | QP                   |

Note:

1. " \*", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement(dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- 4.The emission levels of other frequencies are very lower than the limit and not show in test report.

## 5.5. 混附發射之 RF 傳導發射

### 5.5.1. 適用標準

依據國家通訊傳播委員會低功率射頻電機技術規範之第 4.10.1.5 節，使用頻帶範圍外之任意 100 千赫 (kHz) 內，發射機所產生的射頻功率相較於使用頻帶範圍中包含最高所需功率之 100 千赫 (kHz) 內的射頻功率，至少須衰減 20 dB，以射頻傳導或輻射方式測量。如發射機以本節 4.10.1(2)(2.3) 之峰值傳導輸出功率量測方式者，至少須衰減 30 dB。此外，落於第 3.5 節禁用頻段之輻射發射，應符合第 3.6 節之規定。

#### 備註

解析頻寬設置為 1.3 MHz 是為了提供量測速度。使用限值還是法規定義的基於解析頻寬 100 kHz 情形下主波下降 20dB，如果量測波形接近限值，我們會使用降低解析頻寬方式作驗證。


### 5.5.2. 量測方法

依據國家通訊傳播委員會低功率射頻電機技術規範之附件三，頻率跳頻展頻系統檢測之參考程式七 混附發射之 RF 傳導發射：

(一) 頻譜分析儀設定如下：

1. 頻率掃描範圍足以檢測頻帶內的發射波峰位準以及由受測物產生之最低頻率到第 10 次諧波的所有混附發射，通常需要分幾段以涵蓋全部頻率範圍。
2. 解析頻寬為 100kHz，視訊頻寬不小於解析頻寬。
3. 掃描時間為自動，檢波功能為峰值，訊號軌跡為最大保留(Max Hold)。
4. 將標記設定於任何欲紀錄之波峰上，所顯示之位準值必須符合指定之限制值。

### 5.5.3. 測試架構圖



#### 5.5.4. 混附發射之 RF 傳導發射測試結果


|       |                                |      |            |
|-------|--------------------------------|------|------------|
| 待測物名稱 | OmniAccess Stellar, OAW-AP1301 | 溫度   | 23 ~ 25°C  |
| 測試工程師 | Eric Lin                       | 濕度   | 48 ~ 54%   |
| 測試場地  | SR2                            | 測試日期 | 2020/11/18 |
| 型號    | OAW-AP1301                     |      |            |

| Test Mode | Data Rate (Mbps) | Channel No. | Frequency (MHz) | Limit | Result |
|-----------|------------------|-------------|-----------------|-------|--------|
| 11b       | 1Mbps            | 01          | 2412            | 30dBc | Pass   |
| 11b       | 1Mbps            | 06          | 2437            | 30dBc | Pass   |
| 11b       | 1Mbps            | 11          | 2462            | 30dBc | Pass   |
| 11g       | 6Mbps            | 01          | 2412            | 30dBc | Pass   |
| 11g       | 6Mbps            | 06          | 2437            | 30dBc | Pass   |
| 11g       | 6Mbps            | 11          | 2462            | 30dBc | Pass   |
| 11n-HT20  | MCS0             | 01          | 2412            | 30dBc | Pass   |
| 11n-HT20  | MCS0             | 06          | 2437            | 30dBc | Pass   |
| 11n-HT20  | MCS0             | 11          | 2462            | 30dBc | Pass   |
| 11n-HT40  | MCS0             | 03          | 2422            | 30dBc | Pass   |
| 11n-HT40  | MCS0             | 06          | 2437            | 30dBc | Pass   |
| 11n-HT40  | MCS0             | 09          | 2452            | 30dBc | Pass   |
| VHT20     | MCS0             | 01          | 2412            | 30dBc | Pass   |
| VHT20     | MCS0             | 06          | 2437            | 30dBc | Pass   |
| VHT20     | MCS0             | 11          | 2462            | 30dBc | Pass   |
| VHT40     | MCS0             | 03          | 2422            | 30dBc | Pass   |
| VHT40     | MCS0             | 06          | 2437            | 30dBc | Pass   |
| VHT40     | MCS0             | 09          | 2452            | 30dBc | Pass   |
| 11ax-HE20 | MCS0             | 01          | 2412            | 30dBc | Pass   |
| 11ax-HE20 | MCS0             | 06          | 2437            | 30dBc | Pass   |
| 11ax-HE20 | MCS0             | 11          | 2462            | 30dBc | Pass   |
| 11ax-HE40 | MCS0             | 03          | 2422            | 30dBc | Pass   |
| 11ax-HE40 | MCS0             | 06          | 2437            | 30dBc | Pass   |
| 11ax-HE40 | MCS0             | 09          | 2452            | 30dBc | Pass   |

## 802.11b Out-of-Band Emissions - Ant 0 / Ant 0 + 1

## Channel 01 (2412MHz)

## 100kHz PSD reference Level



## Low Band Edge




## Spurious Emission




## Channel 06 (2437MHz)

## 100kHz PSD reference Level




## Spurious Emission



## Channel 11 (2462MHz)

## 100kHz PSD reference Level



## High Band Edge




## Spurious Emission



## 802.11g Out-of-Band Emissions- Ant 0 / Ant 0 + 1

### Channel 01 (2412MHz)


#### 100kHz PSD reference Level



#### Low Band Edge



#### Spurious Emission



### Channel 06 (2437MHz)

#### 100kHz PSD reference Level




#### Spurious Emission



## Channel 11 (2462MHz)


### 100kHz PSD reference Level



### High Band Edge




### Spurious Emission




## 802.11n-HT20 Out-of-Band Emissions- Ant 0 / Ant 0 + 1

## Channel 01 (2412MHz)


## 100kHz PSD reference Level



## Low Band Edge



## Spurious Emission



## Channel 06 (2437MHz)

## 100kHz PSD reference Level




## Spurious Emission




# Channel 11 (2462MHz)

## 100kHz PSD reference Level



## High Band Edge



## Spurious Emission

