

8THS

To read length in centimeters, omit the final zero after the index line. To read length in millimeters, include the final zero.

LINEAR METRIC
1000 millimeters

RUCKUS

LAN1+PoE

LAN2

LAN3

LAN4

8THS


To read length in centimeters, omit the final zero after the index line. To read length in millimeters, include the final zero.

LINEAR METRIC UNIT
1000 millimeters (m)

PWR ●
CTL ●
2.4G ●
5G ●

901-H510-WW00

SN: 221602011732
MAC: 1CB9C4230360



FC Tested To Comply With FCC Standards
FOR HOME OR OFFICE USE



R-NZ



UL US I.T.E.
LISTED E315548



PoE in LAN/Uplink



Ruckus®
Simply Better Wireless.

H510 Access Point

Default IP Address: 192.168.0.1

User name=super

Password=sp-admin

USI-SZ

FCC ID: S9GH510
IC: 5912A-H510
For indoor use only

48V --- 0.62A 48伏特 0.62安培

Made in China

Model: H510
Ruckus Wireless, Inc.

NCC 合格標籤位置
REGULATORY LABEL PLACEMENT



PCC ID: S9GH510
IC: S912A-H510
For indoor use only
48V $\Rightarrow$ 0.62A 48伏特 0.62安培

Made in China

Model: H510
Ruckus Wireless, Inc.

