



REPORT No.: SZ26010171W01

TEST REPORT

APPLICANT : Aptiv Services Poland S.A.

PRODUCT NAME : P-MIB4

MODEL NAME : P-MIB4

BRAND NAME : APTIV

STANDARD(S) : Article 2 Paragraph 1 of Item 19

RECEIPT DATE : 2026-01-19

TEST DATE : 2026-03-23 to 2026-07-15

ISSUE DATE : 2026-07-17



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Results	4
1.1. Testing Applied Methods	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	6
1.4. Testing Laboratory	6
2. General Description	7
2.1. Information of Applicant and Manufacturer	7
2.2. Information of EUT	7
2.3. Information of Antenna	8
2.4. Channel List of EUT	8
2.5. Test Configuration of EUT	9
2.6. Test Conditions	10
2.7. Test Setup Layout Diagram	11
3. Description of Test Items	12
3.1. Frequency Error	12
3.2. Occupied Bandwidth	13
3.3. Unwanted Emission Intensity	14
3.4. Antenna Power Error	15
3.5. Limitation of Collateral Emission of Receiver	16
3.6. E.I.R.P.	17
3.7. Radio Interference Prevention Capability	18
3.8. Construction Protection Confirmation Method	19
Annex A Test Data and Results	20
Notes	31



REPORT No.: SZ26010171W01

Change History		
Version	Date	Reason for change
1.0	2026-07-17	First edition

1. Summary of Test Results

No.	Description of Test	Test Engineer	Result	Remark
1	Frequency Error	Lin Haoyang	PASS	/
2	Occupied Bandwidth	Lin Haoyang	PASS	/
3	Unwanted Emission Intensity	Lin Haoyang	PASS	/
4	Antenna Power Error	Lin Haoyang	PASS	/
5	Limitation of Collateral Emission of Receiver	Lin Haoyang	PASS	/
6	E.I.R.P.	Lin Haoyang	PASS	/
7	Radio Interference Prevention Capability	Lin Haoyang	PASS	/
8	Construction Protection Confirmation	Lin Haoyang	PASS	/

Note 1: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".

1.1. Testing Applied Methods

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- MIC Notice No.88 Annex 43
- Certification of technical standard conformity for specified radio equipment, etc. Article 2 Paragraph 1 of Item 19
- Radio Equipment Regulations Article 49-20



1.2. Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Due Date	Cal. Body	Cal. Method
EXA Signal Analyzer	Agilent	N9010A	MY53470836	2025.12.23	2026.12.22	SMQ	c
DC Power Supply	IVYTECH	IV3610	1709D361010	2025.09.03	2026.09.02	CCIC	c
Power Sensor	Agilent	U2021XA	MY54180008	2025.09.03	2026.09.02	CCIC	c
Radio Communication Tester	R&S	CMW500	108950	2025.12.23	2026.12.22	CCIC	c

Note 1: The equipment were calibrated by CCIC (Shenzhen) Metrology&Testing Service Co.,Ltd and Shenzhen Academy of Metrology and Quality Inspection.

Note 2: Calibration Method:

- Calibration conducted by the National Institute of Information and Communications Technology (NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1);
- Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992);
- Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1);
- Calibration conducted by using measuring instruments and other equipment listed in the right column of Table No. 3 attached hereto, which shall have been given any of calibration, etc. listed above from a) to c).



REPORT No.: SZ26010171W01

1.3. Measurement Uncertainty

No.	Test Items	Uncertainty	Remark
1	Frequency Error / 99% Bandwidth	$\pm 1.75 \times 10^{-6}$	Confidence levels of 95%
2	Antenna Power	$\pm 1.14\text{dB}$	Confidence levels of 95%
3	Spurious Emissions(<1GHz)	$\pm 2.23\text{dB}$	Confidence levels of 95%
4	Spurious Emissions(>1GHz)	$\pm 1.72\text{dB}$	Confidence levels of 95%
5	Transmission Antenna Gain	$\pm 2.49\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525

2. General Description

2.1. Information of Applicant and Manufacturer

Applicant	Aptiv Services Poland S.A.
Applicant Address	ul. Podgórk Tynieckie 2,30-399 Kraków, Poland
Manufacturer	Aptiv Services Poland S.A.
Manufacturer Address	ul. Podgórk Tynieckie 2,30-399 Kraków, Poland

2.2. Information of EUT

Product Name	P-MIB4		
Sample No.	13#		
Hardware Version	C0		
Software Version	X021		
Blockchain Log:			
Equipment Type	Bluetooth LE		
Bluetooth Version	5.3		
Modulation Technology	GFSK		
Data Rate	1Mbps, 2Mbps		
Operating Frequency Range	2402MHz – 2480MHz (at interval of 2MHz)		
Channel List	Please refer as chapter 2.4 in this report.		
Power Supply	Type	DC Power	
	Voltage (V)	Low	9
		Rated	13.5
		High	16

Note 1: The EUT has two antennas that cannot transmit simultaneously. Both of the two antennas were evaluated separately, only the worst test result (ANT 1) were recorded in the test report.

Note 2: The black bold voltage values were selected for test, about the voltage fluctuation evaluation, please refer as chapter 2.6.2 in this report.

Note 3: The declared of EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3. Information of Antenna

Antenna Manufacturer	N/A
Brand Name	N/A
Model Name	N/A
Antenna Type	Internal Antenna
Antenna Gain	ANT 1: 2.40dBi; ANT 2: 2.51dBi

2.4. Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.



2.5. Test Configuration of EUT

2.5.1. Evaluation of The Worst Case

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel
Frequency Error	Unmodulated Single Carrier	0/19/39
Occupied Bandwidth	GFSK	0/19/39
Unwanted Emission Intensity	GFSK	0/19/39
Antenna Power and Antenna Power Error	GFSK	0/19/39
Limitation of Collateral Emission of Receiver	Continuously Receive	0/19/39
Transmission Radiation Angle Width	GFSK	0/19/39
Radio Interference Prevention Capability	Normal	Normal Use

2.5.2. Operation and Transmitter Power Setting

The EUT was tested while in a continues transmitter/receiver mode under the control of tool which is provided by manufacturer, all the items of transmitter were tested under the power setting as below:

Mode	Data Rate	Channel	Power Setting
Unmodulated Single Carrier	-	0/19/39	Default
GFSK	1Mbps	0/19/39	9
GFSK	2Mbps	0/19/39	9



2.6. Test Conditions

2.6.1. Environment Condition

Temperature (°C)	22
Relative Humidity (%)	48

2.6.2. Power Supply Voltage Fluctuation

During the input supply voltage to the EUT from the external power source is varied by +/- 10%, the output voltage had been confirmed that the fluctuation of power supply to the RF unit of EUT is equal to or less +/- 1%.

Power Supply		External Voltage $V_E(V)$			Internal Voltage V_I		
		V_{EN}	V_{EL}/V_{EH}		$V_{IN}(V)$	$V_{IE}(V)$	Variation of V_I
Type1	DC Power	13.5	V_{EL}	12.150	3.3	3.279	0.64%
			V_{EH}	14.850		3.316	0.48%

V_{EN} : Normal Voltage


V_{EL} : V_{EL} is the declared low voltage provided that $V_{EN} \times 90\%$ is less than the declared low voltage, otherwise it is $V_{EN} \times 90\%$

V_{EH} : V_{EH} is the declared high voltage provided that $V_{EN} \times 110\%$ is larger than the declared high voltage, otherwise it is $V_{EN} \times 110\%$


V_{IN} : The voltage supply to the radio unit.

2.7. Test Setup Layout Diagram


2.7.1. General Measurement



2.7.2. Antenna Power Measurement



2.7.3. Radio Interference Prevention Capability Measurement





3. Description of Test Items

3.1. Frequency Error

3.1.1. Limits

Within $\pm 50\text{ppm}$.

3.1.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.1.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.1.4. Test Deviation

There is no deviation with the original standard.

3.1.5. Test Results

Refer to Annex A.1 in this report.



3.2. Occupied Bandwidth

3.2.1. Limits

Type	Limits
FHSS	$\leq 83.5\text{MHz}$
OFDM 20MHz System	$\leq 26\text{MHz}$
OFDM 40MHz System	$26\text{MHz} < \text{OBW} \leq 40\text{MHz}$
Other	$\leq 26\text{MHz}$

3.2.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.2.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.2.4. Test Deviation

There is no deviation with the original standard.

3.2.5. Test Results

Refer to Annex A.2 in this report.



3.3. Unwanted Emission Intensity

3.3.1. Limits

Frequency Range	Limits
30MHz-2387MHz	$\leq 2.5 \mu\text{W}/\text{MHz}$
2387MHz-2400MHz	$\leq 25 \mu\text{W}/\text{MHz}$
2483.5MHz-2496.5MHz	$\leq 25 \mu\text{W}/\text{MHz}$
2496.5MHz-26000MHz	$\leq 2.5 \mu\text{W}/\text{MHz}$

3.3.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.3.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.3.4. Test Deviation

There is no deviation with the original standard.

3.3.5. Test Results

Refer to Annex A.3 in this report for the worst case.

For the 30MHz-1000MHz frequency band, the value obtained by adding the correction factor calculated using formula " $10 \cdot \log_{10}(1000/100)$ " to the 100kHz reading of the measurement bandwidth (RBW) is converted into a linear unit value, and then compared with the limit.



3.4. Antenna Power Error

3.4.1. Limits

Type	Frequency Range	Limits	
		Antenna Power Density	Antenna Power Error
FHSS	2427-2470.75 MHz	≤ 3 mW/MHz	$\leq +20\%$
	2400-2483.5 MHz (except 2427-2470.75 MHz)	≤ 10 mW/MHz	
DSSS	2400-2483.5 MHz	≤ 10 mW/MHz	
OFDM	2400-2483.5 MHz	≤ 10 mW/MHz (20MHz System) ≤ 5 mW/MHz (40MHz System)	
Other	2400-2483.5 MHz	≤ 10 mW	

3.4.1. Test Procedures

According to MIC Notice No.88 Annex 43.

3.4.2. Test Setup Layout

Refer to chapter 2.7.2 in this report.

3.4.3. Test Deviation

There is no deviation with the original standard.

3.4.4. Test Results

Refer to Annex A.4 in this report.



3.5. Limitation of Collateral Emission of Receiver

3.5.1. Limits

Frequency Range	Limits
30MHz-1000MHz	$\leq 4\text{nW}$
1000MHz-26000MHz	$\leq 20\text{nW}$

3.5.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.5.3. Test Setup Layout

Refer to chapter 2.7.1 in this report.

3.5.4. Test Deviation

There is no deviation with the original standard.

3.5.5. Test Results

Refer to Annex A.5 in this report for the worst case.



3.6.E.I.R.P.

3.6.1.Limits

Type	Frequency Range	Limits
FHSS	2427-2470.75 MHz	6.91dBm/MHz
	2400-2483.5 MHz (except 2427-2470.75 MHz)	12.14dBm/MHz
DSSS	2400-2483.5 MHz	12.14-dBm/MHz
OFDM	2400-2483.5 MHz	12.14dBm/MHz (20MHz System) 9.13dBm/MHz (40MHz System)
Other	2400-2483.5 MHz	12.14dBm

3.6.2.Test Procedures

According to MIC Notice No.88 Annex 43.

3.6.3.Test Setup Layout

Refer to chapter 2.7.2 in this report.

3.6.4.Test Deviation

There is no deviation with the original standard.

3.6.5.Test Results

Refer to Annex A.6 in this report.



3.7. Radio Interference Prevention Capability

3.7.1. Limits

The one automatically to transmit and to receive identification code with the wireless equipment of the wireless station used in the same premises.

3.7.2. Test Procedures

According to MIC Notice No.88 Annex 43.

3.7.3. Test Setup Layout

Refer to chapter 2.7.4 in this report.

3.7.4. Test Deviation

There is no deviation with the original standard.

3.7.5. Test Results

Refer to Annex A.7 in this report.

3.8. Construction Protection Confirmation Method

3.8.1. Limits

The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.

3.8.2. Confirmation Method

The RF and modulation portions are protected against illegal modification as following method:

Protected Method	Description
Shield	The RF module use a shield to protect the RF and modulation portions, if the shield is removed, the module will be damaged to the point that it will not work properly.

3.8.3. Reference Documents


Reference Documents	Item
Photo	



Annex A Test Data and Results

A.1. Frequency Error


Channel	Frequency f_c (MHz)	Test Frequency f (MHz)	Frequency Error (ppm)	Verdict
0	2402	2401.9973	-1.12	PASS
19	2440	2439.9974	-1.07	PASS
39	2480	2479.9974	-1.05	PASS





A.2. Occupied Bandwidth

Mode	Channel	Frequency (MHz)	Measured 99% Occupied Bandwidth (MHz)	Verdict
1Mbps	0	2402	1.033	PASS
	19	2440	1.038	PASS
	39	2480	1.034	PASS
2Mbps	0	2402	2.000	PASS
	19	2440	1.990	PASS
	39	2480	2.002	PASS






A.3. Unwanted Emission Intensity

Mode	Ch.	Freq. (MHz)	Freq.Range (MHz)	MaxFreq. (MHz)	Power (dBm)	Power (μ W/MHz)	Limits (μ W/MHz)	Verdict
1M	0	2402	30-1000	840.920	-69.966	0.0010	2.5	PASS
			1000-2387	2144.300	-58.876	0.0013	2.5	PASS
			2387-2400	2400.000	-28.006	1.5827	25	PASS
			2483.5-2496.5	2484.410	-57.121	0.0019	25	PASS
			2496.5-26000	24658.000	-43.185	0.0480	2.5	PASS
	19	2440	30-1000	833.160	-69.435	0.0011	2.5	PASS
			1000-2387	2385.600	-58.803	0.0013	2.5	PASS
			2387-2400	2389.002	-57.840	0.0016	25	PASS
			2483.5-2496.5	2492.691	-58.270	0.0015	25	PASS
			2496.5-26000	24056.300	-43.310	0.0467	2.5	PASS
	39	2480	30-1000	748.770	-69.556	0.0011	2.5	PASS
			1000-2387	2242.800	-58.423	0.0014	2.5	PASS
			2387-2400	2398.583	-58.704	0.0013	25	PASS
			2483.5-2496.5	2483.981	-43.182	0.0481	25	PASS
			2496.5-26000	24032.800	-43.471	0.0450	2.5	PASS
2M	0	2402	30-1000	756.260	-69.165	0.0012	2.5	PASS
			1000-2387	2209.500	-59.106	0.0012	2.5	PASS
			2387-2400	2400.000	-22.213	6.0076	25	PASS
			2483.5-2496.5	2486.451	-58.838	0.0013	25	PASS
			2496.5-26000	24025.700	-42.710	0.0536	2.5	PASS
	19	2440	30-1000	767.200	-69.931	0.0010	2.5	PASS
			1000-2387	2312.100	-58.756	0.0013	2.5	PASS
			2387-2400	2393.149	-57.810	0.0017	25	PASS
			2483.5-2496.5	2488.882	-58.978	0.0013	25	PASS
			2496.5-26000	24608.600	-43.740	0.0423	2.5	PASS
	39	2480	30-1000	910.760	-68.214	0.0015	2.5	PASS
			1000-2387	2375.900	-58.293	0.0015	2.5	PASS
			2387-2400	2398.934	-57.321	0.0019	25	PASS
			2483.5-2496.5	2483.500	-40.551	0.0881	25	PASS
			2496.5-26000	23985.800	-42.941	0.0508	2.5	PASS



REPORT No.: SZ26010171W01

**MORLAB**

Shenzhen Morlab Communications Technology Co., Ltd.
FL-1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555


Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn



REPORT No.: SZ26010171W01



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL-1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555


Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn



REPORT No.: SZ26010171W01



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn



A.4. Antenna Power Error


ANT 1

Mode	Channel	Test Value P_t (dBm)	Duty Factor	Antenna Power P (dBm)	Antenna Power P (mW)	Declare Power (mW)	Antenna Power Error	Verdict
1Mbps	2402	8.77	0.00	8.77	7.53	9.00	-16.33%	PASS
	2440	8.49		8.49	7.06		-21.56%	PASS
	2480	8.34		8.34	6.82		-24.22%	PASS
2Mbps	2402	8.61	0.00	8.61	7.26	9.00	-19.33%	PASS
	2440	8.43		8.43	6.97		-22.56%	PASS
	2480	8.26		8.26	6.70		-25.56%	PASS

ANT 2

Mode	Channel	Test Value P_t (dBm)	Duty Factor	Antenna Power P (dBm)	Antenna Power P (mW)	Declare Power (mW)	Antenna Power Error	Verdict
1Mbps	2402	9.33	0.00	9.33	8.57	9.00	-4.78%	PASS
	2440	9.56		9.56	9.04		0.44%	PASS
	2480	9.61		9.61	9.14		1.56%	PASS
2Mbps	2402	9.21	0.00	9.21	8.34	9.00	-7.33%	PASS
	2440	9.55		9.55	9.02		0.22%	PASS
	2480	9.57		9.57	9.06		0.67%	PASS


Duty Cycle






A.5. Limitation of Collateral Emission of Receiver

Mode	Ch.	Freq.	Freq.Range(MHz)	MaxFre. (MHz)	Power (dBm)	Power (nW)	Limits (nW)	Verdict
1M	0	2402	30-1000	150.000	-78.132	0.0015	4	PASS
			1000-26000	24645.000	-60.737	0.0844	20	PASS
	19	2440	30-1000	150.000	-77.841	0.0016	4	PASS
			1000-26000	24095.000	-60.933	0.0807	20	PASS
	39	2480	30-1000	150.280	-78.457	0.0014	4	PASS
			1000-26000	24080.000	-60.918	0.0809	20	PASS
2M	0	2402	30-1000	942.770	-79.626	0.0011	4	PASS
			1000-26000	24125.000	-63.790	0.0418	20	PASS
	19	2440	30-1000	761.380	-79.766	0.0011	4	PASS
			1000-26000	24017.500	-65.345	0.0292	20	PASS
	39	2480	30-1000	858.380	-79.639	0.0011	4	PASS
			1000-26000	24575.000	-64.926	0.0322	20	PASS







REPORT No.: SZ26010171W01



1M_2480MHz



2M_2402MHz



2M_2440MHz

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL-1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555


Http://www.morlab.cn

Fax: 86-755-36698525


E-mail: service@morlab.cn



REPORT No.: SZ26010171W01



2M_2480MHz



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn

**A.6. E.I.R.P.****ANT 1**

Mode	Channel	Frequency (MHz)	Measured E.I.R.P. (dBm)	Limit (dBm)	Verdict
1Mbps	0	2402	11.17	12.14	PASS
	19	2440	10.89		PASS
	39	2480	10.74		PASS
2Mbps	0	2402	11.01	12.14	PASS
	19	2440	10.83		PASS
	39	2480	10.66		PASS

ANT 2

Mode	Channel	Frequency (MHz)	Measured E.I.R.P. (dBm)	Limit (dBm)	Verdict
1Mbps	0	2402	11.84	12.14	PASS
	19	2440	12.07		PASS
	39	2480	12.12		PASS
2Mbps	0	2402	11.72	12.14	PASS
	19	2440	12.06		PASS
	39	2480	12.08		PASS

A.7. Radio Interference Prevention Capability

The identification code of the EUT is: 22:22:07:FD:9B:17

Device's Bluetooth address: 22:22:07:FD:9B:17

The result is PASS.



REPORT No.: SZ26010171W01

Notes

1. The report shall have report stamp or our company stamp.
2. The report shall be invalid without all the signatures of the editor and approver.
3. The report shall not be changed.
4. Any objections must be raised to Morlab within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.
5. Conformity declaration:
 - ☒ Morlab issues a statement of conformity based on the corresponding standards (default)
 - ☐ Morlab issues a statement of conformity based on the applicant requirement
6. Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the testing standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule).

_____ END OF REPORT _____