

TEST REPORT

Report No.: 8337EU010802W

Applicant: QPAD Limited

Address: Unit 03-04, 21/F, Eight Commercial Tower, 8 Sun Yip Street, Chai Wan, Hong Kong

Product Name: 2.4G Receiver

Model No.: Model 1 2.4G dongle (refer to clause 2.4)

Trademark: QPAD

Test Standard(s): MIC Notice No.88 Appendix No.43
Ordinance of MPT No.37, 1981:
Article 2 paragraph 1 item (19)

Test Result: Pass

Date of Receipt: Dec. 08, 2025

Test Date: Dec. 09, 2025 – Dec. 16, 2025


Date of Issue: Jan. 07, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:



Mikey Zhu/ Engineer

Reviewed and Approved by:



Sally Zhang/ Manager

SHENZHEN EU TESTING LABORATORY LIMITED

Address: 1/F, Bldg. B1, Fuqiao Fourth Industrial Area, Fuhai Street,
Baoan District, Shenzhen, Guangdong, China

Website: www.eu-test.com

Tel: (86)-755-2357-5384 Email: Service@eu-test.com

Revision Record

Report Version	Issued Date	Description	Status
V0	Jan. 07, 2026	Original	Valid

Table of Contents

1	COVER PAGE.....	1
2	GENERAL INFORMATION	5
2.1	APPLICANT INFORMATION.....	5
2.2	MANUFACTURER INFORMATION.....	5
2.3	FACTORY INFORMATION.....	5
2.4	GENERAL DESCRIPTION OF E.U.T.....	5
2.5	TECHNICAL INFORMATION OF E.U.T.....	6
3	TEST SUMMARY.....	7
3.1	TEST STANDARD.....	7
3.2	TEST VERDICT.....	7
3.3	TEST LABORATORY.....	7
4	TEST CONFIGURATION.....	8
4.1	TEST ENVIRONMENT.....	8
4.2	TEST EQUIPMENT.....	9
4.3	DESCRIPTION OF SUPPORT UNIT.....	9
4.4	MEASUREMENT UNCERTAINTY.....	10
5	TEST ITEMS.....	11
5.1	FREQUENCY TOLERANCE TEST.....	11
5.1.1	Test Requirement.....	11
5.1.2	Test Setup Diagram.....	11
5.1.3	Test Procedure.....	11
5.1.4	Test Deviation.....	11
5.1.5	EUT Operation during Test.....	11
5.1.6	Test Data.....	11
5.2	OCCUPIED BANDWIDTH.....	12
5.2.1	Test Requirement.....	12
5.2.2	Test Setup Diagram.....	12
5.2.3	Test Procedure.....	12
5.2.4	Test Deviation.....	12
5.2.5	EUT Operation during Test.....	12
5.2.6	Test Data.....	12
5.3	ANTENNA POWER / EIRP ANTENNA POWER TEST.....	13
5.3.1	Test Requirement.....	13
5.3.2	Test Setup Diagram.....	13
5.3.3	Test Procedure.....	13
5.3.4	Test Deviation.....	13
5.3.5	EUT Operation during Test.....	13
5.3.6	Test Data.....	13
5.4	SPURIOUS EMISSIONS INTENSITY TEST.....	14
5.4.1	Test Requirement.....	14
5.4.2	Test Setup Diagram.....	14
5.4.3	Test Procedure.....	14
5.4.4	Test Deviation.....	14
5.4.5	EUT Operation during Test.....	14
5.4.6	Test Data.....	14
5.5	SECONDARY RADIATED EMISSIONS TEST.....	15
5.5.1	Test Requirement.....	15
5.5.2	Test Setup Diagram.....	15
5.5.3	Test Procedure.....	15
5.5.4	Test Deviation.....	15

5.5.5	EUT Operation during Test	15
5.5.6	Test Data	15
5.6	INTERFERENCE PREVENTION FUNCTION	16
5.6.1	Test Requirement.....	16
5.6.2	Test Setup Diagram	16
5.6.3	Test Procedure.....	16
5.6.4	Test Deviation	16
5.6.5	EUT Operation during Test	16
5.6.6	Test Data	16
5.7	TRANSMISSION RADIATION ANGLE WIDTH (3dB BEAMWIDTH) MEASUREMENT	17
5.7.1	Test Requirement.....	17
5.7.2	Test Setup Diagram	17
5.7.3	Test Procedure.....	17
5.7.4	Test Deviation	17
5.7.5	EUT Operation during Test	17
5.7.6	Test Data	17
5.8	CONSTRUCTION PROTECTION CONFIRMATION METHOD	18
ANNEX A	TEST SETUP PHOTOS	19
ANNEX B	EXTERNAL PHOTOS	19
ANNEX C	INTERNAL PHOTOS	19
ANNEX D	TEST DATA	19

2 General Information

2.1 Applicant Information

Applicant	QPAD Limited
Address	Unit 03-04, 21/F, Eight Commercial Tower, 8 Sun Yip Street, Chai Wan, Hong Kong

2.2 Manufacturer Information

Manufacturer	QPAD Limited
Address	Unit 03-04, 21/F, Eight Commercial Tower, 8 Sun Yip Street, Chai Wan, Hong Kong

2.3 Factory Information

Factory	QPAD Limited
Address	Unit 03-04, 21/F, Eight Commercial Tower, 8 Sun Yip Street, Chai Wan, Hong Kong

2.4 General Description of E.U.T.

Product Name	2.4G Receiver
Model No. Under Test	Model 1 2.4G dongle
List Model No.	423005, 423006
Description of Model differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in appearance color and model name. (this information provided by the customer)
Rating(s)	Input: 5V==0.02A
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Test Sample No.	-1/2(Normal Sample), -2/2(Engineering Sample)
Hardware Version	V1.0
Software Version	dongle/V1.11
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	2.4G ISM Band (GFSK modulation): 2405-2475MHz
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Technology	2.4G ISM Band (GFSK modulation)
Modulation Type	GFSK
Operating Frequency	2405-2475MHz
Number of Channel	16
Tested Channel	00 (2405 MHz), 08 (2441 MHz), 15 (2475 MHz)
Antenna Type	PCB Antenna
Antenna Gain(Peak)	-0.71 dBi
Antenna Impedance	50Ω
Rated output Power	2.400 mW
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)
00	2405	05	2426	08	2441	13	2466
01	2408	06	2433	09	2445	14	2471
02	2414		2436	10	2453	15	2475
03	2419	07	2439	11	2459	/	/
04	2422		2447	12	2463	/	/

Note: Each EUT operates on 16 frequency channels.

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

No.	Identity	Document Title
1	MIC Notice No.88 Appendix No.43 Ordinance of MPT No.37, 1981: Article 2 paragraph 1 item (19)	Low power data communications system in the 2.4GHz band

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission should be checked to ensure compliance has been maintained.

3.2 Test Verdict

No.	Description	Test Mode	Channel	Verdict	Remark
1	Frequency Tolerance	GFSK	Low/Middle /High	Pass	--
2	Occupied Bandwidth	GFSK	Low/Middle /High	Pass	--
3	Antenna Power / EIRP Antenna Power	GFSK	Low/Middle /High	Pass	--
4	Spurious Emission Intensity	GFSK	Low/Middle /High	Pass	--
5	Secondary Radiated Emission	GFSK	Low/Middle /High	Pass	--
6	Spurious Emissions	GFSK	Low/Middle /High	Pass	--
7	Interference Prevention Function	GFSK	Low/Middle /High	Pass	--
8	Transmission Radiated Angle Width (3dB Beam Bandwidth)	GFSK	Low/Middle /High	N/A	Note ²
9	Construction Protection Confirmation	GFSK	Low/Middle /High	Compliance	--
10	Carrier Sense Function (1)	GFSK	Low/Middle /High	N/A	Note ³
11	Carrier Sense Function (2)	GFSK	Low/Middle /High	N/A	Note ⁴

Note 1: The tests were performed according to the method of measurements prescribed in MIC Notice No.88 Appendix No.43.

Note 2: Note: Because the EIRP is less than 12.14 dBm, this item is not applicable.

Note 3: Not apply to this device, since EIRP does not require compensation through Antenna Power.

Note 4: Application to transmitting devices with OFDM modulation and the occupied bandwidth greater than 26MHz.

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	52%	
Atmospheric Pressure	103 kPa	
Temperature	NT (Normal Temperature)	+26°C
Working Voltage of the EUT	NV (Normal Voltage)	5.0VDC
	LV (Low Voltage)	4.5VDC
	HV (High Voltage)	5.5VDC

Power Supply Voltage Fluctuation Test

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	5.0VDC	4.5VDC	5.5VDC
Output To RF Module	3.3VDC	3.3VDC	3.3VDC
Voltage Variation (%)	--	0.00%	0.00%

Note:

Voltage Variation (%)=(Output high or Low Voltage - Output Normal Voltage)/ Output Normal Voltage* 100%

For extreme voltage test, we have tested the relationship between the external power supply and RF IC power supply. Base on the test results, only the normal voltage was selected to perform all items.

4.2 Test Equipment

Radiated Emission and RF Test					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2025/01/08	2026/01/07
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2023/01/14	2026/01/13
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2023/01/12	2026/01/11
Pre-amplifier	Agilent	8447D	EE-009	2025/01/08	2026/01/07
Pre-amplifier	Agilent	8449B	EE-010	2025/01/08	2026/01/07
MXA Signal Analyzer	Agilent	N9020A	EE-011	2025/01/08	2026/01/07
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2025/01/08	2026/01/07
Test Software	Farad	EZ-EMC	EE-015	N.C.R	N.C.R
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2025/01/08	2026/01/07
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	N.C.R	N.C.R
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-402	2025/02/14	2026/02/13
Loop Antenna	TESEQ	HLA6121	EE-403	2025/02/14	2026/02/13
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2025/02/14	2026/02/13
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2025/07/29	2026/07/28
Power Sensor	ROHDE&SCHWA RZN	NRP18S	ES-052	2025/02/14	2026/02/13
DC Power Source	QJE	QJ3020E	ES-037	2025/07/29	2026/07/28
Note ¹ : Calibration Company: Shenzhen Academy Of Metrology& Quality inspection.					
Note ² : Calibration method: Calibration conducted in foreign countries, which is equivalent to calibration conducted by the NICT or a designated calibration agency under Article 102-18-1 and Article 24-2, Paragraph 4 of the Radio Act.					

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	--	--	--	--

4.4 Measurement Uncertainty

Parameters	Uncertainty
Frequency Error / 99% Bandwidth	$(3.2 \times f \times 10^{-6})$ Hz
Antenna Power	1.82 dB
TX-RX Spurious Emissions	1.84 dB
Transmission Antenna Gain	5.36 dB
Temperature	0.8 °C
Humidity	4 %
DC / AC Power Source	0.04%

Noet: “f” is the nominal signal frequency in Hz.

Note: This uncertainty represents as expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5 Test Items

5.1 Frequency Tolerance Test

5.1.1 Test Requirement

Item	Limits
Frequency Tolerance	$\leq \pm 50$ ppm

5.1.2 Test Setup Diagram



5.1.3 Test Procedure

Test Frequency= test channel
 RBW=VBW=100KHz
 Span=2MHz
 Sweep time=Auto
 Detector mode=Positive peak
 Indication mode=Max hold
 EUT have transmitted unmodulated signal and fixed channelize. f is using the mark cursor to mark the peak frequency value, fc is declaring of channel frequency.

5.1.4 Test Deviation

There is no deviation with the original standard.

5.1.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, carrier mode.

5.1.6 Test Data

PASS.

Please refer to Annex D for details.

5.2 Occupied Bandwidth

5.2.1 Test Requirement

Item	Limits
Occupied Band Width	FHSS $\leq$ 83.5MHz; OFDM $\leq$ 40MHz, DSSS $\leq$ 26MHz; Others $\leq$ 26MHz

5.2.2 Test Setup Diagram



5.2.3 Test Procedure

- Set the spectrum analyzer as follows:
 Center frequency: Test frequency
 Span: Approximately 2 to 3.5 times nominal bandwidth
 Resolution bandwidth: Within 3% of the technical standard
 Video bandwidth: equivalent to resolvable bandwidth
 Sweep time: auto
 Sweep mode: Continuous sweep
 Detection: Positive peak
 Trace mode: Maximum hold
- After repeating sweeps until the display shows steady data, store the values at all data points into the computer array variables.

5.2.4 Test Deviation

There is no deviation with the original standard.

5.2.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.2.6 Test Data

PASS.

Please refer to Annex D for details.

5.3 Antenna Power / EIRP Antenna Power Test

5.3.1 Test Requirement

Item	Limits
Antenna Power Density	a) FH, FH+DS, or FH+OFDM form 2427 - 2470.75 MHz: ≤ 3 mW/MHz b) DS but other than a) from 2400~2483.5 MHz: ≤ 10 mW/MHz c) OFDM, but other than a): For OCB of 26MHz or less: ≤ 10 mW/MHz For OCB of over 26 MHz to 40 MHz: ≤ 5 mw/MHz d) Other than a), b) and c): ≤ 10 mW
Antenna Power Error	+20% (Base on manufacturer declare antenna power density)
EIRP Power	12.14 dBm

5.3.2 Test Setup Diagram



5.3.3 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

5.3.4 Test Deviation

There is no deviation with the original standard.

5.3.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.3.6 Test Data

PASS.

Please refer to Annex D for details.

5.4 Spurious Emissions Intensity Test

5.4.1 Test Requirement

Item	Limits
TX Spurious Emission	$\leq 2.5\mu\text{W}/\text{MHz}$ ($2387\text{MHz} > f$; $2496.5\text{MHz} < f$)
	$\leq 25\mu\text{W}/\text{MHz}$ ($2387\text{MHz} \leq f < 2400\text{MHz}$) and ($2483.5\text{MHz} < f \leq 2496.5\text{MHz}$)

5.4.2 Test Setup Diagram



5.4.3 Test Procedure

Spectrum Parameter	Setting
Attenuation	Auto
RB	30-1000 MHz: 1 MHz/1 MHz
VB	Above 1GHz: 1 MHz/1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Auto

1. The EUT is placed in transmit mode at maximum power/modulation at a fixed channel.
2. Setting of SA is following as: RBW/VBW = 1MHz; / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. Setting of SA is following as 30 MHz and stop frequency 2387 MHz Then to mark peak reading value + cable loss shall be less than 2.5 μW
4. SA adjusted to start frequency 2387 MHz and stop frequency 2400 MHz. Then to mark peak reading value + cable loss shall be less than 25 μW .
5. SA adjusted to start frequency 2483.5 MHz and stop frequency 2496.5 MHz Then to mark peak reading value + cable loss shall be less than 25 μW
6. SA adjusted to start frequency 2496.5 MHz and stop frequency 12500 MHz Then to mark peak reading value + cable loss shall be less than 2.5 μW
7. If the Result_Value is over the requirement, take total sum of 1MHz band centered at the spur frequency like ACLP measurement as Result_Value.

5.4.4 Test Deviation

There is no deviation with the original standard.

5.4.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.4.6 Test Data

PASS.

Please refer to Annex D for details.

5.5 Secondary Radiated Emissions Test

5.5.1 Test Requirement

Item	Limits
RX Spurious Emission	$\leq 4\text{nW}$ ($f < 1\text{GHz}$)
	$\leq 20\text{nW}$ ($1\text{GHz} \leq f$)

5.5.2 Test Setup Diagram



5.5.3 Test Procedure

Spectrum Parameter	Setting
Attenuation	Auto
RB	30-1000 MHz: 100KHz/100KHz
VB	Above 1GHz: 1 MHz/1 MHz
Detector	Peak
Trace	Max Hold
Sweep	Auto

1. The EUT is placed in Rx mode and set to a fixed channel.
2. Setting of SA is following as RB / VB: 100 kHz (below 1GHz emissions) / 1 MHz (above 1GHz emissions) / AT:10 dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak / Trace mode: Max hold
3. SA set RB: 100 kHz and VB: 100 kHz. Then adjust to start frequency 30 MHz and stop frequency 1000 MHz. Search to mark peak reading value + cable loss shall be less than 4 nW
4. SA set RB: 1 MHz and VB: 1 MHz. Then adjust to start frequency 1000 MHz and stop frequency 12500 MHz. Search to mark peak reading value + cable loss shall be less than 20 nW
5. If power level of lower emissions are more than 1/10 of limit (0.4nW for $f < 1\text{GHz}$, 2 nW for $f \geq 1\text{GHz}$), all those are to be indicated in the 2nd and 3rd lines. If others are 1/10 or less more of the limit, no necessary to be indicated

5.5.4 Test Deviation

There is no deviation with the original standard.

5.5.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.5.6 Test Data

PASS.


Please refer to Annex D for details.

5.6 Interference Prevention Function

5.6.1 Test Requirement

Item	Limits
Identification	≥ 48 bits

5.6.2 Test Setup Diagram



5.6.3 Test Procedure

1. In the case that the EUT has the function of automatically transmitting the identification code:
 - a. Transmit the predetermined identification codes from EUT.
 - b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code:
 - a. Transmit the predetermined identification codes from the counterpart.
 - b. Check if communication is normal.
 - c. Transmit the signals other than predetermined ID codes from the counterpart.
 - d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

5.6.4 Test Deviation

There is no deviation with the original standard.

5.6.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.6.6 Test Data

PASS.


Mode	ID Code	Test Results
2.4G	42:C6:A0:38:A2:33	Pass

5.7 Transmission Radiation Angle Width (3dB Beamwidth) Measurement

5.7.1 Test Requirement

Item	Limits
3dB antenna beam width	$360/A$ (If $A < 1$; then $A = 1$) $A = \{ \text{EIRP Power [mW]} / 16.36 \text{ for DS, OFDM} \}$ or $A = \{ \text{EIRP Power [mW]} / 4.9 \text{ for FH} \}$
Note: This test item will not be applied to the transmission antenna which has a gain of 2.14dBi or less.	

5.7.2 Test Setup Diagram



5.7.3 Test Procedure

1. Set EUT and measuring antenna at the same height and roughly facing each other.
2. Set spectrum analyzer with RBW=1 MHz, VBW=1 KHz, Y scale=5 dB, Detector=Peak, Trace mode=Max Hold, and tune reference level to observe receiving signal position.
3. Rotate directions of the EUT horizontally and vertically to find the maximum receiving power.
4. Move the measuring antenna height up and down within $\pm 50\text{cm}$ of EUT height and swing it to find the maximum output of measuring antenna. The output level at the spectrum analyzer is read as "E".
5. Calculate permitted radiation angle in horizontal and vertical using EIRP measured in another test method.
6. Calculate 3dB antenna beam width by the formula below $360/A$ (If $A < 1$; then $A = 1$). $A = \{ \text{EIRP Power [mW]} / 16.36 \text{ for DS, OFDM} \}$ or $A = \{ \text{EIRP Power [mW]} / 4.9 \text{ for FH} \}$

5.7.4 Test Deviation

There is no deviation with the original standard.

5.7.5 EUT Operation during Test

The EUT was programmed to be in continuous transmit, channel-selected mode.

5.7.6 Test Data


Note: Because the EIRP is less than 12.14 dBm, this item is not applicable.

5.8 Construction Protection Confirmation Method

The RF and modulation portions are protected against illegal modification as following method:

Protected Method	Description
Structure protection	The terminal number is 32, terminal pitch is 1mm. it can't be easily opened and modified.

Reference Photo



ANNEX A TEST SETUP PHOTOS

Please refer to the document “8337EU010802W-AA.PDF”

ANNEX B EXTERNAL PHOTOS

Please refer to the document “8337EU010802W-AB.PDF”

ANNEX C INTERNAL PHOTOS

Please refer to the document “8337EU010802W-AC.PDF”

ANNEX D TEST DATA

Please refer to the document “8337EU010802W-AD.PDF”

STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---