


NCC RADIO TEST REPORT

Equipment : RFID 13.56MHz Wireless Module
Brand Name : DELL
Model Name : DWRFID1902
Applicant : 荷蘭商戴爾企業股份有限公司台灣分公司
台北市大安區敦化南路 2 段 218 號 20 樓
Manufacturer : DELL Inc.
One Dell Way, Round Rock, TX 78682, USA
Standard : NCC LP0002 (2018-01-10)

The product was received on Dec. 27, 2019 and testing was started from Jan. 08, 2020 and completed on Jan. 14, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures NCC LP0002 (2018-01-10) and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Reviewed by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1. General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2. Test Configuration of Equipment Under Test.....	7
2.1 Descriptions of Test Mode	7
2.2 Connection Diagram of Test System.....	8
2.3 Table for Supporting Units	9
2.4 EUT Operation Test Setup	9
3. Test Results	10
3.1 AC Power Line Conducted Emissions Measurement	10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement.....	12
3.3 Frequency Stability Measurement	13
3.4 Field Strength of Fundamental Emissions and Mask Measurement.....	14
3.5 Radiated Emissions Measurement.....	16
3.6 Antenna Requirements.....	19
4. List of Measuring Equipment	20
5. Uncertainty of Evaluation	21
Appendix A. Test Results of Conducted Emission Test	
Appendix B. Test Results of Conducted Test Items	
B1. Test Result of 20dB Spectrum Bandwidth	
B2. Test Result of Frequency Stability	
Appendix C. Test Results of Radiated Test Items	
C1. Test Result of Field Strength of Fundamental Emissions	
C2. Results of Radiated Emissions (9 kHz~30MHz)	
C3. Results of Radiated Emissions (30MHz~1GHz)	
Annex A. Receiver Radiated Emission	
Appendix D. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
TR9N2620-09A	01	Initial issue of report	Feb. 06, 2020
TR9N2620-09A	02	Revising Applicant and Sample information	Feb. 10, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	LP0002 2.3	AC Power Line Conducted Emissions	Pass	Under limit 7.03 dB at 13.560MHz
3.2	-	20dB Spectrum Bandwidth	Pass	-
	-	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	LP0002 3.2.1.3	Frequency Stability	Pass	-
3.4	LP0002 3.2.1.2	Field Strength of Fundamental Emissions	Pass	Max level 61.56 dBμV/m at 13.560 MHz
3.5	LP0002 2.8 3.2.1.2	Radiated Spurious Emissions	Pass	Under limit 4.84 dB at 33.880MHz
3.6	LP0002 2.2	Antenna Requirements	Pass	-
Annex A	LP0002 2.11	Receiver Radiated Emission	Pass	Please refer to Annex A

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Celery Wei

1. General Description

1.1 Product Feature of Equipment Under Test

NFC.

Product Specification subjective to this standard	
Sample 1	EUT with NFC Antenna 1 (Manufacturer: Speedwire) and Host 1
Sample 2	EUT with NFC Antenna 1 (Manufacturer: Speedwire) and Host 2
Sample 3	EUT with NFC Antenna 2 (Manufacturer: HB) and Host 1
Sample 4	EUT with NFC Antenna 2 (Manufacturer: HB) and Host 2
Sample 5	EUT with NFC Antenna 1 (Manufacturer: Speedwire) and Host 3
Sample 6	EUT with NFC Antenna 1 (Manufacturer: Speedwire) and Host 4
Sample 7	EUT with NFC Antenna 2 (Manufacturer: HB) and Host 3
Sample 8	EUT with NFC Antenna 2 (Manufacturer: HB) and Host 4
Host Information	Equipment Name: Portable Computer Host 1: Brand Name: DELL Model Name: P34S
	Equipment Name: Portable Computer Host 2: Brand Name: DELL Model Name: P33S
	Equipment Name: Portable Computer Host 3: Brand Name: DELL Model Name: P131G
	Equipment Name: Portable Computer Host 4: Brand Name: DELL Model Name: P119G
Antenna Type	Loop Antenna

Remark: The test results of sample 1 and sample 3 were performed in this test report, and the other test results of sample 5 ~ sample 8 which can be referred to Sporton Report No. TR9N2620-09B.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH03-HY	CO05-HY
Test Engineer	Louis Chung	Tom Lee
Temperature	22~24°C	22~25°C
Relative Humidity	53~55%	45~53

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH11-HY	
Test Engineer	Cookie Ku, Fu Chen and Troye Hsieh	
Temperature	18.6~21.3°C	
Relative Humidity	68.7~69.6%	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ NCC LP0002 (2018-01-10)
- ♦ FCC Part 15 Subpart C §15.225
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz


The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report.

Pre-scanned tests, Notebook type and three orthogonal panels (X, Y, Z) to determine the final configuration (Y plane as worst plane) from all possible combinations.


Test Cases	
AC Conducted Emission	Mode 1: EUT in Host + HDMI Cable + SD Card + USB HD + USB (Type C) HD + Smart Card (Load) + NFC Link + Earphone + AC Adapter
	Mode 2: EUT in Host + HDMI Cable + SD Card + USB HD + USB (Type C) HD + Smart Card (Load) + NFC Idle + Earphone + AC Adapter
Remark: The worst case of conducted emission is mode 1; only the test data of it was reported.	

2.2 Connection Diagram of Test System

<Radiated Emission Mode>



<AC Conducted Emission Mode>



2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
2.	LCD MONITOR	Asus	PB27UQ	FCC DoC	Shielded, 1.6m	Unshielded,1.8m
3.	USB HD	lenovo	F310S	FCC DoC	Shielded, 1.0m	N/A
4.	USB HD	lenovo	F310S	FCC DoC	Shielded, 0.8m	N/A
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
6.	NFC Card	N/A	N/A	N/A	N/A	N/A
Remark: 配件由耕興股份有限公司電磁相容及無線通信實驗室提供併同檢驗，不隨貨提供。						

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0 cm gap to the EUT.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 100 ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	NCC LP0002 3.2.1.1			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength ($\mu\text{V/m}$) at 30m	Field Strength (dB $\mu\text{V/m}$) at 30m	Field Strength (dB $\mu\text{V/m}$) at 10m	Field Strength (dB $\mu\text{V/m}$) at 3m
13.553~13.567	15848	84.0	103.08	124.0

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
Note: Emission level (dB $\mu\text{V/m}$) = 20 log Emission level ($\mu\text{V/m}$).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak


Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the LP0002 Section 2.2.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 08, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jan. 08, 2020	Nov. 14, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Jan. 08, 2020	Nov. 19, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jan. 08, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jan. 08, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jan. 08, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jan. 08, 2020	Jan. 01, 2021	Conduction (CO05-HY)
AC Power Source	AC POWER	AFC-500W	F10407001 1	50Hz~60Hz	Apr. 12, 2019	Jan. 10, 2020	Apr. 11, 2020	Conducted (TH03-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 06, 2019	Jan. 10, 2020	Mar. 05, 2020	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 04, 2019	Jan. 10, 2020	Sep. 03, 2020	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30°C ~70°C	Nov. 26, 2019	Jan. 10, 2020	Nov. 25, 2020	Conducted (TH03-HY)
Software	Audix	E3 6.2009-8-24	RK-00105 3	N/A	N/A	Jan. 10, 2020~ Jan. 14, 2020	N/A	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 03, 2019	Jan. 10, 2020~ Jan. 14, 2020	Dec. 02, 2020	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 12, 2019	Jan. 10, 2020~ Jan. 14, 2020	Oct. 11, 2020	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Jan. 10, 2020~ Jan. 14, 2020	Dec. 25, 2020	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Jan. 10, 2020~ Jan. 14, 2020	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1~4m	N/A	Jan. 10, 2020~ Jan. 14, 2020	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jan. 10, 2020~ Jan. 14, 2020	N/A	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY554201 70	20MHz~8.4GHz	Mar. 08, 2019	Jan. 10, 2020~ Jan. 14, 2020	Mar. 07, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz~44GHz	Oct. 28, 2019	Jan. 10, 2020~ Jan. 14, 2020	Oct. 27, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WHK20/1000 C7/40SS	SN2	20M High Pass	Sep. 15, 2019	Jan. 10, 2020~ Jan. 14, 2020	Sep. 14, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz-30MHz	Mar. 13, 2019	Jan. 10, 2020~ Jan. 14, 2020	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	30M-18G	Mar. 13, 2019	Jan. 10, 2020~ Jan. 14, 2020	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	Jan. 10, 2020~ Jan. 14, 2020	Mar. 12, 2020	Radiation (03CH11-HY)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.00
--	------

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.12
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------




Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Tom Lee	Temperature :	22~25℃
		Relative Humidity :	45~53%

EUT Information

Test Mode : Mode 1
 Test Voltage : 110Vac/60Hz
 Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	34.97	56.00	21.03	L1	OFF	19.5
0.150000	49.89	---	66.00	16.11	L1	OFF	19.5
0.165750	---	23.23	55.17	31.94	L1	OFF	19.5
0.165750	42.35	---	65.17	22.82	L1	OFF	19.5
0.183750	---	30.82	54.31	23.49	L1	OFF	19.5
0.183750	44.20	---	64.31	20.11	L1	OFF	19.5
0.541500	---	30.91	46.00	15.09	L1	OFF	19.5
0.541500	38.65	---	56.00	17.35	L1	OFF	19.5
0.615750	---	33.20	46.00	12.80	L1	OFF	19.5
0.615750	39.34	---	56.00	16.66	L1	OFF	19.5
0.717990	---	35.63	46.00	10.37	L1	OFF	19.5
0.717990	39.83	---	56.00	16.17	L1	OFF	19.5
2.877900	---	26.76	46.00	19.24	L1	OFF	19.6
2.877900	36.45	---	56.00	19.55	L1	OFF	19.6
3.003720	---	26.31	46.00	19.69	L1	OFF	19.6
3.003720	37.45	---	56.00	18.55	L1	OFF	19.6
3.130440	---	25.79	46.00	20.21	L1	OFF	19.6
3.130440	37.93	---	56.00	18.07	L1	OFF	19.6
3.256530	---	24.89	46.00	21.11	L1	OFF	19.6
3.256530	38.23	---	56.00	17.77	L1	OFF	19.6
3.450750	---	23.57	46.00	22.43	L1	OFF	19.6

3.450750	37.38	---	56.00	18.62	L1	OFF	19.6
3.516990	---	23.17	46.00	22.83	L1	OFF	19.6
3.516990	36.16	---	56.00	19.84	L1	OFF	19.6
4.355250	---	31.07	46.00	14.93	L1	OFF	19.6
4.355250	35.88	---	56.00	20.12	L1	OFF	19.6
13.560000	---	42.97	50.00	7.03	L1	OFF	19.8
13.560000	44.62	---	60.00	15.38	L1	OFF	19.8

EUT Information

Test Mode : Mode 1
 Test Voltage : 110Vac/60Hz
 Phase : Neutral

Full Spectrum





Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156683	---	27.06	55.64	28.58	N	OFF	19.5
0.156683	45.77	---	65.64	19.87	N	OFF	19.5
0.165750	---	24.32	55.17	30.85	N	OFF	19.5
0.165750	43.01	---	65.17	22.16	N	OFF	19.5
0.188790	---	32.95	54.09	21.14	N	OFF	19.5
0.188790	48.51	---	64.09	15.58	N	OFF	19.5
0.550680	---	27.38	46.00	18.62	N	OFF	19.5
0.550680	37.13	---	56.00	18.87	N	OFF	19.5
0.611250	---	33.02	46.00	12.98	N	OFF	19.5
0.611250	39.55	---	56.00	16.45	N	OFF	19.5
0.753270	---	34.60	46.00	11.40	N	OFF	19.6
0.753270	38.13	---	56.00	17.87	N	OFF	19.6
2.814000	---	27.51	46.00	18.49	N	OFF	19.6
2.814000	36.15	---	56.00	19.85	N	OFF	19.6
2.897250	---	27.07	46.00	18.93	N	OFF	19.6
2.897250	36.51	---	56.00	19.49	N	OFF	19.6
3.063750	---	27.32	46.00	18.68	N	OFF	19.6
3.063750	39.60	---	56.00	16.40	N	OFF	19.6
3.124500	---	25.94	46.00	20.06	N	OFF	19.6
3.124500	38.19	---	56.00	17.81	N	OFF	19.6
3.208200	---	25.53	46.00	20.47	N	OFF	19.6

3.208200	38.16	---	56.00	17.84	N	OFF	19.6
3.336000	---	24.12	46.00	21.88	N	OFF	19.6
3.336000	37.86	---	56.00	18.14	N	OFF	19.6
3.443100	---	27.29	46.00	18.71	N	OFF	19.6
3.443100	41.77	---	56.00	14.23	N	OFF	19.6
4.341750	---	30.99	46.00	15.01	N	OFF	19.6
4.341750	36.38	---	56.00	19.62	N	OFF	19.6
12.705000	---	33.16	50.00	16.84	N	OFF	19.9
12.705000	38.66	---	60.00	21.34	N	OFF	19.9
13.560000	---	37.35	50.00	12.65	N	OFF	19.9
13.560000	40.55	---	60.00	19.45	N	OFF	19.9

Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
 Ref 10 dBm Att 30 dB RBW 1 kHz VSW 3 kHz SWT 20 ms Marker 1 (T1) -12.61 dBm 13.560060000 MHz 20dB BW 2.640000000 kHz Temp 1 (T1) 0dBm -32.82 dBm 13.558700000 MHz Temp 2 (T1) 0dBm -32.33 dBm 13.561340000 MHz Center 13.56 MHz 1 kHz/ Span 10 kHz Date: 10.JAN.2020 10:40:29		 Ref 10 dBm Att 30 dB RBW 1 kHz VSW 3 kHz SWT 20 ms Marker 1 (T1) -12.38 dBm 13.560060000 MHz 99% BW 2.240000000 kHz Temp 1 (T1) 0dBm -32.81 dBm 13.558700000 MHz Temp 2 (T1) 0dBm -32.33 dBm 13.561340000 MHz Center 13.56 MHz 1 kHz/ Span 10 kHz Date: 10.JAN.2020 10:30:48	
20dB Bandwidth (kHz)	2.64	99% OccupiedBW(kHz)	2.24
Frequency range (MHz)	$f_L > 13.553$	13.55870	Test Result
	$f_H < 13.567$	13.56134	Complies

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.



B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
110	13.560020	-20	0	13.560140
93.5	13.560030		2	13.560140
126.5	13.560020		5	13.560140
			10	13.560140
		-10	0	13.560100
			2	13.560100
			5	13.560100
			10	13.560100
		0	0	13.560100
			2	13.560100
			5	13.560100
			10	13.560100
		10	0	13.560080
			2	13.560080
			5	13.560080
			10	13.560080
		20	0	13.560040
			2	13.560020
			5	13.560020
			10	13.560030
		30	0	13.560060
			2	13.560040
			5	13.560040
			10	13.560040
		40	0	13.560030
			2	13.560030
			5	13.560030
			10	13.560030





Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
		50	0	13.560030
			2	13.560030
			5	13.560040
			10	13.560040
Max.Deviation (MHz)	0.000030	Max.Deviation (MHz)		0.000140
Max.Deviation (ppm)	2.2124	Max.Deviation (ppm)		10.3245
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS


Appendix C. Test Results of Radiated Test Items


C1. Test Result of Field Strength of Fundamental Emissions


<Sample 1>




<Sample 3>



C2.Results of Radiated Spurious Emissions (9 kHz~30MHz)
<Sample 1>






<Sample 3>




Note:

1. 13.56 MHz is fundamental signal which can be ignored.
2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
4. Limit line = specific limits (dBμV) + distance extrapolation factor.

C3.Results of Radiated Spurious Emissions (30MHz~1GHz)
<Sample 1>




<Sample 3>



Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.

Annex. A Receiver Radiated Emission Measurement

A.1 Limit of Receiver Radiated Emission

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

A.2 Measuring Instruments


See list of measuring equipment of this test report.

A.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

A.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz




A.5 Test Result of Receiver Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per NCC LP0002 section 5.13 was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

A.6 Connection Diagram of Test System



A.7 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
Remark: 配件 iPod Earphone 由耕興股份有限公司電磁相容及無線通信實驗室提供併同檢驗，不隨貨提供。						


A.8 Test Result Results of Receiver Radiated Spurious Emissions

Test Engineer :	Cookie Ku, Fu Chen and Troye Hsieh	Temperature :	18.6~21.3°C
		Relative Humidity :	68.7~69.6%
Frequency	34.850 MHz	Margin	Under 6.93 dB
Test Mode	NFC Idle		


<For 9 kHz ~ 30 MHz>


<For Sample 1>


Test Mode :	NFC Rx	Polarization :	Horizontal
--------------------	--------	-----------------------	------------



Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01925	41.47	-80.45	121.92	22.39	19.07	0.01	-	-	Average
0.06912	44.62	-66.19	110.81	25.49	19.12	0.01	-	-	Average
0.11	43.41	-63.37	106.78	24.87	18.53	0.01	-	-	QP
0.13496	33.33	-71.67	105	14.72	18.6	0.01	-	-	Average
0.1602	53.27	-50.24	103.51	34.58	18.68	0.01	-	-	Average
1.249	50.6	-15.08	65.68	31.61	18.98	0.01	100	0	QP
8.376	38.72	-30.78	69.5	18.22	20.38	0.12	-	-	QP
23.731	37.5	-32	69.5	15.32	22	0.18	-	-	QP
29.16	38.53	-30.97	69.5	15.9	22.43	0.2	-	-	QP




<For Sample 3>




Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
3. Limit line = specific limits (dBμV) + distance extrapolation factor.

<For 30 MHz ~ 1 GHz>


<For Sample 1>






<For Sample 3>

Test Mode :	NFC Rx	Polarization :	Horizontal
--------------------	--------	-----------------------	------------



Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.91	24.79	-15.21	40	33.48	22.8	0.79	32.43	-	-	Peak
36.79	25.83	-14.17	40	36.58	20.76	0.82	32.46	-	-	Peak
298.69	28.32	-17.68	46	39.18	18.91	2.28	32.21	-	-	Peak
938.89	32.75	-13.25	46	29.35	29.48	4.1	31.22	-	-	Peak
950.53	33.64	-12.36	46	29.4	30.09	4.12	31.06	-	-	Peak
955.38	34.07	-11.93	46	29.4	30.38	4.13	31	100	0	Peak


Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.