


Japan Test Report

Equipment : Fitness Watch
Model No. : A04125
Brand Name : GARMIN
Applicant : Garmin Corp.
Address : No.68, Zhangshu 2nd Rd., Xizhi Dist., New
Taipei City 221, Taiwan (R.O.C)
Standard : Article 2 Paragraph 1 Item 19
Received Date : Feb. 25, 2021
Tested Date : Mar. 08, 2021

Measurement was conducted by the following test method:
the test method of Ordinance Concerning Technical Regulations Conformity Certification
etc. of Specified Radio Equipment in Annex 1, the Ministry of Internal Affairs and
Communications notification in Annex "43" of Article 88, Paragraph 1 and ARIB STD-T66.

We, International Certification Corporation, would like to declare that the tested sample has
been evaluated and in compliance with the requirement of the above standards. The test
results contained in this report refer exclusively to the product. It may be duplicated
completely for legal use with the approval of the applicant. It shall not be reproduced except
in full without the written approval of our laboratory.

Reviewed by:


James Fan / Assistant Manager

Approved by:


Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Test Equipment and Calibration Data	7
1.3	Testing Applied Standards	7
1.4	Deviation from Test Standard and Measurement Procedure.....	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION.....	9
2.1	Testing Location and Conditions.....	9
2.2	Testing Facility	9
2.3	The Worst Test Modes and Channel Details	9
3	TRANSMITTER TEST RESULTS	10
3.1	Antenna Power	10
3.2	Frequency Tolerance	11
3.3	Occupied Bandwidth	12
3.4	Transmitter Spurious Emissions.....	13
3.5	Interference Prevention Function	14
4	RECEIVER TEST RESULTS	15
4.1	Receiver Spurious Emissions.....	15
5	TEST LABORATORY INFORMATION	16

APPENDIX A.1 TEST RESULTS FOR ANTENNA POWER

APPENDIX A.2 TEST RESULTS FOR ANTENNA POWER

APPENDIX B TEST RESULTS FOR FREQUENCY TOLERANCE

APPENDIX C TEST RESULTS FOR OCCUPIED BANDWIDTH

APPENDIX D TEST RESULTS FOR TRANSMITTER SPURIOUS EMISSIONS

APPENDIX E TEST RESULTS FOR INTERFERENCE PREVENTION FUNCTION

APPENDIX F TEST RESULTS FOR RECEIVER SPURIOUS EMISSIONS

Release Record

Report No.	Version	Description	Issued Date
JR122504	Rev. 01	Initial issue	Aug. 09, 2021

Summary of Test Results

Ref. Std. Clause	Description	Result
3.2(2)(3)	Antenna Power	Pass
3.2(4)	Frequency Tolerance	Pass
3.2(6)	Transmitter Spurious Emission	Pass
3.2(7)	Occupied Bandwidth	Pass
3.3(1)	Receiver Emission	Pass
3.4.1	Interference prevention function	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Power Type	5Vdc from host 3.87Vdc from battery
Type(s) of Modulation / Technology	GFSK = 1Mbps
Frequency Range (MHz)	2402 ~ 2480 MHz
Total Channel Number	79
HW Version	105-04125-00
SW Version	2.0

1.1.2 Accessories

Accessories		
No.	Equipment	Description
1	Battery	Brand: Garmin Model: 361-00144-00 Power Rating: 3.87Vdc, 240mAh
2	USB cable	Brand: GARMIN Model: 320-01069-10 Line: 0.52m shielded without core

1.1.3 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Gain (dBi)	Remarks
1	Garmin	117-01514-00	Monopole	N/A	-3.25934	---

Note: Please refer to antenna report for more details about antenna pattern and other information.

1.1.4 Antenna Power

Operating Mode	Rated Power (mW)	Measured Conducted Power (mW)	Radiated Power(mW)
GFSK	1.00	0.87902	0.415

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	21	2422	41	2442	61	2462
2	2403	22	2423	42	2443	62	2463
3	2404	23	2424	43	2444	63	2464
4	2405	24	2425	44	2445	64	2465
5	2406	25	2426	45	2446	65	2466
6	2407	26	2427	46	2447	66	2467
7	2408	27	2428	47	2448	67	2468
8	2409	28	2429	48	2449	68	2469
9	2410	29	2430	49	2450	69	2470
10	2411	30	2431	50	2451	70	2471
11	2412	31	2432	51	2452	71	2472
12	2413	32	2433	52	2453	72	2473
13	2414	33	2434	53	2454	73	2474
14	2415	34	2435	54	2455	74	2475
15	2416	35	2436	55	2456	75	2476
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18	2419	38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461	---	---

1.1.6 Test Tool and Power Index

Test Tool
ANT Test, Ver. 1.18

Power Index			
Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK	Default	Default	Default

1.1.7 Test Voltage

Test Voltage	☒ Vnom (3.8Vdc)	☒ Vmax (4.45Vdc)	☒ Vmin (3.6Vdc)
--------------	---	--	---

1.1.8 Protection Method for High Frequency and Modulation Section

Protected Method	Description
Glue on RF Part	The RF chipset will be protected by glue.

1.2 Test Equipment and Calibration Data

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Mar. 08, 2021				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101486	Feb. 23, 2021	Feb. 22, 2022
Power Meter	Anritsu	ML2495A	1241002	Nov. 04, 2020	Nov. 03, 2021
Power Sensor	Anritsu	MA2411B	1207366	Nov. 04, 2020	Nov. 03, 2021
DC POWER SOURCE	GW INSTEK	GPC-6030D	GES855395	Nov. 09, 2020	Nov. 08, 2021
Measurement Software	-	SENSE-T66_DTS	V5.10.7	NA	NA
Note 1: Calibration Interval of instruments listed above is one year.					
Note 2: Above instruments are calibrated by Electronics Testing Center					

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Article 2 Paragraph 1 Item 19

1.4 Deviation from Test Standard and Measurement Procedure

None

1.5 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.139 Hz
Conducted power	± 0.808 dB
Frequency error	$\pm 1 \times 10^{-9}$
TX Conducted emission	± 2.680 dB
RX Conducted emission	± 3.034 dB

2 Test Configuration

2.1 Testing Location and Conditions

Test Site	Site Category	Ambient Condition	Tested By
TH01-WS	OVEN Room	24°C / 63%	Alex Huang

2.2 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

2.3 The Worst Test Modes and Channel Details

Test item	Mode	Test channel
Antenna Power Frequency Tolerance Occupied Bandwidth Transmitter Spurious Emission Interference prevention function Receiver Spurious Emissions	GFSK	2402 / 2440 / 2480

3 Transmitter Test Results

3.1 Antenna Power


3.1.1 Limit of Antenna Power

Mode	Limit	Tolerance
1) FH, FH+DS, FH+OFDM	3 mW / MHz	+20 % , -80 %
2) OFDM(Narrow- bandwidht), DS	10 mW / MHz	
3) Other than 1) & 2)	10mW	
4) OFDM (Wide-band)	5 mW / MHz	

3.1.2 Test Procedures

Measure the total power by Power Meter

3.1.3 Test Setup



3.1.4 Test Result of Maximum Transmit Power

Refer to Appendix A1, A2

3.2 Frequency Tolerance

3.2.1 Limit of Frequency Tolerance


Frequency tolerance shall be +/- 50ppm.

3.2.2 Test Procedures

1. Set Span = 500kHz, RBW = 1kHz, VBW = 3kHz, Sweep time = Auto, detector = Peak.
2. Use Peak search function to find the max peak value and record this value (RF).
3. Calculate frequency tolerance by below formula
$$FT(ppm) = \{ (RF) - (MF) / (MF) \} \times 1000000$$

(FT: Frequency Tolerance, RF: Reading Frequency, MF: Measurement Frequency.)

3.2.3 Test Setup



3.2.4 Test Result of Frequency Tolerance

Refer to Appendix B

3.3 Occupied Bandwidth


3.3.1 Limit of Occupied Bandwidth

Mode	Limit (MHz)
FH	83.5
FH+DS	83.5
FH+OFDM	83.5
OFDM(Narrow- bandwidht), DS	26
Others	26
OFDM (Wide-band)	38

3.3.2 Test Procedures

1. Set Span = 40MHz, RBW = VBW = 300kHz, detector = Peak, Sweep time = Auto.
2. Enable OBW function of spectrum analyzer to measure OBW and capture test plot.

3.3.3 Test Setup



3.3.4 Test Result of Occupied Bandwidth

Refer to Appendix C

3.4 Transmitter Spurious Emissions


3.4.1 Limit of Transmitter Spurious Emissions

Item	Limits
Tx Spurious Emission	$\leq 2.5 \mu\text{W}$ ($2387\text{MHz} > f$; $2496.5\text{MHz} < f$).
	$\leq 25 \mu\text{W}$. ($2387\text{MHz} \leq f < 2400\text{MHz}$) and ($2483.5\text{MHz} < f \leq 2496.5\text{MHz}$).

3.4.2 Test Procedures

1. Set EUT to transmit at rated power and channel to perform test.
2. Set RBW = VBW = 1MHz, Detector type = Peak, Sweep time = Auto.
3. Following above setting of spectrum analyzer to measure spurious emission of 30~12500 MHz.

3.4.3 Test Setup



3.4.4 Test Result of Transmitter Spurious Emissions

Refer to Appendix D

3.5 Interference Prevention Function


3.5.1 Limit of Interference Prevention Function

Limits
The identification code shall be 48 bits long

3.5.2 Test Procedures

1. Set EUT under operating mode and link up with companion equipment
2. Check communication status between EUT and companion equipment is normal

3.5.3 Test Setup



3.5.4 Test Result of Interference Prevention Function

Refer to Appendix E

4 Receiver Test Results

4.1 Receiver Spurious Emissions


4.1.1 Limit of Receiver Spurious Emissions

Item	Limits
Rx Spurious Emission	$\leq 4\text{nW}$ ($f < 1\text{GHz}$).
	$\leq 20\text{nW}$ ($1\text{GHz} \leq f$).

4.1.2 Test Procedures

1. Set EUT under receiving condition to perform test.
2. Set RBW = VBW = 100kHz, detector = Peak, Sweep time = Auto for emission measurement below 1GHz.
3. Set RBW = VBW=1MHz, detector = Peak, Sweep time = Auto for emission measurement above 1GHz.

4.1.3 Test Setup



4.1.4 Test Result of Receiver Spurious Emissions

Refer to Appendix F

5 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Summary

Mode	Power (dBm)	Power (mW)	EIRP (dBm)	EIRP (mW)
2.4-2.4835GHz	-	-	-	-
ANT+	-0.56	0.87902	-3.82	0.415

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power (mW)	Power Lim. (mW)	EIRP (dBm)	EIRP (mW)	EIRP Lim. (mW)
ANT+	-	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	-3.25934	-0.57	0.87700	10	-3.83	0.414	16.368
2402MHz_TnomVmin	Pass	-3.25934	-0.58	0.87498	10	-3.84	0.413	16.368
2402MHz_TnomVmax	Pass	-3.25934	-0.56	0.87902	10	-3.82	0.415	16.368
2440MHz_TnomVnom	Pass	-3.25934	-0.77	0.83753	10	-4.03	0.395	16.368
2440MHz_TnomVmin	Pass	-3.25934	-0.77	0.83753	10	-4.03	0.395	16.368
2440MHz_TnomVmax	Pass	-3.25934	-0.76	0.83946	10	-4.02	0.396	16.368
2480MHz_TnomVnom	Pass	-3.25934	-1.53	0.70307	10	-4.79	0.332	16.368
2480MHz_TnomVmin	Pass	-3.25934	-1.54	0.70146	10	-4.80	0.331	16.368
2480MHz_TnomVmax	Pass	-3.25934	-1.52	0.70469	10	-4.78	0.333	16.368

**Summary**

Mode	Result	Power (dBm)	Power (mW)	Declare (mW)	Tolerance (%)	Limit+ (%)	Limit- (%)
2.4-2.4835GHz	-	-	-	-	-	-	-
ANT+	Pass	-0.56	0.87902	1.00	-12.10	20	-80

Result

Mode	Result	Power (dBm)	Power (mW)	Declare (mW)	Tolerance (%)	Limit+ (%)	Limit- (%)
ANT+	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	-0.57	0.87700	1.00	-12.30	20	-80
2402MHz_TnomVmin	Pass	-0.58	0.87498	1.00	-12.50	20	-80
2402MHz_TnomVmax	Pass	-0.56	0.87902	1.00	-12.10	20	-80
2440MHz_TnomVnom	Pass	-0.77	0.83753	1.00	-16.25	20	-80
2440MHz_TnomVmin	Pass	-0.77	0.83753	1.00	-16.25	20	-80
2440MHz_TnomVmax	Pass	-0.76	0.83946	1.00	-16.05	20	-80
2480MHz_TnomVnom	Pass	-1.53	0.70307	1.00	-29.69	20	-80
2480MHz_TnomVmin	Pass	-1.54	0.70146	1.00	-29.85	20	-80
2480MHz_TnomVmax	Pass	-1.52	0.70469	1.00	-29.53	20	-80

**Summary**

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
2.4-2.4835GHz	-	-	-	-	-	-	-
ANT+	Pass	2.402G	2.40202842G	11.8318	±50	1	-


Result

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
ANT+	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.402G	2.40202842G	11.8318	±50	1	-
2402MHz_TnomVmin	Pass	2.402G	2.40202841G	11.8268	±50	1	-
2402MHz_TnomVmax	Pass	2.402G	2.4020284G	11.8231	±50	1	-
2440MHz_TnomVnom	Pass	2.44G	2.44002648G	10.8516	±50	1	-
2440MHz_TnomVmin	Pass	2.44G	2.44002648G	10.8516	±50	1	-
2440MHz_TnomVmax	Pass	2.44G	2.44002647G	10.8496	±50	1	-
2480MHz_TnomVnom	Pass	2.48G	2.48002455G	9.8988	±50	1	-
2480MHz_TnomVmin	Pass	2.48G	2.48002454G	9.8964	±50	1	-
2480MHz_TnomVmax	Pass	2.48G	2.48002454G	9.8935	±50	1	-

ANT+

Freq. Stability


2402MHz_TnomVnom



ANT+

Freq. Stability


2402MHz_TnomVmin



ANT+

Freq. Stability


2402MHz_TnomVmax



ANT+

Freq. Stability


2440MHz_TnomVnom



ANT+

Freq. Stability


2440MHz_TnomVmin



ANT+

Freq. Stability


2440MHz_TnomVmax



ANT+

Freq. Stability


2480MHz_TnomVnom



ANT+

Freq. Stability

2480MHz_TnomVmin






ANT+

Freq. Stability

2480MHz_TnomVmax



**Summary**

Mode	Max-OBW (Hz)	ITU-Code	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-
ANT+	1.148M	1M14D1D	1.108M

Max-OBW = Maximum 99% occupied bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result


Mode	Result	Limit (Hz)	P1-OBW (Hz)
ANT+	-	-	-
2402MHz_TnomVnom	Pass	26M	1.114M
2402MHz_TnomVmin	Pass	26M	1.114M
2402MHz_TnomVmax	Pass	26M	1.113M
2440MHz_TnomVnom	Pass	26M	1.108M
2440MHz_TnomVmin	Pass	26M	1.108M
2440MHz_TnomVmax	Pass	26M	1.108M
2480MHz_TnomVnom	Pass	26M	1.148M
2480MHz_TnomVmin	Pass	26M	1.148M
2480MHz_TnomVmax	Pass	26M	1.148M

P1-OBW = Port 1 99% occupied bandwidth;

ANT+

OBW


2402MHz_TnomVnom



ANT+

OBW


2402MHz_TnomVmin



ANT+

OBW


2402MHz_TnomVmax



ANT+

OBW


2440MHz_TnomVnom



ANT+

OBW


2440MHz_TnomVmin



ANT+

OBW


2440MHz_TnomVmax



ANT+

OBW


2480MHz_TnomVnom



ANT+

OBW


2480MHz_TnomVmin



ANT+

OBW

2480MHz_TnomVmax



**Summary**

Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Freq (Hz)	Psum (dBm/MHz)	Psum (uW/MHz)	Limit (dBm/MHz)	Limit (uW/MHz)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-
ANT+	Pass	2.4965G	12.5G	1M	9.60899G	-44.11	0.03882	-26.02	2.5

Result

Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Freq (Hz)	Psum (dBm/MHz)	Psum (uW/MHz)	Limit (dBm/MHz)	Limit (uW/MHz)
ANT+	-	-	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	30M	2.387G	1M	2.32925G	-55.97	0.00253	-26.02	2.5
2402MHz_TnomVnom	Pass	2.387G	2.4G	1M	2.4G	-41.92	0.06427	-16.02	25
2402MHz_TnomVnom	Pass	2.4835G	2.4965G	1M	2.49185G	-56.02	0.0025	-16.02	25
2402MHz_TnomVnom	Pass	2.4965G	12.5G	1M	9.60899G	-44.11	0.03882	-26.02	2.5
2402MHz_TnomVmin	Pass	30M	2.387G	1M	2.321G	-55.62	0.00274	-26.02	2.5
2402MHz_TnomVmin	Pass	2.387G	2.4G	1M	2.4G	-41.94	0.06397	-16.02	25
2402MHz_TnomVmin	Pass	2.4835G	2.4965G	1M	2.49203G	-55.98	0.00252	-16.02	25
2402MHz_TnomVmin	Pass	2.4965G	12.5G	1M	9.60899G	-44.70	0.03388	-26.02	2.5
2402MHz_TnomVmax	Pass	30M	2.387G	1M	2.35282G	-55.98	0.00252	-26.02	2.5
2402MHz_TnomVmax	Pass	2.387G	2.4G	1M	2.4G	-41.92	0.06427	-16.02	25
2402MHz_TnomVmax	Pass	2.4835G	2.4965G	1M	2.49G	-56.08	0.00247	-16.02	25
2402MHz_TnomVmax	Pass	2.4965G	12.5G	1M	9.60899G	-44.85	0.03273	-26.02	2.5
2440MHz_TnomVnom	Pass	30M	2.387G	1M	2.36932G	-56.02	0.0025	-26.02	2.5
2440MHz_TnomVnom	Pass	2.387G	2.4G	1M	2.38755G	-56.55	0.00221	-16.02	25
2440MHz_TnomVnom	Pass	2.4835G	2.4965G	1M	2.49185G	-56.07	0.00247	-16.02	25
2440MHz_TnomVnom	Pass	2.4965G	12.5G	1M	9.76029G	-45.35	0.02917	-26.02	2.5
2440MHz_TnomVmin	Pass	30M	2.387G	1M	2.33043G	-55.91	0.00256	-26.02	2.5
2440MHz_TnomVmin	Pass	2.387G	2.4G	1M	2.39698G	-56.60	0.00219	-16.02	25
2440MHz_TnomVmin	Pass	2.4835G	2.4965G	1M	2.48854G	-56.05	0.00248	-16.02	25
2440MHz_TnomVmin	Pass	2.4965G	12.5G	1M	9.76029G	-44.79	0.03319	-26.02	2.5
2440MHz_TnomVmax	Pass	30M	2.387G	1M	2.31393G	-55.82	0.00262	-26.02	2.5
2440MHz_TnomVmax	Pass	2.387G	2.4G	1M	2.39808G	-56.54	0.00222	-16.02	25
2440MHz_TnomVmax	Pass	2.4835G	2.4965G	1M	2.48828G	-56.03	0.00249	-16.02	25
2440MHz_TnomVmax	Pass	2.4965G	12.5G	1M	9.76029G	-45.39	0.02891	-26.02	2.5
2480MHz_TnomVnom	Pass	30M	2.387G	1M	2.29272G	-55.99	0.00252	-26.02	2.5
2480MHz_TnomVnom	Pass	2.387G	2.4G	1M	2.39878G	-56.60	0.00219	-16.02	25
2480MHz_TnomVnom	Pass	2.4835G	2.4965G	1M	2.4835G	-55.73	0.00267	-16.02	25
2480MHz_TnomVnom	Pass	2.4965G	12.5G	1M	9.92035G	-45.36	0.02911	-26.02	2.5
2480MHz_TnomVmin	Pass	30M	2.387G	1M	2.36814G	-55.84	0.00261	-26.02	2.5
2480MHz_TnomVmin	Pass	2.387G	2.4G	1M	2.38885G	-56.59	0.00219	-16.02	25
2480MHz_TnomVmin	Pass	2.4835G	2.4965G	1M	2.48355G	-55.72	0.00268	-16.02	25
2480MHz_TnomVmin	Pass	2.4965G	12.5G	1M	9.92035G	-45.15	0.03055	-26.02	2.5
2480MHz_TnomVmax	Pass	30M	2.387G	1M	2.27858G	-55.74	0.00267	-26.02	2.5
2480MHz_TnomVmax	Pass	2.387G	2.4G	1M	2.39951G	-56.49	0.00224	-16.02	25

**CSE-TX-DTS Unwanted Emission Strength****Appendix D**


Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Freq (Hz)	Psum (dBm/MHz)	Psum (uW/MHz)	Limit (dBm/MHz)	Limit (uW/MHz)
2480MHz_TnomVmax	Pass	2.4835G	2.4965G	1M	2.48368G	-55.65	0.00272	-16.02	25
2480MHz_TnomVmax	Pass	2.4965G	12.5G	1M	9.92035G	-44.47	0.03573	-26.02	2.5



ANT+

CSE-TX-DTS

2402MHz_TnomVnom




Limit
Port1

F-Start(Hz)	F-Stop(Hz)	Freq(Hz)	Psum(dBm)	Limit(dBm)	Margin(dB)	P1(dBm)
30M	2.387G	2.32925G	-55.97	-26.02	-29.95	-55.97
2.387G	2.4G	2.4G	-41.92	-16.02	-25.90	-41.92
2.4835G	2.4965G	2.49185G	-56.02	-16.02	-40.00	-56.02
2.4965G	12.5G	9.60899G	-44.11	-26.02	-18.09	-44.11

ANT+

CSE-TX-DTS

2402MHz_TnomVmin



Limit
Port1


F-Start(Hz)	F-Stop(Hz)	Freq(Hz)	Psum(dBm)	Limit(dBm)	Margin(dB)	P1(dBm)
30M	2.387G	2.321G	-55.62	-26.02	-29.60	-55.62
2.387G	2.4G	2.4G	-41.94	-16.02	-25.92	-41.94
2.4835G	2.4965G	2.49203G	-55.98	-16.02	-39.96	-55.98
2.4965G	12.5G	9.60899G	-44.70	-26.02	-18.68	-44.70



ANT+

CSE-TX-DTS

2402MHz_TnomVmax




F-Start(Hz)	F-Stop(Hz)	Freq(Hz)	Psum(dBm)	Limit(dBm)	Margin(dB)	P1(dBm)
30M	2.387G	2.35282G	-55.98	-26.02	-29.96	-55.98
2.387G	2.4G	2.4G	-41.92	-16.02	-25.90	-41.92
2.4835G	2.4965G	2.49G	-56.08	-16.02	-40.06	-56.08
2.4965G	12.5G	9.60899G	-44.85	-26.02	-18.83	-44.85

ANT+

CSE-TX-DTS

2440MHz_TnomVnom




F-Start(Hz)	F-Stop(Hz)	Freq(Hz)	Psum(dBm)	Limit(dBm)	Margin(dB)	P1(dBm)
30M	2.387G	2.36932G	-56.02	-26.02	-30.00	-56.02
2.387G	2.4G	2.38755G	-56.55	-16.02	-40.53	-56.55
2.4835G	2.4965G	2.49185G	-56.07	-16.02	-40.05	-56.07
2.4965G	12.5G	9.76029G	-45.35	-26.02	-19.33	-45.35



ANT+

CSE-TX-DTS


2440MHz_TnomVmin



ANT+

CSE-TX-DTS


2440MHz_TnomVmax



ANT+

CSE-TX-DTS


2480MHz_TnomVnom



ANT+

CSE-TX-DTS

2480MHz_TnomVmin






ANT+

CSE-TX-DTS

2480MHz_TnomVmax



Limit
Port 1

F-Start(Hz)	F-Stop(Hz)	Freq(Hz)	Psum(dBm)	Limit(dBm)	Margin(dB)	P1(dBm)
30M	2.387G	2.27858G	-55.74	-26.02	-29.72	-55.74
2.387G	2.4G	2.39951G	-56.49	-16.02	-40.47	-56.49
2.4835G	2.4965G	2.48368G	-55.65	-16.02	-39.63	-55.65
2.4965G	12.5G	9.92035G	-44.47	-26.02	-18.45	-44.47

**Summary**

Mode	Result	MAC (ID Length)	ID Limit	Function
2.4-2.4835GHz	-	-	-	-
ANT+	Pass	48 bits	48 bits	Good

Result

Mode	Result	MAC (ID Length)	ID Limit	Function
ANT+	-	-	-	-
2402MHz_TnomVnom	Pass	48 bits	48 bits	Good
2402MHz_TnomVmin	Pass	48 bits	48 bits	Good
2402MHz_TnomVmax	Pass	48 bits	48 bits	Good
2440MHz_TnomVnom	Pass	48 bits	48 bits	Good
2440MHz_TnomVmin	Pass	48 bits	48 bits	Good
2440MHz_TnomVmax	Pass	48 bits	48 bits	Good
2480MHz_TnomVnom	Pass	48 bits	48 bits	Good
2480MHz_TnomVmin	Pass	48 bits	48 bits	Good
2480MHz_TnomVmax	Pass	48 bits	48 bits	Good

**Summary**

Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Freq (Hz)	Psum (dBm)	Psum (nW)	Limit (dBm)	Limit (nW)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-
ANT+	Pass	30M	1G	100k	59.59M	-66.88	0.20512	-53.98	4

Result


Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Freq (Hz)	Psum (dBm)	Psum (nW)	Limit (dBm)	Limit (nW)
ANT+	-	-	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	30M	1G	100k	95.96M	-69.92	0.10186	-53.98	4
2402MHz_TnomVnom	Pass	1G	12.5G	1M	2.53238G	-62.37	0.57943	-46.99	20
2402MHz_TnomVmin	Pass	30M	1G	100k	59.59M	-66.88	0.20512	-53.98	4
2402MHz_TnomVmin	Pass	1G	12.5G	1M	9.61206G	-63.19	0.47973	-46.99	20
2402MHz_TnomVmax	Pass	30M	1G	100k	32.43M	-70.29	0.09354	-53.98	4
2402MHz_TnomVmax	Pass	1G	12.5G	1M	9.61206G	-63.61	0.43551	-46.99	20
2440MHz_TnomVnom	Pass	30M	1G	100k	95.48M	-68.50	0.14125	-53.98	4
2440MHz_TnomVnom	Pass	1G	12.5G	1M	12.47556G	-65.31	0.29444	-46.99	20
2440MHz_TnomVmin	Pass	30M	1G	100k	31.94M	-69.88	0.1028	-53.98	4
2440MHz_TnomVmin	Pass	1G	12.5G	1M	12.45256G	-65.62	0.27416	-46.99	20
2440MHz_TnomVmax	Pass	30M	1G	100k	31.94M	-69.77	0.10544	-53.98	4
2440MHz_TnomVmax	Pass	1G	12.5G	1M	10.52631G	-65.31	0.29444	-46.99	20
2480MHz_TnomVnom	Pass	30M	1G	100k	95.96M	-70.52	0.08872	-53.98	4
2480MHz_TnomVnom	Pass	1G	12.5G	1M	12.46119G	-65.70	0.26915	-46.99	20
2480MHz_TnomVmin	Pass	30M	1G	100k	32.91M	-70.65	0.0861	-53.98	4
2480MHz_TnomVmin	Pass	1G	12.5G	1M	12.48994G	-65.68	0.2704	-46.99	20
2480MHz_TnomVmax	Pass	30M	1G	100k	32.43M	-70.13	0.09705	-53.98	4
2480MHz_TnomVmax	Pass	1G	12.5G	1M	12.46838G	-65.50	0.28184	-46.99	20



ANT+

CSE-RX-DTS


2402MHz_TnomVnom



ANT+

CSE-RX-DTS


2402MHz_TnomVmin



ANT+

CSE-RX-DTS

2402MHz_TnomVmax






ANT+

CSE-RX-DTS


2440MHz_TnomVnom



ANT+

CSE-RX-DTS


2440MHz_TnomVmin



ANT+

CSE-RX-DTS


2440MHz_TnomVmax



ANT+

CSE-RX-DTS


2480MHz_TnomVnom



ANT+

CSE-RX-DTS

2480MHz_TnomVmin



ANT+

CSE-RX-DTS

2480MHz_TnomVmax

