

NCC

低功率射頻器材型式試驗報告

產品名稱 : Game Console
型號 : HEG-001
廠牌 : Nintendo
商標 : 
申請者 : Nintendo Co., Ltd.
申請者地址 : 11-1 Hokotate-cho, Kamitoba, Minami-ku, Kyoto, Japan
測試標準 : LP0002 (109 年版)
參考法規 : ANSI C63.10-2013
測試結果 : 符合
接收日期 : 2021/3/25
測試日期 : 2021/3/30~2021/6/26

測試工程師 : 
(許丞哲)

報告審核人 : 
(陳柏均)

報告簽署人 : 
(柯承志)



修訂紀錄

報告編號	版本	描述	發行日期
2103TW3702-T3	1.0	Original Report	2021-06-28

CONTENTS

Description	Page
1. 一般資訊.....	5
2. 產品描述.....	6
2.1 產品資訊.....	6
2.2 產品規格.....	7
2.4 測試配置.....	10
2.5 測試周邊.....	11
2.6 操作程序.....	11
3. 測試設備明細.....	12
4. 量測不確定度.....	13
5. 測試結果.....	14
5.1 電源傳導測試.....	15
5.1.1 量測方法.....	15
5.1.2 限制要求.....	15
5.1.3 測試架構圖.....	15
5.1.4 電源端點測試結果.....	16
5.2 峰值傳導輸出功率.....	18
5.2.1 量測方法.....	18
5.2.2 限制要求.....	18
5.2.3 測試架構圖.....	18
5.2.4 峰值傳導輸出功率測試結果.....	19
5.3 天線之要求.....	46
5.3.1 限制要求.....	46
5.3.2 天線樣式.....	46
5.4 帶外發射限制.....	47
5.4.1 量測方法.....	47
5.4.2 限制要求.....	47
5.4.3 測試架構圖.....	47
5.4.4 帶外輻射測試結果.....	48
5.5 輻射電場強度.....	66
5.5.1 量測方法.....	66
5.5.2 限制要求.....	66
5.5.3 測試架構圖.....	67
5.5.4 輻射電場強度測試結果.....	69
5.6 頻帶邊緣.....	115

5.6.1 量測方法.....	115
5.6.2 限制要求.....	115
5.6.3 測試架構圖.....	116
5.6.4 頻帶邊緣測試結果.....	118
5.7 占用頻寬.....	182
5.7.1 量測方法.....	182
5.7.2 限制要求.....	182
5.7.3 測試架構圖.....	182
5.7.4 占用頻寬測試結果.....	183
5.8. 功率頻譜密度.....	192
5.8.1 量測方法.....	192
5.8.2 限制要求.....	192
5.8.3 測試架構圖.....	192
5.8.4 功率頻譜密度測試結果.....	193

1. 一般資訊

申請者	Nintendo Co., Ltd.
申請者地址	11-1 Hokotate-cho, Kamitoba, Minami-ku, Kyoto, Japan
製造商	Nintendo Co., Ltd.
製造商地址	11-1 Hokotate-cho, Kamitoba, Minami-ku, Kyoto, Japan
實驗室	台灣曼瑞檢測科技有限公司
實驗室地址	33377 台灣桃園市龜山區復興二路 38 號
實驗室資訊	1. MRT facility is a FCC registered (Reg. No. 153292) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm. 2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada. 3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.
實驗室測試環境條件	溫度 (°C) : 20-35 / 濕度 (%RH) : 30-65

2. 產品描述

2.1 產品資訊

產品名稱	Game Console
產品型號	HEG-001
廠牌	Nintendo
商標	
支援規格	2.4G: 802.11b/g/n-20/n-40/VHT-20/VHT-40 5G: 802.11a/n-20/ac-20/n-40/ac-40/ac-80, Band 1,2,3,4 Bluetooth Dual Mode: V4.2
Wi-Fi 規格	802.11b/g/n-20/n-40/ac-20/ac-40 (2TX / 2RX)
頻率範圍	2.4GHz: For 802.11b/g/n-HT20/ac-VHT20: 2412 ~ 2472 MHz For 802.11n-HT40/ac-VHT40: 2422 ~ 2462 MHz
最大輸出功率	802.11b: 17.62dBm 802.11g: 21.12dBm 802.11n-HT20 (SISO): 21.14dBm 802.11n-HT20 (MIMO): 22.39dBm 802.11n-HT40 (SISO): 16.26dBm 802.11n-HT40 (MIMO): 18.99dBm 802.11VHT20 (SISO): 20.07dBm 802.11VHT20 (MIMO): 21.92dBm 802.11VHT40 (SISO): 15.59dBm 802.11VHT40 (MIMO): 18.23dBm
配件	
Dock	Model No: HEG-007 Brand: Nintendo
HDMI cable	Model No: HEG-005 Brand: Nintendo
AC adaptor	Model No: HAC-002 Brand: Nintendo Input: AC 100-240V~1A, 50-60Hz Output: DC 15V, 2.6A/ DC 5V, 1.5A DC Cable Out: Non-Shielding, 2.5m
Joy-con(L)	Model No: HAC-015 Brand: Nintendo
Joy-con(R)	Model No: HAC-016 Brand: Nintendo

2.2 產品規格

Technology	Frequency (MHz)	Modulation	channel Spacing (MHz)	Data Rate (Mbps)	Number of Channels
802.11b	2412~2472	DSSS (CCK, DQPSK, DBPSK)	5	1 ~11	11
802.11g	2412~2472	OFDM (BPSK, QPSK,16QAM,64QAM)	5	6 ~54	11
802.11n-20M/ VHT-20	2412~2472	OFDM (BPSK, QPSK,16QAM,64QAM)	5	7.2-144.4	11
802.11n-40M/ VHT-40	2422~2462	OFDM (BPSK, QPSK,16QAM,64QAM)	5	15-300	7

802.11b/g/n-HT20/VHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	12	2467 MHz
13	2472 MHz	--	--	--	--

802.11n-HT40/VHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	10	2457 MHz	11	2462 MHz

Duty Cycle

Test Mode	Duty Cycle
802.11b	99%
802.11g	94%
802.11 n-HT20/VHT20	93%
802.11 n-HT40/VHT40	88%




2.3 測試模式

Test Mode	Mode 1: Transmit by 802.11b
	Mode 2: Transmit by 802.11g
	Mode 3: Transmit by 802.11n-HT20
	Mode 4: Transmit by 802.11n-HT40
	Mode 5: Receive by 802.11n-HT20

Note: Since 802.11n and 802.11VHT have the same modulation/data rate/bandwidth, and after confirmation of conducted power, we select 802.11n-HT20 and HT40 are covered by 802.11VHT20 and VHT40 in this report.

2.4 測試配置

待測物測試配置圖



Signal Cable Type		Signal Cable Description
A	LAN Cable	Non-Shielded, 3.0m
B	USB 3.0 Cable	Shielded, 0.1m (Brand: Logitec; M/N: LAN-GTJU3)
C	HDMI Cable	Shielded, 1.5m
D	USB 3.0 Cable	Shielded, 1.5 (Brand: Nintendo; M/N: S-1309)
E	USB 3.0 Cable	Shielded, 0.4 (Brand: Nintendo; M/N: HAT-003)
F	Signal Cable	Non-Shielded, 1.8 (Brand: Nintendo; M/N: TTL-232RG)

2.5 測試周邊

待測裝置測試時，其搭配系統測試時之週邊裝置包括如下：

No.	周邊名稱	廠牌	型號	序號	電源線
1	USB LAN Adapter	Logitec	LAN-GTJU3	N/A	N/A
2	Monitor	Dell	U2718Q	N/A	Non-shielded, 1.8m
3	SDEV Cradle	Nintendo	HAT-003	N/A	Non-shielded, 1.5m
4	Adapter	Nintendo	HAC-002	N/A	N/A
5	USB UART Adapter	FTDI Chip	TTL-232RG	N/A	N/A
6	Notebook PC	Panasonic	CF-SV	N/A	Non-shielded, 0.8m

2.6 操作程序

1.	Turn on the power of all equipment.
2.	Execute “cmd.exe: Ver 10.0 18362 657” program
3.	Configure the test channel and the data rate.
4.	Start test.

3. 測試設備明細

傳導干擾 -SR2

儀器名稱	廠牌	型號	財產編號	校正週期	有效日期
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2022/3/23
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2022/4/28
8-Wire ISN (T8)	R&S	ENY81	MRTTWA00018	1 year	2022/5/30
Cable	Rosnol	N1C50-RG400- B1C50-500CM	MRTTWE00013	1 year	2021/6/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2022/3/24

輻射干擾 - AC1

儀器名稱	廠牌	型號	財產編號	校正週期	有效日期
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2021/10/5
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2022/3/24
Active Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2022/5/6
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2022/4/21
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2022/4/28
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2022/4/26
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2022/4/21
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2021/6/16

傳導量測設備 -SR2

儀器名稱	廠牌	型號	財產編號	校正週期	有效日期
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2021/10/14
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2021/7/14
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2022/3/24

EMI 測試軟體

軟體名稱	廠牌	版本
e3	Audix	9.160520a
EMI	Quietek	V3

4. 量測不確定度

電源傳導量測-電源線 (Conducted Emission- Power Line)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.15MHz~30MHz: $\pm 2.53\text{dB}$
輻射干擾量測 (Radiated Spurious Emission)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz~30MHz: $\pm 3.92\text{dB}$ 30MHz~1GHz: $\pm 4.25\text{dB}$ 1GHz~18GHz: $\pm 4.40\text{dB}$ 18GHz~40GHz: $\pm 4.45\text{dB}$
頻率誤差量測 (Frequency Error)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 78.4\text{Hz}$
傳導功率量測 (Conducted Power)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.84\text{dB}$
傳導干擾量測 (Conducted Spurious Emission)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 2.65\text{ dB}$
佔用頻寬量測 (Occupied Bandwidth)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 3.3%
溫度 / 濕度 (Temp. / Humidity)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.82^\circ\text{C}/ \pm 3\%$
直流電源 (DC Voltage)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.3\%$

5. 測試結果

產品名稱 **Game Console**
型號 **HEG-001**

章節	量測項目	限制值	測試結果	測試數據
3.3	電源傳導	低功率射頻器材技術規範 3.3 節	符合	第 5.1 章節
4.10.1.2	峰值傳導輸出功率	$\leq 30.00\text{dBm}$	符合	第 5.2 章節
4.10.1.3	天線之要求	低功率射頻器材技術規範 4.10.1.3 節	符合	第 5.3 章節
4.10.1.5	帶外發射限制	$\leq 20\text{dBc(Peak)}$	符合	第 5.4 章節
3.6	輻射電場強度	低功率射頻器材技術規範 3.6 節	符合	第 5.5 章節
3.5	頻帶邊緣	$\leq 74\text{dBuV/m(Peak)}$ $\leq 54\text{dBuV/m(Average)}$	符合	第 5.6 章節
4.10.1.6(2)(A)	占用頻寬	$\geq 500\text{KHz}$	符合	第 5.7 章節
4.10.1.6(2)(B)	功率頻譜密度	$\leq 8\text{dBm}$	符合	第 5.8 章節

備註：符合性的判定是基於測試結果符合規範的限制值或客戶的宣告要求，測試結果的判定是不考慮測量不確定度的值。

5.1 電源傳導測試

5.1.1 量測方法

待測物放置於1m*2m*0.8m之非導體桌面並離垂直牆面40cm（落地型產品置於地上），將待測物之電源線接至電源阻抗網路器(LISN)，同時保持待測物至LISN距80公分，並將電源線多餘部份以30至40公分之八字形捆綁於電源線中央並離地40cm，於在正常工作狀態下，執行待測物之火線(Line)及地線(neutral)各一次量測。

電源端點場強之測量範圍由 0.15MHz –30MHz，所量測之讀值皆為準尖峰值(Quasi-Peak Value)及平均值(Average Value)。場強接收機之解析頻寬為9kHz。

備 註：經初測驗證過，電源端點干擾測試對測試頻道數並無差異，因此檢附其中一個測試頻道之測試數。


5.1.2 限制要求

以市電為電源之低功率射頻器材，其傳導回電源線上頻率自150kHz至30MHz之射頻電壓(在電源端子每一電源線對接地點)應小於或等於下表所列之限值。測量時應經過50微亨利(μH)及50歐姆(Ω)之電源線阻抗模擬網路(LISN)。頻率重疊處，以較低限值為準。

Frequency 頻率範圍 MHz	傳導限制值(dBuV)	
	準尖峰值	平均值
0.15 - 0.50	66-56 _(註)	56-46 _(註)
0.50-5.0	56	46
5.0 - 30	60	50


註:隨頻率之對數遞減

5.1.3 測試架構圖



5.1.4 電源端點測試結果

EUT	Game Console	Date of Test	2021-04-06
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	25.3°C / 62%
Polarity	Line1	Site / Test Engineer	SR2 / Jay
Test Mode	802.11n-20_TX_CH6_ANT 0+1	Test Voltage	AC 110V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	*	0.154	41.96	9.61	51.57	-14.19	65.75	QP
2	*	0.154	23.20	9.61	32.81	-22.95	55.75	Average
3		0.177	37.17	9.61	46.79	-17.84	64.63	QP
4		0.177	19.91	9.61	29.52	-25.10	54.63	Average
5		0.469	22.51	9.63	32.13	-24.39	56.52	QP
6	*	0.469	20.16	9.63	29.79	-16.74	46.52	Average
7		1.617	16.30	9.68	25.98	-30.02	56.00	QP
8		1.617	13.84	9.68	23.52	-22.48	46.00	Average
9		4.722	22.08	9.73	31.81	-24.19	56.00	QP
10		4.722	14.54	9.73	24.28	-21.72	46.00	Average
11		6.724	25.31	9.79	35.10	-24.90	60.00	QP
12		6.724	19.71	9.79	29.50	-20.50	50.00	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	Game Console	Date of Test	2021-04-06
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	25.3°C /62%
Polarity	Neutral	Site / Test Engineer	SR2 / Jay
Test Mode	802.11n-20_TX_CH6_ANT 0+1	Test Voltage	AC 110V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.172	35.31	9.62	44.93	-19.91	64.84	QP
2	0.172	18.06	9.62	27.68	-27.16	54.84	Average
3	* 0.186	37.46	9.62	47.08	-17.13	64.21	QP
4	* 0.186	20.92	9.62	30.54	-23.67	54.21	Average
5	0.217	32.55	9.62	42.17	-20.74	62.91	QP
6	0.217	17.43	9.62	27.06	-25.86	52.91	Average
7	0.352	24.75	9.63	34.38	-24.53	58.90	QP
8	0.352	16.14	9.63	25.77	-23.14	48.90	Average
9	5.068	20.99	9.75	30.74	-29.26	60.00	QP
10	5.068	15.47	9.75	25.22	-24.78	50.00	Average
11	6.719	28.06	9.80	37.86	-22.14	60.00	QP
12	* 6.719	23.15	9.80	32.94	-17.06	50.00	Average

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

5.2 峰值傳導輸出功率

5.2.1 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀RF輸入端，設定頻譜分析儀之解析度頻寬大於6dB發射頻寬或使用峰值功率表。除使用上述測量方式外，並得使用以最大傳導輸出功率作為測量方式。


5.2.2 限制要求

操作於2400-2483.5 MHz之跳頻或數位調變的發射器材與5725-5850 MHz之跳頻發射器材：1W(含)以下，當跳頻系統符合國家通訊傳播委員會低功率射頻器材技術規範之第4.10.1.6(1)(A)(a)節，其限制值為0.125 W(含)以下。

若用於非固定式點對點操作時，若其發射天線之方向性增益超過6dBi，應依所超過之dB數等量降低峰值輸出功率。如用於固定式點對點(註)操作時，應符合下列情形之一：

- (1)操作於2400-2483.5兆赫(MHz)者，其發射天線之方向性增益超過6dBi，應於每超過3dB降低1dB之峰值輸出功率。
- (2) 操作於5725-5850兆赫(MHz)者，其發射天線之方向性增益超過6dBi，不需降低峰值輸出功率。

5.2.3 測試架構圖



5.2.4 峰值傳導輸出功率測試結果

待測物名稱	Game Console	測試日期	2021/3/30
待測物型號	HEG-001	溫度 / 濕度	23°C / 55%
測試場地 / 測試工程師	SR2 / Eric		

2.4GHz 802.11b RF Output Power (dBm) Antenna A (SISO)

Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit
		1	2	5.5	11		
01	2412	13.73	--	--	--	17.62	30 dBm
06	2437	13.68	13.52	13.48	13.37	17.25	30 dBm
11	2462	13.66	--	--	--	17.24	30 dBm
12	2467	8.65	--	--	--	12.25	30 dBm
13	2472	3.74	--	--	--	7.53	30 dBm

2.4GHz 802.11g RF Output Power (dBm) Antenna A (SISO)

Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		6	9	12	18	24	36	48	54		
01	2412	13.68	--	--	--	--	--	--	--	21.04	30 dBm
06	2437	13.63	13.56	13.44	13.25	13.12	12.85	12.54	12.26	21.12	30 dBm
11	2462	13.80	--	--	--	--	--	--	--	20.99	30 dBm
12	2467	8.73	--	--	--	--	--	--	--	15.95	30 dBm
13	2472	3.65	--	--	--	--	--	--	--	11.56	30 dBm

備註： 1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

2.4GHz 802.11n-20M RF Output Power (dBm) Antenna A (SISO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
01	2412	13.70	--	--	--	--	--	--	--	21.00	30 dBm
06	2437	13.61	13.52	13.46	13.02	12.74	12.68	12.55	12.04	20.88	30 dBm
11	2462	13.65	--	--	--	--	--	--	--	21.14	30 dBm
12	2467	8.63	--	--	--	--	--	--	--	15.82	30 dBm
13	2472	3.54	--	--	--	--	--	--	--	11.54	30 dBm
2.4GHz 802.11n-20M RF Output Power (dBm) Antenna B (SISO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
01	2412	13.62	--	--	--	--	--	--	--	20.84	30 dBm
06	2437	13.66	13.53	13.49	13.12	12.68	12.52	12.35	12.04	21.00	30 dBm
11	2462	13.70	--	--	--	--	--	--	--	20.99	30 dBm
12	2467	8.70	--	--	--	--	--	--	--	16.06	30 dBm
13	2472	3.66	--	--	--	--	--	--	--	11.94	30 dBm

備註： 1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

2.4GHz 802.11n-40M RF Output Power (dBm) Antenna A (SISO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
03	2422	8.95	--	--	--	--	--	--	--	16.12	30 dBm
06	2437	8.92	7.86	7.52	7.26	6.78	6.62	6.43	6.06	16.26	30 dBm
09	2452	8.88	--	--	--	--	--	--	--	15.76	30 dBm
10	2457	8.87	--	--	--	--	--	--	--	15.85	30 dBm
11	2462	8.60	--	--	--	--	--	--	--	15.69	30 dBm
2.4GHz 802.11n-40M RF Output Power (dBm) Antenna B (SISO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
03	2422	8.85	--	--	--	--	--	--	--	16.41	30 dBm
06	2437	8.84	7.78	7.61	7.36	6.81	6.78	6.33	6.23	16.03	30 dBm
09	2452	8.80	--	--	--	--	--	--	--	15.65	30 dBm
10	2457	8.88	--	--	--	--	--	--	--	16.35	30 dBm
11	2462	8.93	--	--	--	--	--	--	--	16.26	30 dBm

備註： 1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

2.4GHz 802.11n-20M RF Output Power (dBm) Antenna A (MIMO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15		
01	2412	12.42	--	--	--	--	--	--	--	19.13	30 dBm
06	2437	12.18	11.95	11.62	10.86	10.34	10.23	9.85	9.66	19.07	30 dBm
11	2462	12.11	--	--	--	--	--	--	--	18.43	30 dBm
12	2467	8.56	--	--	--	--	--	--	--	16.21	30 dBm
13	2472	3.62	--	--	--	--	--	--	--	12.21	30 dBm
2.4GHz 802.11n-20M RF Output Power (dBm) Antenna B (MIMO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15		
01	2412	12.36	--	--	--	--	--	--	--	19.16	30 dBm
06	2437	12.53	11.97	11.75	10.97	10.65	10.32	10.03	9.91	19.67	30 dBm
11	2462	12.46	--	--	--	--	--	--	--	18.86	30 dBm
12	2467	8.79	--	--	--	--	--	--	--	16.32	30 dBm
13	2472	3.64	--	--	--	--	--	--	--	11.97	30 dBm
2.4GHz 802.11n-20M RF Output Power (dBm) Antenna A+B (MIMO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15		
01	2412	15.40	--	--	--	--	--	--	--	22.16	30 dBm
06	2437	15.37	14.97	14.70	13.93	13.51	13.29	12.95	12.80	22.39	30 dBm
11	2462	15.30	--	--	--	--	--	--	--	21.66	30 dBm
12	2467	11.69	--	--	--	--	--	--	--	19.28	30 dBm
13	2472	6.64	--	--	--	--	--	--	--	15.10	30 dBm

備註：1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

2.4GHz 802.11n-40M RF Output Power (dBm) Antenna A (MIMO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15		
03	2422	9.10	--	--	--	--	--	--	--	16.04	30 dBm
06	2437	8.85	7.79	7.53	6.68	5.98	5.96	5.94	5.93	15.68	30 dBm
09	2452	8.90	--	--	--	--	--	--	--	15.92	30 dBm
10	2457	8.88	--	--	--	--	--	--	--	15.48	30 dBm
11	2462	8.69	--	--	--	--	--	--	--	15.66	30 dBm
2.4GHz 802.11n-40M RF Output Power (dBm) Antenna B (MIMO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15		
03	2422	8.98	--	--	--	--	--	--	--	15.81	30 dBm
06	2437	8.94	7.77	7.65	6.89	6.06	5.98	5.67	5.50	16.19	30 dBm
09	2452	9.01	--	--	--	--	--	--	--	15.89	30 dBm
10	2457	9.11	--	--	--	--	--	--	--	16.08	30 dBm
11	2462	9.01	--	--	--	--	--	--	--	16.27	30 dBm
2.4GHz 802.11n-40M RF Output Power (dBm) Antenna A+B (MIMO)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15		
03	2422	12.05	--	--	--	--	--	--	--	18.94	30 dBm
06	2437	11.91	10.79	10.60	9.80	9.03	8.98	8.82	8.73	18.95	30 dBm
09	2452	11.97	--	--	--	--	--	--	--	18.92	30 dBm
10	2457	12.01	--	--	--	--	--	--	--	18.80	30 dBm
11	2462	11.86	--	--	--	--	--	--	--	18.99	30 dBm

備註： 1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

2.4GHz 802.11VHT-20M RF Output Power (dBm) Antenna A (SISO)												
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)									Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8		
01	2412	12.22	--	--	--	--	--	--	--	--	19.41	30 dBm
06	2437	12.22	12.13	11.98	11.93	11.89	11.86	11.85	11.83	11.82	19.19	30 dBm
11	2462	12.48	--	--	--	--	--	--	--	--	19.74	30 dBm
12	2467	7.52	--	--	--	--	--	--	--	--	14.66	30 dBm
13	2472	2.34	--	--	--	--	--	--	--	--	10.13	30 dBm
2.4GHz 802.11VHT-20M RF Output Power (dBm) Antenna B (SISO)												
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)									Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8		
01	2412	12.92	--	--	--	--	--	--	--	--	19.58	30 dBm
06	2437	13.08	13.03	12.96	12.90	11.81	11.64	11.55	11.48	11.42	20.07	30 dBm
11	2462	12.56	--	--	--	--	--	--	--	--	19.65	30 dBm
12	2467	7.82	--	--	--	--	--	--	--	--	15.18	30 dBm
13	2472	2.85	--	--	--	--	--	--	--	--	10.62	30 dBm

備 註： 1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

2.4GHz 802.11VHT-40M RF Output Power (dBm) Antenna A (SISO)													
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)										Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9		
03	2422	7.50	--	--	--	--	--	--	--	--	--	14.98	30 dBm
06	2437	7.39	7.37	7.33	7.08	5.68	5.42	5.19	5.03	4.90	4.85	15.54	30 dBm
09	2452	6.89	--	--	--	--	--	--	--	--	--	15.11	30 dBm
10	2457	7.06	--	--	--	--	--	--	--	--	--	14.92	30 dBm
11	2462	6.96	--	--	--	--	--	--	--	--	--	14.95	30 dBm
2.4GHz 802.11VHT-40M RF Output Power (dBm) Antenna B (SISO)													
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)										Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9		
03	2422	7.62	--	--	--	--	--	--	--	--	--	15.83	30 dBm
06	2437	7.40	7.37	7.29	7.25	6.22	5.92	5.74	5.42	5.33	5.15	15.59	30 dBm
09	2452	7.23	--	--	--	--	--	--	--	--	--	13.77	30 dBm
10	2457	7.36	--	--	--	--	--	--	--	--	--	14.99	30 dBm
11	2462	7.34	--	--	--	--	--	--	--	--	--	14.84	30 dBm

備註： 1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

2.4GHz 802.11VHT-20M RF Output Power (dBm) Antenna A (MIMO)												
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)									Peak Power	Required Limit
		2-MCS0	2-MCS1	2-MCS2	2-MCS3	2-MCS4	2-MCS5	2-MCS6	2-MCS7	2-MCS8		
01	2412	12.33	--	--	--	--	--	--	--	--	18.52	30 dBm
06	2437	12.00	11.80	11.23	10.64	10.09	9.74	9.36	9.11	8.80	18.73	30 dBm
11	2462	11.93	--	--	--	--	--	--	--	--	18.30	30 dBm
12	2467	7.92	--	--	--	--	--	--	--	--	16.19	30 dBm
13	2472	0.94	--	--	--	--	--	--	--	--	12.05	30 dBm
2.4GHz 802.11VHT-20M RF Output Power (dBm) Antenna B (MIMO)												
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)									Peak Power	Required Limit
		2-MCS0	2-MCS1	2-MCS2	2-MCS3	2-MCS4	2-MCS5	2-MCS6	2-MCS7	2-MCS8		
01	2412	11.89	--	--	--	--	--	--	--	--	18.81	30 dBm
06	2437	12.13	11.40	10.85	10.42	10.07	9.91	9.68	9.43	9.09	19.09	30 dBm
11	2462	11.74	--	--	--	--	--	--	--	--	18.83	30 dBm
12	2467	7.50	--	--	--	--	--	--	--	--	15.07	30 dBm
13	2472	2.42	--	--	--	--	--	--	--	--	11.46	30 dBm
2.4GHz 802.11VHT-20M RF Output Power (dBm) Antenna A+B (MIMO)												
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)									Peak Power	Required Limit
		2-MCS0	2-MCS1	2-MCS2	2-MCS3	2-MCS4	2-MCS5	2-MCS6	2-MCS7	2-MCS8		
01	2412	15.13	--	--	--	--	--	--	--	--	21.68	30 dBm
06	2437	15.08	14.61	14.05	13.54	13.09	12.84	12.53	12.28	11.96	21.92	30 dBm
11	2462	14.85	--	--	--	--	--	--	--	--	21.58	30 dBm
12	2467	10.73	--	--	--	--	--	--	--	--	18.68	30 dBm
13	2472	4.75	--	--	--	--	--	--	--	--	14.78	30 dBm

備註： 1. 此項量測係採 Power Meter。

2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)


2.4GHz 802.11VHT-40M RF Output Power (dBm) Antenna A (MIMO)													
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)										Peak Power	Required Limit
		2-MCS0	2-MCS1	2-MCS2	2-MCS3	2-MCS4	2-MCS5	2-MCS6	2-MCS7	2-MCS8	2-MCS9	2-MCS0	
03	2422	7.57	--	--	--	--	--	--	--	--	--	15.69	30 dBm
06	2437	7.69	6.88	6.07	5.12	4.80	4.64	4.51	4.39	4.19	4.04	14.78	30 dBm
09	2452	7.53	--	--	--	--	--	--	--	--	--	14.56	30 dBm
10	2457	7.36	--	--	--	--	--	--	--	--	--	14.25	30 dBm
11	2462	7.19	--	--	--	--	--	--	--	--	--	14.22	30 dBm
2.4GHz 802.11VHT-40M RF Output Power (dBm) Antenna B (MIMO)													
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)										Peak Power	Required Limit
		2-MCS0	2-MCS1	2-MCS2	2-MCS3	2-MCS4	2-MCS5	2-MCS6	2-MCS7	2-MCS8	2-MCS9	2-MCS0	
03	2422	7.60	--	--	--	--	--	--	--	--	--	14.44	30 dBm
06	2437	7.69	6.74	6.37	5.98	5.30	5.04	4.82	4.50	4.25	4.07	15.61	30 dBm
09	2452	6.92	--	--	--	--	--	--	--	--	--	15.48	30 dBm
10	2457	7.09	--	--	--	--	--	--	--	--	--	15.52	30 dBm
11	2462	6.96	--	--	--	--	--	--	--	--	--	15.40	30 dBm
2.4GHz 802.11VHT-40M RF Output Power (dBm) Antenna A+B (MIMO)													
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)										Peak Power	Required Limit
		2-MCS0	2-MCS1	2-MCS2	2-MCS3	2-MCS4	2-MCS5	2-MCS6	2-MCS7	2-MCS8	2-MCS9	2-MCS0	
03	2422	10.60	--	--	--	--	--	--	--	--	--	18.12	30 dBm
06	2437	10.70	9.82	9.23	8.58	8.07	7.85	7.68	7.46	7.23	7.07	18.23	30 dBm
09	2452	10.25	--	--	--	--	--	--	--	--	--	18.05	30 dBm
10	2457	10.24	--	--	--	--	--	--	--	--	--	17.94	30 dBm
11	2462	10.09	--	--	--	--	--	--	--	--	--	17.86	30 dBm

備註： 1. 此項量測係採 Power Meter。


2. 此量測值已含工作週期因子及線材損耗(Cable Loss=1dB)

Antenna Port A (SISO)


802.11 b CH01 (2412MHz) (1Mbps)




802.11 b CH06 (2437MHz) (1Mbps)




802.11 b CH11 (2462MHz) (1Mbps)




802.11 b CH12 (2467MHz) (1Mbps)




802.11 b CH13 (2472MHz) (1Mbps)




802.11 g CH01 (2412MHz) (6Mbps)




802.11 g CH06 (2437MHz) (6Mbps)




802.11 g CH11 (2462MHz) (6Mbps)




802.11 g CH12 (2467MHz) (6Mbps)




802.11 g CH13 (2472MHz) (6Mbps)




802.11 n20 CH01 (2412MHz) (MCS0)




802.11 n20 CH06 (2437MHz) (MCS0)




802.11 n20 CH11 (2462MHz) (MCS0)




802.11 n20 CH12 (2467MHz) (MCS0)




802.11 n20 CH13 (2472MHz) (MCS0)




802.11 n40 CH03 (2422MHz) (MCS0)




802.11 n40 CH06 (2437MHz) (MCS0)




802.11 n40 CH09 (2452MHz) (MCS0)




802.11 n40 CH10 (2457MHz) (MCS0)



802.11 n40 CH11 (2462MHz) (MCS0)




802.11 ac20 CH01 (2412MHz) (MCS0)



802.11 ac20 CH06 (2437MHz) (MCS0)




802.11 ac20 CH11 (2462MHz) (MCS0)




802.11 ac20 CH12 (2467MHz) (MCS0)




802.11 ac20 CH13 (2472MHz) (MCS0)




802.11 ac40 CH03 (2422MHz) (MCS0)




802.11 ac40 CH06 (2437MHz) (MCS0)




802.11 ac40 CH09 (2452MHz) (MCS0)



802.11 ac40 CH10 (2457MHz) (MCS0)




802.11 ac40 CH11 (2462MHz) (MCS0)




Antenna Port B (SISO)


802.11 b CH01 (2412MHz) (1Mbps)




802.11 b CH06 (2437MHz) (1Mbps)




802.11 b CH11 (2462MHz) (1Mbps)




802.11 b CH12 (2467MHz) (1Mbps)




802.11 b CH13 (2472MHz) (1Mbps)




802.11 g CH01 (2412MHz) (6Mbps)




802.11 g CH06 (2437MHz) (6Mbps)




802.11 g CH11 (2462MHz) (6Mbps)




802.11 g CH12 (2467MHz) (6Mbps)




802.11 g CH13 (2472MHz) (6Mbps)




802.11 n20 CH01 (2412MHz) (MCS0)




802.11 n20 CH06 (2437MHz) (MCS0)




802.11 n20 CH11 (2462MHz) (MCS0)




802.11 n20 CH12 (2467MHz) (MCS0)




802.11 n20 CH13 (2472MHz) (MCS0)




802.11 n40 CH03 (2422MHz) (MCS0)




802.11 n40 CH06 (2437MHz) (MCS0)




802.11 n40 CH09 (2452MHz) (MCS0)




802.11 n40 CH10 (2457MHz) (MCS0)




802.11 n40 CH11 (2462MHz) (MCS0)



802.11 ac20 CH01 (2412MHz) (MCS0)




802.11 ac20 CH06 (2437MHz) (MCS0)




802.11 ac20 CH11 (2462MHz) (MCS0)




802.11 ac20 CH12 (2467MHz) (MCS0)




802.11 ac20 CH13 (2472MHz) (MCS0)




802.11 ac40 CH03 (2422MHz) (MCS0)




802.11 ac40 CH06 (2437MHz) (MCS0)




802.11 ac40 CH09 (2452MHz) (MCS0)



802.11 ac40 CH10 (2457MHz) (MCS0)




802.11 ac40 CH11 (2462MHz) (MCS0)




Antenna Port A (MIMO)


802.11 n20 CH01 (2412MHz) (MCS8)




802.11 n20 CH06 (2437MHz) (MCS8)




802.11 n20 CH11 (2462MHz) (MCS8)




802.11 n20 CH12 (2467MHz) (MCS8)




802.11 n20 CH13 (2472MHz) (MCS8)




802.11 n40 CH03 (2422MHz) (MCS8)




802.11 n40 CH06 (2437MHz) (MCS8)




802.11 n40 CH09 (2452MHz) (MCS8)




802.11 n40 CH10 (2457MHz) (MCS8)




802.11 n40 CH11 (2462MHz) (MCS8)




802.11 ac20 CH01 (2412MHz) (MCS0)




802.11 ac20 CH06 (2437MHz) (MCS0)




802.11 ac20 CH11 (2462MHz) (MCS0)




802.11 ac20 CH12 (2467MHz) (MCS0)




802.11 ac20 CH13 (2472MHz) (MCS0)




802.11 ac40 CH03 (2422MHz) (MCS0)




802.11 ac40 CH06 (2437MHz) (MCS0)




802.11 ac40 CH09 (2452MHz) (MCS0)



802.11 ac40 CH10 (2457MHz) (MCS0)




802.11 ac40 CH11 (2462MHz) (MCS0)




Antenna Port B (MIMO)


802.11 n20 CH01 (2412MHz) (MCS8)




802.11 n20 CH06 (2437MHz) (MCS8)




802.11 n20 CH11 (2462MHz) (MCS8)




802.11 n20 CH12 (2467MHz) (MCS8)




802.11 n20 CH13 (2472MHz) (MCS8)




802.11 n40 CH03 (2422MHz) (MCS8)




802.11 n40 CH06 (2437MHz) (MCS8)




802.11 n40 CH09 (2452MHz) (MCS8)




802.11 n40 CH10 (2457MHz) (MCS8)




802.11 n40 CH11 (2462MHz) (MCS8)




802.11 ac20 CH01 (2412MHz) (MCS0)




802.11 ac20 CH06 (2437MHz) (MCS0)




802.11 ac20 CH11 (2462MHz) (MCS0)




802.11 ac20 CH12 (2467MHz) (MCS0)




802.11 ac20 CH13 (2472MHz) (MCS0)




802.11 ac40 CH03 (2422MHz) (MCS0)




802.11 ac40 CH06 (2437MHz) (MCS0)



802.11 ac40 CH09 (2452MHz) (MCS0)



802.11 ac40 CH10 (2457MHz) (MCS0)



802.11 ac40 CH11 (2462MHz) (MCS0)



5.3 天線之要求

5.3.1 限制要求

依據國家通訊傳播委員會低功率射頻器材技術規範之第4.10.1.4節規定，天線之規格可不受下述規定之限制。

低功率射頻器材之發射機或收發信機所使用之天線，應為全固定、半固定式或以獨特之耦合(unique coupling)方式連接機體。製造者可設計供使用者因損壞而替換之天線，但不得設計或使用原認證以外之天線或可供引接各類電纜之標準天線插座或電氣連接頭，如：BNC、F type、N type、M type、UG type、RCA、SMA、SMB...等及其他各類工業或通訊標準接頭。

5.3.2 天線樣式

此 Game Console 其天線為 FPCB Antenna Type，(檢附天線規格書)

Antenna List

Antenna 0

No.	Brand	Part No.	Peak Gain
1	Nintendo	107000100164	0.30dBi

Antenna 1

No.	Brand	Part No.	Peak Gain
1	Nintendo	107000100165	0.19dBi

5.4 帶外發射限制

5.4.1 量測方法

待測物之天線埠經由適當之衰減直接連至頻譜分析儀 RF 輸入端，


- (1) 頻率掃描範圍足以檢測頻帶內的發射波峰位準以及由受測物產生之最低頻率到第 10 次諧波的所有混附發射，通常需要分幾段以涵蓋全部頻率範圍。
- (2) 解析頻寬為 100 kHz，視訊頻寬不小於解析頻寬。
- (3) 掃描時間為自動，檢波功能為峰值，訊號軌跡為最大保留(Max Hold)
- (4) 將標記設定於任何欲紀錄之波峰上，所顯示之位準值必須符合指定之限制值。

5.4.2 限制要求

使用頻帶範圍外之任意 100 千赫 (kHz)內，發射器所產生的射頻功率相較於使用頻帶範圍中包含最高所需功率之 100 千赫 (kHz)內的射頻功率，衰減值限制如下：

- (1)輸出功率以低功率射頻器材技術規範附件二之峰值輸出功率方式量測者，至少須衰減 20 dB，可使用射頻傳導或輻射方式測量。
- (2)輸出功率以數位調變技術系統之最大傳導輸出功率量測方式者，至少須衰減 30 dB。
- (3)若落於禁用頻段之輻射發射，應符合低功率射頻器材技術規範第 3.6 節之規定。

5.4.3 測試架構圖



5.4.4 帶外輻射測試結果

Test Mode	Channel No.	Frequency (MHz)	Limit	Result
Antenna A (SISO)				
802.11b	01	2412	20dBc	Pass
	06	2437	20dBc	Pass
	11	2462	20dBc	Pass
	12	2467	20dBc	Pass
	13	2472	20dBc	Pass
802.11g	01	2412	20dBc	Pass
	06	2437	20dBc	Pass
	11	2462	20dBc	Pass
	12	2467	20dBc	Pass
	13	2472	20dBc	Pass

Test Mode	Channel No.	Frequency (MHz)	Limit	Result
Antenna A (MIMO)				
802.11n-20M	01	2412	20dBc	Pass
	06	2437	20dBc	Pass
	11	2462	20dBc	Pass
	12	2467	20dBc	Pass
	13	2472	20dBc	Pass
802.11n-40M	03	2422	20dBc	Pass
	06	2437	20dBc	Pass
	09	2452	20dBc	Pass
	10	2457	20dBc	Pass
	11	2462	20dBc	Pass


Test Mode	Channel No.	Frequency (MHz)	Limit	Result
Antenna B (MIMO)				
802.11n-20M	01	2412	20dBc	Pass
	06	2437	20dBc	Pass
	11	2462	20dBc	Pass
	12	2467	20dBc	Pass
	13	2472	20dBc	Pass
802.11n-40M	03	2422	20dBc	Pass
	06	2437	20dBc	Pass
	09	2452	20dBc	Pass
	10	2457	20dBc	Pass
	11	2462	20dBc	Pass

Antenna A (SISO)


802.11 b CH01 (2412MHz)




802.11 b CH01 (2412MHz)



802.11 b CH01 (2412MHz)




802.11 b CH01 (2412MHz)




802.11 b CH06 (2437MHz)




802.11 b CH06 (2437MHz)



802.11 b CH06 (2437MHz)




802.11 b CH06 (2437MHz)




802.11 b CH11 (2462MHz)




802.11 b CH11 (2462MHz)




802.11 b CH11 (2462MHz)



802.11 b CH11 (2462MHz)




802.11 b CH12 (2467MHz)



802.11 b CH12 (2467MHz)




802.11 b CH12 (2467MHz)




802.11 b CH12 (2467MHz)




802.11 b CH13 (2472MHz)




802.11 b CH13 (2472MHz)



802.11 b CH13 (2472MHz)




802.11 b CH13 (2472MHz)




802.11 g CH01 (2412MHz)




802.11 g CH01 (2412MHz)



802.11 g CH01 (2412MHz)



802.11 g CH01 (2412MHz)




802.11 g CH06 (2437MHz)




802.11 g CH06 (2437MHz)



802.11 g CH06 (2437MHz)




802.11 g CH06 (2437MHz)




802.11 g CH11 (2462MHz)




802.11 g CH11 (2462MHz)



802.11 g CH11 (2462MHz)




802.11 g CH11 (2462MHz)




802.11 g CH12 (2467MHz)



802.11 g CH12 (2467MHz)



802.11 g CH12 (2467MHz)




802.11 g CH12 (2467MHz)




802.11 g CH13 (2472MHz)




802.11 g CH13 (2472MHz)



802.11 g CH13 (2472MHz)



802.11 g CH13 (2472MHz)




Antenna A (MIMO)


802.11 n-20M CH01 (2412MHz) (MIMO)



802.11 n-20M CH01 (2412MHz) (MIMO)



802.11 n-20M CH01 (2412MHz) (MIMO)




802.11 n-20M CH01 (2412MHz) (MIMO)




802.11 n-20M CH06 (2437MHz) (MIMO)




802.11 n-20M CH06 (2437MHz) (MIMO)



802.11 n-20M CH06 (2437MHz) (MIMO)




802.11 n-20M CH06 (2437MHz) (MIMO)



802.11 n-20M CH11 (2462MHz) (MIMO)




802.11 n-20M CH11 (2462MHz) (MIMO)



802.11 n-20M CH11 (2462MHz) (MIMO)




802.11 n-20M CH11 (2462MHz) (MIMO)




802.11 n-20M CH12 (2467MHz) (MIMO)




802.11 n-20M CH12 (2467MHz) (MIMO)



802.11 n-20M CH12 (2467MHz) (MIMO)



802.11 n-20M CH12 (2467MHz) (MIMO)




802.11 n-20M CH13 (2472MHz) (MIMO)



802.11 n-20M CH13 (2472MHz) (MIMO)






Antenna B (MIMO)


802.11 n-20M CH01 (2412MHz) (MIMO)



802.11 n-20M CH01 (2412MHz) (MIMO)



802.11 n-20M CH01 (2412MHz) (MIMO)



802.11 n-20M CH01 (2412MHz) (MIMO)



802.11 n-20M CH06 (2437MHz) (MIMO)




802.11 n-20M CH06 (2437MHz) (MIMO)



802.11 n-20M CH06 (2437MHz) (MIMO)




802.11 n-20M CH06 (2437MHz) (MIMO)




802.11 n-20M CH11 (2462MHz) (MIMO)



802.11 n-20M CH11 (2462MHz) (MIMO)






802.11 n-20M CH11 (2462MHz) (MIMO)



802.11 n-20M CH11 (2462MHz) (MIMO)







5.5 輻射電場強度

5.5.1 量測方法

待測物置於非導體桌面（落地型產品置於地上），受測物使用交流電源時，將其與任何配件設備之電源線連接至位於旋轉桌的交流電源。受測物使用電池時，測試時應裝置新電池或充電完全的電池。受測物與配件設備之電源線無須束綁，桌面上受測設備的所有電源線由桌子的後緣垂下沿旋轉桌表面接至交流插座。落地型設備的交流電源線可以方便的型態走線。桌面可 360 度旋轉，接收天線置於距待測物 3m 距離，高度可在 1 至 4 公尺間變動，以量測待測物之最大輻射電場強度，接收天線並應於水平及垂直極化方向各量測一次。（待測物擺設方式根據 ANSI C63.10-2013 版本，待測物放置桌中心，1G 以下擺設高度為 80cm/1G 以上擺設高度為 150cm）

- (1) 任一頻率小於或等於 1000 MHz 之訊號,使用 CISPR 準峰值檢波器
- (2) 任一頻率大於 1000 MHz 之訊號，使用平均值檢波器測量，當規定之發射限制值為平均值時(含 1000 MHz 以下)，受測訊號藉由峰值檢波器(RBW:1MHz,VBW:3MHz)所測量之峰值，亦須符合峰值發射限制值，其峰值發射限制值為最大容許平均值加 20 dB。

5.5.2 限制要求


其電場強度不得超過下表之限值，且其不必要之發射皆不得大於主波發射強度。各頻段重疊處，以較嚴格之限制值為準。

頻率(f) (MHz)	電場強度 (微伏特/公尺, $\mu\text{V/m}$)	測距 (公尺)
$0.009 \leq f \leq 0.490$	$2400/f(\text{kHz})$	300
$0.490 < f \leq 1.705$	$24000/f(\text{kHz})$	30
$1.705 < f < 30$	30	30
$30 \leq f \leq 88$	100	3
$88 < f \leq 216$	150	3
$216 < f \leq 960$	200	3
$960 < f$	500	3


上表規定之電場強度，發射頻率在 9 kHz~90 kHz、110 kHz~490 kHz 及 1000MHz 以上者，其量測應以平均值檢波器為基準，且須符合低功率射頻器材技術規範第 6.14.節之規定；其他發射頻率，應以 CISPR 準峰值(quasi-peak) 檢波器測量；非以上表所指定之距離測量時，應符合第 6.5 節之規定，而輻射發射之量測頻率範圍須符合低功率射頻器材技術規範第 6.12 節之規定。

5.5.3 測試架構圖


Under 30MHz Test




Under 1GHz Test Setup



1GHz ~ 18GHz Test Setup:




18GHz ~ 25GHz Test Setup:



5.5.4 輻射電場強度測試結果

EUT	Game Console	Date of Test	2021-04-15
Factor	VULB 9162	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	43.550	1.19	21.59	22.78	-17.22	40.00	100	150	QP
2	135.740	8.18	16.14	24.32	-19.18	43.50	100	265	QP
3	211.260	4.93	18.84	23.77	-19.73	43.50	100	140	QP
4	314.980	6.29	22.02	28.30	-17.70	46.00	100	75	QP
5	599.390	4.63	27.79	32.42	-13.58	46.00	100	235	QP
6 *	872.410	3.43	31.61	35.04	-10.96	46.00	100	300	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-15
Factor	VULB 9162	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 32.510	14.89	18.86	33.75	-6.25	40.00	100	225	QP
2	44.190	3.08	21.68	24.77	-15.23	40.00	100	350	QP
3	73.360	9.73	16.09	25.82	-14.18	40.00	100	235	QP
4	149.240	13.31	15.98	29.29	-14.21	43.50	100	60	QP
5	599.590	5.91	27.79	33.71	-12.29	46.00	100	170	QP
6	730.630	2.74	29.80	32.55	-13.45	46.00	100	120	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-15
Factor	VULB 9162	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_RX_CH 6_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	51.840	1.87	21.71	23.58	-16.42	40.00	100	335	QP
2	139.190	7.89	16.05	23.94	-19.56	43.50	100	260	QP
3	216.230	4.16	19.06	23.22	-22.78	46.00	100	145	QP
4	367.570	3.19	23.52	26.71	-19.29	46.00	100	80	QP
5	* 599.290	8.07	27.79	35.86	-10.14	46.00	100	190	QP
6	806.070	1.10	30.62	31.72	-14.28	46.00	100	255	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-15
Factor	VULB 9162	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_RX_CH 6_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 32.250	13.62	18.81	32.44	-7.56	40.00	100	160	QP
2	44.140	4.38	21.68	26.06	-13.94	40.00	100	55	QP
3	73.860	8.63	15.96	24.59	-15.41	40.00	100	240	QP
4	150.970	12.86	16.01	28.86	-14.64	43.50	100	325	QP
5	599.340	6.40	27.79	34.19	-11.81	46.00	100	330	QP
6	729.650	2.05	29.79	31.84	-14.16	46.00	100	160	QP

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4824.000	47.76	3.33	51.09	-22.91	74.00	150	360	Peak
2	7236.000	37.01	10.97	47.98	-26.02	74.00	150	360	Peak
3	9648.000	30.14	14.70	44.84	-29.16	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	42.80	3.33	46.13	-27.87	74.00	150	360	Peak
2	* 7236.000	35.35	10.97	46.32	-27.68	74.00	150	360	Peak
3	9648.000	30.49	14.70	45.19	-28.81	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4874.000	48.00	3.45	51.45	-22.55	74.00	150	360	Peak
2	7311.000	32.89	11.18	44.07	-29.93	74.00	150	360	Peak
3	9748.000	31.43	14.89	46.32	-27.68	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4874.000	42.99	3.45	46.44	-27.56	74.00	150	360	Peak
2	7311.000	31.97	11.18	43.15	-30.85	74.00	150	360	Peak
3	9748.000	30.73	14.89	45.62	-28.38	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4924.000	47.38	3.57	50.94	-23.06	74.00	150	360	Peak
2	7386.000	32.94	11.39	44.33	-29.67	74.00	150	360	Peak
3	9848.000	32.27	15.07	47.34	-26.66	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	41.72	3.57	45.29	-28.71	74.00	150	360	Peak
2	7386.000	31.81	11.39	43.21	-30.79	74.00	150	360	Peak
3	* 9848.000	31.09	15.07	46.17	-27.83	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4934.000	41.80	3.59	45.39	-28.61	74.00	150	360	Peak
2	7401.000	31.02	11.43	42.46	-31.54	74.00	150	360	Peak
3	* 9868.000	31.93	15.11	47.04	-26.96	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4934.000	38.42	3.59	42.01	-31.99	74.00	150	360	Peak
2	7401.000	31.44	11.43	42.87	-31.13	74.00	150	360	Peak
3	* 9868.000	31.99	15.11	47.11	-26.89	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4944.000	36.49	3.62	40.10	-33.90	74.00	150	360	Peak
2	7416.000	32.06	11.48	43.54	-30.46	74.00	150	360	Peak
3	* 9888.000	31.80	15.15	46.94	-27.06	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4944.000	35.45	3.62	39.07	-34.93	74.00	150	360	Peak
2	7416.000	31.39	11.48	42.87	-31.13	74.00	150	360	Peak
3	* 9888.000	32.25	15.15	47.40	-26.60	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4824.000	45.73	3.33	49.06	-24.94	74.00	150	360	Peak
2	7326.000	32.23	11.22	43.46	-30.54	74.00	150	360	Peak
3	9648.000	31.76	14.70	46.46	-27.54	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	39.52	3.33	42.84	-31.16	74.00	150	360	Peak
2	7236.000	33.50	10.97	44.46	-29.54	74.00	150	360	Peak
3	* 9648.000	29.89	14.70	44.58	-29.42	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4874.000	45.07	3.45	48.52	-25.48	74.00	150	360	Peak
2	7311.000	32.92	11.18	44.10	-29.90	74.00	150	360	Peak
3	9748.000	31.49	14.89	46.38	-27.62	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	39.86	3.45	43.30	-30.70	74.00	150	360	Peak
2	7311.000	32.59	11.18	43.77	-30.23	74.00	150	360	Peak
3	* 9748.000	30.84	14.89	45.72	-28.28	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4924.000	45.91	3.57	49.48	-24.52	74.00	150	360	Peak
2	7386.000	32.56	11.39	43.95	-30.05	74.00	150	360	Peak
3	9848.000	31.41	15.07	46.48	-27.52	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	39.48	3.57	43.04	-30.96	74.00	150	360	Peak
2	7386.000	33.69	11.39	45.09	-28.91	74.00	150	360	Peak
3	* 9848.000	31.58	15.07	46.65	-27.35	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4934.000	41.26	3.59	44.85	-29.15	74.00	150	360	Peak
2	7401.000	30.88	11.43	42.32	-31.68	74.00	150	360	Peak
3	* 9848.000	31.58	15.07	46.65	-27.35	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4934.000	36.15	3.59	39.75	-34.25	74.00	150	360	Peak
2	7401.000	31.51	11.43	42.95	-31.05	74.00	150	360	Peak
3	* 9868.000	30.81	15.11	45.92	-28.08	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4944.000	34.74	3.62	38.36	-35.64	74.00	150	360	Peak
2	7416.000	31.66	11.48	43.14	-30.86	74.00	150	360	Peak
3	* 9888.000	31.52	15.15	46.66	-27.34	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4944.000	34.41	3.62	38.03	-35.97	74.00	150	360	Peak
2	7416.000	31.58	11.48	43.05	-30.95	74.00	150	360	Peak
3	* 9888.000	32.23	15.15	47.38	-26.62	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	42.79	3.33	46.12	-27.88	74.00	150	360	Peak
2	7236.000	35.35	10.97	46.32	-27.68	74.00	150	360	Peak
3	* 9648.000	31.72	14.70	46.42	-27.58	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	38.98	3.33	42.31	-31.69	74.00	150	360	Peak
2	7236.000	32.87	10.97	43.84	-30.16	74.00	150	360	Peak
3	* 9648.000	31.70	14.70	46.40	-27.60	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4874.000	43.02	3.45	46.47	-27.53	74.00	150	360	Peak
2	7311.000	33.89	11.18	45.07	-28.93	74.00	150	360	Peak
3	9748.000	30.66	14.89	45.54	-28.46	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	39.09	3.45	42.54	-31.46	74.00	150	360	Peak
2	7311.000	32.79	11.18	43.97	-30.03	74.00	150	360	Peak
3	* 9748.000	30.72	14.89	45.61	-28.39	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	42.72	3.57	46.29	-27.71	74.00	150	360	Peak
2	7386.000	34.68	11.39	46.07	-27.93	74.00	150	360	Peak
3	* 9848.000	31.69	15.07	46.76	-27.24	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	39.41	3.57	42.98	-31.02	74.00	150	360	Peak
2	7386.000	32.05	11.39	43.44	-30.56	74.00	150	360	Peak
3	* 9848.000	33.57	15.07	48.64	-25.36	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4934.000	40.30	3.59	43.89	-30.11	74.00	150	360	Peak
2	7401.000	31.97	11.43	43.40	-30.60	74.00	150	360	Peak
3	* 9868.000	32.10	15.11	47.21	-26.79	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4934.000	36.56	3.59	40.15	-33.85	74.00	150	360	Peak
2	7401.000	31.67	11.43	43.10	-30.90	74.00	150	360	Peak
3	* 9868.000	30.70	15.11	45.81	-28.19	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4944.000	34.98	3.62	38.59	-35.41	74.00	150	360	Peak
2	7416.000	32.29	11.48	43.77	-30.23	74.00	150	360	Peak
3	* 9888.000	31.62	15.15	46.77	-27.23	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4944.000	35.41	3.62	39.03	-34.97	74.00	150	360	Peak
2	7416.000	31.83	11.48	43.30	-30.70	74.00	150	360	Peak
3	* 9888.000	31.97	15.15	47.12	-26.88	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 3_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4844.000	35.91	3.38	39.29	-34.71	74.00	150	360	Peak
2	7266.000	32.04	11.05	43.10	-30.90	74.00	150	360	Peak
3	* 9688.000	30.19	14.77	44.97	-29.03	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 3_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4844.000	35.88	3.38	39.25	-34.75	74.00	150	360	Peak
2	* 7266.000	34.82	11.05	45.87	-28.13	74.00	150	360	Peak
3	9688.000	30.40	14.77	45.17	-28.83	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	37.34	3.45	40.79	-33.21	74.00	150	360	Peak
2	7311.000	32.75	11.18	43.93	-30.07	74.00	150	360	Peak
3	* 9748.000	30.96	14.89	45.85	-28.15	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	35.62	3.45	39.07	-34.93	74.00	150	360	Peak
2	7311.000	33.47	11.18	44.65	-29.35	74.00	150	360	Peak
3	* 9748.000	31.07	14.89	45.96	-28.04	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 9_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4904.000	36.07	3.52	39.59	-34.41	74.00	150	360	Peak
2	7356.000	32.53	11.31	43.84	-30.16	74.00	150	360	Peak
3	* 9808.000	31.79	15.00	46.78	-27.22	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 9_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4904.000	34.74	3.52	38.26	-35.74	74.00	150	360	Peak
2	7356.000	31.63	11.31	42.94	-31.06	74.00	150	360	Peak
3	* 9808.000	32.97	15.00	47.97	-26.03	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 10_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4914.000	34.90	3.54	38.44	-35.56	74.00	150	360	Peak
2	7371.000	30.99	11.35	42.34	-31.66	74.00	150	360	Peak
3	* 9828.000	32.06	15.04	47.10	-26.90	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 10_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4914.000	35.76	3.54	39.30	-34.70	74.00	150	360	Peak
2	7371.000	32.22	11.35	43.57	-30.43	74.00	150	360	Peak
3	* 9828.000	32.95	15.04	47.99	-26.01	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	35.75	3.57	39.32	-34.68	74.00	150	360	Peak
2	7386.000	31.76	11.39	43.15	-30.85	74.00	150	360	Peak
3	* 9848.000	31.96	15.07	47.03	-26.97	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	34.24	3.57	37.81	-36.19	74.00	150	360	Peak
2	7386.000	31.95	11.39	43.34	-30.66	74.00	150	360	Peak
3	* 9848.000	31.12	15.07	46.19	-27.81	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_RX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1160.969	52.38	-7.24	45.15	-28.85	74.00	150	360	Peak
2	1522.219	49.40	-5.67	43.73	-30.27	74.00	150	360	Peak
3	1660.344	51.44	-5.31	46.13	-27.87	74.00	150	360	Peak
4	1957.844	53.83	-4.53	49.30	-24.70	74.00	150	360	Peak
5	* 2853.531	53.11	-2.44	50.67	-23.33	74.00	150	360	Peak
6	3734.344	45.50	-0.03	45.46	-28.54	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D & BBHA 9170	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_RX_CH 6_ANT 0	Test Voltage	AC 110V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1681.063	47.24	-5.26	41.99	-32.01	74.00	150	360	Peak
2	1942.438	53.18	-4.57	48.61	-25.39	74.00	150	360	Peak
3	2492.813	50.40	-2.25	48.15	-25.85	74.00	150	360	Peak
4 *	2922.594	53.68	-2.48	51.19	-22.81	74.00	150	360	Peak
5	3596.219	48.03	-0.51	47.52	-26.48	74.00	150	360	Peak
6	3751.875	49.91	0.03	49.93	-24.07	74.00	150	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

5.6 頻帶邊緣

5.6.1 量測方法

待測物置於非導體桌面（落地型產品置於地上），受測物使用交流電源時，將其與任何配件設備之電源線連接至位於旋轉桌的交流電源。受測物使用電池時，測試時應裝置新電池或充電完全的電池。受測物與配件設備之電源線無須束綁，桌面上受測設備的所有電源線由桌子的後緣垂下沿旋轉桌表面接至交流插座。落地型設備的交流電源線可以方便的型態走線。桌面可360度旋轉，接收天線置於距待測物3m距離，高度可在1至4公尺間變動，以量測待測物之最大輻射電場強度，接收天線並應於水平及垂直極化方向各量測一次。（待測物擺設方式根據 ANSI C63.10-2013版，待測物放置桌中心，1G以下擺設高度為80cm/1G以上擺設高度為150cm）

- (1) 任一頻率小於或等於1000 MHz 之訊號,使用CISPR準峰值檢波器
- (2) 任一頻率大於1000 MHz 之訊號，使用平均值檢波器測量，當規定之發射限制值為平均值時(含1000 MHz 以下)，受測訊號藉由峰值檢波器(RBW:1MHz,VBW:3MHz)所測量之峰值，亦須符合峰值發射限制值，其峰值發射限制值為最大容許平均值加20 dB。


5.6.2 限制要求

除低功率射頻器材技術規範另有規定外，任何低功率射頻器材之主波皆不得使用下表所列各頻段之頻率低功率射頻器材落於下表所列頻帶內之混附發射，其電場強度必須符合低功率射頻器材技術規範之第3.6節限制規定


頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)	頻 率 (MHz)
0.090~0.110	25.500~25.700	703.00~748.00	2310.0~2390.0	13250~13400
0.490~0.510	37.475~38.275	758.00~803.00	2483.5~2900.0	14470~14500
2.172~2.198	73.500~75.400	825.00~915.00	3260.0~3267.0	15350~16200
3.013~3.033	108.00~138.00	930.00~1240.0	3332.0~3339.0	17700~21400
4.115~4.198	149.90~150.05	1300.0~1427.0	3345.8~3358.0	22010~23120
5.670~5.690	156.70~156.90	1435.0~1626.5	3500.0~4400.0	23600~24000
6.200~6.300	162.01~167.17	1660.0~1785.0	4500.0~5250.0	31200~31800
8.230~8.400	167.72~173.20	1805.0~1880.0	5350.0~5460.0	36430~36500
12.265~12.600	240.00~285.00	1885.0~1900.0	7250.0~7750.0	38600 以上
13.340~13.430	322.00~335.40	1905.0~1985.0	8025.0~8500.0	
14.965~15.020	399.90~410.00	2010.0~2025.0	9000.0~9200.0	
16.700~16.755	485.00~510.00	2110.0~2170.0	9300.0~9500.0	
19.965~20.020	608.00~614.00	2200.0~2300.0	10600~12700	

5.6.3 測試架構圖


Under 30MHz Test




Under 1GHz Test Setup



1GHz ~ 18GHz Test Setup:




18GHz ~25GHz Test Setup:



5.6.4 頻帶邊緣測試結果

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	29.40	32.15	61.55	-12.45	74.00	215	305	Peak
2		28.77	32.30	61.07	-12.93	74.00	215	305	Peak
3		72.01	32.39	104.40	N/A	N/A	215	305	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2377.875	16.52	32.24	48.76	-5.24	54.00	215	305	Average
2	* 2390.000	16.97	32.30	49.26	-4.74	54.00	215	305	Average
3	2410.750	68.27	32.39	100.65	N/A	N/A	215	305	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2369.875	29.72	32.21	61.93	-12.07	74.00	170	310	Peak
2		2390.000	28.71	32.30	61.01	-12.99	74.00	170	310	Peak
3		2410.625	71.11	32.39	103.50	N/A	N/A	170	310	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2372.125	16.88	32.22	49.10	-4.90	54.00	170	310	Average
2		2390.000	16.68	32.30	48.97	-5.03	54.00	170	310	Average
3		2410.750	67.87	32.39	100.26	N/A	N/A	170	310	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.565	71.66	32.61	104.27	N/A	N/A	190	305	Peak
2	2483.500	27.98	32.71	60.69	-13.31	74.00	190	305	Peak
3	* 2489.275	29.15	32.73	61.88	-12.12	74.00	190	305	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.840	68.54	32.61	101.15	N/A	N/A	190	305	Average
2	2483.500	16.21	32.71	48.91	-5.09	54.00	190	305	Average
3	* 2487.020	16.25	32.72	48.97	-5.03	54.00	190	305	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.565	69.69	32.61	102.29	N/A	N/A	195	30	Peak
2	2483.500	28.14	32.71	60.85	-13.15	74.00	195	30	Peak
3	* 2495.215	29.09	32.76	61.85	-12.15	74.00	195	30	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.895	66.25	32.61	98.86	N/A	N/A	195	30	Average
2	2483.500	16.38	32.71	49.09	-4.91	54.00	195	30	Average
3	* 2486.690	16.81	32.72	49.53	-4.47	54.00	195	30	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.650	67.11	32.63	99.74	N/A	N/A	190	305	Peak
2	2483.500	27.27	32.71	59.98	-14.02	74.00	190	305	Peak
3	* 2485.400	28.77	32.72	61.48	-12.52	74.00	190	305	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.950	63.52	32.63	96.15	N/A	N/A	190	305	Average
2	* 2483.500	16.03	32.71	48.73	-5.27	54.00	190	305	Average
3	2487.650	15.98	32.73	48.71	-5.29	54.00	190	305	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.600	65.12	32.63	97.75	N/A	N/A	195	30	Peak
2	2483.500	26.49	32.71	59.20	-14.80	74.00	195	30	Peak
3	* 2488.750	28.47	32.73	61.20	-12.80	74.00	195	30	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.850	61.69	32.63	94.32	N/A	N/A	195	30	Average
2	2483.500	16.05	32.71	48.75	-5.25	54.00	195	30	Average
3	* 2492.500	16.19	32.75	48.94	-5.06	54.00	195	30	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2470.680	61.68	32.65	94.33	N/A	N/A	190	305	Peak
2	2483.500	26.82	32.71	59.53	-14.47	74.00	190	305	Peak
3	* 2485.640	28.80	32.72	61.52	-12.48	74.00	190	305	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2470.800	58.33	32.65	90.98	N/A	N/A	190	305	Average
2	2483.500	15.48	32.71	48.19	-5.81	54.00	190	305	Average
3	* 2488.240	15.94	32.73	48.67	-5.33	54.00	190	305	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2473.400	59.41	32.66	92.07	N/A	N/A	195	30	Peak
2	2483.500	27.60	32.71	60.30	-13.70	74.00	195	30	Peak
3	* 2490.880	28.74	32.74	61.48	-12.52	74.00	195	30	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11b_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2473.120	55.91	32.66	88.58	N/A	N/A	195	30	Average
2	2483.500	15.83	32.71	48.53	-5.47	54.00	195	30	Average
3	* 2487.320	16.13	32.72	48.85	-5.15	54.00	195	30	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	28.58	32.00	60.58	-13.42	74.00	165	50	Peak
2		27.61	32.30	59.91	-14.09	74.00	165	50	Peak
3		73.52	32.39	105.91	N/A	N/A	165	50	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2374.375	15.36	32.23	47.58	-6.42	54.00	165	50	Average
2	* 2390.000	15.89	32.30	48.19	-5.81	54.00	165	50	Average
3	2409.000	63.14	32.38	95.52	N/A	N/A	165	50	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2327.500	29.35	32.02	61.37	-12.63	74.00	170	305	Peak
2	2390.000	28.82	32.30	61.12	-12.88	74.00	170	305	Peak
3	2410.125	71.47	32.38	103.86	N/A	N/A	170	305	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 1_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2365.750	15.53	32.19	47.72	-6.28	54.00	170	305	Average
2	* 2390.000	16.06	32.30	48.36	-5.64	54.00	170	305	Average
3	2409.125	61.12	32.38	93.50	N/A	N/A	170	305	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.735	71.51	32.63	104.14	N/A	N/A	135	65	Peak
2	2483.500	27.49	32.71	60.20	-13.80	74.00	135	65	Peak
3	* 2492.960	29.62	32.75	62.36	-11.64	74.00	135	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2459.190	61.07	32.60	93.67	N/A	N/A	135	65	Average
2	* 2483.500	15.58	32.71	48.28	-5.72	54.00	135	65	Average
3	2494.335	15.53	32.76	48.28	-5.72	54.00	135	65	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.790	71.43	32.63	104.06	N/A	N/A	135	15	Peak
2	2483.500	28.81	32.71	61.52	-12.48	74.00	135	15	Peak
3	* 2487.130	29.22	32.72	61.95	-12.05	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 11_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2464.580	61.11	32.62	93.73	N/A	N/A	135	15	Average
2	2483.500	15.39	32.71	48.10	-5.90	54.00	135	15	Average
3	* 2486.910	15.52	32.72	48.24	-5.76	54.00	135	15	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2472.850	67.53	32.66	100.19	N/A	N/A	135	65	Peak
2	2483.500	27.28	32.71	59.98	-14.02	74.00	135	65	Peak
3	* 2494.650	30.27	32.76	63.02	-10.98	74.00	135	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2466.050	56.98	32.63	89.61	N/A	N/A	135	65	Average
2	2483.500	15.10	32.71	47.81	-6.19	54.00	135	65	Average
3	* 2490.950	15.22	32.74	47.96	-6.04	54.00	135	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2470.750	67.53	32.65	100.18	N/A	N/A	135	15	Peak
2	2483.500	27.51	32.71	60.21	-13.79	74.00	135	15	Peak
3	* 2486.050	28.93	32.72	61.65	-12.35	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 12_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2469.100	57.20	32.64	89.85	N/A	N/A	135	15	Average
2	2483.500	14.93	32.71	47.63	-6.37	54.00	135	15	Average
3	* 2492.500	15.08	32.75	47.83	-6.17	54.00	135	15	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2477.680	62.67	32.68	95.35	N/A	N/A	135	65	Peak
2	2483.500	28.59	32.71	61.29	-12.71	74.00	135	65	Peak
3	* 2491.680	29.22	32.74	61.96	-12.04	74.00	135	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2474.040	51.98	32.67	84.64	N/A	N/A	135	65	Average
2	2483.500	14.85	32.71	47.56	-6.44	54.00	135	65	Average
3	* 2489.280	15.03	32.73	47.77	-6.23	54.00	135	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2473.600	62.61	32.66	95.27	N/A	N/A	135	15	Peak
2	2483.500	27.28	32.71	59.99	-14.01	74.00	135	15	Peak
3	* 2488.840	29.25	32.73	61.98	-12.02	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11g_TX_CH 13_ANT 0	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.920	52.16	32.63	84.79	N/A	N/A	135	15	Average
2	2483.500	14.83	32.71	47.54	-6.46	54.00	135	15	Average
3	* 2486.080	15.04	32.72	47.76	-6.24	54.00	135	15	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2379.000	29.16	32.25	61.41	-12.59	74.00	165	50	Peak
2	* 2390.000	29.88	32.30	62.18	-11.82	74.00	165	50	Peak
3	2406.000	73.13	32.37	105.49	N/A	N/A	165	50	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2378.000	15.33	32.24	47.58	-6.42	54.00	165	50	Average
2	* 2390.000	16.59	32.30	48.89	-5.11	54.00	165	50	Average
3	2410.125	61.31	32.38	93.70	N/A	N/A	165	50	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2355.750	29.20	32.15	61.34	-12.66	74.00	170	305	Peak
2	2390.000	28.40	32.30	60.70	-13.30	74.00	170	305	Peak
3	2413.625	70.70	32.40	103.10	N/A	N/A	170	305	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 1_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2375.250	15.33	32.23	47.56	-6.44	54.00	150	305	Average
2	* 2390.000	16.32	32.30	48.62	-5.38	54.00	150	305	Average
3	2408.625	59.31	32.38	91.68	N/A	N/A	150	305	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.345	71.93	32.61	104.54	N/A	N/A	135	65	Peak
2	* 2483.500	28.93	32.71	61.63	-12.37	74.00	135	65	Peak
3	2494.170	28.81	32.75	61.56	-12.44	74.00	135	65	Peak

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.585	59.93	32.60	92.53	N/A	N/A	135	65	Average
2	2483.500	15.55	32.71	48.26	-5.74	54.00	135	65	Average
3	* 2492.245	15.59	32.75	48.34	-5.66	54.00	135	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2463.700	72.86	32.62	105.48	N/A	N/A	135	15	Peak
2	2483.500	27.64	32.71	60.35	-13.65	74.00	135	15	Peak
3	* 2488.780	29.26	32.73	61.99	-12.01	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.460	60.41	32.63	93.04	N/A	N/A	135	15	Average
2	2483.500	15.00	32.71	47.71	-6.29	54.00	135	15	Average
3	* 2492.960	15.28	32.75	48.03	-5.97	54.00	135	15	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 12_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.250	68.33	32.63	100.96	N/A	N/A	135	65	Peak
2	2483.500	27.74	32.71	60.44	-13.56	74.00	135	65	Peak
3	* 2489.700	30.08	32.73	62.81	-11.19	74.00	135	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 12_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2472.800	56.18	32.66	88.84	N/A	N/A	135	65	Average
2	2483.500	15.10	32.71	47.81	-6.19	54.00	135	65	Average
3	* 2489.800	15.28	32.74	48.01	-5.99	54.00	135	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 12_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2468.800	69.20	32.64	101.84	N/A	N/A	135	15	Peak
2	2483.500	28.27	32.71	60.98	-13.02	74.00	135	15	Peak
3	* 2490.400	29.48	32.74	62.22	-11.78	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 12_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2472.800	56.73	32.66	89.39	N/A	N/A	135	15	Average
2	* 2483.500	15.16	32.71	47.86	-6.14	54.00	135	15	Average
3	2496.950	15.06	32.77	47.83	-6.17	54.00	135	15	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 13_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2470.120	63.75	32.65	96.40	N/A	N/A	135	65	Peak
2	2483.500	27.55	32.71	60.26	-13.74	74.00	135	65	Peak
3	* 2488.320	28.68	32.73	61.40	-12.60	74.00	135	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 13_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2478.000	51.64	32.68	84.32	N/A	N/A	135	65	Average
2	2483.500	14.79	32.71	47.50	-6.50	54.00	135	65	Average
3	* 2486.800	15.06	32.72	47.78	-6.22	54.00	135	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 13_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2470.200	64.33	32.65	96.98	N/A	N/A	135	15	Peak
2	2483.500	27.61	32.71	60.32	-13.68	74.00	135	15	Peak
3	* 2492.160	29.08	32.75	61.82	-12.18	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-20MHz_TX_CH 13_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2477.560	52.43	32.68	85.11	N/A	N/A	135	15	Average
2	2483.500	14.72	32.71	47.42	-6.58	54.00	135	15	Average
3	* 2489.560	15.07	32.73	47.81	-6.19	54.00	135	15	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 3_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2373.000	29.01	32.22	61.23	-12.77	74.00	165	50	Peak
2	* 2390.000	29.08	32.30	61.38	-12.62	74.00	165	50	Peak
3	2408.000	66.91	32.38	99.29	N/A	N/A	165	50	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 3_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2352.420	15.69	32.13	47.82	-6.18	54.00	165	50	Average
2	* 2390.000	16.09	32.30	48.38	-5.62	54.00	165	50	Average
3	2415.980	55.13	32.41	87.54	N/A	N/A	165	50	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 3_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2371.320	29.39	32.21	61.61	-12.39	74.00	170	305	Peak
2	2390.000	28.34	32.30	60.64	-13.36	74.00	170	305	Peak
3	2418.920	64.88	32.42	97.31	N/A	N/A	170	305	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 3_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2376.500	15.99	32.24	48.22	-5.78	54.00	170	305	Average
2	* 2390.000	16.25	32.30	48.54	-5.46	54.00	150	305	Average
3	2408.280	53.14	32.38	85.51	N/A	N/A	150	305	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 9_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2438.080	66.28	32.51	98.79	N/A	N/A	135	65	Peak
2	2483.500	29.16	32.71	61.86	-12.14	74.00	135	65	Peak
3	* 2489.360	30.13	32.73	62.87	-11.13	74.00	135	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 9_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2447.360	54.20	32.55	86.74	N/A	N/A	135	65	Average
2	2483.500	15.66	32.71	48.37	-5.63	54.00	135	65	Average
3	* 2487.360	16.17	32.72	48.90	-5.10	54.00	135	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 9_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2448.880	66.01	32.56	98.57	N/A	N/A	135	15	Peak
2	2483.500	28.82	32.71	61.53	-12.47	74.00	135	15	Peak
3	* 2490.320	29.56	32.74	62.30	-11.70	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 9_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2459.280	54.21	32.60	86.81	N/A	N/A	135	15	Average
2	2483.500	15.62	32.71	48.33	-5.67	54.00	135	15	Average
3	* 2493.520	16.02	32.75	48.77	-5.23	54.00	135	15	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 10_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2443.020	66.13	32.53	98.66	N/A	N/A	135	65	Peak
2	2483.500	28.49	32.71	61.20	-12.80	74.00	135	65	Peak
3	* 2493.560	29.09	32.75	61.85	-12.15	74.00	135	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 10_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2452.610	54.16	32.57	86.73	N/A	N/A	135	65	Average
2	2483.500	15.24	32.71	47.94	-6.06	54.00	135	65	Average
3	* 2490.340	15.71	32.74	48.45	-5.55	54.00	135	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 10_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.170	66.45	32.60	99.05	N/A	N/A	135	15	Peak
2	2483.500	27.28	32.71	59.99	-14.01	74.00	135	15	Peak
3	* 2496.290	29.15	32.76	61.91	-12.09	74.00	135	15	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 10_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2459.610	54.59	32.60	87.19	N/A	N/A	135	15	Average
2	2483.500	15.59	32.71	48.30	-5.70	54.00	135	15	Average
3	* 2489.220	15.77	32.73	48.50	-5.50	54.00	135	15	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C / 60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2448.065	66.31	32.55	98.86	N/A	N/A	135	65	Peak
2	* 2483.500	33.65	32.71	66.35	-7.65	74.00	135	65	Peak
3	2490.380	29.97	32.74	62.71	-11.29	74.00	135	65	Peak

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Horizontal	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2453.915	54.19	32.58	86.77	N/A	N/A	135	65	Average
2	* 2483.500	16.76	32.71	49.46	-4.54	54.00	135	65	Average
3	2489.405	15.90	32.73	48.64	-5.36	54.00	135	65	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.095	66.63	32.63	99.25	N/A	N/A	135	15	Peak
2	* 2483.500	33.86	32.71	66.57	-7.43	74.00	135	15	Peak
3	2498.115	29.29	32.77	62.06	-11.94	74.00	135	15	Peak

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Game Console	Date of Test	2021-04-13
Factor	BBHA 9120D	Temp. / Humidity	24°C /60%
Polarity	Vertical	Site / Test Engineer	AC1 / Kaunaz
Test Mode	802.11n-40MHz_TX_CH 11_ANT 0+1	Test Voltage	AC 110V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2465.680	54.56	32.63	87.19	N/A	N/A	135	15	Average
2	* 2483.500	17.08	32.71	49.79	-4.21	54.00	135	15	Average
3	2489.795	15.65	32.74	48.38	-5.62	54.00	135	15	Average

Note:

1. " * ", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

5.7 占用頻寬

5.7.1 量測方法


待測物之天線埠經由適當之衰減直接連至頻譜分析儀RF輸入端，頻譜分析儀之設定,參考如下:

- (1) Set RBW = 100 kHz
- (2) VBW $\geq 3 \times$ RBW
- (3) Detector = Peak
- (4) Trace mode = max hold
- (5) Sweep = auto couple

5.7.2 限制要求

6dB頻寬至少應有500kHz。

5.7.3 測試架構圖



5.7.4 占用頻寬測試結果


Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Antenna A (SISO)						
802.11b	1	01	2412	9.088	≥ 0.5	Pass
	1	06	2437	8.142	≥ 0.5	Pass
	1	11	2462	9.065	≥ 0.5	Pass
	1	12	2467	9.033	≥ 0.5	Pass
	1	13	2472	9.604	≥ 0.5	Pass
802.11g	6	01	2412	16.370	≥ 0.5	Pass
	6	06	2437	16.370	≥ 0.5	Pass
	6	11	2462	16.380	≥ 0.5	Pass
	6	12	2467	16.400	≥ 0.5	Pass
	6	13	2472	16.360	≥ 0.5	Pass

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Antenna A (MIMO)						
802.11n-HT20	MCS8	01	2412	17.630	≥ 0.5	Pass
	MCS8	06	2437	16.620	≥ 0.5	Pass
	MCS8	11	2462	17.590	≥ 0.5	Pass
	MCS8	12	2467	17.630	≥ 0.5	Pass
	MCS8	13	2472	17.100	≥ 0.5	Pass
802.11n-HT40	MCS8	03	2422	36.380	≥ 0.5	Pass
	MCS8	06	2437	36.380	≥ 0.5	Pass
	MCS8	09	2452	36.320	≥ 0.5	Pass
	MCS8	10	2457	36.350	≥ 0.5	Pass
	MCS8	11	2462	36.160	≥ 0.5	Pass


Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Antenna B (MIMO)						
802.11n-HT20	MCS8	01	2412	17.650	≥ 0.5	Pass
	MCS8	06	2437	17.640	≥ 0.5	Pass
	MCS8	11	2462	17.650	≥ 0.5	Pass
	MCS8	12	2467	17.650	≥ 0.5	Pass
	MCS8	13	2472	16.980	≥ 0.5	Pass
802.11n-HT40	MCS8	03	2422	36.450	≥ 0.5	Pass
	MCS8	06	2437	36.460	≥ 0.5	Pass
	MCS8	09	2452	36.340	≥ 0.5	Pass
	MCS8	10	2457	36.400	≥ 0.5	Pass
	MCS8	11	2462	36.430	≥ 0.5	Pass

Antenna Port A (SISO)


802.11 b CH01 (2412MHz) (1Mbps)



802.11 b CH06 (2437MHz) (1Mbps)




802.11 b CH11 (2462MHz) (1Mbps)




802.11 b CH12 (2467MHz) (1Mbps)




802.11 b CH13 (2472MHz) (1Mbps)




802.11 g CH01 (2412MHz) (6Mbps)




802.11 g CH06 (2437MHz) (6Mbps)




802.11 g CH11 (2462MHz) (6Mbps)



802.11 g CH12 (2467MHz) (6Mbps)




802.11 g CH13 (2472MHz) (6Mbps)




Antenna Port A (MIMO)


802.11 n20 CH01 (2412MHz) (MCS8)




802.11 n20 CH06 (2437MHz) (MCS8)




802.11 n20 CH11 (2462MHz) (MCS8)




802.11 n20 CH12 (2467MHz) (MCS8)




802.11 n20 CH13 (2472MHz) (MCS8)




802.11 n40 CH03 (2422MHz) (MCS8)




802.11 n40 CH06 (2437MHz) (MCS8)




802.11 n40 CH09 (2452MHz) (MCS8)



802.11 n40 CH10 (2457MHz) (MCS8)




802.11 n40 CH11 (2462MHz) (MCS8)




Antenna Port B (MIMO)


802.11 n20 CH01 (2412MHz) (MCS8)




802.11 n20 CH06 (2437MHz) (MCS8)




802.11 n20 CH11 (2462MHz) (MCS8)




802.11 n20 CH12 (2467MHz) (MCS8)




802.11 n20 CH13 (2472MHz) (MCS8)




802.11 n40 CH03 (2422MHz) (MCS8)




802.11 n40 CH06 (2437MHz) (MCS8)




802.11 n40 CH09 (2452MHz) (MCS8)



802.11 n40 CH10 (2457MHz) (MCS8)



802.11 n40 CH11 (2462MHz) (MCS8)



5.8. 功率頻譜密度

5.8.1 量測方法

將發射機之天線埠經由適當之衰減直接連至測試儀器。找出發射峰值並擴展於通帶內，設定解析頻寬為3 kHz，視訊頻寬大於解析頻寬，掃描時間為頻率掃描範圍除以3 kHz。所測得之峰值位準必須應小於或等於8 dBm。

若受測裝置之頻譜線間隔小於3 kHz，測量時應將解析頻寬降低以使頻譜線間隔大於3 kHz，所測得之數據再藉加總3 kHz 頻帶內所有個別頻譜線之功率(即標準化至3 kHz)以決定是否符合規定。


5.8.2 限制要求

在使用頻率範圍之任意3千赫(kHz)頻寬內，由發射機傳導至天線之峰值發射電功率密度在任意期間內，皆不得大於8dBm。

若用於非固定式點對點操作時，若其發射天線之方向性增益超過6dBi，應依所超過之dB數等量降低峰值輸出功率。如用於固定式點對點(註)操作時，應符合下列情形之一：

- (1)操作於2400-2483.5兆赫(MHz)者，其發射天線之方向性增益超過6dBi，應於每超過3dB降低1dB之峰值輸出功率。
- (2) 操作於5725-5850兆赫(MHz)者，其發射天線之方向性增益超過6dBi，不需降低峰值輸出功率。

5.8.3 測試架構圖



5.8.4 功率頻譜密度測試結果

Test Mode	Channel No.	Freq. (MHz)	PSD (dBm)	Limit (dBm)	Result
Antenna A (SISO)					
11b	1	2412	-6.820	≤ 8	Pass
	6	2437	-7.520	≤ 8	Pass
	11	2462	-7.940	≤ 8	Pass
	12	2467	-12.150	≤ 8	Pass
	13	2472	-16.900	≤ 8	Pass
11g	1	2412	-10.850	≤ 8	Pass
	6	2437	-10.940	≤ 8	Pass
	11	2462	-10.750	≤ 8	Pass
	12	2467	-16.050	≤ 8	Pass
	13	2472	-20.680	≤ 8	Pass

Test Mode	Channel No.	Freq. (MHz)	PSD Antenna A (dBm)	PSD Antenna B (dBm)	PSD Antenna A+B (dBm)	Limit (dBm)	Result
Antenna A+B (MIMO)							
11n-20M	1	2412	-12.090	-12.890	-9.461	≤ 8	Pass
	6	2437	-12.830	-11.570	-9.144	≤ 8	Pass
	11	2462	-11.920	-12.140	-9.018	≤ 8	Pass
	12	2467	-14.430	-15.460	-11.904	≤ 8	Pass
	13	2472	-20.720	-21.150	-17.919	≤ 8	Pass
11n-40M	3	2422	-17.720	-17.060	-14.367	≤ 8	Pass
	6	2437	-18.820	-17.250	-14.954	≤ 8	Pass
	9	2452	-18.100	-18.420	-15.247	≤ 8	Pass
	10	2457	-18.180	-18.420	-15.288	≤ 8	Pass
	11	2462	-18.270	-18.320	-15.285	≤ 8	Pass

Antenna Port A (SISO)

802.11 b CH01 (2412MHz) (1Mbps)



802.11 b CH06 (2437MHz) (1Mbps)



802.11 b CH11 (2462MHz) (1Mbps)




802.11 b CH12 (2467MHz) (1Mbps)




802.11 b CH13 (2472MHz) (1Mbps)




802.11 g CH01 (2412MHz) (6Mbps)



802.11 g CH06 (2437MHz) (6Mbps)



802.11 g CH11 (2462MHz) (6Mbps)



802.11 g CH12 (2467MHz) (6Mbps)




802.11 g CH13 (2472MHz) (6Mbps)




Antenna Port A (MIMO)


802.11 n20 CH01 (2412MHz) (MCS8)




802.11 n20 CH06 (2437MHz) (MCS8)




802.11 n20 CH11 (2462MHz) (MCS8)



802.11 n20 CH12 (2467MHz) (MCS8)




802.11 n20 CH13 (2472MHz) (MCS8)



802.11 n40 CH03 (2422MHz) (MCS8)



802.11 n40 CH06 (2437MHz) (MCS8)




802.11 n40 CH09 (2452MHz) (MCS8)



802.11 n40 CH10 (2457MHz) (MCS8)




802.11 n40 CH11 (2462MHz) (MCS8)




Antenna Port B (MIMO)


802.11 n20 CH01 (2412MHz) (MCS8)




802.11 n20 CH06 (2437MHz) (MCS8)




802.11 n20 CH11 (2462MHz) (MCS8)



802.11 n20 CH12 (2467MHz) (MCS8)



802.11 n20 CH13 (2472MHz) (MCS8)




802.11 n40 CH03 (2422MHz) (MCS8)



802.11 n40 CH06 (2437MHz) (MCS8)



802.11 n40 CH09 (2452MHz) (MCS8)



802.11 n40 CH10 (2457MHz) (MCS8)



802.11 n40 CH11 (2462MHz) (MCS8)



The End