RF TEST REPORT

Applicant	XCHENG TECH CO.,LIMITED
FCC ID	2AZ4F-D1
Product	Smart Desktop Terminal
Brand	Kobile;Kripto;Clip;Nextep;Ecline;SAT;Qian;Ghia; CBX;Solux;Dejavoo;slimrate
Model	D1
Report No.	R2206A0595-R1V2
Issue Date	August 23, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2021)/ FCC CFR 47 Part 22H (2021)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying | *Approved by: Xu Kai*

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

TABLE OF CONTENT

1. Test Laboratory 5
1.1. Notes of the Test Report 5
1.2. Test facility 5
1.3. Testing Location 5
2. General Description of Equipment under Test 6
2.1. Applicant and Manufacturer Information 6
2.2. General Information 6
3. Applied Standards 8
4. Test Configuration 9
5. Test Case 11
5.1. RF Power Output and Effective Radiated Power 11
5.2. Occupied Bandwidth 12
5.3. Band Edge Compliance 13
5.4. Peak-to-Average Power Ratio (PAPR) 14
5.5. Frequency Stability 15
5.6. Spurious Emissions at Antenna Terminals 17
5.7. Radiates Spurious Emission 18
6. Test Result 21
6.1. RF Power Output and Effective Radiated Power 21
6.2. Occupied Bandwidth 26
6.3. Band Edge Compliance 34
6.4. Peak-to-Average Power Ratio (PAPR) 42
6.5. Frequency Stability 44
6.6. Spurious Emissions at Antenna Terminals 47
6.7. Radiates Spurious Emission 51
7. Main Test Instruments 54
ANNEX A: The EUT Appearance 55
ANNEX B: Test Setup Photos 56

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Version	Revision description	Issue Date
Rev.0	Initial issue of report.	August 16, 2022
Rev.1	Update description.	August 17, 2022
Rev.2	Update data.	August 23, 2022
Note: This revised report (Report No. R2206A0595-R1V2) supersedes and replaces the previously issued report (Report No. R2206A0595-R1V1). Please discard or destroy the previously issued report and dispose of it accordingly.		

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Radiated Power	2.1046 22.913(a)(5)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 / 22.917(a)	PASS
4	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS

Date of Testing: June 28, 2022 ~July 19, 2022
Date of Sample Received: June 28, 2022

Note: PASS: The EUT complies with the essential requirements in the standard.
FAIL: The EUT does not comply with the essential requirements in the standard.
All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	xukai@ta-shanghai.com

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	XCHENG TECH CO.,LIMITED
Applicant address	ROOM 401F, Building 5, No.2000 LONG DONG Avenue, Pudong New District
Manufacturer	XCHENG TECH CO.,LIMITED
Manufacturer address	ROOM 401F, Building 5, No.2000 LONG DONG Avenue, Pudong New District

2.2. General Information

EUT Description			
Model	D1		
IMEI	864084060007894		
Hardware Version	V1.0		
Software Version	V1.0		
Power Supply	Battery / AC adapter		
Antenna Type	Internal Antenna		
Antenna Gain	2dBi		
Test Mode(s)	GSM 850; WCDMA Band V; LTE Band 5;		
Test Modulation	(GSM/GPRS)GMSK, (EGPRS) GMSK/ 8PSK; (WCDMA) BPSK, QPSK,16QAM; (LTE) QPSK, 16QAM;		
GPRS Multislot Class	12		
EGPRS Multislot Class	12		
HSDPA UE Category	7		
HSUPA UE Category	7		
LTE Category	4		
Maximum E.R.P.	GSM 850:	32.27dBm	
	WCDMA Band V:	21.88dBm	
	LTE Band 5:	23.40dBm	
Rated Power Supply Voltage	7.2V		
Operating Voltage	Minimum: 6.9V Maximum: 8.4V		
Operating Temperature	Lowest: -10°C Highest: +50°C		
Testing Temperature	Lowest: -30°C Highest: +50°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 5	824 ~ 849	869 ~ 894

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EUT Accessory	
Adapter	Manufacturer: Shenzhen Flypower Technology Co., LTD Model: FLY0222052501
Button batteries	Manufacturer: SHENZHEN M&LAK INDUSTRY CO.,LTD Model: CR2032
RJ45&DB9_wire	Manufacturer: Shenzhen Flypower Technology Co., LTD Model: C393-210302-002
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.	

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:
FCC CFR 47 Part 22H (2021)

FCC CFR47 Part 2 (2021)

Reference standard:
ANSI C63.26-2015

KDB 971168 D01 Power Meas License Digital Systems v03r01

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.
Subsequently, only the worst case emissions are reported.
The following testing in GSM/WCDMA/LTE is set based on the maximum RF Output Power.
Test modes are chosen to be reported as the worst case configuration below:

Test items	**Modes/Modulation**	
	GSM 850	WCDMA Band V
RF Power Output and Effective Radiated power	GSM GPRS EGPRS	RMC HSDPA/HSUPA
Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Spurious Emissions at Antenna Terminals	GSM	RMC
Radiates Spurious Emission	GSM	RMC

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test modes are chosen as the worst case configuration below for LTE Band 5:

Test items	Bandwidth (MHz)				Modulation		RB			Test Channel		
	1.4	3	5	10	QPSK	16QAM	1	50%	100%	L	M	H
RF power output and Effective Radiated power	O	O	O	O	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	-	-	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	O	O	O	O	O	O	O	-	-	-	O	-
Spurious Emissions at Antenna Terminals	O	O	O	O	O	-	O	-	-	O	O	O
Radiates Spurious Emission	O	-	O	O	O	-	O	-	-	-	O	-
Note	1. The mark “O” means that this configuration is chosen for testing. 2. The mark “-” means that this configuration is not testing.											

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5. Test Case

5.1. RF Power Output and Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.

ERP can then be calculated as follows:
EIRP (dBm) = Output Power (dBm) - Losses (dB) + Antenna Gain (dBi)
where:dBd refers to gain relative to an ideal dipole.
EIRP (dBm) = ERP (dBm) + 2.15 (dB).

Test Setup



Limits

No specific RF power output requirements in part 2.1046.

Rule Part 22.913(a)(5) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	≤ 7 W (38.45 dBm)

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.4 dB for RF power output, *k* = 2, *U*= 1.19 dB for ERP.

Test Results

Refer to the section 6.1 of this report for test data.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.2. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.
RBW is set to ≥1%EBW, VBW is set to 3x RBW.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 624Hz.

Test Results

Refer to the section 6.2 of this report for test data.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.3. Band Edge Compliance

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.
RBW is set to ⩾1%EBW, VBW is set to 3x RBW.

Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.”

Limit	-13 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 1.96, *U*=0.684dB.

Test Results

Refer to the section 6.3 of this report for test data.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.4. Peak-to-Average Power Ratio (PAPR)

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk}. And measure the total average power and record as P_{Avg}. Both the peak and average power levels must be expressed in the same logarithmic units (*e.g.*, dBm). Determine the PAPR from:
PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.4 dB.

Test Results

Refer to the section 6.4 of this report for test data.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.5. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 6.9 V and 8.4 V, with a nominal voltage of 7.2V.

Test setup

Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75％ confidence level for the normal distribution is with the coverage factor k = 3, U= 0.01ppm.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results

Refer to the section 6.5 of this report for test data.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.6. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.
The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.
RBW is set to 1 kHz (0.009MHz~ 0.15 MHz),
RBW is set to 10 kHz (0.15 MHz~ 30 MHz)
RBW is set to 100 kHz (30MHz~1000 MHz)
RBW is set to 1000 kHz (above 1000MHz)
The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.”

Limit	-13 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor *k* = 1.96.

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-20GHz	1.407 dB

Test Results

Refer to the section 6.6 of this report for test data.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.7. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26-2015.
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=100kHz,VBW=300kHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
Power(EIRP)=PMea- PAg - Pcl + Ga
The measurement results are amend as described below:
Power(EIRP)=PMea- Pcl + Ga
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

= EIRP-2.15dB.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup

9KHz~ 30MHz



30MHz~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.”

Limit	-13 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95％ confidence level for the normal distribution is with the coverage factor *k* = 1.96, *U*= 3.55 dB.

Test Results

Refer to the section 6.7 of this report for test data.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6. Test Result

6.1. RF Power Output and Effective Radiated Power

GSM 850		Maximum Output Power (dBm)			ERP (dBm)		
		Channel 128	Channel 190	Channel 251	Channel 128	Channel 190	Channel 251
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)	824.2 (MHz)	836.6 (MHz)	848.8 (MHz)
GSM(GMSK)	Results	32.34	32.40	32.38	32.19	32.25	32.23
GPRS (GMSK)	1TXslot	32.35	32.42	32.40	32.20	32.27	32.25
	2TXslots	31.86	31.92	31.90	31.71	31.77	31.75
	3TXslots	30.44	30.48	30.45	30.29	30.33	30.30
	4TXslots	29.42	29.50	29.47	29.27	29.35	29.32
EGPRS (8PSK)	1TXslot	25.65	25.73	25.87	25.50	25.58	25.72
	2TXslots	24.55	24.62	24.75	24.40	24.47	24.60
	3TXslots	22.51	22.60	22.72	22.36	22.45	22.57
	4TXslots	21.47	21.44	21.56	21.32	21.29	21.41

WCDMA Band V		Maximum Output Power (dBm)			ERP (dBm)		
		Channel 4132	Channel 4183	Channel 4233	Channel 4132	Channel 4183	Channel 4233
		826.4 (MHz)	836.6 (MHz)	846.6 (MHz)	826.4 (MHz)	836.6 (MHz)	846.6 (MHz)
RMC		21.95	22.03	22.00	21.80	21.88	21.85
HSDPA	Sub - Test 1	21.41	21.45	21.44	21.26	21.30	21.29
	Sub - Test 2	21.40	21.47	21.41	21.25	21.32	21.26
	Sub - Test 3	20.87	20.97	20.93	20.72	20.82	20.78
	Sub - Test 4	20.88	20.98	20.91	20.73	20.83	20.76
HSUPA	Sub - Test 1	21.37	21.44	21.39	21.22	21.29	21.24
	Sub - Test 2	20.36	20.42	20.38	20.21	20.27	20.23
	Sub - Test 3	20.83	20.90	20.87	20.68	20.75	20.72
	Sub - Test 4	20.29	20.39	20.35	20.14	20.24	20.20
	Sub - Test 5	21.30	21.37	21.33	21.15	21.22	21.18

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5						
Bandwidth (MHz)	UL Channel	RB Size	RB Position	Modulation	Power (dBm)	ERP (dBm)
1.4	20407	1	#0	QPSK	23.15	23.00
1.4	20407	1	#Mid	QPSK	23.55	23.40
1.4	20407	1	#Max	QPSK	23.33	23.18
1.4	20407	3	#0	QPSK	23.17	23.02
1.4	20407	3	#Mid	QPSK	23.18	23.03
1.4	20407	3	#Max	QPSK	23.32	23.17
1.4	20407	6	#0	QPSK	22.26	22.11
1.4	20407	1	#0	16QAM	22.12	21.97
1.4	20407	1	#Mid	16QAM	22.50	22.35
1.4	20407	1	#Max	16QAM	22.10	21.95
1.4	20407	3	#0	16QAM	22.43	22.28
1.4	20407	3	#Mid	16QAM	22.36	22.21
1.4	20407	3	#Max	16QAM	22.31	22.16
1.4	20407	6	#0	16QAM	21.28	21.13
1.4	20525	1	#0	QPSK	23.13	22.98
1.4	20525	1	#Mid	QPSK	23.35	23.20
1.4	20525	1	#Max	QPSK	23.12	22.97
1.4	20525	3	#0	QPSK	23.17	23.02
1.4	20525	3	#Mid	QPSK	23.21	23.06
1.4	20525	3	#Max	QPSK	23.25	23.10
1.4	20525	6	#0	QPSK	22.32	22.17
1.4	20525	1	#0	16QAM	22.21	22.06
1.4	20525	1	#Mid	16QAM	22.32	22.17
1.4	20525	1	#Max	16QAM	22.23	22.08
1.4	20525	3	#0	16QAM	22.19	22.04
1.4	20525	3	#Mid	16QAM	22.25	22.10
1.4	20525	3	#Max	16QAM	22.29	22.14
1.4	20525	6	#0	16QAM	21.24	21.09
1.4	20643	1	#0	QPSK	23.16	23.01
1.4	20643	1	#Mid	QPSK	23.55	23.40
1.4	20643	1	#Max	QPSK	23.23	23.08
1.4	20643	3	#0	QPSK	23.36	23.21
1.4	20643	3	#Mid	QPSK	23.33	23.18
1.4	20643	3	#Max	QPSK	23.25	23.10
1.4	20643	6	#0	QPSK	22.25	22.10
1.4	20643	1	#0	16QAM	22.41	22.26
1.4	20643	1	#Mid	16QAM	21.95	21.80
1.4	20643	1	#Max	16QAM	22.44	22.29
1.4	20643	3	#0	16QAM	21.74	21.59

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1.4	20643	3	#Mid	16QAM	22.24	22.09
1.4	20643	3	#Max	16QAM	22.17	22.02
1.4	20643	6	#0	16QAM	21.30	21.15
3	20415	1	#0	QPSK	23.30	23.15
3	20415	1	#Mid	QPSK	23.25	23.10
3	20415	1	#Max	QPSK	23.21	23.06
3	20415	8	#0	QPSK	22.22	22.07
3	20415	8	#Mid	QPSK	22.21	22.06
3	20415	8	#Max	QPSK	22.25	22.10
3	20415	15	#0	QPSK	22.23	22.08
3	20415	1	#0	16QAM	22.33	22.18
3	20415	1	#Mid	16QAM	22.34	22.19
3	20415	1	#Max	16QAM	22.25	22.10
3	20415	8	#0	16QAM	21.17	21.02
3	20415	8	#Mid	16QAM	21.16	21.01
3	20415	8	#Max	16QAM	21.24	21.09
3	20415	15	#0	16QAM	21.17	21.02
3	20525	1	#0	QPSK	23.26	23.11
3	20525	1	#Mid	QPSK	23.30	23.15
3	20525	1	#Max	QPSK	22.73	22.58
3	20525	8	#0	QPSK	21.79	21.64
3	20525	8	#Mid	QPSK	22.28	22.13
3	20525	8	#Max	QPSK	21.86	21.71
3	20525	15	#0	QPSK	22.34	22.19
3	20525	1	#0	16QAM	21.94	21.79
3	20525	1	#Mid	16QAM	21.96	21.81
3	20525	1	#Max	16QAM	21.98	21.83
3	20525	8	#0	16QAM	21.31	21.16
3	20525	8	#Mid	16QAM	20.80	20.65
3	20525	8	#Max	16QAM	20.80	20.65
3	20525	15	#0	16QAM	20.76	20.61
3	20635	1	#0	QPSK	23.15	23.00
3	20635	1	#Mid	QPSK	22.63	22.48
3	20635	1	#Max	QPSK	22.63	22.48
3	20635	8	#0	QPSK	21.70	21.55
3	20635	8	#Mid	QPSK	21.66	21.51
3	20635	8	#Max	QPSK	22.23	22.08
3	20635	15	#0	QPSK	22.23	22.08
3	20635	1	#0	16QAM	21.87	21.72
3	20635	1	#Mid	16QAM	21.83	21.68
3	20635	1	#Max	16QAM	21.87	21.72
3	20635	8	#0	16QAM	20.76	20.61
3	20635	8	#Mid	16QAM	20.80	20.65

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

3	20635	8	#Max	16QAM	20.84	20.69
3	20635	15	#0	16QAM	20.80	20.65
5	20425	1	#0	QPSK	23.16	23.01
5	20425	1	#Mid	QPSK	23.30	23.15
5	20425	1	#Max	QPSK	23.15	23.00
5	20425	12	#0	QPSK	22.18	22.03
5	20425	12	#Mid	QPSK	22.24	22.09
5	20425	12	#Max	QPSK	22.19	22.04
5	20425	25	#0	QPSK	21.71	21.56
5	20425	1	#0	16QAM	22.07	21.92
5	20425	1	#Mid	16QAM	22.73	22.58
5	20425	1	#Max	16QAM	21.98	21.83
5	20425	12	#0	16QAM	20.77	20.62
5	20425	12	#Mid	16QAM	20.74	20.59
5	20425	12	#Max	16QAM	21.30	21.15
5	20425	25	#0	16QAM	20.88	20.73
5	20525	1	#0	QPSK	22.59	22.44
5	20525	1	#Mid	QPSK	23.27	23.12
5	20525	1	#Max	QPSK	22.65	22.50
5	20525	12	#0	QPSK	21.72	21.57
5	20525	12	#Mid	QPSK	21.73	21.58
5	20525	12	#Max	QPSK	21.74	21.59
5	20525	25	#0	QPSK	21.83	21.68
5	20525	1	#0	16QAM	22.17	22.02
5	20525	1	#Mid	16QAM	22.30	22.15
5	20525	1	#Max	16QAM	22.10	21.95
5	20525	12	#0	16QAM	21.27	21.12
5	20525	12	#Mid	16QAM	20.66	20.51
5	20525	12	#Max	16QAM	20.83	20.68
5	20525	25	#0	16QAM	21.54	21.39
5	20625	1	#0	QPSK	23.18	23.03
5	20625	1	#Mid	QPSK	22.71	22.56
5	20625	1	#Max	QPSK	22.71	22.56
5	20625	12	#0	QPSK	21.73	21.58
5	20625	12	#Mid	QPSK	21.83	21.68
5	20625	12	#Max	QPSK	22.24	22.09
5	20625	25	#0	QPSK	21.78	21.63
5	20625	1	#0	16QAM	21.80	21.65
5	20625	1	#Mid	16QAM	21.91	21.76
5	20625	1	#Max	16QAM	21.77	21.62
5	20625	12	#0	16QAM	20.72	20.57
5	20625	12	#Mid	16QAM	20.75	20.60
5	20625	12	#Max	16QAM	20.75	20.60

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5	20625	25	#0	16QAM	20.91	20.76
10	20450	1	#0	QPSK	23.13	22.98
10	20450	1	#Mid	QPSK	23.29	23.14
10	20450	1	#Max	QPSK	22.75	22.60
10	20450	25	#0	QPSK	21.83	21.68
10	20450	25	#Mid	QPSK	21.68	21.53
10	20450	25	#Max	QPSK	21.81	21.66
10	20450	50	#0	QPSK	21.86	21.71
10	20450	1	#0	16QAM	22.35	22.20
10	20450	1	#Mid	16QAM	22.04	21.89
10	20450	1	#Max	16QAM	21.87	21.72
10	20450	25	#0	16QAM	20.87	20.72
10	20450	25	#Mid	16QAM	20.78	20.63
10	20450	25	#Max	16QAM	20.87	20.72
10	20450	50	#0	16QAM	20.87	20.72
10	20525	1	#0	QPSK	22.71	22.56
10	20525	1	#Mid	QPSK	22.96	22.81
10	20525	1	#Max	QPSK	22.76	22.61
10	20525	25	#0	QPSK	21.82	21.67
10	20525	25	#Mid	QPSK	21.75	21.60
10	20525	25	#Max	QPSK	21.87	21.72
10	20525	50	#0	QPSK	21.82	21.67
10	20525	1	#0	16QAM	21.77	21.62
10	20525	1	#Mid	16QAM	22.03	21.88
10	20525	1	#Max	16QAM	21.69	21.54
10	20525	25	#0	16QAM	20.82	20.67
10	20525	25	#Mid	16QAM	20.97	20.82
10	20525	25	#Max	16QAM	20.87	20.72
10	20525	50	#0	16QAM	20.91	20.76
10	20600	1	#0	QPSK	22.84	22.69
10	20600	1	#Mid	QPSK	22.78	22.63
10	20600	1	#Max	QPSK	22.65	22.50
10	20600	25	#0	QPSK	21.77	21.62
10	20600	25	#Mid	QPSK	21.78	21.63
10	20600	25	#Max	QPSK	21.83	21.68
10	20600	50	#0	QPSK	21.80	21.65
10	20600	1	#0	16QAM	21.95	21.80
10	20600	1	#Mid	16QAM	21.96	21.81
10	20600	1	#Max	16QAM	21.84	21.69
10	20600	25	#0	16QAM	20.91	20.76
10	20600	25	#Mid	16QAM	20.86	20.71
10	20600	25	#Max	16QAM	20.85	20.70
10	20600	50	#0	16QAM	21.02	20.87

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6.2. Occupied Bandwidth

Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 850 (GMSK)	128	824.2	0.248	0.307
	190	836.6	0.246	0.312
	251	848.8	0.245	0.307
GPRS 850 (GMSK)	128	824.2	0.244	0.310
	190	836.6	0.244	0.313
	251	848.8	0.250	0.317
EGPRS 850 (8PSK)	128	824.2	0.252	0.311
	190	836.6	0.254	0.314
	251	848.8	0.249	0.316
WCDMA Band V (RMC)	4132	826.4	4.153	4.685
	4183	836.6	4.163	4.671
	4233	846.6	4.173	4.673

LTE Band 5						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	20407	824.7	1.096	1.278
			20525	836.5	1.095	1.273
			20643	848.3	1.091	1.306
		3	20415	825.5	2.679	2.929
			20525	836.5	2.699	2.933
			20635	847.5	2.687	2.930
		5	20425	826.5	4.501	4.918
			20525	836.5	4.513	4.903
			20625	846.5	4.503	4.877
		10	20450	829	8.974	9.690
			20525	836.5	9.008	9.797
			20600	844	8.994	9.761
	16QAM	1.4	20407	824.7	1.095	1.280
			20525	836.5	1.099	1.289
			20643	848.3	1.092	1.268

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

		3	20415	825.5	2.686	2.901
			20525	836.5	2.691	2.925
			20635	847.5	2.690	2.910
		5	20425	826.5	4.502	4.833
			20525	836.5	4.506	4.943
			20625	846.5	4.508	4.953
		10	20450	829	9.004	9.701
			20525	836.5	8.961	9.751
			20600	844	8.979	9.672

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

GSM 850 CH-Low

GSM 850 GPRS CH-Low



GSM 850 CH-Middle



GSM 850 GPRS CH-Middle

GSM 850 CH-High

GSM 850 GPRS CH-High

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

GSM 850 EGPRS CH-Low



WCDMA Band V CH-Low

GSM 850 EGPRS CH-Middle



WCDMA Band V CH-Middle

GSM 850 EGPRS CH-High



WCDMA Band V CH-High



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 QPSK 1.4MHz CH-Low



LTE Band 5 QPSK 3MHz CH-Low



LTE Band 5 QPSK 1.4MHz CH-Middle



LTE Band 5 QPSK 3MHz CH-Middle



LTE Band 5 QPSK 1.4MHz CH-High



LTE Band 5 QPSK 3MHz CH-High



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 QPSK 5MHz CH-Low



LTE Band 5 QPSK 10MHz CH-Low



LTE Band 5 QPSK 5MHz CH-Middle



LTE Band 5 QPSK 10MHz CH-Middle



LTE Band 5 QPSK 5MHz CH-High



LTE Band 5 QPSK 10MHz CH-High



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 16QAM 1.4MHz CH-Low



LTE Band 5 16QAM 3MHz CH-Low



LTE Band 5 16QAM 1.4MHz CH-Middle



LTE Band 5 16QAM 3MHz CH-Middle



LTE Band 5 16QAM 1.4MHz CH-High



LTE Band 5 16QAM 3MHz CH-High



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 16QAM 5MHz CH-Low



LTE Band 5 16QAM 10MHz CH-Low



LTE Band 5 16QAM 5MHz CH-Middle



LTE Band 5 16QAM 10MHz CH-Middle



LTE Band 5 16QAM 5MHz CH-High



LTE Band 5 16QAM 10MHz CH-High



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6.3. Band Edge Compliance

GSM 850 CH-Low

GSM 850 CH-High

GSM 850 GPRS CH-Low

GSM 850 GPRS CH-High

GSM 850 EGPRS CH-Low

GSM 850 EGPRS CH-High

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

WCDMA Band V CH-Low	WCDMA Band V CH-High

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 QPSK 1.4MHz CH-Low 1RB

LTE Band 5 QPSK 1.4MHz CH-High 1RB



LTE Band 5 QPSK 1.4MHz CH-Low 100%RB

LTE Band 5 QPSK 1.4MHz CH-High 100%RB

LTE Band 5 QPSK 3MHz CH-Low 1RB

LTE Band 5 QPSK 3MHz CH-High 1RB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 QPSK 3MHz CH-Low 100%RB



LTE Band 5 QPSK 3MHz CH-High 100%RB

LTE Band 5 QPSK 5MHz CH-Low 1RB



LTE Band 5 QPSK 5MHz CH-High 1RB

LTE Band 5 QPSK 5MHz CH-Low 100%RB

LTE Band 5 QPSK 5MHz CH-High 100%RB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 QPSK 10MHz CH-Low 1RB

LTE Band 5 QPSK 10MHz CH-High 1RB

LTE Band 5 QPSK 10MHz CH-Low 100%RB



LTE Band 5 QPSK 10MHz CH-High 100%RB

LTE Band 5 16QAM 1.4MHz CH-Low 1RB



LTE Band 5 16QAM 1.4MHz CH-High 1RB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 16QAM 1.4MHz CH-Low 100%RB

LTE Band 5 16QAM 1.4MHz CH-High 100%RB

LTE Band 5 16QAM 3MHz CH-Low 1RB

LTE Band 5 16QAM 3MHz CH-High 1RB

LTE Band 5 16QAM 3MHz CH-Low 100%RB



LTE Band 5 16QAM 3MHz CH-High 100%RB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 16QAM 5MHz CH-Low 1RB

LTE Band 5 16QAM 5MHz CH-High 1RB

LTE Band 5 16QAM 5MHz CH-Low 100%RB



LTE Band 5 16QAM 5MHz CH-High 100%RB



LTE Band 5 16QAM 10MHz CH-Low 1RB

LTE Band 5 16QAM 10MHz CH-High 1RB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 16QAM 10MHz CH-Low 100%RB	LTE Band 5 16QAM 10MHz CH-High 100%RB
	

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6.4. Peak-to-Average Power Ratio (PAPR)

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
GSM 850 (GMSK)	128	824.2	32.09	29.43	2.66	≤13	PASS
	190	836.6	32.11	29.44	2.67	≤13	PASS
	251	848.8	32.10	29.43	2.67	≤13	PASS
GPRS 850 (GMSK)	128	824.2	32.06	29.40	2.66	≤13	PASS
	190	836.6	32.08	29.41	2.67	≤13	PASS
	251	848.8	32.07	29.40	2.67	≤13	PASS
EGPRS 850 (8PSK)	128	824.2	28.13	22.46	5.67	≤13	PASS
	190	836.6	28.18	22.49	5.69	≤13	PASS
	251	848.8	28.54	22.83	5.71	≤13	PASS
WCDMA Band V (RMC)	4132	826.4	24.77	21.76	3.01	≤13	PASS
	4183	836.6	24.80	21.80	3.00	≤13	PASS
	4233	846.6	24.68	21.68	3.00	≤13	PASS

LTE Band 5								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	20407	824.7	26.96	21.17	5.79	≤13	PASS
		20525	836.5	26.70	21.12	5.58	≤13	PASS
		20643	848.3	26.67	21.14	5.53	≤13	PASS
	3	20415	825.5	27.07	21.37	5.70	≤13	PASS
		20525	836.5	26.71	21.15	5.56	≤13	PASS
		20635	847.5	26.72	21.11	5.61	≤13	PASS
	5	20425	826.5	27.46	21.68	5.78	≤13	PASS
		20525	836.5	27.26	21.65	5.61	≤13	PASS
		20625	846.5	27.34	21.62	5.72	≤13	PASS
	10	20450	829	27.34	21.68	5.66	≤13	PASS
		20525	836.5	27.26	21.67	5.59	≤13	PASS
		20600	844	27.41	21.68	5.73	≤13	PASS
16QAM	1.4	20407	824.7	26.56	20.19	6.37	≤13	PASS
		20525	836.5	26.43	20.16	6.27	≤13	PASS
		20643	848.3	26.65	20.22	6.43	≤13	PASS
	3	20415	825.5	26.59	20.18	6.41	≤13	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

		20525	836.5	26.52	20.20	6.32	≤13	PASS
		20635	847.5	26.64	20.16	6.48	≤13	PASS
	5	20425	826.5	27.07	20.68	6.39	≤13	PASS
		20525	836.5	26.97	20.66	6.31	≤13	PASS
		20625	846.5	27.03	20.66	6.37	≤13	PASS
	10	20450	829	27.10	20.70	6.40	≤13	PASS
		20525	836.5	27.00	20.67	6.33	≤13	PASS
		20600	844	27.11	20.69	6.42	≤13	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6.5. Frequency Stability

GSM 850						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability（ppm）	Frequency Stability（ppm）	Verdict
Temperature	Voltage	GMSK	8PSK	GMSK	8PSK	
Normal（25℃）	Normal	14.54	12.45	0.01738	0.01488	PASS
Extreme（50℃）		2.76	5.41	0.00330	0.00647	PASS
Extreme（40℃）		8.96	5.85	0.01071	0.00700	PASS
Extreme（30℃）		10.23	9.09	0.01223	0.01087	PASS
Extreme（20℃）		15.48	16.08	0.01850	0.01922	PASS
Extreme（10℃）		13.03	3.18	0.01557	0.00381	PASS
Extreme（0℃）		3.98	6.09	0.00475	0.00727	PASS
Extreme（-10℃）		4.26	8.02	0.00509	0.00959	PASS
Extreme（-20℃）		9.70	17.70	0.01160	0.02115	PASS
Extreme（-30℃）		7.50	6.81	0.00897	0.00814	PASS
25℃	LV	14.76	8.94	0.01764	0.01069	PASS
	HV	5.01	7.12	0.00599	0.00851	PASS

WCDMA Band V						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability（ppm）	Frequency Stability（ppm）	Verdict
Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
Normal（25℃）	Normal	10.06	11.61	0.01202	0.01388	PASS
Extreme（50℃）		13.86	5.63	0.01656	0.00673	PASS
Extreme（40℃）		11.75	3.02	0.01404	0.00361	PASS
Extreme（30℃）		9.22	5.60	0.01102	0.00669	PASS
Extreme（20℃）		16.34	6.09	0.01953	0.00729	PASS
Extreme（10℃）		16.08	15.03	0.01922	0.01796	PASS
Extreme（0℃）		16.15	11.14	0.01930	0.01332	PASS
Extreme（-10℃）		1.47	9.68	0.00175	0.01157	PASS
Extreme（-20℃）		14.54	11.90	0.01738	0.01422	PASS
Extreme（-30℃）		10.17	12.27	0.01216	0.01466	PASS
25℃	LV	8.20	7.40	0.00981	0.00884	PASS
	HV	11.67	13.04	0.01395	0.01558	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability（ppm）	Frequency Stability（ppm）	Verdict
BANDWIDTH	1.4MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal（25℃）	Normal	7.37	8.10	0.00881	0.00968	PASS
Extreme（50℃）		5.43	15.24	0.00649	0.01822	PASS
Extreme（40℃）		16.52	4.19	0.01975	0.00501	PASS
Extreme（30℃）		1.14	3.81	0.00136	0.00456	PASS
Extreme（20℃）		16.53	15.65	0.01976	0.01871	PASS
Extreme（10℃）		17.89	16.72	0.02138	0.01998	PASS
Extreme（0℃）		5.27	3.70	0.00630	0.00443	PASS
Extreme（-10℃）		1.65	4.62	0.00198	0.00552	PASS
Extreme（-20℃）		16.51	1.78	0.01974	0.00213	PASS
Extreme（-30℃）		4.81	13.19	0.00575	0.01577	PASS
25℃	LV	1.30	12.87	0.00155	0.01539	PASS
	HV	5.00	17.13	0.00598	0.02048	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability（ppm）	Frequency Stability（ppm）	Verdict
BANDWIDTH	3MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal（25℃）	Normal	7.82	1.85	0.00935	0.00222	PASS
Extreme（50℃）		15.43	1.88	0.01844	0.00225	PASS
Extreme（40℃）		4.76	1.77	0.00569	0.00211	PASS
Extreme（30℃）		2.67	10.72	0.00319	0.01281	PASS
Extreme（20℃）		4.18	17.34	0.00500	0.02073	PASS
Extreme（10℃）		14.12	17.17	0.01688	0.02053	PASS
Extreme（0℃）		5.19	5.78	0.00620	0.00690	PASS
Extreme（-10℃）		1.66	8.07	0.00198	0.00965	PASS
Extreme（-20℃）		1.24	6.53	0.00148	0.00780	PASS
Extreme（-30℃）		9.75	14.58	0.01166	0.01743	PASS
25℃	LV	3.24	11.03	0.00387	0.01318	PASS
	HV	14.74	9.10	0.01762	0.01088	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability（ppm）	Frequency Stability（ppm）	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal（25℃）	Normal	15.02	5.92	0.01795	0.00707	PASS
Extreme（50℃）		3.87	17.97	0.00463	0.02148	PASS
Extreme（40℃）		14.14	8.90	0.01690	0.01063	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Extreme（30℃）		1.76	4.67	0.00210	0.00558	PASS
Extreme（20℃）		7.25	15.63	0.00866	0.01868	PASS
Extreme（10℃）		15.29	9.87	0.01828	0.01179	PASS
Extreme（0℃）		7.47	14.74	0.00893	0.01761	PASS
Extreme（-10℃）		1.72	12.04	0.00206	0.01439	PASS
Extreme（-20℃）		15.56	9.43	0.01860	0.01128	PASS
Extreme（-30℃）		17.04	14.25	0.02037	0.01703	PASS
25℃	LV	8.86	10.24	0.01059	0.01225	PASS
	HV	2.39	8.16	0.00285	0.00975	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability（ppm）	Frequency Stability（ppm）	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal（25℃）	Normal	9.68	4.00	0.01157	0.00478	PASS
Extreme（50℃）		17.93	6.99	0.02143	0.00835	PASS
Extreme（40℃）		6.03	12.45	0.00721	0.01488	PASS
Extreme（30℃）		3.73	16.86	0.00446	0.02015	PASS
Extreme（20℃）		6.70	14.24	0.00801	0.01702	PASS
Extreme（10℃）		1.20	11.69	0.00143	0.01397	PASS
Extreme（0℃）		12.15	2.06	0.01452	0.00246	PASS
Extreme（-10℃）		2.63	11.03	0.00314	0.01318	PASS
Extreme（-20℃）		7.09	10.46	0.00848	0.01251	PASS
Extreme（-30℃）		7.68	1.80	0.00918	0.00215	PASS
25℃	LV	9.71	15.04	0.01161	0.01797	PASS
	HV	14.86	4.37	0.01776	0.00522	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6.6. Spurious Emissions at Antenna Terminals

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.

GSM 850 CH-Low 9kHz ~ 20GHz



GPRS 850 CH-Low 9kHz ~ 20GHz



GSM 850 CH-Middle 9kHz ~ 20GHz



GPRS 850 CH-Middle 9kHz ~ 20GHz



GSM 850 CH-High 9kHz ~ 20GHz



GPRS 850 CH-High 9kHz ~ 20GHz



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EGPRS 850 CH-Low 9kHz ~ 20GHz



WCDMA BAND V CH-Low 9kHz ~ 20GHz



EGPRS 850 CH-Middle 9kHz ~ 20GHz



WCDMA BAND V CH-Middle 9kHz ~ 20GHz



EGPRS 850 CH-High 9kHz ~ 20GHz



WCDMA BAND V CH-High 9kHz ~ 20GHz



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 1.4MHz CH-Low 9kHz~10GHz



LTE Band 5 3MHz CH-Low 9kHz~10GHz



LTE Band 5 1.4MHz CH-Middle 9kHz~10GHz



LTE Band 5 3MHz CH-Middle 9kHz~10GHz



LTE Band 5 1.4MHz CH-High 9kHz~10GHz



LTE Band 5 3MHz CH-High 9kHz~10GHz



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 5MHz CH-Low 9kHz~10GHz



LTE Band 5 10MHz CH-Low 9kHz~10GHz



LTE Band 5 5MHz CH-Middle 9kHz~10GHz



LTE Band 5 10MHz CH-Middle 9kHz~10GHz



LTE Band 5 5MHz CH-High 9kHz~10GHz



LTE Band 5 10MHz CH-High 9kHz~10GHz



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6.7. Radiates Spurious Emission

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.55	-34.25	1.70	8.70	Vertical	-29.40	-13.00	16.40	270
3	2509.80	-42.39	2.30	12.00	Vertical	-34.84	-13.00	21.84	0
4	3346.40	-49.59	2.70	12.70	Vertical	-41.74	-13.00	28.74	45
5	4183.00	-51.46	3.00	12.50	Vertical	-44.11	-13.00	31.11	225
6	5019.60	-58.44	3.40	12.50	Vertical	-51.49	-13.00	38.49	90
7	5856.20	-57.57	3.40	12.80	Vertical	-50.32	-13.00	37.32	45
8	6692.80	-58.45	4.10	11.50	Vertical	-53.20	-13.00	40.20	315
9	7529.40	-54.71	4.20	12.20	Vertical	-48.86	-13.00	35.86	90
10	8366.00	-55.37	4.30	12.50	Vertical	-49.32	-13.00	36.32	225

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Vertical position.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1671.20	-48.82	1.70	8.70	Vertical	-43.97	-13.00	30.97	45
3	2510.40	-41.69	2.30	12.00	Vertical	-34.14	-13.00	21.14	225
4	3346.40	-61.41	2.70	12.70	Vertical	-53.56	-13.00	40.56	45
5	4183.00	-63.81	3.00	12.50	Vertical	-56.46	-13.00	43.46	270
6	5019.60	-62.22	3.40	12.50	Vertical	-55.27	-13.00	42.27	90
7	5856.20	-63.85	3.40	12.80	Vertical	-56.60	-13.00	43.60	45
8	6692.80	-56.04	4.10	11.50	Vertical	-50.79	-13.00	37.79	315
9	7529.40	-54.69	4.20	12.20	Vertical	-48.84	-13.00	35.84	90
10	8366.00	-55.74	4.30	12.50	Vertical	-49.69	-13.00	36.69	225

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Vertical position.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.00	-40.14	1.70	8.70	Vertical	-35.29	-13.00	22.29	90
3	2509.50	-27.69	2.30	12.00	Vertical	-20.14	-13.00	7.14	45
4	3346.00	-50.09	2.70	12.70	Vertical	-42.24	-13.00	29.24	225
5	4182.50	-58.04	3.00	12.50	Vertical	-50.69	-13.00	37.69	90
6	5019.00	-62.60	3.40	12.50	Vertical	-55.65	-13.00	42.65	45
7	5855.50	-63.76	3.40	12.80	Vertical	-56.51	-13.00	43.51	315
8	6692.00	-57.77	4.10	11.50	Vertical	-52.52	-13.00	39.52	90
9	7528.50	-54.56	4.20	12.20	Vertical	-48.71	-13.00	35.71	45
10	8365.00	-55.04	4.30	12.50	Vertical	-48.99	-13.00	35.99	270

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Vertical position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.60	-42.12	1.70	8.70	Vertical	-37.27	-13.00	24.27	135
3	2503.30	-27.06	2.30	12.00	Vertical	-19.51	-13.00	6.51	180
4	3337.50	-50.75	2.70	12.70	Vertical	-42.90	-13.00	29.90	90
5	4171.88	-59.91	3.00	12.50	Vertical	-52.56	-13.00	39.56	45
6	5006.25	-61.23	3.40	12.50	Vertical	-54.28	-13.00	41.28	225
7	5840.63	-64.28	3.40	12.80	Vertical	-57.03	-13.00	44.03	90
8	6675.00	-58.27	4.10	11.50	Vertical	-53.02	-13.00	40.02	270
9	7509.38	-53.85	4.20	12.20	Vertical	-48.00	-13.00	35.00	45
10	8343.75	-54.58	4.30	12.50	Vertical	-48.53	-13.00	35.53	135

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Vertical position.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1664.40	-46.04	1.70	8.70	Vertical	-41.19	-13.00	28.19	270
3	2496.60	-29.04	2.30	12.00	Vertical	-21.49	-13.00	8.49	135
4	3326.00	-48.67	2.70	12.70	Vertical	-40.82	-13.00	27.82	90
5	4157.50	-62.26	3.00	12.50	Vertical	-54.91	-13.00	41.91	45
6	4989.00	-61.49	3.40	12.50	Vertical	-54.54	-13.00	41.54	135
7	5820.50	-63.75	3.40	12.80	Vertical	-56.50	-13.00	43.50	0
8	6652.00	-57.57	4.10	11.50	Vertical	-52.32	-13.00	39.32	90
9	7483.50	-54.22	4.20	12.20	Vertical	-48.37	-13.00	35.37	45
10	8315.00	-55.53	4.30	12.50	Vertical	-49.48	-13.00	36.48	270

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.
2. The worst emission was found in the antenna is Vertical position.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

7. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Climate Chamber	ESPEC	SU-242	93000506	2021-12-12	2022-12-11
Wideband radio communication tester	R&S	CMW500	113645	2022-05-14	2023-05-13
Spectrum Analyzer	Keysight	N9020A	MY50510203	2021-12-12	2022-12-11
Universal Radio Communication Tester	Agilent	E5515C	GB44400275	2021-12-12	2022-12-11
Signal Analyzer	R&S	FSV3030	101411	2021-12-12	2022-12-11
Spectrum Analyzer	R&S	FSV30	104028	2021-12-12	2022-12-11
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	01111	2019--9-12	2022-09-11
Horn Antenna	Schwarzbeck	BBHA 9120D	1594	2020-12-17	2023-12-16
Software	R&S	EMC32	10.35.10	/	/

********END OF REPORT ********

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX A: The EUT Appearance

The EUT Appearance is submitted separately.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX B: Test Setup Photos

The Test Setup Photos is submitted separately.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.