



報告編號 : 4789022848-TW-R0-V0

頁碼 : 1 of 55

報告發行日期 : 2019/10/21

低功率射頻電機試驗報告

產品名稱 : Car Sharing Module

型號 : CSM4

申請廠商 : Fuba Automotive Electronics GmbH

申請者地址 : Tec Center 1, 31162 Bad Salzdetfurth

製造廠商 : Fuba Automotive Electronics GmbH

製造商地址 : Tec Center 1, 31162 Bad Salzdetfurth

實驗室名稱 : 優力國際安全認證有限公司

實驗室地址 : 新竹縣竹東鎮中興路四段 372-7 號 B 戶、E 戶

試驗受理日期 : 108 年 5 月 22 日

試驗完成日期 : 108 年 6 月 3 日 ~ 108 年 6 月 6 日

待測物接收日期 : 108 年 5 月 24 日

依據標準 : 低功率射頻電機技術規 (LP0002) 107 年 1 月版



備註:

1. 此份報告未經優力國際安全認證有限公司書面同意，不得部分複製。
2. 本測試報告僅對受測之樣品負責。
3. 本測試報告需加負責人簽名始可生效。
4. 此案產品內外觀照請參考報告編號 4789022848-EP。

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 2 of 55

報告發行日期 : 2019/10/21

認可報告之試驗機構

優力國際安全認證有限公司

實驗室地址：新竹縣竹東鎮中興路四段 372-7 號 B 戶，E 戶

測試場地：新竹縣竹東鎮中興路四段 372-7 號 B 戶，E 戶

Tel：886-2-7737-3000 Fax：886-3-583-7948

財團法人全國認證基金會

認證編號：3398

認證有效期間：2017.08.29 ~ 2020.08.28

認可能量範圍：低功率射頻電機技術規範(LP0002)

報告製作者：

李依婷

, 日期： 108 年 10 月 21 日

審核與授權者：

吳俊南

, 日期： 108 年 10 月 21 日


Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



原始報告編號: 4789022848-TW-R0-V0

[illegible]

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone :+886-2-7737-3000
Facsimile (FAX) :+886-3-583-7948 Doc No: 17-

Doc No: 17-EM-F0880 / 2.0



目錄

1. 一般資料	6
1.1 產品描述	6
1.2 補助測試之週邊設備	10
1.3 測試架構圖	10
2. 量測儀器及測試配置說明	11
2.1 量測設備	11
2.2 測試應用參考標準	12
2.3 量測不確定度	13
2.4 試驗環境	13
3. 適用規範	14
3.1 規範要求	14
4. 測試紀錄結果	18
4.1 峰值傳導輸出功率	18
4.2 發射頻寬	20
4.3 功率頻譜密度	23
4.4 混附波及頻帶邊緣之傳導發射	26
4.5 場強輻射	33
附錄 I 頻帶邊緣輻射量測	48
附錄 II 混附波輻射量測	52
附錄 III 場強輻射配置照片	54



測試項目與結果判定總表

項次	測試項目	適用規範	結果判定
1	峰值傳導輸出功率	低功率射頻電機技術規範 3.10.1.2 節	合格
2	發射頻寬	低功率射頻電機技術規範 3.10.1.6 節	合格
3	功率頻譜密度	低功率射頻電機技術規範 3.10.1.6 節	合格
4	混附波及頻帶邊緣之傳導發射	低功率射頻電機技術規範 3.10.1.5 節	合格
5	場強輻射	低功率射頻電機技術規範 2.8 節、 3.10.1.5 節	合格
6	電源線傳導干擾	低功率射頻電機技術規範 2.3 節	Note2

Note:

1. 對於頻帶邊緣輻射測試圖記錄在附錄 I，混附波輻射測試圖記錄在附錄 II。
2. 本產品為車用裝置(DC)操作產品，故無實施此項測試。

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



1. 一般資料

1.1 產品描述

產 品 名 稱	Car Sharing Module
廠 牌	Car Sharing
型 號	CSM4
額 定 電 壓	12 Vdc
調 變 方 式	GFSK
傳 輸 速 率	Up to 2Mbps
頻 率 使 用 範 圍	2402 MHz ~ 2480 MHz
頻 道 數 量	40
發 射 功 率	LE 1M (BT4.0): 3.3 dBm LE 2M (BT5.0): 3.34 dBm
測 試 軟 體	SmartRF Studio 7 v2.8.0
天 線 型 態	見註 1

註:

1. 此待測設備搭配測試的天線，其資料如下：

天線型式	天線型號	商標	接頭型式	增益 (dBi)
PCB	N/A	N/A	N/A	5
Note : 1. 適用規範請見本報告 3.1 節第 (5)、(6) 的規定。 2. 依據測試數據結果，符合低功率射頻電機技術規範之要求。 3. 此天線資訊由客戶提供，詳請參閱製造商的產品規格或使用手冊。				

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



2. 此報告中待測物輻射測試模式評估如下表:

模式	測試狀態
模式 1	Bluetooth LE4.0 (1M)TX_Ch00,19,39
模式 2	Bluetooth LE5.0 (2M) TX_Ch00,19,39
模式 3	Bluetooth LE RX

發射模式:

1 GHz以上之輻射量測以模式1與模式2進行量測, 1 GHz以下之輻射量測以最差模式1之測試通道39進行量測。

接收模式:

1 GHz以上與1 GHz以下的輻射量測以模式3進行量測。

3. 場強輻射量測之外的測試項目, 以GFSK調變技術進行測試並記錄最終量測結果於報告中。
4. 此待測設備, 經評估三個正交軸方位評估測試擺設方式: 平躺、垂直、側放, 其中以垂直擁有最大場強輻射量測干擾值, 故以此擺放方式進行最終量測, 並將測試結果紀錄。




報告編號 : 4789022848-TW-R0-V0

頁碼 : 8 of 55


報告發行日期 : 2019/10/21

5. Duty cycle of test signal.

BT4.0: Duty cycle of test signal is $\geq 98\%$, duty factor is not required.



BT5.0: Duty cycle of test signal is $\geq 98\%$, duty factor is not required.



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



6. 此裝置各頻道的中心頻率如下：

頻道	對應頻率 (MHz)	頻道	對應頻率 (MHz)	頻道	對應頻率 (MHz)	頻道	對應頻率 (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

詳細之規格請參考使用說明書。



1.2 補助測試之週邊設備

待測設備於受測時均接上其所屬的配件或一般用途之相關設備；下列輔助設備或配件測試中所使用的配備，以形成一個代表待測物實際運作的受測系統。


No.	裝置名稱	廠牌	型號	序號	Remark
1	Notebook	DELL	Latitude E5470	3JFKWF2	N/A
2	DC Power Supply	GW Insrek	GPD-2303S	GEQ902177	N/A

NOTE:

1. All power cords of the above support units are non-shielded (1.8m).

1.3 測試架構圖

在測試筆電上開啟測試軟體（SmartRF Studio 7 v2.8.0）進行控制。該測試軟體用於啟用連續傳輸或接收模式，並根據需要選擇測試通道，數據速率，調變方式和功率設置。



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



2. 量測儀器及測試配置說明

2.1 量測設備

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
Radiated Spurious Emission					
Spectrum Analyzer	Keysight	N9010A	MY56070827	Nov. 8, 2018	1 year
EMI Test Receiver	Rohde & Schwarz	ESR7	101754	Nov. 8, 2018	1 year
Loop Antenna	ETS lindgren	6502	00213440	Dec. 11, 2018	1 year
Trilog-Broadband Antenna with 5dB Attenuator	Schwarzbeck & EMCI	VULB 9168 & N-6-05	774 & AT-N0538	Jan. 14, 2019	1 year
Horn Antenna (1-18 GHz)	Schwarzbeck	BBHA 9120 D	01690	Jan. 25, 2019	1 year
Horn Antenna(18-40 GHz)	Schwarzbeck	BBHA 9170	781	Jan.16, 2019	1 year
Preamplifier (30-1000 MHz)	EMCI	EMC330E	980405	Jan. 30, 2019	1 year
Preamplifier (1-18 GHz)	EMCI	EMC051835BE	980406	Jan. 29, 2019	1 year
Preamplifier (18-40GHz)	EMCI	EMC184040SEE	980426	May 8, 2019	1 year
RF Cable (9 KHz~18 GHz)	UltraPhase & EMC Instrument	A1K50-UP0358-A1K50-1500&EMC106-NM-SM-2500/7000	170111-4&170219/170102	Jan. 29, 2019	1 year
RF Cable (18 GHz~40 GHz)	UltraPhase	K1K50-UP0264-K1K50-2500/2500/600	170214-2/170214-6/170111-1	Jan. 29, 2019	1 year

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 12 of 55

報告發行日期 : 2019/10/21

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
Antenna Port Conducted Measurement					
Spectrum Analyzer	Keysight	N9010A	MY56070834	Nov. 8, 2018	1 year
Spectrum Analyzer	Rohde & Schwarz	FSV40	101490	Sep. 25, 2018	1 year
Pulse Power Sensor	Anrisu	MA2411B	1531202	Dec. 17, 2018	1 year
Power Meter	Anrisu	ML2495A	1645002	Dec. 17, 2018	1 year

UL Software

Software	Test Item	Version
EZ EMC	Radiated measurement	1.1.4.2
Keysight.TestSystem	Conducted measurement	1.0.0.0

2.2 測試應用參考標準

本報告中記錄的測試程序參照如下：

KDB558074 D01 Meas Guidance v05r02, KDB414788 D01 Radiated Test Site v01r01 and ANSI C63.10-2013.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



2.3 量測不確定度

此報告中關於量測之符合性聲明，採用 ISO Guide 98-4 的 8.2.4 與 8.2.5 章節中描述的準確度方法為判定規則。

下列量測不確定水準是參照量測儀器 CISPR 16-4-2 所規定之不確定度。

Test Item	Measurement Frequency Range	K	U(dB)
RF Conducted	9 kHz – 40 GHz	2	1.0
Radiated disturbance below 30MHz	9 kHz - 30 MHz	2	2.2
Radiated disturbance below 1 GHz	30 MHz ~ 1 GHz	2	5.3
Radiated disturbance above 1GHz	1 GHz ~ 40 GHz	2	4.8

2.4 試驗環境

產品測試時之環境條件如下：

測試項目	環境條件	輸入功率	測試日期	測試人員
峰值傳導輸出功率	23~25 deg. C, 66~68 % RH	12Vdc	2019/06/03 ~ 2019/06/04	高琮濠
發射頻寬	23~25 deg. C, 66~68 % RH	12Vdc	2019/06/03 ~ 2019/06/04	高琮濠
功率頻譜密度	23~25 deg. C, 66~68 % RH	12Vdc	2019/06/03 ~ 2019/06/04	高琮濠
混附波及頻帶邊緣之傳導發射	23~25 deg. C, 66~68 % RH	12Vdc	2019/06/03 ~ 2019/06/04	高琮濠
場強輻射	24~26 deg. C, 65~70 % RH	12Vdc	2019/06/03 ~ 2019/06/06	陳麒年

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



3. 適用規範

3.1 規範要求

(1) 峰值傳導輸出功率之要求

操作於 2.4000~2.4835 GHz 頻段:

依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.2 節之規定:

數位調變技術系統: 1 W(含)以下。

除使用附件二之峰值輸出功率測量方式外,並得使用以最大傳導輸出功率(Maximum Conducted Output Power)作為測量方式。

(2) 發射頻寬之要求

操作於 2.400~2.4835 GHz 頻段:

對使用數位調變技術(digital modulation techniques)系統之低功率發射機,依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.6 節之規定,6 dB 頻寬至少應有 500 kHz。

(3) 功率頻譜密度之要求

操作於 2.400~2.4835 GHz 頻段:

依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.6 節之規定,在使用頻率範圍之任一 3 kHz 頻寬內,由發射機傳導至天線之功率頻譜密度在任意傳輸期間內,皆小於或等於 8 毫分貝(dBm),且應依 3.10.1.3 之方式降低功率頻譜密度限制值。

(4) 帶外發射之要求

操作於 2.400~2.4835 GHz 頻段:

依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.5 節之要求,操作頻帶範圍外之任意 100 kHz 內,發射機所產生的射頻功率相較於使用頻帶範圍中包含最高所需功率之 100 kHz 內的射頻功率,其衰減值限制如下:

(1) 輸出功率以附件二之峰值輸出功率方式測量者,至少須衰減 20 dB,可使用射頻傳導或輻射方式測量。

(2) 輸出功率以 3.10.1.2(1)(C)之最大傳導輸出功率測量方式者,至少須衰減 30 dB。

此外,落於 2.7 禁用頻段之輻射發射,應符合 2.8 之規定。



頻率(f) (MHz)	電場強度 (微伏特/公尺, uV/m)	測距(公尺)
0.009 - 0.490 (含)	2,400/f(kHz)	300
0.490 (不含) - 1.705 (含)	24,000/f(kHz)	30
1.705 (不含) - 30 (不含)	30	30
30 (含) - 88 (含)	100	3
88 (不含) - 216 (含)	150	3
216 (不含) - 960 (含)	200	3
960 (不含)以上	500	3

(5) 天線之規定

天線規格不受第 2.2 節規定之限制。

(6) 天線增益之要求

低功率發射機，依據國家通訊傳播委員會低功率射頻電機技術規範 3.10.1.3 節之規定如下：

操作於 2.400~2.4835 GHz 頻段：

(A) 進行固定式點對點操作時，其發射天線之方向性增益超過 6 dBi，每超過 3 dBi，最大傳導輸出功率限制值應降低 1 dB。

(B) 天線以多向波束發射方式(含同時發射或循序發射)將訊號導向多個接收機或接收機群組時，應符合下列規定：

(a) 非同時發射多向波束者，所有載波或頻道傳輸至所有天線陣列或陣列群之總和傳導輸出功率應符合 3.10.1.2 之功率限制值。如天線/天線陣列群之方向性增益超過 6 dBi，每超過 3 dBi，總和傳導輸出功率限制值應降低 1 dB。方向性增益值應計算如下：

(i) 方向性增益值 = $10\log(\text{天線陣列之單元數目}) + \text{各單元中最高之方向性增益值}$ 。

(ii) 天線陣列間之遮蔽效應或波束干涉損失能充分佐證時，方向性增益得低於(i)計算數值。

(b) 同時發射多向波束於相同或不同頻道者，其每一波束功率應符合(a)之功率限制值。如發射波束有重疊現象，功率應降低，以確保總和傳導輸出功率符合

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



(a)之限制值。同時發射的所有波束總和傳導輸出功率不大於(a)總和傳導輸出功率限制值加 8 dB。方向性增益值計算同(a)。

(c) 發射機之天線具備單向波束功能者，應符合(1)(A)及(3)後段之規定。

除(A)及(B)外，使用超過 6 dBi 方向增益之發射天線時，應依超過 6 dBi 天線方向增益的 dBi 總量，等量減少最大傳導輸出功率限制值。

(7) 傳導之規定

依據國家通訊傳播委員會低功率射頻電機技術規範之 2.3 節，電源傳導干擾之限制要求如下：

頻率(MHz)	傳導限制值 (dBuV)	
	準峰值(Quasi-peak)	平均值(Average)
0.15-0.5	66-56 (註)	56-46 (註)
0.5-5	56	46
5-30	60	50

(註)：隨頻率之對數遞減。

(8) 無線資訊傳輸設備必須擁有安全功能之要求

依據國家通訊傳播委員會低功率射頻電機技術規範 4.7.7.3 節之規定，無線資訊傳輸設備必須擁有安全功能，以保護未經授權之一方更改軟體。製造商應提出符合本節規定之相關證明文件或符合性聲明。



(9) 限制使用之頻帶

除本規範另有規定外，任何低功率射頻電機之主波皆不得使用下表所列各頻段之頻率；低功率射頻電機落於下表所列頻段之混附發射，其電場強度必須符合 2.8 之限制規定。

頻率(MHz)	頻率(MHz)	頻率(MHz)
0.090~0.110	240.00~285.00	3332.0~3339.0
0.490~0.510	322.00~335.40	3345.8~3358.0
2.172~2.198	399.90~410.00	3500.0~4400.0
3.013~3.033	485.00~510.00	4500.0~5250.0
4.115~4.198	608.00~614.00	5350.0~5460.0
5.670~5.690	703.00~748.00	7250.0~7750.0
6.200~6.300	758.00~803.00	8025.0~8500.0
8.230~8.400	825.00~915.00	9000.0~9200.0
12.265~12.600	930.00~1240.0	9300.0~9500.0
13.340~13.430	1300.0~1427.0	10600~12700
14.965~15.020	1435.0~1626.5	13250~13400
16.700~16.755	1660.0~1785.0	14470~14500
19.965~20.020	1805.0~1880.0	15350~16200
25.500~25.700	1885.0~1900.0	17700~21400
37.475~38.275	1905.0~1985.0	22010~23120
73.500~75.400	2010.0~2025.0	23600~24000
108.00~138.00	2110.0~2170.0	31200~31800
149.90~150.05	2200.0~2300.0	36430~36500
156.70~156.90	2310.0~2390.0	38600 以上
162.01~167.17	2483.5~2900.0	-
167.72~173.20	3260.0~3267.0	-

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



4. 測試紀錄結果

4.1 峰值傳導輸出功率


4.1.1 適用標準

請見本報告 3.1 節第 (1) 的規定。

4.1.2 測試方法

- a) 將待測物之天線埠經由適當之衰減器接到功率計上。
- b) 設定待測物處於連續發射狀態。
- c) 計算其輸出功率峰值。

4.1.3 測試配置圖



The loss between RF output port of the EUT and the input port of the Power Meter has been taken into consideration.



4.1.4 測試結果

LE 1M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	2.08	3.19	30	Pass
19	2440	2.14	3.30	30	Pass
39	2480	1.85	2.67	30	Pass

LE 2M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	2.08	3.19	30	Pass
19	2440	2.16	3.34	30	Pass
39	2480	1.85	2.68	30	Pass

4.1.5 測試結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

4.2 發射頻寬


4.2.1 適用標準

請見本報告 3.1 節第 (2) 的規定。

4.2.2 測試方法

- 將待測物之天線埠經由適當之衰減器接到頻譜分析儀上。
- 設定待測物處於連續發射狀態。
- 計算最大輸出功率峰值減 6 dB 的最大頻率範圍。

4.2.3 測試配置圖



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.




4.2.4 測試結果

LE 1M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.7093	0.5	Pass
19	2440	0.7233	0.5	Pass
39	2480	0.7233	0.5	Pass

此測試圖僅放測試結果最差的頻道



Underwriters Laboratories Taiwan Co., Ltd.


Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948



LE 2M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	1.3866	0.5	Pass
19	2440	1.4585	0.5	Pass
39	2480	1.4625	0.5	Pass

此測試圖僅放測試結果最差的頻道



4.2.5 測試結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948



4.3 功率頻譜密度


4.3.1 適用標準

請見本報告 3.1 節第 (3) 的規定。

4.3.2 測試方法

- 將待測物之天線埠經由適當之衰減器接到頻譜分析儀上。
- 設定解析頻寬為 3 kHz，視訊頻寬為 10 kHz，掃描時間為 auto
- 掃描頻寬設於足夠觀察發射機所產生的主頻信號，並找到最大的峰值準位。
- 其峰值位準必須不大於+8 dBm。

4.3.3 測試配置圖



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.




4.3.4 測試結果

LE 1M

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	2402	-5.970	8	Pass
19	2440	-5.660	8	Pass
39	2480	-5.840	8	Pass

此測試圖僅放測試結果最差的頻道



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: 17-EM-F0880 / 2.0



LE 2M

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	2402	-10.810	8	Pass
19	2440	-11.710	8	Pass
39	2480	-12.430	8	Pass

此測試圖僅放測試結果最差的頻道



4.3.5 測試結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948



4.4 混附波及頻帶邊緣之傳導發射


4.4.1 適用標準

請見本報告 3.1 節第 (4) 的規定。

4.4.2 測試方法

將射頻輸出連接到頻譜分析儀，設定頻譜分析儀之解析頻寬為 100 kHz，視訊頻寬不小於解析頻寬，所有諧波與混附波必須比許可頻段中最高發射峰值至少低 20dB，並評估許可頻段之最高與最低的頻帶邊緣發射及混附波發射。

4.4.3 測試配置圖



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.




報告編號 : 4789022848-TW-R0-V0

頁碼 : 27 of 55

報告發行日期 : 2019/10/21

4.4.4 測試結果

LE 1M



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 28 of 55

報告發行日期 : 2019/10/21



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 29 of 55

報告發行日期 : 2019/10/21



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0




報告編號 : 4789022848-TW-R0-V0

頁碼 : 30 of 55

報告發行日期 : 2019/10/21

LE 2M



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 31 of 55

報告發行日期 : 2019/10/21



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 32 of 55

報告發行日期 : 2019/10/21



4.4.5 測試結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



4.5 場強輻射

4.5.1 適用標準

請見本報告 3.1 節第 (4)、(9) 的規定。

4.5.2 測試方法

在半電波暗室，將待測物置於 0.8 米高的非金屬桌面，使其操作在工作狀態。接收天線置於 3 米距離。桌面要 360 度旋轉，另外接收天線從離地 1 米至 4 米升降變化，以找出最大的輻射電場強度，接收天線分別置於水平、垂直極化各執行測試一次。

Note：對於 1 GHz 以上場強輻射的測試，待測物則置於 1.5 米高的非金屬桌面

頻譜設定如下：

Peak

頻率範圍	RBW	VBW
9 kHz~150 kHz	200 Hz	600 Hz
150 kHz~30 MHz	10 kHz	30 kHz
30 MHz~1 GHz	120 kHz	360 kHz
Above 1GHz	1 MHz	3 MHz

Average

調變方式	RBW	VBW
Bluetooth LE	1 MHz	10 Hz

Note: Quasi-Peak RBW = 120 kHz

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


Doc No: 17-EM-F0880 / 2.0

4.5.3 測試配置圖

<Frequency Range 9 kHz ~ 30 MHz>




<Frequency Range 30 MHz ~ 1 GHz>



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
 Telephone : +886-2-7737-3000
 Facsimile (FAX) : +886-3-583-7948

<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the Appendix III.

4.5.4 場強之計算公式

結果值 Result value (dBuV/m) = 機器讀值 Reading value (dBuV/m) + 校正因子
 Correction Factor (dB/m)

餘裕度 Margin(dB) = 結果值 Result value (dBuV/m) - 限制值 Limit value (dBuV/m)



4.5.5 測試結果

發射模式

Above 1GHz Data :

EUT Test Condition		Measurement Detail	
Mode 1	Channel 0	Frequency Range	1 GHz ~ 26.5 GHz

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2340.800	54.57	-7.66	46.91	74.00	-27.09	peak
@	2402.000	105.78	-7.58	98.20	-	-	peak
-	2388.600	41.91	-7.60	34.31	54.00	-19.69	AVG
@	2402.000	105.38	-7.58	97.80	-	-	AVG
*	4804.000	48.69	-3.09	45.60	74.00	-28.40	peak
#	7206.000	57.91	3.56	61.47	78.20	-16.73	peak
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2388.600	54.44	-7.60	46.84	74.00	-27.16	peak
@	2402.000	108.34	-7.58	100.76	-	-	peak
-	2388.200	42.80	-7.61	35.19	54.00	-18.81	AVG
@	2402.000	107.99	-7.58	100.41	-	-	AVG
*	4804.000	47.48	-3.09	44.39	74.00	-29.61	peak
#	7206.000	59.93	3.56	63.49	80.76	-17.27	peak

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. "@": Fundamental Frequency.
5. "#": The radiated frequency is out of the restricted band.
6. "*": The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
7. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 37 of 55

報告發行日期 : 2019/10/21

EUT Test Condition		Measurement Detail	
Mode 1	Channel 19	Frequency Range	1 GHz ~ 26.5 GHz

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2318.800	53.82	-7.50	46.32	74.00	-27.68	peak
@	2440.000	106.58	-7.70	98.88	-	-	peak
-	2504.800	54.10	-7.60	46.50	74.00	-27.50	peak
-	2349.800	41.25	-7.72	33.53	54.00	-20.47	AVG
@	2440.000	106.11	-7.70	98.41	-	-	AVG
-	2493.800	41.29	-7.60	33.69	54.00	-20.31	AVG
*	4880.000	48.62	-3.02	45.60	74.00	-28.40	peak
*	7320.000	49.87	3.63	53.50	74.00	-20.50	peak
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2388.400	55.86	-7.61	48.25	74.00	-25.75	peak
@	2440.000	107.42	-7.70	99.72	-	-	peak
-	2496.800	54.14	-7.59	46.55	74.00	-27.45	peak
-	2383.400	41.20	-7.62	33.58	54.00	-20.42	AVG
@	2440.000	106.96	-7.70	99.26	-	-	AVG
-	2500.800	41.28	-7.58	33.70	54.00	-20.30	AVG
*	4880.000	48.07	-3.02	45.05	74.00	-28.95	peak
-	7320.000	52.69	3.63	56.32	74.00	-17.68	peak
-	7320.000	46.96	3.63	50.59	54.00	-3.41	AVG

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. "@": Fundamental Frequency.
5. "* * ": The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
6. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 38 of 55

報告發行日期 : 2019/10/21

EUT Test Condition		Measurement Detail	
Mode 1	Channel 39	Frequency Range	1 GHz ~ 26.5 GHz

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
@	2480.000	106.29	-7.64	98.65	-	-	peak
-	2483.500	56.01	-7.63	48.38	74.00	-25.62	peak
@	2480.000	105.87	-7.64	98.23	-	-	AVG
-	2483.500	44.22	-7.63	36.59	54.00	-17.41	AVG
*	4960.000	44.12	-2.89	41.23	74.00	-32.77	peak
-	7440.000	52.67	3.87	56.54	74.00	-17.46	peak
-	7440.000	47.05	3.87	50.92	54.00	-3.08	AVG
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
@	2480.000	107.80	-7.64	100.16	-	-	peak
-	2483.500	56.57	-7.63	48.94	74.00	-25.06	peak
@	2480.000	107.37	-7.64	99.73	-	-	AVG
-	2483.500	45.73	-7.63	38.10	54.00	-15.90	AVG
*	4960.000	44.17	-2.89	41.28	74.00	-32.72	peak
-	7440.000	53.62	3.87	57.49	74.00	-16.51	peak
-	7440.000	48.41	3.87	52.28	54.00	-1.72	AVG

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. "@": Fundamental Frequency.
5. "*": The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
6. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 39 of 55

報告發行日期 : 2019/10/21

EUT Test Condition		Measurement Detail	
Mode 2	Channel 0	Frequency Range	1 GHz ~ 26.5 GHz

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2389.400	54.12	-7.60	46.52	74.00	-27.48	peak
@	2402.000	105.69	-7.58	98.11	-	-	peak
-	2387.600	41.56	-7.61	33.95	54.00	-20.05	AVG
@	2402.000	104.36	-7.58	96.78	-	-	AVG
*	4804.000	48.35	-3.09	45.26	74.00	-28.74	peak
#	7206.000	57.85	3.56	61.41	78.11	-16.70	peak
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2386.600	54.10	-7.62	46.48	74.00	-27.52	peak
@	2402.000	108.36	-7.58	100.78	-	-	peak
-	2388.400	42.52	-7.61	34.91	54.00	-19.09	AVG
@	2402.000	107.08	-7.58	99.50	-	-	AVG
*	4804.000	46.77	-3.09	43.68	74.00	-30.32	peak
#	7206.000	59.98	3.56	63.54	80.78	-17.24	peak

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. "@": Fundamental Frequency.
5. "#": The radiated frequency is out of the restricted band.
6. "*": The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
7. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



EUT Test Condition		Measurement Detail	
Mode 2	Channel 19	Frequency Range	1 GHz ~ 26.5 GHz

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2360.600	54.41	-7.69	46.72	74.00	-27.28	peak
@	2440.000	106.47	-7.70	98.77	-	-	peak
-	2492.600	54.59	-7.60	46.99	74.00	-27.01	peak
-	2386.400	41.10	-7.62	33.48	54.00	-20.52	AVG
@	2440.000	104.92	-7.70	97.22	-	-	AVG
-	2485.000	41.36	-7.63	33.73	54.00	-20.27	AVG
*	4880.000	48.20	-3.02	45.18	74.00	-28.82	peak
*	7320.000	49.95	3.63	53.58	74.00	-20.42	peak
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	2313.200	54.25	-7.47	46.78	74.00	-27.22	peak
@	2440.000	107.52	-7.70	99.82	-	-	peak
-	2500.400	54.20	-7.58	46.62	74.00	-27.38	peak
-	2388.400	41.45	-7.61	33.84	54.00	-20.16	AVG
@	2440.000	106.19	-7.70	98.49	-	-	AVG
-	2498.000	41.44	-7.58	33.86	54.00	-20.14	AVG
*	4880.000	47.54	-3.02	44.52	74.00	-29.48	peak
-	7320.000	53.06	3.63	56.69	74.00	-17.31	peak
-	7320.000	44.62	3.63	48.25	54.00	-5.75	AVG

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. "@": Fundamental Frequency.
5. " * ": The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
6. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



報告編號 : 4789022848-TW-R0-V0

頁碼 : 41 of 55

報告發行日期 : 2019/10/21

EUT Test Condition		Measurement Detail	
Mode 2	Channel 39	Frequency Range	1 GHz ~ 26.5 GHz

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
@	2480.000	106.19	-7.64	98.55	-	-	peak
-	2483.500	60.50	-7.63	52.87	74.00	-21.13	peak
@	2480.000	104.71	-7.64	97.07	-	-	AVG
-	2483.500	49.26	-7.63	41.63	54.00	-12.37	AVG
*	4960.000	43.05	-2.89	40.16	74.00	-33.84	peak
-	7440.000	52.75	3.87	56.62	74.00	-17.38	peak
-	7440.000	43.95	3.87	47.82	54.00	-6.18	AVG
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
@	2480.000	107.88	-7.64	100.24	-	-	peak
-	2483.500	62.05	-7.63	54.42	74.00	-19.58	peak
@	2480.000	106.56	-7.64	98.92	-	-	AVG
-	2483.500	51.75	-7.63	44.12	54.00	-9.88	AVG
*	4960.000	43.78	-2.89	40.89	74.00	-33.11	peak
-	7440.000	53.73	3.87	57.60	74.00	-16.40	peak
-	7440.000	45.21	3.87	49.08	54.00	-4.92	AVG

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. "@": Fundamental Frequency.
5. "*": The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
6. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



其他不必要之訊號


9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.


30 MHz ~ 1 GHz Data:

EUT Test Condition		Measurement Detail	
Mode 1	Channel 39	Frequency Range	30 MHz ~ 1 GHz

Horizontal



Vertical



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948



報告編號 : 4789022848-TW-R0-V0

頁碼 : 43 of 55

報告發行日期 : 2019/10/21

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	64.6613	44.89	-16.43	28.46	40.00	-11.54	peak
-	125.1893	47.82	-17.45	30.37	43.50	-13.13	peak
-	213.4593	48.37	-17.63	30.74	43.50	-12.76	peak
-	284.1400	47.94	-14.27	33.67	46.00	-12.33	peak
-	494.7270	38.28	-9.49	28.79	46.00	-17.21	peak
-	768.8812	43.56	-4.30	39.26	46.00	-6.74	peak
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	39.9910	53.11	-15.59	37.52	40.00	-2.48	peak
-	64.8553	44.07	-16.46	27.61	40.00	-12.39	peak
-	124.8013	49.12	-17.48	31.64	43.50	-11.86	peak
-	215.3993	51.30	-17.62	33.68	43.50	-9.82	peak
-	280.0337	43.02	-14.39	28.63	46.00	-17.37	peak
-	766.3593	37.32	-4.32	33.00	46.00	-13.00	peak

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0




接收模式


Above 1 GHz Data:

EUT Test Condition		Measurement Detail	
Mode 3	Bluetooth LE RX	Frequency Range	1 GHz ~ 26.5 GHz

Horizontal



Vertical



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948



報告編號 : 4789022848-TW-R0-V0

頁碼 : 45 of 55

報告發行日期 : 2019/10/21

Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	1700.400	50.69	-10.55	40.14	74.00	-33.86	peak
-	2300.500	45.80	-7.36	38.44	74.00	-35.56	peak
-	3066.350	44.95	-6.12	38.83	74.00	-35.17	peak
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	1403.750	55.42	-9.83	45.59	74.00	-28.41	peak
-	2300.500	44.94	-7.36	37.58	74.00	-36.42	peak
-	3034.050	44.05	-6.24	37.81	74.00	-36.19	peak

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



其他不必要之訊號


9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.


30 MHz ~ 1 GHz Data:

EUT Test Condition		Measurement Detail	
Mode 3	Bluetooth LE RX	Frequency Range	30 MHz ~ 1 GHz

Horizontal



Vertical



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948



Antenna Polarity & Test Distance: Horizontal at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	64.5320	45.12	-16.41	28.71	40.00	-11.29	peak
-	125.3187	45.98	-17.43	28.55	43.50	-14.95	peak
-	213.5240	49.54	-17.64	31.90	43.50	-11.60	peak
-	282.2000	47.63	-14.32	33.31	46.00	-12.69	peak
-	500.4823	38.75	-9.36	29.39	46.00	-16.61	peak
-	728.9820	40.87	-4.99	35.88	46.00	-10.12	peak
Antenna Polarity & Test Distance: Vertical at 3 m							
Notation	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
-	39.9910	52.42	-15.59	36.83	40.00	-3.17	peak
-	64.6289	44.96	-16.42	28.54	40.00	-11.46	peak
-	124.3487	47.56	-17.51	30.05	43.50	-13.45	peak
-	214.2030	52.13	-17.63	34.50	43.50	-9.00	peak
-	280.0337	43.57	-14.39	29.18	46.00	-16.82	peak
-	767.1352	39.66	-4.32	35.34	46.00	-10.66	peak

Remarks:

1. Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
2. Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
3. Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

4.5.6 測試結果判定

依據測試數據結果，符合低功率射頻電機技術規範之要求。

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


Doc No: 17-EM-F0880 / 2.0



附錄 I 頻帶邊緣輻射量測

模式 1

Peak



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0




報告編號 : 4789022848-TW-R0-V0

頁碼 : 49 of 55

報告發行日期 : 2019/10/21

Average



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0




報告編號 : 4789022848-TW-R0-V0

頁碼 : 50 of 55

報告發行日期 : 2019/10/21

模式 2

Peak



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



Average



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000


Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



附錄 II 混附波輻射量測

模式 1



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0




報告編號 : 4789022848-TW-R0-V0

頁碼 : 53 of 55

報告發行日期 : 2019/10/21

模式 2



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0



附錄 III 場強輻射配置照片

Above 1GHz



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0880 / 2.0





報告編號 : 4789022848-TW-R0-V0

頁碼 : 55 of 55

報告發行日期 : 2019/10/21

Below 1GHz



Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0880 / 2.0