



NTHV	BLE_1 M	Ant1	2402	2496.5~13000	9914.44	-32.46	≤-26	0.56754	≤2.5	PASS
				30~2387	2210.81	-45.64	≤-26	0.02729	≤2.5	PASS
				2387~2400	2399.97	-35.46	≤-16	0.28445	≤25	PASS
				2483.5~2496.5	2492.87	-39.92	≤-16	0.10186	≤25	PASS
				2496.5~13000	9603.00	-32.32	≤-26	0.58614	≤2.5	PASS
			2440	30~2387	2248.82	-42.71	≤-26	0.05358	≤2.5	PASS
				2387~2400	2387.48	-40.20	≤-16	0.09550	≤25	PASS
				2483.5~2496.5	2488.46	-39.74	≤-16	0.10617	≤25	PASS
				2496.5~13000	9754.78	-31.95	≤-26	0.63826	≤2.5	PASS
				30~2387	2288.89	-42.64	≤-26	0.05445	≤2.5	PASS
	BLE_2 M	Ant1	2480	2387~2400	2394.59	-40.83	≤-16	0.08260	≤25	PASS
				2483.5~2496.5	2486.34	-39.94	≤-16	0.10139	≤25	PASS
				2496.5~13000	9914.97	-32.45	≤-26	0.56885	≤2.5	PASS
				30~2387	2210.23	-46.67	≤-26	0.02153	≤2.5	PASS
				2387~2400	2399.97	-22.06	≤-16	6.22300	≤25	PASS
			2402	2483.5~2496.5	2483.63	-39.68	≤-16	0.10765	≤25	PASS
				2496.5~13000	9602.47	-32.17	≤-26	0.60674	≤2.5	PASS
				30~2387	2248.82	-44.68	≤-26	0.03404	≤2.5	PASS
				2387~2400	2399.79	-39.71	≤-16	0.10691	≤25	PASS
				2483.5~2496.5	2488.69	-40.07	≤-16	0.09840	≤25	PASS
			2440	2496.5~13000	9754.78	-32.30	≤-26	0.58884	≤2.5	PASS
				30~2387	2289.48	-42.32	≤-26	0.05861	≤2.5	PASS
				2387~2400	2399.71	-40.91	≤-16	0.08110	≤25	PASS
				2483.5~2496.5	2492.72	-39.81	≤-16	0.10447	≤25	PASS
				2496.5~13000	9914.44	-32.28	≤-26	0.59156	≤2.5	PASS

Note: 1. The product was tested at 25℃ and 55% humidity condition;

2. All condition has been tested, list the worst case in this item

3. SA set to from 2.4965GHz to 13GHz, plot shows from 2.497GHz to 13GHz as of SA's default format

















































